Decoding and reconstruction of surface materials from EEG

Taiki Orima[1,2]*, Suguru Wakita[1],& Isamu Motoyoshi[1]

1. Department of Life Sciences, The University of Tokyo

2. Japan Society for the Promotion of Science

*Correspondence: taikiorima@gmail.com

Abstract

Human visual system can easily recognize natural surface material categories and can reliably evaluate surface properties such as gloss and transparency. A large number of psychophysical and neurophysiological studies have revealed that these behavioral judgments on surface materials depend on low- and high-level statistical features. In the present study, we investigated how the neural representation of statistical features enables human visual system to recognize material categories, evaluate surface properties, and eventually obtain a complex and rich phenomenal appearance. To achieve this goal, we measured and analyzed VEPs for 191 natural surface images composed of 20 different material categories such as fabric, gravel, and metal. First, we classified the material categories and perceived surface properties from the VEPs using SVM. As a result, the 20 material categories were significantly classified by the VEPs at approximately ~150 ms and the perceived surface lightness, chromaticity, and smoothness were significantly classified by the VEPs at approximately ~175 ms, while the glossiness, hardness, and heaviness were significantly classified by the VEPs at approximately 200 ms or later. Subsequent reverse-correlation analysis revealed that the VEPs at short latencies, which classified material categories and perceived surface properties, were highly correlated with low- and high-level global statistical features (PS texture statistics and style information) included in natural surface images. This dynamic correlation supports the idea that material discrimination and evaluation of surface

properties are based on neural representations of global image features. To demonstrate this idea more directly, we trained deep generative models (MVAE) that reconstruct the surface image itself from VEPs via style information (gram matrix of the dCNN output). The model successfully reconstructed realistic visual stimuli and some of them were nearly indistinguishable from the original images. These findings suggest that the neural representation of statistical image features, which were reflected even in low-spatial-resolution EEG and formed at short latencies in the visual cortex, not simply enable human visual system to recognize material categories and evaluate surface properties but provides the essential basis for rich and complex phenomenal impressions (qualia) of natural surfaces.

Introduction

Objects in the natural environment have unique surface properties derived from a variety of materials, and the retinal images of these natural surfaces are extremely complex. However, we can easily estimate surface properties such as glossiness, transparency, and hardness (Motoyoshi et al., 2007; Sharan et al., 2008; Fleming et al. Kentridge, 2015; Fleming, 2017) and can reliably and rapidly recognize material categories (Fleming et al., 2013; Wiebel et al., 2013; Sharan et al., 2013, 2014; Fleming, 2017). Many psychophysical studies have revealed how the visual system correctly or incorrectly estimates material and surface properties from retinal images based on low- and high-level image features.

A series of electrophysiological and functional brain imaging studies have also unveiled neural substrates of visual material and surface property processing (Edward et al., 2003; Cant et al. Hiramatsu et al., 2011; Nishio et al. 2012; Okazawa et al. 2012; Wiebel et al. 2014). For example, Hiramatsu et al. (2011) used fMRI to measure brain activity for visual stimuli of CGs mimicking various materials, and showed that information related to material perception is processed in a hierarchical manner. Specifically, the dissimilarity matrices of brain activity in the early visual cortex (V1 and V2) strongly correlated with that of image statistics, while the dissimilarity matrix of spindle gyrus activity strongly correlated with that of ratings for each stimulus. These results suggested that the lower-level visual areas represented information about image statistics, while the relatively higher-level visual areas represented some higher-level information that highly correlated with the perceived surface properties. Another fMRI study on macaque monkeys using similar visual stimuli also suggested that V1 reflects the encoding of lower-level image features, while V4 integrates information directly related to the perception of object material properties (Goda et al., 2014). These studies suggest that hierarchical neural representations of low- and high-level image features in the visual cortex support material discrimination and evaluation of surface properties.

In most everyday situations, material perception largely (but not entirely) depends on the image appearance of interior textured regions rather than on the contours of objects. As larger body of evidence suggest that the appearance of these textural regions is based on

global statistical features of the image region of interest (Bergen & Adelson, 1988; Heeger & Bergen, 1995; Zipser et al. Portilla & Simoncelli, 2000; Baker & Mareschal, 2001; Motoyoshi et al. 2007; Freeman & Simoncelli, 2011; Freeman et al. 2013; Ziemba et al. 2019; Orima & Motoyoshi, 2021; Okada & Motoyoshi, 2021). For example, the best-known model by Portilla & Simoncelli (2000) can predict the appearance of various natural texture images by energy, autocorrelation/cross-correlation, and moment statistics of subband images of different orientations and spatial frequencies, and eventually can synthesize perceptually equivalent images. Recent neurophysiological studies have shown that these lower-level statistics represented in PS models are encoded in V1 and V2 (Freeman & Simoncelli, 2011; Freeman et al. 2013; Okazawa et al. 2015, 2017; Ziemba et al. 2019), and the integrated higher-level statistical features of those lower-level statistics are represented in V4 (Arcizet et al., 2008; Okazawa et al., 2015, 2017). Furthermore, the neural style transfer technique (Gatye et al., 2015) focusing on the Gram matrix (covariance between channels) in deep convolutional neural networks (dCNN), although less formulated than the previous texture models such as the PS model, describes the appearance of natural texture images based on statistical feature representations in dCNNs much more precisely than the PS statistics and is possible to synthesize an almost indistinguishable images from the original images observed in the central field of view. These findings suggest that the appearance of arbitrary texture images which is captured at a glance can almost completely be explained by the hierarchical neural representation of low- and high- level statistical image features in the visual cortex.

It has been suggested that human perception of surface materials can be explained by both low- and high-level image statistics of surface areas. For example, some early studies suggested that surface gloss perception is supported by very low-level statistics such as moment statistics (Adelson, 2001; Motoyoshi et al. 2007; Sharan et al. 2008; Motoyoshi & Matoba, 2012). However, this idea had obvious limitations (Anderson & Kim, 2009; Wiebel et al., 2015), which was represented by the inability of PS models to reproduce gloss perception (Wang et al., 2013). Other studies have denied the use of image statistics and instead indicated the importance of the visual cues corresponding to

physical properties such as local 3D shapes and highlights (Anderson & Kim, 2009; Kim & Anderson, 2010; Marlow & Anderson, 2013). However, these features are subjectively defined by researchers rather than objectively measured from images, and their experimental evidence is often obtained by using unrealistic or extremely rare visual stimuli. It has also been pointed out that most of the glossiness perception in a wide range of natural images can be explained even by very low level image statistics such as luminance histograms (Wiebel et al., 2015). On the other hand, recent findings, such as the remarkable success of neural style transfer (Gatys et al., 2015) and the recent accurate prediction of gloss perception and misperception using unsupervised deep learning models (Storrs et al., 2021), strongly support the idea that low- and high-level statistical representations for textural images can still explain a wide range of the perception of material properties. Higher-level neural activity that could not be explained by image statistics in the previous fMRI studies (e.g., Goda et al., 2014) is expected to be explained by these higher-level image statistics.

Given that the statistical representation is invariant to the layout of features within an image region, we expected that the neural response of these features could be extracted even from EEG with low spatial resolution. Indeed, we have shown not only that the visual evoked potentials (VEPs) for various natural texture images were systematically correlated with low-level image statistics, but that we could synthesize perceptually similar textures based on image statistics reconstructed by the VEPs (Orima & Motoyoshi, 2021). In a subsequent study, they also succeeded in synthesizing photorealistic texture images from VEPs using a deep generative model (MVAE) (Wakita et al., 2021). Based on these findings, by using EEG signals, it is natural to assume that we can decode material perception, which is believed to be governed by low-level and high-level statistical feature representations. If it is possible to decode perceived surface properties and material categories from EEG signals that are evoked through observation of visual stimuli for a few hundred milliseconds, and to synthesize similar image appearances from the EEG signals, it would further support the idea that a large part of material perception depends on low- and high-level textural (statistical) information.

In the present study, we conducted a series of experiments and analyses using EEG to

find dynamic and multidimensional neural representations that support the perception and discrimination of natural surfaces in a single glance. In part 1, we trained a support vector machine (SVM) using measured VEPs as input. As a result, material categories and perceived surface properties were classified at a statistically significant level, and the temporal development of visual material processing was revealed. The results suggest that neural representations, as reflected in the temporal patterns of the EEG, support the discrimination of natural surface materials and the perception of their characteristics. In Part 2, to clarify how such neural representations are related to statistical features in surface images, we applied representation similarity analysis between subband image statistics or style information in dCNN models and VEPs. We found that style information is highly correlated with the VEPs. Inspired by this strong correlation, in Part 3, we attempted to reconstruct the surface images presented to observers from the VEPs using a multimodal variational autoencoder (MVAE), which followed the model in our previous study (Wakita et al., 2021). The results showed that some of the reconstructed images were strikingly similar to the original images and most of the reconstructed images from the VEPs reproduced the original images. Psychophysical experiments showed that more than 80% of the reconstructed images were more similar to the original than randomly reconstructed images, and that the perceived material categories and perceived surface properties of the reconstructed images matched those of the original images at a significant level. These results support the findings of a series of material perception studies and suggest that even rich and complex properties of object surfaces that are difficult to describe can be decoded by simple VEPs. Therefore, these results provided further support for the idea that human texture and material perception relies on lower-level, global features that are reflected even in VEPs.

Part 1: Classification of Material Categories and Surface properties from VEPs

First, we measured VEPs for a large number of natural surface images made of various materials, and used SVM to examine how the VEPs reflect neural information that supports perceptual categorization of material categories and surface properties.

Method

Observers

Fifteen naïve students participated in the experiment. All observers had normal or corrected vision. All experiments were conducted in accordance with the guidelines set by the "Ethical Review Committee for Experimental Research on Human Subjects, Faculty of Arts and Sciences, The University of Tokyo," and the all observers provided written informed consent.

Equipment

In EEG recordings, the visual stimuli were generated by a PC (HP Z2 Mini G4 Workstation) and presented on a 24-inch gamma-corrected LCD (BenQ XL2420T) with a refresh rate of 60 Hz and a spatial resolution of 1.52 min/pixel at the 88 cm viewing distance we used.

In psychophysical experiments, visual stimuli were generated by a PC (HP Z2 Mini G4 Workstation) and presented on a 24-inch gamma-corrected LCD (BenQ XL2720) with a refresh rate of 60 Hz and a spatial resolution of 1.47 min/pixel at the 73 cm viewing distance we used.

Visual stimulus

The original images of the visual stimuli were 191 natural texture images of 256 x 256 pixels (Fig. 1). All images were collected from the Motoyoshi Lab texture database and the Internet. All images were categorized into one of the following material categories: bark, fabric, feather, feather, fish scale, fur, glass, grass, gravel, hair, leather, metal, paper, paste, plastic, powder, rock, skin, soil, sponge and wood.

Each image was further divided into five variants, each of which was cropped from the upper left, upper right, lower left, lower right, and center of each image to a size of 5.7 x 5.7 deg (224 x 224 pixels), which were used for EEG measurements.

Figure 1. Visual stimuli used in the experiment. One image from each material category is shown as a representative.

EEG recording procedures

The EEG experiments were conducted in a shielded dark room. In each session, 191 of 5.7 x 5.7 deg natural surface images were presented once in a random order. All images were presented for a duration of 500 ms, followed by a 750 ms uniform background blank. Observers viewed the visual stimuli foveally through steady fixation on the small black dot that appeared in the center of the screen. EEG recordings were made while the observers viewed the visual stimuli. The observer's eye movements were controlled by the pre-experiment instruction (cf. Orima & motoyoshi, 2021, 2023). This session was repeated 5 times for each of 5 variants, 25 times in total for each observer. The same variant was presented in the same session.

EEG data preprocessing

EEG data were obtained from 31 electrodes (Fp1, Fp2, F3, F4, C3, C4, P3, P4, O1, O2, F7, F8, T7, T8, P7, P8, Fz, Cz, Pz, FC1, FC2, CP1, CP2, FC5, FC6, CP5, CP6, FT9, FT10, TP9, and TP10) in accordance with the international 10-20 system at a sampling rate of 1000 Hz (BrainVision Recorder, BrainAmp amplifier, EasyCap; Brain Products GmbH). The impedance of each electrode was kept below 5 kΩ (except Cz, P3, and FT10 for one observer). An additional electrode, located between Fz and AFz, was used as ground. In addition, all electrodes were referenced to another electrode located between Fz and Cz, and all electrode data were re-referenced offline using the average of all electrodes. The recorded EEG data were filtered by a 0.1-40 Hz bandpass filter and divided into epochs of

-0.4-0.8 s from the stimulus onset. Baseline correction was performed using -100-0 ms from stimulus onset as a baseline. The artifact component (i.e., eye movements) was removed by independent component analysis and the epochs including abnormal amplitude (exceeding the range form -75 to 75 µV) were rejected to remove epochs with eye blinks. Additionally, 28 epochs (0.04 % of the total) in which the trigger did not work correctly were excluded from the data.

<u>Measurement of surface properties values</u>

In a separate session from the EEG experiment, fifteen observers rated the surface properties of each visual stimulus on a 5-point scale from 0 to 4. Observers rated the lightness (dark-light), chromaticity (achromatic-vividly colored), smoothness (rough-smooth), glossiness (matte-gloss), hardness (soft-hard), and heaviness (light-heavy) of a 6.3 x 6.3 deg visual stimulus presented in random order at the center of the screen. The observers rated twice for each visual stimulus with free viewing. The averaged values within each observer and then across observers were used as the representative values of each surface characteristic.

Results

<u>VEPs</u>

Figure 2 shows the grand average VEPs for all images every 50 ms from 50 ms to 500 ms after the stimulus onset. Red indicates positive amplitudes and blue indicates negative amplitudes. VEPs were particularly large in the occipital lobe (O1/O2). A rise in VEPs in the occipital lobe (O1/O2) was observed about 100 ms after the stimulus onset, and then they began to decrease about 150 ms and later. Thereafter, the amplitude increased again in the occipital lobe, peaking at about 250 ms, and then decreased in the occipital lobe.

Time from stimulus onset (msec)

Figure 2. Topographical map of measured VEPs. The color of the map represents the potential and corresponds to the indicator on the right.

Classification of material category

To examine whether the VEPs reflect the information sufficiently enough to discriminate material categories, we trained SVMs to classify the 20 material categories of the corresponding visual stimuli using the VEPs as input.

EEG data were preprocessed as explained in the method section and 1~50, 1~75, ..., 1~500 ms data of the stimulus onset (accumulation condition), or 1~50, 26~75, ..., 451~500 ms of the stimulus onset were used as input (time-window condition). Of all the channels used in the EEG experiments, we used the EEG data from 29 electrodes (F3, F4, C3, C4, P3, P4, O1, O2, F7, F8, T7, T8, P7, P8, Fz, Cz, Pz, FC1, FC2, CP1, CP2, FC5, FC6, CP5, CP6, FT9, FT10, TP 9, and TP10). We used the VEPs averaged across observers as input because the maximum number of VEPs for each visual stimulus for each observer was 25, and even if all of them were averaged, they were still noisy. For each classification, the time and electrode data for each image were flattened, resulting in 29xT (T: number of time points) variables for each image, but the maximum number of independent variables was 14,500, which was much larger than the sample size of 191. Therefore, taking advantage of the fact that the data for each time point and each electrode in the VEPs were correlated with each other, principal component analysis (PCA) was applied to the VEPs, and the principal component (PC) scores up to the PCs whose cumulative explanatory power were greater than 99% were used for the classifications. The number of principal components selected was an average of 123 and a maximum of 144 for accumulation condition, and an average of 58 and a maximum of 73 for time-window condition, all of which were smaller than the sample size of 191. The classifications were performed using the Matlab function 'fitcecoc' as a multiclass classification using the one vs one method.

To perform statistical test of the classifications using the number of images as the sample size, the train/test split in SVM training was performed using the leave one out method.

In other words, only the VEPs for one image were used as testing data, and the remaining VEPs were input for training the SVM model. The predictions were made by inputting the testing VEP to the trained SVM model. This was repeated 191 times for each SVM model, the number of images, and the average of the prediction was used as the classification accuracy of the SVM model.

Figure 3 shows the classification accuracy of material categories by the SVM models. The light blue line indicates the classification accuracy of accumulation condition, the yellow line indicates the classification accuracy of time-window condition, and the error bars indicate the standard error of the classification accuracy at each time. Each colored line at the top of the graph indicates that the corresponding classification accuracy was statistically significant (p<0.05, FDR corrected) by binomial tests. We adopted the Benjamini-Hochberg false discovery rate (FDR) correction method (Benjamini & Hochberg, 1995) to address the multiple comparison. The dotted line indicates the chance level (5 %).

Figure 3. Classification accuracy of 20 material categories by the VEPs. Light blue line represents the classification accuracy of accumulation condition, and yellow line represents the classification accuracy of time-window condition. Error bars indicate ±1 s.e.m. between cross-validation sets.

Under the accumulation condition, The classification accuracy of the 20 material

categories became significant at 150 ms after the stimulus onset, eventually reaching nearly 35 %, much higher than the chance level. The results of the time-window condition revealed that the classification accuracy was greatest at around 200 ms after the stimulus onset. These results suggest that the information encoded before 200 ms of stimulus onset may contribute significantly to the discrimination of material categories. The classification results of the accumulation condition also showed that the classification accuracy continued to increase even at later latencies, such as 300 ms after the stimulus onset, suggesting that information encoded at later latencies also contributed to the encoding of material categories.

Classification of perceived surface properties

Next, to examine whether the VEPs reflect the information related to the evaluation of various surface properties, we split rating values of each surface characteristic into 5-steps to distribute the same number of data for each step, and we trained SVMs to classify 5-step degree of each surface characteristic (lightness, chromaticity, smoothness, hardness, and heaviness) of the corresponding visual stimuli using the VEPs as input.

EEG data were preprocessed as explained in the method section and 1~50, 1~75, ..., 1~500 ms data of the stimulus onset. Of all the channels used in the EEG experiments, we used the EEG data from 29 electrodes (F3, F4, C3, C4, P3, P4, O1, O2, F7, F8, T7, T8, P7, P8, Fz, Cz, Pz, FC1, FC2, CP1, CP2, FC5, FC6, CP5, CP6, FT9, FT10, TP 9, and TP10). We used the VEPs averaged across observers as input because the maximum number of VEPs for each visual stimulus for each observer was 25, and even if all of them were averaged, they were still noisy. For each classification, the time and electrode data for each image were flattened, resulting in 29xT (T: number of time points) variables for each image, but the maximum number of independent variables was 14,500, which was much larger than the sample size of 191. Therefore, taking advantage of the fact that the data for each time point and each electrode in the VEPs were correlated with each other, principal component analysis (PCA) was applied to the VEPs, and the principal component (PC) scores up to the PCs whose cumulative explanatory power were greater than 99% were used for the classifications. The number of principal components selected was an average of 123 and a maximum of 144, all of which were smaller than the sample size of

191. The classifications were performed using the Matlab function 'fitcecoc' as a multiclass classification using the one vs one method.

To perform statistical test of the classifications using the number of images as the sample size, the train/test split in SVM training was performed using the leave one out method. In other words, only the VEPs for one image were used as testing data, and the remaining VEPs were input for training the SVM model. The predictions were made by inputting the testing VEP to the trained SVM model. This was repeated 191 times for each SVM model, the number of images, and the average of the prediction was used as the classification accuracy of the SVM model.

Figure 4 shows the classification accuracy of the SVM models classifying surface properties. In each panel, the color of each line corresponds to the legend, with darker colors corresponding to larger rating values. Each color line at the top of each panel indicates that the corresponding classification accuracy was statistically significant ($p<0.05$, FDR corrected) by a binomial test, and the dotted line represents the chance level (20 %).

Figure 4. Classification accuracy of surface properties by the VEPs. Each graph represents the classification accuracy when all VEPs up to the time of each point were input. The error bars corresponding to ±1 s.e.m. between cross-validation sets are omitted for the sake of graph readability, since they are determined dependently from the number of data and the average value.

The classification accuracies of lightness, chromaticity, and smoothness were statistically significant within 175 ms after the stimulus onset, while those of glossiness, hardness, and heaviness became consecutively significant only after 200 ms from the stimulus onset. In addition, the classification accuracies were varied among the surface properties. For instance, smoothness was classified with high accuracy, including the group that was classified with more than 70 %, while glossiness was classified with high accuracy only in the "very glossy" group.

Part 2: Relationship between Statistical Image Features and VEPs

The results of Part 1 showed that VEPs for various surface images can classify the perceived material categories and perceived surface properties of the corresponding visual stimuli. Given that VEPs tend to reflect global properties of visual stimuli, these results suggest that the perception of natural surface materials and characteristics are supported by global statistical features. To test this hypothesis, we investigated how the VEPs for natural surface images correlated with the two representative statistical image features: image statistics that have been suggested to contribute to texture perception in previous studies (Portilla & Simoncelli, 2000) and style information computed by the neural style transfer technique (Gatys et al., 2015), which is capable to capture rich and complex surface properties.

Method

Computation of the image statistics

First, we computed low-level statistical features, image statistics, that have been shown to be important for texture perception in the previous studies (Portilla & Simoncelli, 2000; Hiramatsu et al., 2011; Orima & Motoyoshi, 2021). First, each image was converted to Lab color space. For the L channel, the image was decomposed to subband images of 7 spatial frequencies (2- 128 c/image, 1-octave steps) and 8 orientation bands (0-157.5°, 22.5° steps) using bandpass filters of 1-octave spatial frequency bandwidth and 30° orientation bandwidth. For each subband images, the moment statistics (log SD, skewness, and log kurtosis) were calculated. In addition, correlations between subband energy images of different orientation and spatial frequency were calculated. These image statistics were properly summarized in the same manner as our previous study (Orima & Motoyoshi, 2021) considering the property of textures. For the color channels, pixel moment statistics were calculated according to the previous studies (cf. Hiramatsu et al., 2011). These procedures yielded 47 values of image statistics for each visual stimulus.

Figure 5 shows a synthesized image generated using the algorithm provided by Portilla & Simoncelli (2000), which synthesizes images using image statistics that are theoretically almost equivalent to those computed in the present study. The PS synthesized images

retain some aspects of surface materials and characteristics, but other surface properties, such as glossiness and hardness, are different from the original image (see Wang et al., 2013).

Computation of the style information

Neural style transfer (NST) developed by Gatys et al. (2015) is a technique that enables us to apply a "style" of images, which describes complex surface properties such as painting styles of artistic images, to arbitrary images. The style information computed by this algorithm is calculated as a gram matrix of activations of convolutional blocks in a dCNN such as VGG19, which performs object recognition.

In the present study, we computed the gram matrices of the activations of the first to fifth convolutional blocks when each visual stimulus was input to VGG19 (Simonyan & Zisserman, 2014). The sizes of the gram matrices derived from the first to fifth convolutional blocks were 64x64, 128x128, 256x256, 512x512, and 512x512, respectively, yielding 610,304 values in total for each visual stimulus.

Figure 5 also shows style synthesized images sharing only style information with the original image. For each image, white noise was used to compute content loss, and the original image was used to compute style loss. As shown in Figure 5, the synthesized image based on the style information reproduces almost exactly the surface properties of the natural surface, including material and gloss. Therefore, image statistics and style information may play such an important role in the perception of surfaces that they can reconstruct images that accurately reproduce surface materials and characteristics.

Original

PS synth.

Style synth.

Figure 5. Examples of PS-synthesized and style synthesized images. Each image in the lower row corresponds to the original image in the upper row in the same column.

Reverse-correlation analysis between VEPs and statistical image features

To investigate the latency to represent image statistics and style information in the visual cortex, we performed a reverse correlation analysis between representational similarity of VEPs and the image statistics, or the style information.

For the analysis, the VEPs of 29 electrodes, excluding Fp1 and Fp2, were used. To clarify how the correlations changed in accordance with latency, we used data from 1~50, 26~75, ... , 451~500 ms after stimulus onset. Correlation coefficients were calculated between the dissimilarity matrix of the VEPs and that of image statistics or style information.

Result

Figure 6 shows the temporal development of the correlations (N = 18,145) between the dissimilarity matrix of the VEPs and that of the image statistics (yellow line) or style information (green line). The correlation with the image statistics reached a maximum at around 200 ms after the stimulus onset (r_{max} = 0.22, $p < 10^{-189}$), while the correlation with style information reached a maximum at around 175 ms after the stimulus onset (r = 0.38, p ≃ 0).

Figure 6. Temporal development of the correlation between the dissimilarity matrix of the VEPs and the image statistics, or the style information for each time window.

Image statistics are spatially global image features computed from the entire image. The style information is also global information because it is the gram matrix, inter-channel correlations, of the activation in the dCNN model (Krizhevsky et al., 2012; Zeiler & Fergus 2014), which consequently learned similar kernels to the receptive field properties of neurons in the human visual cortex and statistical structure of natural images. Therefore, these results suggest that the perception of natural surfaces is strongly supported by statistical image features.

Part 3: Surface Image Reconstruction from VEPs

The results of Part 1 and Part 2 suggest that the perception of natural surfaces is supported by statistical image features, and such features are strongly reflected in the VEPs for natural surface images. Inspired by these results, we hypothesized that it might be possible to reconstruct statistical features from VEPs and even decode perceptual impressions of natural surfaces based on these features. In Part 3, we constructed a multimodal variational autoencoder (MVAE) model using the VEPs measured in Part 1 and their corresponding visual stimuli as inputs, and attempted to reconstruct the visual stimuli themselves only by the VEPs.

Method

The MVAE model

Figure 7 shows a schematic diagram of the developed MVAE model based on Wakita, Orima, & Motoyoshi (2021). Surface images and VEPs of a certain variant were used as testing data, and the remaining variants were assigned as the training data. 5-fold cross-validations were performed to ensure that each variant was assigned to the testing data (variant condition).

The EEG data were preprocessed as described in the method section of the Part 1 and treated as 500 dimensional vector data from 1 ms to 500 ms after the stimulus onset. 30-35 samples of EEG data corresponding to a single texture stimulus were picked up in random combinations and averaged for input to the model. The average waveforms were normalized to min0 and max1 to eliminate the influence of the absolute value of each channel (cf. Wakita et al., 2021). The VEPs of 29 electrodes (F3, F4, C3, C4, P3, P4, O1, O2, F7, F8, T7, T8, P7, P8, Fz, Cz, Pz, FC1, FC2, CP1, CP2, FC5, FC6, CP5, CP6, FT9, FT10, TP9, and TP10) were used as input. The visual stimuli resized to 128 x 128 pixels was used as the other modal input. The reconstructed image was also a 128 x 128 pixels image. The learning rate was set to 5e-5 and the Adam gradient descent method was used to train the model. The batch size was 16, vector size of latent variables in the MVAE model was 256, and the training epoch was 1,500.

Table 1 shows the architecture of the MVAE model. In practice, except for the final output

layer, each convolution layer is followed by batch normalization and ReLU rectifier. The design of the loss function is the same as in the previous study (Wakita et al., 2021).

For comparison, another MVAE model was developed and trained using only VEPs within 200 ms from stimulus onset. This was because it would be interesting to compare this model with the MVAE model trained using all VEPs as input, considering the fact that the results of the Part 1 suggested that the encoding of information related to low-level image features and surface properties is completed within 200 ms after stimulus onset. This MVAE model was trained under the same conditions as the MVAE model developed first, but because the size of the input VEPs was different, the structure of the model was slightly different, as shown in Table 2. We developed both MVAE models using almost the same number of parameters as possible.

Figure 7. Schematic diagram of MVAE.

Table 1. Architecture of the MVAE models trained with all VEPs.

Image modal		EEG modal	
encoder	decoder	encoder	decoder
Input 3x128x128	FC 256-256	Input 29x500	FC 256-256
Conv2d 1-32-1	UpConv2d 3-512-1	Conv1d 3-128-2	UpConv1d 3-256-2
ResNetBlock 3-32-1	ResNetBlock 3-512-1	ResNetBlock 3-128-1	ResNetBlock 3-256-1
AvgPool2d 1/4	UpConv2d 2-256-1	Conv1d 1-128-1	UpConv1d 3-128-2
Conv2d 1-64-1	ResNetBlock 3-256-1	ResNetBlock 3-128-1	ResNetBlock 3-128-1
ResNetBlock 3-64-1	UpConv2d 2-128-1	Conv1d 1-128-1	UpConv1d 3-128-2
AvgPool2d 1/2	ResNetBlock 3-128-1	ResNetBlock 3-128-1	ResNetBlock 3-128-1
Conv2d 1-128-1	UpConv2d 4-64-1	Conv1d 1-128-1	UpConv1d 3-64-2
ResNetBlock 3-128-1	ResNetBlock 3-64-1	ResNetBlock 3-128-1	ResNetBlock 3-64-1
AvgPool2d 1/2	UpConv2d 4-32-1	AvgPool1d 1/3	UpConv1d 3-64-2
Conv2d 1-256-1	ResNetBlock 3-32-1	Conv1d 3-256-2	ResNetBlock 3-64-1
ResNetBlock 3-256-1	UpConv2d 1-3-1	ResNetBlock 3-256-1	UpConv1d 3-32-2
AvgPool2d 1/2	Sigmoid	Conv1d 1-256-1	ResNetBlock 3-32-1
COnv2d 1-512-1	Output 3x128x123	ResNetBlock 3-256-1	UpConv1d 3-32-2-2
ResNetBlock 3-512-1		Conv1d 1-256-1	ResNetBlock 3-32-1
Conv2d 1-512-1		ResNetBlock 3-256-1	UpConv1d 4-29-2-2
AvgPool2d 1/4		Conv1d 1-256-1	ResNetBlock 3-29-1
FC 512-256 (mean)		ResNetBlock 3-256-1	UpConv1d 1-29-1
FC 512-256 (var)		AvgPool1d 1/3	ResNetBlock 3-29-1
		Conv1d 3-512-2	Sigmoid
		ResNetBlock 3-512-1	Output 29x500
		Conv1d 1-512-1	
		ResNetBlock 3-512-1	
		Conv1d 1-512-1	
		ResNetBlock 3-512-1	
		Conv1d 3-256-2	
		AvgPool1d 1/2	
		FC 256-256 (mean)	
		FC 256-256 (var)	

Table 2. Architecture of the MVAE models trained with VEPs from stimulus onset to 200 ms.

Image modal		EEG modal	
encoder	decoder	encoder	decoder
same as full VEP		Input 29x200	FC 256-256
		Conv1d 3-128-2	UpConv1d 2-256-2
		ResNetBlock 3-128-1	ResNetBlock 3-256-1
		Conv1d 1-128-1	UpConv1d 3-128-2
		ResNetBlock 3-128-1	ResNetBlock 3-128-1
		Conv1d 1-128-1	UpConv1d 3-128-2
		ResNetBlock 3-128-1	ResNetBlock 3-128-1
		Conv1d 1-128-1	UpConv1d 3-64-2
		ResNetBlock 3-128-1	ResNetBlock 3-64-1
		AvgPool1d 1/3	UpConv1d 2-64-1
		Conv1d 3-256-2	ResNetBlock 3-64-1
		ResNetBlock 3-256-1	UpConv1d 3-32-2
		Conv1d 1-256-1	ResNetBlock 3-32-1
		ResNetBlock 3-256-1	UpConv1d 3-32-2
		Conv1d 1-256-1	ResNetBlock 3-32-1
		ResNetBlock 3-256-1	UpConv1d 3-29-2
		Conv1d 1-256-1	ResNetBlock 3-29-1
		ResNetBlock 3-256-1	UpConv1d 2-29-1
		AvgPool1d 1/3	ResNetBlock 3-29-1
		Conv1d 3-512-2	Sigmoid
		ResNetBlock 3-512-1	Output 29x200
		Conv1d 1-512-1	
		ResNetBlock 3-512-1	
		Conv1d 1-512-1	
		ResNetBlock 3-512-1	
		Conv1d 1-512-1	
		ResNetBlock 3-512-1	
		Conv1d 1-256-1	
		AvgPool1d 1/2	
		FC 256-256 (mean)	
		FC 256-256 (var)	

Result

Reconstruction of visual stimuli from VEPs (variant condition)

Figure 8a shows the reconstructed image when the average VEPs assigned to the testing

data were input to the MVAE model, which has been trained with all VEPs in the training set. The input VEPs were normalized to min0 and max1 for each image and within each channel in the same way as training. As shown in Fig. 8a, many reconstructed images are similar to the original images, and some of them were photorealistic and hard to distinguish from the original images.

Figure 8b shows the reconstructed images when the average VEPs assigned to the testing data were input to the MVAE model, which has been trained with the VEPs within 200 ms from stimulus onset. Although some of the reconstructed images were comparable to those in Fig. 8a, many of them had slightly lower quality.

(a) Full length VEP

(b) VEP at ~200 ms

Figure 8. Examples reconstructed images only from the VEPs in the testing data (variant condition). (a) Reconstruction images via the MVAE models trained with full length VEPs, (b) Reconstruction images via the MVAE model trained with VEPs within 200 ms from stimulus onset.

To quantitatively assess the quality of the reconstructed images, we examined whether the reconstructed images in each validation set were similar to the original images through psychophysical rating experiments. We adopted the two alternative forced choice (2AFC) experiment, following the previous study (Wakita et al., 2021). In the experiment, the original image was presented at the center of the screen, the corresponding reconstructed image (target) was presented on one side, and a randomly selected non-corresponding reconstructed image (non-target) was presented on the other side. Eleven

observers responded which image was more similar to the original image by pressing a button with free viewing. The viewing distance was adjusted so that the stimulus size was 5.7 x 5.7 deg (40 cm). Observers were strongly instructed to judge by pure visual appearance, not by categorical classification. Responses were made once for each validation set, and the responses to the five validation sets were averaged to obtain a representative value for each observer. Finally, the percentage of correct responses was averaged across observers. The reconstructed images from the two types of MVAE models were evaluated in separate experimental blocks.

Figure 9a shows the results of the experiment. We found that 46.6 % of reconstructed images from the VEPs within 200 ms from the stimulus onset were more similar to the original images (green bars), while 83.2 % of the reconstructed from the full length VEPs were more similar to the original images (blue bars). Note that we considered a target image is "more similar" than a non-target image if the correct response rate was significantly above the chance level (50 %) of the 2AFC experiment (two-tailed t-test; $p <$ 0.05, FDR-corrected). These results suggest that the perceptual appearance of the surface image itself was successfully reconstructed from the VEPs. As shown in the scatterplot in Fig. 9b, the correlation between the ratings was 0.36. Overall, the reconstructed images from the VEPs within 200 ms from the stimulus onset had lower quality, but we could not find consistent trend across conditions.

Figure 9. (a) Probability of responses that the reconstructed images (target) were more similar to the original images than a non-target image. Blue indicates the results for full length VEPs, and green indicates the results for the VEPs within 200 ms from the stimulus onset. The red dotted line indicates chance level, and the dots at the top of each panel indicates that the correct response rate was statistically significant. (b) A scatter plot of the data in (a). The horizontal axis represents the reconstruction from the VEPs with 200 ms from the stimulus onset, and the vertical axis represents the reconstruction from the full length VEPs. The red dotted lines indicate chance levels, and error bars at each point indicate ±1 s.e.m. between observers in the corresponding axes.

In addition, for the MAVE model trained on the full length VEPs, we also tested which

material category the reconstructed images would be classified into. Ten observers classified the reconstructed images presented at the center of the screen into one of 20 categories according to the legend presented on the right side of the screen. Responses were made once for each validation set, and the responses to the five validation sets were averaged to obtain a representative value for each observer. Finally, the proportion of correct responses was averaged across observers. As shown in Fig. 10a, for 72.3% of the images, the reconstructed images were classified into the same material category as the original images at a statistically significant level (two-tailed t-test; $p < 0.05$, FDR-corrected), suggesting that the material category was successfully reproduced by the VEPs. Figure 10b shows the average proportion of correct for each material category. The results show that grass, fish scale, paper, gravel, and leather were particularly well reconstructed.

Figure 10. (a) Probability of responses that the reconstructed images were classified into the correct material category. The experiment was conducted only for the reconstructed images from the full length VEPs. (b) Average probability of responses for each material category that the reconstructed images were classified into the correct material category. In each panel, the red dotted line represents the chance level, the dots in (a) and the * in (b) at the top of each panel indicate that the proportion of correct was statistically significant ($p < 0.05$, FDR-corrected). Error bars at each point indicate ±1 s.e.m. between observers.

Figure 11 shows the comparison of the surface characteristic evaluation values for the reconstructed image from the VEP with those for the original images. The scatter plot in Fig. 11a shows the relationship between the surface characteristic evaluation for the original imagess (X-axis) and that for the reconstructed image (Y-axis) under the variant condition. Together with the results in Fig. 10a, this plot shows that observers perceived similar surface properties in the reconstructed image as in the original image, but the degree of similarity was different for each surface characteristic. Fig. 11b shows the correlations between surface characteristic evaluation values for the original and

reconstructed images: r = 0.76, 0.66, 0.76, 0.59, 0.62, and 0.61 for lightness, chromaticity, smoothness, glossiness, hardness, and heaviness, respectively. The correlations were relatively low for glossiness, hardness, and heaviness.

Figure 11. (a) A scatter plot of surface characteristic evaluation values for the original images and the reconstructed images. Each point corresponds to each image, and each color corresponds to each surface characteristic shown in the right of the panel. (b) Correlation coefficients between the surface characteristic evaluation values for the original images and the reconstructed images.

Note that the grading of material categories and surface properties was not performed for the MVAE model trained with VEPs within 200 ms from the stimulus onset, where the reconstruction of the visual stimuli was not successful very much.

Classification of material categories and surface properties by latent variables in MVAE models

The reconstructed images from the VEPs retained the material categories and surface properties of the original images. This may be because the MVAE models trained by the visual stimuli and the corresponding VEPs acquired information related to the material categories and surface properties that were reflected in the VEPs. To confirm this

hypothesis directly, we tested whether the 256-dimensional latent variables (z) of the MVAE models that was obtained by inputting the VEPs of the testing data could classify the material categories and surface properties of the corresponding visual stimuli. Latent variables were extracted from each of the five trained MVAE models in the variant condition, and each of them was used as the input to SVM models to classify material categories and surface properties of corresponding visual stimulus. The training and testing procedures of SVM models were the same as the Part 1. The classification accuracy was averaged across the five MVAE models, and finally, a binomial test was conducted using the number of images as the sample size.

Figure 12 shows the classification accuracy of material categories and surface properties by the latent variables of the MVAE model. The material categories and all surface properties except for glossiness were significantly classified, especially smoothness was classified with high accuracy. The result was consistent with our observation that the smoothness of the original images was well reflected in the reconstructed images.

Figure 12. Classification accuracy of material categories and surface properties by latent variables in the MVAE model. Dotted lines in each panel represent the chance level of the classifications. Error bars indicate ±1 s.e.m. between the five MVAE models and * indicate the significant classification accuracy ($p < 0.05$, FDR-corrected).

Reconstruction of visual stimuli from VEPs (image-split condition)

The results of variant condition were obtained using only the VEPs in the testing set, but there was a problem that the corresponding visual stimulus of the VEPs in the testing set and those of the VEPs in the training set shares the same original images, that is, we could not confirm under the variant condition whether the MVAE model can reconstruct images that have never encountered only by the VEPs for perfectly unknown images.

To address this problem, we constructed another MVAE model under the condition that the images and corresponding VEPs used for training were not used for testing at all. In this model, 191 original images were split into a 5:1 ratio, and the smaller portion of images were allocated as the testing data (image-split condition). The images included in the testing data and the VEPs for the variant images in the testing data were not used for training at all.

Figure 13 shows the reconstructed images of the image-split condition. In the image-split condition, many images were reconstructed realistically.

Figure 13. Reconstructed images only from tshe VEP in the testing data under the image-split condition.

To evaluate the quality of these reconstructed images and to assign material categories, we conducted the rating experiment using the same experimental paradigm as in the variant condition. As shown in Fig. 14a, 50 % of the reconstructed images were considered more similar to the original images at a statistically significant level (one-tailed t-test; p<0.05, FDR-corrected). In addition, Fig. 14b shows that 28.1% of the reconstructed images were classified into the same material category as the original image at a statistically significant level (two-tailed t-test; p<0.05, FDR-corrected). Note

that images with a 0 % correct response rate in Fig. 14b were classified into a specific wrong category, resulting in 0 % accuracy instead of the chance level of 5 %.

Figure 14. Probability of responses that the reconstructed images (target) were more similar to the original images than a non-target image under the image-split consition. (a) Similarity to the original image, (b) Material category assignment, respectively. In each panel, the red dotted line indicates the chance level, and the blue dots at the top of each panel indicates that the proportion of correct responses was statistically significant. Error bars at each point indicate ±1 s.e.m. between observers.

The results of part 3 showed that it is even possible to reconstruct the surface image itself from VEPs for natural surface images, and some reconstructed images were photorealistic. Furthermore, the results of the image-split condition showed that even completely unknown surface images can be reconstructed by the VEPs.

These results suggest that the perception of object surface material and surface properties are strongly based on global textural features to the extent that the visual

stimuli themselves can be reconstructed from VEPs for surface images.

General Discussion

In the present study, we measured VEPs for natural surface images made of a wide range of materials to investigate the dynamic neural representations underlying the classification of material categories, surface properties, and the perceptual appearance of natural surfaces themselves. Part 1 showed that material categories and various perceived surface properties (lightness, chromaticity, smoothness, glossiness, hardness, and heaviness) can be decoded from VEP signals with high accuracy using SVM. Part 2 showed that these VEP signals at early latencies strongly correlated with dCNN style information in each image, suggesting that neural representations of lower- and higher-level statistical image features in the visual cortex support the perception of material categories and surface properties. Inspired by these results, in Part 3, we attempted to reconstruct the surface image itself by training a deep generative model (MVAE) using the surface images and corresponding VEPs as input. As a result, some of the reconstructed images were remarkably similar to the original images, suggesting that it is possible to decode even the indescribable impression of natural surface images. These results further support the idea that the perception of texture and material quality on complex natural surfaces is supported by neural representations of statistical image features that are reflected even in VEPs with low spatial resolution.

Rapid neural coding of surface materials

The SVMs trained to classify the material categories and surface properties of the corresponding visual stimuli by the VEPs achieved significant classifications for all conditions. The 20 material categories began to be significantly classified at around 150 ms after stimulus onset, and the classification accuracy reached a maximum at around 175-225 ms under the time-window condition. These results are consistent with previous studies showing that object surface material can be classified from early latency ERPs (Wiebel et al., 2014), some of natural surface material categories are distinguished and perceived based on statistical features of images that are suggested to be encoded in

early latency (Fleming, 2013; Orima & Motoyoshi, 2021), and that material categories can be classified by visual stimuli presented for very short periods of time (Sharan et al., 2014).

Another type of SVM significantly classified 6 types of perceived surface properties of each visual stimulus. Lightness and smoothness were classified within 150 ms from the stimulus onset, and chromaticity was classified within 175 ms from the stimulus onset. Especially, smoothness was classified with 70 % of classification accuracy, which was much higher than the chance level. These results suggest that lightness, chromaticity, and smoothness can be highly characterized only by the statistical image features that are easily reflected in the VEP at early latency (Orima & Motoyoshi, 2021). In fact, lightness, chromaticity, and smoothness correlates very strongly with the pixel mean of the luminance channel, the mean or SD of the color channel, and the meddle to high spatial frequency subband SD, respectively. These surface properties are also controlled by the manipulation of these image statistics (Giesel & Zaidi, 2013), suggesting that it is highly likely that these surface properties can be described by image statistics.

On the other hand, although the perceived glossiness, hardness, and heaviness of the surface could be classified at a significant level, the classification accuracy by the VEPs at early latencies remained lower than the other surface properties and became significant continuously for the first time at 200 ms after the stimulus onset. These results suggest that glossiness, hardness, and heaviness were perceived based on information whose encoding process is not easily reflected in the VEPs at early latencies. Previous studies have suggested that surface glossiness can be manipulated by the skewness of subband images (Motoyoshi et al., 2007), but while skewness can be computed by combining the outputs of simple and complex cells of V1, it is difficult to describe it only by their respective outputs. Therefore, the fact that only late latency VEPs for extremely glossy surface images could significantly classify glossiness is not inconsistent with the previous findings.

The result that the glossiness of visual stimuli could be classified from VEPs is consistent with the idea that glossiness can be captured by image features, as suggested by the previous studies that pointed out that the glossiness of visual stimuli can be easily

captured (Nagai et al., 2015) and described by image statistics (Motoyoshi et al., 2007). In the present study, only extremely glossy stimuli were significantly classified, but it is possible that the glossiness may be classified more accurately if the other image features had been controlled.

Although surface hardness and heaviness can be distinguished by visual information, their perception cannot be explained by the image features alone. These facts may be the reason why it was difficult to classify hardness and heaviness by the VEP at early latency. For example, in the previous studies, perceived surface hardness was not significantly classified from low-level image statistics alone, nor from BOLD signals in the early visual cortex such as V1 and V2 (Jacobs et al., 2014; Baumgartner & Gegenfurtner, 2016). These previous findings suggest that perceived surface hardness is difficult to explain solely by image statistics, which are likely to be reflected in early latency VEPs, and that perceived hardness is not largely reflected in brain activity of the early visual system. On the other hand, it has also been suggested that surface hardness can be determined merely from visual information (Baumgartner et al., 2013), which is consistent with our findings that hardness could be classified by the VEPs at a statistically significant level.

As shown in the demonstration in Fig. 5, synthetic images that shared only the statistical features of the visual stimulus with the original image, such as image statistics and style information, retained surface properties similar to those of the original image. Based on these observations, we confirmed that the statistical features of the visual stimulus are very important for the perception of natural surfaces. Furthermore, reverse correlation analysis between these image features and the VEPs revealed that the VEPs at 175-200 ms after the stimulus onset were strongly correlated with the style information. These latencies overlap with the latency at which the classification accuracy of the material category by the VEPs was maximized in Part 1, suggesting that the style information, which is strongly reflected in the VEPs, contributed significantly to the perception of material categories and surface properties. In addition, the VEPs at 175-200 ms after the stimulus onset were revealed to be correlated with the energy of spatial frequency subbands (Hansen et al., 2011), subband image statistics (Orima & Motoyoshi, 2021), and various types of statistical features (Greene & Hansen, 2020). Therefore, it is implied

that such style information is a mid-level feature that might be encoded following lower-level statistical features such as image statistics.

Style information is a feature that can accurately represent many types of the natural surface properties. Since the style information of surface images correlated strongly with the VEPs at a particular latency, it may be a relatively global image feature that reflects the statistical regularity of natural images, which may also be reflected in the VEPs. Therefore, even glossiness, which has been considered difficult to predict with statistical features in previous studies (Anderson & Kim, 2009) but successfully captured by the style information, was found to be describable with a higher-level statistical feature. These results support the previous studies (Nishida & Shinya, 1998; Motoyoshi et al., 2007; Sawayama & Nishida, 2018) that have shown that the materials and surface properties of natural surfaces depends on statistical features.

Reconstruction of surface appearance from EEG

In Part 3, we successfully reconstructed the visual stimulus only by the simple VEPs for the natural surface images. As shown in Fig. 8, some of the reconstructed images reproduced the impression of the original images quite faithfully, and other images were revealed to be reconstructed similarly to the original images (Fig. 9a). In addition, the observers classified the reconstructed images into the 20 material categories used in the experiment, and the results showed that many of the reconstructed images were classified into the same material categories as the original images at a statistically significant level (Fig. 10b). These results indicate that the material of the visual stimuli was also reconstructed. The MVAE models used for this reconstruction was trained by inputting a set of visual stimuli and their corresponding VEPs, and we defined the reconstructed image as the output image only from the VEPs in the testing set. However, the train-test split in this condition was performed with five different variants that were partially cropped from the original images, and although the corresponding visual stimuli to the VEPs in the testing set were not used for training, other parts of the original images that shared certain parts were used for training. Therefore, from a strict point of view, the train-test split was not perfect in the variant condition because the MVAE models "knew" the images that were similar to the corresponding visual stimulus to the

VEPs in the testing set. We therefore conducted a similar analysis (image-split condition) in which both the images and VEPs were completely split into training and testing data, that is, the corresponding visual stimulus to the VEPs in the testing set never be used for training.

The results showed that, as in the variant condition, some reconstructed images were very similar to the original images (Fig. 13), and the 50 % of reconstructed images were similar to the original images at statistically significant levels and 28.1 % of them were classified into the same material categories as the original images (Fig. 14). These results in Part 3 suggest that it is possible to reconstruct perceptually very similar images from the VEPs with low spatial resolution, i.e., to decode the visual impression itself, which is difficult to express in simple terms. The results of the image-split condition also showed that the MVAE model had certain generalization performance.

Under the variant condition, most of the reconstructed images were classified into the same material category as the original images and were shown to be more similar to the original images than the non-target images at a statistically significant level. As shown in Fig. 10b, images in all material categories except for feather were reconstructed significantly above the chance level. In addition, as shown in Fig. 11, the surface properties perceived from the original images and the those perceived from the reconstructed images were highly correlated, but the correlation was different for each surface characteristic. Specifically, the correlations were high for lightness, chromaticity, and smoothness, but relatively low for glossiness, hardness, and heaviness. The surface properties that were highly correlated are the same as the surface properties reflected in the VEPs at early latency, as suggested in Fig. 4. These results indicate that the images reconstructed by the VEPs retain surface properties that are well reflected in the VEPs at early latency.

Previous brain decoding studies have attempted to decode perceptual content or perception itself from brain activity patterns. Typically, it has been suggested that image attributes such as object category, scene category, orientation, and color of visual stimuli can be decoded based on brain activity measured by fMRI (Cox and Savoy, 2003; Haynes and Rees, 2005; Kamitani and Tong, 2005 Brouwer and Heeger, 2009; Parkes et al.,

2009; Peelen et al. 2009; Walther et al. 2009; Said et al. 2010). Although these early studies reconstructed lower-level characteristics of visual stimuli or image features associated with the visual stimuli, which were not visual impression itself, recent studies have proposed techniques to recover the visual stimuli themselves (Shen et al. 2019a, b). However, fMRI has many negative aspects associated with its cost of use, inconvenience of measurement and analysis, and potential invasiveness, which make it unsuitable for realistic use as a brain machine interface (BMI). To overcome such disadvantages, brain decoding using EEG has been investigated recently, which is superior to fMRI in terms of portability, invasiveness, and cost (Kaneshiro et al., 2015; Palazzo et al. 2020; Wakita et al., 2021). Some of these studies have succeeded in decoding perceived visual stimuli based on brain activity obtained from EEG, following the development of deep generative models such as the generative adversarial network (GAN, Goodfellow et al., 2014). However, the images generated from the brain activity remain blurred images with low resolution (Palazzo et al., 2017, 2020). On the other hand, previous studies focusing on style loss (Wakita et al., 2021) and the present study have succeeded in reconstructing images, some of which were indistinguishable from the original images and most of which retained the surface properties of the original images. In particular, the fact that the reconstructed images faithfully reproduced the material categories and surface properties, which were the main theme to address in the present study, suggests how much information related to the material categories and surface properties is reflected in the VEPs. This goal would have been difficult to be achieve with a model that proposed in the previous study, which reconstructed visual stimuli that would be blurred and may be difficult to determine surface properties.

Dynamical neural representations for material perception

The results of the present study suggest that low- and high-level statistical features are crucial for the perception of natural surface materials and surface properties. This idea was confirmed by the fact that the classification accuracy of material categories and some surface properties became significant within 175 ms after the stimulus onset as shown in Figs. 3 and 4, that style information characterizing surface perception correlated strongly with the VEPs within 200 ms after the stimulus onset, and that the visual impression of

surface images were successfully reconstructed only by the VEPs via MVAE models. These results are consistent with the fact that the global information that can be perceived in a single glance contributes to the rough perception of scenes and objects as well as natural surfaces (Potter, 1976; Thorpe et al. 2001; Greene & Oliva, 2009; Greene & Hansen, 2020; Jagadeesh & Gardner, 2022; Orima & Motoyoshi, 2023).

On the other hand, as shown in Fig. 3, the classification accuracy of material categories continued to increase after 200 ms from the stimulus onset, and some surface properties, such as glossiness, hardness, and heaviness, were well classified by the VEPs after 200 ms from the stimulus onset. These results indicate that semantic or abstract information that cannot be represented by statistical features alone contribute to the natural surface perception. The EEGs at such latencies have been found as the P300 (Sutton et al., 1965), which is said to reflect the perceived uncertainty, and N400 (Kutas & Hillyard, 1980), which is thought to reflect semantic discrepancies. Such ERP components at around 200~400 ms after the stimulus onset are usually observed in experiments involving psychological tasks that require attention to visual stimuli, and it was difficult to measure them directly in the experimental paradigm of the present study. However, it is worth discussing the fact that the VEPs at such latencies was found to be important. Previous studies (Kutas & Federmeier, 2000; Mudrik et al., 2014) have suggested that N400 reflects the use of semantic memory in language comprehension and responses to contextually strange scenes. Therefore, it is possible that the EEG signals at 200~400 ms from the stimulus onset reflected the processing of the meaning of visual stimuli. Although, to some extent, material categories can be distinguished by image features such as color and contrast, semantic analysis of the visual stimuli would also be necessary for the observer to recognize a particular material completely. In addition, the perception of surface properties such as glossiness, hardness, and heaviness would be reaffirmed by haptic perception (Baumgartner et al., 2013) and analysis with attention, even though there are some aspects that can be predicted from image features alone. Therefore, it is possible that the VEPs at later latencies (200 ms or later) also reflected an encoding process of information that contributed to material recognition, which was different from the information reflected in the VEPs at earlier latencies. Similar findings were also

reported in the previous study (Orima & Motoyoshi, 2021), in which a component correlated with "unnaturalness" of synthetic textures was found in the VEPs after 200 ms from the stimulus onset.

Use of EEGs for understanding natural vision

The MVAE models developed in the present study reconstructed very high-quality visual stimuli from simple VEPs alone. However, the realistic images such as reconstructed images obtained in the present study were not generated by the VEPs for natural scene images (obtained in Orima & Motoyoshi, 2023). Previous studies have found that the perception of texture, including natural surface images used in the present study, is largely based on lower-level features such as image statistics (Bergen & Adelson, 1988; Heeger & Bergen, 1995; Zipser et al. 1996; Portilla & Simoncelli, 2000; Baker & Mareschal, 2001; Motoyoshi et al. 2007; Freeman & Simoncelli, 2011; Freeman et al. 2013; Ziemba et al., 2019; Orima & Motoyoshi, 2021), but natural scenes have many aspects that cannot be explained by lower-level features alone (Groen et al., 2013; Epstein & Baker, 2019; Greene & Hansen, 2020). Information reflected in the EEG signals is global because of the limited spatial resolution of the EEG, which is recorded as the summation of a huge number of neurons' responses. This may be the reason why the reconstruction of natural scene images was challenging. Therefore, it is reasonable to assume that the remarkable results of the present study were limited to texture stimuli.

It is also difficult to completely deny the possibility that the MVAE model developed in the present study is generalizable only to the image set used in the present study. Although the results of the image-split condition confirm that the realistic reconstruction are not the product of complete overfitting to the image dataset of the present study, it was still imperfect. In the image-split condition, the training data included images similar to those assigned to the testing data (e.g., the training data was set to include grass images because the testing data included grass images). If a VEP for an image that did not resemble any image in the training data, the reconstructed image would not similar to the original image. One goal of brain decoding research is to fully reproduce perception from brain activity. The present study could play a part, but to achieve this goal completely, it would be necessary to train on a much larger number of images and VEPs than used in

the present study, as the AlexNet (Krizhevsky et al., 2012), which is a great object recognition model.

The architecture of the MVAE models used in the present study were the same as the model constructed in the previous study (Wakita et al., 2021), except that the number of parameters were increased to address color images. In the MVAE model used in the previous study and in the present study, one of the two modals was based on a two-dimensional image input, and the other was based on a one-dimensional VEP input. Recent study has developed a model called EEGNet, which yields high accuracy in EEG-based classification (Lawhern et al., 2018). In the other previous study, the EEGNet model is used to visualize spatiotemporal cortical mapping for natural scene perception (Orima & Motoyoshi, 2023). By using a two-dimensional network like EEGNet model instead of a one-dimensional convolutional network, it ma be possible to reconstruct the original image more realistically and to visualize the contribution of VEPs to the visual impression in a spatiotemporal manner. It would be interesting to explore more valid models as a means of decoding brain activity in the future.

Refernces

Adelson, E. H. (2001, June). On seeing stuff: the perception of materials by humans and machines. In Human vision and electronic imaging VI (Vol. 4299, pp. 1-12). SPIE.

Anderson, B. L., & Kim, J. (2009). Image statistics do not explain the perception of gloss and lightness.

Arcizet, F., Jouffrais, C., & Girard, P. (2008). Natural textures classification in area V4 of the macaque monkey. experimental brain research, 189, 109-120.

Arthur, B. J., Sunayama-Morita, T., Coen, P., Murthy, M., & Stern, D. L. (2013). Multi-channel acoustic recording and automated analysis of Drosophila courtship songs. bmc biology, 11(1), 1-11.

Baker, C. L., & Mareschal, I. (2001). Processing of second-order stimuli in the visual cortex.

Baumgartner, E., Wiebel, C. B., & Gegenfurtner, K. R. (2013). Visual and haptic representations of material properties. multisensory research, 26(5), 429-455.

Baumgartner, E., & Gegenfurtner, K. R. (2016). Image statistics and the representation of material properties in the visual cortex. frontiers in Psychology, 7, 1185.

Benjamini, Y., & Hochberg, Y. (1995). Controlling the false discovery rate: a practical and powerful approach to multiple testing. Methodological), 57(1), 289-300.

Bergen, J. R., & Adelson, E. H. (1988). Early vision and texture perception.

Brouwer, G. J., & Heeger, D. J. (2009). Decoding and reconstructing color from responses in human visual cortex. journal of Neuroscience, 29(44), 13992-14003.

Cant, J. S., & Goodale, M. A. (2007). Attention to form or surface characteristics modulates different regions of the human occipitotemporal cortex. Cerebral Cortex, 17(3), 713-731.

Cant, J. S., Arnott, S. R., & Goodale, M. A. (2009). fMR-adaptation reveals separate processing regions for the perception of form and texture in the human ventral stream. Experimental Brain Research, 192, 391-405.

Cavina-Pratesi, C., Kentridge, R. W., Heywood, C. A., & Milner, A. D. (2010). Separate processing of texture and form in the ventral stream: evidence from FMRI and visual agnosia. Cerebral Cortex, 20(2), 433-446.

Chadwick, A. C., & Kentridge, R. W. (2015). The perception of gloss: A review. vision research, 109, 221-235.

Cox, D. D., & Savoy, R. L. (2003). Functional magnetic resonance imaging (fMRI) "brain reading": detecting and classifying distributed patterns of fMRI Neuroimage, 19(2), 261-270.

Edwards, R., Xiao, D., Keysers, C., Földiák, P., & Perrett, D. (2003). Color sensitivity of cells responsive to complex stimuli in the temporal cortex. journal of neurophysiology, 90(2), 1245-1256.

Epstein, R. A., & Baker, C. I. (2019). Scene perception in the human brain. annual review

of vision science, 5, 373.

Fleming, R. W. (2012). Human perception: Visual heuristics in the perception of glossiness.

Fleming, R. W., Wiebel, C., & Gegenfurtner, K. (2013). Perceptual qualities and material classes. journal of vision, 13(8), 9-9.

Fleming, R. W. (2014). Visual perception of materials and their properties. vision research, 94, 62-75.

Fleming, R. W. (2017). Material perception. annual review of vision science, 3, 365-388.

Freeman, J., & Simoncelli, E. P. (2011). Metamers of the ventral stream. nature neuroscience, 14(9), 1195-1201.

Freeman, J., Ziemba, C. M., Heeger, D. J., Simoncelli, E. P., & Movshon, J. A. (2013). A functional and perceptual signature of the second visual area in primates. nature neuroscience, 16(7), 974-981.

Gatys, L. A., Ecker, A. S., & Bethge, M. (2015). A neural algorithm of artistic style. arXiv preprint arXiv:1508.06576.

Ghebreab, S., Scholte, S., Lamme, V., & Smeulders, A. (2009). A biologically plausible model for rapid natural scene identification. in Advances in Neural Information Processing Systems, 22.

Giesel, M., & Zaidi, Q. (2013). Frequency-based heuristics for material perception. journal of vision, 13(14), 7-7.

Goda, N., Tachibana, A., Okazawa, G., & Komatsu, H. (2014). Representation of the material properties of objects in the visual cortex of nonhuman primates.

Goodfellow, I., Pouget-Abadie, J., Mirza, M., Xu, B., Warde-Farley, D., Ozair, S., et al. (2014). "Generative adversarial nets," in Proceedings of the Advances in Neural Information Processing Systems.

Greene, M. R., & Hansen, B. C. (2020). Disentangling the independent contributions of visual and conceptual features to the spatiotemporal dynamics of scene categorization.

Neuroscience, 40(27), 5283-5299.

Groen, I. I., Ghebreab, S., Prins, H., Lamme, V. A., & Scholte, H. S. (2013). From image statistics to scene gist: evoked neural activity reveals a transition from low-level natural image structure to scene category. Neuroscience, 33(48), 18814-18824.

Hansen, B. C., Jacques, T., Johnson, A. P., & Ellemberg, D. (2011). From spatial frequency contrast to edge preponderance: the differential modulation of early visual evoked potentials by natural scene stimuli. neuroscience, 28(3), 221-237.

Haynes, J. D., & Rees, G. (2005). Predicting the orientation of invisible stimuli from activity in the human primary visual cortex. nature neuroscience, 8(5), 686-691.

Heeger, D. J., & Bergen, J. R. (1995, September). Pyramid-based texture analysis/synthesis. In Proceedings of the 22nd annual conference on Computer graphics and interactive techniques (pp. 229-238).

Hiramatsu, C., Goda, N., & Komatsu, H. (2011). Transformation from image-based to perceptual representation of materials along the human ventral visual pathway. Neuroimage, 57(2), 482-494.

Jacobs, R. H., Baumgartner, E., & Gegenfurtner, K. R. (2014). The representation of material categories in the brain. frontiers in Psychology, 5, 146.

Jagadeesh, A. V., & Gardner, J. L. (2022). Texture-like representation of objects in human visual cortex. Proceedings of the National Academy of Sciences, 119(17), e2115302119.

Kamitani, Y., & Tong, F. (2005). Decoding the visual and subjective contents of the human brain.

Kaneshiro, B., Perreau Guimaraes, M., Kim, H. S., Norcia, A. M., & Suppes, P. (2015). A representational similarity analysis of the dynamics of object processing using single-trial EEG classification. Plos one, 10(8), e0135697.

Kim, J., & Anderson, B. L. (2010). Image statistics and the perception of surface gloss and lightness.

Köteles, K., De Maziere, P. A., Van Hulle, M., Orban, G. A., & Vogels, R. (2008). Coding of images of materials by macaque inferior temporal cortical neurons. European Journal of Neuroscience, 27(2), 466-482.

Krizhevsky, A., Sutskever, I., & Hinton, G. E. (2017). Imagenet classification with deep convolutional neural networks. Communications of the ACM, 60(6), 84-90.

Kutas, M., & Federmeier, K. D. (2000). Electrophysiology reveals semantic memory use in language comprehension. trends in cognitive sciences, 4(12), 463-470.

Kutas, M., & Hillyard, S. A. (1980). Reading senseless sentences: Brain potentials reflect semantic incongruity.

Lawhern, V. J., Solon, A. J., Waytowich, N. R., Gordon, S. M., Hung, C. P., & Lance, B. J. (2018). EEGNet: a compact convolutional neural network for EEG-based brain-computer interfaces. journal of neural engineering, 15(5), 056013.

Marlow, P. J., & Anderson, B. L. (2013). Generative constraints on image cues for perceived gloss. journal of vision, 13(14), 2-2.

Motoyoshi, I., & Matoba, H. (2012). Variability in constancy of the perceived surface reflectance across different illumination statistics. Vision Research, 53(1), 30-39.

Motoyoshi, I., Nishida, S. Y., Sharan, L., & Adelson, E. H. (2007). Image statistics and the perception of surface qualities. Nature, 447(7141), 206-209.

Mudrik, L., Shalgi, S., Lamy, D., & Deouell, L. Y. (2014). Synchronous contextual irregularities affect early scene processing: replication and extension. neuropsychologia, 56, 447-458.

Nagai, T., Matsushima, T., Koida, K., Tani, Y., Kitazaki, M., & Nakauchi, S. (2015). Temporal properties of material categorization and material rating: visual versus non-visual material features. Vision Research, 115, 259-270.

Nishida, S. Y., & Shinya, M. (1998). Use of image-based information in judgments of surface-reflectance properties.

Nishida, S. Y. (2019). Image statistics for material perception.Current Opinion in

Behavioral Sciences, 30, 94-99.

Nishio, A., Goda, N., & Komatsu, H. (2012). Neural selectivity and representation of gloss in the monkey inferior temporal cortex.

Nunez, P. L., & Srinivasan, R. (2006). Electric fields of the brain: the neurophysics of EEG. Oxford University Press, USA.

Okazawa, G., Goda, N., & Komatsu, H. (2012). Selective responses to specular surfaces in the macaque visual cortex revealed by fMRI. neuroimage, 63(3), 1321-1333.

Okazawa, G., Tajima, S., & Komatsu, H. (2015). Image statistics underlying natural texture selectivity of neurons in macaque V4. Proceedings of the National Academy of Sciences, 112(4), E351-E360.

Okazawa, G., Tajima, S., & Komatsu, H. (2017). Gradual development of visual texture-selective properties between macaque areas V2 and V4. Cerebral Cortex, 27(10), 4867-4880.

Orima, T., & Motoyoshi, I. (2021). Analysis and synthesis of natural texture perception from visual evoked potentials.

Orima, T., & Motoyoshi, I. (2023). Spatiotemporal cortical dynamics for rapid scene recognition as revealed by EEG decoding. bioRxiv, 2023-02.

Palazzo, S., Spampinato, C., Kavasidis, I., Giordano, D., & Shah, M. (2017). Generative adversarial networks conditioned by brain signals. in Proceedings of the IEEE international conference on computer vision (pp. 3410-3418).

Palazzo, S., Spampinato, C., Kavasidis, I., Giordano, D., Schmidt, J., & Shah, M. (2020). Decoding brain representations by multimodal learning of neural activity and visual features. Intelligence, 43(11), 3833-3849.

Parkes, L. M., Marsman, J. B. C., Oxley, D. C., Goulermas, J. Y., & Wuerger, S. M. (2009). Multivoxel fMRI analysis of color tuning in the human primary visual cortex. journal of Vision, 9(1), 1-1.

Peelen, M. V., Fei-Fei, L., & Kastner, S. (2009). Neural mechanisms of rapid natural scene

categorization in human visual cortex.

Polich, J., & Criado, J. R. (2006). Neuropsychology and neuropharmacology of P3a and P3b. International Journal of Psychophysiology, 60(2), 172-185.

Portilla, J., & Simoncelli, E. P. (2000). A parametric texture model based on joint statistics of complex wavelet coefficients. International journal of computer vision, 40, 49-70.

Said, C. P., Moore, C. D., Engell, A. D., Todorov, A., & Haxby, J. V. (2010). Distributed representations of dynamic facial expressions in the superior temporal sulcus. journal of vision, 10(5), 11-11.

Sawayama, M., & Nishida, S. Y. (2018). Material and shape perception based on two types of intensity gradient information. ploS computational biology, 14(4), e1006061.

Scholte, H. S., Ghebreab, S., Waldorp, L., Smeulders, A. W., & Lamme, V. A. (2009). Brain responses strongly correlate with Weibull image statistics when processing natural images.

Sharan, L., Li, Y., Motoyoshi, I., Nishida, S. Y., & Adelson, E. H. (2008). Image statistics for surface reflectance perception.

Sharan, L., Rosenholtz, R., & Adelson, E. H. (2014). Accuracy and speed of material categorization in real-world images. journal of vision, 14(9), 12-12.

Shen, G., Dwivedi, K., Majima, K., Horikawa, T., & Kamitani, Y. (2019). End-to-end deep image reconstruction from human brain activity. frontiers in computational neuroscience, 13, 21.

Shen, G., Horikawa, T., Majima, K., & Kamitani, Y. (2019). Deep image reconstruction from human brain activity. ploS computational biology, 15(1), e1006633.

Simonyan, K., & Zisserman, A. (2014). Very deep convolutional networks for large-scale image recognition. arXiv preprint arXiv:1409.1556.

Storrs, K. R., Anderson, B. L., & Fleming, R. W. (2021). Unsupervised learning predicts human perception and misperception of gloss. Nature Human Behaviour, 5(10), 1402-1417.

Sutton, S., Braren, M., Zubin, J., & John, E. R. (1965). Evoked-potential correlates of stimulus uncertainty.Science, 150(3700), 1187-1188.

Wakita, S., Orima, T., & Motoyoshi, I. (2021). Photorealistic reconstruction of visual texture from EEG signals.

Walther, D. B., Caddigan, E., Fei-Fei, L., & Beck, D. M. (2009). Natural scene categories revealed in distributed patterns of activity in the human brain. journal of neuroscience, 29(34), 10573-10581.

Wang, Q., Motoyoshi, I., & Nishida, S. Y. (2013). Characterization of high-level images features for surface gloss perception.

Wiebel, C. B., Valsecchi, M., & Gegenfurtner, K. R. (2013). The speed and accuracy of material recognition in natural images. Attention, Perception, & Psychophysics, 75, 954-966.

Wiebel, C. B., Valsecchi, M., & Gegenfurtner, K. R. (2014). Early differential processing of material images: evidence from ERP classification. journal of vision, 14(7), 10-10.

Wiebel, C. B., Toscani, M., & Gegenfurtner, K. R. (2015). Statistical correlates of perceived gloss in natural images. vision research, 115, 175-187.

Zeiler, M. D., & Fergus, R. (2014). Visualizing and understanding convolutional networks. In Computer Vision-ECCV 2014: 13th European Conference, Zurich, Switzerland,. September 6-12, 2014, Proceedings, Part I 13 (pp. 818-833). Springer International Publishing.

Ziemba, C. M., Perez, R. K., Pai, J., Kelly, J. G., Hallum, L. E., Shooner, C., & Movshon, J. A. (2019). Laminar differences in responses to naturalistic texture in macaque V1 and V2. journal of Neuroscience, 39(49), 9748-9756.

Zipser, K., Lamme, V. A., & Schiller, P. H. (1996). Contextual modulation in primary visual cortex. journal of neuroscience, 16(22), 7376-7389.