1   Cost-benefit Tradeoff Mediates the Rule- to Memory-based Processing Transition
2   during Practice
3

4   Guochun Yang[1,2,*] and Jiefeng Jiang[1,2,3,*]
5
[1] Cognitive Control Collaborative, University of Iowa, Iowa City, IA 52242, USA.
[2] Department of Psychological and Brain Sciences, University of Iowa, Iowa City, IA
52242, USA.
[3] Iowa Neuroscience Institute, University of Iowa, Iowa City, IA 52242, USA.
*Correspondence: guochun-yang@uiowa.edu (G.Y.) and jiefeng-jiang@uiowa.edu
(J.J.)

Abstract
Practice not only improves task performance but also changes task execution from
rule- to memory-based processing by incorporating experiences from practice.
However, *how* and *when* this change occurs is unclear. We test the hypothesis that
strategy transitions in task learning can result from decision-making guided by cost-
benefit analysis. Participants learn two task sequences and are then queried about the
task type at a cued sequence and position. Behavioral improvement with practice can
be accounted for by a computational model implementing cost-benefit analysis, and
the model-predicted strategy transition points align with the observed behavioral
slowing. Model comparisons using behavioral data show that strategy transitions are
better explained by a cost-benefit analysis across alternative strategies rather than
solely on memory strength. Model-guided fMRI findings suggest that the brain
encodes a decision variable reflecting the cost-benefit analysis and that different
strategy representations are double-dissociated. Further analyses reveal that strategy
transitions are associated with activation patterns in the dorsolateral prefrontal cortex
and increased pattern separation in the ventromedial prefrontal cortex. Together, these
findings support cost-benefit analysis as a mechanism of practice-induced strategy
shift.
30
31 **Keywords**: cost-benefit tradeoff; decision-making; practice; task representation;
32 cognitive control; memory retrieval; pattern separation

Introduction

During task learning, practice improves performance and reduces effort. Practice effects occur in multiple cognitive functions supporting task execution. For example, it speeds up the processing of task-relevant information[1,2]. Additionally, with practice, task execution becomes more robust to distraction and requires less attentional control[3,4]. Crucially, practice also changes the strategy used to perform a task. For example, Schuck et al.[5] observed that with practice participants spontaneously shift from a rule-based strategy to a less effortful strategy relying on task-irrelevant information. More generally, strategy switches can occur between two common types of strategies: those based on task rules and those based on experiences[6-9]. For instance, novice chess players must apply the rules to search for the best move, whereas experienced players can leverage their memory of previous games to recognize board configurations, thus reducing the effort of searching and retrieving the best move[10-12]. This transition from rule-based processing to memory-based retrieval is termed automatization and is vital in learning complex tasks (e.g., chess, programming, and arithmetic)[13,14]. However, little is known about *when* and *how* this transition happens.

Logan[13] proposes that the transition from rule- to memory-based processing can be conceptualized as a competition between the two strategies, with the winning strategy determined by which strategy completes the task more efficiently. Early in training, the rule-based strategy tends to dominate. With increased practice, the memory strategy becomes more advantageous and is more likely to prevail. This suggests a transition point after which performance would primarily rely on memory retrieval. A key question concerns the mechanisms underlying this transition. Logan posits that the transition could occur "*either as a consequence of statistical properties of the race or because of a strategic decision to trust memory and abandon the algorithm.*"[13] While Logan and colleagues[13,15] have extensively examined the former possibility, it remains unclear whether the transition can be explained through a decision-making framework. A previous study[5] found that signals in the medial prefrontal cortex (MPFC) predict the strategy transition ahead of time, suggesting the possibility of strategy evaluation and decision-making processes underlying the shift. However, systematic tests of this hypothesis are sparse.

The decision-making literature proposes that the control of goal-directed behavior relies on a cost-benefit analysis between alternative options[16,17]. Similarly, we hypothesize that the transitions in strategy during task performance may also reflect the optimization of a cost-benefit tradeoff. Conceptually, a memory-based strategy retrieves the answer directly and bypasses the execution of the rules. Thus, it is less effortful and less costly than a rule-based strategy. However, the memory-based strategy depends on the accumulation of experience, meaning its benefit is initially low and gradually increases as the memory becomes stronger with practice. In contrast, the benefit of rule-based processing remains consistently high from the outset. Therefore, early in task learning (e.g., a novice chess player), the rule-based strategy is favored because its higher benefit outweighs its higher cost compared to

the memory-based strategy. As more experience is gained (e.g., a veteran chess
player), the increased benefit enables the memory-based strategy to outperform the
rule-based strategy in the cost-benefit tradeoff, leading to a strategy transition from
rule- to memory-based processing. The memory-based strategy remains the winning
strategy afterwards.

In this study, we aim to test the hypothesis that the strategy transition is
determined by comparing values across alternative strategies. We call the model
meeting these criteria the decision-selection model (Fig. 1A, left). Alternatively,
different strategies could be implemented simultaneously without the decision-making
process, which we refer to as the both-active model (Fig. 1A, middle). Another
possible hypothesis is that the decision to use memory-based strategy could be
determined solely by the strength of memories, with the transition occurring whenever
the memories are strong enough to retrieve instances[19], independent of the value
associated with the rule-based strategy. We term this approach the decision-memory-
threshold model. It is important to note that the decision-selection and both-active
models share identical model settings because they predict the same behavioral
patterns but differ in their predictions regarding neural representation (see below).

To test the decision-selection model, we design a two-phase experiment. Human
participants (n = 33) learn two different task sequences (i.e., A and B) involving the
same component tasks (i.e., Helmet, Vest, Glasses, Tool, and Weapon) in the training
phase (Fig. 1B; each task sequence consists of five distinct delayed matching tasks;
see Materials and Methods). In the following test phase, participants are asked to
report the task type at a cued position from one sequence (e.g., A4, denoting the 4th
position in sequence A) while undergoing fMRI scanning (Fig. 1C). As previously
described, the decision-selection model predicts that participants will start with a rule-
based strategy (i.e., by recalling the task sequence learned from the training phase and
identifying the cued task) and switch to the memory-based strategy when the retrieval
of cue-task associations becomes more efficient than sequence recall with practice
(Fig. 1D).

To preview the results, we construct a computational model (M0) to account for
performance by determining the optimal strategy in a way consistent with both the
decision-selection and the both-active models. We find that M0 can successfully fit
the behavioral data and identify transition points marked by a switch cost occurring
after the strategy transition. We also test several alternative models, including nested
models (M1-M5) and extended models (M6-M8), and find that M0 outperforms all
alternative models. Importantly, M0 also outperforms the decision-memory-threshold
model (M9) in accounting for behavioral data. To compare the decision-selection
model with the both-active model, we focus on their different predictions on neural
representations. Specifically, the decision-selection model posits that the brain
encodes a decision variable reflecting the value difference between the rule- and
memory-based strategies, whereas the both-active model does not assume the
existence of such a decision variable. Our fMRI findings support the decision-
selection model over the both-active model.

To gain insights into the neural substrates of the decision-selection model, we
compare the fMRI patterns from trials where the model predicts different strategies
and find that neural patterns show a double dissociation across a broad range of brain
regions. We also analyze fMRI signal changes surrounding strategy transitions and
find that the right dorsolateral prefrontal cortex (dlPFC) encodes the current winning
strategy. Linking the improved memory to strategy transitions, we observe that the
ventromedial PFC (vmPFC) tracks the increase of the memory strength of cue-task
associations. In summary, these findings are consistent with the idea that strategy
selection is driven by a dynamic cost-benefit analysis and that the strategy transition
occurs when the value (i.e., cost-benefit tradeoff) of the memory-based strategy
outweighs that of the rule-based strategy.

Figure. 1. Alternative models and the experimental design. A) Three main
alternative models and how improved memory from practice affects strategy
application. In the decision-selection model, the memory-based strategy replaces the
rule-based strategy when the former provides better value (i.e., cost-benefit tradeoff).
In the both-active model, both strategies are always implemented. In the decision-
memory-threshold model, the strategy switches to memory-based whenever the
memory strength reaches a pre-defined threshold. B) Design of the training phase.
Top panel: During the training phase, participants learn two sequences of tasks (one
example sequence shown) with practice. Each sequence consists of five different tasks
in a fixed order, indicated by a cue (A or B) presented before the first trial of the
corresponding sequence. Each task requires the participant to equip an avatar with a
specific type of gear (e.g., helmet). Bottom panel: A task starts with a goal image and
then two option gears, one on each side of an avatar. Participants are required to
choose the gear that matches the goal image. The goal image is randomized for each
mini-block to ensure that the sequences are defined by equipment types (e.g., weapon)

rather than by specific stimuli (e.g., dagger). C) Design of the test phase. Top panel:
During the test phase, a cue denoting the position from a sequence (e.g., A4, denoting
the 4[th] position in sequence A) is displayed in the center of the screen. Surrounding
the cue are six equipment images denoting five task types plus a foil
(MOUSTACHE), with their spatial locations fixed but the display images randomly
selected within each equipment type. Participants are required to identify the task type
at the cued position of the sequence by selecting the equipment representing the task
type (e.g., nunchaku, representing the weapon task). Bottom panel: trial time course.
D) Illustration of the two strategies. The rule-based strategy recalls the cued sequence
(e.g., A) from the first position till the cued position (e.g., 4), whereas the memory
strategy retrieves the association between the cue (e.g., A4) and the task (e.g.,
weapon) directly.

Results

The results are organized into two parts: The first part compares the decision-selection
model with alternative models (Fig. 2, Table 1). The second part investigates the
neural substrates and their behavioral significance of the key components of the
decision-selection model (Fig. 3-7).

Model-free Behavioral Results

The task involves training and test phases. In the training phase, participants were
trained to learn the transition orders of two sequences (A and B) until they
remembered transitions between tasks with greater than 90% accuracy (see Methods).
In the test phase, they were asked to select the task type of a sequence at a specific
position (e.g., A4, indicating the fourth task of sequence A) within the scanner. For
the test phase data, we conducted a model-free analysis. Since the rule-based strategy
assumes a higher cost for later positions, whereas the memory strategy treats different
cued positions equally, a transition from rule-based to memory-based strategy would
predict a decreasing cost for later positions over time. To test this hypothesis, we
analyzed trial-wise response times (RTs) and error rates (ERs) separately using linear
mixed-effects (LME) models. Predictors included cued position (1–4), block (1–6),
and their interaction. RT results (Fig. 2A) showed a significant main effect of block (β
$= –0.33$, SE $= 0.03$, 95% confidence interval (CI) $= [–0.39\ –0.28]$, $t(33.3) = –11.41$, p
$< .001$, $\eta_p^2 = .40$), a significant main effect of position ($\beta = 0.48$, SE $= 0.05$, 95% CI $=$
$[0.38\ 0.59]$, $t(33.0) = 9.68$, $p < .001$, $\eta_p^2 = .58$), and a significant interaction effect (β
$= –0.10$, SE $= 0.02$, 95% CI $= [–0.14\ –0.07]$, $t(59.8) = –5.73$, $p < .001$, $\eta_p^2 = .06$).
Post-hoc comparisons showed that the linear effect of position in block 1 and 2 was
larger than block 2−6 and 4−6, respectively ($ps < .05$). ER results showed significant
main effects of block ($\beta = –0.20$, SE $= 0.05$, 95% CI $= [–0.29\ –0.10]$, $t(33.0) = –4.17$,
$p < .001$, $\eta_p^2 = .06$), position ($\beta = 0.20$, SE $= 0.05$, 95% CI $= [0.11\ 0.30]$, $t(36.6) =$
4.41, $p < .001$, $\eta_p^2 = .06$), and a significant interaction effect ($\beta = –0.13$, SE $= 0.04$,
95% CI $= [–0.21\ –0.04]$, $t(40.4) = –3.09$, $p = .004$, $\eta_p^2 = .02$). Post-hoc comparisons
showed that the linear effect of position in block 1 was larger than in blocks 3 and 6,

in block 2 compared to blocks 3, 4 and 6, and in block 5 compared to block 6, *p*s <
.05. We also replicated these findings using all five cued positions (Supplementary
Note S1). Note that the slope of block 6 was not completely flat because not all
participants had transitioned to memory strategy by that time. Overall, we observed
three patterns: (1) performance, when collapsed across cued positions, improved over
time; (2) performance, when collapsed across blocks, was worse when the later
sequence positions were cued; and (3) this negative association between performance
and cued position decreased with time.

Figure 2. Behavioral and computational modeling results. A) behavioral data (RT,
left panel, and ER, right panel) and model predicted RT (middle panel) displayed as a
function of cued position and block. Error bars denote standard errors of the mean
(SEMs). B) The structure of the decision-selection model (M0). C) Model comparison
based on the group-level ΔAIC (Akaike information criteria), i.e., increased AIC of
alternative models (see Table 1 and Methods) compared to the winning model (M0,
illustrated in panel B). D) Individual model-estimated parameters (α = learning rate, λ
= cost-benefit tradeoff, γ = recency effect, see definitions in Materials and Methods)
and beta coefficients for rule implementation cost (C) and memory strength (S)
effects. E) Change of model predicted strategy over time. The Y axis shows the
model-inferred proportion of participants using the rule-based strategy. Trials were

counted for each cue separately. F) The RT as a function of trial number relative to
the cue's transition point. The inset highlights the increase of RT on the trial
following the estimated strategy switch. Error bars denote SEMs. G) Post-strategy
switch slowing of real data (dashed red line) and its null distribution (histogram)
estimated using randomly selected transition points.

Model-based Behavioral Results

We constructed several computational models to capture the dynamics of transitioning
from rule- to memory-based strategies (Fig. 2B and Materials and Methods). Our first
model (M0) is a quantitative implementation of the decision-selection model. It
includes three main components: learning, decision, and prediction. The learning
component updates the memory strength of the cue-task associations (i.e., a
probabilistic distribution of the correct task, denoted as M) using a delta rule with
learning rate α. The decision component makes winner-take-all decisions about which
strategy to apply using cost-benefit analyses. The prediction component predicts trial-
wise RT based on linear predictors of values driven by rule- (V_R) or memory-based
(V_M) strategies, depending on the strategy used. The model was fit to trial-wise RT
data to estimate model parameters and trial-wise predictions of the strategy used. On
each trial, the model performs a cost-benefit analysis to determine which strategy to
use based on their values, defined as a weighted sum of cost and benefit.
Conceptually, the rule-based strategy retrieves a task before the cued position (e.g.,
the first task of a sequence) and recalls later tasks using sequential memory until the
cued position is reached. On the other hand, the memory-based strategy directly
retrieves the cued task through cue-task associations. Thus, the rule-based strategy is
more effortful (and thus costly) than the memory strategy. Early in the test phase, the
cue-task association is weak, whereas the participants have strong sequential memory
of the task order from the training phase. Thus, the rule-based strategy provides better
value than the memory strategy due to its higher benefit (despite higher cost) and is
favored. As participants receives feedback with practice, the cue-task association
becomes stronger. Along with its smaller effort compared to the rule-based strategy,
the memory-based strategy eventually achieves a higher value, leading to the strategy
transition (Fig. 1A, left panel).
Based on the trial-wise model prediction of which strategy to use, trials were
categorized as rule-based and memory-based trials. For each participant, the model
outputs were then linked to trial-wise RT using a linear model (M0, Table 1) with the
following regressors: (1) rule implementation cost (C, number of steps from recalling
start to cued position) for rule trials, (2) the strength of the cue-task association (S) for
memory trials, quantified as the reversed entropy of the task distribution conditioned
on the cued position, (3) trial type (i.e., rule trials ($Type_R$) vs. memory trials ($Type_M$)),
(4) the interaction between C and aggregated times of rule implementation since the
beginning of the experiment ($C*Times_R$) reflecting the practice effects of rule
implementation (i.e., more experience would accelerate sequence recall and reduce
the effect of C on RT), (5) log-transformed trial number reflecting practice effect not
involving strategy switch and (6) response (dummy coded). We compared M0 to its

reduced versions (Table 1, M1-M5) using likelihood ratio tests at the group level.
Specifically, M1 assumes behavioral performance doesn't vary across the two trial
types; M2 assumes there is no practice effect of rule implementation; M3 incorporates
both assumptions from M1 and M2; M4 assumes only rule-based strategy has been
implemented throughout the task; and M5 assumes the model uses neither rule-based
nor memory-based strategy. M0 outperformed all other models (ps < 0.001, Fig. 2C).
Of note, M4 and M5 were outperformed by all other models that assume two
strategies (ps < .001), suggesting that both strategies were used. These results suggest
that all components in M0 are important to account for behavior.
We then compared M0 to three extended models, each examining the necessity of
accounting for a specific factor. First, to test whether the behavioral performance
considers the improved efficiency of rule-based strategy (i.e., increased instead of
fixed values) in the cost-benefit analysis, we compared M0 to M6 (Table 1 and
Supplementary Note S2). Comparison between unnested models was achieved
through the Akaike information criteria (AIC). The results showed that M6 (AIC = –
3928) performed worse than M0 (AIC = –4019), p < .001, suggesting no evidence of
such consideration. Second, we explored the possibility of applying a backward
sequence recall strategy with model M7, where recall could start from the last position
and progress backward to the cued position, akin to backward replay. This model
(AIC = –3984, worse than that of M0, p < .001) was not supported by behavioral data
(Table 1 and Supplementary Note S3). Third, we tested whether the cost-benefit
analysis was probabilistic (i.e., strategy can switch back and forth) using M8, which
assumes that both strategies influence trial-level performance in a weighted manner
(see *Methods and Materials*). M8 performed worse (AIC = –3095) than M0 (Table 1,
p < .001), suggesting that only the winning strategy determines behavioral
performance.
Finally, to compare M0 to the decision-memory-threshold model, we developed
another model (M9) without the cost-benefit analysis. This model predicts strategy
switches when the memory strength reaches a threshold, regardless of the value of the
rule-based strategy. However, M9 performed worse (AIC = –3823) than the M0, p
< .001 (Table 1), suggesting that the decision relies on the evaluation and comparison
of alternative strategies.
As M0 was the winning model, it was used for all subsequent analyses. Individual
model parameters from M0 are shown in Fig. 2D. The effect of C was significantly
above 0 (β = 0.33, SE = 0.09, Cohen's d = 0.64, 95% CI = [0.15 0.51], $t(32)$ = 3.70, p
< .001), indicating that participants were slower when the model predicted more steps
to recall. The interaction between the simulation cost and the accumulated rule-based
trials was significant (β = –0.09, SE = 0.04, Cohen's d = –0.38, 95% CI = [–0.18 –
0.01], $t(32)$ = –2.20, p = .035), suggesting that sequence recall accelerated over time.
The memory strength effect (S) was also significant (β = –0.61, SE = 0.17, Cohen's d
= –0.61, 95% CI = [–0.96 –0.26], $t(32)$ = –3.52, p = .001), suggesting that participants
responded faster when the model predicts a stronger cue-task association on memory
trials. Based on this model, the predicted proportion of participants using the rule-
based strategy decreased over time (Fig. 2E), indicating that the rule-based strategy

was replaced by the memory strategy with practice. We defined transition points as
the moments immediately before the trial in which the value of the memory strategy
first surpassed the rule-based strategy (Fig. S2A). Transition points were defined for
each cue except for cues at position 1 because for that position no transition was
necessary. Among the remaining 192 trials for cued positions 2–5, the model
predicted that a participant would apply the rule-based strategy on 94 ± 37 trials,
varying from 21 to 166 trials.

Table 1. Description of tested models and model comparison results.

Model regressors	M0*	M1	M2	M3	M4	M5	M6	M7	M8	M9
C	+	+	+	+	+	−	−	+	+	+
C discounting	−	−	−	−	−	−	+	−	−	−
backward recall	−	−	−	−	−	−	−	+	−	−
S	+	+	+	+	−	−	+	+	+	+
Type (R/M)	+	−	+	−	−	−	+	+	+	+
C_R*$Times_R$	+	+	−	−	+	−	+	+	+	+
Comparison between strategies	+	+	+	+	−	−	+	+	+	−
Probabilistic / **D**eterministic	D	D	D	D	D	D	D	D	P	D
AIC	−4019	−3917	−3959	−3866	−2497	−1878	−3928	−3984	−3095	−3823
Compared with M0 (p value)		< .001	< .001	< .001	< .001	< .001	< .001	< .001	< .001	< .001

Note. The predictors of logged trial number and response were included in all models
and are hence not reported in this table. C = cost of rule implementation (forward
recall); S = memory strength; R = rule trial; M = memory trial; AIC = Akaike
information criteria. Specifically, M0 represents settings of both the decision-
selection and the both-active models, and M9 represents the decision-memory-
threshold model. * denotes the winning model.

Behavioral slowing following model-predicted strategy transition

To validate the transition points predicted by the model, we tested the strategy
switch cost following the transition point[20]. Using an LME model, we observed a
significant increase in RT after transition points ($\beta = 0.40$, SE = 0.15, 95% CI = [0.10
0.69], $t(80.5) = 2.64$, $p = .0010$, $\eta_p^2 = .15$, Fig. 2F). To examine further whether this
effect is reliably linked to the model-predicted transition points, we repeated this
analysis 5,000 times using randomly selected transition points for each cue and each
subject. The observed post-switch slowing was greater than all random ones ($p <$
.001, Fig. 2G). Notably, this effect is independent of the model fitting, which only

assumes that the mean RT for memory and rule trials can be different (i.e., different
intercepts), without any assumptions regarding the two adjacent trials surrounding the
transition point. We further tested the alternative explanation that the structure of the
computational model introduces biases leading to artificially reported post-transition
slowing. To this end, we repeated the post-transition slowing analysis using randomly
sampled model parameters while keeping the architecture of the model constant 5,000
times. The median of the resulting distribution was centered around 0, and
significantly lower than the observed post-switch slowing, $p = .005$ (Fig. S2B), thus
ruling out the possibility that the model artificially introduced a post-switch slowing
effect. The post-transition slowing results suggest that the model accurately predicted
when strategy transition occurs.

Stronger Activation of the Winning Strategy than the Losing Strategy in fMRI Data

As the behavior is not affected by the losing strategy, behavioral analyses cannot test
whether the losing strategy is implemented as posited in the both-active model. On the
other hand, the decision-selection model predicts that fMRI activation patterns
selectively encode the rule- and memory-based strategies for rule and memory trials,
respectively. We conducted fMRI analysis to assess the representational strength of
the two strategies. For the rule-based strategy, we predicted that the similarity of
fMRI activation patterns across two trials would reflect the number of shared recalled
tasks (Fig. 3AB). For the memory-based strategy, we tested the cue effect such that
the two trials' activation patterns will be more similar if they share the same cue than
if they do not, as the cue and its association with the task are used in the memory
strategy (Fig. 3AC).

Figure 3. Coding schemes of representational similarity for rule- and memory-based effects. A) The two task sequences. Letters a-e represent the five tasks. B) The hypothetical representational similarity for the rule effect is quantified as the number of shared recalled tasks between the two trials. For example, cues A4 and B4 share three tasks in rule implementation, namely a, c, and d (red nodes), resulting in a similarity level of 3. C) The hypothetical representational similarity for the cue effect (reflecting the memory strategy) is defined by the concordance of the cues and hence their associated tasks. For example, the cues A4 and B4 are different, thereby yielding a similarity value of 0. The light gray nodes and arrows in panels B and C indicate the tasks that are neither sequentially recalled nor retrieved by the cue.

Results showed widespread brain regions with significant rule effects on rule trials, but not on memory trials (Fig. 4A-B). By contrast, significant cue effects were observed in widespread regions on memory trials but only in limited visual and motor regions on rule trials (Fig. 4D-E). To statistically test the strength of each effect across trial types while controlling for processing shared by both strategies (e.g., visual processing), we compared each effect between rule and memory trials. A stronger rule effect on rule trials compared to memory trials was observed in the striatum, frontoparietal, temporal, and occipital regions (Fig. 4C, ps < 0.05 corrected), whereas a stronger cue effect on memory trials compared to rule trials was found in similar regions with less spatial extent (Fig. 4F, ps < 0.05 corrected). Importantly, no regions showed a statistically significant effect in the opposite direction in either test, suggesting that the representation is likely selective. A conjunction analysis identified a double dissociation between trial type and strategy in frontoparietal, temporal, occipital and subcortical regions (Fig. 4G, see Table S1 for a detailed list of brain regions and statistics). We replicated these findings after regressing out the difficulty of different conditions with a covariate of the RT difference in the regression model (see Fig. S6). The double dissociation showing stronger representations of the winning strategy than the losing strategy suggests that the winning strategy is selectively implemented or prioritized.

Figure 4. Double dissociation of rule and memory representations on their respective trials revealed by multivariate activation patterns. A significant representation of the rule effect is observed on rule (R) trials (panel A) but not on memory (M) trials (panel B). C) A stronger rule effect on rule trials than memory trials (R–M) is found in frontoparietal, temporal, occipital and subcortical regions. In contrast, the cue effect is observed in more regions on memory trials (panel E) than on rule trials (panel D). Regions showing a stronger memory effect on memory than on rule trials (M–R) include frontoparietal, temporal, occipital and subcortical regions (panel F). G) Regions showing double dissociation (i.e., the conjunction of C and F) with both stronger rule effect representations in rule trials and stronger cue effect representations in memory trials. The middle panel illustrates the double dissociation with an example region (left inferior prefrontal sulcus; IFSa). All subcortical regions are depicted in an axial slice at z = 0.

Neural Coding of Key Variables in the Decision-selection Model

We then conducted a multivariate analysis of fMRI data to test the encoding of the key variables of the computational model[21]. A similar analysis using univariate fMRI methods is presented in Supplementary Fig. S3. For the rule-based strategy, we tested the variable of cued position, as later cued position is associated with higher rule implementation cost (e.g., more tasks to sequentially recall, higher difficulty and higher working memory load). We found that this variable was encoded in the left IFSa, $p < .05$, FDR corrected (Fig. 5AD). In contrast, for the memory-based strategy, we tested the encoding of the memory strength of cue-task associations (Eq. 3) and found that memory strength was encoded in primary visual regions (bilateral V1, V2, right V3, right V4), sensorimotor regions (left primary motor area, left lateral 8B,

right area 2), and temporoparietal junction regions (left PF complex, left intraparietal
2, right PFm complex, right medial intraparietal area), among others (left rostral area
6, left auditory 5 complex, right middle TE1 and right dorsal 32), all $ps < .05$, FDR
corrected (Fig. 5BD). In addition, given the importance of the posterior parietal cortex
in memory retrieval[22], we also tested the memory strength effect in bilateral PFm,
PGs, and PGi, and results showed that four of the six regions (bilateral PGs, right
PFm and right PGs) reached significance, $ps < 0.03$, Bonferroni corrected.
To test the presence of the cost-benefit analysis process predicted by the decision-
selection model, we searched for brain regions encoding the decision variable, defined
as the absolute value difference between the two strategies. We expected to observe
this effect in the dorsomedial prefrontal area[16]. Consistently, the right 8BM and the
right supplementary and cingulate eye field (SCEF) showed a significant decision
variable effect, $ps < .05$, FDR corrected. In addition, this effect was also observed in
primary visual regions (bilateral V1-V4), sensorimotor regions (bilateral areas 1, 2,
3b, 4, right 3a, bilateral dorsal area 6, bilateral 24dd, right 7AL), as well as other areas
such as the right anterior area 6, the right anterior part of inferior frontal junction
(IFJa), right PF complex and right A4, $ps < .05$, FDR corrected (Fig. 5CD). The
evidence supporting the encoding of the decision variable also argues against the
both-active model, which assumes that there is no decision-making process to select
the winning strategy prior to the race.

Brain-behavioral Correlation of Memory-based Strategy

We next examined the explanatory power of the decision-selection model by
investigating whether the model-fitting results were linked to the neural findings. The
model fitting yielded a λ parameter that reflects the preference for the memory-based
strategy over the rule-based strategy. A smaller λ value corresponds to a relatively
higher value of the memory-based strategy (see Methods). Therefore, we predicted
that a smaller λ would correlate with stronger encoding of memory strength in the
brain. To test this prediction, we calculated the average memory encoding strength
across regions showing statistically significant representation of memory strength
(Fig. 5B). Our analysis revealed a negative correlation between λ (log-transformed)
and encoding strength, $r = –0.52$, $p = 0.001$, one-tailed, uncorrected (Fig. 3E). This
negative correlation was observed in 3 out of 17 regions (bilateral V1 and left PF), ps
< 0.05, one-tailed, FDR corrected, with the strongest correlation observed in the left
PF, $r = –0.50$, $p = 0.026$, one-tailed, FDR corrected (Fig. 5F). These results suggest
that the extent to which individuals prioritize the memory strategy is related to their
neural sensitivity of memory encoding.

Figure 5. Multivariate encoding of rule-, memory-based strategies and the decision variable. A) The left inferior prefrontal region encodes the cued position, reflecting the cost of rule implementation. B) The memory strength is encoded in the visual, sensorimotor and temporoparietal association regions. C) The decision variable is encoded in sensorimotor and dorsomedial prefrontal regions. D) The encoding strength of three representative regions (highlighted by black ovals in A-C) for the cued position (left), memory strength (middle) and decision variable (right). Each dot represents one subject. E) and F) show a negative correlation between the model prediction of the cost-benefit tradeoff factor (log-transformed λ) and the neural memory encoding strength from those brain regions identified in B) on average (E) and a single region left PF for example (F), respectively.

Our behavioral and modeling results suggest an abrupt shift of strategy when the

value of memory retrieval outweighs the rule implementation (Fig. 2F and Fig. S2A).

We anticipated that there are neural substrates underlying this abrupt shift[5,23], distinct

from the overall differences observed during the constant application of the two

strategies (Fig. 4). Therefore, we next aimed to identify the brain regions supporting

the strategy switch. To this end, we treated a transition point as a boundary separating

the two time periods using different strategies. We then tested the boundary effect

(i.e., higher pattern similarity between trials on the same side of the boundary than

different, termed as "within boundary" and "between boundary" conditions,

respectively). To focus on the effects specific to the boundary, we compared pattern

similarity of the trials immediately adjacent to the transition point with other

temporally close trials (i.e., between 2 and 6 trials away from the transition point). We

excluded trial pairs involving different cues to prevent potential confounding effects

from intrinsic differences across cues (Fig. 4C). We found that the right dorsolateral

PFC (dlPFC region, area p9-46v) showed a statistically significant boundary effect

(Fig. 6, $\beta = 0.0109$, SE = 0.0028, 95% CI = [0.0054 0.0165], $t(1358.0) = 3.86$, $p =$

.023 corrected, $\eta_p^2 = .0116$). No other regions survived the correction for multiple

comparisons. This effect was stronger than its null distribution using shuffled

transition points over 5,000 iterations ($p = .024$, Fig. 6C), suggesting that the

boundary effect is tied to the model-estimated transition points. To further rule out the

possibility that this finding captured a generic trial-type effect (i.e., independent of the

trials' temporal distance from the transition points), we repeated the same analysis by

replacing the temporally close trials with trials that were more than 6 trials away from

the transition point and did not observe the boundary effect ($t(30.7) = 0.84$, $p = .203$

uncorrected). In other words, it appears that this effect only occurred on trials near

strategy transition and hence supports the relation between dlPFC representation and

strategy transition.

Figure 6. Dorsolateral PFC encodes the boundary effect across the transition

point. A) The right p9-46v shows a higher within-boundary than cross-boundary

pattern similarity for trials around the transition points. B) Pattern similarity (group

mean ± SEM) as a function of within/cross-boundary in the region right p9-46v. C)

The significant boundary effect (i.e., the higher pattern similarity within-boundary

than cross-boundary condition, indicated by the red dashed line), compared with a
null distribution obtained by randomly shuffling the transition point 5,000 times.

Ventromedial PFC Pattern-separates Cue-task Associations

As the decision-selection model considers the improvement in memory strength as the
driving factor of the strategy switch, we tested the increase in memory strength by
analyzing the level of pattern-separation[24]. In other words, we predicted that pattern
similarity between different cues would reduce with practice. To focus on strategy
transition, trials were time-locked to their corresponding transition points. Trial
positions containing too few (< 30) data points were excluded from the analysis. The
predicted decrease of between-cue pattern similarity was observed in the left
ventromedial PFC (vmPFC, 10r area, Fig. 7AB, $t(52.4) = -3.93$, $p < .001$, $p = .048$
corrected, $\eta_p^2 = .2279$). No other regions survived the correction for multiple
comparisons. Moreover, to explore the possibility that vmPFC displays a generic
decrease of between-cue pattern similarity over time, we repeated this analysis 5,000
times with randomly selected transition points. These randomized data maintain the
chronological order of trials. The generic decrease hypothesis predicts that the effects
in the repeated analysis will be similar to the observed effect. However, results
showed that the degree of pattern separation observed in the left vmPFC (i.e., the
negative slope β) falls below all values in this distribution, $p < 0.001$ (Fig. 7C). This
rules out a possibility of bias due to a generic temporal effect. Together, the results
suggest that the vmPFC separates neural representations of different cue-task
associations during task learning, potentially strengthening these associative
memories via reducing interference between associations.

Figure 7. Ventromedial PFC pattern-separates cue-task associations. The left 10r
area shows that pattern similarity among different cues decreases over time. A) The
anatomical location. B) A scatter plot of trial similarity as a function of trial number
relative to the transition point and the corresponding fitting lines. Red and blue colors
indicate rule and memory trials, respectively. C) The significant pattern separation
effect (i.e., the negative coefficient, indicated by the red dashed line) compared with a
null distribution obtained by randomly shuffling the transition point 5,000 times.

Discussion

Practice improves task performance not only by making task execution more efficient but also by changing the strategy used to perform the task. Here, we investigated when and how task strategies and related neural representations change in task learning. After learning two task sequences, participants were asked to report the task type at a cued position from one sequence. The behavioral data showed worse performance at later cued positions, suggesting that participants adopted a strategy to recall (via forward replay) the task sequence to obtain an answer. Additionally, the strength of the cued position effect decreased over time, which could be explained by a transition to a memory-based strategy that retrieves the cued task directly from memory (i.e., performance is not sensitive to cued position). To understand *how* and *when* the transition occurs, we incorporated decision-making principles—cost-benefit analysis across strategies and selective strategy implementation—into a decision-selection model. This model accurately predicted transition points, as evidenced by a significant post-transition switch cost (Fig. 2F). Support for the cost-benefit analysis hypothesis also came from the observation that the decision-selection model outperformed a decision-memory-threshold model, which predicts that strategy transition occurs whenever the memory strength of cue-task associations surpasses a certain threshold. We further observed fMRI activation patterns that aligned with a stronger representation of the winning strategy (Fig. 4), consistent with the decision-selection model. Importantly, we observed an encoding of the decision variable (Fig. 5C) that supports the decision-selection model over the both-active model. We then delved into the decision-selection model and found that strategy transition is related to the shift in neural representation in the dlPFC (Fig. 6) and associated with a gradual pattern separation in the vmPFC (Fig. 7).

These findings highlight *when* the transition between rule- and memory-based strategies occurs. Our computational model reconciles the gradual increase in pattern separation in neural data (Fig. 7, also see ref[25]) and the abrupt strategy switch (Fig. 2F, also see ref[5]) by introducing trial-level cost-benefit analysis between the two strategies. In other words, as the cue-task associations strengthen, the cost-benefit tradeoff (i.e., value) for the memory strategy increases gradually and monotonically (Fig. S2A). When it starts to achieve a better cost-benefit tradeoff than rule implementation, subsequent trials will use the memory strategy. The estimated transition points were validated by independent analyses of post-transition slowing (Fig. 2F and S2B) and the boundary effect in the dlPFC (Fig. 6). These model-based findings not only documented a strategy shift in practice-induced automaticity[13], but also provided a new decision-making account of *how* it occurs. Specifically, model comparison results (Table 1) highlight the importance of cost-benefit tradeoffs in the human brain's decision-making process when choosing between alternative strategies[16,26,27]. We further observed that the decision variable of the cost-benefit analysis was encoded in the dmPFC (Fig. 3C). This is consistent with the finding that dmPFC accumulates information prior to the strategy shift[5], indicating that the cost-benefit analysis may provide the information to switch strategy in our study.

Several brain areas seem to represent both strategies (Fig. 4). This may seem
contradictory to the assumption that there are two distinct strategies. We argue that
although the two strategies lead to the response in different ways, they indeed share
some common cognitive processes, such as visual processing of the cue, memory
retrieval and response production. Thus, the same brain regions may be involved in
some processes that support both strategies. Crucially, we showed a double
dissociation in a subset of these regions, such as the frontoparietal regions (Fig. 4G),
where their activation patterns changed with the strategy. This suggests that these
brain regions support the two strategies in different ways. The double dissociation
results are consistent with the decision-selection model. One alternative explanation
to this finding is that the losing strategy was implemented but terminated prematurely
as the other strategy winning the race, leading to weaker representations. Thus, the
double-dissociation patterns in Fig. 4 are not sufficient to rule out the both-active
model. However, we argue that this explanation is not against the conclusion that the
winning strategy is represented more strongly than the losing strategy. More
importantly, the encoding of the decision variable (Fig. 5C-F) endorses the decision-
selection model.
Of note, the recall of tasks from learned sequences suggests that sequential replay
is part of the rule-based strategy[28,29]. To test this hypothesis, we conducted a
multivariate classification analysis to decode tasks that could be replayed (i.e., tasks
prior to the cued task). We found that these tasks could indeed be decoded from
regions such as the left dlPFC, but only in rule trials, not in memory trials.
Additionally, in frontoparietal and visual areas, these tasks could be better decoded in
rule trials compared to memory trials (Supplementary Note S8, Fig. S7), thereby
supporting the assumption of forward replay through the task sequences.
When focusing on behavioral and neural changes related to strategy transition, we
first observed post-transition slowing in behavior (Fig. 2F) and a numerical trend of
increased fMRI activation in the prefrontal cortex following estimated transition
points (Fig. S4). We further found that dlPFC activation patterns were different before
and after strategy transition (Fig. 6). This difference was specific to trials near the
transition point instead of reflecting the difference between the two strategies per se.
This boundary effect may signal the establishment of an event boundary[23,30] that
segments experiences by strategy to reduce interference from the rule-based strategy
after the strategy transition[30]. We speculate that the right dlPFC may encode two
contexts to host cognitive control information to guide the execution of different
strategies. This is in line with our prior work documenting that the right dlPFC
encodes context-specific cognitive control information in a task switching paradigm[31]
and organizes different types of cognitive control information[32].
Pattern separation is a fundamental mechanism for organizing the memories of
multiple similar items[24]. We showed that with practice, the neural pattern similarity
across different cues was gradually reduced (Fig. 7), implying an increasingly
pronounced pattern separation. This finding is in line with recent research illustrating
robust pattern separation over time during the learning process[25]. We identified the
most robust pattern separation in the left ventromedial frontal region[33], underscoring

the significance of the vmPFC in episodic memory[34], pattern separation[35], prospective
memory[36], and concept construction[37].
In conclusion, the present study demonstrates *how* and *when* a transition from a
rule-based to a memory-based strategy occurs during practice to improve performance
and reduce effort. The strategy transition occurs when the value of a memory-based
strategy outweighs that of the rule-based strategy, as determined by a cost-benefit
analysis. This process is characterized by a selective representation of the more
efficient strategy at any given time, which, while optimizing performance, introduces
an event boundary and a cost of transition between different strategy phases. These
findings offer a new decision-making framework for understanding how practice is
associated with neural and behavioral changes.

Acknowledgement

This project was supported by the National Institute of Mental Health (R01MH131559 to J.J.). This work was conducted on an MRI instrument funded by S10RR028821. We thank Tobias Egner, Tammy Tran, Kai Hwang, Jan Wessel, Eliot Hazeltine, Atsushi Kikumoto, the members of the Cognitive Control Collaborative and the members of the Human Perception and Performance Group at the University of Iowa for helpful discussions. We thank Bettina Bustos for helping with editing the manuscript.

Author Contributions

Conceptualization: J.J. and G.Y.; Data curation: G.Y.; Formal Analysis: J.J. and G.Y.; Funding acquisition: J.J.; Investigation: J.J. and G.Y.; Methodology: J.J. and G.Y.; Supervision: J.J.; Writing – original draft: G.Y.; Writing – review & editing: J.J. and G.Y.

Declaration of Interests

The authors declare no competing interests.

Materials and Methods

Subjects

We enrolled 36 participants. Two subjects were excluded due to lower than 70% accuracy in the test phase (see below). One more subject was excluded due to excessive head motion. The final sample consisted of 33 participants (18-42 years old, average of 25.0 ± 6.9 years; 22 females). All participants reported no history of psychiatric or neurological disorders, with normal or corrected-to-normal vision. The experiments were approved by the Institutional Review Board of the University of Iowa (Approval No.: 202001312). Written informed consent was obtained from all subjects prior to the experiment.

Experimental design

Training phase

The purpose of the training phase is to provide the participants with a set of rules (i.e., task sequences) to construct a rule-based strategy. Participants underwent training via an online web-based program to learn task transitions in sequences A (a→b→c→d→e) and B (d→c→a→e→b) (Fig. 4A). They performed multiple 5-trial mini-blocks to equip an avatar with gear based on a goal image (Fig. 1A). Each trial started with a sequence cue, followed by a goal image, a gear selection screen, and

feedback. To facilitate the learning of task transitions, two test trials were
administered after each mini-block, in which participants indicated the 1st/2nd/3rd
task following a cued task (Fig. S1). The training lasted 3-6 blocks and stopped when
participants achieved a block-average accuracy of > 90% on test trials. Participants
underwent the above training between 4-24 hours before scanning and performed
another short repetition (1-2 blocks) immediately before scanning. For a detailed
description, see Supplementary Note S4.

Test phase

In the test phase, the participants performed a new task that can be initially solved
using the rules learned in the training phase. With practice, the task can also be solved
using the memory-based strategy. The test phase was conducted in the scanner. The
stimuli were back-projected onto a screen (with a viewing angle of ~14.0° between
the equipment pictures and the center of the screen) behind the subject and viewed via
a surface mirror mounted onto the head coil. On each trial, a cue with a letter and a
number indicating the sequence and position (e.g., A4) was shown at the center of the
screen (Fig. 1B). Six equipment images, representing the five equipment types and a
foil (MOUSTACHE), were shown around the cue. The images were randomly
selected from the two images of each equipment type. The locations of the six
equipment types were randomized at the subject level but fixed within each subject.
These fixed locations facilitate the implementation of the memory-based strategy.
Participants were asked to select the equipment type representing the cued task with a
pair of button pads, each assigned with three fingers (index, middle, and ring fingers).
The screen proceeded to a fixation for 8s if participants responded correctly or to
feedback for 1s and then a fixation for 7s if an error was made or no response was
received within 9s following the cue. The test phase consisted of 6 blocks of 40 trials
each.

Behavioral analysis

The analysis was centered on test phase data with RT and ER as dependent variables.
For RTs, we excluded the error trials (4.4%), and trials with outlier RTs (> 3 SDs
above the median, 1.5%). We constructed an LME model with the block (1–6),
position (1–4, which enabled the isolation of the clean effect of sequential recall by
excluding position 5—known to involve a recency effect[38]), their interaction, and
intercept as fixed effects. Each slope and the intercept also included a random effect
at the subject level. We used the "AOCTOOL" and "multcompare" functions in
Matlab to compare the slopes of position between different blocks. For all LME
models conducted in this study, we estimated the degree of freedom with the
Satterthwaite approach[39]. For validation purposes, we expanded the analysis to
include positions 1–5 (see Supplementary Note S1).

Computational Model

We built a computational model to simulate how the brain chooses between rule- and
memory-based strategies using cost-benefit analysis. For the cost, the rule-based
strategy has a cost C compared to the memory strategy:

$$C = L_t - i, \tag{1}$$

where L_t is the cued position (e.g., 4 in cue A4), and i is the sequence recall starting
position. For example, when i is 1 and L_t is 4, the cost is 3 as there are 3 task
transitions from position 1 to 4.

We operationalize the benefit as the probability of generating the correct
response. For the rule-based strategy, as the participants have learned the transitions
between steps from the training phase, the benefit depends on the strength of cue-task
association at the starting position of the recall. For the memory strategy, the benefit
relies on the strength of cue-task association at the cued position. Thus, for each
sequence, we modeled the cue-task association using a probabilistic distribution for
each position i on each trial t as $M_{i,t}(j)$, which represents the model's belief that the
task j is at position i. At the beginning of the experiment (i.e., $t = 0$), $M_{i,t}(j)$ was
initialized in the following manner: For position 1, we assumed a perfect memory
from the training phase with a probability of 1 for the correct task. For positions 2–4,
a uniform distribution was used to simulate the situation of no informative cue-task
associations. In position 5, the probability of the correct task received a boost of γ to
account for the recency effect; all other tasks had the same probability. After each
trial, the probability distribution $M_{i,t}$ is updated as a result of learning the correct task
at the cued position using a delta rule:

$$M_{i,t}(j) = \begin{cases} M_{i,t}(j)+\alpha*(1-M_{i,t}(j)), & \text{if } j \text{ is the true task at position } i \\ M_{i,t}(j) - \frac{\alpha*(1-M_{i,t}(j))}{4}, & \text{if } j \text{ is another task} \end{cases}, \tag{2}$$

where α is the learning rate ranging from 0 to 1.

The memory strength index S is quantified as the reversed entropy of $M_{i,t}$:

$$S = -H(M_{i,t}) = \sum_{j=1}^{5} p_j * \log(p_j), \tag{3}$$

Note that a higher S indicates stronger memory strength. Therefore, the quantified
value (i.e., cost-benefit tradeoff) for starting recall at position i is:

$$V_{i,t} = \lambda * S - C = -\lambda * H(M_{i,t}) - (L_t - i), \tag{4}$$

where λ is the tradeoff between cost and benefit, ranging from 0.01 to 100. On trial t
the decision of choosing the best recall starting position i^* is determined by:

$$i^* = \underset{i}{\operatorname{argmax}}\,(V_{i,t}), \tag{5}$$

When i^* is the cued position, memory strategy is implemented as no sequence recall
is needed. When i^* is before the cued position, a rule-based strategy is selected.

Model fitting

We hypothesized that the RT for the rule and memory trials would be influenced by
the rule implementation cost and memory strength, respectively. Therefore, we fit the

model outputs to the RT using a linear regression, which serves as the connection of
the model predictions and behavior:

$\quad$ RT ~ C*Type$_R$ + S*Type$_M$ + Type$_R$ + Type$_M$ + C*Times$_R$ + log(Trial) +

$\hfill$ Response, $\hfill$ (6)

where the Type$_R$ and Type$_M$ encode the factors of rule and memory trials,
respectively, while the C*Times$_R$ encodes the interaction between rule
implementation cost and the aggregated number of recalled steps since the beginning
of the experiment. The Response is a categorical factor encoding the response buttons.
The objective function was defined as the residual sum of squares (RSS) from Eq. 6.
To estimate the free parameters α, λ, and γ, we ran the optimization 100 times (using
fmincon in Matlab) with random starting values and chose the values that led to the
minimum RSS. To determine the best structure of the regression model, we compared
this model to its reduced versions (Table 1) using the likelihood ratio test. The
likelihood of each alternative model was estimated using an LME model
incorporating data and predictors from all subjects. P-values comparing the
unrestricted model (M0) to each of the restricted models (M1–M5) were obtained
through the ratio of likelihood, assessed against a chi-square null distribution, with
degrees of freedom equal to the difference in the number of parameters between the
two models. Comparisons between the alternative models were achieved using either
the likelihood ratio test when they are nested or the Akaike information criterion
(AIC) otherwise. The p value for the AIC comparison was estimated with exp(–
ΔAIC/2) between two models.

$\quad$ To further test whether strategy selection is probabilistic or deterministic, we
refined our model (M8) by incorporating a trial-wise weighting based on the certainty
of the chosen strategy. Specifically, the weight W was calculated using a softmax
function:

$$W = \frac{e^V}{e^{V_R} + e^{V_M}},$$

where V$_R$ and V$_M$ represent the values of rule- and memory-based strategies,
respectively, while V denotes the expected value (either V$_R$ or V$_M$, determined by the
trial type) of each trial. As M8 predicts which strategy to use in a probabilistic
manner, we used the probabilities as observation-level weights to predict RT using the
same regression formula in Eq. 6. The regression analysis predicting behavioral RTs
was conducted with the "lscov" function in Matlab. Other settings are the same as
M0.

$\quad$ The decision-memory-threshold hypothesis was tested with a new model (M9).
Unlike previous models that decide between rule- and memory-based strategies, M9
specifically predicts that a transition to memory-based strategy occurs when its value
exceeds a certain threshold (i.e., without comparing to the rule-based strategy).
Therefore, we introduced a subject-specific free parameter θ (indicating the
threshold), against which we compare the value of the memory-based strategy on each
trial. This comparison determines whether to retain the rule-based strategy or switch
to the memory-based strategy. In addition, we removed the parameter λ from M9, as it

does not involve direct comparisons between the two strategies. All other settings
remain consistent with those of M0.

Behavioral transition point analysis

To estimate the group-level effect of post-strategy switch slowing[20], we conducted an
LME model using the trial type to predict RTs for the last rule and first memory trial.
An intercept was added to capture the average RT. All predictors are treated as both
the fixed effect and random effect at the subject level. Therefore, the model takes the
following form:
$RT = \beta_0 + \beta_1 TrialType + C + S + C*Times_R + \log(Trial) + RandomSlopes + \varepsilon,$ (7)
769

where TrialType encodes either rule or memory trials, and RandomSlopes represents
the random effect for the intercept and the slope of each fixed effect. We also
estimated the null distribution for the post-strategy switch slowing by repeating the
LME analysis using random permutation tests, in which transition points were
shuffled 5,000 times. To test if the model inherently introduces the post-strategy
switch slowing, we ran an additional permutation test by randomizing the model
parameters 5,000 times. The p-value was determined by the percentage of
permutations inconsistent with the null hypothesis (e.g., with stronger or the same
post-switch slowing than the real data in this test).

fMRI Image acquisition and preprocessing

Functional imaging was performed on a 7T GE 950 scanner using echo-planar
imaging (EPI) sensitive to BOLD contrast [in-plane resolution of 1.7×1.7 mm^2, 128
$\times$ 128 matrix, 75 slices with a thickness of 2.0 mm and no interslice skip, repetition
time (TR) of 1000 ms, multiband acceleration factor of 4, echo-time (TE) of 20.5 ms,
and a flip angle of 50°]. In addition, a sagittal T1-weighted anatomical image was
acquired as a structural reference scan, with a total of 512 slices at a thickness of 0.43
mm with no gap and an in-plane resolution of 0.70×0.43 mm^2.
Before preprocessing, the first eight volumes of the functional images were
removed due to the unstable signals. The anatomical and functional data were
preprocessed with the fMRIprep 22.0.2[40] (RRID:SCR_016216), which is based on
Nipype 1.8.5[41] (RRID:SCR_002502). The BOLD time series were resampled to the
MNI152NLin2009cAsym space without smoothing. For a more detailed description
of preprocessing, see Supplementary Note S4. After preprocessing, we resampled the
functional data to a spatial resolution of $2 \times 2 \times 2$ mm^3. The preprocessed data was
smoothed with a full width at half maximum (FWHM) Gaussian kernel of 6 mm and
2 mm for univariate and RSA, respectively. All analyses were conducted in
volumetric space, and surface maps are produced with Connectome Workbench
(https://www.humanconnectome.org/software/connectome-workbench) for display
purposes only.

 Estimation of fMRI activation

A generalized linear model (GLM) was conducted across six sessions (one for each
block), with each session comprising trial-wise regressors time-locked to the onset of
the cue. These regressors were convolved with a canonical hemodynamic response
function (HRF) in SPM 12 (http://www.fil.ion.ucl.ac.uk/spm). We further added
volume-level nuisance regressors, including the six head motion parameters, global
signal, white matter signal, cerebrospinal fluid signal, and outlier TRs (defined as
standard DVARS > 5 or frame-displacement > 0.9 mm from previous TR). Low-
frequency signal drifts were filtered using a cutoff period of 128 s. The GLM yielded
one beta map per trial, which was then noise normalized by dividing the original beta
coefficients by the square root of the covariance matrix of the error terms[42]. The noise
normalization was done separately for each of the 426 ROIs based on the extended
Human Connectome Project multimodal parcellation atlas (HCPex, version 1.1[43]),
resulting in one fMRI activation map for each trial. Error trials, outlier RT trials, and
trials including large head movement volumes were excluded from further analysis.
ROIs containing less than 50 voxels (i.e., 37 subcortical regions) were excluded from
further analyses.

Multivariate regression analyses

We adopted a multivariate regression analysis approach from previous research[21] to
quantify the representational strength of the cued position (representing rule
implementation cost), memory strength, and the decision variable. The decision
variable was operationalized as the absolute value difference (log-transformed) in $V_{i,t}$
(Eq. 4) between the two best values. The analysis was performed separately for each
variable. In each analysis, a variable served as the main predictor, while the other two
variables and the behavioral RT served as nuisance regressors. The analysis was
conducted for each of the 426 ROIs, which underwent a 3-fold cross-validation
procedure, where the data from 6 runs and the trial-wise variable time course were
divided into chronological folds (2 runs per fold). Note that for the cued position
effect, we only included participants who had rule trials in all blocks. For the training
folds, trial-wise fMRI activity levels from each ROI were fitted to the variable time
course using ridge regression[44] to prevent overfitting. The resulting weights were
applied to the fMRI data in the test fold, generating a predicted variable time course.
A stronger linear correlation between predicted and actual variable time courses
indicated a robust representation of the variable in neural data. Following this,
Fisher's transformation was applied to the three correlation coefficients obtained from
each fold, and their mean served as the quantification of representational strength for
the ROI.
For group-level analyses, we conducted a one-sample *t*-test against 0 for each
ROI. Statistical results were corrected for multiple comparisons across all ROIs using
the false discovery rate (FDR) method at the level of $q < 0.05$, with each individual
ROI at uncorrected $p < .001$, both one-tailed (right).

RSA

For each ROI, the representational similarity between trials from different runs was

defined as their voxel-wise correlation coefficient. Trial pairs from the same run were

excluded due to their inflated similarity scores[45,46]. Vectorized representational

similarity data were used as the dependent variable in the LME model analysis. In

addition to fixed effects of interest, we added the intercept and two nuisance fixed

effects encoding ROI-mean activation of each of the two trials to rule out the

influence of activation strength on similarity score. Random effects consisted of the

intercept and the slope for each fixed effect at the subject level. Statistical results were

corrected for multiple comparisons across all the ROIs with FDR at the level of $q <$

0.05, with each individual ROI at uncorrected $p < 0.001$, both one-tailed. For the

detailed LME models, see Supplementary Note S5.

References

1. Fitts, P.M., and Posner, M.I. (1967). Human performance.
2. Anderson, J.R. (1982). Acquisition of cognitive skill. Psychological review *89*, 369-406. 10.1037/0033-295x.89.4.369.
3. Miller, E.K., and Cohen, J.D. (2001). An integrative theory of prefrontal cortex function. Annu Rev Neurosci *24*, 167-202. 10.1146/annurev.neuro.24.1.167.
4. Schneider, W., and Detweiler, M. (1988). A connectionist/control architecture for working memory. In Psychology of learning and motivation, (Elsevier), pp. 53-119.
5. Schuck, N.W., Gaschler, R., Wenke, D., Heinzle, J., Frensch, P.A., Haynes, J.D., and Reverberi, C. (2015). Medial prefrontal cortex predicts internally driven strategy shifts. Neuron *86*, 331-340. 10.1016/j.neuron.2015.03.015.
6. Dolan, Ray J., and Dayan, P. (2013). Goals and Habits in the Brain. Neuron *80*, 312-325. 10.1016/j.neuron.2013.09.007.
7. Evans, J.S., and Stanovich, K.E. (2013). Dual-Process Theories of Higher Cognition: Advancing the Debate. Perspect Psychol Sci *8*, 223-241. 10.1177/1745691612460685.
8. Evans, J.S.B.T. (2008). Dual-Processing Accounts of Reasoning, Judgment, and Social Cognition. Annual review of psychology *59*, 255-278. 10.1146/annurev.psych.59.103006.093629.
9. Kahneman, D. (2011). Thinking, fast and slow (macmillan).
10. Sheridan, H., and Reingold, E.M. (2017). Chess players' eye movements reveal rapid recognition of complex visual patterns: Evidence from a chess-related visual search task. J Vis *17*, 4. 10.1167/17.3.4.
11. van Opheusden, B., Kuperwajs, I., Galbiati, G., Bnaya, Z., Li, Y., and Ma, W.J. (2023). Expertise increases planning depth in human gameplay. Nature *618*, 1000-1005. 10.1038/s41586-023-06124-2.
12. Bilalic, M., Langner, R., Erb, M., and Grodd, W. (2010). Mechanisms and neural basis of object and pattern recognition: a study with chess experts. Journal of experimental psychology. General *139*, 728-742. 10.1037/a0020756.
13. Logan, G.D. (1988). Toward an instance theory of automatization. Psychological review *95*, 492-527. 10.1037/0033-295x.95.4.492.
14. Rickard, T.C. (1997). Bending the power law: A CMPL theory of strategy shifts and the automatization of cognitive skills. Journal of Experimental Psychology: General *126*, 288-311. 10.1037/0096-3445.126.3.288.
15. Compton, B.J., and Logan, G.D. (1991). The transition from algorithm to retrieval in memory-based theories of automaticity. Mem Cognit *19*, 151-158. 10.3758/bf03197111.
16. Shenhav, A., Botvinick, M.M., and Cohen, J.D. (2013). The expected value of control: an integrative theory of anterior cingulate cortex function. Neuron *79*, 217-240. 10.1016/j.neuron.2013.07.007.
17. Musslick, S., and Cohen, J.D. (2021). Rationalizing constraints on the capacity for cognitive control. Trends Cogn Sci *25*, 757-775. 10.1016/j.tics.2021.06.001.

18. Heathcote, A., and Matzke, D. (2022). Winner Takes All! What Are Race
Models, and Why and How Should Psychologists Use Them? Current Directions
in Psychological Science *31*, 383-394. 10.1177/09637214221095852.
19. Siegler, R.S. (1988). Strategy choice procedures and the development of
multiplication skill. Journal of experimental psychology. General *117*, 258-275.
10.1037//0096-3445.117.3.258.
20. Lemaire, P., and Lecacheur, M. (2010). Strategy switch costs in arithmetic
problem solving. Mem Cognit *38*, 322-332. 10.3758/MC.38.3.322.
21. Jiang, J., Wagner, A.D., and Egner, T. (2018). Integrated externally and internally
generated task predictions jointly guide cognitive control in prefrontal cortex.
Elife *7*. 10.7554/eLife.39497.
22. Kuhl, B.A., and Chun, M.M. (2014). Successful remembering elicits event-
specific activity patterns in lateral parietal cortex. J Neurosci *34*, 8051-8060.
10.1523/JNEUROSCI.4328-13.2014.
23. Radvansky, G.A., and Zacks, J.M. (2017). Event Boundaries in Memory and
Cognition. Curr Opin Behav Sci *17*, 133-140. 10.1016/j.cobeha.2017.08.006.
24. Yassa, M.A., and Stark, C.E.L. (2011). Pattern separation in the hippocampus.
Trends Neurosci *34*, 515-525. 10.1016/j.tins.2011.06.006.
25. Mill, R.D., and Cole, M.W. (2023). Neural representation dynamics reveal
computational principles of cognitive task learning. bioRxiv.
10.1101/2023.06.27.546751.
26. Lieder, F., and Griffiths, T.L. (2017). Strategy selection as rational
metareasoning. Psychological review *124*, 762-794. 10.1037/rev0000075.
27. Shenhav, A., Musslick, S., Lieder, F., Kool, W., Griffiths, T.L., Cohen, J.D., and
Botvinick, M.M. (2017). Toward a Rational and Mechanistic Account of Mental
Effort. Annu Rev Neurosci *40*, 99-124. 10.1146/annurev-neuro-072116-031526.
28. Liu, Y., Dolan, R.J., Kurth-Nelson, Z., and Behrens, T.E.J. (2019). Human
Replay Spontaneously Reorganizes Experience. Cell *178*, 640-652 e614.
10.1016/j.cell.2019.06.012.
29. Schuck, N.W., and Niv, Y. (2019). Sequential replay of nonspatial task states in
the human hippocampus. Science *364*. 10.1126/science.aaw5181.
30. Wanjia, G., Favila, S.E., Kim, G., Molitor, R.J., and Kuhl, B.A. (2021). Abrupt
hippocampal remapping signals resolution of memory interference. Nat Commun
12, 4816. 10.1038/s41467-021-25126-0.
31. Jiang, J., Wang, S.F., Guo, W., Fernandez, C., and Wagner, A.D. (2020).
Prefrontal reinstatement of contextual task demand is predicted by separable
hippocampal patterns. Nat Commun *11*, 2053. 10.1038/s41467-020-15928-z.
32. Yang, G., Wu, H., Li, Q., Liu, X., Fu, Z., and Jiang, J. (2024). Dorsolateral
prefrontal activity supports a cognitive space organization of cognitive control.
Elife *12*. 10.7554/eLife.87126.
33. Nash, M.I., Hodges, C.B., Muncy, N.M., and Kirwan, C.B. (2021). Pattern
separation beyond the hippocampus: A high-resolution whole-brain investigation
of mnemonic discrimination in healthy adults. Hippocampus *31*, 408-421.
10.1002/hipo.23299.

34. Euston, D.R., Gruber, A.J., and McNaughton, B.L. (2012). The role of medial
prefrontal cortex in memory and decision making. Neuron *76*, 1057-1070.
10.1016/j.neuron.2012.12.002.
35. Guise, K.G., and Shapiro, M.L. (2017). Medial Prefrontal Cortex Reduces
Memory Interference by Modifying Hippocampal Encoding. Neuron *94*, 183-192
e188. 10.1016/j.neuron.2017.03.011.
36. Brown, T.I., Carr, V.A., LaRocque, K.F., Favila, S.E., Gordon, A.M., Bowles, B.,
Bailenson, J.N., and Wagner, A.D. (2016). Prospective representation of
navigational goals in the human hippocampus. Science *352*, 1323-1326.
10.1126/science.aaf0784.
37. Bowman, C.R., and Zeithamova, D. (2018). Abstract Memory Representations in
the Ventromedial Prefrontal Cortex and Hippocampus Support Concept
Generalization. J Neurosci *38*, 2605-2614. 10.1523/jneurosci.2811-17.2018.
38. Talmi, D., and Goshen-Gottstein, Y.J.M. (2006). The long-term recency effect in
recognition memory. *14*, 424-436.
39. Satterthwaite, F.E. (1946). An Approximate Distribution of Estimates of Variance
Components. Biometrics Bulletin *2*. 10.2307/3002019.
40. Esteban, O., Markiewicz, C.J., Blair, R.W., Moodie, C.A., Isik, A.I., Erramuzpe,
A., Kent, J.D., Goncalves, M., DuPre, E., Snyder, M., et al. (2019). fMRIPrep: a
robust preprocessing pipeline for functional MRI. Nat Methods *16*, 111-+.
10.1038/s41592-018-0235-4.
41. Gorgolewski, K., Burns, C.D., Madison, C., Clark, D., Halchenko, Y.O.,
Waskom, M.L., and Ghosh, S.S. (2011). Nipype: a flexible, lightweight and
extensible neuroimaging data processing framework in python. Frontiers in
neuroinformatics *5*, 13. 10.3389/fninf.2011.00013.
42. Walther, A., Nili, H., Ejaz, N., Alink, A., Kriegeskorte, N., and Diedrichsen, J.
(2016). Reliability of dissimilarity measures for multi-voxel pattern analysis.
NeuroImage *137*, 188-200. 10.1016/j.neuroimage.2015.12.012.
43. Huang, C.C., Rolls, E.T., Feng, J., and Lin, C.P. (2022). An extended Human
Connectome Project multimodal parcellation atlas of the human cortex and
subcortical areas. Brain Struct Funct *227*, 763-778. 10.1007/s00429-021-02421-6.
44. Xue, G., Dong, Q., Chen, C., Lu, Z., Mumford, J.A., and Poldrack, R.A. (2010).
Greater neural pattern similarity across repetitions is associated with better
memory. Science *330*, 97-101. 10.1126/science.1193125.
45. Cai, M.B., Schuck, N.W., Pillow, J.W., and Niv, Y. (2019). Representational
structure or task structure? Bias in neural representational similarity analysis and
a Bayesian method for reducing bias. PLoS Comput Biol *15*, e1006299.
10.1371/journal.pcbi.1006299.
46. Mumford, J.A., Davis, T., and Poldrack, R.A. (2014). The impact of study design
on pattern estimation for single-trial multivariate pattern analysis. Neuroimage
103, 130-138. 10.1016/j.neuroimage.2014.09.026.
981