Tree sequences as a general-purpose tool for population genetic inference

Logan S. Whitehouse[1*], Dylan Ray[1*], and Daniel R. Schrider[1@]

Affiliations: [1]Department of Genetics, University of North Carolina, Chapel Hill, North

Carolina, USA

Address: [1]120 Mason Farm Rd, Chapel Hill, NC 27514

[@]Corresponding author

[*]Contributed equally to this work

E-mail: drs@unc.edu

Running head: Population genetic inference with tree sequences

Keywords: tree sequences, machine learning, population genetics

ABSTRACT

As population genetics data increases in size new methods have been developed to store genetic information in efficient ways, such as tree sequences. These data structures are computationally and storage efficient, but are not interchangeable with existing data structures used for many population genetic inference methodologies such as the use of convolutional neural networks (CNNs) applied to population genetic alignments. To better utilize these new data structures we propose and implement a graph convolutional network (GCN) to directly learn from tree sequence topology and node data, allowing for the use of neural network applications without an intermediate step of converting tree sequences to population genetic alignment format. We then compare our approach to standard CNN approaches on a set of previously defined benchmarking tasks including recombination rate estimation, positive selection detection, introgression detection, and demographic model parameter inference. We show that tree sequences can be directly learned from using a GCN approach and can be used to perform well on these common population genetics inference tasks with accuracies matching or exceeding that of a less efficient CNN-based method. As tree sequences become more widely used in population genetics research we foresee developments and optimizations of this work to provide a foundation for population genetics inference moving forward.

INTRODUCTION

Recent decades have seen dramatic growth in the volume, scale, and diversity of population genetic datasets. This explosion in the amount of data has coincided with the development of an expansive set of statistical methods designed to make more accurate and detailed evolutionary inferences from this glut of data. Initial methods often relied on examining the values of statistics

that summarize relevant aspects of genetic diversity (Watterson 1975; Nei and Li 1979; Tajima

1989; Fu and Li 1993). For example, statistics quantifying information about the presence of

high-frequency derived alleles may be used to identify recent positive selection, which produces

an excess of high-frequency derived alleles via genetic hitchhiking (Fay and Wu 2000). In

addition to statistics that summarize the distribution of allele frequencies in a population,

researchers have designed statistics to capture other properties of genetic variation as well, such

as the density of polymorphism (Nei and Li 1979; Nei and Tajima 1981), patterns of haplotypic

diversity (Hudson *et al.* 1994; Sabeti *et al.* 2002; Voight *et al.* 2006; Garud *et al.* 2015), and the

extent of linkage disequilibrium (Kelly 1997; Kim and Nielsen 2004). Because such summary

statistics necessarily result in the loss of potentially valuable information by representing

population genomic diversity by a single number, more recent approaches, such as approximate

Bayesian computation (ABC) sought to combine multiple summaries into a higher-dimensional

representation of the data that could then be used for inference (Tavare *et al.* 1997; Pritchard *et*

al. 1999; Beaumont *et al.* 2002). ABC methods work by comparing large sets of simulations,

each summarized by a vector of statistics, to identify the evolutionary model and/or parameter

combination that best matches the observed data. Importantly, the summary statistic vector can

capture a variety of properties of genetic variation, that together may be informative about the

evolutionary models/parameters being considered.

More recently, researchers have begun developing supervised machine learning (SML)

methods for population genetic inference (Schrider and Kern 2018; Korfmann *et al.* 2023a).

Unlike traditional applications of supervised learning, these approaches use simulated data to

train and test methods before applying them to empirical datasets. This reliance on simulated

training data makes SML approaches to population genetic inference similar in principle to ABC,

although these methods often have greater accuracy and computational efficiency (Pudlo *et al.*

2016; Raynal *et al.* 2019). SML methods have been applied to a variety of population genetic

tasks including detecting positive selection (Pavlidis *et al.* 2010; Lin *et al.* 2011; Ronen *et al.*

2013; Pybus *et al.* 2015; Kern and Schrider 2018; Mughal and DeGiorgio 2019; Mughal *et al.*

2020; Hejase *et al.* 2022; Whitehouse and Schrider 2022; Arnab *et al.* 2022), demographic

parameter estimation (Sheehan and Song 2016; Wang *et al.* 2021) and model inference (Sanchez

et al. 2021), inferring recombination rates (Gao *et al.* 2016; Adrion *et al.* 2020), detecting

introgression (Schrider *et al.* 2018; Gower *et al.* 2021; Ray *et al.* 2023), and numerous other

applications (Battey *et al.* 2020, 2021; Yelmen *et al.* 2021; Smith *et al.* 2023; Booker *et al.*

2023).

The initial applications of SML to population genetic problems took as their input a

vector of summary statistics, and yielded sizable accuracy gains on several tasks (reviewed in

Schrider and Kern 2018). Because representing genetic diversity within a population by a set of

statistics may still result in valuable information being lost, researchers have more recently

begun to experiment with deep learning methods that are capable of directly examining a

population genetic alignment as input and learning their own set of features to extract from these

data (Chan *et al.* 2018; Flagel *et al.* 2019). Although deep learning has allowed for a multitude of

significant advances in population genetics (reviewed in Korfmann *et al.* 2023a), one important

drawback of this approach is that population genetic alignments are an inefficient format for

representing data (Kelleher *et al.* 2019). Because of the large amount of information that must be

stored in onboard GPU memory, examining large genomic regions or entire chromosomes and/or

large sample sizes is a significant computational challenge for deep learning methods that take

alignments as their input.

One approach to alleviate this issue is to store genetic information as tree sequences: the

sequence along the chromosome of genealogies describing the shared evolutionary history of the

sequenced genomes (Kelleher *et al.* 2016), with adjacent genealogies in this sequence separated

by the breakpoints of recombination events that resulted in a change to the sample's genealogy

(Wiuf and Hein 1999). Tree sequences can be used to concisely store all of the information

present in a population genetic alignment, and this innovation has led to dramatic improvements

in simulation efficiency (Kelleher *et al.* 2018; Haller and Messer 2022). Relatedly, tree

sequences can be used as a hyper-efficient form of lossless compression for population genetic

data (Kelleher *et al.* 2019), and can in principle describe the near-complete evolutionary history

of a sample. These advantages have motivated the development of methods to use sequence data

to infer tree sequences (Kelleher *et al.* 2019; Speidel *et al.* 2019; Zhang *et al.* 2023) or ancestral

recombination graphs (ARGs; Rasmussen *et al.* 2014; Mahmoudi *et al.* 2022), a similar but more

complete representation of a sample's history.

In addition to inferring tree sequences from data, there is growing interest in conducting

inference on the tree sequences themselves. For example, tree sequences have been used to

efficiently compute commonly used summary statistics with dramatic improvements in speed

and memory usage (Ralph *et al.* 2020). Researchers have also begun developing methods using

tree sequences or summaries thereof as input to machine learning methods for evolutionary

inference (Hejase *et al.* 2022; Pearson and Durbin 2023; Korfmann *et al.* 2023b). Given that

when applied to real datasets such methods will be run on tree sequences that are inferred with a

considerable amount of error (Zhang *et al.* 2023) one concern may be that tree-sequence methods

using erroneous input information may produce less satisfactory results than methods directly

acting on the input sequence data. However despite this potential drawback SML methods that

are trained to handle potential errors in their tree-sequence input could potentially circumvent

this problem (Mo and Siepel 2023), resulting in successful use of SML on inferred tree

sequences.

With these potential strengths and weaknesses of tree sequence-based inference in mind,

we sought to assess whether deep learning approaches trained on tree sequences are likely to add

value in comparison to methods acting directly on population genetic alignments. We address

this question by assessing the performance of graph convolutional networks (GCNs), a

generalization of convolutional neural networks (CNNs) to handle graphical input data. We train

GCNs to solve common tasks in population genetic inference: detecting loci that have

experienced introgression between closely related species, identifying selective sweeps,

estimating recombination rates, and inferring demographic parameters (the same tasks examined

previously by Flagel *et al.* (2019)). Encouragingly, we find that GCNs trained to use inferred tree

sequences yield equivalent or better accuracy to those trained on population genetic alignments.

We close with a discussion of the implications of our GCN's performance for future population

genetic research leveraging this increasingly commonly used representation of evolutionary

histories and genetic variation data.

RESULTS

Our goal is to assess the general effectiveness of the approach of performing population genetic

inference from inferred tree sequences. To this end, we evaluate the performance of graph

convolutional networks (GCNs), a type of deep neural network that takes graphical data as its

input, when applied to inferred tree sequences. We gauge the success of GCNs by comparing

their performance to that of CNNs trained on image representations of the input population

genetic alignment data—this comparison is an informative measuring stick given that the CNN-

image approach has been shown to be highly effective on a number of population genetic

problems, as discussed above. We focus our assessment on the four tasks examined by Flagel *et*

al. (2019): estimating historical recombination rates, detecting and classifying selective sweeps,

detecting the presence and directionality of introgression, and inferring demographic parameters.

We begin with an overview of GCNs and how they differ from CNNs as well as their application

to tree sequences before addressing the two approaches' performance on each problem in turn.

Graph convolutional networks on tree sequences

Convolutional neural networks (CNNs) have proved remarkably effective in a variety of fields

(e.g. Hochreiter and Schmidhuber 1997; LeCun *et al.* 1998; Erhan *et al.* 2013; and reviewed in

Gu *et al.* 2018; Li *et al.* 2022), and in recent years have been successfully applied to a number of

problems in population genetics (Korfmann *et al.* 2023a). These networks work by extracting

features from images, or other structured data that can be represented as tensors of two or more

dimensions such as audio or video data, using convolutional filters. By using a series of

convolution filter layers, often combined with pooling layers that downsample the data, CNNs

are able to extract features within the data that are pertinent to the target task. These features are

typically then passed as input into a one or more fully connected layers that then emit the final

prediction: a vector of values corresponding to either to class membership probabilities in the

case of classification (e.g. with each class representing a different possible object present in the

image), or to estimated parameter/attribute values in the case of regression. The convolutional

filters in a CNN, each of which is smaller than the input to which they are applied, work by

striding across the input image and at each step performing a transformation of the portion of the

input image that is currently "covered" by the filter (LeCun *et al.* 1989). The transformed value

is a function of the pixels in the input image and also the values of the weights of the filter

(specifically, the grand sum of the Hadamard product between the filter and the corresponding

portion of the input). The filter then moves to another location of the input and repeats the

process, until a filtered version of the image has been produced. During training, the weights of

the convolutional filters are adjusted to minimize error on the task at hand, thereby producing a

set of filters that are capable of extracting low-level structural features (e.g. edges in an image)

from the input image that are informative for downstream classification/regression by the rest of

the neural network. When multiple layers of convolutions are stacked on top of each other, with

the output from one layer passed to the next, features about higher level structures present in the

input (e.g. shapes in the image) can be extracted.

GCNs work similarly to CNNs in that they extract features from an input using

parameterized filters to convolve over the input space. As the name implies however, rather than

an image or "image-like" data structure GCN input consists of a graph. This graph is represented

as a pair of matrices: 1) an adjacency matrix describing the structure and connectedness of the

nodes in the graph, and 2) a feature matrix containing a vector of attributes for each node in the

graph. When centered on a focal node, convolutions in GCNs incorporate information from each

of its neighbors, with iterative convolutions passing information from further nodes through

information sharing and, in the case of graph attention networks (GATs), attention. GCNs are

thus a generalization of CNNs, with the latter being a special case where each pixel in the input

corresponds to a node within a lattice graph structure. The design of GCNs allows them to learn

from explicit connectedness in a graph to make inferences based on topology and features.

Although a relatively new form of neural networks, GCNs have been shown to have excellent

accuracy on tasks where graph data is relevant and have become a widely-researched type of

neural network (reviewed in Zhou *et al.* 2020), however they have had only limited use in

population genetics applications (Korfmann *et al.* 2023a; b).

Because genealogies are a type of graph, the trees in a tree sequence are a fitting input for

a GCN. However, in order to extract the most information possible for inference the spatial

relationship between trees must be considered as well. To accomplish this we built a hybrid

GCN-RNN architecture to learn both the graph structure of each tree in a sequence as well as the

spatial relationship of trees along a chromosome. Each tree is passed through six graph

convolution layers which extract information from an individual tree in the sequence comprising

of node features (node age, number of mutations, population label; see Methods for more details)

and the connectedness of the graph through adjacency matrix (represented by edge indices).

After graph convolution, we pass the node features through two RNNs (recurrent neural

networks), the first of which compresses the features from each tree into a single feature vector

and the second compresses the features from each sequence of trees into a single vector. This

vector is then used as input to a fully-connected network (MLP) that is used to optimize output

for a given task. This combination of models optimizing for a single task results in an

architecture able to learn both the spatial relatedness of nodes within a tree and their relevance as

well as the larger-scale structured information of the tree sequence as a whole. This architecture

is displayed in Figure 1.

Figure 1. Overview of the GCN architecture. A) Each tree in the input tree sequence contains *n* nodes each summarized by *f* features, and is thus represented by an $n \times f$ node feature matrix per-tree, which is affine-transformed in the "node embedding" layer of the neural network (Table 1). B) For each tree, the affine-transformed node feature matrix is concatenated to a vector of edge indices specifying the tree topology, and also to the original feature matrix (i.e. a "skip connection"). This concatenated matrix is then input to multiple graph convolutional layers with skip connections. C) For each tree, the features from graph convolution layers are then fed as input to a GRU, resulting in a compressed, learned vector representation of the tree and its

features. D) These compressed vector representations are concatenated to a "tree summary
vector" that encodes summaries of the size and shape of the tree, as well as the size and location
of the chromosomal segment corresponding to the tree. The resulting vectors for all trees are then
concatenated together into one matrix corresponding to the entire tree sequence, and passed
through another GRU layer that produces a flattened vector representation of the entire tree
sequence. E) This vector is then concatenated to a "tree-sequence summary vector" containing
information about the distribution of values in the original tree summary vectors and the number
of trees in the original sequence (which may be less than the padded length of this vector). This
vector is then passed through multiple fully-connected layers culminating in a final output layer
tailored to the target task. Throughout the diagram, solid lines with arrows show the flow of
information through layers that transform the input, while dashed lines with arrows show the
flow of information that has been unaltered by any preceding layers in the network.
219

GCNs can leverage tree-sequence data to accurately estimate recombination rates

Estimating historical recombination rates is a deeply important task to population genetics as the

recombination rate modulates key evolutionary processes and also affects our ability to make

inferences about these processes. For example, when considering the effects of selection, the

recombination rate between loci influences the degree of selective interference between them

(Hill and Robertson 1966). Moreover, in the case of positive selection, the signatures of selection

are much more difficult to detect in the presence of high rates of recombination due to the rapid

exchange of alleles, which dampens the hitchhiking effect by preserving more genetic diversity

in the vicinity of the selected site (Shriner *et al.* 2003). Because the recombination rate has a

direct influence on the correlation between alleles in a sample of genomes, population genomic

data can in principle be used to get an accurate estimate of the recombination rate landscape

across the genome (Hudson 2001; Auton and McVean 2007; Chan *et al.* 2012; Gao *et al.* 2016;

Adrion *et al.* 2020).

235
236 **Figure 2. Predicted versus true recombination rates for the (A) CNN and (B) GCN**
237 **architectures.** Predictions are plotted against a reference diagonal dashed line, and each panel
238 shows the root mean squared error (RMSE) and coefficient of determination (R^2) for the given
239 method
240

To assess the utility of tree-sequence based recombination rate inference, we trained our

GCN for this task and compared its performance to the CNN previously shown by Flagel *et al.*

(2019) to accurately estimate recombination rates. Specifically, we simulated data using the same

parameter values as in Flagel *et al.* (2019)) to generate samples of phased chromosomes which

we used to estimate the crossover rate per base pair per meiosis by either passing these data

directly into a CNN or through a tree-sequence inference procedure before passing the resulting

trees into the GCN. In the context of tree sequences, recombination plays a very direct role in the

structure of the data: most recombination events will alter the tree topology, and thus the number

of trees in the tree sequence minus 1 is equal to the number of historical recombination events

that could possibly be observed. However, because *inferred* tree sequences will contain errors, it

is not clear whether we should expect methods that examine information from inferred tree

sequences to estimate recombination to be more accurate than methods that directly examine the

haplotype data. As shown in Figure 2, our GCN using tree sequences performed slightly better

than our CNN (RMSE = 5.54E-03 compared to RMSE = 6.01E-03) that takes the population

genetic alignment as input. Thus, the presence of error in inferred tree sequences does not

preclude the accurate inference of recombination rates from such data.

GCNs dramatically outperform CNNs in detecting selective sweeps

The ability to detect loci affected by positive selection is a longstanding problem in population

genetics (Stephan 2019). Selective sweeps occur when positive selection affecting an allele

causes it to rapidly increase in frequency in a population, creating a valley of diversity that

recovers at increasing genetic distances from the selected site (Smith and Haigh 1974; Kaplan *et*

al. 1989). Sweeps also produce an excess of high-frequency derived alleles (Fay and Wu 2000),

a deficit of haplotypic diversity (Hudson *et al.* 1994; Fay and Wu 2000; Sabeti *et al.* 2002), and

elevated linkage disequilibrium (Kelly 1997; Kim and Nielsen 2004) near the target of selection.

Recently, there has been great interest in characterizing and detecting the signatures of "soft

sweeps" (Hermisson and Pennings 2017) which may be common in large, rapidly evolving

populations (Hermisson and Pennings 2005; Karasov *et al.* 2010; Garud *et al.* 2015), and which

produce somewhat different signatures than classic "hard" sweeps (Przeworski *et al.* 2005; Berg

and Coop 2015). Recently, a number of machine learning methods have been designed to detect

the multidimensional signatures of both of these types of sweeps (Pybus *et al.* 2015; Schrider and

Kern 2016; Mughal and DeGiorgio 2019; Hejase *et al.* 2022; Whitehouse and Schrider 2022,

2023; Caldas *et al.* 2022; Lauterbur *et al.* 2022).

However, it should be noted that the presence of all of these signatures of selection is a

side effect of the profound effect that positive selection has on genealogies in the genomic

vicinity of the selected locus. The shapes and sizes of trees are affected by selection in that the

genealogies of loci near the selected site have a very short branches, especially internal branches,

while genealogies at intermediate distances from the sweeping allele may have a subset of long

branches as a consequence of recombination during the sweep (Fay and Wu 2000; Przeworski *et*

al. 2005; Stephan 2019). Moreover, because of the reduced time period for historical

recombination events to occur during the sweep, trees near the selected locus will correspond to

a larger stretch of sequence than those from more distant loci that have experienced more

recombination (Sabeti *et al.* 2002; Przeworski *et al.* 2005; Ferrer-Admetlla *et al.* 2014;

DeGiorgio and Szpiech 2022). Thus, tree sequences may provide a great deal of information

about recent positive selection.

To assess the potential of GCNs for detecting sweeps, we used the same simulated

benchmarking scenario as Flagel *et al.* (2019), and trained our networks to classify regions as

undergoing a recent hard selective sweep (from a *de novo* mutation), being linked to a recent

hard sweep, undergoing a soft sweep (from standing variation), being linked to a soft sweep, or

evolving neutrally. Specifically, we simulated data under the JPT model from Schrider and Kern

(2017) to generate training, testing, and validation sets as described in the Methods. We find that

the GCN architecture outperforms the CNN for all classes except neutrality, where their

performance is equal (Figure 3). Indeed, the GCN obtains an average increase of 6.4% of test

samples assigned to the proper class (the confusion matrix diagonal) relative to the CNN (65.5%

accuracy for the GCN vs 58.8% for the CNN). Perhaps more strikingly, the GCN exhibits a

sizable increase relative to the CNN in the area under the receiver operating characteristic (ROC)

curve (AUROC) and in average precision (AP, equal to the area under the precision-recall curve)

for distinguishing sweeps from neutrality (difference in AUROC of 0.085 and difference in AP

of 0.151; Figure 4A, B). The increase in accuracy is less notable for distinguishing between hard

and soft sweeps, with an AUROC increase of 0.004 and AP increase of 0.007 for the GCN

compared to the CNN (Figure 4C, D).

302
303
304

Figure 3. Confusion matrices showing performance of the CNN architecture and GCN architecture on the sweep detection task. A) Confusion matrix summarizing the CNN's performance on a held-out test set. For this problem, there are five classes specifying the type of sweep (hard versus soft), whether a focal window is impacted by direct selection within the window or linked selection outside of the window (sweep vs. linked), or neutrally evolving. Each entry in the matrix shows the fraction of simulated examples under a given class (the True Class, specified by the row of the matrix) that were assigned to a given class by the network (the Predicted Class, specified by the column of the matrix). Diagonal entries thus represent correct classifications, and errors are represented in the off-diagonal entries, and each row sums to 1. B) Confusion matrix summarizing the GCN's performance on the same test set.

Figure 4. Receiver operating characteristic (ROC) and precision-recall (PR) curves
summarizing performance of the CNN (blue) and GCN (orange) on the sweep-detection
task. (A) ROC curves showing how well each method distinguishes between selective sweeps
(whether hard or soft) and unselected regions (whether sweep-linked or neutral). The curves
show the true and false positive rates for the CNN (blue) and GCN (orange) at varying
classification thresholds. The score used to classify a window as a sweep vs. unselected at a
given threshold was the sum of the neural network's class membership probabilities for the "hard
sweep" and "soft sweep" classes to yield a combined "sweep" probability. The area under the
ROC curve (AUC) for each network is shown in the inset. B) Precision-recall curves showing the
two network's performance on the same "sweep vs. unselected" task, here showing the precision
(i.e. the positive predictive value, or fraction of regions classified as sweeps that truly were
sweeps) and recall (the true positive rate) at varying classification thresholds. The average

precision (AP, which is equal to the area under the PR curve) is shown in the inset. C) ROC
curves for distinguishing between hard and soft sweeps, with hard sweeps treated as positives
and soft sweeps as negatives for this binary classification task. D) Precision-recall curves for the
"hard vs. soft" task.

**Figure 5. Confusion matrices showing the neural network's accuracies on the introgression
inference task.** Confusion matrices are shown in the same manner as for Figure 3, but here the
three classes are introgression from *Drosophila simulans* to *D. sechellia*, introgression from *D.
sechellia* to *D. simulans*, and no introgression. A) Confusion matrix for the CNN. B) Confusion
matrix for the GCN.

GCNs perform similarly to CNNs on the task of detecting introgression

A variety of approaches have therefore been developed to identify the signatures of introgression

between pairs of closely related species (Hudson *et al.* 1992; Huson *et al.* 2005; Rosenzweig *et
al.* 2016), including several machine learning methods (Schrider *et al.* 2018; Gower *et al.* 2021;

Ray *et al.* 2023). Previously, Flagel et al. (2019) showed that a CNN substantially outperforms

FILET, a supervised machine learning method that detects introgression between closely related

347   species with impressive accuracy (Schrider et al. 2018). Here we compared the performance of

Figure 6. Receiver operating characteristic (ROC) and precision-recall (PR) curves for the
introgression detection task. A) ROC curves summarizing the performance of the CNN (blue)
and GCN (orange) on the task of distinguishing between windows with introgression (in either
direction) and without introgression. The area under the ROC curve (AUC) for each network is
shown in the inset. B) Precision-recall curves for the task of distinguishing between windows
with and without introgression. The average precision (AP, which is equal to the area under the
PR curve) is shown in the inset. C) ROC curves for the task of distinguishing between
introgression from *D. simulans* to *D. sechellia* and introgression from *D. sechellia* to *D.*
simulans. D) Precision-recall curves for the task of inferring the direction of introgression.

the tree-sequence based GCN to our CNN on simulated data modeling gene flow between

Drosophila simulans and *Drosophila sechellia* (see Methods for details). We find that both

networks perform well (Figures 5,6), but as is the case for the other tasks the GCN outperforms

the CNN (86.2% accuracy for the GCN versus 85.1% for the CNN). The overall error profile is

very similar for the two architectures (Figure 5) indicating that the GCN's improvement over the

CNN is not due to any specific class, but rather due to slight accuracy increases (1–2%) across

all three classes. The GCN has an AUROC increase of 0.004 and AP increase of 0.002 when

measuring accuracy distinguishing between genomic windows with and without introgression,

and an increase in AUROC of 0.004 and AP of 0.007 when inferring the direction of

introgression (Figure 6).

GCNs show improvement compared to CNNs on a demographic inference task

Perhaps one of the most widely studied tasks in population genetics is the inference of

demographic models and their associated parameters from. Many statistical approaches have

been developed to allow researchers to estimate a population's history of size changes, splitting

and merging events, and expansions and contractions (Gutenkunst *et al.* 2009, 2010; Li and

Durbin 2011; Browning and Browning 2015; Terhorst *et al.* 2017; Kamm *et al.* 2020; Santiago *et*

al. 2020; Excoffier *et al.* 2021) These include several deep learning methods that have been

designed in recent years (Sanchez *et al.* 2021; Wang *et al.* 2021), one of which applies graph

convolutions to the tree sequence for inference (Korfmann *et al.* 2023b). To compare the

performance of our GCN to the CNN on a demographic inference task, we reexamined the 3-

epoch model presented in Flagel *et al.* (2019). We simulated data under this model and assessed

each network's accuracy in estimating its 5 parameters: the population sizes in each of the 3

epochs, and the 2 transition times between these epochs.

We found that the GCN architecture outperforms the CNN on all estimations except the

ancestral population size (N_2) where the two methods perform equally as measured by both root

mean squared error (RMSE) and the coefficient of determination (R^2) on test data (Figure 7).

With respect to population size inference, the difference in accuracy between the GCN and CNN

was most pronounced for the present-day population size (N_0; improvement in RMSE and R^2 of

0.046 and 0.048, respectively, for the GCN over the CNN), with the middle epoch's population

size inference (N_1) showing smaller differences in accuracy (difference in RMSE and R^2 of 0.026

and 0.045, respectively), and again no difference between the two methods for the ancestral size.

For the inferred times of population size changes, we again observed greater difference in

accuracy for the inferred time of the most recent event (T_1; difference in RMSE and R^2 of 0.067

and 0.069, respectively) than for the inferred time of the more ancient size change (T_2; difference

in RMSE and R^2 of 0.043 and 0.047). This improvement in accuracy is somewhat modest

(average RMSE decrease of 0.055 and average R^2 decrease of 0.058 across all parameters), and

we remind the reader that this test case involves the inference of demographic parameters from a

single genomic region as a proof of concept rather than examining genome-wide data as is

typically done in practice. Nonetheless, these results demonstrate the GCN's ability to examine

inferred tree sequences and extract information relevant to past demographic events at least as

well as a CNN directly examining the population genetic alignment.

Figure 7. Performance of the CNN and GCN on the task of demographic parameter estimation on a held-out test set. The top row shows the predicted versus true values for the CNN (panel A) and GCN (panel B) for the present-day population size N_0, and subsequent rows show the same for the time of the most recent population size change (T_1, panels C and D), the second population size (N_1, panels E and F), the time of the more ancient population size change (T_2, panels G and H), and the ancestral population size (N_2, panels C and D). Each panel also shows the root mean squared error (RMSE) and coefficient of determination (R^2) for the given method on the given parameter. Values are log-scaled for visual clarity and plotted against a reference diagonal dashed line.

Performance and computational efficiency

Perhaps the most enticing attribute of tree sequences is that they can provide extremely compact representations of population genomic data (Kelleher *et al.* 2019), leading to the possibility that they can be leveraged to reduce the computational burden of evolutionary inference pipelines. We therefore compared the computational cost of our GCN and CNN on the problems examined above. With respect to

preprocessing, our GCN's pipeline has an advantage over our CNN pipeline in that tree

sequences are relatively fast to infer compared to the sorting and matching steps that we perform

on alignments before passing them into the CNN. For instance, computing Relate outputs for

1000 simulated replicates of length 10 kb from the introgression case took on average ~ 5

minutes for a single CPU core vs. ~ 21 minutes to seriate and match the same number replicates.

In terms of memory efficiency, the size of a single replicate of from the introgression data set

after the tree-sequence inference step was 3.25 times the size of the original simulations (Tables

2, 3). Similar trends are observed for the recombination and demography problems. For sweep

detection, the GCN requires slightly less memory than the CNN, but this is a consequence of our

downsampling of the tree sequence for the GCN (Methods), while the CNN examines the entire

input alignment.

Training time is also an important consideration when choosing deep learning

architecture. We note that our CNN, due to the smaller input sizes and the greater efficiency of

image convolutions over graph convolutions with current hardware and software, are faster to

train and usually require less RAM (Tables 1, 2). This is in spite of the fact that our choice of

CNN has almost 2 orders of magnitude more learnable parameters than our proposed GCN

architecture (21,280,965 vs. 228,837 respectively). However, we find both approaches to be

accomplishable on consumer-grade hardware, i.e. on a single GPU with ~ 12 Gb of RAM.

Table 1: GPU training and approximate RAM usage for the GCN architecture. All training times are reported for a single NVIDIA A100 GPU. RAM estimates were obtained via *nvidia-smi* while training was running. For the GCN, batch size in terms of number of input trees varies stochastically due to the variable tree sequence length.

Problem	Time	RAM (1 batch)	RAM (1 replicate)	Batch size	Total epochs
Recombination rate	5.5 hrs	8.7 Gb	145 Mb	60	28
Introgression	12.4 hrs	8.3 Gb	231 Mb	36	43
Sweeps	24.6 hrs	10.7 Gb	535 Mb	20	67
Demography	14.5 hrs	8.4 Gb	280 Mb	30	100

Table 2: GPU training and approximate RAM usage for the CNN architecture. All training times are reported for a single NVIDIA A100 GPU.

Problem	Time	RAM (1 batch)	RAM (1 replicate)	Batch size	Total epochs
Recombination rate	0.86 hrs	3.07 Gb	51 Mb	60	18
Introgression	0.66 hrs	3.4 Gb	71 Mb	48	13
Sweeps	7.1 hrs	24.2 Gb	605 Mb	40	18
Demography	0.85 hrs	3.5 Gb	109 Mb	32	23

DISCUSSION

The size and quantity of population genetic datasets are increasingly large, making downstream

analysis more computationally intensive. As researchers develop new, more compact data

structures for population genetics, new methods must be developed to fully take advantage of

these structures' potential to tackle long standing problems in the field with greater

computational efficiency and perhaps better accuracy as well. Tree sequences have become

increasingly popular, both in the context of estimation from empirical data and in simulation

(Kelleher *et al.* 2018; Haller *et al.* 2019; Ralph *et al.* 2020). However, there has yet to be a

fundamental shift in population genetics inference approaches away from less efficient data

structures (Korfmann *et al.* 2023a). In principle, tree sequences have a key advantage over

genotype information in that they can represent the complete evolutionary history of a sample of

genome sequences, making them an attractive avenue for downstream evolutionary inference.

Several previous studies have presented deep learning approaches for analyzing tree-

sequence data, with initial methods using predefined sets of features summarizing the properties

of trees in the sequence that are then fed into a neural network (Hejase *et al.* 2022; Mo and

Siepel 2023; Pearson and Durbin 2023). While these approaches showed great promise, because

they examine summaries of the trees rather than the tree itself, they could potentially omit

valuable information present in the tree sequence. Just as deep learning-based methods operating

directly on genotype/haplotype matrices are able to extract more useful information than vectors

of statistics designed to summarize aspects of a sample of genotypes/haplotypes (e.g. allele

frequencies, linkage disequilibrium) (Kern and Schrider 2018; Flagel *et al.* 2019), graph neural

networks operating directly on tree sequences may perform better than methods using predefined

tree summaries (e.g. the number of lineages present in the tree within each of a set of non-

overlapping time intervals (Hejase *et al.* 2022)). Indeed, this approach was used successfully by

(Korfmann *et al.* 2023b). for demographic inference. Here, we adopt a similar strategy, using a

GCN to show that tree sequence-based inference appears to be at least as powerful of a

framework for evolutionary inference as deep neural networks acting directly on a population

genetic alignment.

The main caveat with using tree sequences is that in empirical data the true evolutionary

history of a sample can never be known, and therefore tree sequences must be estimated from

genotypes (Kelleher *et al.* 2019; Mahmoudi *et al.* 2022). As it stands, inference methods can

produce highly inaccurate tree sequences when benchmarked on simulated data (Zhang *et al.*

2023), suggesting that using tree sequences as input for further inferences may be problematic.

Moreover, the paradigm of inferring a population sample's tree sequence to use as input for a

downstream inference task does on the face of it appear to be unnecessarily complicated, and

appears to violate the following imperative from Vapnik: "When solving a problem of interest,

do not solve a more general problem as an intermediate step" (Vapnik 2006). For example, if we

wish to infer whether a given locus has experienced a selective sweep, it may not be desirable to

first infer the full evolutionary history of every segment of DNA along a large stretch of

chromosome surrounding this locus, as this would clearly be a more challenging task than

directly searching for evidence of recent positive selection.

Why then, might tree sequence-based inference still be generally highly effective, as our

results seem to suggest? First, it seems probable that incorrect tree sequences contain information

that, although incorrectly describing the true evolutionary history of a sample, can be useful for

population genetic inference. In addition, tree sequences allow for a more concise representation

of population genetic data than a genotype matrix. Moreover, tree sequence inference may serve

as a form of de-noising by aggregating data across sites in a region in order to extract a

meaningful pattern that may not be easily observable directly from sequence data (especially in

the presence of sequencing error), even if that pattern does not describe the true evolutionary

history. In any case, supervised machine learning methods combined with tree sequences can be

especially powerful because one can train the machine learning model on tree sequences that are

inferred from simulated data (as we have done here), rather than the true tree sequences, so that

the training tree sequences may exhibit a similar error profile as tree sequences inferred from real

data. In this framework, it does not matter whether the tree sequences are correct, but only that

they contain information useful for the task at hand. Moreover, the impact of any remaining

fundamental differences between tree sequences from simulated vs. real data could potentially be

mitigated via the machine learning technique of domain adaptation (Ganin and Lempitsky 2015),

wherein a network can be trained to learn to ignore systematic differences between simulated and

real data before downstream prediction (Mo and Siepel 2023). Thus, in spite of the somewhat

unusual workflow, relying on inferred tree sequences as input to supervised machine learning

methods may in fact prove to be an especially powerful and robust strategy.

We note that although we have provided an attempt at solving multiple population

genetics inference tasks the number supervised machine learning approaches to population

genetics has ballooned in recent years such as detecting selective sweeps (Kern and Schrider

2018; Hejase *et al.* 2022; Whitehouse and Schrider 2023), detecting introgression (Schrider *et al.*

2018; Gower *et al.* 2021; Ray *et al.* 2023), predicting locations of recombination (Adrion *et al.*

2020) among others (reviewed in Schrider and Kern 2018; Flagel *et al.* 2019; Korfmann *et al.*

2023a). The encouraging benchmarking results from our GCN suggest that machine learning

methods using tree sequences will likely prove to be a powerful addition to this ever-growing

suite of tools and tasks.

One important limitation of our work is that, although our networks were able to be

trained and executed on consumer-grade hardware, we have not made exhaustive attempts to

improve computational efficiency. Indeed, we find that our CNN is more efficient than the GCN

in terms of both memory usage and training time, with the current advantage of the GCN being

its faster preprocessing time. However, the latter is a consequence of our choice to sort our

alignments in order to improve performance, a computationally expensive process (Ray *et al.*

2023) and it is important to note that the cost of this step will depend on the sorting algorithm

used and the size and number of alignments to be sorted. Moreover, at least some problems,

exchangeable neural networks that do not require any sorting may be used (Chan *et al.* 2018).

However, we note that the advantage in compactness afforded by tree sequences is not observed

at small sample sizes (Kelleher *et al.* 2019), and the tasks examined here all used small to modest

sample sizes. Thus, our conclusions about the relative efficiency of GCNs vs. CNNs may not

hold for tasks requiring much larger samples. Further investigations into optimizations of both

architecture and processing algorithms may increase the favorability of the GCN in all aspects.

future efforts experimenting with more compact tree representations (Kelleher *et al.* 2018, 2019;

Haller *et al.* 2019; Ralph *et al.* 2020; Mahmoudi *et al.* 2022) and different neural network

architectures may yield improvements in this area.

Finally, we note that we have only explored a relatively small number of population

genetic inference tasks that are of particularly broad interest to researchers. We therefore

encourage exploration of tree sequence-based deep learning inference as a general framework for

population genetic inference. Our hope is that this may not only lead to improved accuracy on

the problems examined here, but that tree sequence-deep learning paradigm may prove useful for

a wider array of problems and, as has proved to be the case for alignment-based deep learning

applications, even empower researchers to tackle new problems (Battey *et al.* 2021; Yelmen *et*

al. 2021; Korfmann *et al.* 2023a; Smith *et al.* 2023; Booker *et al.* 2023; Whitehouse and Schrider

2023).

METHODS

Tree sequence inference

For each problem, simulations were performed as described in the sections below, producing *ms-*

style output. The simulation output was then formatted for input to *RELATE* (Speidel *et al.*

2019), a recently developed method that, when given a sample of genomes along with estimate

of the mutation rate, recombination rate, and effective population size, infers the sample's

genome-wide genealogy in the form of a sequence of rooted binary trees. *RELATE* outputs this

sequence of trees in order along the chromosome, with each tree spanning a variable length of

sequence bounded by the breakpoints of inferred historical recombination events that altered the

tree topology. This was done for each simulation replicate for each problem described below,

using the mutation, recombination rate and effective population size parameters listed in Table

S1.

Overview of Graph Convolutional Networks (GCNs)

Graph convolution (Kipf and Welling 2017) works by aggregating information at each node in a

graph by combining data from its neighbors (those nodes with which it shares an edge). The

input to a graph convolution operator is a graph or a set of nodes and edges (N, E), where each

$x \in N$ is some n-dimensional vector containing information about a given node, and each

element of E is a pair of node indices representing a connection between those two nodes. The

edges of a graph are often specified instead by an adjacency matrix $\mathbf{A}$ which specifies the

topology of the graph: i.e. $\mathbf{A}$ has a value of 1 at entry ij if node i and node j share an edge and a

value of 0 otherwise. Formally the graph convolution can be written in matrix form as:

$$\mathbf{X}' = \hat{\mathbf{D}}^{-1/2}\hat{\mathbf{A}}\hat{\mathbf{D}}^{-1/2}\mathbf{X}\mathbf{\Theta} \quad (1)$$

where $\mathbf{X}$ is a matrix consisting of the n node feature vectors $\hat{\mathbf{A}} = \mathbf{A} + \mathbf{I}$ with I as the identity

matrix and $\hat{D}_{ii} = \sum_{j=0} \hat{A}_{ij}$ as the diagonal degree matrix. Here features are first aggregated

according to the connectivity specified in $\mathbf{A}$ including the features belonging to the node itself

(hence the addition of the identity matrix specifying self-connectivity, a "self-loop") and then

normalized using the degree matrix to avoid exploding gradients. Then, they are transformed

according to some learnable matrix Θ that is optimized through gradient descent during training.

For clarity, the node-wise formula is:

$$\mathbf{x}_i' = \Theta^\top \sum_{j \in \mathcal{N}(i) \cup \{i\}} \frac{1}{\sqrt{\hat{d}_j \hat{d}_i}} \mathbf{x}_j \quad (2)$$

where the degree of node (including self-connectivity) i is $\hat{d}_i = 1 + |\mathcal{N}(i)|$, with $\mathcal{N}(i)$ being

the set of neighbors of node i, and x_i being the node features for node i. Thus, in each graph

convolution step, each node's features are updated to the weighted sum of all its neighbors

features including its own (i.e. the features of the set of nodes *, as specified in the summation).,

Specifically, where each contribution of each node j's feature vector is weighted by the

reciprocal of the square root of the product of node *'sits degree and node i's degree and the

degree of its neighbor, as in the denominator of Equation 2. Then, that resulting sum is

transformed according to the learnable matrix Θ. This is called a "convolution" on graphs as it is

analogous to convolutions on images where the "kernel" of a graph convolution operates over

each local neighborhood of each node much like an image convolution kernel operates on some

rectangular region around each pixel (see example in Figure S1).

In the case of genealogical trees, the node features returned by each graph convolution

operation are a function of those of its parent and its two children if it is an internal node, its two

children only if it is the root node, and its parent only if it is a leaf node. For our input graphs we

used the following features: the age of a node (the time in generations that the coalescence event

associated with it occurred, or 0 for leaf nodes), the number of mutations on the branch from its

parent (mean and standard deviation normalized via the training data), and a one-hot encoded

label vector specifying whether the node is internal (i.e. ancestral) or external (present day)

respectively, and the population label if the node is external (for internal nodes the population is

considered unknown). Thus, if there are k populations the size of the label vector is $k + 1$. Note

that the definition of graph convolution allows for directionality of the edges, i.e. one can specify

whether node i passes information to node j in each graph convolution operation or vice-versa.

Here we specify that the edges are unidirectional with the direction being child to parent. Thus,

for our GCN $\mathcal{N}(i)$ is the set of child nodes of node i., Fand no update is performed for external

nodes in the tree $\mathcal{N}(i)$ is the empty set, and thus for those nodes $\mathcal{N}(i) \cup \{i\} = \{i\}$, meaning

only the focal node is considered during the convolution.

GCN Network Architecture and training

The GCN architecture implemented here (illustrated in Fig. 1) consists of two components: a

graph-learning network, or layers that operate on graphs, and two recurrent networks that operate

on sequences of feature vectors. First, each tree in the input sequence has its node features

transformed via a learned affine transform with bias, to which the original features are

concatenated to via a "skip connection" before each tree is then input separately to a series of

independent graph convolution layers with skip connections, comprising a graph convolution

"block" of layers. At each layer, the output from the previous layer is transformed via

convolution and added to itself, then the result is normalized and passed to the ReLU activation

function (Agarap 2018). For normalization in the GCN layers we use LayerNorm (Ba *et al.*

2016). The graph convolution layer we chose for our architecture is the Graph Attention

Convolution (GATConv) from (Brody *et al.* 2022) implemented in Pytorch (Paszke *et al.* 2019).

It is a modified form of the proposed convolution operator that we detail in the previous section

in that node features from each neighbor are linearly transformed *before* they are summed in the

update step and are weighted by learned attention coefficients instead of simply the degree of the

nodes, enabling the network to potentially learn which neighbor's features are more or less

relevant for accomplishing the given regression task. In short, weighting by node degrees as

described in the previous section prevents gradient explosion whereas weighting by attention

prevents gradient explosion *and* has the benefit of learning the most optimally-informative

connections in the graph for a given task (Brody *et al.* 2022). Formally the convolution with

attention is specified as:

$$\mathbf{x}'_i = \alpha_{i,i}\mathbf{\Theta}_s\mathbf{x}_i + \sum_{j \in \mathcal{N}(i)} \alpha_{i,j}\mathbf{\Theta}_t\mathbf{x}_j \ (3)$$

641   Where the attention coefficients α are computed as:

$$\alpha_{i,j} = \frac{\exp\left(\mathbf{a}^\top \mathrm{LeakyReLU}\left(\mathbf{\Theta}_s\mathbf{x}_i + \mathbf{\Theta}_t\mathbf{x}_j\right)\right)}{\sum_{k \in \mathcal{N}(i) \cup \{i\}} \exp\left(\mathbf{a}^\top \mathrm{LeakyReLU}\left(\mathbf{\Theta}_s\mathbf{x}_i + \mathbf{\Theta}_t\mathbf{x}_k\right)\right)} \ (4).$$

With $\mathbf{a} \in \mathbb{R}^d$ and $\mathbf{\Theta}s, \mathbf{\Theta}_t \in \mathbb{R}^{d' \times d}$ being learnable parameters weighted during training where

d and d' are the dimension of the input features and output features respectively and R^d being a d-

dimensional vector of real numbers. In each GATConv layer, attention coefficients $\alpha_{i,j}$ are

computed which selectively filter messages from neighboring nodes. This attention mechanism

is comprised of the same two learnable affine transformation matrices used in eq. 5, $\mathbf{\Theta}_s$ and $\mathbf{\Theta}_t$,

which transform the focal node and its neighbor's node features respectively and $\mathbf{a}$ being a

trainable weight vector onto which the summed features are projected via the dot product and

then normalized over all neighbors to sum to one using the softmax function. In this way, the

attention mechanism hopes to weight the messages from neighboring nodes with $\alpha_{i,j}$ such that

returned features have the most impact on loss reduction for a given target. Note that self-

attention coefficients expressing how much the focal node's own features contribute to the

features in the next layer ($\alpha_{i,i}$) are also computed in a similar manner.

After passing through the GATConv layers, features obtained from the nodes in each tree

are separately passed through a Gated Recurrent Unit (GRU; (Cho *et al.* 2014)) and the hidden

features are returned as the compressed vector representation of each tree in the sequence. For

each GRU's input, the order of nodes in the tree is the same order that is returned by RELATE in

Newick format. The vector emitted by each GRU is concatenated to a "tree summary vector"

containing the following features about the original tree: the time of coalescence of all

individuals in the tree, the mean, median, and standard deviation of coalescence times, the mean,

median, standard deviation, skew, and maximum of the branch lengths in the tree, the midpoint

of the chromosomal segment the tree corresponds to (scaled from 0 to 1, with 0 being the left end

of the simulated chromosome and 1 being the right end), and the fraction of the entire sequence

accounted for by this segment. The resulting vectors, one for each input tree, are then

concatenated into a single matrix, which is in turn passed through another GRU that emits a

feature vector summarizing the entire tree sequence. A global vector (the "tree sequence

summary vector") which consists of the mean, standard deviation, and median of the tree

summary vectors, as well as the number of graphs in the original sequence, is embedded using an

affine transform with bias and then concatenated to the resulting hidden vector from the previous

GRU, resulting in a 1D vector containing learned information from the graph convolution

process and summary statistics about the tree sequence as a whole. Each global vector and pre-

computed tree summary vector for the graphs is mean and standard deviation normalized via the

training data set in preprocessing. Finally, this is passed through three fully connected layers (a

multi-layer perceptron, "MLP") with the first two using ReLU activations and batch

normalization (Ioffe and Szegedy 2015), and the final (output) layer using no activation function.

This results in classification scores which could be interpreted as posterior probabilities by

applying the softmax function, or in the case of regression, z-scores for the various values to be

predicted (all y values for the regression tasks are standardized via the mean and standard

deviation computed from the training set). We provide a table specifying the dimensionality of

the inputs and outputs in each layer of our network as well as the activations used for clarity

(Table 1).

When passing the ragged sequences to the final GRU layer they are each padded to the

maximum length observed in the given batch. For all the experiments however, we first

downsample the tree sequences if they are > 128 trees in length by randomly selecting a

sequential window of 128 trees and omitting the others. This cap on tree sequence lengths

allowed us to increase the batch size while still being able to train using a single GPU. For some

tasks, namely in the case of recombination rate and demographic parameter regression, this is far

more than the average number of trees observed in the chosen window size and thus most tree

sequences are passed in full to the network. However, in the case of the sweep detection

problem, there are often far more than 128 trees in the tree sequence, and thus many of the

replicates passed to the network are downsampled sequences. Further details of how we

downsample the tree sequences and the average amount of downsampling are given in the

sections detailing each task.

For classification tasks, we used categorical cross entropy as our loss function to be

minimized during training:

$$\frac{1}{N} \sum_{i=1}^{N} \sum_{c=1}^{M} y_{i,c} \log y_{i,c} \tag{5}$$

Where $y_{i,c}$ is a binary indicator of the correct class and $y_{i,c}$ is our posterior probability estimate

that the observation came from this class where i is the replicate index, c is the class index, M is

the number of classes, and N is the batch size or number of replicates considered in each

gradient step. For regression tasks, we use a variant of L1 loss (i.e. mean absolute error (MAE))

because of L1's relative insensitivity to outliers; specifically, we used the "smooth L1" loss

function, whose slope decays at values closer to zero (Girshick 2015). However, note that for all

methods and tasks we report final regression accuracies in root mean-squared error (RMSE) to

better compare to Flagel et al. (2019). y values for the regression tasks are standardized via the

mean and standard deviation computed from the training set. We trained using the ADAM

optimizer (Kingma and Ba 2017) with a learning rate of 1e-4 for up to 100 epochs or until their

validation accuracy stopped increasing for 10 consecutive epochs. For each problem we specify

the batch size in the sections below.

Table 3: Graph neural network layers and their input/output shapes and activation

functions.

B = number of tree sequences per batch (batch size)
T = number of trees in a single sequence
T' = maximum number of trees in a sequence in a given batch, used for padding
N = number of nodes in a single tree

$T{\times}N$ = matrix of trees × nodes comprising all nodes in a single tree sequence (i.e. the number of nodes across all trees in a single sequence)

F = number of node features calculated for each node in the input tree sequence

E = number of edges in all graphs included in the batch of tree sequences

M = the size of the output (the number of classes for classification, or 1 for regression)

$(..., n)$ = number of features

E.g. A shape of $(B, T{\times}N, 4)$ is equivalent to a 3D matrix consisting of a batch (B) of 4 features

layer	type	input shape(s)	output shape	activation
node embedding	Linear	$(B, T{\times}N, F)$	$(B, T{\times}N, 26)$	none
skip	concatenation	$(B, T{\times}N, F)$, $(B, T{\times}N, 26)$	$(B, T{\times}N, 26+F)$	none
graph convolutions (x6)	GATv2Conv (Veličković *et al.* 2018)	$(2, E)$, $(B, T{\times}N, 26+F)$	$(B, T{\times}N, 26+F)$	ReLU
skip	concatenation	$(B, T{\times}N, F)$, $(B, T{\times}N, 26+F)$	$(B, T{\times}N, 26+2F)$	none
reshape		$(B, T{\times}N, 26+2F)$	$(B, T, N, 26+2F)$	none
RNN	GRU (1-layer, unidirectional)	$(B, T, N, 26+2F)$	$(B, T, 256)$	none
tree-level statistics	concatenation	$(B, T, 12)$, $(B, T, 256)$	$(B, T, 268)$	none
reshape and pad sequences		$(B, T, 268)$	$(B, T', 268)$	none
RNN	GRU (1-layer, unidirectional)	$(B, T', 268)$	$(B, 256)$	none
tree-sequence-level (global) statistics	concatenation	$(B, 37)$, $(B, 256)$	$(B, 293)$	none
MLP (x2)	Fully-Connected	$(B, 293)$	$(B, 256)$	ReLU

| output | Fully-Connected | $(B, 256)$ | (B, M) | none |

Because input tree sequences are of variable length, here we define the dimensionality of a single

batch as $(B, T \times N)$ where B is the batch size (number of tree sequences in a batch) and $T \times N$ is the

number of trees × the number of nodes. For each node, we calculate a set of F features, giving us

an input shape of $(B, T \times N, F)$ as shown in the "input shape" column for the first layer Table 3

(the "node embedding" row). The inputs to the graph convolution layers are a 2-D tensor of

shape $(T \times N, 26+F)$, where $T \times N$ is again the total number of nodes in the tree sequence, and 26

features per node resulting from concatenated with the original node features from the first skip

connection), and a list of edge indices of shape $(2, E)$ specifying the pairwise connections

between nodes where each row is a pair of node indices the edge connects, similar to an

adjacency matrix this information is used by the graph convolution layers to utilize the node

connectedness. The input and output shapes of the skip connection layer, reshaping layer, and

first GRU layer that follow the graph convolution layers are also determined by T, N, and F as

shown in Table 1. When considering the input to the second GRU layer, T' refers to the padded

tree sequence length, which is the maximum observed number of trees among the B tree

sequences in a given batch. This padding is performed because all tree sequences in a given

batch must have the same length, and we chose to increase the length of tree sequences to T' by

concatenating tensors filled with zeros to the end of the GRU's input tensor rather than

downsampling the tree sequence by removing trees. Note that this padding was done using

PyTorch's `pack_padded_sequence` function that allows for more efficient computation by

allowing T' to vary across batches rather than setting it to the maximum length across all batches

and instructing the GRUs to ignore the padded part of the sequence during forward and

backward computations (Paszke *et al.* 2019). This is followed by another concatenation layer and

then several fully connected layers culminating in the output layer. The input and output shapes

for all of these are shown in Table 1. All benchmark tasks except the introgression-detection

task use identical output shapes for all layers except the final output layer, which is task-

dependent. In total, the chosen architecture has 228,837 parameters for the demography and

positive selection problems, 229,771 parameters for the introgression classification problem, and

228,381 parameters for the recombination rate problem.

CNN training

The CNN used for comparison was the Pytorch (Paszke *et al.* 2019) implementation of the

ResNet34 architecture (He *et al.* 2015). ResNets are a type of CNN that feature skip or residual

connections that merge output from the convolutions with the output from previous layers via

addition, and have been shown to perform competitively on traditional image recognition tasks

(Reddi *et al.* 2020). The model architecture is illustrated in Figure S2. Models were trained for

up to 100 epochs or until their validation accuracy stopped increasing for 10 consecutive epochs.

For classification tasks (selection detection, introgression detection) categorical cross entropy

loss was used, while smooth L1 (Girshick 2015) loss was used for regression tasks (rho

estimation, demographic inference). The ADAM optimizer with default settings (lr=0.001,

betas=(0.9, 0.999)) (Kingma and Ba 2017) was used for all networks. All genotype matrix inputs

were formatted to be of shape (populations, individuals, polymorphisms) and were padded with

zeros to the max observed number of polymorphisms in each case. The rows were sorted based

on cosine distance using seriation as described in (Ray *et al.* 2023) using Googles OR-tools

package (Perron and Furnon 2019); note that the sorting algorithm and similarity metric differ

from that used by (Flagel *et al.* 2019) as we found the seriation approach to perform better on the

task of identifying introgressed haplotypes (Ray *et al.* 2023). Data was represented as binary

encoding of 0 or 1 (ancestral or derived) for all tasks.

The batch size for the CNN for both regression cases was 32. The batch size for the

selection problem was 10 as the padded size was very large at 5000 SNPs. The batch size for the

introgression problem was 96. The CNN used for comparison was the ResNet34 architecture (He

et al. 2015) which was implemented in PyTorch. ResNets are a type of CNN that feature skip or

residual connections that merge output from the convolutions with the output from previous

layers via addition, and have been shown to perform competitively on traditional image

recognition tasks.

Test Cases

Inferring the historical recombination rate

Simulations for training and benchmarking performance on recombination rate inference were

done using *ms* (Hudson 2002) with the same simulation commands used by Flagel *et al.* (2019);

these commands are available at

https://raw.githubusercontent.com/flag0010/pop_gen_cnn/master/historical_recombination/phase

d/run.ms.sh. In particular, for each simulation replicate a population size N was drawn from the

set {5000, 10,000, 20,000, 50,000}, and, after setting the locus size to L=50 kb and the mutation

rate to μ=1.5×10^{-8}, a recombination rate ρ=4NrL was chosen such that the per-base pair crossover

rate, r, was drawn from a truncated exponential distribution with lower and upper boundaries of

10^{-8} and 10^{-6}, respectively. The sample size was set to 50 haploid chromosomes. Simulation and

formatting resulted in 189,528 replicates for training the CNN, and 9,956 for its validation.

Recombination rates values were log-scaled and then standardized to a z-score using the

training set mean and standard deviation. Note that the validation and test data were also

standardized using the training set's mean and standard deviation to prevent data leakage from

the training to the validation/test data. Because the number of segregating sites differed across

simulation replicates, the data was padded to 376 polymorphisms or the maximum observed

number of polymorphisms in the simulated replicates. The median number of trees returned by

RELATE (computed from training data) was 13 with a standard deviation of 24.05. For the

GCN, the training and validation sets had 174,575 and 18,625 replicates respectively. The test

set used to compare the two approaches had 9,715 replicates.

Detecting selective sweeps

We benchmarked accuracy on the task of detecting selective sweeps by adopting the approach of

(Schrider and Kern 2016; Flagel *et al.* 2019) in that we define the problem as a classification task

with 5 classes: hard sweeps (a sweep of a *de novo* mutation), hard-linked regions (i.e. those close

to a hard sweep), soft sweeps (selection on standing variation), soft-linked regions (close to a

soft sweep), and neutrally evolving regions. Sweeps were simulated using *discoal* (Kern and

Schrider 2016) with the same simulation parameters used by Schrider and Kern (2017) to

generate training and test data for the JPT sample (Japanese individuals from Tokyo) from Phase

3 of the 1000 Genomes dataset (Auton *et al.* 2015).

For the hard and soft sweep classes, the target of selection was located at the center of the

simulated chromosome. For the sweep-linked classes the target of selection was located outside

of the central "sub-window" (which accounts for 1/11 of the total length of the selected

chromosome). For this task we consider a simulated example to be a sweep if the central

polymorphism in the sampled window is the target of selection. Sweep-linked classes are defined

as having a sweeping allele in the sampled window but not in the center, while the neutral class

does not have any selection in the simulation.

For sweep scenarios we condition on the sweeping allele having reached at time $\tau \sim U(0,$

$2000)$ generations ago. The sample size was set to 104 haploid individuals. Genotype matrices

were either padded or cropped to 5000 polymorphisms. The training, validation, and test sets for

the CNN had 236,232, 26,432, and 22,480 replicates respectively.

For the tree sequences, sequences containing more than 128 trees were downsampled as

in the other problems, but instead of sequential window sampling we sampled trees by setting

the probability that a tree was sampled by the fraction of the chromosome that it spanned, and

then sampling with replacement while keeping the original ordering intact. This was done

because a large proportion of simulations had >> 128 trees in sequence (the median length across

the five categories was 107 with standard deviation of 111.2) and non-linked replicates can have

selection almost anywhere along the simulated chromosome, thus contiguous window sampling

could often miss the relevant signal. The training, validation, and test sets for the GCN had

224,555, 25,445, and 22,480 replicates respectively, with the latter being the same test set used

to assess performance of the CNN. The training, validation and testing data were evenly

balanced across the five categories.

Detecting introgressed loci

We used the *Drosophila* simulations generated for (Ray *et al.* 2023) as data for a 3-class

classifier problem to benchmark each networks' ability to detect the presence and direction of

introgression within a genomic region. In brief, we simulated a pulse migration event from *D.*

simulans to *D. sechellia* at a random time sampled from $U(0.3, 0.5) \times T$, where T is the

population split time inferred by bootstrapped ∂a∂i (Gutenkunst *et al.* 2010) replicate inferences

on *D. simulans* inbred and *D. sechellia* wild-caught genomes. In contrast to the parameterization

simulated by Ray et al. (2023) which used more recent introgression events, we chose the

introgression time distribution to be $U(0.3, 0.5) \times T$ to make the problem a more difficult

benchmark (because older introgression events have introgressed haplotypes that are less

diverged between the donor and recipient population, and also that have had more time to be

broken up by recombination events after the introgression event).

For this task genotype matrices are formatted in the shape of (*samples*, *populations*, *individuals*,

polymorphisms). Data was padded to 665 polymorphisms or the maximum observed number of

polymorphisms in simulated replicates. The median number of trees returned by RELATE

(computed from training data) was 68 with a standard deviation of 11.56. For the GCN, the

training and validation sets had 232,050 and 25,950 replicates respectively. For the CNN, the

training and validation sets had 244,740 and 13,260 replicates respectively. The test set used to

compare the methods contained 12,900 replicates, and the training, validation, and test sets were

all class-balanced.

Demographic inference

As in Flagel *et al.* (2019) we tested the ability of our networks to perform demographic inference

by simulating a 3-epoch demographic model with 5 parameters: the present-day population size

(N_0 which was drawn from $U(100, 4\times10^4)$), the time of the most recent population size change

($T_1 \sim U(100, 3500)$), the population size during the middle epoch ($N_1 \sim U(100, 5000)$), the time of

the ancient population size change (T_2, which was set to T_1 plus a value drawn from $U(1, 3500)$),

and the ancestral population size ($N_2 \sim U(100, 2\times10^4)$). These data were simulated using *ms* and

the corresponding scripts can be found at

https://github.com/flag0010/pop_gen_cnn/tree/master/demography. For the CNN, the training /

validation had 94,036 and 5,164 replicates respectively.

The data was padded to 652 polymorphisms or the maximum observed number of

polymorphisms in the simulated replicates. Target values were log-scaled and standardized prior

to training and testing, with the validation and testing data being standardized according to the

mean and standard deviation of the log-scaled training data. For the GCN, the training and

validation sets had 82,820 and 9,168 replicates respectively. The median number of trees in

sequence was 53 with a standard deviation of 37.0. The test set used to compare the two

methods contained 3,995.

DATA AND CODE AVAILABILITY

All code associated with this work can be found at

https://github.com/SchriderLab/TreeSeqPopGenInference. Model weights can be downloaded

from

https://drive.google.com/drive/folders/1WRf8pecfRavOQjmZF7Otr4lXbcouVunm?usp=sharing

.

ACKNOWLEDGMENTS

The authors thank Will Booker for comments on the manuscript, and members of the Kern and

Ralph Labs for feedback on preliminary data. LSW was supported by NIH award R01AI153523,

DDR was supported by NIH award R01HG010774, and DRS was supported by NIH award

R35GM138286.

REFERENCES

Adrion J. R., J. G. Galloway, and A. D. Kern, 2020 Predicting the Landscape of Recombination

Using Deep Learning. Mol. Biol. Evol. 37: 1790–1808.

https://doi.org/10.1093/molbev/msaa038

Agarap A. F., 2018 Deep learning using rectified linear units (relu). ArXiv Prepr.

ArXiv180308375.

Arnab S. P., M. R. Amin, and M. DeGiorgio, 2022 Uncovering footprints of natural selection

through time-frequency analysis of genomic summary statistics. 2022.10.05.510997.

Auton A., and G. McVean, 2007 Recombination rate estimation in the presence of hotspots.

Genome Res. 17: 1219–1227. https://doi.org/10.1101/gr.6386707

Auton A., G. R. Abecasis, D. M. Altshuler, R. M. Durbin, G. R. Abecasis, *et al.*, 2015 A global

reference for human genetic variation. Nature 526: 68–74.

https://doi.org/10.1038/nature15393

Ba J. L., J. R. Kiros, and G. E. Hinton, 2016 Layer Normalization

Battey C., P. L. Ralph, and A. D. Kern, 2020 Predicting geographic location from genetic

variation with deep neural networks, (P. J. Wittkopp, M. Nordborg, C. Huber, A. Harpak,

and L. Speidel, Eds.). eLife 9: e54507. https://doi.org/10.7554/eLife.54507

Battey C. J., G. C. Coffing, and A. D. Kern, 2021 Visualizing population structure with

variational autoencoders. G3 GenesGenomesGenetics 11: jkaa036.

https://doi.org/10.1093/g3journal/jkaa036

Beaumont M. A., W. Zhang, and D. J. Balding, 2002 Approximate Bayesian computation in

population genetics. Genetics 162: 2025–2035.

https://doi.org/10.1093/genetics/162.4.2025

Berg J. J., and G. Coop, 2015 A Coalescent Model for a Sweep of a Unique Standing Variant.

Genetics 201: 707–725. https://doi.org/10.1534/genetics.115.178962

Booker W. W., D. D. Ray, and D. R. Schrider, 2023 This population does not exist: learning the

distribution of evolutionary histories with generative adversarial networks. Genetics

iyad063. https://doi.org/10.1093/genetics/iyad063

Brody S., U. Alon, and E. Yahav, 2022 How Attentive are Graph Attention Networks?

Browning S. R., and B. L. Browning, 2015 Accurate Non-parametric Estimation of Recent

Effective Population Size from Segments of Identity by Descent. Am. J. Hum. Genet. 97:

404–418. https://doi.org/10.1016/j.ajhg.2015.07.012

Caldas I. V., A. G. Clark, and P. W. Messer, 2022 Inference of selective sweep parameters

through supervised learning. 2022.07.19.500702.

Chan A. H., P. A. Jenkins, and Y. S. Song, 2012 Genome-Wide Fine-Scale Recombination Rate

Variation in Drosophila melanogaster. PLOS Genet. 8: e1003090.

https://doi.org/10.1371/journal.pgen.1003090

Chan J., V. Perrone, J. Spence, P. Jenkins, S. Mathieson, *et al.*, 2018 A Likelihood-Free

Inference Framework for Population Genetic Data using Exchangeable Neural Networks,

in *Advances in Neural Information Processing Systems*, Curran Associates, Inc.

Cho K., B. van Merrienboer, C. Gulcehre, D. Bahdanau, F. Bougares, *et al.*, 2014 Learning

Phrase Representations using RNN Encoder-Decoder for Statistical Machine Translation

DeGiorgio M., and Z. A. Szpiech, 2022 A spatially aware likelihood test to detect sweeps from

haplotype distributions. PLOS Genet. 18: e1010134.

https://doi.org/10.1371/journal.pgen.1010134

Erhan D., C. Szegedy, A. Toshev, and D. Anguelov, 2013 Scalable Object Detection using Deep

Neural Networks

Excoffier L., N. Marchi, D. A. Marques, R. Matthey-Doret, A. Gouy, *et al.*, 2021 fastsimcoal2:

demographic inference under complex evolutionary scenarios. Bioinformatics 37: 4882–

4885. https://doi.org/10.1093/bioinformatics/btab468

Fay J. C., and C. I. Wu, 2000 Hitchhiking under positive Darwinian selection. Genetics 155:

1405–1413.

Ferrer-Admetlla A., M. Liang, T. Korneliussen, and R. Nielsen, 2014 On detecting incomplete

soft or hard selective sweeps using haplotype structure. Mol. Biol. Evol. 31: 1275–1291.

https://doi.org/10.1093/molbev/msu077

Flagel L., Y. Brandvain, and D. R. Schrider, 2019 The Unreasonable Effectiveness of

Convolutional Neural Networks in Population Genetic Inference. Mol. Biol. Evol. 36:

220–238. https://doi.org/10.1093/molbev/msy224

Fu Y. X., and W. H. Li, 1993 Statistical Tests of Neutrality of Mutations. Genetics 133: 693–

709.

Ganin Y., and V. Lempitsky, 2015 Unsupervised Domain Adaptation by Backpropagation

Gao F., C. Ming, W. Hu, and H. Li, 2016 New Software for the Fast Estimation of Population

Recombination Rates (FastEPRR) in the Genomic Era. G3 GenesGenomesGenetics 6:

1563–1571. https://doi.org/10.1534/g3.116.028233

Garud N. R., P. W. Messer, E. O. Buzbas, and D. A. Petrov, 2015 Recent Selective Sweeps in

North American Drosophila melanogaster Show Signatures of Soft Sweeps. PLOS Genet.

11: e1005004. https://doi.org/10.1371/journal.pgen.1005004

Girshick R., 2015 Fast R-CNN

Gower G., P. I. Picazo, M. Fumagalli, and F. Racimo, 2021 Detecting adaptive introgression in

human evolution using convolutional neural networks. eLife 10: e64669.

https://doi.org/10.7554/eLife.64669

Gu J., Z. Wang, J. Kuen, L. Ma, A. Shahroudy, *et al.*, 2018 Recent advances in convolutional

neural networks. Pattern Recognit. 77: 354–377.

https://doi.org/10.1016/j.patcog.2017.10.013

Gutenkunst R. N., R. D. Hernandez, S. H. Williamson, and C. D. Bustamante, 2009 Inferring the

Joint Demographic History of Multiple Populations from Multidimensional SNP

Frequency Data. PLOS Genet. 5: e1000695.

https://doi.org/10.1371/journal.pgen.1000695

Gutenkunst R., R. Hernandez, S. Williamson, and C. Bustamante, 2010 Diffusion

Approximations for Demographic Inference: DaDi. Nat. Preced. 1–1.

https://doi.org/10.1038/npre.2010.4594.1

Haller B. C., J. Galloway, J. Kelleher, P. W. Messer, and P. L. Ralph, 2019 Tree-sequence

recording in SLiM opens new horizons for forward-time simulation of whole genomes.

Mol. Ecol. Resour. 19: 552–566. https://doi.org/10.1111/1755-0998.12968

Haller B. C., and P. W. Messer, 2022 SLiM 4: Multispecies Eco-Evolutionary Modeling. Am.

Nat. E000–E000. https://doi.org/10.1086/723601

He K., X. Zhang, S. Ren, and J. Sun, 2015 Deep Residual Learning for Image Recognition

Hejase H. A., Z. Mo, L. Campagna, and A. Siepel, 2022 A Deep-Learning Approach for

Inference of Selective Sweeps from the Ancestral Recombination Graph. Mol. Biol. Evol.

39: msab332. https://doi.org/10.1093/molbev/msab332

Hermisson J., and P. S. Pennings, 2005 Soft Sweeps. Genetics 169: 2335–2352.

https://doi.org/10.1534/genetics.104.036947

Hermisson J., and P. S. Pennings, 2017 Soft sweeps and beyond: understanding the patterns and

probabilities of selection footprints under rapid adaptation. Methods Ecol. Evol. 8: 700–

716. https://doi.org/10.1111/2041-210X.12808

Hill W. G., and A. Robertson, 1966 The effect of linkage on limits to artificial selection. Genet.

Res. 8: 269–294.

Hochreiter S., and J. Schmidhuber, 1997 Long Short-Term Memory. Neural Comput. 9: 1735–

1780. https://doi.org/10.1162/neco.1997.9.8.1735

Hudson R. R., M. Slatkin, and W. P. Maddison, 1992 Estimation of Levels of Gene Flow from

DNA Sequence Data. Genetics 132: 583–589.

Hudson R. R., K. Bailey, D. Skarecky, J. Kwiatowski, and F. J. Ayala, 1994 Evidence for

positive selection in the superoxide dismutase (Sod) region of Drosophila melanogaster.

Genetics 136: 1329–1340. https://doi.org/10.1093/genetics/136.4.1329

Hudson R. R., 2001 Two-locus sampling distributions and their application. Genetics 159: 1805–

1817. https://doi.org/10.1093/genetics/159.4.1805

Hudson R. R., 2002 Generating samples under a Wright–Fisher neutral model of genetic

variation. Bioinformatics 18: 337–338. https://doi.org/10.1093/bioinformatics/18.2.337

Huson D. H., T. Klöpper, P. J. Lockhart, and M. A. Steel, 2005 Reconstruction of Reticulate

Networks from Gene Trees, pp. 233–249 in *Research in Computational Molecular*

Biology, Lecture Notes in Computer Science. edited by Miyano S., Mesirov J., Kasif S.,

Istrail S., Pevzner P. A., *et al.* Springer, Berlin, Heidelberg.

Ioffe S., and C. Szegedy, 2015 Batch Normalization: Accelerating Deep Network Training by

Reducing Internal Covariate Shift

Kamm J., J. Terhorst, R. Durbin, and Y. S. Song, 2020 Efficiently inferring the demographic

history of many populations with allele count data. J. Am. Stat. Assoc. 115: 1472–1487.

https://doi.org/10.1080/01621459.2019.1635482

Kaplan N. L., R. R. Hudson, and C. H. Langley, 1989 The "hitchhiking effect" revisited.

Genetics 123: 887–899. https://doi.org/10.1093/genetics/123.4.887

Karasov T., P. W. Messer, and D. A. Petrov, 2010 Evidence that Adaptation in Drosophila Is Not

Limited by Mutation at Single Sites. PLOS Genet. 6: e1000924.

https://doi.org/10.1371/journal.pgen.1000924

Kelleher J., A. M. Etheridge, and G. McVean, 2016 Efficient Coalescent Simulation and

Genealogical Analysis for Large Sample Sizes. PLOS Comput. Biol. 12: e1004842.

https://doi.org/10.1371/journal.pcbi.1004842

Kelleher J., K. R. Thornton, J. Ashander, and P. L. Ralph, 2018 Efficient pedigree recording for

fast population genetics simulation. PLOS Comput. Biol. 14: e1006581.

https://doi.org/10.1371/journal.pcbi.1006581

Kelleher J., Y. Wong, A. W. Wohns, C. Fadil, P. K. Albers, *et al.*, 2019 Inferring whole-genome

histories in large population datasets. Nat. Genet. 51: 1330–1338.

https://doi.org/10.1038/s41588-019-0483-y

Kelly J. K., 1997 A test of neutrality based on interlocus associations. Genetics 146: 1197–1206.

https://doi.org/10.1093/genetics/146.3.1197

Kern A. D., and D. R. Schrider, 2016 Discoal: flexible coalescent simulations with selection.

Bioinformatics 32: 3839–3841. https://doi.org/10.1093/bioinformatics/btw556

Kern A. D., and D. R. Schrider, 2018 diploS/HIC: An Updated Approach to Classifying

Selective Sweeps. G3 GenesGenomesGenetics 8: 1959–1970.

https://doi.org/10.1534/g3.118.200262

Kim Y., and R. Nielsen, 2004 Linkage disequilibrium as a signature of selective sweeps.

Genetics 167: 1513–1524. https://doi.org/10.1534/genetics.103.025387

Kingma D. P., and J. Ba, 2017 Adam: A Method for Stochastic Optimization

Kipf T. N., and M. Welling, 2017 Semi-Supervised Classification with Graph Convolutional

Networks

Korfmann K., O. E. Gaggiotti, and M. Fumagalli, 2023a Deep Learning in Population Genetics.

Genome Biol. Evol. 15: evad008. https://doi.org/10.1093/gbe/evad008

Korfmann K., T. Sellinger, F. Freund, M. Fumagalli, and A. Tellier, 2023b Simultaneous

Inference of Past Demography and Selection from the Ancestral Recombination Graph

under the Beta Coalescent. 2022.09.28.508873.

Lauterbur M. E., K. Munch, and D. Enard, 2022 Versatile detection of diverse selective sweeps

with Flex-sweep. 2022.11.15.516494.

LeCun Y., B. Boser, J. S. Denker, D. Henderson, R. E. Howard, *et al.*, 1989 Backpropagation

Applied to Handwritten Zip Code Recognition. Neural Comput. 1: 541–551.

https://doi.org/10.1162/neco.1989.1.4.541

LeCun Y., L. Bottou, Y. Bengio, and P. Haffner, 1998 Gradient-based learning applied to

document recognition. Proc. IEEE 86: 2278–2324.

Li H., and R. Durbin, 2011 Inference of Human Population History From Whole Genome

Sequence of A Single Individual. Nature 475: 493–496.

https://doi.org/10.1038/nature10231

Li Z., F. Liu, W. Yang, S. Peng, and J. Zhou, 2022 A Survey of Convolutional Neural Networks:

Analysis, Applications, and Prospects. IEEE Trans. Neural Netw. Learn. Syst. 33: 6999–

7019. https://doi.org/10.1109/TNNLS.2021.3084827

Lin K., H. Li, C. Schlötterer, and A. Futschik, 2011 Distinguishing Positive Selection From

Neutral Evolution: Boosting the Performance of Summary Statistics. Genetics 187: 229–

244. https://doi.org/10.1534/genetics.110.122614

Mahmoudi A., J. Koskela, J. Kelleher, Y. Chan, and D. Balding, 2022 Bayesian inference of

ancestral recombination graphs. PLOS Comput. Biol. 18: e1009960.

https://doi.org/10.1371/journal.pcbi.1009960

Mo Z., and A. Siepel, 2023 Domain-adaptive neural networks improve supervised machine

learning based on simulated population genetic data. 2023.03.01.529396.

Mughal M. R., and M. DeGiorgio, 2019 Localizing and Classifying Adaptive Targets with Trend

Filtered Regression. Mol. Biol. Evol. 36: 252–270.

https://doi.org/10.1093/molbev/msy205

Mughal M. R., H. Koch, J. Huang, F. Chiaromonte, and M. DeGiorgio, 2020 Learning the

properties of adaptive regions with functional data analysis. PLOS Genet. 16: e1008896.

https://doi.org/10.1371/journal.pgen.1008896

Nei M., and W. H. Li, 1979 Mathematical model for studying genetic variation in terms of

restriction endonucleases. Proc. Natl. Acad. Sci. 76: 5269–5273.

https://doi.org/10.1073/pnas.76.10.5269

Nei M., and F. Tajima, 1981 DNA Polymorphism Detectable by Restriction Endonucleases.

Genetics 97: 145–163.

Paszke A., S. Gross, F. Massa, A. Lerer, J. Bradbury, *et al.*, 2019 PyTorch: An Imperative Style,

High-Performance Deep Learning Library

Pavlidis P., J. D. Jensen, and W. Stephan, 2010 Searching for footprints of positive selection in

whole-genome SNP data from nonequilibrium populations. Genetics 185: 907–922.

https://doi.org/10.1534/genetics.110.116459

Pearson A., and R. Durbin, 2023 Local Ancestry Inference for Complex Population Histories.

2023.03.06.529121.

Perron L., and V. Furnon, 2019 OR-Tools

Pritchard J. K., M. T. Seielstad, A. Perez-Lezaun, and M. W. Feldman, 1999 Population growth

of human Y chromosomes: a study of Y chromosome microsatellites. Mol. Biol. Evol.

16: 1791–1798. https://doi.org/10.1093/oxfordjournals.molbev.a026091

Przeworski M., G. Coop, and J. D. Wall, 2005 The signature of positive selection on standing

genetic variation. Evol. Int. J. Org. Evol. 59: 2312–2323.

Pudlo P., J.-M. Marin, A. Estoup, J.-M. Cornuet, M. Gautier, *et al.*, 2016 Reliable ABC model

choice via random forests. Bioinformatics 32: 859–866.

https://doi.org/10.1093/bioinformatics/btv684

Pybus M., P. Luisi, G. M. Dall'Olio, M. Uzkudun, H. Laayouni, *et al.*, 2015 Hierarchical

boosting: a machine-learning framework to detect and classify hard selective sweeps in

human populations. Bioinformatics 31: 3946–3952.

https://doi.org/10.1093/bioinformatics/btv493

Ralph P., K. Thornton, and J. Kelleher, 2020 Efficiently Summarizing Relationships in Large

Samples: A General Duality Between Statistics of Genealogies and Genomes. Genetics

215: 779–797. https://doi.org/10.1534/genetics.120.303253

Rasmussen M. D., M. J. Hubisz, I. Gronau, and A. Siepel, 2014 Genome-Wide Inference of

Ancestral Recombination Graphs. PLOS Genet. 10: e1004342.

https://doi.org/10.1371/journal.pgen.1004342

Ray D. D., L. Flagel, and D. R. Schrider, 2023 IntroUNET: identifying introgressed alleles via

semantic segmentation. 2023.02.07.527435.

Raynal L., J.-M. Marin, P. Pudlo, M. Ribatet, C. P. Robert, *et al.*, 2019 ABC random forests for

Bayesian parameter inference. Bioinforma. Oxf. Engl. 35: 1720–1728.

https://doi.org/10.1093/bioinformatics/bty867

Reddi V. J., C. Cheng, D. Kanter, P. Mattson, G. Schmuelling, *et al.*, 2020 MLPerf Inference

Benchmark

Ronen R., N. Udpa, E. Halperin, and V. Bafna, 2013 Learning Natural Selection from the Site

Frequency Spectrum. Genetics 195: 181–193.

https://doi.org/10.1534/genetics.113.152587

Rosenzweig B. K., J. B. Pease, N. J. Besansky, and M. W. Hahn, 2016 Powerful methods for

detecting introgressed regions from population genomic data. Mol. Ecol. 25: 2387–2397.

https://doi.org/10.1111/mec.13610

Sabeti P. C., D. E. Reich, J. M. Higgins, H. Z. P. Levine, D. J. Richter, *et al.*, 2002 Detecting

recent positive selection in the human genome from haplotype structure. Nature 419:

832–837. https://doi.org/10.1038/nature01140

Sanchez T., J. Cury, G. Charpiat, and F. Jay, 2021 Deep learning for population size history

inference: Design, comparison and combination with approximate Bayesian computation.

Mol. Ecol. Resour. 21: 2645–2660. https://doi.org/10.1111/1755-0998.13224

Santiago E., I. Novo, A. F. Pardiñas, M. Saura, J. Wang, *et al.*, 2020 Recent Demographic

History Inferred by High-Resolution Analysis of Linkage Disequilibrium. Mol. Biol.

Evol. 37: 3642–3653. https://doi.org/10.1093/molbev/msaa169

Schrider D. R., and A. D. Kern, 2016 S/HIC: Robust Identification of Soft and Hard Sweeps

Using Machine Learning. PLOS Genet. 12: e1005928.

https://doi.org/10.1371/journal.pgen.1005928

Schrider D. R., and A. D. Kern, 2017 Soft Sweeps Are the Dominant Mode of Adaptation in the

Human Genome. Mol. Biol. Evol. 34: 1863–1877.

https://doi.org/10.1093/molbev/msx154

Schrider D. R., and A. D. Kern, 2018 Supervised Machine Learning for Population Genetics: A

New Paradigm. Trends Genet. TIG 34: 301–312.

https://doi.org/10.1016/j.tig.2017.12.005

Schrider D. R., J. Ayroles, D. R. Matute, and A. D. Kern, 2018 Supervised machine learning

reveals introgressed loci in the genomes of Drosophila simulans and D. sechellia. PLOS

Genet. 14: e1007341. https://doi.org/10.1371/journal.pgen.1007341

Sheehan S., and Y. S. Song, 2016 Deep Learning for Population Genetic Inference. PLoS

Comput. Biol. 12: e1004845. https://doi.org/10.1371/journal.pcbi.1004845

Shriner D., D. C. Nickle, M. A. Jensen, and J. I. Mullins, 2003 Potential impact of recombination

on sitewise approaches for detecting positive natural selection. Genet. Res. 81: 115–121.

https://doi.org/10.1017/S0016672303006128

Smith J. M., and J. Haigh, 1974 The hitch-hiking effect of a favourable gene. Genet. Res. 23:

23–35. https://doi.org/10.1017/S0016672300014634

Smith C. C. R., S. Tittes, P. L. Ralph, and A. D. Kern, 2023 Dispersal inference from population

genetic variation using a convolutional neural network. Genetics iyad068.

https://doi.org/10.1093/genetics/iyad068

1127 Speidel L., M. Forest, S. Shi, and S. R. Myers, 2019 A method for genome-wide genealogy

1128   estimation for thousands of samples. Nat. Genet. 51: 1321–1329.

1129   https://doi.org/10.1038/s41588-019-0484-x

1130 Stephan W., 2019 Selective Sweeps. Genetics 211: 5–13.

1131   https://doi.org/10.1534/genetics.118.301319

1132 Tajima F., 1989 Statistical Method for Testing the Neutral Mutation Hypothesis by DNA

1133   Polymorphism. Genetics 123: 585–595.

1134 Tavare S., D. J. Balding, R. C. Griffiths, and P. Donnelly, 1997 Inferring Coalescence Times

1135   from DNA Sequence Data. Genetics 145: 505. https://doi.org/10.1093/genetics/145.2.505

1136 Terhorst J., J. A. Kamm, and Y. S. Song, 2017 Robust and scalable inference of population

1137   history from hundreds of unphased whole-genomes. Nat. Genet. 49: 303–309.

1138   https://doi.org/10.1038/ng.3748

1139 Vapnik V., 2006 *Estimation of Dependences Based on Empirical Data*. Springer New York,

1140   New York, NY.

1141 Veličković P., G. Cucurull, A. Casanova, A. Romero, P. Liò, *et al.*, 2018 Graph Attention

1142   Networks

1143 Voight B. F., S. Kudaravalli, X. Wen, and J. K. Pritchard, 2006 A Map of Recent Positive

1144   Selection in the Human Genome. PLoS Biol. 4: e72.

1145   https://doi.org/10.1371/journal.pbio.0040072

1146 Wang Z., J. Wang, M. Kourakos, N. Hoang, H. H. Lee, *et al.*, 2021 Automatic inference of

1147   demographic parameters using generative adversarial networks. Mol. Ecol. Resour. 21:

1148   2689–2705. https://doi.org/10.1111/1755-0998.13386

1149 Watterson G. A., 1975 On the number of segregating sites in genetical models without

recombination. Theor. Popul. Biol. 7: 256–276. https://doi.org/10.1016/0040-

5809(75)90020-9

Whitehouse L. S., and D. R. Schrider, 2022 Timesweeper: Accurately Identifying Selective

Sweeps Using Population Genomic Time Series. 2022.07.06.499052.

Whitehouse L. S., and D. R. Schrider, 2023 Timesweeper: accurately identifying selective

sweeps using population genomic time series. Genetics 224: iyad084.

https://doi.org/10.1093/genetics/iyad084

Wiuf C., and J. Hein, 1999 Recombination as a Point Process along Sequences. Theor. Popul.

Biol. 55: 248–259. https://doi.org/10.1006/tpbi.1998.1403

Yelmen B., A. Decelle, L. Ongaro, D. Marnetto, C. Tallec, *et al.*, 2021 Creating artificial human

genomes using generative neural networks. PLOS Genet. 17: e1009303.

https://doi.org/10.1371/journal.pgen.1009303

Zhang B. C., A. Biddanda, Á. F. Gunnarsson, F. Cooper, and P. F. Palamara, 2023 Biobank-scale

inference of ancestral recombination graphs enables genealogical analysis of complex

traits. Nat. Genet. 55: 768–776. https://doi.org/10.1038/s41588-023-01379-x

Zhou J., G. Cui, S. Hu, Z. Zhang, C. Yang, *et al.*, 2020 Graph neural networks: A review of

methods and applications. AI Open 1: 57–81.