Exploring the repository of *de novo* designed bifunctional antimicrobial peptides through deep learning

Ruihan Dong[1,2#], Rongrong Liu[3#], Ziyu Liu[3#], Yangang Liu[4#], Gaomei Zhao[5], Honglei Li[6], Shiyuan Hou[3], Xiaohan Ma[3], Huarui Kang[3], Jing Liu[3], Fei Guo[7], Ping Zhao[4], Junping Wang[5], Cheng Wang[5,*], Xingan Wu[3,*], Sheng Ye[1,*], Cheng Zhu[1,*]

[1] Frontiers Science Center for Synthetic Biology (Ministry of Education), Tianjin Key Laboratory of Function and Application of Biological Macromolecular Structures, School of Life Sciences, Faculty of Medicine, Tianjin University, Tianjin 300072, China

[2] Center for Quantitative Biology, Academy for Advanced Interdisciplinary Studies, Peking University, Beijing 100871, China

[3] Department of Microbiology, School of Basic Medicine, Fourth Military Medical University, Xi'an 710000, Shaanxi, China

[4] Department of Microbiology, Second Military Medical University, Shanghai 200433, China

[5] State Key Laboratory of Trauma and Chemical Poisoning, Institute of Combined Injury of PLA, College of Preventive Medicine, Third Military Medical University (Army Medical University), Chongqing 400038, China

[6] Tianjin Cancer Hospital Airport Hospital, Tianjin 300308, China

[7] School of Computer Science and Engineering, Central South University, Changsha 410083, Hunan, China

[#] These authors contributed equally to this work.

[*] Correspondence: wangctmmu@126.com (C.W.), wuxingan@fmmu.edu.cn (X.W.), sye@tju.edu.cn (S.Y.), cheng_zhu@tju.edu.cn (C.Z.)

Abstract

Antimicrobial peptides (AMPs) are attractive candidates to combat antibiotic resistance for their capability to target bio-membranes and restrict a wide range of pathogens. It is a daunting challenge to discover novel AMPs due to their sparse distributions in a vast peptide universe, especially for peptides that demonstrate potencies for both bacterial membranes and viral envelopes. Here we establish a *de novo* AMP design framework by bridging a deep generative module and a graph-encoding activity regressor. The generative module learns hidden 'grammars' of AMP features and produces candidates sequentially pass antimicrobial predictor and antiviral classifiers. We discover 16 bifunctional AMPs and experimentally validated their abilities to inhibit a spectrum of pathogens *in vitro* and in animal models. Notably, P076 is a highly potent bactericide with the minimal inhibitory concentration of 0.21 μM against multidrug-resistant *A. baumannii*, while P002 broadly inhibits five enveloped viruses. Our study provides feasible means to uncover sequences that simultaneously encode antimicrobial and antiviral activities, thus bolstering the function spectra of AMPs to combat a wide range of drug-resistant infections.

Keywords

Antimicrobial peptides, Antiviral peptides, Deep learning, Dual-function, Generative model, Sequence design

Introduction

In the post-antibiotic era, microbes rapidly evolve to become antimicrobial-resistant under the pressure of antibiotic abuse and through horizontal transfer of resistance genes.[1] Due to increasing cases of untreatable bacterial infections, the World Health Organization (WHO) has projected a looming health threat of 10 million casualties per year by 2050.[2] Specifically, the WHO has identified six antimicrobial-resistant pathogens (*Enterococcus faecium*, *Staphylococcus aureus*, *Klebsiella pneumoniae*, *Acinetobacter baumannii*, *Pseudomonas aeruginosa*, and *Enterobacter* species) as ESKAPE. The ESKAPE pathogens have severely limited the treatment options for serious infections and impaired the conditions of immunodeficient patients.[3] In sharp contrast, the majority of clinically available antibiotics were developed more than 30 years ago.[4] Hence, there are urgent needs for targeted generation and screening of novel molecules with desired therapeutic properties for the next-generation broad-spectrum antimicrobial agents.

As a naturally evolved defense line of innate immune system, antimicrobial peptides (AMPs) are cationic macromolecules (usually 10-60 amino acids) widely present in all living organisms.[5] AMPs are attractive alternatives to conventional antibiotic treatment because they effectively inhibit a wide range of pathogens, such as the Gram-positive and Gram-negative bacteria, fungi, and viruses.[5] The majorities of AMPs featured amphiphilic patterns of amino acid sequences and enriched positive charges (e.g., lysine and arginine residues), which allowed AMPs to disrupt the membrane components and exert antimicrobial effects.[6] Due to the relative constant compositions of biological membranes as the essential AMP targets, development of resistance to AMPs were rare events even after 100 passages of lab evolutions.[7, 8]

Notably, the naturally evolved and rationally designed AMP sequences (~20 000) are housed in several databases (APD,[9] DBAASP,[10] DRAMP,[11] etc.) and paired with experimentally validated activities (minimal inhibitory concentration, or MIC), thus facilitating data mining endeavors for more diverse sequences and more effective peptides.[12] Indeed, deep learning models have led to the discovery of highly efficient AMPs (e.g., MIC of 2 μM against *E. coli*). Specifically, predictive models like Deep-AMPEP30,[13] AMPlify,[14] TransImbAMP,[15] and sAMPpred-GAT[16] utilized deep convolutional, recurrent, attention-based, and graph neural networks to learn and recognize latent

representations of meaningful peptides. These models recently enabled comprehensive mining of

the human gut microbiome,[17] modern and ancient human proteomes,[18, 19] or even the entire

sequence space of hexapeptides.[8] Generative models like PepVAE,[20] CLaSS,[21] and HydrAMP[22]

reconstructed the sequences from latent space according to the encoder-decoder architecture of

variational autoencoders (VAE), while PepGAN[23] and AMPGAN v2[24] utilized the generative

adversarial network (GAN) to approximate the antimicrobial sequences by deceiving the

discriminator.

Despite the recent advances of data-driven AMP classifiers and generators, the exploration of a

vast AMPs repertoire is still hindered by several factors: (1) The sparsity of AMPs in the whole

peptide space, which demands accurate prediction of MIC values for efficient sampling and

filtering of AMP analogues.[22, 25] The current machine learning predictive models usually perform

the binary classification task and label the generated sequences as active or not, instead of giving

specific activity values. To overcome this shortcoming, a popular pipeline combines independent

modules of filtering, classification, and regression, but it faces risks of step-wise bias

accumulation.[8] (2) The impact of different phospholipid species on the efficacy of AMPs. Due to

the data incompleteness of antimicrobial measurements, a majority of AMP classifiers or MIC

predictions were specific to *E. coli* (Gram-negative). Nevertheless, these models were applied to

find peptides that inhibit other Gram-positive bacteria (e.g., *S. aureus*), based on the assumption

that the shared membrane components are potential targets of AMPs. More importantly, the

enveloped virus also possesses a targetable membrane, which closely mimic the phospholipid

components of cellular organelles. Even though the AMP database recorded antiviral activities of

at least 2 000 antiviral peptides (AVPs), whether the current models can readily generate antiviral

peptides remain elusive. (3) Lack of rigorous pre-clinical models. To advance the designed AMPs

towards clinical trials, the experiments should reflect the efficacy of AMPs in tissue samples and

require the determination of safe doses of a particular sequence before practical applications. To

our knowledge, more than 120 AMPs have been suggested by deep learning models in the past

three years, only a fraction of these studies demonstrated animal results.

In the current study, we addressed these shortcomings and presented a new deep learning-based *de*

novo AMP design framework, consisting of a GAN generator and an antimicrobial activity

regressor named AMPredictor. The graph convolution network (GCN) of AMPredictor allowed us

to effectively train a regression model for the task of MIC predictions. Through in-depth

investigations of generated sequences (e.g., antiviral possibilities), we selected three top-ranking

sequences (P001, P002, and P076) and evaluated their efficacies against different pathogens (four

drug-resistant bacteria and five enveloped virus). Out of the three candidates, we found P076 is a

potent bactericide with MIC of 0.21 μM against multidrug-resistant bacterium. It also

outperformed a clinically relevant antibiotic polymyxin B in terms of safety and efficacy, as

evaluated in mouse models. Another peptide P002 broadly neutralized viruses in cellular infection

models. We challenged our computational models to generate bifunctional AMPs and our results

demonstrated that these peptides inhibited a spectrum of pathogens, but with delicate preferences

towards bacterial or viral species.

Results

Bridging the generator and regressor for *de novo* AMP design

The overall architecture for designing functional peptides fuses a generative adversarial network

and an antimicrobial activity predictor (AMPredictor, Figure 1a). We aim to explore beyond the

known antimicrobial templates or accessible proteomics space. We trained the GAN module with

3280 AMP sequences to capture the pattern of antimicrobial peptides through few-shot learning.

The training goal of GAN is to reach a relative balance between the generator and discriminator

(see Methods Equation 1). The generator takes random noise as input to produce fake samples,

which are fed into the discriminator along with the real data. The discriminator tries to distinguish

between the real and fake data, then returns a probability to update the weights of the networks.[26]

Here, we employed a low-dimensional vector called amino acid factors (AAF) to encode the

peptide sequences and describe their physicochemical features.[27] We monitored the generated

sequences at different training stages (epoch 1, 100, 200, 400, 800) and visualized the optimization

process using two common dimension reduction approaches, uniform manifold approximation and

projection (UMAP) and t-distributed stochastic neighbor embedding (t-SNE). We clearly observed

the distributions of newly sampled sequences among the existing AMPs after mapping peptide

AAF features onto the two-dimensional space (Figure 1b). With iterating and updating, the

generator learns the feature distribution of actual data and generates diverse sequences.

We checked the novelty and diversity of generated sequences at epoch 1000 by aligning them with

our training set. The sequence similarities were evaluated by global alignment using BLOSUM62

matrix. We found the identity of each generated sequence was around 0.35 to the known database

(Figure 1c), indicating a low level of similarity to the existing AMPs. With distinct sequence

compositions, generated peptides still hold similar physiochemical features to real AMPs, as

evidenced by six descriptors of aliphatic index, aromaticity, net charge, the ratio of hydrophobic

amino acids, instability index, and isoelectric point (Figure 1d).[28] The distribution of these

descriptors closely resembled the physiochemical features of AMPs in the training set. Hence,

adopting residue features as the input of GAN generator can capture the functional properties of

actual AMPs.

We then developed an independent module AMPredictor to estimate the MIC values of arbitrary

peptide sequences. AMPredictor is a GCN-based regression model, equivalent to the 'score

function' in virtual drug screen. Unlike the low-dimensional descriptor adopted by GAN generator,

we designed distinct representations of peptides in AMPredictor for model accuracy and

orthogonal verification of GAN-generated sequences. We chose graph as the representation of

peptides, with their amino acid residues as graph nodes and the predicted contact maps as graph

edges. The node features were embeddings from the protein language model ESM.[29] The peptide

graphs were then fed into a three-layer GCN to learn the hidden 'grammars' of AMP features. In

addition to the sequence-level and structural-level features, we transformed the input amino acid

sequences into Morgan fingerprints to encode the chemical features at each residual position. This

atomic-level information was concatenated with GCN representations before entering a three-layer

fully-connected networks to regress on MIC datasets (Figure 1a). AMPredictor obtained a low root

mean squared error (RMSE) of 0.5348 and a high Pearson correlation coefficient (PCC) of 0.7072

on the test set (10% size of the dataset) (Figure 1b). The output of AMPredictor is the logMIC

value of an AMP sequence.

By integrating the representations of residual-level, sequence-level, and protein structural level

information, AMPredictor obtained the best performance in comparison to its ablating versions

(Table S1). The ablation study indicated that the context embeddings from ESM play vital roles in

predicting MICs, and the contact map assisted in improvement despite it being a simplified

representation of protein structure. We also compared the performance of AMPredictor with five

typical deep neural networks as baselines, including the multilayer perceptron (MLP),

convolutional neural network (CNN), gated recurrent unit (GRU), long short-term memory

(LSTM), and Transformer. AMPredictor outperforms these methods in terms of accuracy at the

task of predicting antimicrobial activity values (scatter plots in Figure S2). Hence, a well-trained

generator could produce a variety of AMP candidates and then AMPredictor ranked the candidates

by MIC values. Together with coarse to fine representations of AMP samples, the GAN and

AMPredictor facilitated *de novo* design and *in silico* evaluation of AMPs.

Figure 1. Deep learning-based design of novel antimicrobial peptides.

a. The overall framework of generative adversarial network (GAN) generator and AMPredictor.

b. Visualization of GAN training process via UMAP and t-SNE. The newly generated sequences fit the distribution of known AMP space gradually.

c. Global alignment match scores between the generated sequences and itself and AMPs in the training set.

d. Six physiochemistry properties of generated peptides and real AMP sets.

e. Regression results of AMPredictor model on its test set.

191 f. The sequences of three selected peptides as well as their predicted and experimentally validated

192 MIC values against *E. coli* ATCC 25922.

195 **Designing bifunctional antimicrobial peptides**

196 Our study was based on the hypothesis that both bacterial membranes and viral envelopes were

197 potential targets of AMPs, and the dual-function of antibacterial and antiviral could be encoded

198 into one peptide sequence. We directly compared the outcome of two different training sets for two

199 versions of the GAN generator: with or without adding AVP sequences, for their efficiencies of

200 designing bifunctional peptides (Figure 2a). The generator v1 was trained solely on collected AMP

201 sequences, and generator v2 was trained on the AMP set and known 1788 AVPs from AVPdb. To

202 establish a sequential workflow and filter out antimicrobial peptides with antiviral capabilities, we

203 then considered assembling several AVP classifiers subsequent to the AMPredictor. As the source

204 data, the AVPdb provided ~2000 sequences with IC_{50} labels.[30] However, data curation resulted in

205 only 759 unique AVPs. We determined that the quantitative data of AVPs were insufficient for

206 training another GCN-based regression model. Instead, binary classification should exhibit

207 robustness against noise of a relatively small dataset. Hence, we merely made yes/no decisions

208 using a collective of five published AVP classification tools (AVPpred,[31] DeepAVP,[32] Deep-

209 AVPpred,[33] ENNAVIA,[34] and AI4AVP,[35] details in Table S2). We obtained 1024 new peptides from

210 each generator and kept the sequences with a predicted MIC value of less than 10 µM by

211 AMPredictor. More than one hundred peptides passed the ensemble filter of all five AVP classifiers.

212 Interestingly, generator v2 did not feature a higher passing ratio, although it was trained with AVPs.

213 Based on their hemolysis and other physicochemical properties, we selected 12 peptides from each

214 generator for experimental validation. We also checked their novelty by BLAST with the training

215 set or DRAMP database and all their E-values are greater than 0.1 or no hits found (Table S3).

217 All 24 peptides exhibited effective antibacterial capability in inhibiting six different strains

218 involving three multidrug-resistant species (Figure 2b). Several peptides obtained remarkable

219 MIC values of less than 1 µM, such as P026 and P036, indicating the effectiveness of our generator

220 for *de novo* designing AMPs. Then we used a stricter rule of 'antibacterial' to define bifunctional

221 peptides. If the MIC value of a peptide was less than 10 µM against at least one strain, we described

it as antibacterial. We also tested whether these peptides can inhibit Herpes simplex virus 1 (HSV-

1) at the concentration of 10 µM. The 'antiviral' feature of a peptide was checked when significant

inhibition was observed in immunofluorescence experiments. There were six and seven

bifunctional AMPs out of 12 from generators v1 and v2, respectively (Figure 2c). Given that we

did not screen on more virus species, the success rate of being antiviral is relatively lower than

being antibacterial. This result indicates the capability of our design method for bifunctional AMPs.

Through the comparison between generators v1 and v2, we demonstrated that the antiviral feature

was 'naturally' encoded in AMP sequences.

We then paired small-scale design with more comprehensive experimental characterization, using

four drug-resistant bacteria, five enveloped viruses, and animal infection models, focusing on

generator v1. We acquired 104 novel peptides via the *de novo* design framework. Among them, 42

and 26 were predicted to own MIC values below 10 µM and 5 µM, respectively (supplemental

spread sheet). The small-scale design procedure did not sacrifice the efficiency of discovering

novel peptides and featured a comparable success rate with AMPredictor. We regarded a peptide

as an antiviral candidate if four or more positive votes were recorded and 32 peptides met our

criteria.

We also conducted a comprehensive evaluation of efficacy and safety *in silico*, to select novel

AMPs before experimental validations. Considering the membrane corruption mechanism of most

AMPs, we predicted their hemolytic activity as a quick measure of cellular toxicity.[36] Through the

ranking of high activity and low toxicity, we picked three potent peptides P001, P002, and P076

(Figure 1f), all of which featured amphiphilic signatures of sequence and enriched cationic regions

(e.g., helical wheel projections in Figure S3), for *in vitro* and *in vivo* experimental assessment.

Figure 2. Large-scale design and validation of bifunctional AMPs.

a. Schemes of designing bifunctional AMPs from two versions of generators. 12 designed peptides from each generator were selected for experimental validation.

b. MIC test of 24 designed peptides against six bacterial strains. The first group included 12 peptides from generator v1, and the other 12 peptides were from generator v2.

c. Antiviral and antibacterial results for bifunctional peptides. The rows with pink or purple backgrounds are bifunctional AMPs acquired from generators v1 or v2, respectively.

In vitro **antibacterial and hemolytic assays**

We examined the antibacterial activity of P001, P002, and P076 against one Gram-positive (*S. aureus*) and three Gram-negative (*A. baumannii*, *E. coli*, and *P. aeruginosa*) bacteria, including three ESKAPE strains. For each species, we cultured a standard strain and a multidrug-resistant

(MDR) strain, and measured the MIC values of individual peptides using the broth microdilution
method. All the peptides exhibited inspiring bactericidal properties with MICs ranging from 0.20
to 15.18 μM (corresponding to 0.625 to 40 μg/mL, Figure 3a). P001 showed broad-spectrum
antibacterial capability with MICs less than 4 μM across all the eight strains of four bacteria species.
P002 featured lower MIC values in inhibiting Gram-positive bacteria *S. aureus*, while P076 mainly
inhibits Gram-negative bacteria *A. baumannii*, *E. coli*, and *P. aeruginosa*. Notably, the
experimentally measured MICs against *E. coli* agreed well with the predictions of AMPredictor
(Figure 1f), indicating the accuracy of our regression models.
270
The hemolytic analysis revealed that both P001 and P002 displayed dose-dependent toxicity to
mouse erythrocytes (Figure 3b), with average hemolysis higher than 50% at high concentrations
(20 μM, or 100 μg/mL). Nevertheless, the hemolysis of P076 was lower than 1% at concentrations
up to 70 μM. We also inspected the apparent cytotoxicity (CC_{50}) of three peptides on three
mammalian cell lines (Vero-E6, A549, Huh-7) using CCK8 assays. For the cell cultures, CC_{50}
values of all three peptides were well above 30 μM (Figure S8a). The CC_{50} of P076, specifically,
were in the range of 35.5 μM (for A549 cells from lung tissues) to 66.8 μM (for Huh-7 cells from
liver tissues). The *in vitro* safety assays pointed out thresholds of concentration for administrating
these peptides, which were adapted in subsequent animal experiments for estimation of safe dosage.
280
Our data suggest that all three peptides are potential candidates for inhibiting the clinically relevant
A. baumannii, which is a top-ranking pathogen with critical priority for development of new
antibiotics, as defined by WHO.[3] The MIC of P076 at eliminating the persistent MDRAB reached
0.21 μM, a value half of P001 and P002 (0.40 and 0.47 μM, respectively). Meanwhile, P076 was
comparable with P001 but more efficient than P002 against *E. coli* and *P. aeruginosa*. Despite a
slight inferiority in killing *S. aureus*, P076 owned a better biosafety. Taken together, the sequence
of P076 likely leveraged the balance between efficacy and safety, we therefore focused the
following *in vivo* evaluation and animal infection models on P076.
289
290

Figure 3. Antibacterial and toxicological evaluations of P076 peptide.

a. *In vitro* antibacterial assessment of peptides by determination of MICs.

b. Hemolysis of increasing concentrations of peptides. Results are shown as the means $\pm$ standard

deviation (SDs).

c. Survival curves of mice given P076 and PB. Arrows indicate the drug concentration inducing a

50% death.

d. H&E staining of mouse kidneys. The scale bar indicates 200 μm.

e. Survival of infected mice treated with P076 and CIP.

f. g. Bacterial colonization of MDRAB in mouse peritoneal lavage fluid and spleen. Results are

shown as the means $\pm$ SDs. ***, P<0.001. n.s., no significance.

In vivo antibacterial and toxicological evaluations

We first determined a safe dosage for administrating P076 on mouse models. A total of 140 C57 mice (randomly divided into 14 groups) were given increasing concentrations of P076 through intraperitoneal injection, and the cyclic peptide antibiotic polymyxin B (PB) was employed as a positive control. In spite of nephrotoxicity, PB is one of the polymyxin antibiotics that is considered "the last ditch" for the treatment of infections caused by extensively drug-resistant Gram-negative bacteria in clinic.[37] Animal survival was monitored for 48 h after a single drug administration. The P076 concentration to induce a 50% death was calculated to be 80 mg/kg, approximately 3-fold higher than that of PB (26 mg/kg, Figure 3c). Hematoxylin-eosin (HE) staining further verified that no pathological changes were observed in the mice liver, spleen and kidneys of mice given 32 mg/kg P076 after 12 h, whereas an apparent renal tubular injury was discovered in PB-treated mouse (Figure 3c and S5a).

Encouraged by the biocompatibility of P076, we further conducted an *in vivo* antibacterial assay using a mouse peritoneal infection model.[38] A total of 3×10^7 CFU of MDRAB was intraperitoneally injected in C57 mouse to establish infection symptoms. P076 was administered at 2 mg/kg at 0.5 and 2.5 h after bacterial invasion. As the positive control treatment, we employed a single injection of 32 mg/kg ciprofloxacin (CIP) at 0.5 h after infection. The mice given PBS (blank buffer) or CIP all deceased after 48 h, while 50% of the mice treated with P076 remained alive (Figure 3e). Additional investigations revealed that the bacterial colonization in the peritoneal lavage fluid of PBS-treated mouse was averagely 1.1×10^6 CFU, which was 25 times higher than that in the mice treated with P076 (4.2×10^4 CFU, P<0.001), whereas CIP featured less of effect on the number of bacteria (Figure 3f). Similarly, P076 dramatically decreased the bacterial loads in the mouse spleen (about seven times lower, Figure 3g and S5b), thus demonstrating the prospect of P076 to be developed into a new antibiotic.

Figure 4. Antiviral assays of AMPs against CHIKV, HTNV, DENV-2, and HSV-1.

a. Quantitative real-time PCR of virus RNA with gradient concentrations of P001, P002, and P076.

b. Immunofluorescence results of four viruses with gradient concentrations of P002.

All experiments are performed in triplicates. Column bars are means $\pm$ SEMs. * P<0.05, ** P<0.01,

*** P<0.001, **** P<0.0001. ns, no significance.

Broad-spectrum antiviral assays

A cohort of traditional antimicrobial peptides have been rediscovered with antiviral abilities.[39] One significant reason is that their membrane-disrupting capacity can adapt to both bacterial membranes and viral envelopes, which may be captured by AMPredictor and AVP classifier filters. Thus, we tested the antiviral activities of P001, P002, and P076, which passed our dual filters. Our experiments included five typical enveloped viruses. Chikungunya virus (CHIKV), Hantaan virus (HTNV), Dengue virus 2 (DENV-2), Herpes simplex virus 1 (HSV-1), and severe acute respiratory syndrome coronavirus 2 (SARS-CoV-2, and the BA.2. omicron variant) are all pathogens of the past or ongoing epidemics, such as the chikungunya fever, hemorrhagic fever with renal syndrome, dengue, encephalitis, and COVID-19. Hence, the peptide drugs may be repurposed as preventions against viral infections.

We incubated the peptides with different viruses before they invaded the cultured cells and self-amplified. We analyzed the potential antiviral effects of P001, P002, P076 at the mRNA and protein levels, respectively. At the mRNA level, the quantitative real-time PCR suggested dose-dependent inhibition of viral-specific gene expressions (E1 gene for CHIKV, S gene for HTNV, VP16 gene for HSV-1, NS5a gene for DENV-2, ORF for SARS-CoV-2, Figure 4a and Figure S6b). At the protein level, we applied fluorescence-conjugated antibodies to visualize trace amounts of virus populations. Corroborating with the RT-PCR results, P002 nearly abolished all viral infections at 12.5 μM (Figure 4b, Figure S6a and Figure S7). To quantify the immunofluorescence results, we plotted the log-scale fluorescent focus forming unit (FFU) against varying peptide concentrations (Figure S8b). Among the three peptides, P002 exhibited the highest potential with EC_{50} of 0.37 μM (against CHIKV) to 2.08 μM (against HTNV) (Figure 4b, Table S4). The EC_{50} of P076 and P001 were in the range of 1.62 to 2.67 μM (except for inhibiting DENV-2).

Additionally, we tested the antiviral effects of P135 and P244 from our second round of generation. Both the immunofluorescence and qRT-PCR results showed that these AMPs were active broad-spectrum antiviral peptides against four viruses (Figure S9, S10). In particular, these two AMPs showed a significant inhibition on DENV-2, for which P135 obtained an EC_{50} of 0.09 μM (Table

S3). Hence, we demonstrated the effectiveness of GAN and AMPredictor combined pipeline on

discovering new antiviral peptides.

Combining the EC_{50} and CC_{50} calculations, we calculated the selectivity index ($SI = CC_{50}/EC_{50}$)

as the experimental guides of safety versus efficacy (Table S5). The SI of P002 against four viruses

are 149.21, 31.75, 51.05, and 59.01, three of which outperformed the SI of P001 and P076,

especially for the case of HTNV. Hence, we further observed the performance of P002 with

transmission electron microscopy. For the control set, the viruses were allowed to propagate in

cells for days and identified as assembled particles in cytosol (Figure 5a, b). When the viruses were

mixed with 10 μM P002 before addition to the cells, the viral particles became absent while the

cell morphology kept intact, indicating the broad-spectrum inhibition effects of P002 (Figure 5c,

d).

Because we observed a gradient of antimicrobial and antiviral activities from P001, P002, and

P076 with their individual preferences against bacteria and viruses, we aimed to probe the

interactions between peptides and different phospholipid assemblies, thus deriving feasible means

judging their underlying preferences. We performed all-atom molecular dynamics simulations with

molecular models of bacterial membranes and viral envelopes, placed each peptide adjacent to the

phospholipid bilayers, and simulated them attaching to the membrane (Figure S11a, b). For the

model of Gram-negative bacteria systems, the MM/PBSA calculations and ΔG_{bind} distinguished

P002 from P076 and P001 (Table S10). Evaluated by ΔG_{bind} (-465.79 ± 11.39 kJ/mol), P076 would

associate with the membrane of Gram-negative bacteria tighter than others. For the model of viral

envelopes, all binding energies were weaker than that to bacteria. The ranking of $\Delta G_{nonpolar}$

corroborated with the antiviral potential of P002. Combining this energy term with a geometrical

parameter (average distance between the COM of peptide and phosphorus atoms in the top leaflet

on z-axis) may predict the behavior of P002 better than $\Delta G_{nonpolar}$ alone (Figure S11c).

Figure 5. Transmission electron microscopy (TEM) of viral infection with P002.

a. b. Cells infected with virus, where the red arrows mark the viral particles.

c. Cells are treated with 10 μM P002 and infected with virus (MOI=1), where no viral proliferation is observed.

d. Control of intact cells with 10 μM P002.

All experiments are performed in triplicates.

Membrane-penetration mechanisms

We hypothesized that a common target among bacteria and viruses was the membrane components. To shed light on the possible membrane-penetration abilities of designed peptides, we applied

quantitative measurements, first by focusing on signature components of Gram-negative bacterial

outer membranes. We measured the binding of three peptides to lipopolysaccharide (LPS) via

biolayer interferometry (BLI). More P076 and P001 peptides were recruited to immobilized LPS

than that of P002 at 500 nM (Figure 6b). Further experiments demonstrated that P076 bound to

lipid A, the innermost part of LPS, at an equilibrium dissociation constant (K_D) of 56.1 nM. This

binding affinity of P076 to lipid A was slightly higher than that of P001 (65.7 nM) and was

approximately 2.4-fold less than that of P002 (135 nM, Figure 6a). Then we directly investigated

the membrane permeability by 1-N-phenylnaphthylamine (NPN) uptake assay. NPN is a

fluorescent dye for detecting the impaired outer membrane of Gram-negative bacteria. P076

elicited a stronger membrane penetration relative to P001 and P002 (wavelength scanning in

Figure 6c). Together, our results suggested that P076 could efficiently bind to and damage bacterial

membranes.

To gain a more comprehensive understanding of AMP-membrane interactions with fine content of

amphiphilic assemblies (both outer membranes and inner membranes), we also observed the

membrane attachment and partial insertion of AMPs via all-atom molecular dynamics simulations.

The top leaflet of Gram-negative bacterial outer membranes was built as simplified *E. coli* LPS

(lipid A and R1 core). With an initial equilibrated position above the membrane surface, the peptide

started to approach the oligosaccharides of LPS and then bind to them. During the simulation

processes, P002 and P076 gradually inserted into the outer leaflet, and represented poses binding

to LPS at 100 ns (Figure 6e). We also measured the distance between the COM of peptide and

phosphorus atoms of lipid A on z-axis in the latter 50 ns of trajectories (Figure 6d). Compared with

the initial value about 4 nm (showing as dashed line), this metric of P002 and P076 declined to

less than 2 nm. Nevertheless, P001 performed weaker interactions with an increasing distance,

which was consistent with the membrane-disrupting experiment in Figure 6c. Moreover, three

AMPs tended to attach to the membrane in the MD simulations with lipid bilayer system

mimicking the inner membranes of Gram-negative bacteria (Figure S11b). Collectively,

experimental characterizations along with computational simulations indicate the membrane-

acting mechanisms of our AMPs when playing antimicrobial roles. Further explanation of

membrane-disrupting details or other potential biomolecular targets remains to be explored in the

future.

Figure 6. Bacterial membrane-acting assessment of AMPs.

a. Binding kinetics of three AMPs to lipid A measured by biolayer interferometry.

b. Binding thicknesses of 500 nM AMPs to immobilized LPS within 120 seconds.

c. Fluorescence intensity of NPN after excitation at 350 nm. The maximum emission appeared at

approximately 396 nm, where P001, P002, and P076 were detected higher intensity than control.

d. The distance between COM of peptides and phosphorus atoms of lipid A (around the midplane

of G- bacterial outer membranes) during the last 50 ns of the MD simulation trajectories. The gray

dashed line displays the initial distance at 0 ns.

e. Snapshots of P076 with G- bacterial outer membranes at 0 ns, 50 ns, and 100 ns. Only the top

leaflet (LPS) is shown. Tan balls represent the phosphorus atoms of lipid A molecules.

Discussion

The traditional 'lock and key' model for therapeutic molecule design requires knowledge of target structures.[40] When the targets are biological membranes, the means of docking and ranking by binding affinities (K_D) can easily become futile. The rapid development of deep neural networks, on the other hand, has facilitated self-supervised learning of meaningful molecule representations in hidden dimensions.[29] Combined with vast data of known AMPs, numerous deep learning models have enabled mining of new antibiotics.[18, 19] In the current study, we deployed a new combination of descriptors to extract representations of biological sequences at residual and protein levels. First, we transformed input amino acid sequences into Morgan fingerprints to encode the chemical features of each residue. Second, the scaffolds of AMPs are closely relative to their antimicrobial function, but rarely considered at the structural level in recently reported models (except for sAMPpred-GAT[16]). Instead of using limited amounts of crystal structures, we introduced predicted contact maps of peptides as the edge encoding of peptide graphs. Finally, we added the embedding from ESM as the residue node features to present the associations of a single peptide sequence in the large protein repertoire. ESM was trained on millions of natural protein sequences via mask attention mechanism and assisted in few-shot learning via transferring the related knowledge of protein sequences.[29] The resulting AMPredictor accurately predicted the MICs of three *de novo* design AMPs in our study. As an independent test on 28 new AMPs discovered by different models, AMPredictor also scored well (Table S6).

Despite the ability of deep learning model to guide targeted generation and screen of functional peptides, it lacks the merit of molecular docking program to explicitly consider subtle environmental features. For a particular sequence, we found it was difficult to tell its preference towards bacterial membranes or viral envelopes, due to slight differences in their lipid compositions. Consequently, we observed broad antimicrobial activity for P001, broad antiviral activity for P002, while P076 demonstrated superior capacity on *A. baumannii*. As a control, we made a tiny change of P076 C-terminal with amide modification but observed loss of functions (Table S7). The change of a few atoms on an intact sequence can lead to dramatic functional consequences, which may be challenging for neural networks to capture.

Recent studies indicated unexpected side effects of traditional antibiotics. Instead of restraining
the growth of carbapenem-resistant *Enterobacteriaceae* in the intestine environment, broad-
spectrum antibiotics reduced gut microbial populations and depleted beneficial metabolites, thus
facilitated colonization of *Enterobacteriaceae* species.[41] With more limitations of conventional
small molecule antibiotics discovered, AMPs are attractive alternatives to conventional antibiotic
treatment. Their wide bioactivity spectra can expand to virus, thus minimizing the cost of screen
multiple drugs. Our results suggested efficient *in silico* screen tools plus rigorous experimental
validations could uncover highly potent peptide drugs without comprising on safety, and large-
scale animal experiment could facilitate translation towards clinical research. In summary, we
believe that a mature workflow involving sequence generation and evaluation can promote the
discovery of ideal AMPs to eventually alleviate the hazard of drug-resistant diseases.
494

Methods

Data Curation. Our AMP dataset is collected from PepVAE,[20] containing 3280 antimicrobial peptide sequences with their minimal inhibitory concentrations (MICs) in logarithmic form. To integrate various AMP sequence and bioactivity data, Witten et al. developed the Giant Repository of AMP Activity (GRAMPA).[42] Since the MIC values change when targeting different microbial strains, only AMPs inhibiting *E. coli* are selected. Also, to simplify the input and reduce accidental effect, peptides without modifications are filtered so that no cysteine appears (amino acid composition in Figure S1a). The sequence length of AMPs are less than 40 amino acids, and the majority of lengths ($\sim$ 60%) are between 10 and 20 (Figure S1a). Labels, i.e., logMIC values, are distributed from -1 to 4. During the training process, the dataset is divided into the training, validation, and testing sets in a ratio of 8:1:1 randomly. The entire AMP dataset (3280 sequences) is used for training the generator v1. The AVP dataset for training the generator v2 is collected from AVPdb (accessed in Aug. 2023). AVPs with lengths of more than 60 amino acids are excluded. After removing overlaps with the AMP dataset, 1788 AVPs are kept and added to the training set of generator v2.

Generator. The generative adversarial network (GAN) is composed of a generator network and a discriminator. Through the co-training strategy, the generator evolves to produce ideal sequences from random noises z, fitting the distribution of real samples and faking the discriminator.

$$min_G max_D V(G, D) = E_{x \sim p_{real(x)}}[log D(x)] + E_{z \sim p_{fake(z)}}\left[log\left(1 - D\big(G(z)\big)\right)\right] \qquad (1)$$

For the combined training of GAN generator and discriminator, the AMP sequences were encoded with amino acid factors (AAF). AAF encoding represents five physiochemical values, including the polarity, secondary structures, molecular size, codon diversity, and charges.[27] The GAN architecture was utilized to generate novel AMP sequences, where three layers of 2D convolution were inside both the generator and discriminator.[43] Loss function modified with WGAN-GP strategy was taken to avoid mode collapse, and the optimizer was kept as RMSProp. The learning rate was 1e-4. Cross training ratio between generator and discriminator was set as 1:5. Deep learning-based models were trained on an NVIDIA GeForce RTX 2080 Ti GPU. After training for

1000 epochs, string sequences are calculated via cosine similarity. A batch of sequences were
generated with the limited length of 30 amino acids. Redundant alanine (A) at the end of every
sequence were removed, therefore leaving sequences with variable length.

Predictor. Antimicrobial peptide activity predictor (AMPredictor) was built based on PyTorch
and PyTorch Geometric library. All input sequences were treated with padded zeros to reach
unified lengths of 60. For chemical fingerprint, RDKit (www.rdkit.org) was used to transform each
amino acid into 2048-bit Morgan fingerprint in peptide sequences. For each peptide, the fingerprint
vectors were concatenated and contrasted into a 60-dimensional vector by average.[44] Pretrained
language model esm1b_t33_650M_UR50S was used to provide the embeddings and the contact
maps.

During the training process, the optimizer was Adam, and loss function was the mean squared loss.
Batch size and learning rate were decided upon grid-search, whose values were 128 and 0.001,
respectively (Figure S1b). Evaluation metrics MSE, RMSE, PCC, and CI are calculated as
following:

541
$$MSE = \frac{1}{n}\sum_{1}^{n}(b_i - a_i)^2 \tag{2}$$

542
$$RMSE = \sqrt{\frac{1}{n}\sum_{1}^{n}(b_i - a_i)^2} \tag{3}$$

543
$$PCC = \frac{\sum_{i=1}^{n}(a_i - \bar{a})(b_i - \bar{b})}{\sqrt{\sum_{i=1}^{n}(a_i - \bar{a})^2 \sum_{i=1}^{n}(b_i - \bar{b})^2}} \tag{4}$$

544
$$CI = \frac{1}{Z}\sum_{a_i > a_j} h(b_i - b_j) \tag{5}$$

where a_i is the real activity label of peptide i, and b_i is the predicted activity value, Z is the scale
constant, and $h(b)$ is the step function.

For comparisons in Figure S2, five baseline models were implemented by DeepPurpose package.[45]
The amino acid composition encoding was used as the input of MLP, while one hot encoding was

for CNN, CNN-GRU, and CNN-LSTM. Fragment partition fingerprint of peptides was fed into

the Transformer encoder.

In ablation study, three encoding approaches (chemical fingerprint, contact matrix, and ESM) and

their different combinations were tested individually. It was noted that the peptide graph exists

only when both the node embedding and contact matrix are present together. Therefore, a CNN

with the same number of layers and output dimension was adopted instead of the GCN in ablation

test.

Peptide synthesis. All the peptides were synthesized by DGpeptide Co., ltd. with 95% purity via

solid-phase peptide synthesis procedures. Mass spectrometry was used to verify the molecular

weights (Figure S4, S12-S35).

MIC detection. The minimum inhibitory concentrations (MICs) of peptides against bacteria

including *A. baumannii* (ATCC 19606), multidrug-resistant *A. baumannii* (MDRAB) ,[46] *S.*

aureus (ATCC 25923), methicillin-resistant *S. aureus* (MRSA, ATCC 43300), *E. coli* (ATCC

25922), multidrug-resistant *E. coli* (MDREC),[47] *P. aeruginosa* (PAO1), and multidrug-resistant

P. aeruginosa (MDRPA),[48] were determined using the broth microdilution method recommended

by the Clinical and Laboratory Standards Institute (CLSI) with modifications reported by the

Hancock laboratory.[49] Peptides were prepared in 0.01% acetic acid containing 0.2% BSA at

concentrations of 6.25, 12.5, 25, 50, 100, 200, 400, 800, 1600, and 3200 μg/mL. Bacteria grown

to the mid-logarithmic phase in Meller-Hinton broth (MHB) were diluted to 2×10^5 CFU/mL.

Aliquot of 100 μL of the bacterial suspension was then co-incubated with 11 μL of the peptides at

37°C in a sterile polypropylene microtiter plate (3365, Corning, Shanghai, China). An M2e

microplate reader (Molecular Devices, Silicon Valley, CA, USA) was applied to detect the

bacterial absorbance at 600 nm after 18 h. The recorded MIC was the lowest concentration of

peptides causing a 70% reduction in bacterial turbidity.

Hemolytic assay. The hemolysis of peptides was evaluated as previously described in Ref.[50]

Briefly, the fresh mouse blood was centrifuged at 1000 g for 10 min and washed with cold PBS

three times. The erythrocytes were collected and diluted in saline solution to prepare a 2% (v/v)

suspension. A total of 75 μL of the erythrocyte suspension was co-incubated with 75 μL of the peptides (6.25, 12.5, 25, 50, 100, 200, and 400 μg/mL) at 37°C for 1 h. After centrifuging at 1000 g for 10 min, 60 μL supernatant was obtained, and the absorbance was determined at 414 nm. This experiment was conducted in triplicate and repeated twice.

***In vivo* antibacterial evaluation.** The therapeutic efficacy of P076 peptide against drug-resistant bacteria was analyzed using a mouse peritoneal infection model.[38] The 8-week-old female C57 mice (n = 10) was intraperitoneally administered with 3×10^5 CFU/mL of MDRAB. P076 (2 mg/kg) was given by intraperitoneal injection at 0.5 and 2.5 h after bacterial infection. Ciprofloxacin (CIP, C129896, Aladdin, 32 mg/kg) was employed as the control. Mouse survival was monitored for 48 h. For detection of the bacterial colonization, another 24 mice were randomly divided into four groups (n = 6 for each group). The mice were euthanized 12 h after MDRAB infection, and the peritoneal cavity was rinsed with 2 mL of PBS. Additionally, mouse liver and spleen were obtained by surgery and homogenized in 1 mL of PBS. The lavage fluid and tissue suspension were both diluted for bacterial colony counting using an MHB agar plate as described in MIC detection.

***In vivo* toxicological evaluation.** The 8-week-old female mice (18-22 g) were randomly divided into 14 groups (n = 10 for each group). P076 peptide and polymyxin B (PB, P105490, Aladdin, Shanghai, China) were given to the mice by intraperitoneal injection at 4, 8, 16, 32, 64, and 128 mg/kg. Mouse survival was monitored for 48 h. For pathologic analysis, mouse liver, spleen, and kidneys were obtained by surgery for hematoxylin-eosin (HE) staining after treatment with 64 mg/kg P076 and PB for 12 h. Mice were cared for and treated in accordance with the NIH guidelines for the care and use of laboratory animals (NIH Publication No. 85e23 Rev. 1985). Animal experiments were conducted with approval from the Animal Experimental Ethics Committee of the Army Medical University (AMUWEC20223290).

Cell cultures. Vero-E6 (African green monkey kidney cell line), Huh-7 (Hepatocellular carcinoma cell line), A549 (Human Lung carcinoma cell line) and HeLa-hACE2 were cultured in DMEM (Thermo Fisher Scientific, Waltham, USA) containing 10% fetal bovine serum in a 5% CO_2 incubator at 37°C. HSV-1 and CHIKV were propagated in Vero-E6 cells. DENV-2 and HTNV

were propagated in Huh-7 and A549 cells, respectively. And SARS-CoV-2 were propagated in

HeLa-hACE2 cells.

Cytotoxicity measurements. The Vero-E6, Huh-7 and A549 cells (2×10^4 cells/well) were

inoculated in the 96-well culture plate and grown overnight to 90% confluence at 37°C. The cells

were treated with different concentrations of peptides (P001, P002, and P076) for 1 hour, and the

same concentration of PBS was used as a control. After 48 hours of cell culture, 10% CCK8

solution was added to each well and incubated at 37°C for 1 hour. The absorbance was measured

at 450 nm using a microplate reader. The CC_{50} represents the peptide concentration at the 50% of

viability of uninfected cells.

Immunofluorescence assay. The cells were cultured in a 96-well plate (2×10^4 cells/well).

Different viruses were mixed with P001, P002, or P076 peptides for 10 min before infecting the

cells for 1 h. The infected cells were then cultured with DMEM containing 10% serum for 24-48

h. After discarding the supernatant and washing it three times with PBS, it was permeated with

PBS containing 0.2% Triton X-100 (containing 0.1% BSA) at room temperature for 30 minutes.

Then, the cells were mixed with an antiviral antibody at 4°C overnight. After washing with PBS

three times, the cells were incubated with fluorescence-conjugated secondary antibodies at room

temperature for 1 hour. Cell nuclei were stained using 4',6'- diamidino-2-phenylindole (DAPI) in

the dark for 5 min, and images were obtained by fluorescence microscope.

Real-time PCR. The cells were cultured in a 6-well plate (2×10^5 cells/well) following the same

cell culture procedures as in the immunofluorescence assay. Cellular RNAs were extracted and

purified using a viral RNA extraction kit (Qiagen, Dusseldorf, Germany), and then cDNA was

synthesized and monitored with SuperScript-III kit (Takara, Dalian, China). qRT–PCR analysis

was performed using SYBR Green (BIO-RAD, California, USA) according to the manufacturer's

protocol. Viral RNA expression was calculated using the $2^{-\Delta\Delta C.T.}$ (cycle threshold) method

normalized to GAPDH expression. The qRT–PCR primers sequences for HTNV, CHIKV, HSV-

1 and DENV-2 are listed in the Table S8, while the detection kits (Daan gene, Guangzhou, China)

were used for SARS-CoV-2 wild-type and BA.2 subtype.

Transmission electron microscopy. The cells were cultured in a 6-well plate (2×10^5 cells/well)

following the same cell culture procedures as in the immunofluorescence assay. The virus-infected

cells were collected by centrifugation to prepare cell particles and fixed in cacodylate sodium

buffer containing 1% glutaraldehyde (0.2 M, pH 7.2). The fixed sample was dehydrated by acetone

solution and embedded in epoxy resin. The sample was polymerized at 60°C for 3 days. The resin

block was used to prepare ultrathin slices (50-70 nm thick). These sections were supported by

copper mesh, negatively stained with uranyl acetate and lead citrate (electron microscopy) and

observed with a JEM100SX transmission electron microscope (JEOL, Tokyo, Japan).

Biolayer interferometry. The Octet Red96 BLI platform (Sartorius BioAnalytical Instruments,

Bohemia, USA) was utilized to measure the binding kinetics of three peptides to lipid A (L5399,

Sigma, Shanghai, China). Peptides were diluted with 75 mM NaCl solution at concentrations of

100, 200, 400, and 600 nM. The amine reactive second-generation (AR2G) biosensors were

processed with 1-ehtyl-3-(3-dimethylaminopropy) carbodiimide hydrochloride (EDC, E1769,

Sigma) and sulfo-N-hydroxysulfosuccinimide (s-NHS, 56485, Sigma). Subsequently, lipid A was

loaded onto the activated AR2G biosensors at 30°C for 5 min, and both the processes of association

and disassociation were monitored for 5 min to measure the kinetic constants. The equilibrium

dissociation constant (K_D) was defined as the division of dissociation rate constant (K_{off}) and the

association rate constant (K_{on}). In case of LPS, AR2G biosensors immobilized with 15 μg/mL LPS

(L2880, Sigma) were incubated with 500 nM peptides for 2 min in 75 mM NaCl solution. The

binding thickness was recorded and analyzed using ForteBio Data Analysis 7.0 software.

NPN uptake assay. MDRAB in mid-logarithmic phase was diluted to 1×10^8 CFU/mL in 10 mM

sodium phosphate buffer (pH 7.4). Then 10 μL of each peptide was mixed with 190 μL of MDRAB

at 37°C for 1 hour. Afterwards, 1-N-phenylnaphthylamine (NPN, 104043, Sigma, Shanghai, China)

was added with a final concentration of 10 μM. The fluorescence intensity was assessed with the

wavelength ranging from 380 to 450 nm at 2 nm intervals, after excitation at 350 nm using a Tecan

Infinite M1000 Pro microplate reader (Mannedorf, Zurich, Switzerland). Each experiment was

conducted in duplicate and repeated three times.

Molecular dynamics simulations. The initial structures of peptides were built via AlphaFold2 single sequence version.[51] Lipid bilayer models were constructed by CHARMM-GUI server along with placing parallel peptides approximately 2 nm above the membrane surface.[52] Nine systems were built for three peptides versus three kinds of lipid bilayers (viral envelopes, Gram-negative bacterial inner membranes and outer membranes).[39, 53] Ions of 150 mM NaCl were added to neutralize the system, and the calcium ions were used for LPS in outer leaflet of bacterial outer membranes. Detailed system settings are recorded in Table S9. The standard CHARMM-GUI equilibration protocols including NVT and NPT ensembles were adopted, keeping the temperature at 310K. All-atom MD simulations were performed using GROMACS 2021.2 with the CHARMM36 force field and the TIP3P water model for 100 ns, with a time step of 2 fs.[54, 55] Three independent run was performed for each system. The visual molecular dynamics (VMD) software version 1.9.4 was used for visualization.

The distance between the center of mass (COM) of peptides and phosphorus atoms in top leaflets was calculated via *gmx distance*. Binding free energy was calculated using the molecular mechanics Poisson-Boltzmann surface area (MM/PBSA) method on average of extracted 20 frames from the last 20 ns. The binding free energy of a peptide-membrane complex is calculated as below:

$$\Delta G_{bind} = G_{complex} - (G_{peptide} + G_{membrane}) \tag{6}$$

$$G_{bind} = G_{polar} + G_{nonpolar} = (E_{elec} + G_{psolv}) + (E_{vdw} + G_{sasa}) \tag{7}$$

where E_{elec} is the Coulomb potential, E_{vdw} is the van der Waals energy, G_{psolv} and G_{sasa} are polar and nonpolar solvation free energy. Following previous study, the dielectric constant was set as 7 for phospholipids and the entropy term was neglected.[56]

Data Availability

All the python codes of the AMP design model are available at https://github.com/ruihan-dong/GAN-for-AMP-Design and https://github.com/ruihan-dong/AMPredictor. An online version of AMPredictor can be accessed via https://huggingface.co/spaces/ruihan-dong/AMPredictor.

Acknowledgements

We thank Prof. Chen Song from Peking University for helpful discussion in MD. We also thank Qiaozhen Meng, Yuqian Pu and Nan Song from Tianjin University. This work was supported by the National Key Research and Development Program of China (grant no. 2020YFA0908500), the National Natural Science Foundation of China (grant no. 22007071, 31971127, 81971563, 82272330, 32100122, 62322215), Shanghai Sailing Program (21YF1457800), and Independent Research Project of State Key Laboratory of Trauma and Chemical Poisoning (SKLYQ202101).

Author Contributions

C.Z. and R.D. devised the project. C.Z., S.Y., and H.L. conceived the main conceptual ideas and were in charge of overall direction and planning. R.D. and F.G. developed the computational model. J.W., C.W., and G.Z. measured antimicrobial activities and performed animal experiments. X.W., R.L., Z.L., S.H., X.M., H.K., and J.L. carried out antiviral evaluations. Y.L. and P.Z. carried out anti-SARS-CoV-2 evaluations. C.Z. and R.D. analyzed the data and wrote the paper with input from all authors.

Conflict of Interest

There are no conflicts to declare.

References

1. A. Lewies, L. H. Du Plessis and J. F. Wentzel, Antimicrobial Peptides: the Achilles' Heel of Antibiotic Resistance?, *Probiotics Antimicrob Proteins*, 2019, **11**, 370-381.

2. C. Antimicrobial Resistance, Global burden of bacterial antimicrobial resistance in 2019: a systematic analysis, *Lancet*, 2022, **399**, 629-655.

3. D. M. P. De Oliveira, B. M. Forde, T. J. Kidd, P. N. A. Harris, M. A. Schembri, S. A. Beatson, D. L. Paterson and M. J. Walker, Antimicrobial Resistance in ESKAPE Pathogens, *Clin Microbiol Rev*, 2020, **33**.

4. M. I. Hutchings, A. W. Truman and B. Wilkinson, Antibiotics: past, present and future, *Curr Opin Microbiol*, 2019, **51**, 72-80.

5. Y. Huan, Q. Kong, H. Mou and H. Yi, Antimicrobial Peptides: Classification, Design, Application and Research Progress in Multiple Fields, *Front Microbiol*, 2020, **11**, 582779.

6. M. Mahlapuu, J. Hakansson, L. Ringstad and C. Bjorn, Antimicrobial Peptides: An Emerging Category of Therapeutic Agents, *Front Cell Infect Microbiol*, 2016, **6**, 194.

7. R. Spohn, L. Daruka, V. Lazar, A. Martins, F. Vidovics, G. Grezal, O. Mehi, B. Kintses, M. Szamel, P. K. Jangir, B. Csorgo, A. Gyorkei, Z. Bodi, A. Farago, L. Bodai, I. Foldesi, D. Kata, G. Maroti, B. Pap, R. Wirth, B. Papp and C. Pal, Integrated evolutionary analysis reveals antimicrobial peptides with limited resistance, *Nat Commun*, 2019, **10**, 4538.

8. J. Huang, Y. Xu, Y. Xue, Y. Huang, X. Li, X. Chen, Y. Xu, D. Zhang, P. Zhang, J. Zhao and J. Ji, Identification of potent antimicrobial peptides via a machine-learning pipeline that mines the entire space of peptide sequences, *Nat Biomed Eng*, 2023, **7**, 797-810.

9. G. Wang, X. Li and Z. Wang, APD3: the antimicrobial peptide database as a tool for research and education, *Nucleic Acids Res*, 2016, **44**, D1087-1093.

10. M. Pirtskhalava, A. A. Amstrong, M. Grigolava, M. Chubinidze, E. Alimbarashvili, B. Vishnepolsky, A. Gabrielian, A. Rosenthal, D. E. Hurt and M. Tartakovsky, DBAASP v3: database of antimicrobial/cytotoxic activity and structure of peptides as a resource for development of new therapeutics, *Nucleic Acids Res*, 2021, **49**, D288-D297.

11. G. Shi, X. Kang, F. Dong, Y. Liu, N. Zhu, Y. Hu, H. Xu, X. Lao and H. Zheng, DRAMP 3.0: an enhanced comprehensive data repository of antimicrobial peptides, *Nucleic Acids Res*, 2022, **50**, D488-D496.

12. J. Xu, F. Li, A. Leier, D. Xiang, H. H. Shen, T. T. Marquez Lago, J. Li, D. J. Yu and J. Song, Comprehensive assessment of machine learning-based methods for predicting antimicrobial peptides, *Brief Bioinform*, 2021, **22**.

13. J. Yan, P. Bhadra, A. Li, P. Sethiya, L. Qin, H. K. Tai, K. H. Wong and S. W. I. Siu, Deep-AmPEP30: Improve Short Antimicrobial Peptides Prediction with Deep Learning, *Mol Ther Nucleic Acids*, 2020, **20**, 882-894.

14. C. Li, D. Sutherland, S. A. Hammond, C. Yang, F. Taho, L. Bergman, S. Houston, R. L. Warren, T. Wong, L. M. N. Hoang, C. E. Cameron, C. C. Helbing and I. Birol, AMPlify: attentive deep learning model for discovery of novel antimicrobial peptides effective against WHO priority pathogens, *BMC Genomics*, 2022, **23**, 77.

15. Y. Pang, L. Yao, J. Xu, Z. Wang and T. Y. Lee, Integrating transformer and imbalanced multi-label learning to identify antimicrobial peptides and their functional activities, *Bioinformatics*, 2022, **38**, 5368-5374.

16. K. Yan, H. Lv, Y. Guo, W. Peng and B. Liu, sAMPpred-GAT: prediction of antimicrobial peptide by graph attention network and predicted peptide structure, *Bioinformatics*, 2023, **39**.

17. Y. Ma, Z. Guo, B. Xia, Y. Zhang, X. Liu, Y. Yu, N. Tang, X. Tong, M. Wang, X. Ye, J. Feng, Y. Chen and J. Wang, Identification of antimicrobial peptides from the human gut microbiome using deep learning, *Nat Biotechnol*, 2022, **40**, 921-931.

18. J. Maasch, M. D. T. Torres, M. C. R. Melo and C. de la Fuente-Nunez, Molecular de-extinction of ancient antimicrobial peptides enabled by machine learning, *Cell Host Microbe*, 2023, **31**, 1260-1274 e1266.

19. M. D. T. Torres, M. C. R. Melo, L. Flowers, O. Crescenzi, E. Notomista and C. de la Fuente-Nunez, Mining for encrypted peptide antibiotics in the human proteome, *Nat Biomed Eng*, 2022, **6**, 67-75.

20. S. N. Dean, J. A. E. Alvarez, D. Zabetakis, S. A. Walper and A. P. Malanoski, PepVAE: Variational Autoencoder Framework for Antimicrobial Peptide Generation and Activity Prediction, *Front Microbiol*, 2021, **12**, 725727.

21. P. Das, T. Sercu, K. Wadhawan, I. Padhi, S. Gehrmann, F. Cipcigan, V. Chenthamarakshan, H. Strobelt, C. Dos Santos, P. Y. Chen, Y. Y. Yang, J. P. K. Tan, J. Hedrick, J. Crain and A. Mojsilovic, Accelerated antimicrobial discovery via deep generative models and molecular dynamics simulations, *Nat Biomed Eng*, 2021, **5**, 613-623.

22. P. Szymczak, M. Mozejko, T. Grzegorzek, R. Jurczak, M. Bauer, D. Neubauer, K. Sikora, M. Michalski, J. Sroka, P. Setny, W. Kamysz and E. Szczurek, Discovering highly potent antimicrobial peptides with deep generative model HydrAMP, *Nat Commun*, 2023, **14**, 1453.

23. A. Tucs, D. P. Tran, A. Yumoto, Y. Ito, T. Uzawa and K. Tsuda, Generating Ampicillin-Level Antimicrobial Peptides with Activity-Aware Generative Adversarial Networks, *ACS Omega*, 2020, **5**, 22847-22851.

24. C. M. Van Oort, J. B. Ferrell, J. M. Remington, S. Wshah and J. Li, AMPGAN v2: Machine Learning-Guided Design of Antimicrobial Peptides, *J Chem Inf Model*, 2021, **61**, 2198-2207.

25. A. Pandi, D. Adam, A. Zare, V. T. Trinh, S. L. Schaefer, M. Burt, B. Klabunde, E. Bobkova, M. Kushwaha, Y. Foroughijabbari, P. Braun, C. Spahn, C. Preusser, E. Pogge von Strandmann, H. B. Bode, H. von Buttlar, W. Bertrams, A. L. Jung, F. Abendroth, B.

Schmeck, G. Hummer, O. Vazquez and T. J. Erb, Cell-free biosynthesis combined with
deep learning accelerates de novo-development of antimicrobial peptides, *Nat Commun*,
2023, **14**, 7197.

26.   I. J. Goodfellow, J. Pouget-Abadie, M. Mirza, B. Xu, D. Warde-Farley, S. Ozair, A.
Courville and Y. Bengio, Generative Adversarial Nets, *Adv Neur In*, 2014, **27**, 2672-2680.

27.   W. R. Atchley, J. Zhao, A. D. Fernandes and T. Druke, Solving the protein sequence metric
problem, *Proc Natl Acad Sci U S A*, 2005, **102**, 6395-6400.

28.   A. T. Muller, G. Gabernet, J. A. Hiss and G. Schneider, modlAMP: Python for antimicrobial
peptides, *Bioinformatics*, 2017, **33**, 2753-2755.

29.   A. Rives, J. Meier, T. Sercu, S. Goyal, Z. Lin, J. Liu, D. Guo, M. Ott, C. L. Zitnick, J. Ma
and R. Fergus, Biological structure and function emerge from scaling unsupervised
learning to 250 million protein sequences, *Proc Natl Acad Sci U S A*, 2021, **118**.

30.   A. Qureshi, H. Tandon and M. Kumar, AVP-IC50 Pred: Multiple machine learning
techniques-based prediction of peptide antiviral activity in terms of half maximal inhibitory
concentration (IC50), *Biopolymers*, 2015, **104**, 753-763.

31.   N. Thakur, A. Qureshi and M. Kumar, AVPpred: collection and prediction of highly
effective antiviral peptides, *Nucleic Acids Res*, 2012, **40**, W199-204.

32.   J. Li, Y. Pu, J. Tang, Q. Zou and F. Guo, DeepAVP: A Dual-Channel Deep Neural Network
for Identifying Variable-Length Antiviral Peptides, *IEEE J Biomed Health Inform*, 2020,
24, 3012-3019.

33.   R. Sharma, S. Shrivastava, S. K. Singh, A. Kumar, A. K. Singh and S. Saxena, Deep-
AVPpred: Artificial Intelligence Driven Discovery of Peptide Drugs for Viral Infections,
IEEE J Biomed Health Inform, 2022, **26**, 5067-5074.

34.   P. B. Timmons and C. M. Hewage, ENNAVIA is a novel method which employs neural
networks for antiviral and anti-coronavirus activity prediction for therapeutic peptides,
Brief Bioinform, 2021, **22**.

35.   T. T. Lin, Y. Y. Sun, C. T. Wang, W. C. Cheng, I. H. Lu, C. Y. Lin and S. H. Chen, AI4AVP:
an antiviral peptides predictor in deep learning approach with generative adversarial
network data augmentation, *Bioinform Adv*, 2022, **2**, vbac080.

36.   P. B. Timmons and C. M. Hewage, HAPPENN is a novel tool for hemolytic activity
prediction for therapeutic peptides which employs neural networks, *Sci Rep-Uk*, 2020, **10**.

37.   J. H. Chung, A. Bhat, C. J. Kim, D. Yong and C. M. Ryu, Combination therapy with
polymyxin B and netropsin against clinical isolates of multidrug-resistant Acinetobacter
baumannii, *Sci Rep*, 2016, **6**, 28168.

38.   G. Zhao, C. Jia, C. Zhu, M. Fang, C. Li, Y. Chen, Y. He, S. Han, Y. He, J. Gao, T. Wang, C.
Wang and J. Wang, gamma-Core Guided Antibiotic Design Based on Human Enteric
Defensin 5, *Membranes (Basel)*, 2022, **13**.

39. R. Liu, Z. Liu, H. Peng, Y. Lv, Y. Feng, J. Kang, N. Lu, R. Ma, S. Hou, W. Sun, Q. Ying, F. Wang, Q. Gao, P. Zhao, C. Zhu, Y. Wang and X. Wu, Bomidin: An Optimized Antimicrobial Peptide With Broad Antiviral Activity Against Enveloped Viruses, *Front Immunol*, 2022, **13**, 851642.

40. D. B. Kitchen, H. Decornez, J. R. Furr and J. Bajorath, Docking and scoring in virtual screening for drug discovery: methods and applications, *Nat Rev Drug Discov*, 2004, **3**, 935-949.

41. A. Y. G. Yip, O. G. King, O. Omelchenko, S. Kurkimat, V. Horrocks, P. Mostyn, N. Danckert, R. Ghani, G. Satta, E. Jauneikaite, F. J. Davies, T. B. Clarke, B. H. Mullish, J. R. Marchesi and J. A. K. McDonald, Antibiotics promote intestinal growth of carbapenem-resistant Enterobacteriaceae by enriching nutrients and depleting microbial metabolites, *Nat Commun*, 2023, **14**, 5094.

42. W. Jacob and W. Zack, Deep learning regression model for antimicrobial peptide design, *bioRxiv*, 2019, DOI: 10.1101/692681, 692681.

43. L. Tzu-Tang, Y. Li-Yen, W. Ching-Tien, L. Ga-Wen, K. Chi-Fong, S. Yang-Hsin, C. Shu-Hwa and L. Chung-Yen, Discovering Novel Antimicrobial Peptides in Generative Adversarial Network, *bioRxiv*, 2021, DOI: 10.1101/2021.11.22.469634, 2021.2011.2022.469634.

44. C. K. Schissel, S. Mohapatra, J. M. Wolfe, C. M. Fadzen, K. Bellovoda, C. L. Wu, J. A. Wood, A. B. Malmberg, A. Loas, R. Gómez-Bombarelli and B. L. Pentelute, Deep learning to design nuclear-targeting abiotic miniproteins, *Nat Chem*, 2021, **13**, 992-+.

45. K. X. Huang, T. F. Fu, L. M. Glass, M. Zitnik, C. Xiao and J. M. Sun, DeepPurpose: a deep learning library for drug-target interaction prediction, *Bioinformatics*, 2020, **36**, 5545-5547.

46. C. Wang, G. Zhao, S. Wang, Y. Chen, Y. Gong, S. Chen, Y. Xu, M. Hu, X. Wang, H. Zeng, A. Wang, D. Liu, Y. Su, T. Cheng, F. Chen and J. Wang, A Simplified Derivative of Human Defensin 5 with Potent and Efficient Activity against Multidrug-Resistant Acinetobacter baumannii, *Antimicrob Agents Chemother*, 2018, **62**.

47. G. Zhao, Y. Chen, Y. He, F. Chen, Y. Gong, S. Chen, Y. Xu, Y. Su, C. Wang and J. Wang, Succinylated casein-coated peptide-mesoporous silica nanoparticles as an antibiotic against intestinal bacterial infection, *Biomater Sci*, 2019, **7**, 2440-2451.

48. C. Gao, Y. Wang, Y. Zhang, J. Wei, X. Cheng, J. Zhang, Q. Zou and J. Gu, Complete Genome Sequence of Pseudomonas aeruginosa XN-1, Isolated from the Sputum of a Severe Pneumonia Patient, *Microbiol Resour Announc*, 2020, **9**.

49. M. Wu and R. E. Hancock, Interaction of the cyclic antimicrobial cationic peptide bactenecin with the outer and cytoplasmic membrane, *J Biol Chem*, 1999, **274**, 29-35.

50. A. Oddo and P. R. Hansen, Hemolytic Activity of Antimicrobial Peptides, *Methods Mol Biol*, 2017, **1548**, 427-435.

51. M. Mirdita, K. Schutze, Y. Moriwaki, L. Heo, S. Ovchinnikov and M. Steinegger, ColabFold: making protein folding accessible to all, *Nat Methods*, 2022, **19**, 679-682.

872   52.   E. L. Wu, X. Cheng, S. Jo, H. Rui, K. C. Song, E. M. Davila-Contreras, Y. Qi, J. Lee, V.
873   Monje-Galvan, R. M. Venable, J. B. Klauda and W. Im, CHARMM-GUI Membrane
874   Builder toward realistic biological membrane simulations, *J Comput Chem*, 2014, **35**,
875   1997-2004.

876   53.   R. Allsopp, A. Pavlova, T. Cline, A. M. Salyapongse, R. E. Gillilan, Y. P. Di, B. Deslouches,
877   J. B. Klauda, J. C. Gumbart and S. Tristram-Nagle, Antimicrobial Peptide Mechanism
878   Studied by Scattering-Guided Molecular Dynamics Simulation, *J Phys Chem B*, 2022, **126**,
879   6922-6935.

880   54.   R. B. Best, X. Zhu, J. Shim, P. E. Lopes, J. Mittal, M. Feig and A. D. Mackerell, Jr.,
881   Optimization of the additive CHARMM all-atom protein force field targeting improved
882   sampling of the backbone phi, psi and side-chain chi(1) and chi(2) dihedral angles, *J Chem*
883   *Theory Comput*, 2012, **8**, 3257-3273.

884   55.   J. B. Klauda, R. M. Venable, J. A. Freites, J. W. O'Connor, D. J. Tobias, C. Mondragon-
885   Ramirez, I. Vorobyov, A. D. MacKerell, Jr. and R. W. Pastor, Update of the CHARMM all-
886   atom additive force field for lipids: validation on six lipid types, *J Phys Chem B*, 2010, **114**,
887   7830-7843.

888   56.   J. Lee, S. W. Jung and A. E. Cho, Molecular Insights into the Adsorption Mechanism of
889   Human β-Defensin-3 on Bacterial Membranes, *Langmuir*, 2016, **32**, 1782-1790.