Liquid phase electron microscopy of bacterial ultrastructure.

Authors

Brian J. Caffrey[1*†], Adrián Pedrazo-Tardajos[1†], Emanuela Liberti[1], Ben Gaunt[1], Judy S. Kim[1,2] and Angus I. Kirkland[1,2].

Affiliations

† These authors contributed equally to this work.

[1]The Rosalind Franklin Institute, Harwell Science and Innovation Campus, Didcot, UK

[2]Department of Materials, University of Oxford, Oxford, OX1 3PH, UK

*Corresponding authors: brian.caffrey@rfi.ac.uk

Abstract

Recent advances in liquid phase scanning transmission electron microscopy (LP-STEM) have enabled the study of dynamic biological processes at nanometre resolutions, paving the way for live-cell imaging using electron microscopy. However, this technique is often hampered by the inherent thickness of whole cell samples and damage from electron beam irradiation. These restrictions degrade image quality and resolution, impeding biological interpretation. Here we detail the use of graphene encapsulation, STEM, and energy-dispersive X-ray (EDX) spectroscopy methods to mitigate these issues, providing unprecedented levels of intracellular detail in aqueous specimens. We demonstrate the feasibility of our approach using a radiation resistant, gram-positive bacterium, *Deinococcus radiodurans*, chosen specifically for its tolerance to the highly oxidative environments created by electron irradiation. This work shows the potential of LP-STEM to examine internal cellular structures in thick biological samples and identify key ultrastructure in these samples using a variety of imaging techniques.

Teaser

Liquid phase electron microscopy reveals bacterial ultrastructure using graphene encapsulation.

Introduction

Liquid phase electron microscopy (LP-EM) is a technique that enables the analysis of intracellular, real-time dynamics with nanometre precision in native, hydrated, aqueous environments. This rapidly emerging field of research has provided unique insights into hard materials (*1*), such as the formation of platinum nanocrystals (*2*) and the electrochemical analysis of lithium-ion batteries (*3*). More recently, LP-EM has also expanded to the analysis of biological materials such as proteins (*4*), bacteria (*5*), and even eukaryotic yeast (*6*) and human cells (*7*, *8*). However, ultrastructural analysis of the internal components of these biological materials is difficult due to limitations in sample thickness and electron beam fluence.

Central to addressing these limitations are considerations of the most appropriate imaging geometry for LP-EM imaging of biological samples. Conventional transmission electron microscopy (TEM) is the most widely used imaging technique in biological LP-EM (*9*) and in structural biology more generally (*10*). The popularity of brightfield TEM (BF-TEM) in biological sciences is due, in part, to phase contrast being dominant in low atomic number soft matter samples (*11*). However, spatial resolution in BF-TEM decreases significantly beyond thicknesses greater than the elastic mean free path of electrons in water ($\lambda \sim 300$ nm at 300 kV (*12*)). In addition, as the sample thickness increases the flux in the elastically scattered wavefield decreases reducing the phase contrast even for zero loss filtered images. As most prokaryotic and eukaryotic cells are greater than 500 nm in thickness, conventional BF-TEM has limitations for high-resolution imaging of whole cell samples. Annular darkfield STEM (ADF-STEM) using incoherently scattered electron phase information, can provide superior spatial resolution as it is less affected by the effects of chromatic aberration (*13*), although at the expense of a reduced signal due to weak scattering at high angles from light element materials. The ADF-STEM geometry can also provide valuable complementary information on the elemental composition of biological samples using energy dispersive X-ray (EDX) spectroscopy which, for example, enables the localisation of biominerals with distinct elemental signatures in bacteria (*14*) and in tissue sections to distinguish between different heavy metal conjugated immuno-labels (*15*).

While ADF-STEM can improve image contrast over BF-TEM for thicker samples, the total thickness of the liquid cell in which the specimen is enclosed plays an equally significant role in limiting the achievable resolution and signal-to-noise ratios (SNR) of both LP-ADF-STEM imaging and EDX spectroscopy (*16*). This sample thickness limitation is compounded further by the need for samples to be enclosed in thin membrane windows to partition the sample from the microscope vacuum, e.g. each silicon nitride (Si_3N_4) window in dedicated TEM liquid holders is typically ~50 nm thick, in addition to the liquid/sample thickness. Graphene liquid cells (GLC) can overcome some of the effects from the geometry of commercially available liquid holders, minimising the liquid encapsulation in a single atomic layer,

therefore maximising the achievable imaging and spectral resolution from aqueous environments in LP-
EM applications.

The selection of appropriate biological models are also important to achieving high resolution images of
important biology using LP-EM. The *Deinococcus* genus is distinguished by an extraordinarily high
tolerance to the effects of environmental hazards, such as arsenic (*17*), ionizing and UV irradiation (*18*),
and desiccation (*19*). *D. radiodurans*, the type species of the genus, is a spherical, non-motile, didermal
bacterium and is one of the most radiation-resistant of the *Deinococcus* genus, thirty times more resistant
than the more commonly studied, *Escherichia coli* (*20*). While the biochemical mechanisms underlying this
resistance are not yet fully understood, it is thought that this extreme radiation resistance evolved from its
adaptation to dry environments (*21*) with dehydration being a more common physiological stressor than
environmental radiation. Mechanisms for the unusual radiation resistance of *D.radiodurans* have been
suggested to involve DNA damage resistance and repair pathways, as evidenced by the unusually large
number of (>100) radiation-induced double-strand breaks (DSBs) that this species can withstand without
lethality or mutagenesis. The proteins responsible for these resistance and repair pathways require
protection from the oxidative environments created by irradiation and are therefore highly dependent on
radical oxygen scavenger Mn^{2+} complexes (*22*) and antioxidant carotenoids such as deinoxanthin (*23*).
These chemicals require a rich source of nutrients, in order to maintain effective concentrations. In turn
resistance mechanisms may allow *D.radiodurans* to tolerate electron irradiation for longer, mitigating the
effects of electron beam damage. *D.radiodurans* is therefore an ideal candidate for ultrastructural study
using LP-EM techniques.

In this work, we demonstrate the capabilities of graphene encapsulation and STEM-EDX imaging in studies
of biological specimens in the liquid phase. We use these to provide insights into *D.radiodurans*
ultrastructure using graphene encapsulating environments, localising manganese ions in phosphate-
containing storage granules within the bacterium and demonstrate the ultrastructural response of
D.radiodurans to nutrient restriction and desiccation *in vivo*.

Results

Graphene liquid cell assembly and morphology of *D.radiodurans.*

Using the graphene encapsulation method developed previously (*24*, *25*), it is possible to confine biological samples within graphene encapsulated aqueous environments in standard Au-flat and Au Quantifoil grids (Fig.1A-D). A single-layer graphene grid was submerged in a container with a biological buffer of interest and the sample was pipetted over it. The second layer of graphene was then carefully lowered onto the grid by removing excess buffer from the container and allowed to dry. The encapsulated bacteria were immediately inspected using brightfield light microscopy (LM). In all lysogeny broth (LB) cultures, *D.radiodurans* cells typically formed tightly packed tetrads, with a high degree of asymmetric division and poorly formed central septa in early exponential growth phases and predominantly octads with thick central septa in stationary phase cultures (Fig. S1A-D). In low nutrient media preparations, the cells primarily formed single cocci or diads, as observed previously in studies of *D.radiodurans* nutrient-dependent pleomorphisms (*26*, *27*). The graphene encapsulation appears to be tolerated by *D.radiodurans* as shown by the integrity of the membrane under visual inspection in LM and EM (Fig.1G). Thus, we calculated the approximate value of the sustained pressure on a *D.radiodurans* cell, using the Laplace pressure (*28*), yielding an approximate pressure of 0.5 atmosphere (~50 kPa) (Fig. S2, S3). A more detailed methodology includes different pressure contributions such as Van der Waals and elastic components (*29*), which yields a pressure around 1.6 atmospheres (~162 kPa). This result is in good agreement with both the measured intactness of the membrane (*30*) and the calculated pressure for samples as thick as bacteria or cells (1 µm) using different parameters (*28*). In the case that a direct contact between the pristine graphene and the hydrated membrane of *D.radiodurans* is considered, the estimated pressure is several orders of magnitude lower. See analysis in supplementary information for more details.

Fig.1. Schematic of graphene blister assembly and LM/EM analysis of encapsulated *D.radiodurans*.

A) Freshly prepared single-layer graphene grids placed in water on filter paper, with the second layer of graphene suspended above. **B)** After exchanging water with buffer (HEPES), the sample is added directly to the top of the graphene grids. **C)** Solution is removed slowly to ensure the graphene layer remains intact over the grids. **D)** Solution is completely removed, and grids allowed to air dry. **E)** Expanded view of panel **(D)** of graphene blisters (GB) with encapsulated *D.radiodurans*. **F)** Brightfield light microscope image of DAPI-stained *D.radiodurans* grown in LB broth, indicating nucleoid (cyan) and phosphate granules (magenta). **G)** LP-ADF-LPSTEM image (log grayscale) of encapsulated bacteria at 100kX, with both inner membrane (IM) and outer membrane (OM), along with graphene blister edge (GB) indicated. Scale bars: F: 5 μm; G: 500 nm.

D.radiodurans growth stages, ultrastructure, and elemental distribution.

Imaging whole bacteria provides cellular context to subcellular features, allowing rapid screening of multiple bacteria at different stages of growth and capturing rare cellular events which may be obscured by sample thickness or removed by thinning in conventional cryo-EM studies (*31*).

Bacteria were encapsulated at different phases of the bacterial growth curve; stationary phase bacteria were often found in groups of octads, with multiple high contrast granules present. The periplasmic space between the outer and inner membrane (OM and IM, respectively) was ~90 nm (Fig.2A-B), with a peptidoglycan (PG) component ~35 nm thick and an interstitial layer (IL) ~55 nm thick. This agrees with previously reported descriptions of a dense diffuse periplasmic layer (*32*) and cell envelope thickness measurements from frozen vitrified sections (*33*) of *D.radiodurans*. The surface layer (S-layer), typically reported as a 20 nm thick layer (*33*), was not clearly visible. However, a high contrast layer (HCL), ~55 nm thick, likely containing the S-layer and carbohydrate coat (*34–37*), was observed (Fig.2B).

The characteristic stages of septal growth and cell division in *D.radiodurans* were observed in encapsulated bacteria (Fig.2Ci-ii). Septal growth begins perpendicular to the central septum of the tetrad, dividing a single coccus into two cocci with characteristic septal aversion, as previously reported in conventional EM studies (*38*) (Fig.2D, E). Large phosphate granules were evident in the majority of *D.radiodurans* cocci, with smaller storage granules ranging from 40 – 150 nm in size, potentially used for carbohydrate storage often visible (*39*), as highlighted in Fig.2E. In early exponential cultures, the phosphate granules appeared smaller, were difficult to differentiate from carbohydrate granules and were also more numerous (Fig. S1A). Merging of the septa leads to complete cellular division into two cocci (Fig.2F). Further division into four cocci begins with the formation of septa in the centre of and perpendicular to the previous septum and on opposite sides of the cell walls (Fig.2G). The septa advance from the central and peripheral edges toward the centre of the coccus with a diminishing slit formed between the advancing septal edges (Fig.2H), as observed previously by optical microscopy (*40*) and conventional EM (*38*).

Several asymmetric divisions of cocci were also observed (Fig. S4A), along with s-shaped septal growths from the centre of the cell (Fig. S4 B, C) and multiple diagonally orientated septa at different stages of division (Fig. S4D, E). It was possible to image these structures at fluences as low as ~0.5 e^-/nm^2 (Fig. S5). A fluence of 0.5 e^-/nm^2 is an order of magnitude lower than the fluence threshold for maintaining transcriptionally active *E.coli*, suggesting live cell imaging of these structures may therefore be possible in the near future (*41*). Note, while the terms electron dose and electron fluence are often used interchangeably in the field of electron microscopy, electron fluence is defined as the number of impacted electrons on a sample per unit area, i.e. 100 e^-/nm^2 = 1 e^-/Å^2, and electron dose is strictly defined as the energy absorbed per unit area, expressed in units of Grays. Therefore, in all subsequent images we quote the total cumulative

fluence (TCF) in SI units of e^-/nm^2, which accounts for all electron beam irradiation up to and including the

image shown.

At higher magnifications, some ultrastructural features were visible within the encapsulated cells (Fig.3A;

Fig. S6A-D), including protein (P), DNA, peptidoglycan (PG), septal edges (S) and storage granules (SG).

Protein was dispersed throughout the cell and power spectra (PS) calculated from image areas containing

protein (Fig.3B, red ROI), show enhanced frequencies corresponding to a spacing of 24 ± 8 nm consistent

with bacterial ribosomes, not observed in the PS calculated form the peptidoglycan region, blue ROI (Fig.

3B, Inset; Fig. S6 E-H).

EDX analysis of the IM and PG indicates a relatively high abundance of sulphur. We propose that this

periplasmic layer may act as a reservoir for sulphur-containing amino acids and low molecular weight

thiols, such as cysteine/methionine and bacillithiol, respectively, which are integral to the cells redox

homoeostasis and antioxidant defence system (*42–44*). Most storage granules imaged, were enriched in

phosphorous, oxygen and potassium (Fig.3C, Fig. S7). Other counterions including, magnesium were also

observed to correlate spatially with phosphate granules although the EDX SNR was poor due to the

relatively low fluence used for acquisition. While calcium counterions were also observed in

polyphosphates with *D.radiodurans*, these were relatively rare events and usually only in single

polyphosphate granules within desiccated individuals. Sulphur was found to correlate with the cell

membrane, along with sodium and chlorine (Fig. 3D, 4).

Spherical, low contrast particles were also observed, roughly 30 nm in size, associated with the IM on the

cytoplasmic side and are likely to be similar structures to those previously reported as macromolecular

complexes (MC) (*33*), thought to be Dps2 clusters for iron sequestration (*22*) (Fig.3B). However, there was

no significant iron signal found anywhere within the cell in the EDX maps (Fig. 4). This is possibly due to

iron being dispersed throughout the cell rather than being concentrated in any specific area making the

signal extremely weak in an already relatively low signal map (Fig. S7B).

Fig.2 *D.radiodurans* **growth stages and membrane composition in graphene encapsulated environments.**

A) Bandpass (BP) filtered LP-ADF-STEM section of encapsulated late exponential phase (OD_{600}: 0.65) *D.radiodurans* cell envelope, with the density profile region of interest (ROI) highlighted (TCF: 37,500 e$^-$/nm^2). **B)** Corresponding density profile of cell envelope components reveal a periplasmic space (Pp) between the inner and outer membrane, a peptidoglycan layer (PG) followed by an interstitial layer (IL) and a final high contrast layer (HCL). **C i-ii)** BP filtered LP-ADF-STEM images of encapsulated stationary phase *D.radiodurans* octads at various stages of division from the same sample (TCF: 93 e$^-$/nm^2). **D-H):** Expanded view of single cocci from octad ROIs showing septum progression stages. **D)** Characteristic septal aversions visible. **E)** Septa meeting side on, in the cell centre. Asterisk (*): Small storage granules; Arrowheads: Phosphate storage granules. **F)** Two cocci separated by a completed septum. **G)** New septa begin to emerge perpendicular to the central septum. **H)** Later stage of tetrad formation. Scale bar: A: 100 nm; C i-ii: 1 µm, D-H: 250 nm.

Fig.3 Ultrastructural detail and elemental distribution in *D.radiodurans* **using LP-ADF-STEM and EDX.**

A) BP filtered LP-ADF-STEM and **B)** LP-BF-STEM image of encapsulated bacteria internal structure (TCF: 11,800 e$^-$/nm^2), **Inset:** PS of cytosolic (red) ROI, with spatial frequency at (15 nm)$^{-1}$ marked (dashed red). **C)** EDX spectra of ROIs in **(B)**. **D)** Gaussian filtered and contrast normalized phosphorous and sulphur EDX map of **(A, B)** with membrane and polyphosphate outlines (Dashed white lines) (TCF: 50,300 e$^-$/nm^2). Scale bar for A, B,D: 250 nm; PS: (2 nm^{-1})**.**

Manganese accumulates in bacterial phosphate granules.

Manganese is implicated in *D.radiodurans* radiation resistance and appear to localise with phosphate ions (*22*) suggesting that manganese acts as a counterion to cellular phosphate. Using EDX analysis, at biologically relevant fluences i.e. <3,000 e⁻/nm² (*45*), we confirm that manganese localizes to phosphate granules following $MnCl_2$ supplementation of bacterial media (Fig. 4; Fig. S8A). However, we were unable to observe accumulations of naturally occurring manganese-containing polyphosphates in *D.radiodurans* at the fluences used to record the maps (Fig. S8 B, C). These manganese-containing phosphate granules may act as a store of reactive oxygen species-scavenging manganese cations for release during oxidative stress.

Fig.4 Manganese accumulates in bacterial phosphate granules.
Summed LP-ADF-STEM image of bacteria incubated in $MnCl_2$ (Average TCF: 2,979 e⁻/nm²). **Top Row:** Intracellular elements; **Middle row:** Cell membrane associated elements; **Bottom Row:** Polyphosphate associated elements. Scale bar: 500 nm

Vacuum desiccation in *D.radiodurans* leads to separation of cell membrane, a marker for liquid encapsulation.

To assess the effect of vacuum desiccation on *D.radiodurans*, a sample exponentially growing bacteria were placed on a graphene grid as previously mentioned, however after a short period (<5 mins) of drying the grid was placed directly into the microscope. Bacteria exposed to the vacuum detached from their membranes causing large cracks to form (Fig.5A). These characteristic cracks, act as an internal standard for verification of encapsulation, making selection of regions of interest (ROI) straightforward even at relatively low fluences (<1 e$^-$/nm^2). This reduces the requisite pre-acquisition fluence budget (*46*), thus allowing more fluence to be used for single frame high resolution imaging or multi-frame, dynamic time course experiments.

Nutrient restriction leads to enrichment of different *D.radiodurans* pleomorphs.

As *D.radiourans* demonstrates nutrient-induced pleomorphisms (*26*), we decided to grow *D.radiodurans* in nutrient-restricted conditions (10% v/v LB media) in an effort to explore the different ultrastructure of these pleomorphs and to create smaller cell volumes to potentially enable three-dimensional data acquisition using LP-STEM tomography. It was readily apparent using light microscopy that nutrient-restriction dramatically reduces the number of tetrads and increases the number of monad and diads in solution. This was confirmed in the electron microscope, as most bacteria present were diad forms. While the diads did appear to have a less dense cytoplasm than tetrads there was little difference in the ultrastructural features, with the primary difference being a more spherical shape rather than ellipsoidal. Interestingly, in some individuals it was clear that the peptidoglycan wall between two individuals was in a ring shape rather than a singular partition suggesting that there may be significant intercell communication in these diads at this stage of growth (Fig.5B). We also observed diads which do not display this ring-shaped aperture and instead had a typical peptidoglycan partition, these appeared more ellipsoidal, suggesting that there may be a need for this type of aperture at this specific stage of cell growth. A similar decrease in the ellipticity of the cells at specific growth phases has been observed previously by high resolution light microscopy (*40*).

266
267 **Fig.5 Effect of different environmental stressors on *D.radiodurans* ultrastructure.**
268 **A)** LP-ADF-STEM image of vacuum desiccated bacteria in a torn graphene liquid cell (TCF: 93 e^-/nm^2);
269 Dashed red line: Tear in graphene, White arrows: Examples of desiccation-related membrane separation.
270 **B)** LP-ADF-STEM image of encapsulated diad, grown in 10% LB media (TCF: 2,334 e^-/nm^2); Dashed
271 yellow line: Ring shaped membrane between individuals. Scale bar: A: 2 μm; B: 500 nm.
272

Discussion

The LP-STEM studies presented here demonstrate an effective technique for imaging whole biological
specimens and their internal ultrastructure in native aqueous environments, without the need for heavy-
metal staining, nanoparticle tagging, cryogenic/plastic preservation requiring specialized equipment and
leading to potential artefacts. The graphene liquid cells used, prepared from relatively simple materials,
provide high contrast for LP-EM analysis. In combination with STEM-EDX techniques, they can provide
greater internal information than other native preparation approaches, such as conventional whole-cell cryo-
transmission electron microscopy/tomography techniques where samples contain layers of vitreous ice.

As the graphene liquid cells are prepared on EM grids, they can fit in most standard EM holders. Unlike
commercially available silicon nitride chip liquid cells, the nature of GLCs means each graphene blister is
an independent liquid cell, keeping potential hydrolysis products from the electron beam localised to a
single blister and preventing the build-up and diffusion of free radicals casing damage in adjacent cells.
The isolated nature of graphene blisters also means that in the event of a failure of a single liquid cell, there
is no significant release of liquid inside the microscope column. This contrasts with conventional silicon
nitride chip liquid cell applications where failure of the chip may lead to the release of larger volumes of
liquid and gases in the column and where great care is required to ensure the liquid cell remains sealed.

However, the most significant advance in imaging quality is the electron transparency of the graphene and
thinner liquid volume.

There are several variables that we found to significantly affect sample quality and sensitivity and image
SNR. For example, we found that while gold Au-flat grids produced a tighter encapsulation and more
reproducible number of blisters, gold Quantifoil grids gave images with better SNR over larger fields-of-
view. Additionally, buffer composition is a significant factor; the use of phosphate buffered saline led to
substantial amounts of salt precipitates on the grid obscuring the field-of-view. We therefore used a simpler
zwitterionic buffer, HEPES, for our experiments. Degassing before encapsulation was also essential to limit
the formation of gas bubbles in the buffer under the electron beam.

Our study emphasises the importance of selecting suitable model organisms for study in LP-EM.
D.radiodurans has proven to be an extremely valuable test sample for exploring LP-EM/EDX capabilities
due to its radiation resistance, elementally heterogenous nature and round coccoid shape, which lends itself
readily to study in GLCs. Previously, it was shown that in transcriptionally active *E.coli*, 50% of the
population received a lethal fluence (LF$_{50}$) at ~10 e$^-$/nm^2, in commercially available silicon nitride chips
(*41*). However, *D.radiodurans* is known to tolerate fluences at least tenfold greater in magnitude than
E.coli, suggesting an LF$_{50}$ of *D.radiodurans* under the same circumstances of approximately 100 e$^-$/nm^2.
This fluence limit is further increased by the 2-7x protection factor afforded by graphene encapsulation
(*47–49*), potentially leading the way for low fluence live-cell imaging in LP-STEM. Our observations of
proteins at ~24 nm and other biomolecules within these bacterial cells suggest that even at cumulative
fluences significantly higher than the putative LF$_{50}$ of *D.radiodurans*, it may still be more favorable to
monitor protein dynamics and interactions *in situ* than in purified protein solutions, with beam-related
damage potentially mitigated by the native reactive oxygen defense system of *D.radiodurans*.
D.radiodurans response to desiccation by creating cracks in their membrane from rapid depressurization in
the microscope vacuum, also demonstrate their utility in LPEM analysis, by acting as an internal marker
for aqueous environments within the electron microscope.

We have also demonstrated the use of LP-STEM-EDX applications to build an elemental understanding of
the bacterial cell at the ultrastructural level. LP-STEM-EDX has enabled us to demonstrate that Mn ions
localize to polyphosphate granules *in situ*, without the need for denaturants and fixatives. We have also
mapped significant concentrations of sulphur residing in the periplasm, suggesting a potential mechanism
for oxidative homeostasis in *D.radiodurans*. This periplasmic sulphur may help manage redox homeostasis
within *D.radiodurans*, being released into the cytoplasm on irradiation to help inhibit oxidative damage
induced by free radicals and protect biomolecules critical to cellular survival. These LP-STEM-EDX

studies demonstrate the potential to use both native elemental distributions and non-native elemental probes
to localise biomolecules and structures of interest within a cell.

Finally, this study is a proof of principal showing how LP-STEM-EDX enables the analysis of large-scale
cellular events, such as cell division, under relatively low fluence conditions (<100 e$^-$/nm^2) and can resolve
even finer ultrastructural details, such as proteins and nucleic acids albeit at a higher fluence. The techniques
described herein illustrate the potential of LP-EM to explore fundamental biological questions *in situ*.
Electron fluence, sample thickness and the fundamental characteristics of graphene, such as its grain size,
may however limit its broader application to larger cells and tissues. Ultimately, LP-EM techniques
combined with emerging low-fluence imaging applications such as ptychography (*50, 51*) and compressive
sensing (*52*) mean that imaging cellular dynamics *in vivo* at sub-nanometre resolutions in an electron
microscope may soon be achievable.

Materials and Methods

Growth of *D. radiodurans*

5 ml of Lysogeny Broth (LB) was inoculated with *D. radiodurans* (Strain R$_1$; DSMZ 20539) frozen culture
and incubated at 30 °C for 24hrs with shaking. 500 µl of the resulting culture was added to 5 ml of fresh
LB [1% w/v Glucose] and after this reached early exponential phase (OD$_{600}$: ~0.3) was further incubated
and then collected at different time points: 15 min (early exponential phase, A600 nm = 0.35), 2 h (mid-
exponential phase, A600 nm = 0.65) and 20 h (stationary phase, A600 nm = 1.65). For the Mn accumulation
experiment, early exponential phase bacteria were incubated with sterile-filtered MnCl$_2$ [0.1 or 1 mM] for
4hrs, then spun down and encapsulated. A control growth with water was performed and followed
simultaneously. For the restrictive media experiment, 500 µl of stationary phase bacteria were added to 5ml
of fresh 10% LB media in ddH$_2$O [1% w/v Glucose] and incubated overnight. 2ml of the resulting samples
were then spun down at 500g for the LB preparations and 2000g for the restrictive preparations for 5 mins,
resuspended in 1 ml of nitrogen degassed 4-(2-hydroxyethyl)-1-piperazineethanesulfonic acid (HEPES)
buffer [25 mM] and encapsulated in graphene for LP-STEM/EDX imaging.

Brightfield light microscopy imaging of DAPI-stained *D.radiodurans*
Imaging was carried out with an upright brightfield light microscope, Eclipse Ni (Nikon, USA) using 10x
and 40x air immersion objectives.

Graphene liquid cell encapsulation
The hydrated graphene enclosed environments were obtained by first creating a graphene TEM grid by
transferring graphene to a TEM grid using cellulose acetate butyrate (*53*) followed by a dry-cleaning
procedure (*54*) at 310 °C overnight. This is the basis of the liquid cell. The top graphene layer for

encapsulation was fabricated using a polymer-free transfer method (*55*), which provides a flat top surface to the hydrated environment which then adapts to the morphology of the target. The main steps are described in detail in refs (*56*) and (*25*) to prepare the base TEM grid and the creation of the encapsulated environments respectively (*57*).

The commercial based TEM grids used throughout the different experiments to create the hydrated encapsulated environments were Au-Flat (2/2) 300 Mesh, 45nm Thick from Protochips and Au Quantifoil R1.2/1.3 300 mesh from Quantifoil.

Liquid phase STEM imaging

All STEM imaging was performed on a 300kV GRAND-ARM 2 (JEOL) with a spherical aberration corrector, with an illumination semi-angle (α) of 15.95 mrad and annular dark-field (ADF) [Inner collection semi-angle (β^{in}: 37.1 mrad)/Outer collection semi-angle (β^{out}: 83 mrad), limited by the differential pumping aperture and bright-field (BF) detectors (β_{BF}: 20.8 mrad). The microscope was aligned using the standard gold waffle thin film. Images of aqueous bacteria were typically recorded at 20 kX, 100 kX and 200 kX magnifications (pixel size: 5, 1 and 0.5 nm respectively), 2048 x 2048 frame size and 20 μs dwell time.

Liquid phase EDX imaging

Energy-dispersive X-ray spectroscopy was performed in STEM mode on a 300kV GRAND-ARM 2 (JEOL) on aqueous bacterial samples at 20kX, 100 kX and 200 kX magnifications (pixel size: 20, 4 and 2 nm) respectively), 512 x 512 frame size and 20 μs dwell times, using dual liquid N_2 cooled Si (Li) JEOL detectors with a combined solid angle of 1.41 sr.

STEM/EDX Image preprocessing

To enhance high-resolution details and to remove background noise, a Gaussian bandpass filter was applied to each micrograph (High Pass :300 px/Low Pass:2 px), using the ImageJ Bandpass filter plugin. Horizontal STEM scanning artefacts were smoothed using the "Suppress Stripes" function at 5% in the ImageJ Bandpass filter plugin. All images were then normalised with 0.35% pixel saturation, using the "Contrast Enhance" function in ImageJ.

EDX maps were produced in JEOL Analysis Station Software and processed in Hyperspy (*58*). Maps were binned by 2 in x-y and Gaussian filtered ($\sigma = 2$ px) to remove noise, using the "Gaussian Blur" function in ImageJ. All maps were then contrast normalised with 0% pixel saturation, using the "Contrast Enhance" function in ImageJ. All maps were generated using the respective elemental Kα lines.

384 **Fluence History Tracking with Axon Studio**

385 The Axon Studio software from Protochips Inc., was used in conjunction with Axon Dose to accurately

386 track the fluence history of each imaged area, providing an accurate readout of specimen total cumulative

387 fluence.

References

1. S. Pu, C. Gong, A. W. Robertson, Liquid cell transmission electron microscopy and its applications. *R. Soc. Open Sci.* (2020), , doi:10.1098/rsos.191204.

2. H. Zheng, R. K. Smith, Y. W. Jun, C. Kisielowski, U. Dahmen, A. Paul Alivisatos, Observation of single colloidal platinum nanocrystal growth trajectories. *Science (80-.).* (2009), doi:10.1126/science.1172104.

3. B. L. Mehdi, J. Qian, E. Nasybulin, C. Park, D. A. Welch, R. Faller, H. Mehta, W. A. Henderson, W. Xu, C. M. Wang, J. E. Evans, J. Liu, J. G. Zhang, K. T. Mueller, N. D. Browning, Observation and quantification of nanoscale processes in lithium batteries by operando electrochemical (S)TEM. *Nano Lett.* (2015), doi:10.1021/acs.nanolett.5b00175.

4. C. Wang, Q. Qiao, T. Shokuhfar, R. F. Klie, High-resolution electron microscopy and spectroscopy of ferritin in biocompatible graphene liquid cells and graphene sandwiches. *Adv. Mater.* (2014), doi:10.1002/adma.201306069.

5. E. Kennedy, E. M. Nelson, T. Tanaka, J. Damiano, G. Timp, Live Bacterial Physiology Visualized with 5 nm Resolution Using Scanning Transmission Electron Microscopy. *ACS Nano* (2016), doi:10.1021/acsnano.5b07697.

6. D. B. Peckys, P. Mazur, K. L. Gould, N. De Jonge, Fully hydrated yeast cells imaged with electron microscopy. *Biophys. J.* (2011), doi:10.1016/j.bpj.2011.03.045.

7. D. B. Peckys, U. Korf, N. De Jonge, Local variations of HER2 dimerization in breast cancer cells discovered by correlative fluorescence and liquid electron microscopy. *Sci. Adv.* (2015), doi:10.1126/sciadv.1500165.

8. L. Kong, J. Liu, M. Zhang, Z. Lu, H. Xue, A. Ren, J. Liu, J. Li, W. Li Ling, G. Ren, Facile hermetic TEM grid preparation for molecular imaging of hydrated biological samples at room temperature. *Nat. Commun.* **14** (2023).

9. H. Wu, H. Friedrich, J. P. Patterson, N. A. J. M. Sommerdijk, N. de Jonge, Liquid-Phase Electron Microscopy for Soft Matter Science and Biology. *Adv. Mater.* (2020), doi:10.1002/adma.202001582.

10. H. R. Saibil, Cryo-EM in molecular and cellular biology. *Mol. Cell* (2022), doi:10.1016/j.molcel.2021.12.016.

11. N. de Jonge, Theory of the spatial resolution of (scanning) transmission electron microscopy in liquid water or ice layers. *Ultramicroscopy* (2018), doi:10.1016/j.ultramic.2018.01.007.

12. M. N. Yesibolati, S. Laganá, S. Kadkhodazadeh, E. K. Mikkelsen, H. Sun, T. Kasama, O. Hansen, N. J. Zaluzec, K. Mølhave, Electron inelastic mean free path in water. *Nanoscale* (2020), doi:10.1039/d0nr04352d.

13. P. Rez, T. Larsen, M. Elbaum, Exploring the theoretical basis and limitations of cryo-STEM tomography for thick biological specimens. *J. Struct. Biol.* (2016), doi:10.1016/j.jsb.2016.09.014.

14. J. Miot, D. Jézéquel, K. Benzerara, L. Cordier, S. Rivas-Lamelo, F. Skouri-Panet, C. Férard, M. Poinsot, E. Duprat, Mineralogical diversity in Lake Pavin: Connections with water column chemistry and biomineralization processes. *Minerals* (2016), doi:10.3390/min6020024.

15. M. Scotuzzi, J. Kuipers, D. I. Wensveen, P. De Boer, K. C. W. Hagen, J. P. Hoogenboom, B. N. G. Giepmans, Multi-color electron microscopy by element-guided identification of cells, organelles and molecules. *Sci. Rep.* (2017), doi:10.1038/srep45970.

16. D. J. Kelly, M. Zhou, N. Clark, M. J. Hamer, E. A. Lewis, A. M. Rakowski, S. J. Haigh, R. V. Gorbachev, Nanometer Resolution Elemental Mapping in Graphene-Based TEM Liquid Cells. *Nano Lett.* (2018), doi:10.1021/acs.nanolett.7b04713.

17. K. Suresh, G. S. N. Reddy, S. Sengupta, S. Shivaji, Deinococcus indicus sp. nov., an arsenic-resistant bacterium from an aquifer in West Bengal, India. *Int. J. Syst. Evol. Microbiol.* (2004), doi:10.1099/ijs.0.02758-0.

18. M. M. Cox, J. R. Battista, Deinococcus radiodurans - The consummate survivor. *Nat. Rev. Microbiol.* (2005), , doi:10.1038/nrmicro1264.

19. M. Tanaka, A. M. Earl, H. A. Howell, M. J. Park, J. A. Eisen, S. N. Peterson, J. R. Battista, Analysis of Deinococcus radiodurans's transcriptional response to ionizing radiation and desiccation reveals novel proteins that contribute to extreme radioresistance. *Genetics* (2004), doi:10.1534/genetics.104.029249.

20. M. J. Daly, A new perspective on radiation resistance based on Deinococcus radiodurans. *Nat. Rev. Microbiol.* (2009), doi:10.1038/nrmicro2073.

21. V. Mattimore, J. R. Battista, Radioresistance of Deinococcus radiodurans: Functions necessary to survive ionizing radiation are also necessary to survive prolonged desiccation. *J. Bacteriol.* (1996), doi:10.1128/jb.178.3.633-637.1996.

22. S. P. Santos, Y. Yang, M. T. G. Rosa, M. A. A. Rodrigues, C. B. De La Tour, S. Sommer, M. Teixeira, M. A. Carrondo, P. Cloetens, I. A. Abreu, C. V. Romão, The interplay between Mn and Fe in Deinococcus radiodurans triggers cellular protection during paraquat-induced oxidative stress. *Sci. Rep.* (2019), doi:10.1038/s41598-019-53140-2.

23. L. Lemee, E. Peuchant, M. Clerc, M. Brunner, H. Pfander, Deinoxanthin: A new carotenoid isolated from Deinococcus radiodurans. *Tetrahedron* (1997), doi:10.1016/S0040-4020(96)01036-8.

24. J. M. Yuk, J. Park, P. Ercius, K. Kim, D. J. Hellebusch, M. F. Crommie, J. Y. Lee, A. Zettl, A. P. Alivisatos, High-resolution EM of colloidal nanocrystal growth using graphene liquid cells.

457  *Science (80-.)*. (2012), doi:10.1126/science.1217654.

25. N. Jain, Y. Hao, U. Parekh, M. Kaltenegger, A. Pedrazo-Tardajos, R. Lazzaroni, R. Resel, Y. H. Geerts, S. Bals, S. Van Aert, Exploring the effects of graphene and temperature in reducing electron beam damage: A TEM and electron diffraction-based quantitative study on Lead Phthalocyanine (PbPc) crystals. *Micron* (2023), doi:10.1016/j.micron.2023.103444.

26. H. M. Joshi, R. S. Toleti, Nutrition induced pleomorphism and budding mode of reproduction in Deinococcus radiodurans. *BMC Res. Notes* (2009), doi:10.1186/1756-0500-2-123.

27. S. K. Shukla, G. Gomathi Sankar, A. Paraneeiswaran, T. Subba Rao, Differential radio-tolerance of nutrition-induced morphotypes of Deinococcus radiodurans R1. *Curr. Microbiol.* (2014), doi:10.1007/s00284-013-0472-9.

28. S. M. Ghodsi, S. Sharifi-Asl, P. Rehak, P. Král, C. M. Megaridis, R. Shahbazian-Yassar, T. Shokuhfar, Assessment of Pressure and Density of Confined Water in Graphene Liquid Cells. *Adv. Mater. Interfaces* (2020), doi:10.1002/admi.201901727.

29. E. Khestanova, F. Guinea, L. Fumagalli, A. K. Geim, I. V. Grigorieva, Universal shape and pressure inside bubbles appearing in van der Waals heterostructures. *Nat. Commun.* (2016), doi:10.1038/ncomms12587.

30. R. Al Faouri, R. Henry, A. S. Biris, R. Sleezer, G. J. Salamo, Adhesive force between graphene nanoscale flakes and living biological cells. *J. Appl. Toxicol.* (2017), doi:10.1002/jat.3478.

31. K. Khanna, E. Villa, Revealing bacterial cell biology using cryo-electron tomography. *Curr. Opin. Struct. Biol.* (2022), , doi:10.1016/j.sbi.2022.102419.

32. M. Eltsov, J. Dubochet, Fine structure of the Deinococcus radiodurans nucleoid revealed by cryoelectron microscopy of vitreous sections. *J. Bacteriol.* (2005), doi:10.1128/JB.187.23.8047-8054.2005.

33. D. L. Sexton, S. Burgold, A. Schertel, E. I. Tocheva, Super-resolution confocal cryo-CLEM with cryo-FIB milling for in situ imaging of Deinococcus radiodurans. *Curr. Res. Struct. Biol.* (2022), doi:10.1016/j.crstbi.2021.12.001.

34. H. Rothfuss, J. C. Lara, A. K. Schmid, M. E. Lidstrom, Involvement of the S-layer proteins Hpi and SlpA in the maintenance of cell envelope integrity in Deinococcus radiodurans R1. *Microbiology* (2006), doi:10.1099/mic.0.28971-0.

35. F. H. Karrenberg, I. Wildhaber, W. Baumeister, Surface structure variants in Deinococcus radiodurans. *Curr. Microbiol.* (1987), doi:10.1007/BF01568163.

36. A. von Kügelgen, S. van Dorst, V. Alva, T. A. M. Bharat, A multidomain connector links the outer membrane and cell wall in phylogenetically deep-branching bacteria. *Proc. Natl. Acad. Sci. U. S. A.* (2022), doi:10.1073/pnas.2203156119.

37. A. von Kügelgen, S. van Dorst, K. Yamashita, D. L. Sexton, E. I. Tocheva, G. Murshudov, V. Alva, T. A. M. Bharat, Interdigitated immunoglobulin arrays form the hyperstable surface layer of the extremophilic bacterium Deinococcus radiodurans. *Proc. Natl. Acad. Sci. U. S. A.* (2023), doi:10.1073/pnas.2215808120.

38. R. G. E. Murray, M. Hall, B. G. Thompson, Cell division in Deinococcus radiodurans and a method for displaying septa. *Can. J. Microbiol.* (1983), doi:10.1139/m83-217.

39. D. Slade, M. Radman, Oxidative Stress Resistance in Deinococcus radiodurans . *Microbiol. Mol. Biol. Rev.* (2011), doi:10.1128/mmbr.00015-10.

40. K. Floc'h, F. Lacroix, P. Servant, Y. S. Wong, J. P. Kleman, D. Bourgeois, J. Timmins, Cell morphology and nucleoid dynamics in dividing Deinococcus radiodurans. *Nat. Commun.* (2019), doi:10.1038/s41467-019-11725-5.

41. E. Kennedy, E. M. Nelson, J. Damiano, G. Timp, Gene Expression in Electron-Beam-Irradiated Bacteria in Reply to "live Cell Electron Microscopy Is Probably Impossible." *ACS Nano* (2017), , doi:10.1021/acsnano.6b06616.

42. J. D. Helmann, Bacillithiol, a new player in bacterial redox homeostasis. *Antioxidants Redox Signal.* (2011), , doi:10.1089/ars.2010.3562.

43. G. L. Newton, M. Rawat, J. J. La Clair, V. K. Jothivasan, T. Budiarto, C. J. Hamilton, A. Claiborne, J. D. Helmann, R. C. Fahey, Bacillithiol is an antioxidant thiol produced in Bacilli. *Nat. Chem. Biol.* (2009), doi:10.1038/nchembio.189.

44. Y. Xiong, L. Wei, S. Xin, R. Min, F. Liu, N. Li, Y. Zhang, Comprehensive Temporal Protein Dynamics during Postirradiation Recovery in Deinococcus radiodurans. *Oxid. Med. Cell. Longev.* (2022), doi:10.1155/2022/1622829.

45. T. Grant, N. Grigorieff, Measuring the optimal exposure for single particle cryo-EM using a 2.6 Å reconstruction of rotavirus VP6. *Elife* (2015), doi:10.7554/eLife.06980.

46. M. Ilett, M. S'Ari, H. Freeman, Z. Aslam, N. Koniuch, M. Afzali, J. Cattle, R. Hooley, T. Roncal-Herrero, S. M. Collins, N. Hondow, A. Brown, R. Brydson, Analysis of complex, beam-sensitive materials by transmission electron microscopy and associated techniques: TEM of Beam Sensitive Materials. *Philos. Trans. R. Soc. A Math. Phys. Eng. Sci.* (2020), , doi:10.1098/rsta.2019.0601.

47. G. Algara-Siller, S. Kurasch, M. Sedighi, O. Lehtinen, U. Kaiser, The pristine atomic structure of MoS2 monolayer protected from electron radiation damage by graphene. *Appl. Phys. Lett.* (2013), doi:10.1063/1.4830036.

48. B. Janicek, P. Kharel, S. hyun Bae, P. Huang, Quantifying the Protection Factor of Graphene Substrates for Atomic-scale Imaging of Organic Crystals. *Microsc. Microanal.* (2020), doi:10.1017/s1431927620015834.

49. H. Cho, M. R. Jones, S. C. Nguyen, M. R. Hauwiller, A. Zettl, A. P. Alivisatos, The use of
graphene and its derivatives for liquid-phase transmission electron microscopy of radiation-
sensitive specimens. *Nano Lett.* (2017), doi:10.1021/acs.nanolett.6b04383.

50. Z. Ding, S. Gao, W. Fang, C. Huang, L. Zhou, X. Pei, X. Liu, X. Pan, C. Fan, A. I. Kirkland, P.
Wang, Three-dimensional electron ptychography of organic–inorganic hybrid nanostructures. *Nat.*
Commun. (2022), doi:10.1038/s41467-022-32548-x.

51. C. Huang, J. S. Kim, A. I. Kirkland, Cryo-electron ptychography: Applications and potential in
biological characterisation. *Curr. Opin. Struct. Biol.* **83**, 102730 (2023).

52. D. Nicholls, J. Wells, A. Stevens, Y. Zheng, J. Castagna, N. D. Browning, Sub-Sampled Imaging
for STEM: Maximising Image Speed, Resolution and Precision Through Reconstruction
Parameter Refinement. *Ultramicroscopy* (2022), doi:10.1016/j.ultramic.2021.113451.

53. G. Burwell, N. Smith, O. Guy, Investigation of the utility of cellulose acetate butyrate in minimal
residue graphene transfer, lithography, and plasma treatments. *Microelectron. Eng.* (2015),
doi:10.1016/j.mee.2015.04.097.

54. G. Algara-Siller, O. Lehtinen, A. Turchanin, U. Kaiser, Dry-cleaning of graphene. *Appl. Phys.*
Lett. (2014), doi:10.1063/1.4871997.

55. W. Regan, N. Alem, B. Alemán, B. Geng, Ç. Girit, L. Maserati, F. Wang, M. Crommie, A. Zettl,
A direct transfer of layer-area graphene. *Appl. Phys. Lett.* (2010), doi:10.1063/1.3337091.

56. Y. Zhang, J. P. van Schayck, A. Pedrazo-Tardajos, N. Claes, W. E. M. Noteborn, P. H. Lu, H.
Duimel, R. E. Dunin-Borkowski, S. Bals, P. J. Peters, R. B. G. Ravelli, Charging of Vitreous
Samples in Cryogenic Electron Microscopy Mitigated by Graphene. *ACS Nano* (2023),
doi:10.1021/acsnano.3c03722.

57. A. Pedrazo-Tardajos, S. Bals, GRAPHENE LAYER TRANSFER METHOD (2020), (available at
https://patents.google.com/patent/EP4011828A1/en?oq=EP4011828A1).

58. F. de la Peña, E. Prestat, V. T. Fauske, P. Burdet, J. Lähnemann, P. Jokubauskas, T. Furnival, M.
Nord, T. Ostasevicius, K. E. MacArthur, D. N. Johnstone, M. Sarahan, J. Taillon, T. Aarholt,
pquinn-dls, V. Migunov, A. Eljarrat, J. Caron, C. Francis, T. Nemoto, T. Poon, S. Mazzucco,
actions-user, N. Tappy, N. Cautaerts, S. Somnath, T. Slater, M. Walls, F. Winkler, H. W. Ånes,
hyperspy/hyperspy: Release v1.7.3 (2022), , doi:10.5281/zenodo.7263263.

Acknowledgments

We would like to thank Tobias Starborg and Yusuf Mohammed for help with equipment and valuable discussions.

Funding

This work was supported by The Rosalind Franklin Institute, funded by UK Research and Innovation and the Engineering and Physical Sciences Research Council. This research did not receive any specific grant from funding agencies in the public, commercial, or not-for-profit sectors.

Author contributions

B.C. conceptualization; B.C. and A.P.T. investigation; B.C., A.P.T., E.L., B.G., J.K. and A.I.K methodology; B.C. and A.P.T. formal analysis; B.G. software, A.P.T. resources; B.C. and A.P.T. visualisation, B.C. and A.P.T validation, B.C., A.P.T., J.K. and A.I.K. writing – original draft, B.C., A.P.T., B.G., E.L., B.G., J.K. and A.I.K. writing – review & editing, B.C., J.K. and A.I.K project administration.

Competing interests

The authors declare that they have no competing interests.

Data and materials availability

The data that support this study are available from the corresponding authors upon request. The raw data, LM, ADF-/BF-STEM, EDX and TEM images from this study have been deposited in the Zenodo database [https://doi.org/XX.XXXX/zenodo.XXXX].

Supplementary Text

Fig. S1 *D.radiodurans* **morphology and growth stages in graphene encapsulated environments.**

LP-ADF-STEM image of encapsulated early exponential phase (OD$_{600}$: 0.35) **(A)**, late exponential phase
(OD$_{600}$: 0.65) **(B)** and late stationary phase (OD$_{600}$:1.65) **(C)** *D.radiodurans*. **(D)** LP-ADF-STEM image of
encapsulated *D.radiodurans* diad from the late stationary phase sample. (TCF: 93 e$^-$/nm^2) Scale bar: A-C:
5 μm. D: 500 nm.

Analysis of sustained pressures inside graphene encapsulated *D.radiodurans*

We have measured the average size of the *D.radiodurans*. Based on the measurements from 13

bacteria from ADF-STEM images, *D.radiodurans* has an ellipsoidal geometry. The average

lengths of the long axis and short axis are 2.91 ± 0.23 µm and 2.09 ± 0.13 µm, respectively. These

values include both random and systematic errors. The standard deviations of the lengths of the

long axis and short axis are 0.57 and 0.32 µm, respectively (Fig.S2).

The pressure inside a graphene liquid cell can be estimated by using the pressure of Laplace(*28*):

590
$$\Delta P = \frac{\gamma}{2R}$$

591   Where ΔP is the Laplace pressure gradient, γ the interfacial energy of graphene−water and R is the radius

592   of the encapsulated *D.radiodurans*. The error associated with the calculated value is:

593
$$(E)^2 = \left(\frac{\partial f(X_1, X_2, \ldots)}{\partial X_1}\Delta X_1\right)^2 + \left(\frac{\partial f(X_1, X_2, \ldots)}{\partial X_2}\Delta X_2\right)^2 + \cdots.,$$

594   Thus:

595
$$E_{\Delta P} = \frac{\gamma \cdot E_R}{2R^2}$$

596
$$\Delta P_1 = \frac{\gamma_{Graphene-Water}}{2R_1} = \frac{0.09\,\frac{J}{m^2}}{2 \cdot 1.05 \cdot 10^{-6}\,m} = (4.3 \pm 0.5) \cdot 10^{+4}\,\frac{J}{m^3} = 0.42 \pm 0.05\,atm$$

597
$$\Delta P_2 = \frac{\gamma_{Graphene-Water}}{2R_2} = \frac{0.09\,\frac{J}{m^2}}{2 \cdot 1.46 \cdot 10^{-6}\,m} = (3.1 \pm 0.5) \cdot 10^{+4}\,\frac{J}{m^3} = 0.31 \pm 0.05\,atm$$

599   To calculate the pressure exerted by graphene directly, without intermediate water, on a hydrated

600   *D.radiodurans*, some approximations can be applied. The first is that the membrane of a *D.radiodurans* is

601   chemically similar to that of *E.coli*, and hence the surface tension can be estimated. Therefore, we can use

602   the measured interaction force between a single flake of pristine graphene and the cell wall of a living

603   *E.coli*: 38.2 ± 16.4 pN. Then, using the following equation (*30*) we can approximate the interfacial energy:

604
$$\gamma = \frac{F}{L}$$

605   Where F is the adhesive force and L is length over which that force is distributed. In the case of

606   D.*radiodurans* we can simplify its geometry to a circumference, where d is the diameter of the

607 *D.radiodurans* which value is in the range of length of the long and short axis previously measured (2.1-
608 2.9 μm):

609
$$\gamma_1 = \frac{F}{\pi \cdot d} = \frac{38.2 \cdot 10^{-12} N}{\pi \cdot 2.1 \cdot 10^{-6} m} = \frac{38.2 \cdot 10^{-6} N}{\pi \cdot 2.1 m} = 5.8 \cdot 10^{-6} \frac{J}{m^2}$$

610
$$\gamma_2 = \frac{F}{\pi \cdot d} = \frac{38.2 \cdot 10^{-12} N}{\pi \cdot 2.9 \cdot 10^{-6} m} = \frac{38.2 \cdot 10^{-6} N}{\pi \cdot 2.9 m} = 4.2 \cdot 10^{-6} \frac{J}{m^2}$$

611 The error associated can be calculated using the same equation for error previously displayed, hence:

612
$$E_\gamma = \sqrt{\left(\frac{E_F}{\pi \cdot d}\right)^2 + \left(\frac{F \cdot E_d}{\pi \cdot d^2}\right)^2}$$

613
$$E_{\gamma_1} = \sqrt{\left(\frac{16.4 \cdot 10^{-12}}{\pi \cdot 2.1 \cdot 10^{-6}}\right)^2 + \left(\frac{38.2 \cdot 10^{-12} \cdot 0.1 \cdot 10^{-6}}{\pi \cdot (2.1 \cdot 10^{-6})^2}\right)^2} = 2.5 \cdot 10^{-6} \frac{J}{m^2}$$

614
$$E_{\gamma_2} = \sqrt{\left(\frac{16.4 \cdot 10^{-12}}{\pi \cdot 2.9 \cdot 10^{-6}}\right)^2 + \left(\frac{38.2 \cdot 10^{-12} \cdot 0.2 \cdot 10^{-6}}{\pi \cdot (2.9 \cdot 10^{-6})^2}\right)^2} = 1.8 \cdot 10^{-6} \frac{J}{m^2}$$

615
$$\gamma_1 = (5.8 \pm 2.5) \cdot 10^{-6} \frac{J}{m^2}$$

616
$$\gamma_2 = (4.2 \pm 1.8) \cdot 10^{-6} \frac{J}{m^2}$$

617 We can estimate the pressure within the encapsulated region from the surface tension exerted by pristine
618 graphene on the membrane surface. This estimation is based on the Laplace pressure equation. The error in
619 this estimation can be calculated using the following equation:

620
$$E_P = \sqrt{\left(\frac{\Delta\gamma}{2R}\right)^2 + \left(\frac{\gamma \cdot \Delta R}{2R^2}\right)^2}$$

621
$$\Delta P_1 = \frac{\gamma_1}{2R_1} = \frac{5.8 \cdot 10^{-6} \frac{J}{m^2}}{2 \cdot 1.05 \cdot 10^{-6} m} = 2.76 \pm 1.22 \frac{J}{m^3} = (2.7 \pm 1.2) \cdot 10^{-5} atm$$

622
$$\Delta P_2 = \frac{\gamma_2}{2R_2} = \frac{4.2 \cdot 10^{-6} \frac{J}{m^2}}{2 \cdot 1.45 \cdot 10^{-6} m} = 1.45 \pm 0.63 \frac{J}{m^3} = (1.4 \pm 0.7) \cdot 10^{-5} atm$$

623   In addition, the different pressures calculated above can be compared to the pressure calculated using a

624   more detailed analysis which includes other pressure components such as Van der Waals and elastic, as

625   performed by Khestanova *et al*(*29*) in the following equation:

626
$$P = \frac{4\pi\gamma}{5 \cdot 1.7}\left(\frac{5c_1 Y}{\pi\gamma}\right)^{\frac{1}{6}}\left(\frac{1}{t \cdot l^2}\right)^{\frac{1}{3}}$$

627   Where γ is the total adhesion energy ($\gamma = \gamma_{Graphene-Graphene} - \gamma_{Graphene-Water}$,where

628    $\gamma_{Graphene-Graphene}$ and $\gamma_{Graphene-Water}$ are the adhesion energy between two graphene layers and

629   graphene and water respectively), Y is the Young's modulus and t and l are the height and the radius of the

630   encapsulated area, respectively. Substituting the variables by the associated values we reach almost twice

631   atmospheric pressure:

633
$$P = 161389.4\, Pa = 1.59\, atm$$

635   This equation can also be used to estimate the total pressure of other encapsulated biological structures,

636   such as viruses and proteins, which are of utmost importance in future experiments (Fig. S3).

Fig. S2 Statistical analysis of *D.radiodurans* **size distribution.**

The centre line indicates the median values; × indicates the mean.

Fig. S3 Analysis of the pressure on different volumes of spherical, graphene-encapsulated structures
and its correlation with the size of relevant biological structures.

Fig. S4 Asymmetric division and other irregularities in septal development in *D.radiodurans*.

A) Individual cocci within a tetrad at different stages of cell division (Late stationary phase). **B)** S-shaped septum without complete perpendicular septum (Late stationary phase). **C)** S-shaped septum with complete perpendicular septum (Early exponential phase**). D)** Diagonal septa within individual cocci in late stationary phase and early exponential phase **(E)**. Scale bar: 500 nm.

655 **Fig. S5 Imaging** *D.radiodurans* **at different fluence.**

656 BP-filtered LP-ADF-STEM images of *D.radiodurans* at fluences of **A)** 0.5, **B)** 5.8 and **C)** 65 e/nm^2. Each
657 individual coccus and endogenous polyphosphates are clearly visible at fluences as low as 5.8 e$^-$/nm^2.

Fig. S6 *D.radiodurans* **ultrastructure in graphene encapsulated environments.**
A) Low magnification ADF-STEM image of encapsulated grouped *D.radiodurans* tetrad, Fig.3A ROI
marked in red. **B)** Raw ADF-STEM image of *D.radiodurans*, **C)** After bandpass filter applied to **(B)**, after
contrast enhancement to **(C)**. Corresponding full size power spectra for ROIs in Fig. 3B of storage granules
(E), cytosol **(F; Fig. 3B inset)** and peptidoglycan **(G)**, $(18 \text{ nm})^{-1}$ boundary marked by semicircles. **H)** Radial
profile plot of the power spectra **(E-G)**, demonstrating a peak frequency $\sim 0.0417 \text{ nm}^{-1}$ in the cytosol not
present in the peptidoglycan. Scale bar: A: 1 μm; B-D: 250 nm; PS: $(2 \text{ nm})^{-1}$.

Fig. S7 *D.radiodurans* **elemental distribution in graphene encapsulated environments.**
A) Raw ADF-STEM image of Fig.3A and individual element maps. **I)** EDX spectrum of **(A)**, showing different elemental peaks, with no signal evident for Fe Kα lines. Scale bar: A: 250 nm.

Fig. S8 Manganese accumulation in bacterial phosphate granules.

Individual element maps of *D.radiodurans* treated with **(A)** and without **(B)** $MnCl_2$. **C)** EDX spectra of individual phosphate granules, selected area marked with dotted lines in **(A)** and **(B)**. Scale bar: A-B: 500 nm.