Liquid phase electron microscopy of bacterial ultrastructure

Authors

Brian J. Caffrey[1*]†, Adrián Pedrazo-Tardajos[1]†, Emanuela Liberti[1], Ben Gaunt[1,2], Judy S. Kim[1,3] and Angus I. Kirkland[1,3].

Affiliations

† These authors contributed equally to this work.

[1]The Rosalind Franklin Institute, Harwell Science and Innovation Campus, Didcot, UK

[2] Nuffield Department of Women's & Reproductive Health, University of Oxford, John Radcliffe Hospital, Oxford, OX3 9DU, U.K.

[3]Department of Materials, University of Oxford, Oxford, OX1 3PH, UK

*Corresponding authors: brian.caffrey@rfi.ac.uk

Abstract

Recent advances in liquid phase scanning transmission electron microscopy (LP-STEM) have enabled the study of dynamic biological processes at nanometre resolutions, paving the way for live-cell imaging using electron microscopy. However, this technique is often hampered by the inherent thickness of whole cell samples and damage from electron beam irradiation. These restrictions degrade image quality and resolution, impeding biological interpretation. Here we detail the use of graphene encapsulation, STEM, and energy-dispersive X-ray (EDX) spectroscopy methods to mitigate these issues, providing unprecedented levels of intracellular detail in aqueous specimens. This work demonstrates the potential of LP-STEM to examine and identify internal cellular structures in thick biological samples, in a radiation resistant, gram-positive bacterium, Deinococcus radiodurans using a variety of imaging techniques.

Introduction

Liquid phase electron microscopy (LP-EM) is a technique that enables the analysis of intracellular, real-time dynamics with nanometre precision in native, hydrated, aqueous environments. This rapidly emerging field of research has provided unique insights into hard materials [1], such as the formation of platinum nanocrystals [2] and the electrochemical analysis of lithium-ion batteries [3]. More recently, LP-EM has also expanded to the analysis of biological materials such as proteins [4], bacteria [5], and even eukaryotic yeast [6] and human cells [7,8]. However, ultrastructural analysis of the internal components of these biological materials is difficult due to limitations in sample thickness and electron beam fluence.

Central to addressing these limitations are considerations of the most appropriate imaging geometry for LP-EM imaging of biological samples. Conventional transmission electron microscopy (TEM) is the most widely used imaging technique in biological LP-EM [9] and in structural biology more generally [10]. The popularity of brightfield TEM (BF-TEM) in biological sciences is due, in part, to phase contrast being dominant in low atomic number soft matter samples [11]. However, spatial resolution in BF-TEM decreases significantly beyond thicknesses greater than the elastic mean free path of electrons in water ($\lambda \sim 300$ nm at 300 kV [12]). In addition, as the sample thickness increases the flux in the elastically scattered wavefield decreases reducing the phase contrast even for zero loss filtered images. As most prokaryotic and eukaryotic cells are greater than 500 nm in thickness, conventional BF-TEM has limitations for high-resolution imaging of whole cell samples. Annular darkfield STEM (ADF-STEM) using incoherently scattered electron phase information, can provide superior spatial resolution as it is less affected by the effects of chromatic aberration [13], although at the expense of a reduced signal due to weak scattering at high angles from light element materials. The ADF-STEM geometry can also provide valuable complementary information on the elemental composition of biological samples using energy dispersive X-ray (EDX) spectroscopy which, for example, enables the localisation of biominerals with distinct elemental signatures in bacteria [14] and in tissue sections to distinguish between different heavy metal conjugated immuno-labels [15].

While ADF-STEM can improve image contrast over BF-TEM for thicker samples, the total thickness of

the liquid cell in which the specimen is enclosed plays an equally significant role in limiting the

achievable resolution and signal-to-noise ratios (SNR) of both LP-ADF-STEM imaging and EDX

spectroscopy [16]. This sample thickness limitation is compounded further by the need for samples to be

enclosed in thin membrane windows to partition the sample from the microscope vacuum, e.g. each

silicon nitride (Si_3N_4) window in dedicated TEM liquid holders is typically ~50 nm thick, in addition to

the liquid/sample thickness. Graphene liquid cells (GLC) can overcome some of the effects from the

geometry of commercially available liquid holders, minimising the liquid encapsulation in a single atomic

layer, therefore maximising the achievable imaging and spectral resolution from aqueous environments in

LP-EM applications.

Selection of appropriate biological models are also important to achieving high resolution images of

important biology using LP-EM. The *Deinococcus* genus is distinguished by an extraordinarily high

tolerance to the effects of environmental hazards, such as arsenic [17], ionizing and UV irradiation [18], and

desiccation [19]. *D. radiodurans*, the type species of the genus, is a spherical, non-motile, didermal

bacterium and is one of the most radiation-resistant of the *Deinococcus* genus, thirty times more resistant

than the more commonly studied, *Escherichia coli* [20]. While the biochemical mechanisms underlying this

resistance are not yet fully understood, it is thought that this extreme radiation resistance evolved from its

adaptation to dry environments [21] with dehydration being a more common physiological stressor than

environmental radiation. Mechanisms for the unusual radiation resistance of *D.radiodurans* have been

suggested to involve DNA damage resistance and repair pathways, as evidenced by the unusually large

number of (>100) radiation-induced double-strand breaks (DSBs) that this species can withstand without

lethality or mutagenesis. The proteins responsible for these resistance and repair pathways require

protection from the oxidative environments created by irradiation and are therefore highly dependent on

radical oxygen scavenger Mn^{2+} complexes [22] and antioxidant carotenoids such as deinoxanthin [23]. These

chemicals require a rich source of nutrients, to maintain effective concentrations. These resistance

mechanisms, in turn, may allow *D.radiodurans* to tolerate electron irradiation for longer, mitigating the

effects of electron beam damage [24]. *D.radiodurans* is therefore an ideal candidate for ultrastructural study

using LP-EM techniques.

In this work, we demonstrate the capabilities of graphene encapsulation and STEM-EDX imaging in

studies of biological specimens in the liquid phase. We use these to provide insights into *D.radiodurans*

ultrastructure using graphene encapsulating environments, localising manganese ions in phosphate-

containing storage granules within the bacterium and demonstrate the ultrastructural response of

D.radiodurans to nutrient restriction and desiccation *in vivo*.

Results

Graphene liquid cell assembly and morphology of *D.radiodurans.*

Using the graphene encapsulation method developed previously [25,26], it is possible to confine biological

samples within graphene encapsulated aqueous environments in standard Au-flat and Au Quantifoil grids

(Fig.1A-E). A single-layer graphene grid was submerged in a container with a biological buffer of interest

and the sample was pipetted over it. The second layer of graphene was then carefully lowered onto the

grid by removing excess buffer from the container and allowed to dry. The encapsulated bacteria were

immediately inspected using brightfield light microscopy (LM). The graphene encapsulation appears to

be tolerated by *D.radiodurans* as shown by the integrity of the membrane under visual inspection in LM

and EM (Fig.S1A-B). Thus, we calculated the approximate value of the sustained pressure on a

D.radiodurans cell, using the Laplace pressure [29], yielding an approximate pressure of 0.5 atmosphere

(~50 kPa) (Fig. S2, S3). A more detailed methodology includes different pressure contributions such as

Van der Waals and elastic components [30], which yields a pressure around 1.6 atmospheres (~162 kPa).

This result is in good agreement with both the measured intactness of the membrane [31] and the calculated

pressure for samples as thick as bacteria or cells (1 µm) using different parameters [29]. In the case that a

direct contact between the pristine graphene and the hydrated membrane of *D.radiodurans* is considered,

the estimated pressure is several orders of magnitude lower. See analysis in supplementary information

for more details. In all lysogeny broth (LB) cultures, *D.radiodurans* cells typically formed tightly packed

tetrads, with a high degree of asymmetric division and poorly formed central septa in early exponential

growth phases and predominantly octads with thick central septa in stationary phase cultures (Fig. S1C-

F). In low nutrient media preparations, the cells primarily formed single cocci or diads, as observed

previously in studies of *D.radiodurans* nutrient-dependent pleomorphisms [27,28].

Fig.1. Schematic of graphene blister assembly and LM/EM analysis of encapsulated *D.radiodurans*.

A) Freshly prepared single-layer graphene grids placed in water on filter paper, with the second layer of

graphene suspended above. **B)** After exchanging water with buffer (HEPES), the sample is added directly

to the top of the graphene grids. **C)** Solution is removed slowly to ensure the graphene layer remains

intact over the grids. **D)** Solution is completely removed, and grids allowed to air dry. **E)** Expanded view

of panel **(D)** of graphene blisters (GB) with encapsulated *D.radiodurans*.

112   *D.radiodurans* **growth stages, ultrastructure, and elemental distribution.**

113   Imaging whole bacteria provides cellular context to subcellular features, allowing rapid screening of

114   multiple bacteria at different stages of growth and capturing rare cellular events which may be obscured

115   by sample thickness or removed by thinning in conventional cryo-EM studies [32].

116   Bacteria were encapsulated at different phases of the bacterial growth curve; stationary phase bacteria

117   were often found in groups of octads, with multiple high contrast granules present. The periplasmic space

118   between the outer and inner membrane (OM and IM, respectively) was ~90 nm (Fig.2A-B), with a

119   peptidoglycan (PG) component ~35 nm thick and an interstitial layer (IL) ~55 nm thick. This agrees with

120   previously reported descriptions of a dense diffuse periplasmic layer [33] and cell envelope thickness

121   measurements from frozen vitrified sections [34] of *D.radiodurans*. The surface layer (S-layer), typically

122   reported as a 20 nm thick layer [34], was not clearly visible. However, a high contrast layer (HCL), ~55 nm

123   thick, likely containing the S-layer and carbohydrate coat [35–38], was observed (Fig.2B).

124   The characteristic stages of septal growth and cell division in *D.radiodurans* were observed in

125   encapsulated bacteria (Fig.2Ci-ii). Septal growth begins perpendicular to the central septum of the tetrad,

126   dividing a single coccus into two cocci with characteristic septal aversion, as previously reported in

127   conventional EM studies [39] (Fig.2D, E). Large phosphate granules were evident in the majority of

128   *D.radiodurans* cocci, with smaller storage granules ranging from 40 – 150 nm in size, potentially used for

129   carbohydrate storage often visible [40], as highlighted in Fig.2E. In early exponential cultures, the phosphate

130   granules appeared smaller, were difficult to differentiate from carbohydrate granules and were also more

131   numerous (Fig. S1A). Merging of the septa leads to complete cellular division into two cocci (Fig.2F).

132   Further division into four cocci begins with the formation of septa in the centre of and perpendicular to

133   the previous septum and on opposite sides of the cell walls (Fig.2G). The septa advance from the central

134   and peripheral edges toward the centre of the coccus with a diminishing slit formed between the

135   advancing septal edges (Fig.2H), as observed previously by optical microscopy [41] and conventional EM

136   [39].

Several asymmetric divisions of cocci were also observed (Fig. S4A), along with s-shaped septal growths

from the centre of the cell (Fig. S4 B, C) and multiple diagonally orientated septa at different stages of

division (Fig. S4D, E). It was possible to image these structures at fluences as low as ~0.5 e$^-$/nm^2 (Fig.

S5). A fluence of 0.5 e$^-$/nm^2 is an order of magnitude lower than the fluence threshold for maintaining

transcriptionally active *E.coli*, suggesting live cell imaging of these structures may therefore be possible

in the near future [42]. Note, while the terms electron dose and electron fluence are often used

interchangeably in the field of electron microscopy, electron fluence is defined as the number of impacted

electrons on a sample per unit area, i.e. 100 e$^-$/nm^2 = 1 e$^-$/Å^2, and electron dose is strictly defined as the

energy absorbed per unit area, expressed in units of Grays. Therefore, in all subsequent images we quote

the total cumulative fluence (TCF) in SI units of e$^-$/nm^2, which accounts for all electron beam irradiation

up to and including the image shown.

At higher magnifications, some ultrastructural features were visible within the encapsulated cells (Fig.3A;

Fig. S6A-D), including protein (P), DNA, peptidoglycan (PG), septal edges (S) and storage granules

(SG). Protein was dispersed throughout the cell and power spectra (PS) calculated from image areas

containing protein (Fig.3B, red ROI), show enhanced frequencies corresponding to a spacing of 24 ± 8

nm consistent with bacterial ribosomes, not observed in the PS calculated form the peptidoglycan region,

blue ROI (Fig. 3B, Inset; Fig. S6 E-H).

EDX analysis of the IM and PG indicates a relatively high abundance of sulphur. We propose that this

periplasmic layer may act as a reservoir for sulphur-containing amino acids and low molecular weight

thiols, such as cysteine/methionine and bacillithiol, respectively, which are integral to the cells redox

homoeostasis and antioxidant defence system [43–45]. Most storage granules imaged, were enriched in

phosphorous, oxygen and potassium (Fig.3C, Fig. S7). Other counterions including, magnesium were also

observed to correlate spatially with phosphate granules although the EDX SNR was poor due to the

relatively low fluence used for acquisition. While calcium counterions were also observed in

polyphosphates with *D.radiodurans*, these were relatively rare events and usually only in single

polyphosphate granules within desiccated individuals. Sulphur was found to correlate with the cell

membrane, along with sodium and chlorine (Fig. 3D, 4).

Spherical, low contrast particles were also observed, roughly 30 nm in size, associated with the IM on the

cytoplasmic side and are likely to be similar structures to those previously reported as macromolecular

complexes (MC) [34], thought to be Dps2 clusters for iron sequestration [22] (Fig.3B). However, there was no

significant iron signal found anywhere within the cell in the EDX maps (Fig. 4). This is possibly due to

iron being dispersed throughout the cell rather than being concentrated in any specific area making the

signal extremely weak in an already relatively low signal map (Fig. S7B).

Fig.2 *D.radiodurans* **growth stages and membrane composition in graphene encapsulated**

environments.

A) Bandpass (BP) filtered LP-ADF-STEM section of encapsulated late exponential phase (OD$_{600}$: 0.65)

D.radiodurans cell envelope, with the density profile region of interest (ROI) highlighted (TCF: 37,500 e^{-}

/nm^2). **B)** Corresponding density profile of cell envelope components reveal a periplasmic space (Pp)

between the inner and outer membrane, a peptidoglycan layer (PG) followed by an interstitial layer (IL)

and a final high contrast layer (HCL). **C i-ii)** BP filtered LP-ADF-STEM images of encapsulated

stationary phase *D.radiodurans* octads at various stages of division from the same sample (TCF: 93 e⁻

/nm^2). **D-H):** Expanded view of single cocci from octad ROIs showing septum progression stages. **D)**

Characteristic septal aversions visible. **E)** Septa meeting side on, in the cell centre. Asterisk (*): Small

storage granules; Arrowheads: Phosphate storage granules. **F)** Two cocci separated by a completed

septum. **G)** New septa begin to emerge perpendicular to the central septum. **H)** Later stage of tetrad

formation. Scale bar: A: 100 nm; C i-ii: 1 µm, D-H: 250 nm.

Fig.3 Ultrastructural detail and elemental distribution in *D.radiodurans* **using LP-ADF-STEM and**

EDX.

A) BP filtered LP-ADF-STEM and **B)** LP-BF-STEM image of encapsulated bacteria internal structure

(TCF: 11,800 e$^-$/nm^2), **Inset:** PS of cytosolic (red) ROI, with spatial frequency at (15 nm)$^{-1}$ marked

(dashed red). **C)** EDX spectra of ROIs in **(B)**. **D)** Gaussian filtered and contrast normalized phosphorous

and sulphur EDX map of **(A, B)** (TCF: 50,300 e$^-$/nm^2). Scale bar for A, B,D: 250 nm; PS: (2 nm^{-1})**.**

Manganese accumulates in bacterial phosphate granules.

Manganese is implicated in *D.radiodurans* radiation resistance and appear to localise with phosphate ions [22] suggesting that manganese acts as a counterion to cellular phosphate. Using EDX analysis, at biologically relevant fluences i.e. $<3,000$ e$^-$/nm^2 [46], we confirm that manganese localizes to phosphate granules following $MnCl_2$ supplementation of bacterial media (Fig. 4; Fig. S8A). Interestingly, manganese is not distributed uniformly across all polyphosphates within the cell, suggesting distinct biological roles for the different polyphosphates-cation identities. However, we were unable to observe accumulations of naturally occurring manganese-containing polyphosphates in *D.radiodurans* at the fluences used to record the maps (Fig. S8 B, C). These manganese-containing phosphate granules may act as a store of reactive oxygen species-scavenging manganese cations for release during oxidative stress.

Fig.4 Manganese accumulates in bacterial phosphate granules.

Summed LP-ADF-STEM image of bacteria incubated in MnCl$_2$ (Average TCF: 2,979 e$^-$/nm^2). **Top Row:** Intracellular elements; **Middle row:** Cell membrane associated elements; **Bottom Row:** Polyphosphate associated elements. Scale bar: 500 nm

Vacuum desiccation in *D.radiodurans* leads to separation of cell membrane, a marker for liquid encapsulation.

To assess the effect of vacuum desiccation on *D.radiodurans*, a sample exponentially growing bacteria were placed on a graphene grid as previously mentioned, however after a short period (<5 mins) of drying the grid was placed directly into the microscope. Bacteria exposed to the vacuum detached from their membranes causing large cracks to form (Fig.5A). These characteristic cracks, act as an internal standard for verification of encapsulation, making selection of regions of interest (ROI) straightforward even at relatively low fluences (<1 e$^-$/nm^2). This reduces the requisite pre-acquisition fluence budget [47], thus allowing more fluence to be used for single frame high resolution imaging or multi-frame, dynamic time course experiments.

Nutrient restriction leads to enrichment of different *D.radiodurans* pleomorphs.

As *D.radiourans* demonstrates nutrient-induced pleomorphisms [27], we decided to grow *D.radiodurans* in nutrient-restricted conditions (10% v/v LB media) in an effort to explore the different ultrastructure of these pleomorphs and to create smaller cell volumes to potentially enable three-dimensional data acquisition using LP-STEM tomography. It was readily apparent using light microscopy that nutrient-restriction dramatically reduces the number of tetrads and increases the number of monad and diads in solution. This was confirmed in the electron microscope, as most bacteria present were diad forms. While the diads did appear to have a less dense cytoplasm than tetrads there was little difference in the ultrastructural features, with the primary difference being a more spherical shape rather than ellipsoidal. Interestingly, in some individuals it was clear that the peptidoglycan wall between two individuals was in a ring shape rather than a singular partition suggesting that there may be significant intercell communication in these diads at this stage of growth (Fig.5B). We also observed diads which do not display this ring-shaped aperture and instead had a typical peptidoglycan partition, these appeared more ellipsoidal, suggesting that there may be a need for this type of aperture at this specific stage of cell

232 growth. A similar decrease in the ellipticity of the cells at specific growth phases has been observed

233 previously by high resolution light microscopy [41].

Fig.5 Effect of different environmental stressors on *D.radiodurans* ultrastructure.

236 **A)** LP-ADF-STEM image of vacuum desiccated bacteria in a torn graphene liquid cell (TCF: 93 e^-/nm^2);

237 Dashed red line: Tear in graphene, White arrows: Examples of desiccation-related membrane separation.

238 **B)** LP-ADF-STEM image of encapsulated diad, grown in 10% LB media (TCF: 2,334 e^-/nm^2); Dashed

239 yellow line: Ring shaped membrane between individuals. Scale bar for A, C: 500 nm; B: 2 μm.

Discussion

The LP-STEM studies presented here demonstrate an effective technique for imaging whole biological

specimens and their internal ultrastructure in native aqueous environments, without the need for heavy-

metal staining, nanoparticle tagging, cryogenic/plastic preservation requiring specialized equipment and

leading to potential artefacts. The graphene liquid cells used, prepared from relatively simple materials,

provide high contrast for LP-EM analysis. In combination with STEM-EDX techniques, they can provide

greater internal information than other native preparation approaches, such as conventional whole-cell

cryo-transmission electron microscopy/tomography techniques where samples contain layers of vitreous

ice.

As the graphene liquid cells are prepared on EM grids, they can fit in most standard EM holders. Unlike

commercially available silicon nitride chip liquid cells, the nature of GLCs means each graphene blister is

an independent liquid cell, keeping potential hydrolysis products from the electron beam localised to a

single blister and preventing the build-up and diffusion of free radicals casing damage in adjacent cells.

The isolated nature of graphene blisters also means that in the event of a failure of a single liquid cell,

there is no significant release of liquid inside the microscope column. This contrasts with conventional

silicon nitride chip liquid cell applications where failure of the chip may lead to the release of larger

volumes of liquid and gases in the column and where great care is required to ensure the liquid cell

remains sealed. However, the most significant advance in imaging quality is the electron transparency of

the graphene and thinner liquid volume.

There are several variables that we found to significantly affect sample quality and sensitivity and image

SNR. For example, we found that while gold Au-flat grids produced a tighter encapsulation and more

reproducible number of blisters, gold Quantifoil grids gave images with better SNR over larger fields-of-

view. Additionally, buffer composition is a significant factor; the use of phosphate buffered saline led to

substantial amounts of salt precipitates on the grid obscuring the field-of-view. We therefore used a

simpler zwitterionic buffer, HEPES, for our experiments. Degassing before encapsulation was also

essential to limit the formation of gas bubbles in the buffer under the electron beam.

Our study emphasises the importance of selecting suitable model organisms for study in LP-EM.

D.radiodurans has proven to be an extremely valuable test sample for exploring LP-EM/EDX capabilities

due to its radiation resistance, elementally heterogenous nature and round coccoid shape, which lends

itself readily to study in GLCs. Previously, it was shown that in transcriptionally active *E.coli*, 50% of the

population received a lethal fluence (LF_{50}) at ~10 e$^-$/nm^2, in commercially available silicon nitride chips

[42]. However, *D.radiodurans* is known to tolerate fluences at least tenfold greater in magnitude than *E.coli*,

suggesting an LF_{50} of *D.radiodurans* under the same circumstances of approximately 100 e$^-$/nm^2. This

fluence limit is further increased by the 2-7x protection factor afforded by graphene encapsulation [48–50],

potentially leading the way for low fluence live-cell imaging in LP-STEM. Our observations of proteins

at ~24 nm and other biomolecules within these bacterial cells suggest that even at cumulative fluences

significantly higher than the putative LF_{50} of *D.radiodurans*, it may still be more favorable to monitor

protein dynamics and interactions *in situ* than in purified protein solutions, with beam-related damage

potentially mitigated by the native reactive oxygen defense system of *D.radiodurans*. *D.radiodurans*

response to desiccation by creating cracks in their membrane from rapid depressurization in the

microscope vacuum, also demonstrate their utility in LPEM analysis, by acting as an internal marker for

aqueous environments within the electron microscope.

We have also demonstrated the use of LP-STEM-EDX applications to build an elemental understanding

of the bacterial cell at the ultrastructural level. LP-STEM-EDX has enabled us to demonstrate that Mn

ions localize to polyphosphate granules *in situ*, without the need for denaturants and fixatives. We have

also mapped significant concentrations of sulphur residing in the periplasm, suggesting a potential

mechanism for oxidative homeostasis in *D.radiodurans*. This periplasmic sulphur may help manage redox

homeostasis within *D.radiodurans*, being released into the cytoplasm on irradiation to help inhibit

oxidative damage induced by free radicals and protect biomolecules critical to cellular survival. These

LP-STEM-EDX studies demonstrate the potential to use both native elemental distributions and non-

native elemental probes to localise biomolecules and structures of interest within a cell.

Finally, this study is a proof of principal showing how LP-STEM-EDX enables the analysis of large-scale

cellular events, such as cell division, under relatively low fluence conditions (<100 e$^-$/nm^2) and can

resolve even finer ultrastructural details, such as proteins and nucleic acids albeit at a higher fluence. The

techniques described herein illustrate the potential of LP-EM to explore fundamental biological questions

in situ. Electron fluence, sample thickness and the fundamental characteristics of graphene, such as its

grain size, may however limit its broader application to larger cells and tissues. Ultimately, LP-EM

techniques combined with emerging low-fluence imaging applications such as ptychography [51,52] and

compressive sensing [53] mean that imaging cellular dynamics *in vivo* at sub-nanometre resolutions in an

electron microscope may soon be achievable.

Materials and Methods

Growth of *D. radiodurans*

5 ml of Lysogeny Broth (LB) was inoculated with *D. radiodurans* (Strain R_1; DSMZ 20539) frozen

culture and incubated at 30 °C for 24hrs with shaking. 500 µl of the resulting culture was added to 5 ml of

fresh LB [1% w/v Glucose] and after this reached early exponential phase (OD_{600}: ~0.3) was further

incubated and then collected at different time points: 15 min (early exponential phase, A600 nm = 0.35), 2

h (mid-exponential phase, A600 nm = 0.65) and 20 h (stationary phase, A600 nm = 1.65). For the Mn

accumulation experiment, early exponential phase bacteria were incubated with sterile-filtered $MnCl_2$ [0.1

or 1 mM] for 4hrs, then spun down and encapsulated. A control growth with water was performed and

followed simultaneously. For the restrictive media experiment, 500 µl of stationary phase bacteria were

added to 5ml of fresh 10% LB media in ddH_2O [1% w/v Glucose] and incubated overnight. 2ml of the

resulting samples were then spun down at 500g for the LB preparations and 2000g for the restrictive

preparations for 5 mins, resuspended in 1 ml of nitrogen degassed 4-(2-hydroxyethyl)-1-

piperazineethanesulfonic acid (HEPES) buffer [25 mM] and encapsulated in graphene for LP-

STEM/EDX imaging.

Brightfield light microscopy imaging of DAPI-stained *D.radiodurans*

317 Imaging was carried out with an upright brightfield light microscope, Eclipse Ni (Nikon, USA) using 10x

318 and 40x air immersion objectives.

Graphene liquid cell encapsulation

The hydrated graphene enclosed environments were obtained by first creating a graphene TEM grid by

transferring graphene to a TEM grid using cellulose acetate butyrate [54] followed by a dry-cleaning

procedure [55] at 310 °C overnight. This is the basis of the liquid cell. The top graphene layer for

encapsulation was fabricated using a polymer-free transfer method [56], which provides a flat top surface to

the hydrated environment which then adapts to the morphology of the target. The main steps are described

in detail in refs [57] and [26] to prepare the base TEM grid and the creation of the encapsulated environments

respectively [58].

The commercial based TEM grids used throughout the different experiments to create the hydrated

encapsulated environments were Au-Flat (2/2) 300 Mesh, 45nm Thick from Protochips and Au Quantifoil

R1.2/1.3 300 mesh from Quantifoil.

Liquid phase STEM imaging

All STEM imaging was performed on a 300kV GRAND-ARM 2 (JEOL) with a spherical aberration

corrector, with an illumination convergence semi-angle (α) of 15.95 mrad and annular dark-field (ADF)

[Inner collection semi-angle (β^{in}: 37.1 mrad)/Outer collection semi-angle (β^{out}: 83 mrad), measurement

limited by the differential pumping aperture and bright-field (BF) detectors (β_{BF}: 20.8 mrad). The

microscope was aligned using the standard gold waffle thin film. Images of aqueous bacteria were

typically recorded at 20 kX, 100 kX and 200 kX magnifications (pixel size: 5, 1 and 0.5 nm respectively),

2048 x 2048 frame size and 20 µs dwell time.

Liquid phase EDX imaging

Energy-dispersive X-ray spectroscopy was performed in STEM mode on a 300kV GRAND-ARM 2

(JEOL) on aqueous bacterial samples at 20kX, 100 kX and 200 kX magnifications (pixel size: 20, 4 and 2

nm) respectively), 512 x 512 frame size and 20 µs dwell times, using dual liquid N_2 cooled Si (Li) JEOL

detectors with a combined solid angle of 1.41 sr.

STEM/EDX Image preprocessing

To enhance high-resolution details and to remove background noise, a Gaussian bandpass filter was applied to each micrograph (High Pass :300 px/Low Pass:2 px), using the ImageJ Bandpass filter plugin. Horizontal STEM scanning artefacts were smoothed using the "Suppress Stripes" function at 5% in the ImageJ Bandpass filter plugin. All images were then normalised with 0.35% pixel saturation, using the "Contrast Enhance" function in ImageJ.

EDX maps were produced in JEOL Analysis Station Software and processed in Hyperspy [59]. Maps were binned by 2 in x-y and Gaussian filtered ($\sigma = 2$ px) to remove noise, using the "Gaussian Blur" function in ImageJ. All maps were then contrast normalised with 0% pixel saturation, using the "Contrast Enhance" function in ImageJ. All maps were generated using the respective elemental Kα lines.

Fluence History Tracking with Axon Studio

The Axon Studio software from Protochips Inc., was used in conjunction with Axon Dose to accurately track the fluence history of each imaged area, providing an accurate readout of specimen total cumulative fluence.

References

1. Pu, S., Gong, C. & Robertson, A. W. Liquid cell transmission electron microscopy and its applications. *Royal Society Open Science* at https://doi.org/10.1098/rsos.191204 (2020).

2. Zheng, H. *et al.* Observation of single colloidal platinum nanocrystal growth trajectories. *Science (80-.).* (2009) doi:10.1126/science.1172104.

3. Mehdi, B. L. *et al.* Observation and quantification of nanoscale processes in lithium batteries by operando electrochemical (S)TEM. *Nano Lett.* (2015) doi:10.1021/acs.nanolett.5b00175.

4. Wang, C., Qiao, Q., Shokuhfar, T. & Klie, R. F. High-resolution electron microscopy and spectroscopy of ferritin in biocompatible graphene liquid cells and graphene sandwiches. *Adv. Mater.* (2014) doi:10.1002/adma.201306069.

5. Kennedy, E., Nelson, E. M., Tanaka, T., Damiano, J. & Timp, G. Live Bacterial Physiology Visualized with 5 nm Resolution Using Scanning Transmission Electron Microscopy. *ACS Nano* (2016) doi:10.1021/acsnano.5b07697.

6. Peckys, D. B., Mazur, P., Gould, K. L. & De Jonge, N. Fully hydrated yeast cells imaged with electron microscopy. *Biophys. J.* (2011) doi:10.1016/j.bpj.2011.03.045.

7. Peckys, D. B., Korf, U. & De Jonge, N. Local variations of HER2 dimerization in breast cancer cells discovered by correlative fluorescence and liquid electron microscopy. *Sci. Adv.* (2015) doi:10.1126/sciadv.1500165.

8. Kong, L. *et al.* Facile hermetic TEM grid preparation for molecular imaging of hydrated biological samples at room temperature. *Nat. Commun.* (2023) doi: 10.1038/s41467-023-41266.

9. Wu, H., Friedrich, H., Patterson, J. P., Sommerdijk, N. A. J. M. & de Jonge, N. Liquid-Phase Electron Microscopy for Soft Matter Science and Biology. *Advanced Materials* at https://doi.org/10.1002/adma.202001582 (2020).

10. Saibil, H. R. Cryo-EM in molecular and cellular biology. *Molecular Cell* at https://doi.org/10.1016/j.molcel.2021.12.016 (2022).

11. de Jonge, N. Theory of the spatial resolution of (scanning) transmission electron microscopy in

383   liquid water or ice layers. *Ultramicroscopy* (2018) doi:10.1016/j.ultramic.2018.01.007.

384 12. Yesibolati, M. N. *et al.* Electron inelastic mean free path in water. *Nanoscale* (2020)

385   doi:10.1039/d0nr04352d.

386 13. Rez, P., Larsen, T. & Elbaum, M. Exploring the theoretical basis and limitations of cryo-STEM

387   tomography for thick biological specimens. *J. Struct. Biol.* (2016) doi:10.1016/j.jsb.2016.09.014.

388 14. Miot, J. *et al.* Mineralogical diversity in Lake Pavin: Connections with water column chemistry

389   and biomineralization processes. *Minerals* (2016) doi:10.3390/min6020024.

390 15. Scotuzzi, M. *et al.* Multi-color electron microscopy by element-guided identification of cells,

391   organelles and molecules. *Sci. Rep.* (2017) doi:10.1038/srep45970.

392 16. Kelly, D. J. *et al.* Nanometer Resolution Elemental Mapping in Graphene-Based TEM Liquid

393   Cells. *Nano Lett.* (2018) doi:10.1021/acs.nanolett.7b04713.

394 17. Suresh, K., Reddy, G. S. N., Sengupta, S. & Shivaji, S. Deinococcus indicus sp. nov., an arsenic-

395   resistant bacterium from an aquifer in West Bengal, India. *Int. J. Syst. Evol. Microbiol.* (2004)

396   doi:10.1099/ijs.0.02758-0.

397 18. Cox, M. M. & Battista, J. R. Deinococcus radiodurans - The consummate survivor. *Nature*

398   *Reviews Microbiology* at https://doi.org/10.1038/nrmicro1264 (2005).

399 19. Tanaka, M. *et al.* Analysis of Deinococcus radiodurans's transcriptional response to ionizing

400   radiation and desiccation reveals novel proteins that contribute to extreme radioresistance.

401   *Genetics* (2004) doi:10.1534/genetics.104.029249.

402 20. Daly, M. J. A new perspective on radiation resistance based on Deinococcus radiodurans. *Nat.*

403   *Rev. Microbiol.* (2009) doi:10.1038/nrmicro2073.

404 21. Mattimore, V. & Battista, J. R. Radioresistance of Deinococcus radiodurans: Functions necessary

405   to survive ionizing radiation are also necessary to survive prolonged desiccation. *J. Bacteriol.*

406   (1996) doi:10.1128/jb.178.3.633-637.1996.

407 22. Santos, S. P. *et al.* The interplay between Mn and Fe in Deinococcus radiodurans triggers cellular

408   protection during paraquat-induced oxidative stress. *Sci. Rep.* (2019) doi:10.1038/s41598-019-

53140-2.

23.   Lemee, L., Peuchant, E., Clerc, M., Brunner, M. & Pfander, H. Deinoxanthin: A new carotenoid

isolated from Deinococcus radiodurans. *Tetrahedron* (1997) doi:10.1016/S0040-4020(96)01036-8.

24.   Egerton, R. F. Mechanisms of radiation damage in beam-sensitive specimens, for TEM

accelerating voltages between 10 and 300 kV. *Microsc. Res. Tech.* (2012) doi:10.1002/jemt.22099.

25.   Yuk, J. M. *et al.* High-resolution EM of colloidal nanocrystal growth using graphene liquid cells.

Science (80-.). (2012) doi:10.1126/science.1217654.

26.   Jain, N. *et al.* Exploring the effects of graphene and temperature in reducing electron beam

damage: A TEM and electron diffraction-based quantitative study on Lead Phthalocyanine (PbPc)

crystals. *Micron* (2023) doi:10.1016/j.micron.2023.103444.

27.   Joshi, H. M. & Toleti, R. S. Nutrition induced pleomorphism and budding mode of reproduction in

Deinococcus radiodurans. *BMC Res. Notes* (2009) doi:10.1186/1756-0500-2-123.

28.   Shukla, S. K., Gomathi Sankar, G., Paraneeiswaran, A. & Subba Rao, T. Differential radio-

tolerance of nutrition-induced morphotypes of Deinococcus radiodurans R1. *Curr. Microbiol.*

(2014) doi:10.1007/s00284-013-0472-9.

29.   Ghodsi, S. M. *et al.* Assessment of Pressure and Density of Confined Water in Graphene Liquid

Cells. *Adv. Mater. Interfaces* (2020) doi:10.1002/admi.201901727.

30.   Khestanova, E., Guinea, F., Fumagalli, L., Geim, A. K. & Grigorieva, I. V. Universal shape and

pressure inside bubbles appearing in van der Waals heterostructures. *Nat. Commun.* (2016)

doi:10.1038/ncomms12587.

31.   Al Faouri, R., Henry, R., Biris, A. S., Sleezer, R. & Salamo, G. J. Adhesive force between

graphene nanoscale flakes and living biological cells. *J. Appl. Toxicol.* (2017)

doi:10.1002/jat.3478.

32.   Khanna, K. & Villa, E. Revealing bacterial cell biology using cryo-electron tomography. *Current

Opinion in Structural Biology* at https://doi.org/10.1016/j.sbi.2022.102419 (2022).

33.   Eltsov, M. & Dubochet, J. Fine structure of the Deinococcus radiodurans nucleoid revealed by

435  cryoelectron microscopy of vitreous sections. *J. Bacteriol.* (2005) doi:10.1128/JB.187.23.8047-

436  8054.2005.

437 34. Sexton, D. L., Burgold, S., Schertel, A. & Tocheva, E. I. Super-resolution confocal cryo-CLEM

438  with cryo-FIB milling for in situ imaging of Deinococcus radiodurans. *Curr. Res. Struct. Biol.*

439  (2022) doi:10.1016/j.crstbi.2021.12.001.

440 35. Rothfuss, H., Lara, J. C., Schmid, A. K. & Lidstrom, M. E. Involvement of the S-layer proteins

441  Hpi and SlpA in the maintenance of cell envelope integrity in Deinococcus radiodurans R1.

442  *Microbiology* (2006) doi:10.1099/mic.0.28971-0.

443 36. Karrenberg, F. H., Wildhaber, I. & Baumeister, W. Surface structure variants in Deinococcus

444  radiodurans. *Curr. Microbiol.* (1987) doi:10.1007/BF01568163.

445 37. von Kügelgen, A., van Dorst, S., Alva, V. & Bharat, T. A. M. A multidomain connector links the

446  outer membrane and cell wall in phylogenetically deep-branching bacteria. *Proc. Natl. Acad. Sci.*

447  *U. S. A.* (2022) doi:10.1073/pnas.2203156119.

448 38. von Kügelgen, A. *et al.* Interdigitated immunoglobulin arrays form the hyperstable surface layer of

449  the extremophilic bacterium Deinococcus radiodurans. *Proc. Natl. Acad. Sci. U. S. A.* (2023)

450  doi:10.1073/pnas.2215808120.

451 39. Murray, R. G. E., Hall, M. & Thompson, B. G. Cell division in Deinococcus radiodurans and a

452  method for displaying septa. *Can. J. Microbiol.* (1983) doi:10.1139/m83-217.

453 40. Slade, D. & Radman, M. Oxidative Stress Resistance in Deinococcus radiodurans . *Microbiol.*

454  *Mol. Biol. Rev.* (2011) doi:10.1128/mmbr.00015-10.

455 41. Floc'h, K. *et al.* Cell morphology and nucleoid dynamics in dividing Deinococcus radiodurans.

456  *Nat. Commun.* (2019) doi:10.1038/s41467-019-11725-5.

457 42. Kennedy, E., Nelson, E. M., Damiano, J. & Timp, G. Gene Expression in Electron-Beam-

458  Irradiated Bacteria in Reply to 'live Cell Electron Microscopy Is Probably Impossible'. *ACS Nano*

459  at https://doi.org/10.1021/acsnano.6b06616 (2017).

460 43. Helmann, J. D. Bacillithiol, a new player in bacterial redox homeostasis. *Antioxidants and Redox*

Signaling at https://doi.org/10.1089/ars.2010.3562 (2011).

44.   Newton, G. L. *et al.* Bacillithiol is an antioxidant thiol produced in Bacilli. *Nat. Chem. Biol.*

(2009) doi:10.1038/nchembio.189.

45.   Xiong, Y. *et al.* Comprehensive Temporal Protein Dynamics during Postirradiation Recovery in

Deinococcus radiodurans. *Oxid. Med. Cell. Longev.* (2022) doi:10.1155/2022/1622829.

46.   Grant, T. & Grigorieff, N. Measuring the optimal exposure for single particle cryo-EM using a 2.6

Å reconstruction of rotavirus VP6. *Elife* (2015) doi:10.7554/eLife.06980.

47.   Ilett, M. *et al.* Analysis of complex, beam-sensitive materials by transmission electron microscopy

and associated techniques: TEM of Beam Sensitive Materials. *Philosophical Transactions of the*

Royal Society A: Mathematical, Physical and Engineering Sciences at

https://doi.org/10.1098/rsta.2019.0601 (2020).

48.   Algara-Siller, G., Kurasch, S., Sedighi, M., Lehtinen, O. & Kaiser, U. The pristine atomic

structure of MoS2 monolayer protected from electron radiation damage by graphene. *Appl. Phys.*

Lett. (2013) doi:10.1063/1.4830036.

49.   Janicek, B., Kharel, P., Bae, S. hyun & Huang, P. Quantifying the Protection Factor of Graphene

Substrates for Atomic-scale Imaging of Organic Crystals. *Microsc. Microanal.* (2020)

doi:10.1017/s1431927620015834.

50.   Cho, H. *et al.* The use of graphene and its derivatives for liquid-phase transmission electron

microscopy of radiation-sensitive specimens. *Nano Lett.* (2017) doi:10.1021/acs.nanolett.6b04383.

51.   Ding, Z. *et al.* Three-dimensional electron ptychography of organic–inorganic hybrid

nanostructures. *Nat. Commun.* (2022) doi:10.1038/s41467-022-32548-x.

52.   Huang, C., Kim, J. S. & Kirkland, A. I. Cryo-electron ptychography: Applications and potential in

biological characterisation. *Curr. Opin. Struct. Biol.* **83**, 102730 (2023).

53.   Nicholls, D. *et al.* Sub-Sampled Imaging for STEM: Maximising Image Speed, Resolution and

Precision Through Reconstruction Parameter Refinement. *Ultramicroscopy* (2022)

doi:10.1016/j.ultramic.2021.113451.

54.   Burwell, G., Smith, N. & Guy, O. Investigation of the utility of cellulose acetate butyrate in

minimal residue graphene transfer, lithography, and plasma treatments. *Microelectron. Eng.*

(2015) doi:10.1016/j.mee.2015.04.097.

55.   Algara-Siller, G., Lehtinen, O., Turchanin, A. & Kaiser, U. Dry-cleaning of graphene. *Appl. Phys.*

Lett. (2014) doi:10.1063/1.4871997.

56.   Regan, W. *et al.* A direct transfer of layer-area graphene. *Appl. Phys. Lett.* (2010)

doi:10.1063/1.3337091.

57.   Zhang, Y. *et al.* Charging of Vitreous Samples in Cryogenic Electron Microscopy Mitigated by

Graphene. *ACS Nano* (2023) doi:10.1021/acsnano.3c03722.

58.   Pedrazo-Tardajos, A. & Bals, S. GRAPHENE LAYER TRANSFER METHOD. (2020).

59.   de la Peña, F. *et al.* hyperspy/hyperspy: Release v1.7.3. at https://doi.org/10.5281/zenodo.7263263

(2022).

Acknowledgments

We would like to thank Tobias Starborg, Yusuf Mohammed for help with equipment and valuable

discussions and Chen Huang for help setting up the electron microscope for EDX.

Funding

This work was supported by The Rosalind Franklin Institute, funded by UK Research and Innovation and

the Engineering and Physical Sciences Research Council. This research did not receive any specific grant

from funding agencies in the public, commercial, or not-for-profit sectors.

Author contributions

B.C. conceptualization; B.C. and A.P.T. investigation; B.C., A.P.T., E.L., B.G., J.K. and A.I.K

methodology; B.C. and A.P.T. formal analysis; B.G. software, A.P.T. resources; B.C. and A.P.T.

visualisation, B.C. and A.P.T validation, B.C., A.P.T., J.K. and A.I.K. writing – original draft, B.C.,

A.P.T., B.G., E.L., B.G., J.K. and A.I.K. writing – review & editing, B.C., J.K. and A.I.K project

administration.

Competing interests

The authors declare that they have no competing interests.

Data and materials availability

The data that support this study are available from the corresponding authors upon request. The raw data,

LM, ADF-/BF-STEM, EDX and TEM images from this study have been deposited in the Zenodo

database [https://doi.org/10.5281/zenodo.10625794]

Supplementary Materials

<u>Analysis of sustained pressures inside graphene encapsulated *D.radiodurans*</u>

We have measured the average size of the *D.radiodurans*. Based on the measurements from 13

bacteria from ADF-STEM images, *D.radiodurans* has an ellipsoidal geometry. The average

lengths of the long axis and short axis are 2.91 ± 0.23 μm and 2.09 ± 0.13 μm, respectively.

These values include both random and systematic errors. The standard deviations of the lengths

of the long axis and short axis are 0.57 and 0.32 μm, respectively (Fig.S2).

The pressure inside a graphene liquid cell can be estimated by using the pressure of Laplace[29]:

527
$$\Delta P = \frac{\gamma}{2R}$$

528   Where ΔP is the Laplace pressure gradient, γ the interfacial energy of graphene−water and R is the radius

529   of the encapsulated *D.radiodurans*. The error associated with the calculated value is:

530
$$(E)^2 = \left(\frac{\partial f(X_1, X_2, \dots)}{\partial X_1}\Delta X_1\right)^2 + \left(\frac{\partial f(X_1, X_2, \dots)}{\partial X_2}\Delta X_2\right)^2 + \cdots,$$

531   Thus:

532
$$E_{\Delta P} = \frac{\gamma \cdot E_R}{2R^2}$$

533
$$\Delta P_1 = \frac{\gamma_{Graphene-Water}}{2R_1} = \frac{0.09\,\frac{J}{m^2}}{2 \cdot 1.05 \cdot 10^{-6}\,m} = (4.3 \pm 0.5) \cdot 10^{+4}\,\frac{J}{m^3} = 0.42 \pm 0.05\,atm$$

534
$$\Delta P_2 = \frac{\gamma_{Graphene-Water}}{2R_2} = \frac{0.09\,\frac{J}{m^2}}{2 \cdot 1.46 \cdot 10^{-6}\,m} = (3.1 \pm 0.5) \cdot 10^{+4}\,\frac{J}{m^3} = 0.31 \pm 0.05\,atm$$

536   To calculate the pressure exerted by graphene directly, without intermediate water, on a hydrated

537   *D.radiodurans*, some approximations can be applied. The first is that the membrane of a *D. radiodurans*

538   is chemically similar to that of *E.coli*, and hence the surface tension can be estimated. Therefore, we can

539   use the measured interaction force between a single flake of pristine graphene and the cell wall of a living

540   *E.coli*: 38.2 ± 16.4 pN. Then, using the following equation [31] we can approximate the interfacial energy:

541
$$\gamma = \frac{F}{L}$$

542   Where F is the adhesive force and L is length over which that force is distributed. In the case of

543   *radiodurans* we can simplify its geometry to a circumference, where d is the diameter of the *radiodurans*

544   which value is in the range of length of the long and short axis previously measured (2.1-2.9 μm):

545
$$\gamma_1 = \frac{F}{\pi \cdot d} = \frac{38.2 \cdot 10^{-12} N}{\pi \cdot 2.1 \cdot 10^{-6} \, m} = \frac{38.2 \cdot 10^{-6} N}{\pi \cdot 2.1 \, m} = 5.8 \cdot 10^{-6} \frac{J}{m^2}$$

546
$$\gamma_2 = \frac{F}{\pi \cdot d} = \frac{38.2 \cdot 10^{-12} N}{\pi \cdot 2.9 \cdot 10^{-6} \, m} = \frac{38.2 \cdot 10^{-6} N}{\pi \cdot 2.9 \, m} = 4.2 \cdot 10^{-6} \frac{J}{m^2}$$

547   The error associated can be calculated using the same equation for error previously displayed, hence:

548
$$E_\gamma = \sqrt{\left(\frac{E_F}{L}\right)^2 + \left(\frac{F \cdot E_L}{L^2}\right)^2}$$

549
$$E_{\gamma_1} = \sqrt{\left(\frac{16.4 \cdot 10^{-6}}{\pi \cdot 2.1}\right)^2 + \left(\frac{16.4 \cdot 10^{-12} \cdot 0.1 \cdot 10^{-6}}{(2.1 \cdot 10^{-6})^2}\right)^2} = 2.5 \cdot 10^{-6} \frac{J}{m^2}$$

550
$$E_{\gamma_2} = \sqrt{\left(\frac{16.4 \cdot 10^{-6}}{\pi \cdot 2.9}\right)^2 + \left(\frac{16.4 \cdot 10^{-12} \cdot 0.2}{2.9^2}\right)^2} = 1.8 \cdot 10^{-6} \frac{J}{m^2}$$

551
$$\gamma_1 = (5.8 \pm 2.5) \cdot 10^{-6} \frac{J}{m^2}$$

552
$$\gamma_2 = (4.2 \pm 1.8) \cdot 10^{-6} \frac{J}{m^2}$$

553 We can estimate the pressure within the encapsulated region from the surface tension exerted by pristine

554 graphene on the membrane surface. This estimation is based on the Laplace pressure equation. The error

555 in this estimation can be calculated using the following equation:

556
$$E_P = \sqrt{\left(\frac{\Delta\gamma}{2R}\right)^2 + \left(\frac{\gamma \cdot \Delta R}{2R^2}\right)^2}$$

557
$$\Delta P_1 = \frac{\gamma_1}{2R_1} = \frac{5.8 \cdot 10^{-6}\frac{J}{m^2}}{2 \cdot 1.05 \cdot 10^{-6}\ m} = 2.76 \pm 1.23\frac{J}{m^3} = (2.7 \pm 1.2) \cdot 10^{-5}atm$$

558
$$\Delta P_2 = \frac{\gamma_2}{2R_2} = \frac{4.2 \cdot 10^{-6}\frac{J}{m^2}}{2 \cdot 1.45 \cdot 10^{-6}\ m} = 1.45 \pm 0.66\frac{J}{m^3} = (1.4 \pm 0.7) \cdot 10^{-5}\ atm$$

559 In addition, this pressure can be compared with the pressure calculated using a more detailed analysis

560 which includes other pressure components such as Van der Waals and elastic, as performed by

561 Khestanova et al[30] in the following equation:

562
$$P = \frac{4\pi\gamma}{5 \cdot 1.7}\left(\frac{5c_1Y}{\pi\gamma}\right)^{\frac{1}{6}}\left(\frac{1}{t \cdot l^2}\right)^{\frac{1}{3}}$$

563 Where γ is the total adhesion energy ($\gamma = \gamma_{Graphene-Graphene} - \gamma_{Graphene-Water}$, where

564 $\gamma_{Graphene-Graphene}$ and $\gamma_{Graphene-Water}$ are the adhesion energy between two graphene layers and

565 graphene and water respectively), Y is the Young's modulus and t and l are the height and the radius of

566 the encapsulated area, respectively. Substituting the variables by the associated values we reach almost

567 twice atmospheric pressure:

569
$$P = 161389.4\ Pa = 1.59\ atm$$

This equation can also be used to estimate the total pressure of other encapsulated biological structures,

such as viruses and proteins, which are of utmost importance in future experiments (Fig. S3).

Fig. S1 *D.radiodurans* morphology and growth stages in graphene encapsulated environments.

A) Brightfield light microscope image of DAPI-stained *D.radiodurans* grown in LB broth,

indicating nucleoid (cyan) and phosphate granules (magenta). **B)** LP-ADF-LPSTEM image (log

grayscale) of encapsulated bacteria at 100kX, with both inner membrane (IM) and outer

membrane (OM), along with graphene blister edge (GB) indicated. LP-ADF-STEM image of

encapsulated early exponential phase (OD_{600}: 0.35) **(C)**, late exponential phase (OD_{600}: 0.65) **(D)**

and late stationary phase (OD_{600}:1.65) **(E)** *D.radiodurans*. **(F)** LP-ADF-STEM image of

encapsulated *D.radiodurans* diad from the late stationary phase sample. (TCF: 93 e^-/nm^2) Scale

bar: A,C-E: 5 µm. B,F: 500 nm.

Fig. S2 Statistical analysis of *D.radiodurans* size distribution.

586   The centre line indicates the median values; × indicates the mean.

Fig. S3 Analysis of the pressure on different volumes of spherical, graphene-encapsulated structures

589 **and its correlation with the size of relevant biological structures.**

Fig. S4 Asymmetric division and other irregularities in septal development in *D.radiodurans*.

A) Individual cocci within a tetrad at different stages of cell division (Late stationary phase). **B)** S-shaped septum without complete perpendicular septum (Late stationary phase). **C)** S-shaped septum with complete perpendicular septum (Early exponential phase**). D)** Diagonal septa within individual cocci in late stationary phase and early exponential phase **(E)**. Scale bar: 500 nm.

597

598 **Fig. S5 Imaging** *D.radiodurans* **at different fluence.**

599 BP-filtered LP-ADF-STEM images of *D.radiodurans* at fluences of **A)** 0.5, **B)** 5.8 and **C)** 65 e/nm^2. Each

600 individual coccus and endogenous polyphosphates are clearly visible at fluences as low as 5.8 e$^-$/nm^2.

601 Scale bar: 2 μm.

Fig. S6 *D.radiodurans* **ultrastructure in graphene encapsulated environments.**

A) Low magnification ADF-STEM image of encapsulated grouped *D.radiodurans* tetrad, Fig.3A ROI

marked in red. **B)** Raw ADF-STEM image of *D.radiodurans*, **C)** After bandpass filter applied to **(B)**, after

contrast enhancement to **(C)**. Corresponding full size power spectra for ROIs in Fig. 3B of storage

granules **(E)**, cytosol **(F; Fig. 3B inset)** and peptidoglycan **(G)**, (18 nm)$^{-1}$ boundary marked by

semicircles. **H)** Radial profile plot of the power spectra **(E-G)**, demonstrating a peak frequency ~0.0417

nm^{-1} in the cytosol not present in the peptidoglycan. Scale bar: A: 1 μm; B-D: 250 nm; PS: (2 nm)$^{-1}$.

Fig. S7 *D.radiodurans* **elemental distribution in graphene encapsulated environments.**

A) Raw ADF-STEM image of Fig.3A and individual element maps. **I)** EDX spectrum of **(A)**, showing

different elemental peaks, with no signal evident for Fe Kα lines. Scale bar: A: 250 nm.

616   **Fig. S8 Manganese accumulation in bacterial phosphate granules.**

617   Individual element maps of D.radiodurans treated with **(A)** and without (**B**) $MnCl_2$. **C)** EDX spectra of

618   individual phosphate granules, selected area marked with dotted lines in **(A)** and **(B)**. Scale bar: A-B: 500

619   nm.