Reconstructing Voice Identity from Noninvasive Auditory Cortex Recordings

Charly Lamothe[1,2] ✉, Etienne Thoret[1,2,3,4], Régis Trapeau[1], Bruno L. Giordano[1], Julien Sein[1,5], Sylvain Takerkart[1], Stéphane Ayache[2], Thierry Artières[2,6,7] ✉, Pascal Belin[1,7] ✉

[1]La Timone Neuroscience Institute UMR 7289, CNRS, Aix-Marseille University, Marseille, France. [2]Laboratoire d'Informatique et Systèmes UMR 7020, CNRS, Aix-Marseille University, Marseille, France. [3]Perception, Representation, Image, Sound, Music UMR 7061, CNRS, Marseille, France. [4]Institute of Language Communication & the Brain, Marseille. [5]Centre IRM-INT@CERIMED, Marseille, France. [6]École Centrale de Marseille, Marseille, France. [7]These authors jointly supervised this work: Thierry Artières, Pascal Belin. ✉e-mail: charlylmth@gmail.com, thierry.artieres@lis-lab.fr, pascal.belin@univ-amu.fr

Abstract

The cerebral processing of voice information is known to engage Temporal Voice Areas (TVAs) that respond preferentially to conspecific vocalizations. But how voice information related to the stable physical characteristics of the speaker such as gender, age or identity is represented by neuronal populations in these areas remains poorly understood. Here we used a deep neural network (DNN) to generate a high-level, small-dimension representational space of voice stimuli—the 'voice latent space' (VLS)—and examined its linear relation with cerebral activity via encoding, representational similarity and decoding analyses. We find that the VLS maps onto fMRI measures of cerebral activity in response to tens of thousands of voice stimuli from hundreds of different speaker identities, and better accounts for the representational geometry for speaker identity in the TVAs than in A1. Moreover, the VLS allowed TVA-based reconstructions of voice stimuli that preserved important aspects of speaker gender and identity as assessed by both machine classifiers and human listeners. These results demonstrate that a low-dimensional, DNN-derived space accounts well for cerebral voice representations and provide insights into representational differences between A1 and the TVAs, paving the way to noninvasive brain-computer interface applications.

Introduction

The human voice carries speech, but is also an "auditory face" that carries much valuable information on the stable physical characteristics of the speaker (hereafter, 'identity-related'; Belin et al., 2004, 2011). The ability of listeners to extract identity-related information in voice such as gender, age, or unique identity even in brief stimuli plays a crucial role in our social interactions, yet its neural bases remain poorly understood compared to those of speech processing. Studies over the past two decades have clearly established via complementary neuroimaging techniques that the cerebral processing of voice information involves a set of temporal voice areas (TVAs) in secondary auditory cortical regions of the human (fMRI: Belin et al., 2000, von Kriegstein et al., 2004, Pernet et al., 2015; EEG, MEG: Charest et al., 2009, Capilla et al., 2013, Barbero et al., 2021; Electrophysiology: Rupp et al., 2022, Zhang et al., 2021) as well as macaque brain (Petkov et al., 2008; Bodin et al., 2021). The TVAs respond more strongly to sounds of voice – with or without speech (Pernet et al., 2015; Rupp et al., 2022; Trapeau et al., 2023)—and categorize voice apart from other sounds (Bodin et al., 2021) but the nature of the information encoded at these stages of cortical processing, especially with respect to speaker identity-related information, remains largely unknown (Blank et al., 2014; Belin et al., 2018).

In recent years, deep neural networks (DNNs) have emerged as a powerful tool for representing complex visual data, such as images (LeCun, Bengio, & Hinton, 2015) or videos (Liu et al., 2020). In the auditory domain, DNNs have been shown to provide valuable representations—so called feature or latent spaces—for modeling the cerebral processing of sound (brain encoding) (speech: Kell et al., 2018, Millet et al., 2022; semantic content Caucheteux et al., 2022, Caucheteux et King, 2022, Caucheteux et al., 2023, Giordano et al., 2023; music: Güçlü et al., 2016), or reconstructing the stimuli listened by a participant (brain decoding) (Akbari et al., 2019). They have not yet been used to explain cerebral representations of identity-related information, due in part to the focus on speech information (von Kriegstein 2003; Morillon et al., 2022).

Here, we addressed this challenge by training a 'Variational autoencoder' (VAE; Kingma et

Welling, 2014) DNN to reconstruct voice spectrograms from 182,000 250-ms voice samples

from 405 different speaker identities in 8 different languages form the CommonVoice

database (Ardila et al., 2020). Brief (250ms) samples were used in order to emphasize

speaker identity-related information in voice, already available after a few hundreds of

milliseconds (Schweingerger et al., 1997; Lavan, 2023), over linguistic information unfolding

over longer time periods. While a quarter of a second is admittedly short compared to

standards of e.g. computational speaker identification that typically uses 2-3s samples, this

short duration is sufficient to allow near perfect gender classification and performance levels

well above chance for speaker discrimination (Fig. 5). This brief duration allowed presenting

many more stimuli to our participants in the scanner, while preserving acceptable levels of

behavioral and classifier performance.

State-of-the-art studies have largely relied on task-optimized neural networks (i.e., DNN

trained using supervised learning to classify a category from the input) to study sensory

cortex processes (Yamins et DiCarlo, 2016; Schrimpf et al., 2018). They can reach high

accuracies in brain encoding (Khaligh-Razavi and Kriegeskorte, 2014; Schrimpf et al., 2018;

Han et al., 2019), however there is increasing evidence that unsupervised learning such as

used for the VAE also provides plausible computational models for investigating brain

processing (Higgins et al., 2021; Zhuang et al, 2021; Millet et al., 2022; Orhan et al., 2022).

Thus, the VAE-derived VLS, exploited within encoding, representational similarity and

decoding frameworks, offers a potentially promising tool for investigating the representations

of voice stimuli in the secondary auditory cortex (Naselaris et al., 2011). Autoencoders learn

to compress stimuli with high dimensionality into a lower-dimensional space that nonetheless

allows reconstruction of the original stimuli via an inverse transformation learned by the

second part of the network called the decoder. Fig. 1a shows the architecture of the VAE,

with its encoder that reduces an input spectrogram to a highly compressed, 128-dimension

voice latent space (VLS) representation, and its decoder that reconstructs the spectrogram

from this VLS representation. Points in the VLS correspond to voice samples with different

identities and phonetic content. A line segment in the VLS contains points corresponding to

perceptual interpolations between its two extremities (Fig. 1b; Supplementary Audio 1). VLS

coordinates of samples presented to the participants averaged by speaker identity suggests

that a major organizational dimension of the latent space is along voice gender (Fig. 1b)

(colored by age or language in Supplementary Figure 1).

In order to test whether VLS accounts well for cerebral activity in response to voice stimuli,

we scanned three healthy volunteers using fMRI to measure an indirect index of their

cerebral activity across 10+ hours of scanning each, in response to ~12,000 of the voice

samples, denoted *BrainVoice* in the following, used to train the DNN. The small number of

participants does not allow for generalization at the level of the general population as in

standard fMRI studies, but allows testing for replicability as in comparable studies involving

10+ hours of scanning per participant (VanRullen & Reddy, 2019). Different stimulus sets

were used across participants to provide a stringent test of replicability based on subject-

level analyses. Stimuli consisted of randomly spliced 250-ms excerpts of speech samples

from the CommonVoice database (Ardila et al., 2020) by 119 speakers in 8 different

languages. For assessing generalization performances of decoding models and brain-based

reconstruction, six different test stimuli were repeated more often (60 times) for each

participant to provide robust estimates of their induced cerebral activity (see Methods). We

first modeled these responses to voice using a general linear model (GLM) (Friston et al.,

1994) with several nuisance regressors as an initial denoising step (Supplementary Figure

4), then used a second GLM modeling cerebral responses to the different speaker identities

(Supplementary Figure 3a), resulting in one voxel activity map per speaker (Supplementary

Figure 3b). We independently localized in each participant several regions of interest (ROIs)

on which subsequent analyses were focused: the anterior, middle and posterior TVAs in

each hemisphere (individually localized via an independent 'voice localizer scan' and MNI

coordinates provided in Pernet et al., 2015; Supplementary Figure 3c) as well as primary

auditory cortex (A1) (using a probabilistic map in MNI space (Penhune et al., 1996;

Supplementary Figure 3d).

We first asked how the VLS could account for the brain responses to speaker identities

(encoding) measured in A1 and the TVAs, in comparison with a linear autoencoder's latent

space (LIN). This approach was chosen because it has been demonstrated that a linear

autoencoder with a d-dimensional hidden layer projects data in the same subspace as the

one spanned by the d first eigenvectors of a principal component analysis (PCA) (Gallinari &

LeCun et al., 1987; Plaut et al., 2018). For this, we used a general linear model (GLM) of

fMRI responses to the speaker identities, resulting in one voxel activity map per speaker

(Supplementary Figure 3). Then, we computed the average VLS coordinates of the fMRI

voice stimuli for each speaker identity, which may be seen as a speaker representation in

the VLS (see *Identity-based and stimulus-based representations* section). Next we trained a

linear voxel-based encoding model to predict the speaker voxel activity maps from the

speaker VLS coordinates. As VAE achieves compression through a series of nonlinear

transformations (Wetzel, 2017), we choose to contrast its results with a linear autoencoder's

latent space. This method has previously been applied to fMRI-based image reconstructions

(Cowen et al., 2014; VanRullen & Reddy, 2019; Mozafari et al., 2020).

The extent to which the VLS allows linearly predicting the fMRI recordings does not provide

insight into the representational geometries, i.e., the differences between the patterns of

cerebral activity for speaker identity. We addressed this subsequent question by using

representational similarity analysis (RSA; Kriegeskorte et al., 2008) in order to test which

model better accounts for the representational geometry for voice identities in the auditory

cortex. Using RSA as a model comparison framework has been shown relevant to examine

the brain-model relationship from complementary angles (Diedrichsen et Kriegeskorte,

2017). We built speaker x speaker representational dissimilarity matrices (RDMs) capturing

pairwise differences in cerebral activity or model predictions between all pairs of speakers;

then we examined how well the LIN and VLS-derived RDMs correlated with the cerebral

RDMs from A1 and the TVAs.

A strong test of the adequacy of models of brain activity, and a long-standing goal in

computational neurosciences, is the reconstruction of a stimulus presented to a participant

from the evoked brain responses. While reconstruction of visual stimuli (images, videos)

from cerebral activity has been performed by a number of groups (VanRullen et Reddy,

2019; Mozafari et al., 2020; Le et al., 2021; Gaziv et al., 2022; Chen et al., 2023), validating

the DNN-derived representational spaces, comparable work in the auditory domain is

scarce, almost exclusively concentrated on linguistic information (Santoro et al., 2017).

Akbari et al. used a DNN to reconstruct speech stimuli based on ECoG recording of auditory

cortex activity, an invasive method compared to techniques like fMRI. They obtained good

phonetic recognition rate, but chance-level gender categorization performance from

reconstructed spectrograms, and no evaluation of speaker identity discrimination.

Here we built on the linear relationship uncovered in our encoding analysis between the VLS

and the fMRI recordings to invert it and try and predict VLS coordinates from the recorded

fMRI data; then, using the decoder, we reconstructed the spectrograms of stimuli presented

to the participants (Wu et al., 2006; Naselaris et al., 2011). The voice identity information

available in the reconstructed stimuli was finally assessed using both machine learning

classifiers and behavioral tasks by human listeners (Fig. 4).

Results

Voice Information in the Voice Latent Space (VLS). In order to probe the informational

content of the VLS, linear classifiers were trained to categorize the voice stimuli from 405

speakers by gender (2 classes), age (2 classes) or identity (119 classes, cf Methods) based

on VLS coordinates, or their LIN features as control (Fig. 1c,d,e; we aggregated the stimuli

from the 3 participants; for each model computed the latent space of each stimulus and

averaged the latent spaces by speaker identity, leading to 405 128-dimensional vectors. We

then trained linear classifiers using a 5-fold cross validation scheme, see *Characterization of*

the autoencoder latent space). The mean of the distribution of accuracies obtained for 100

random classifier initializations (as to account for variance; Bouthillier et al., 2018) was

significantly above chance level (all ps < 1e-10) for all classifications (LIN: gender (mean

accuracy ± s.d.) = 97.64±1.77%, $t(99)=266.94$; age: 64.39±4.54%, $t(99)=31.53$; identity:

40.52±9.14%, $t(99)=39.37$; VLS: gender: 98.59±1.19%, $t(99)=406.47$; age: 67.31±4.86%,

$t(99)=35.41$; identity: 38.40±8.75%, $t(99)=38.73$). We then evaluated the difference in

performance at preserving identity-related information between the VLS and LIN via one-way

ANOVAs. Results showed a significant effect of Feature (LIN/VLS) in categories (all $F_s(1,$

$198) > 225.15$, all ps<.0001) but not in identity. Post-hoc paired t-tests showed that the VLS

was better than the LIN at encoding information related to voice identity, as evidenced by a

significant difference in means for gender ($t(99)=-6.11$, p<.0001), age ($t(99)=-6.10$, p<.0001)

but not for identity classifications ($t(99)=1.71$).

Fig. 1 | DNN-derived Voice Latent Space (VLS). a, *Variational autoencoder (VAE)*

Architecture. Two networks learned complementary tasks. An encoder was trained using

182K voice samples to compress their spectrogram into a 128-dimension representation, the

voice latent space (VLS) while a decoder learned the reverse mapping. The network was

trained end-to-end by minimizing the difference between the original and reconstructed

spectrograms. b, Distribution of the 405 speaker identities along the first 2 principal

components of the VLS coordinates from all sounds, averaged by speaker identity. Each

disk represents a speaker identity colored by gender. PC2 largely maps onto voice gender

(ANOVAs on the first two components: PC1: F(1, 405)=0.10, p=.74; PC2: F(1, 405)=11.00,

p<.001). Large disks represent the average of all male (black) or female (gray) speaker

coordinates, with their associated reconstructed spectrograms (note the flat fundamental

frequency (f_0) and formant frequencies contours caused by averaging). The bottom of

spectrograms illustrate an interpolation between stimuli of two different speaker identities:

spectrograms at the extremes correspond to two original stimuli (A, B) and their VLS-

reconstructed spectrograms (A', B'). Intermediary spectrograms were reconstructed from

linearly interpolated coordinates between those two points in the VLS (red line) (cf.

*Supplementary Audio 1). **c,d e,** Performance of linear classifiers at categorizing speaker*

gender (chance level: 50%), age (young/adult, chance level: 50%) or identity (119 identities,

chance level: 0.84%) based on VLS or LIN coordinates. Error bars indicate standard error of

the mean (s.e.m) across 100 random classifier initializations. All ps<1e-10. The horizontal

*black dashed lines indicate chance levels. ****: p<0.0001.*

Thus, despite its low number of dimensions (each input spectrogram has 401x21=8421

parameters and is summarized in the VLS by a mere 128 dimensions), the VLS appears to

meaningfully represent the different sources of voice information perceptually available in the

vocal stimuli. This representational space therefore constitutes a relevant candidate for

linearly modeling voice stimulus representations by the brain.

Brain Encoding We used a linear voxel-based encoding model to test whether VLS linearly

maps onto cerebral responses to speaker identities measured with fMRI in the different

ROIs. A regularized linear regression model (cf. Methods) was trained on a subset of the

data (5-fold cross validation scheme) to predict the voxel maps for each speaker identity. For

each fold, the trained model was tested on the held-out speaker identities (Fig. 2a). For each

ROI, the performance of the model was assessed using the Pearson correlation score

between the true and the predicted responses of each voxel (Schrimpf et al., 2021). Similar

predictions were tested with features derived from LIN (cf. Methods). Fig. 2b shows, for each

of the ROIs, the distribution of correlation coefficients obtained for the 2 sets of features

across voxels, hemispheres and participants.

One-sample t-tests showed that the means of Fisher z-transformed coefficients for both LIN

features and VLS were significantly higher than zero (LIN: A1 $t(197)=7.25$, $p<.0001$, pTVA

$t(175)=4.49$, $p<.0001$, mTVA $t(164)=9.12$, $p<.0001$ and aTVA $t(147)=6.81$, $p<.0001$; VLS: A1

$t(197)=4.76$, $p<.0001$, mTVA $t(164)=10.12$, $p<.0001$ and aTVA $t(147)=5.52$, $p<.0001$ but not

pTVA $t(175)=-1.60$) (Supplementary Tables 2-3).

A mixed ANOVA performed on the Fisher z-transformed coefficients with Feature (VLS, LIN)

and ROI (A1, pTVA, mTVA, aTVA) as factors showed a significant effect of Feature ($F(3,$

$683)=56.65$, $p<.0001$), a significant effect of ROI ($F(3, 683)=18.50$, $p<.0001$), and a

moderate interaction Feature x ROI ($F(3, 683)=5.25$, $p<.01$). Post-hoc comparisons revealed

that the mean of correlation coefficients was higher for LIN than for VLS in A1 ($t(197)=4.02$,

$p<.0001$), pTVA ($t(175)=6.64$, $p<.0001$), aTVA ($t(147)=3.78$, $p<.001$) but not in mTVA

($t(164)=0.58$) (Supplementary Table 4); and that the voxel patterns are better predicted in

mTVA than in A1 for both models (LIN: $t(361)=2.36$, $p<.05$; VLS: $t(361)=4.91$, $p<.0001$)

(Supplementary Table 5). However, we found by inspecting the distribution of model-voxel

correlations that both models account for different parts of the voice identities responses,

and differently across ROIs (Fig. 2c).

Fig. 2 | Predicting brain activity from the VLS. a, *Linear prediction of brain activity from*

VLS for ~135 speaker identities in the different ROIs. We first fit a GLM to predict the BOLD

responses to each voice speaker identity. Then, using the trained encoder, we computed the

average VLS coordinates of the voice stimuli presented to the participants based on speaker

identity. Finally, we trained a linear voxel-based encoding model to predict the speaker voxel

activity maps from the speaker VLS coordinates. The cube illustrates the linear relationship

*between the fMRI responses to speaker identity and the VLS coordinates. The left face of the cube represents the activity of the voxels for each speaker identity, with each line corresponding to one speaker. The right face displays the VLS coordinates for each speaker identity. The top face of the cube shows the weight vectors of the encoding model. **b,** Encoding results. For each region of interest, the performance of the model was assessed using the Pearson correlation score between the true and the predicted responses of each voxel on the held-out speaker identities. Pearson's correlation coefficients were computed for each voxel on the speakers' axis, then averaged across hemispheres and participants. Similar predictions were tested with the LIN features. Error bars indicate standard error of the mean (s.e.m) across voxels. *p < 0.05; **p < 0.01; **p < 0.001; ****p < 0.0001. **c,** Venn diagrams of the number of voxels in each ROI with the LIN, the VLS or both models. For each ROI and each voxel, we checked whether the test correlation was higher than the median of all participant correlations (intersection circle), and if not which model (LIN or VLS) yielded the highest correlation (left or right circles).*

Representational Similarity Analysis For RSA, we built speaker x speaker representational dissimilarity matrices (RDMs) capturing for each ROI the dissimilarity in voxel space between each pair of speaker voxel maps ('brain RDMs'; cf. Methods) using Pearson's correlation (Walther et al., 2016). We compared these four bilateral brain RDMs (A1, aTVA, mTVA, pTVA) to two 'model RDMs' capturing speaker pairwise feature differences predicted by LIN and the VLS (Fig. 3a) built using cosine distance (Xing et al., 2015; Bhattacharya et al., 2017; Wang et al., 2018). Fig. 3b shows for each ROI the Spearman correlation coefficients between the brain RDMs and the two model RDMs, for each participant and hemisphere (Kriegeskorte et al., 2008; Fig. 3c for an example of brain-model correlation).

These brain-model correlation coefficients were compared to zero using a 'maximum statistics' approach based on random permutations of the model RDMs' rows and columns, (Maris & Oostenveld, 2007; cf. Methods; Fig. 3b). For the LIN model, only one brain-model

RDM correlation was significantly different from zero (one-tailed test): in mTVA, right

hemisphere in S3 (p=.0500). For the VLS model, in contrast, 5 significant brain-model RDM

correlations were observed in all four ROIs: in A1, right hemisphere in S3 (p=.0142); pTVA:

right hemisphere in S3 (p=.0160); mTVA: left hemisphere in S3 (p=.007); aTVA: left

hemispheres in S1 (p=.0417) and S3 (p=.0001) (Supplementary Table 6).

A two-way repeated-measures ANOVA with Feature (VLS, LIN) and ROI (A1, pTVA, mTVA,

aTVA) as factors performed on the Fisher z-transformed correlation coefficients showed a

tendency towards a significant effect of Feature ($F(1, 2)=22.53$, $p=.04$), and no ROI ($F(3,$

$6)=1.79$, $p=.30$) or interaction effects ($F(3, 6)=1.94$, $p=.22$). We compared the correlation

coefficients between the VLS and LIN models within participants and hemispheres using

one-tailed tests, based on the a priori hypothesis that the VLS models would exhibit greater

brain-model correlations than the LIN models (cf. Methods). The results revealed two

significant differences in one of the three participants, both in favor of the VLS model (S3:

right pTVA, p=.0366; left aTVA, p=.00175) (Supplementary Table 7).

Fig. 3 | The VLS better explains representational geometry for voice identities in the TVAs than the linear model. a, *Representational dissimilarity matrices (RDMs) of pairwise speaker dissimilarities for ~135 identities (arranged by gender, cf. side bars), according to LIN and VLS.* **b,** *Spearman correlation coefficients between the brain RDMs for A1 and the 3 TVAs, and the 2 model RDMs. Error bars indicate standard error of the mean (s.e.m) across brain-model correlations.* **c,** *Example of brain-model RDM correlation in the TVAs. The VLS RDM and the brain RDM yielding one of the highest correlations (LaTVA) are shown in insert.*

Decoding and Reconstruction We finally inverted the brain-VLS relationship to predict

linearly VLS coordinates based on fMRI measurements (Fig. 4a; see 'Brain decoding' in

Methods), and reconstruct via the trained decoder the spectrograms of 18 Test Stimuli (3

participants x 6 stimuli per participant; see Fig. 4b, and Supplementary Audio 2; audio

estimated from spectrogram through phase reconstruction).

Fig. 4 | Reconstructing voice identity from brain recordings. a, A linear voxel-based

decoding model was used to predict the VLS coordinates of 18 Test Stimuli based on fMRI

responses to ~12 000 Train stimuli in the different ROIs. To reconstruct the audio stimuli

from the brain recordings, the predicted VLS coordinates were then fed to the trained

decoder to yield reconstructed spectrograms, synthesized into sound waveforms using the

Griffin-Lim phase reconstruction algorithm (Griffin & Lim, 1983). b, Reconstructed

spectrograms of the stimuli presented to the participants. Left panels show the spectrogram

 of example original stimuli reconstructed from the VLS, and the right panels brain-

 reconstructed spectrograms via LIN and the VLS (cf Supplementary Audio 2).

We first assessed the nature of the reconstructed stimuli by using a DNN trained to

categorize natural audio events (Howard et al., 2017): all reconstructed versions of the 18

Test Stimuli were categorized as 'speech' (1 class out of 521 - no 'voice' classes). To

evaluate the preservation of voice identity information in the reconstructed voices, pre-

trained linear classifiers were used to classify the speaker gender (2 classes), age (2

classes), and identity (17 classes) of the 18 reconstructed Test Stimuli. The mean of the

accuracy distribution obtained across random classifier initializations (20 per ROI) used on

the stimuli reconstructed from the induced brain activity was significantly above chance level

for gender (LIN: pTVA (mean accuracy ± s.d.): 72.08±5.48, $t(39)=25.15$; VLS: A1:

61.11±2.15, $t(39)=32.25$; pTVA: 63.89±2.78, $t(39)=31.22$), age (LIN: pTVA: 54.58±4.14,

$t(39)=6.90$; aTVA: 63.96±12.55, $t(39)=6.94$; VLS: pTVA: 65.00±7.26, $t(39)=12.89$; aTVA:

60.42±5.19, $t(39)=12.54$) and identity (LIN: A1: 9.20±9.23, $t(39)=2.24$; pTVA: 9.48±4.90,

$t(39)=4.59$; aTVA: 9.41±6.28, $t(39)=3.51$; VLS: pTVA: 16.18±7.05, $t(39)=9.11$; aTVA:

8.23±4.70, $t(39)=3.12$) (Fig. 5a-c; Supplementary Tables 8-10).

Two-way ANOVAs with Feature (VLS, LIN) and ROI (A1, pTVA, mTVA, aTVA) as factors

performed on classification accuracy scores (gender, age, identity) revealed for gender

classifications significant effects of Feature $F(1, 312)=12.82$, $p<.0005$) and of ROI (gender:

$F(3, 312)=245.06$, $p<.0001$; age: $F(3, 312)=64.49$, $p<.0001$; identity: $F(3, 312)=14.49$,

$p<.0001$), as well as Feature x ROI interactions (gender: $F(3, 312)=56.74$, $p<.0001$; age:

$F(3, 312)=4.31$, $p<.001$; identity: $F(3, 312)=8.82$, $p<.0001$). Post-hoc paired t-tests indicated

that the VLS was better than LIN in preserving gender, age and identity information in at

least one TVA compared with A1 (gender: aTVA: $t(39)=5.13$, $p<.0001$; age: pTVA:

$t(39)=9.78$, $p<.0001$; identity: pTVA: $t(39)=4.01$, $p<.0005$) (all tests in Supplementary Table

11). Post-hoc two sample t-tests comparing ROIs revealed significant differences in all

classifications, in particular with pTVA outperforming other ROIs in gender (LIN: pTVA vs A1:

t(78)=22.40, p<.0001; pTVA vs mTVA: t(78)=10.92, p<.0001; pTVA vs aTVA: t(78)=31.47,

p<.0001; VLS: pTVA vs A1: t(78)=4.94, p<.0001; pTVA vs mTVA: t(78)=13.96, p<.0001;

pTVA vs aTVA: t(78)=22.06, p<.0001), age (LIN: pTVA vs A1: t(78)=7.26, p<.0001; pTVA vs

mTVA: t(78)=10.11, p<.0001; VLS: pTVA vs A1: t(78)=5.71, p<.0001; pTVA vs mTVA:

t(78)=10.11, p<.0001; pTVA vs aTVA: t(78)=3.21, p<.005) and identity (LIN: pTVA vs mTVA:

t(78)=2.27, p<.05; VLS: pTVA vs A1: t(78)=6.45, p<.0001; pTVA vs mTVA: t(78)=6.62,

p<.0001; pTVA vs aTVA: t(78)=5.85, p<.0001) (Supplementary Table 12).

We further evaluated voice identity information in the reconstructed stimuli by testing human

participants (n=13) in a series of 4 online experiments assessing the reconstructed stimuli

on: (i) naturalness judgment; (ii) gender categorization; (iii) age categorization; and (iv)

speaker categorization (cf Methods). The naturalness rating task showed that the VLS-

reconstructed stimuli sounded more natural compared to LIN-reconstructed ones, as

revealed by a two-way repeated-measures ANOVA (factors: Feature and ROI) with a strong

effect of Feature (F(1, 12)=53.72, p<.0001) and a small ROI x Feature interaction (F(3,

36)=5.36, p<.005). Post-hoc paired t-tests confirmed the greater naturalness of VLS-

reconstructed stimuli in both A1 and the TVAs (all ps<.0001) (Fig. 5g).

For the gender task, one-sample t-tests showed that categorization of the reconstructed

stimuli was only significantly above chance level for the VLS (A1: (mean accuracy ± s.d.)

55.77±10.84, t(25)=2.66, p<.01; pTVA: 61.75±7.11, t(25)=8.26, p<.0001; aTVA: 55.13±9.23,

t(25)=2.78, p<.01). Regarding the age and speaker categorizations, results also indicated

that both the LIN- and VLS-reconstructed stimuli yielded above-chance performance in the

TVAs (age: LIN: aTVA, 55.77±14.95, t(25)=1.93, p<.05; VLS: aTVA, 63.14±11.82,

t(25)=5.56, p<.0001; identity: LIN: pTVA: 54.38±9.34, t(17)=1.93, p<.05; VLS: pTVA:

63.33±6.75, t(17)=8.14, p<.0001) (Supplementary Tables 13-15). Two-way repeated-

measures ANOVAs revealed a significant effect of ROI for all categories (gender: F(3,

27)=5.90, p<.05; age: F(3, 36)=14.25, p<.0001; identity: F(3, 24)=38.85, p<.0001), and a

Feature effect for gender (F(1, 9)=43.61, p<.0001) and identity (F(1, 8)=14.07, p<.001), but

not for age (F(1, 12)=4.01, p=0.07), as well as a ROI x Feature interaction for identity

356 discrimination (F(3, 24)=3.52, p<.05) (Supplementary Tables 16-17 for the model and ROI

357 comparisons).

Fig. 5 | Behavioural and machine classification of the reconstructed stimuli. a,b,c,

Decoding of voice identity information in brain-reconstructed spectrograms. Performance of

linear classifiers at categorizing speaker gender (chance level: 50%), age (chance level:

50%), and identity (17 identities, chance level: 5.88%). Error bars indicate s.e.m across 40

random classifier initializations per ROI (instance of classifiers; 2 hemispheres x 20 seeds).

The horizontal black dashed line indicates chance level. The blue and yellow dashed lines

*indicate ceiling levels for the LIN and the VLS respectively. *p < .05; **p < .001, ***p < .001;*

*****p < .0001. **d,e,f,** Listener performance at categorizing speaker gender (chance level:*

50%) and age (chance level: 50%), and at identity discrimination (chance level: 50%) in the

brain-reconstructed stimuli. Error bars indicate s.e.m across participant scores. The

horizontal black dashed line indicates chance level, while the red, blue and yellow dashed

lines indicate the ceiling levels for the original stimuli, the LIN-reconstructed and the VLS-

*reconstructed, respectively. *p < .05; **p < .01; ***p < .001, ***p < .0001. **g,** Perceptual*

ratings of voice naturalness in the brain-reconstructed stimuli' as assessed by human

*listeners. *p < .05, ****p < .0001.*

Discussion

In this study we examined to what extent the cerebral activity elicited by brief voice stimuli can be explained by machine-learned representational spaces, with a specific focus on identity-related information. We trained a linear model and a DNN model to reconstruct 100,000s of short voice samples from 100+ speakers, providing low-dimensional spaces (LIN and VLS) which we related to fMRI measures of cerebral response to thousands of these stimuli. We find: (i) that 128 dimensions are sufficient to explain a sizeable portion of the brain activity elicited by the voice samples and yield brain-based voice reconstructions that preserve identity-related information; (ii) that the DNN-derived VLS outperforms the LIN space particularly in yielding more brain-like representational spaces and more naturalistic voice reconstructions; (iii) that different ROIs have different degrees of brain-model relationship, with marked differences between A1 and the the a, m, and pTVAs.

Low-dimensional spaces generated by machine learning have been used to approximate cerebral face representations and reconstruct recognizable faces based on fMRI (VanRullen et Reddy, 2019; Dado et al, 2022). In the auditory domain, however, they have mostly been used with a focus on linguistic (speech) information, ignoring identity-related information (but see Akbari et al., 2019). Here we applied them to brief voice stimuli–with minimal linguistic content but already rich identity-related information–and found that as little as 128 dimensions account reasonably well for the complexity of cerebral responses to thousands of these voice samples as measured by fMRI (Fig. 2). LIN and VLS both showed brain-like representational geometries, particularly the VLS in the aTVAs (Fig. 3). They made possible what is to our knowledge the first fMRI-based voice reconstructions to preserve voice-related identity information such as gender, age or even individual identity, as indicated by above-chance categorization or discrimination performance by both machine classifiers (Fig. 5a-c) and human listeners (Fig. 5d-f). Note that LIN and VLS also represent the limited linguistic content of the brief stimuli, as indicated by high language classification performance (Supplementary Figure 4).

Estimation of fMRI responses (encoding) by LIN yielded correlations largely comparable to

those by VLS (Fig. 2b) although many voxels were only explained by one or the other space

(Fig. 2c). But in the RSA, VLS yielded higher overall correlations with brain RDMs (Fig. 3),

suggesting a representational geometry closer to that instantiated in the brain than LIN.

Further, VLS-reconstructed stimuli sounded more natural than the LIN-reconstructed ones

(Fig. 5g) and yielded both the best speaker discrimination by listeners (Fig. 5f) and speaker

classification by machine classifiers (Fig. 5c). Unlike LIN, which was generated via linear

transforms, VLS was obtained through a series of nonlinear transformations (Wetzel, 2017).

The fact that the VLS outperforms LIN in terms of decoding performance is an indication that

nonlinear transformation is required to better account for brain representation of voices

(Naselaris et al., 2011; Cowen et al., 2014; Han et al., 2019).

Comparisons between ROIs revealed important differences between A1 and the a, m and

pTVAs. For both LIN and VLS, predictions of fMRI signal (encoding) were more accurate for

the mTVAs than for A1, and for A1 than for the pTVAs (Fig. 2b). The aTVAs yielded the

highest correlations with the models in the RSA (Fig. 3). Stimulus reconstructions (Fig. 4)

based on the TVAs also yielded better gender, age and identity classification than those

based on A1, with gender and identity best preserved in the pTVA-, and to a lesser extent, in

the aTVA-based reconstructions (Fig. 5). These results show that the a and pTVAs not only

respond more strongly to vocal sounds than A1, they also better represent identity-related

information in voice better than mTVA, which was previously anticipated in some

neuroimaging studies (Latinus et al., 2011; Charest et al., 2013; Aglieri et al., 2021).

Overall, we show that a DNN-derived representational space provides an interesting

approximation of the cerebral representations of brief voice stimuli that can preserve identity-

related information. We find remarkable that such results could be obtained to explain sound

representations despite the poor temporal resolution of fMRI. Future work combining more

complex architectures to time-resolved measures of cerebral activity such as magneto-

encephalography (Défossez et al., 2023) or ECoG (Pasley et al., 2012) will likely yield better

models of the cerebral representations of voice information.

Methods

Experimental procedure overview

Three participants attended 13 MRI sessions each. The first session was dedicated to

acquire high-resolution structural data, as well as to identify the voice-selective areas of

each participant using a 'voice localizer' based on different stimuli than those in the same

experiment (Pernet et al., 2015; see below).

The next 12 sessions began with the acquisition of two fast structural scans for inter-session

realignment purposes, followed by six functional runs, during which the main stimulus set of

the experiment was presented. Each functional run lasted approximately 12 minutes.

Participants 1 and 2 attended all scanning sessions (72 functional runs in total); due to

technical issues, Participant 3 only performed 24 runs.

Participants were instructed to stay in the scanner while listening to the stimuli. To maintain

participants' awareness during functional scanning, they were asked to press an MRI-

compatible button each time they heard the same stimulus two times in a row, a rare event

occurring 3% of the time (correct button hits (median accuracy ± s.d.): S1=96.67±7.10,

S2=100.00±0.89, S3=95.00±3.68).

Scanning sessions were spaced by at least two days to avoid possible auditory fatigue due

to the exposure to scanner noise. To ensure that participants' hearing abilities did not vary

across scanning sessions, hearing thresholds were measured before each session using a

standard audiometric procedure (Martin and Champlin, 2000; ISO 2004) and compared with

the thresholds obtained prior the first session.

Participants

This study was part of the project 'Réseaux du Langage' and was promoted by the National Center for Scientific Research (CNRS). It has been given favorable approval by the local ethics committee (Comité de Protection des Personnes Sud-Méditerranée) on the date of 13th February 2019. The National Agency for Medicines (ANSM) has been informed of this study, which is registered under the number 2017-A03614-49. Three native French human speakers were scanned (all females; 26-33 years old). Participants gave written informed consent and received a compensation of 40€ per hour for their participation. All were right-handed and no one had hearing disorder or neurological disease. All participants had normal hearing thresholds of 15 dB HL, for octave frequencies between 0.125 and 8 kHz.

Stimuli

The auditory stimuli were divided into two sequences. One 'voice localizer' sequence to identify the voice-selective areas of each participant (Pernet et al., 2015) and a main voice stimuli.

Voice localizer stimuli. The voice localizer stimuli consisted of 96 complex sounds of 500ms grouped in four categories of human voice, macaque vocalizations, marmoset vocalizations, and complex non-vocal sounds (more details in Bodin et al., 2021).

Main voice stimuli. The main stimulus set consisted of brief human voice sounds sampled from the Common Voice dataset (Ardila et al., 2020). Stimuli were organized into four main category levels: language (English, French, Spanish, Deutch, Polish, Portuguese, Russian, Chinese), gender (female/male), age (young/adult; young: teenagers and twenties; adult: thirties to sixties included) and identity (S1: 135 identities; S2: 142 identities; S3: 128 identities; ~44 samples per identity). Throughout the manuscript, the term 'gender' rather than 'sex' was utilized in reference to the demographic information obtained from the participants of the Common Voice dataset (Ardila et al., 2020), as it was the terminology employed in the survey ('male/female/other'). Stimulus sets were different for each

participant and the number of stimuli per set also varied slightly (number of unique stimuli:

Participant 1, N=6150; Participant 2, N=6148; Participant 3, N=5123). For each participant,

six stimuli were selected randomly among the sounds having a high energy (as measured

with the amplitude envelope) from their stimulus set and were repeated extensively (60

times), to improve the performance of the brain decoding (VanRullen et Reddy, 2019;

Horikawa & Kamitani, 2017; Chang et al., 2019); these will be called the "repeated" stimuli

hereafter, the remaining stimuli were presented twice. The third participant attended 5

BrainVoice sessions instead of 12, one BrainVoice session corresponding to 1030 stimuli

(1024 unique stimuli and 6 'test' stimuli). Specifically, 5270 stimuli were presented to the

third participant instead of ~12,000 for the two others. Among these 5270 stimuli, 5120

unique stimuli were presented once, as for the two other participants, 6 'test' stimuli were

presented 25 times (150 trials). The stimuli were balanced within each run according to

language, gender, age, and identity, as to avoid any potential adaptation effect. In addition,

identity was balanced across sessions.

All stimuli of the main set were resampled at 24414 Hz and adjusted in duration (250 ms).

For each stimulus, a fade-in and a fade-out were applied with a 15 ms cosine ramp to their

onset and offset, and were normalized by dividing the root mean square amplitude. During

fMRI sessions, stimulus presentations were controlled using custom Matlab scripts

(Mathworks, Natick, MA, USA) interfaced with an RM1 Mobile Processor (Tucker-David

Technologies, Alachua, USA). The auditory stimuli were delivered pseudo-randomly through

MRI-compatible earphones (S14, SensiMetrics, USA) at a comfortable sound pressure level

that allowed for clear and intelligible listening.

Computational models

We used two computational models to learn representational space for voice signals, Linear

Autoencoder (LIN) and Deep Variational Autoencoder (VAE; Kingma et Welling., 2014). Both

are encoder-decoder models that are learnt to reproduce at their output their input while

going through a low dimensional representation space usually called latent space (that we

will call *voice latent space* since they are learnt on voice data). The autoencoders were

trained on a dataset of 182K sounds from the Common Voice dataset (Ardila et al., 2020),

balanced in gender, language and identity to reduce the bias in the synthesis (Gutierrez et

al., 2021). Both models operate on sounds which were represented as spectrograms that we

describe below. These representations were tested in all the encoding/decoding and RSA

analyses.

Spectrograms

We used amplitude spectrograms as input of the models that we describe below. Short term

Fourier transforms of the waveform were computed using a sliding window of length 50 ms

with a hop size of 12.5 ms (hence an overlap of 37.5 ms) and applying a Hamming window

of size 800 samples before computing the Fourier transform of each slice. Only the

magnitude of the spectrogram was kept and the phase of the complex representation was

removed. At the end, a 250 ms sound is represented by a 21×401 matrix with 21 time steps

and 401 frequency bins.

We used a custom code based on $numpy.fft$ package (Harris et al., 2020). The size and

the overlap between the sliding windows of the spectrogram were chosen to conform with

the uncertainty principle between time and frequency resolution. The main constraint was to

find a trade-off between accurate phase reconstruction with the Griffin & Lim algorithm

(1983) and a reasonable size of the spectrogram.

We standardized each of the 401 frequency bands separately, by centering all the data

corresponding to each frequency band at every time step in all spectrograms, which involved

removing their mean, and dividing by their standard deviation. This separate standardization

of frequency bands resulted in a smaller reconstruction error compared to standardizing

across all the bands.

Deep neural network

We designed a deep variational autoencoder (VAE; Kingma et Welling, 2014) of 15 layers

with an intermediate hidden representation of 128 neurons that we refer to as the *voice*

latent space (VLS). In an autoencoder model, the two sub-network components, the *Encoder*

and the *Decoder*, are jointly learned on complementary tasks (Fig. 1a). The Encoder network

(noted Enc hereafter; 7 layers) learns to map an input, s (a spectrogram of a sound), onto a

(128-dimensional) *voice latent space* representation (z; in blue in the middle of Fig. 1a),

while the Decoder (noted Dec hereafter; 7 layers) aims at reconstructing the spectrogram s

from z. The learning objective of the full model is to make the output spectrogram

$Dec(Enc(s))$ as close as possible to the original one s. This reconstruction objective is

defined as the L2 loss, $||Dec(Enc(s)) - s||^2$. The parameters of the Encoder and of the

Decoder are jointly learned using gradient descent to optimize the average L2 loss

computed on the training set $\sum_{s \in Training\ Set} ||Dec(Enc(s)) - s||^2$. We trained this DNN on

the Common Voice dataset (Ardila et al., 2020) according to VAE learning procedure (as

explained in Kingma et Welling., 2019) until convergence (network architecture and

particularities of the training procedure are provided in Supplementary Table 1), using the

PyTorch python package (Paszke et al., 2019).

Linear autoencoder

We trained a linear autoencoder on the same dataset (described above) to serve as a linear

baseline. Both the *Encoder* and the *Decoder* networks consisted of a single fully-connected

layer, without any activation functions. Similar to the VAE, the latent space obtained from the

Encoder was a 128-dimensional vector. The parameters of both the *Encoder* and of the

Decoder were jointly learned using gradient descent to optimize the average L2 loss

computed on the training set.

Neuroimaging data acquisition

Participants were scanned using a 3 Tesla Prisma scanner (Siemens Healthcare, Erlangen, Germany) equipped with a 64-channel receiver head-coil. Their movements were monitored during the acquisition using the software FIRMM (Dosenbach et al., 2017). The whole-head high-resolution structural scan acquired during the first session was a T1-weighted multi-echo MPRAGE (MEMPRAGE) (TR = 2.5 s, TE = 2.53, 4.28, 6.07, 7.86 ms, TI=1000 ms flip angle: 8°, matrix size = 208 × 300 × 320; resolution 0.8 × 0.8 × 0.8 mm^3, acquisition time: 8min22s). Lower resolution scans acquired during all other sessions were T1-weighted MPRAGE scans (TR = 2.3 s, TE = 2.88 ms, TI=900ms, flip angle: 9°, matrix size = 192 × 240 × 256; resolution 1 × 1 × 1 mm^3, sparse sampling with 2.8 times undersampling and compressed sensing reconstruction, acquisition time: 2min37). Functional imaging was performed using an EPI sequence (multiband factor = 5 , TR = 462 ms, TE = 31.2 ms, flip angle: 45°, matrix size = 84 × 84 × 35, resolution 2.5 × 2.5 × 2.5 mm^3). Functional slices were oriented parallel to the lateral sulci with a z-axis coverage of 87.5 mm, allowing it to fully cover both the TVAs (Pernet et al., 2015) and the FVAs (Aglieri et al., 2018). The physiological signals (heart rate and respiration) were measured with the external sensors of Siemens.

Pre-processing of neuroimaging data and general linear modeling

Tissue segmentation and brain extraction was performed on the structural scans using the default segmentation procedure of SPM 12 (Ashburner et al., 2012). The preprocessing of the BOLD responses involved correcting motion, registering inter-runs, detrending and smoothing the data. Each functional volume was realigned to a reference volume taken from a steady period in the session that was spatially the closest to the average of all sessions. Transformation matrices between anatomical and functional data were computed using boundary-based registration (FSL; Smith et al., 2004). The data were respectively detrended and smoothed using the *nilearn* functions $clean\_img$ and $smooth\_img$ (kernel size of 3mm)

(Abraham et al., 2014), resulting in the matrix $Y \in R^{S \times V}$, with S the number of scans and V

the number of voxels.

A first general linear model (GLM) was fit to regress out the noise by predicting Y from a

"denoised" design matrix, composed of $R = 38$ regressors of nuisance (Supplementary

Figure 4). These regressors of nuisance, also called covariates of no interest, included: 6

head motion parameters (3 variable for the translations, 3 variables for the rotations); 18

'RETROICOR' regressors (Glover et al., 2000) using the *TAPAS PhysIO* package (Kasper et

al., 2017) (with the hyperparameters set as specified in Snoek et al.) were computed from

the physiological signals; 13 regressors modeling slow artifactual trends (sines and cosines,

cut frequency of the high-pass filter = 0.01 Hz); and a confound-mean predictor. The design

matrix was convolved with an hemodynamic response function (HRF) with a peak at 6s and

an undershoot at 16s (Glover et al., 1999), we note the convolved design matrix as $X_d \in$

$R^{S \times R}$. The "denoise" GLM's parameters $\beta_d \in R^{R \times V}$ were optimized to minimize the

amplitude of the residual $\beta_d = argmin_{\beta \in R^{R \times V}} \ || \ Y \ - X_d \ \beta \ ||^2$. We used a lag-1

autoregressive model (ar(1)) to model the temporal structure of the noise (Friston et al.,

2002). The *denoised* BOLD signal Y_d was then obtained from the original one according to

$Y_d = Y - (X_d \ \beta_d) \in R^{S \times V}$.

A second "stimulus" GLM model was used to predict the denoised BOLD responses for each

stimulus using a design matrix $X_s \in R^{S \times (N_S+1)}$ (which was convolved with an hemodynamic

response function, HRF as above) and a parameters matrix $\beta_s \in R^{(N_S+1) \times V}$ where N_S stands

for the number of stimuli. The last row (resp. column) of β_s (resp. X_s) stands for a silence

condition. Again, β_s was learned to minimize the residual $\beta_s = argmin_{\beta \in R^{(N_S+1) \times V}} \ || Y_d -$

$X_s \ \beta \ ||^2$. Once learned, each of the first N_s line of β_s was corrected by subtracting the

$(N_s+1)^{th}$ line, yielding the contrast maps for stimuli $\tilde{\beta}_s \in R^{N_S \times V}$. We note hereafter $\tilde{\beta}_s[i, :] \in$

R^V the contrast map for a given stimulus, it is the i^{th} line of $\tilde{\beta}_s$.

A third "identity" GLM was fit to predict the BOLD responses of each voice speaker identity,

using a design matrix $\beta_i \in R^{(N_i+1) \times V}$ and a design matrix $X_i \in R^{S \times (N_i+1)}$ (which was again

convolved with an hemodynamic response function, HRF) where N_s stands for the number

of unique speakers. Again the last row/column in β_i and X_i stands for the silent condition. β_i

is learned to minimize the residual $\beta_i = argmin_{\beta \in R^{(N_i+1) \times V}} ||Y_d - X_i \beta ||^2$ (Supplementary

Figure 3a). Again, the final speaker contrast maps were obtained by contrasting (i.e.,

subtracting) the regression coefficients in a row of β_i with the silence condition (last row;

Supplementary Figure 3a), yielding $\tilde{\beta}_i \in R^{N_s \times V}$. Here the j^{th} row of $\tilde{\beta}_i$, $\tilde{\beta}_i[j,:] \in R^V$,

represents the amplitude of the BOLD response of the contrast map for speaker j (i.e. to all

the stimuli from this speaker).

A fourth "localizer" GLM model was used to predict the denoised BOLD responses of each

sound category from the *Voice localizer stimuli* presented above. The procedure was similar

as described for the two previous GLM models. Once the GLM was learned, we contrasted

the human voice category with the other sound categories in order to localize for each

participant the posterior Temporal Voice Area (pTVA), medial Temporal Voice Area (mTVA)

and anterior Temporal Voice Area (aTVA) in each hemisphere. The center of each TVA

corresponded to the local maximum of the voice > non voice t-map whose coordinates were

the closest to the TVAs reported in (Pernet et al., 2015). The analyses were carried on for

each region of interest (ROI) of each hemisphere.

Additionally, we defined for each participant the primary auditory cortex (A1) as the

maximum value of the probabilistic map (non-linearly registered to each participant

functional space) of Heschl's gyri provided with the MNI152 template (Penhune et al., 1996),

intersected with the sound vs silence contrast map.

Identity-based and stimulus-based representations

We performed analyses either at the stimulus level, e.g. predicting the neural activity of a

participant listening to a given *stimulus* ($\tilde{\beta}_s$'s lines) from the *voice latent space* representation

of this stimuli, or at the speaker identity level, e.g. predicting the average neural activity in

response to stimuli of a given speaker *identity* ($\tilde{\beta}_i$'s lines) from this speaker's *voice latent*

space representation. The identity-based analyses were used for the characterization of the

voice latent space (Fig. 1), the brain encoding (Fig. 2), and the representational similarity

analysis (Fig. 3), while the stimulus-based analyses were used for the brain decoding

analyses (Fig. 4, 5).

We conducted stimulus-based analyses to examine the relationship between stimulus

contrast maps in neural activity ($\tilde{\beta}_s$) and the encodings of individual stimulus spectrograms

computed by the encoder of an autoencoder model (either linear or deep variational

autoencoder) on the computational side. We will note $z_s^{lin} \in R^{N_s \times 128}$ encodings of stimuli

by the LIN model and $z_s^{vae} \in R^{N_s \times 128}$ the encodings of stimuli computed by the VAE

model. The encoding of the kth stimuli by one of these models is the kth row of the

corresponding matrix and it is noted as $z_s^{model}[k,:]$.

For identity-based analyses we studied relationships between identity contrast maps in $\tilde{\beta}_i$ on

the neural activity side, and an encoding of speaker identity in the VLS implemented by an

autoencoder model (LIN or VAE) on the computational side, e.g. we note $z_i^{vae}[j]$ the

representation of speaker *j* as computed by the *vae* model. We chose to define a speaker

identity-based representation as the average of a set of sample-based representations for

stimuli from this speaker, e.g. $z_i^{model}[j] = 1/|S_j| \sum_{k \in S_j} z_s^{model}[k,:]$ where S_j stands for the

set of stimuli by speaker *j* and *model* stands for *vae* or *lin*. Averaging in the *voice latent*

space is expected to be much more powerful and relevant than averaging in the input space

spectrograms (VanRullen & Reddy, 2019).

Characterization of the autoencoder latent space

We characterized the organization of the *voice latent space* (VLS) and of the features

computed by the linear autoencoder (LIN) by measuring through classification experiments

the presence of information about speaker's gender, age, and identity in the representations

learned by these models.

We first computed the speaker's identity *voice latent space* representations for each of the

405 speakers in the main voice dataset (135+142+128 see *Stimuli* section) as explained

above.

Next we used these speakers' *voice latent space* representation to investigate if the gender,

age, identity were encoded in the VLS. To do so we divided the data in separate train and

test sets and learned classifiers to predict gender, age, or identity from the train set. The

balanced (to avoid the small effects associated with unbalanced folds) accuracy of the

classifiers were then evaluated on the test set. The higher the performance on the test set

the more we are confident that the information is encoded in the VLS. More specifically for

each task (gender, age, identity), we trained a Logistic Regression classifier (linear

regularized logistic regression; L2 penalty, tol=0.0001, fit_intercept=True,

intercept_scaling=1, max_iter=100) using the scikit-learn python package (Pedregosa et al.,

2018).

In order to statistically evaluate the significance of the results and to avoid a potential

overfitting, the classifications were repeated 20 times with 20 different initializations (*seed*)

and the metrics were then averaged for each voice category (gender, age). More

specifically, we repeated the following experiment 20 times with 20 different random seeds.

For each seed, we performed 5 train-test splits with 80% of the data in the training and 20%

in the test set. For each split we used 5-fold cross validation on the training set to select the

optimal value for the regularization hyperparameter C (searching between 10 values

logarithmically spaced on the interval [-3, +3]). We then computed the generalization

performance on the test set of the model trained on the full training set with the best

hyperparameter value. Reported results were then averaged over 20 experiments. Note that

data were systematically normalized with a scaler fitted on the training set. We used a robust

scaling strategy for these experiments (removing the median, then scaling to the quantile

range; 25th quantile and 75th quantile) which occurs to be more relevant with a small training

set.

To investigate how speaker identity information is encoded in the latent space

representations of speakers' voices, we computed speaker identity *voice latent space*

representations by averaging 20 stimulus-based representations, in order to obtain a limited

amount of data per identity that could be distributed across training and test datasets.

We first tested whether the mean of the distribution of accuracy scores obtained for 20

seeds was significantly above chance level using one-sample t-tests. We then evaluated the

difference in classification accuracy between the VLS and LIN via one-way ANOVAs

(dependent variable: test balance accuracy; between factor: Feature), for each category

(speaker gender, age, identity). We performed post-hoc planned paired t-tests between the

models to test the significance of the VLS-LIN difference.

Brain encoding

We performed encoding experiments on identity-based representations for each of the three

participants (Fig. 2). For each participant we explored the ability to learn a regularized linear

regression that predicts a speaker-based neural activity, e.g. the j^{th} speaker's contrast map

$\tilde{\beta}_i[j] \in R^V$, from this speaker's voice latent space representation, that we note $z_i{}^{model}[j] \in$

R^{128} (Fig. 2a). We carried out these regression analyses for each ROI (A1, pTVA, mTVA,

aTVA) in each hemisphere and participant, independently.

The regression model parameters $\widehat{W}_{encod} \in R^{128 \times V}$ were learned according to:

$$\widehat{W}_{encod} = argmin_{W_{encod} \in R^{128 \times V}} \sum_{j=1..N_i} (z_i{}^{model}[j] \times W_{encod} - \tilde{\beta}_i[j])^2 + \lambda \|W_{encod}\|^2$$

where λ is a hyperparameter tuning the optimal tradeoff between the data fit and the

penalization terms above. We used the ridge regression with built-in cross-validation as

implemented as $RidgeCV$ in the scikit-learn library (Pedregosa et al., 2018).

The statistical significance of each result was assessed with the following procedure. We

repeated the following experiment 20 times with different random seeds. Each time, we

performed 5 train-test splits with 80% of the data in the training and 20% in the test set. For

each split we used RidgeCV (relying on leave-one-out) on the training set to select the

optimal value for the hyperparameter λ (searching between 10 values logarithmically spaced

on the interval [10^{-1}; 10^{8}]). Following standard practice in machine learning, we then

computed the generalization performance on the test set of the model trained on the full

training set with the best hyperparameter value. Reported results are then averaged over 20

experiments. Note that here again with small training sets data were systematically

normalized in each experiment using robust scaling.

Evaluation relied on the 'brain score' procedure (Schrimpf et al., 2018) which evaluates the

performance of the ridge regression with a Pearson's correlation score. Correlations

between measured neural activities $\tilde{\beta}_i$ and predicted ones $z_i{}^{\widehat{model}} * W_{encod}$ were computed

for each voxel and averaged over repeated experiments (folds and seeds) yielding one

correlation value for every voxel and for every setting. The significance of the results was

assessed with one-sample t-tests for the Fisher z-transformed correlation scores (3 x

participants x 2 hemispheres x V voxels). For each region of interest, the scores are reported

across participants and hemispheres (Fig. 2b). The exact same procedure was followed for

the LIN modeling.

In order to determine which of the two feature spaces (VLS, LIN) and which of the two ROI

(A1, TVAs) yielded the best prediction of neural activity, we compared the means of

distributions of correlations coefficients using a mixed ANOVA performed on the Fisher z-

transformed coefficients (dependent variable: correlation; between factor: ROI; repeated

measurements: Feature; between-participant identifier: voxel).

For each ROI, we then used t-tests to perform post-hoc contrasts for the VLS-LIN difference

in brain encoding performance (comparison tests in Fig. 2b; Supplementary Table 4). We

finally conducted two-sample t-tests between the brain encoding model's scores trained to

predict A1 and those trained to predict temporal voice areas to test the significance of the

A1-TVAs difference (Supplementary Table 5).

The statistical tests were all performed using the *pingouin* python package (Vallat., 2018).

Representational similarity analysis

The RSA analyses were carried out using the package *rsatoolbox* (Schütt et al., 2021;

https://github.com/rsagroup/rsatoolbox). For each participant, region of interest and

hemisphere, we computed the cerebral Representational Dissimilarity Matrix (RDM) using

the Pearson's correlation between the speaker identity-specific response patterns of the

GLM estimates $\tilde{\beta}_i$ (Walther et al., 2016) (Fig. 3a). The model RDMs were built using cosine

distance (Xing et al., 2015; Bhattacharya et al., 2017; Wang et al., 2018), capturing speaker

pairwise feature differences predicted by the computational models LIN and the VLS (Fig.

3a). For greater comparability with the rest of the analyses described here, the GLM

estimates and the computational models' features were first normalized using robust scaling.

We computed the Spearman correlations coefficients between the brain RDMs for each ROI,

and the two model's RDMs (Fig. 3b). We assessed the significance of these brain-model

correlation coefficients within a permutation-based 'maximum statistics' framework for

multiple comparison correction (one-tailed inference; N permutations = 10,000 for each test;

permutation of rows and columns of distance matrices, see Giordano et al., 2023 and Maris

& Oostenveld, 2007; see Fig. 3b). We evaluated the VLS-LIN difference using a two-way

repeated-measures ANOVA on the Fisher z-transformed Spearman correlation coefficients

(dependent variable: correlation; within factors: ROI and Feature; participant identifier:

 participant hemisphere pair). The same permutation framework was also used to assess the

753 significance of the difference between the RSA correlation for the VLS and LIN models.

Brain decoding

Brain decoding was investigated at the stimulus level. The stimuli's voice latent space

representations $z_s{}^{model} \in R^{N \times 128}$ and voice samples' contrast maps $\tilde{\beta}_s \in R^{N \times V}$ were

divided into train and test splits, normalized across voice samples using robust scaling, then

fit to the training set. For every participant and each ROI, we trained a L_2-regularized linear

model $W \in R^{V \times 128}$ model to predict the voice samples' latent vectors from the voice

samples' contrast maps (Fig. 4a). The hyperparameter selection and optimization was done

similarly as in the Brain encoding scheme. Training was performed on non repeated stimuli

(see Stimuli section). We then used the trained models to predict for each participant the 6

repeated stimuli that were the most presented. Waveforms were estimated starting from the

reconstructed spectrograms using the Griffin-Lim phase reconstruction algorithm (Griffin &

Lim, 1983).

We then used classifier analyses to assess the presence of voice information (gender, age,

speaker identity) in the reconstructed latent representations (i.e., the latent representation

predicted from the brain activity of a participant listening to a specific stimulus) (Fig. 5a, b, c).

To this purpose, we first trained linear classifiers to categorize the training voice stimuli

(participant 1, N = 6144; participant 2, N = 6142; participant 3, N = 5117; total, N = 17403) by

gender (2 classes), age (2 classes) or identity (17 classes) based on VLS coordinates.

Secondly, we used the previously trained classifiers to predict the identity information based

on the VLS derived from the brain responses of the 18 Test voice stimuli (3 participants x 6

stimuli). We first tested using one-sample t-tests that the mean of the distribution of accuracy

scores obtained across random classifier initializations of classifiers (2 hemispheres x 20

seeds = 40) was significantly above chance level, for each category, ROI and model. We

then evaluated the difference in performance at preserving identity-related information

depending on the model or ROI via two-way ANOVAs (dependent variable: accuracy;

between factors: Feature and ROI). We performed post-hoc planned paired t-tests between

each model pair to test the significance of the VLS-LIN difference. Two-sample t-tests were

finally used to test the significance of the A1-TVAs difference.

Listening tests

We recruited 13 participants through the online platform Prolific (www.prolific.co) for a series

of online behavioral experiments. All participants reported having normal hearing. The

purpose of these experiments was to evaluate how well voice identity information and

naturalness are preserved in fMRI-based reconstructed voice excerpts. In the main session,

participants carried out 4 tasks, in the following order: 'speaker discrimination' (~120 min),

'perceived naturalness' (~30 min), 'gender categorization' (~30 min), 'age categorization'

(~30 min). The experiment lasted 3 hours and 35 minutes, and each participant was paid

£48.

Prior to the main experiment session, participants carried out a short loudness-change

detection task to ensure that they wore headphones, and that they were attentive and

properly set up for the main experiment (Woods et al., 2017). On each of 12 trials,

participants heard 3 tones and were asked to identify which tone was the least loud by

clicking on one of 3 response buttons: 'First', 'Second', or 'Third'. Participants were admitted

to the main experiment only if they achieved perfect performance in this task. We

additionally refined the participant pool by excluding those who performed badly on the

original stimuli.

The next three tasks were each carried out on the same set of 342 experimental stimuli,

each presented on a different trial: 18 original stimuli, 36 stimuli reconstructed directly from

the LIN and the VLS models, and 18 stimuli x 2 models x 4 regions of interest x 2

hemispheres= 288 brain-reconstructed stimuli.

In the 'perceived naturalness' task, participants were asked to rate how natural the voice

sounded on a scale ranging from 'Not at all natural' to 'Highly natural' (i.e., similar to a real

recording), and were instructed to use the full range of the scale.

During the 'gender categorization' task, participants categorized the gender by clicking on a

'Female' or 'Male' button.

Finally, in the 'age categorization' task, participants categorized the age of the speaker by

clicking on a 'Younger' or 'Older' button.

In the 'speaker discrimination' task, participants carried out 684 trials (342 experimental

stimuli x 2) with short breaks in between. On each trial, they were presented with 2 short

sound stimuli, one after the other, and participants had to indicate whether they were from

the same speaker or not.

To evaluate the performance of the participants, we firstly conducted one-sample t-tests to

examine whether the mean accuracy score calculated from their responses was significantly

higher than the chance level for each model and ROI. Next, we used two-way repeated-

measures ANOVAs to assess the variation in participants' performances in identifying

identity-related information (dependent variable: accuracy; between-participant factors:

Feature and ROI). To determine the statistical significance of the VLS-LIN difference, we

carried out post-hoc planned paired t-tests between each model pair. Finally, we employed

two-sample t-tests to evaluate the statistical significance of the A1-TVAs difference.

Data and code availability

All data and codes will be made publicly available upon the article publication.

References

825   Abraham, A., Pedregosa, F., Eickenberg, M., Gervais, P., Mueller, A., Kossaifi, J.,

826   Gramfort, A., Thirion, B., & Varoquaux, G. (2014). Machine learning for

827   neuroimaging with scikit-learn. *Frontiers in Neuroinformatics*, *8*.

828   https://www.frontiersin.org/articles/10.3389/fninf.2014.00014

829   Akbari, H., Khalighinejad, B., Herrero, J. L., Mehta, A. D., & Mesgarani, N. (2019).

830   Towards reconstructing intelligible speech from the human auditory cortex.

831   *Scientific Reports*, *9*(1), 874. https://doi.org/10.1038/s41598-018-37359-z

832   Ardila, R., Branson, M., Davis, K., Henretty, M., Kohler, M., Meyer, J., Morais, R.,

833   Saunders, L., Tyers, F. M., & Weber, G. (2020). *Common Voice: A Massively-*

834   *Multilingual Speech Corpus* (arXiv:1912.06670). arXiv.

835   https://doi.org/10.48550/arXiv.1912.06670

836   Ashburner, J. (2012). SPM: A history. *NeuroImage*, *62*(2), 791–800.

837   https://doi.org/10.1016/j.neuroimage.2011.10.025

838   Barbero, F. M., Calce, R. P., Talwar, S., Rossion, B., & Collignon, O. (2021). Fast

839   Periodic Auditory Stimulation Reveals a Robust Categorical Response to Voices in

840   the Human Brain. *ENeuro*, *8*(3), ENEURO.0471-20.2021.

841   https://doi.org/10.1523/ENEURO.0471-20.2021

842   Belin, P., Bestelmeyer, P. E. G., Latinus, M., & Watson, R. (2011). Understanding Voice

843   Perception: Understanding voice perception. *British Journal of Psychology*, *102*(4),

844   711–725. https://doi.org/10.1111/j.2044-8295.2011.02041.x

845   Belin, P., Bodin, C., & Aglieri, V. (2018). A "voice patch" system in the primate brain for

846   processing vocal information? *Hearing Research*, *366*, 65–74.

847   https://doi.org/10.1016/j.heares.2018.04.010

Belin, P., Fecteau, S., & Bédard, C. (2004). Thinking the voice: Neural correlates of voice perception. *Trends in Cognitive Sciences*, *8*(3), 129–135. https://doi.org/10.1016/j.tics.2004.01.008

Belin, P., & Zatorre, R. J. (2003). Adaptation to speaker's voice in right anterior temporal lobe: *NeuroReport*, *14*(16), 2105–2109. https://doi.org/10.1097/00001756-200311140-00019

Belin, P., Zatorre, R. J., Lafaille, P., Ahad, P., & Pike, B. (2000). Voice-selective areas in human auditory cortex. *Nature*, *403*(6767), 309–312. https://doi.org/10.1038/35002078

Bhattacharya, G., Alam, J., & Kenny, P. (2017). Deep Speaker Embeddings for Short-Duration Speaker Verification. *Interspeech 2017*, 1517–1521. https://doi.org/10.21437/Interspeech.2017-1575

Blank, H., Wieland, N., & von Kriegstein, K. (2014). Person recognition and the brain: Merging evidence from patients and healthy individuals. *Neuroscience & Biobehavioral Reviews*, *47*, 717–734. https://doi.org/10.1016/j.neubiorev.2014.10.022

Bodin, C., Trapeau, R., Nazarian, B., Sein, J., Degiovanni, X., Baurberg, J., Rapha, E., Renaud, L., Giordano, B. L., & Belin, P. (2021). Functionally homologous representation of vocalizations in the auditory cortex of humans and macaques. *Current Biology*, S0960982221011477. https://doi.org/10.1016/j.cub.2021.08.043

Bouthillier, X., Delaunay, P., Bronzi, M., Trofimov, A., Nichyporuk, B., Szeto, J., Sepah, N., Raff, E., Madan, K., Voleti, V., Kahou, S. E., Michalski, V., Serdyuk, D., Arbel, T., Pal, C., Varoquaux, G., & Vincent, P. (2021). *Accounting for Variance in Machine Learning Benchmarks* (arXiv:2103.03098). arXiv. http://arxiv.org/abs/2103.03098

Capilla, A., Belin, P., & Gross, J. (2013). The Early Spatio-Temporal Correlates and

Task Independence of Cerebral Voice Processing Studied with MEG. *Cerebral*

Cortex, *23*(6), 1388–1395. https://doi.org/10.1093/cercor/bhs119

Caucheteux, C., Gramfort, A., & King, J.-R. (2022). Deep language algorithms predict

semantic comprehension from brain activity. *Scientific Reports*, *12*(1), Article 1.

https://doi.org/10.1038/s41598-022-20460-9

Caucheteux, C., Gramfort, A., & King, J.-R. (2023). Evidence of a predictive coding

hierarchy in the human brain listening to speech. *Nature Human Behaviour*, 1–12.

https://doi.org/10.1038/s41562-022-01516-2

Caucheteux, C., & King, J.-R. (2022). Brains and algorithms partially converge in natural

language processing. *Communications Biology*, *5*(1), Article 1.

https://doi.org/10.1038/s42003-022-03036-1

Chang, N., Pyles, J. A., Marcus, A., Gupta, A., Tarr, M. J., & Aminoff, E. M. (2019).

BOLD5000, a public fMRI dataset while viewing 5000 visual images. *Scientific*

Data, *6*(1), Article 1. https://doi.org/10.1038/s41597-019-0052-3

Charest, I., Pernet, C., Latinus, M., Crabbe, F., & Belin, P. (2013). Cerebral Processing

of Voice Gender Studied Using a Continuous Carryover fMRI Design. *Cerebral*

Cortex, *23*(4), 958–966. https://doi.org/10.1093/cercor/bhs090

Charest, I., Pernet, C. R., Rousselet, G. A., Quiñones, I., Latinus, M., Fillion-Bilodeau,

S., Chartrand, J.-P., & Belin, P. (2009). Electrophysiological evidence for an early

processing of human voices. *BMC Neuroscience*, *10*(1), 127.

https://doi.org/10.1186/1471-2202-10-127

Chen, Z., Qing, J., Xiang, T., Yue, W., & Zhou, J. (2022). *Seeing Beyond the Brain:*

Conditional Diffusion Model with Sparse Masked Modeling for Vision Decoding.

https://doi.org/10.48550/arXiv.2211.06956

Cowen, A. S., Chun, M. M., & Kuhl, B. A. (2014). Neural portraits of perception:

Reconstructing face images from evoked brain activity. *NeuroImage*, *94*, 12–22.

https://doi.org/10.1016/j.neuroimage.2014.03.018

Défossez, Alexandre, Charlotte Caucheteux, Jérémy Rapin, Ori Kabeli, et Jean-Rémi

King. 2023. « Decoding Speech Perception from Non-Invasive Brain Recordings ».

Nature Machine Intelligence 5(10):1097-1107. doi: 10.1038/s42256-023-00714-5

Diedrichsen, J., & Kriegeskorte, N. (2017). Representational models: A common

framework for understanding encoding, pattern-component, and representational-

similarity analysis. *PLOS Computational Biology*, *13*(4), e1005508.

https://doi.org/10.1371/journal.pcbi.1005508

Dosenbach, N. U. F., Koller, J. M., Earl, E. A., Miranda-Dominguez, O., Klein, R. L.,

Van, A. N., Snyder, A. Z., Nagel, B. J., Nigg, J. T., Nguyen, A. L., Wesevich, V.,

Greene, D. J., & Fair, D. A. (2017). Real-time motion analytics during brain MRI

improve data quality and reduce costs. *NeuroImage*, *161*, 80–93.

https://doi.org/10.1016/j.neuroimage.2017.08.025

Friston, K. J., Glaser, D. E., Henson, R. N. A., Kiebel, S., Phillips, C., & Ashburner, J.

(2002). Classical and Bayesian inference in neuroimaging: Applications.

NeuroImage, *16*(2), 484–512. https://doi.org/10.1006/nimg.2002.1091

Friston, K. J., Holmes, A. P., Worsley, K. J., Poline, J.-P., Frith, C. D., & Frackowiak, R.

S. J. (1994). Statistical parametric maps in functional imaging: A general linear

approach. *Human Brain Mapping*, *2*(4), 189–210.

https://doi.org/10.1002/hbm.460020402

Gaziv, G., Beliy, R., Granot, N., Hoogi, A., Strappini, F., Golan, T., & Irani, M. (2022).

Self-supervised Natural Image Reconstruction and Large-scale Semantic

Classification from Brain Activity. *NeuroImage*, *254*, 119121.

https://doi.org/10.1016/j.neuroimage.2022.119121

Giordano, B. L., Esposito, M., Valente, G., & Formisano, E. (2023). Intermediate

acoustic-to-semantic representations link behavioral and neural responses to

natural sounds. *Nature Neuroscience*, 1–9. https://doi.org/10.1038/s41593-023-

01285-9

Glover, G. H. (1999). Deconvolution of Impulse Response in Event-Related BOLD

fMRI1. *NeuroImage*, *9*(4), 416–429. https://doi.org/10.1006/nimg.1998.0419

Glover, G. H., Li, T. Q., & Ress, D. (2000). Image-based method for retrospective

correction of physiological motion effects in fMRI: RETROICOR. *Magnetic*

Resonance in Medicine, *44*(1), 162–167. https://doi.org/10.1002/1522-

2594(200007)44:1<162::aid-mrm23>3.0.co;2-e

Griffin, D. & Jae Lim. (1983). Signal estimation from modified short-time Fourier

transform. *ICASSP '83. IEEE International Conference on Acoustics, Speech, and*

Signal Processing, *8*, 804–807. https://doi.org/10.1109/ICASSP.1983.1172092

Güçlü, U., Thielen, J., Hanke, M., Gerven, M. A. J. van, & Gerven, M. A. J. van. (2016).

Brains on Beats. *In Proceedings of the International Conference on Neural*

Information Processing Systems, 2101–2109. https://doi.org/null

Gutierrez, M. (2021). Algorithmic Gender Bias and Audiovisual Data: A Research

Agenda. *International Journal of Communication*, *15*, 439–461.

Han, K., Wen, H., Shi, J., Lu, K.-H., Zhang, Y., Fu, D., & Liu, Z. (2019). Variational

autoencoder: An unsupervised model for encoding and decoding fMRI activity in

visual cortex. *NeuroImage*, *198*, 125–136.

https://doi.org/10.1016/j.neuroimage.2019.05.039

Harris, C. R., Millman, K. J., van der Walt, S. J., Gommers, R., Virtanen, P.,

Cournapeau, D., Wieser, E., Taylor, J., Berg, S., Smith, N. J., Kern, R., Picus, M.,

Hoyer, S., van Kerkwijk, M. H., Brett, M., Haldane, A., del Río, J. F., Wiebe, M.,

Peterson, P., … Oliphant, T. E. (2020). Array programming with NumPy. *Nature*,

585(7825), 357–362. https://doi.org/10.1038/s41586-020-2649-2

Higgins, I., Chang, L., Langston, V., Hassabis, D., Summerfield, C., Tsao, D., &

Botvinick, M. (2021). Unsupervised deep learning identifies semantic

disentanglement in single inferotemporal face patch neurons. *Nature*

Communications, *12*(1), 6456. https://doi.org/10.1038/s41467-021-26751-5

Horikawa, T., & Kamitani, Y. (2017). Generic decoding of seen and imagined objects

using hierarchical visual features. *Nature Communications*, *8*(1), 15037.

https://doi.org/10.1038/ncomms15037

Howard, A. G., Zhu, M., Chen, B., Kalenichenko, D., Wang, W., Weyand, T., Andreetto,

M., & Adam, H. (2017). MobileNets: Efficient Convolutional Neural Networks for

Mobile Vision Applications. *ArXiv:1704.04861 [Cs]*. http://arxiv.org/abs/1704.04861

Kasper, L., Bollmann, S., Diaconescu, A. O., Hutton, C., Heinzle, J., Iglesias, S.,

Hauser, T. U., Sebold, M., Manjaly, Z.-M., Pruessmann, K. P., & Stephan, K. E.

(2017). The PhysIO Toolbox for Modeling Physiological Noise in fMRI Data. *Journal*

of Neuroscience Methods, *276*, 56–72.

https://doi.org/10.1016/j.jneumeth.2016.10.019

Kell, A. J. E., Yamins, D. L. K., Shook, E. N., Norman-Haignere, S. V., & McDermott, J.

H. (2018). A Task-Optimized Neural Network Replicates Human Auditory Behavior,

Predicts Brain Responses, and Reveals a Cortical Processing Hierarchy. *Neuron*,

98(3), 630-644.e16. https://doi.org/10.1016/j.neuron.2018.03.044

Khaligh-Razavi, S.-M., & Kriegeskorte, N. (2014). Deep Supervised, but Not

Unsupervised, Models May Explain IT Cortical Representation. *PLoS*

Computational Biology, *10*(11), e1003915.

https://doi.org/10.1371/journal.pcbi.1003915

Kingma, D. P., & Welling, M. (2014). Auto-Encoding Variational Bayes. *ArXiv:1312.6114*

[Cs, Stat]. http://arxiv.org/abs/1312.6114

Kingma, D. P., & Welling, M. (2019). An Introduction to Variational Autoencoders.

Foundations and Trends® in Machine Learning, *12*(4), 307–392.

https://doi.org/10.1561/2200000056

Kriegeskorte, N. (2008). Representational similarity analysis – connecting the branches

of systems neuroscience. *Frontiers in Systems Neuroscience*.

https://doi.org/10.3389/neuro.06.004.2008

Kriegstein, K. V., & Giraud, A.-L. (2004). Distinct functional substrates along the right

superior temporal sulcus for the processing of voices. *NeuroImage*, *22*(2), 948–955.

https://doi.org/10.1016/j.neuroimage.2004.02.020

Lavan, Nadine. 2023. « The Time Course of Person Perception From Voices: A

Behavioral Study ». *Psychological Science* 34(7):771-83. doi:

10.1177/09567976231161565.

Le, L., Ambrogioni, L., Seeliger, K., Güçlütürk, Y., van Gerven, M., & Güçlü, U. (2022).

Brain2Pix: Fully convolutional naturalistic video frame reconstruction from brain

activity. *Frontiers in Neuroscience*, *16*.

https://www.frontiersin.org/articles/10.3389/fnins.2022.940972

LeCun, Y., Bengio, Y., & Hinton, G. (2015). Deep learning. *Nature*, *521*(7553), Article

7553. https://doi.org/10.1038/nature14539

Liu, D., Li, Y., Lin, J., Li, H., & Wu, F. (2020). Deep Learning-Based Video Coding: A

Review and a Case Study. *ACM Computing Surveys*, *53*(1), 11:1-11:35.

https://doi.org/10.1145/3368405

Maris, E., & Oostenveld, R. (2007). Nonparametric statistical testing of EEG- and MEG-

data. *Journal of Neuroscience Methods*, *164*(1), 177–190.

https://doi.org/10.1016/j.jneumeth.2007.03.024

Martin, F. N., & Champlin, C. A. (2000). Reconsidering the limits of normal hearing.

Journal of the American Academy of Audiology, *11*(2), 64–66.

Millet, J., Caucheteux, C., Orhan, P., Boubenec, Y., Gramfort, A., Dunbar, E., Pallier, C.,

& King, J.-R. (2022). *Toward a realistic model of speech processing in the brain*

with self-supervised learning (arXiv:2206.01685). arXiv.

https://doi.org/10.48550/arXiv.2206.01685

Morillon, B., Arnal, L. H., & Belin, P. (2022). The path of voices in our brain. *PLOS*

Biology, *20*(7), e3001742. https://doi.org/10.1371/journal.pbio.3001742

Mozafari, M., Reddy, L., & VanRullen, R. (2020). Reconstructing Natural Scenes from

fMRI Patterns using BigBiGAN. *2020 International Joint Conference on Neural*

Networks (IJCNN), 1–8. https://doi.org/10.1109/IJCNN48605.2020.9206960

Nagrani, Arsha, Joon Son Chung, et Andrew Zisserman. 2017. « VoxCeleb: a large-

scale speaker identification dataset ». P. 2616-20 in *Interspeech 2017*.

Naselaris, T., Kay, K. N., Nishimoto, S., & Gallant, J. L. (2011). Encoding and decoding

in fMRI. *NeuroImage*, *56*(2), 400–410.

https://doi.org/10.1016/j.neuroimage.2010.07.073

Pasley, B. N., David, S. V., Mesgarani, N., Flinker, A., Shamma, S. A., Crone, N. E.,

Knight, R. T., & Chang, E. F. (2012). Reconstructing Speech from Human Auditory

Cortex. *PLOS Biology*, *10*(1), e1001251.

https://doi.org/10.1371/journal.pbio.1001251

Paszke, A., Gross, S., Massa, F., Lerer, A., Bradbury, J., Chanan, G., Killeen, T., Lin,

1021   Z., Gimelshein, N., Antiga, L., Desmaison, A., Köpf, A., Yang, E., DeVito, Z.,

1022   Raison, M., Tejani, A., Chilamkurthy, S., Steiner, B., Fang, L., … Chintala, S.

1023   (2019). *PyTorch: An Imperative Style, High-Performance Deep Learning Library*

1024   (arXiv:1912.01703). arXiv. https://doi.org/10.48550/arXiv.1912.01703

1025   Pedregosa, F., Varoquaux, G., Gramfort, A., Michel, V., Thirion, B., Grisel, O., Blondel,

1026   M., Müller, A., Nothman, J., Louppe, G., Prettenhofer, P., Weiss, R., Dubourg, V.,

1027   Vanderplas, J., Passos, A., Cournapeau, D., Brucher, M., Perrot, M., & Duchesnay,

1028   É. (2018). *Scikit-learn: Machine Learning in Python* (arXiv:1201.0490). arXiv.

1029   https://doi.org/10.48550/arXiv.1201.0490

1030   Penhune, V. B., Zatorre, R. J., MacDonald, J. D., & Evans, A. C. (1996).

1031   Interhemispheric anatomical differences in human primary auditory cortex:

1032   Probabilistic mapping and volume measurement from magnetic resonance scans.

1033   *Cerebral Cortex (New York, N.Y.: 1991)*, *6*(5), 661–672.

1034   https://doi.org/10.1093/cercor/6.5.661

1035   Pernet, C. R., McAleer, P., Latinus, M., Gorgolewski, K. J., Charest, I., Bestelmeyer, P.

1036   E. G., Watson, R. H., Fleming, D., Crabbe, F., Valdes-Sosa, M., & Belin, P. (2015).

1037   The human voice areas: Spatial organization and inter-individual variability in

1038   temporal and extra-temporal cortices. *NeuroImage*, *119*, 164–174.

1039   https://doi.org/10.1016/j.neuroimage.2015.06.050

1040   Petkov, C. I., Kayser, C., Steudel, T., Whittingstall, K., Augath, M., & Logothetis, N. K.

1041   (2008). A voice region in the monkey brain. *Nature Neuroscience*, *11*(3), Article 3.

1042   https://doi.org/10.1038/nn2043

Rupp, K., Hect, J. L., Remick, M., Ghuman, A., Chandrasekaran, B., Holt, L. L., & Abel, T. J. (2022). Neural responses in human superior temporal cortex support coding of voice representations. *PLOS Biology*, *20*(7), e3001675. https://doi.org/10.1371/journal.pbio.3001675

Santoro, R., Moerel, M., De Martino, F., Valente, G., Ugurbil, K., Yacoub, E., & Formisano, E. (2017). Reconstructing the spectrotemporal modulations of real-life sounds from fMRI response patterns. *Proceedings of the National Academy of Sciences*, *114*(18), 4799–4804. https://doi.org/10.1073/pnas.1617622114

Schrimpf, M., Blank, I. A., Tuckute, G., Kauf, C., Hosseini, E. A., Kanwisher, N., Tenenbaum, J. B., & Fedorenko, E. (2021). The neural architecture of language: Integrative modeling converges on predictive processing. *Proceedings of the National Academy of Sciences*, *118*(45), e2105646118. https://doi.org/10.1073/pnas.2105646118

Schrimpf, M., Kubilius, J., Hong, H., Majaj, N. J., Rajalingham, R., Issa, E. B., Kar, K., Bashivan, P., Prescott-Roy, J., Geiger, F., Schmidt, K., Yamins, D. L. K., & DiCarlo, J. J. (2018). *Brain-Score: Which Artificial Neural Network for Object Recognition is most Brain-Like?* [Preprint]. Neuroscience. https://doi.org/10.1101/407007

Schütt, H. H., Kipnis, A. D., Diedrichsen, J., & Kriegeskorte, N. (2021). *Statistical inference on representational geometries* (arXiv:2112.09200). arXiv. http://arxiv.org/abs/2112.09200

Schweinberger, S. R., A. Herholz, et W. Sommer. 1997. « Recognizing Famous Voices: Influence of Stimulus Duration and Different Types of Retrieval Cues ». *Journal of Speech, Language, and Hearing Research: JSLHR* 40(2):453-63. doi: 10.1044/jslhr.4002.453.

Smith, S. M., Jenkinson, M., Woolrich, M. W., Beckmann, C. F., Behrens, T. E. J.,

Johansen-Berg, H., Bannister, P. R., De Luca, M., Drobnjak, I., Flitney, D. E.,

Niazy, R. K., Saunders, J., Vickers, J., Zhang, Y., De Stefano, N., Brady, J. M., &

Matthews, P. M. (2004). Advances in functional and structural MR image analysis

and implementation as FSL. *NeuroImage*, *23*, S208–S219.

https://doi.org/10.1016/j.neuroimage.2004.07.051

Snoek, L., van der Miesen, M. M., Beemsterboer, T., van der Leij, A., Eigenhuis, A., &

Steven Scholte, H. (2021). The Amsterdam Open MRI Collection, a set of

multimodal MRI datasets for individual difference analyses. *Scientific Data*, *8*(1),

Article 1. https://doi.org/10.1038/s41597-021-00870-6

Trapeau, R., Thoret, E., & Belin, P. (2022). The Temporal Voice Areas are not "just"

Speech Areas. *Frontiers in Neuroscience*, *16*, 1075288.

https://doi.org/10.3389/fnins.2022.1075288

Vallat, R. (2018). Pingouin: Statistics in Python. *Journal of Open Source Software*,

3(31), 1026. https://doi.org/10.21105/joss.01026

VanRullen, R., & Reddy, L. (2019). Reconstructing faces from fMRI patterns using deep

generative neural networks. *Communications Biology*, *2*(1), 193.

https://doi.org/10.1038/s42003-019-0438-y

von Kriegstein, K., Eger, E., Kleinschmidt, A., & Giraud, A. L. (2003). Modulation of

neural responses to speech by directing attention to voices or verbal content.

Cognitive Brain Research, *17*(1), 48–55. https://doi.org/10.1016/S0926-

6410(03)00079-X

Walther, A., Nili, H., Ejaz, N., Alink, A., Kriegeskorte, N., & Diedrichsen, J. (2016).

Reliability of dissimilarity measures for multi-voxel pattern analysis. *NeuroImage*,

137, 188–200. https://doi.org/10.1016/j.neuroimage.2015.12.012

Wang, X., Xu, Y., Wang, Y., Zeng, Y., Zhang, J., Ling, Z., & Bi, Y. (2018).
Representational similarity analysis reveals task-dependent semantic influence of
the visual word form area. *Scientific Reports*, *8*(1), 3047.
https://doi.org/10.1038/s41598-018-21062-0

Wetzel, S. J. (2017). Unsupervised learning of phase transitions: From principal
component analysis to variational autoencoders. *Physical Review E*, *96*(2), 022140.
https://doi.org/10.1103/PhysRevE.96.022140

Woods, K. J. P., Siegel, M. H., Traer, J., & McDermott, J. H. (2017). Headphone
screening to facilitate web-based auditory experiments. *Attention, Perception, &
Psychophysics*, *79*(7), 2064–2072. https://doi.org/10.3758/s13414-017-1361-2

Wu, M. C.-K., David, S. V., & Gallant, J. L. (2006). COMPLETE FUNCTIONAL
CHARACTERIZATION OF SENSORY NEURONS BY SYSTEM IDENTIFICATION.
Annual Review of Neuroscience, *29*(1), 477–505.
https://doi.org/10.1146/annurev.neuro.29.051605.113024

Xing, C., Wang, D., Liu, C., & Lin, Y. (2015). Normalized Word Embedding and
Orthogonal Transform for Bilingual Word Translation. *Proceedings of the 2015
Conference of the North American Chapter of the Association for Computational
Linguistics: Human Language Technologies*, 1006–1011.
https://doi.org/10.3115/v1/N15-1104

Yamins, D. L. K., & DiCarlo, J. J. (2016). Using goal-driven deep learning models to
understand sensory cortex. *Nature Neuroscience*, *19*(3), 356–365.
https://doi.org/10.1038/nn.4244

Zäske, R., Perlich, M.-C., & Schweinberger, S. R. (2016). To hear or not to hear: Voice
processing under visual load. *Attention, Perception, & Psychophysics*, *78*(5), 1488–
1495. https://doi.org/10.3758/s13414-016-1119-2

1117   Zhang, Y., Ding, Y., Huang, J., Zhou, W., Ling, Z., Hong, B., & Wang, X. (2021).

1118   Hierarchical cortical networks of "voice patches" for processing voices in human

1119   brain. *Proceedings of the National Academy of Sciences*, *118*(52), e2113887118.

1120   https://doi.org/10.1073/pnas.2113887118

Acknowledgements

We thank Bruno Nazarian for the design of an MRI-compatible button. We thank Jean-Luc

Anton and Kepkee Loh for useful discussions. This work was funded by the European

Research Council (ERC) under the European Union's Horizon 2020 research and innovation

program (grant agreement no. 788240). This work was performed in the Center IRM-

INT@CERIMED (UMR 7289, AMU-CNRS), platform member of France Life Imaging network

(grant ANR-11-INBS-0 0 06). This work, carried out within the Institute of Convergence ILCB

(ANR-16-CONV-0002), has benefited from support from the French government (*France

2030*), managed by the French National Agency for Research (ANR) and the Excellence

Initiative of Aix-Marseille University (A*MIDEX).