Reconstructing Voice Identity from Noninvasive Auditory Cortex

Recordings

Charly Lamothe[1,2] ✉, Etienne Thoret[1,2,3,4], Régis Trapeau[1], Bruno L.

Giordano[1], Julien Sein[1,5], Sylvain Takerkart[1], Stéphane Ayache[2], Thierry

Artières[2,6,7] ✉, Pascal Belin[1,7] ✉

[1]La Timone Neuroscience Institute UMR 7289, CNRS, Aix-Marseille University, Marseille,

France. [2]Laboratoire d'Informatique et Systèmes UMR 7020, CNRS, Aix-Marseille

University, Marseille, France. [3]Perception, Representation, Image, Sound, Music UMR 7061,

CNRS, Marseille, France. [4]Institute of Language Communication & the Brain, Marseille.

[5]Centre IRM-INT@CERIMED, Marseille, France. [6]École Centrale de Marseille, Marseille,

France. [7]These authors jointly supervised this work: Thierry Artières, Pascal Belin. ✉e-mail:

charlylmth@gmail.com, thierry.artieres@lis-lab.fr, pascal.belin@univ-amu.fr

Abstract

The cerebral processing of voice information is known to engage, in human as well as non-

human primates, "temporal voice areas" (TVAs) that respond preferentially to conspecific

vocalizations. However, how voice information is represented by neuronal populations in

these areas, particularly speaker identity information, remains poorly understood. Here, we

used a deep neural network (DNN) to generate a high-level, small-dimension

representational space for voice identity—the 'voice latent space' (VLS)—and examined its

linear relation with cerebral activity via encoding, representational similarity, and decoding

analyses. We find that the VLS maps onto fMRI measures of cerebral activity in response to

tens of thousands of voice stimuli from hundreds of different speaker identities and better

accounts for the representational geometry for speaker identity in the TVAs than in A1.

Moreover, the VLS allowed TVA-based reconstructions of voice stimuli that preserved

essential aspects of speaker identity as assessed by both machine classifiers and human

listeners. These results indicate that the DNN-derived VLS provides high-level

representations of voice identity information in the TVAs.

Introduction

The human voice carries speech, but is also an "auditory face" that carries much valuable

information on the stable physical characteristics of the speaker (hereafter, 'identity-related';

Belin et al., 2004, 2011). The ability of listeners to extract identity-related information in voice

such as gender, age, or unique identity even in brief stimuli plays a crucial role in our social

interactions, yet its neural bases remain poorly understood compared to those of speech

processing. Studies over the past two decades have clearly established via complementary

neuroimaging techniques that the cerebral processing of voice information involves a set of

temporal voice areas (TVAs) in secondary auditory cortical regions of the human (fMRI:

Belin et al., 2000, von Kriegstein et al., 2004, Pernet et al., 2015; EEG, MEG: Charest et al.,

2009, Capilla et al., 2013, Barbero et al., 2021; Electrophysiology: Rupp et al., 2022, Zhang

et al., 2021) as well as macaque brain (Petkov et al., 2008; Bodin et al., 2021). The TVAs

respond more strongly to sounds of voice – with or without speech (Pernet et al., 2015; Rupp

et al., 2022; Trapeau et al., 2022)—and categorize voice apart from other sounds (Bodin et

al., 2021) but the nature of the information encoded at these stages of cortical processing,

especially with respect to speaker identity-related information, remains largely unknown

(Blank et al., 2014; Belin et al., 2018).

In recent years, deep neural networks (DNNs) have emerged as a powerful tool for

representing complex visual data, such as images (LeCun et al., 2015) or videos (Liu et al.,

2020). In the auditory domain, DNNs have been shown to provide valuable

representations—so-called feature or latent spaces—for modeling the cerebral processing of

sound (brain encoding) (speech: Kell et al., 2018; Millet et al., 2022; Tuckute & Feather,

2023; semantic content: Caucheteux et al., 2022; Caucheteux & King, 2022; Caucheteux et

al., 2023; Giordano et al., 2023; music: Güçlü et al., 2016), or reconstructing the stimuli

listened by a participant (brain decoding) (Akbari et al., 2019). They have not yet been used

to explain cerebral representations of identity-related information due in part to the focus on

speech information (von Kriegstein et al., 2003).

Here, we addressed this challenge by training a 'Variational autoencoder' (VAE; Kingma et

Welling, 2014) DNN to reconstruct voice spectrograms from 182,000 250-ms voice samples

from 405 different speaker identities in 8 different languages from the CommonVoice

database (Ardila et al., 2020). Brief (250 ms) samples were used to emphasize speaker

identity-related information in voice, already available after a few hundred milliseconds

(Schweinberger et al., 1997; Lavan, 2023), over linguistic information unfolding over longer

periods (word, >350 ms; Mcallister et al., 1994). While a quarter of a second is admittedly

short compared to standards of, e.g., computational speaker identification that typically uses

2-3 s samples, this short duration is sufficient to allow near-perfect gender classification and

performance levels well above chance for speaker discrimination (Fig. 5d, red dotted line).

This brief duration allowed the presentation of many more stimuli to our participants in the

scanner while preserving acceptable behavioral and classifier performance levels.

State-of-the-art studies have primarily relied on task-optimized neural networks (i.e., DNN

trained using supervised learning to classify a category from the input) to study sensory

cortex processes (Yamins & DiCarlo, 2016; Schrimpf et al., 2018). They can reach high

accuracies in brain encoding (Khaligh-Razavi & Kriegeskorte, 2014; Schrimpf et al., 2018;

Han et al., 2019). However, there is increasing evidence that unsupervised learning, such as

that used for the VAE, also provides plausible computational models for investigating brain

processing (Higgins et al., 2021; Zhuang et al., 2021; Millet et al., 2022; Orhan et al., 2022).

Thus, the VAE-derived VLS, exploited within encoding, representational similarity, and

decoding frameworks, offers a potentially promising tool for investigating the representations

of voice stimuli in the secondary auditory cortex (Naselaris et al., 2011). Autoencoders learn

to compress stimuli with high dimensionality into a lower-dimensional space that nonetheless

allows reconstruction of the original stimuli via an inverse transformation learned by the

second part of the network called the decoder. Fig. 1a shows the architecture of the VAE,

with its encoder that reduces an input spectrogram to a highly compressed, 128-

dimension *voice latent space* (VLS) representation and its decoder that reconstructs the

spectrogram from this VLS representation. We selected this latent space size as it was the

first value that produced satisfactory reconstructions. Points in the VLS correspond to voice

samples with different identities and phonetic content. A line segment in the VLS contains

points corresponding to perceptual interpolations between its two extremities (Fig. 1b;

Supplementary Audio 1). VLS coordinates of samples presented to the participants

averaged by speaker identity suggest that a major organizational dimension of the latent

space is voice gender (Fig. 1b) (colored by age or language in Supplementary Figure 1).

In order to test whether VLS accounts well for cerebral activity in response to voice stimuli,

we scanned three healthy volunteers using fMRI to measure an indirect index of their

cerebral activity across 10+ hours of scanning each in response to ~12,000 of the voice

samples, denoted *BrainVoice* in the following (different from the ones used to train the DNN).

The small number of participants does not allow for generalization at the general population

level as in standard fMRI studies. However, it allows testing for replicability as in comparable

studies involving 10+ hours of scanning per participant (VanRullen & Reddy, 2019). Different

stimulus sets were used across participants to provide a stringent test of replicability based

on subject-level analyses. Stimuli consisted of randomly spliced 250-ms excerpts of speech

samples from the CommonVoice database (Ardila et al., 2020) by 119 speakers in 8

languages. For assessing generalization performances of decoding models and brain-based

reconstruction, six test stimuli were repeated more often (60 times) for each participant to

provide robust estimates of their induced cerebral activity (see Methods). We first modeled

these responses to voice using a general linear model (GLM) (Friston et al., 1994) with

several nuisance regressors as an initial denoising step (Supplementary Figure 3), then

used a second GLM modeling cerebral responses to the different speaker identities

(Supplementary Figure 2a), resulting in one voxel activity map per speaker (Supplementary

Figure 2b). We independently localized in each participant several regions of interest (ROIs)

on which subsequent analyses were focused: the anterior, middle and posterior TVAs in

each hemisphere (individually localized via an independent 'voice localizer scan' and MNI

coordinates provided in Pernet et al., 2015; Supplementary Figure 2c) as well as primary

auditory cortex (A1) (using a probabilistic map in MNI space (Penhune et al., 1996;

Supplementary Figure 2d).

We first asked how the VLS could account for the brain responses to speaker identities

(encoding) measured in A1 and the TVAs, in comparison with a linear autoencoder's latent

space (LIN). This approach was chosen to compare a representation learned linearly under

similar conditions (same input data, learning algorithm, reconstruction objective and latent

space size) with the VLS, which has non-linear transformations and a regularized latent

space. For this, we used a general linear model (GLM) of fMRI responses to the speaker

identities, resulting in one voxel activity map per speaker (Supplementary Figure 2). Then,

we computed the average VLS coordinates of the fMRI voice stimuli for each speaker

identity, which may be seen as a speaker representation in the VLS (see *Identity-based and*

stimulus-based representations section). Next we trained a linear voxel-based encoding

model to predict the speaker voxel activity maps from the speaker VLS coordinates. As VAE

achieves compression through a series of nonlinear transformations (Wetzel, 2017), we

choose to contrast its results with a linear autoencoder's latent space. This method has

previously been applied to fMRI-based image reconstructions (Cowen et al., 2014;

VanRullen & Reddy, 2019; Mozafari et al., 2020).

The extent to which the VLS allows linearly predicting the fMRI recordings does not provide

insight into the representational geometries, i.e., the differences between the patterns of

cerebral activity for speaker identity. We addressed this question by using representational

similarity analysis (RSA; Kriegeskorte et al., 2008) to test which model better accounts for

the representational geometry for voice identities in the auditory cortex. Using RSA as a

model comparison framework is relevant to examining the brain-model relationship from

complementary angles (Diedrichsen & Kriegeskorte, 2017; Giordano et al., 2023; Tuckute &

Feather, 2023). We built speaker x speaker representational dissimilarity matrices (RDMs)

capturing pairwise differences in cerebral activity or model predictions between all pairs of

speakers; then, we examined how well the LIN and VLS-derived RDMs correlated with the

cerebral RDMs from A1 and the TVAs.

A robust test of the adequacy of models of brain activity, and a long-standing goal in

computational neurosciences, is the reconstruction of a stimulus presented to a participant

from the evoked brain responses. While reconstruction of visual stimuli (images, videos)

from cerebral activity has been performed by a number of groups (VanRullen & Reddy,

2019; Mozafari et al., 2020; Le et al., 2022; Gaziv et al., 2022; Dado et al., 2022; Chen et al.,

2023), validating the DNN-derived representational spaces, comparable work in the auditory

domain is scarce, almost exclusively concentrated on linguistic information (Santoro et al.,

2017). Akbari et al. (2019) used a DNN to reconstruct speech stimuli based on ECoG

recording of auditory cortex activity, an invasive method compared to techniques like fMRI.

They obtained a good phonetic recognition rate but chance-level gender categorization

performance from reconstructed spectrograms and no evaluation of speaker identity

discrimination.

Here, we built on the linear relationship uncovered in our encoding analysis between the

VLS and the fMRI recordings to invert it and try to predict VLS coordinates from the recorded

fMRI data; then, using the decoder, we reconstructed the spectrograms of stimuli presented

to the participants (Wu et al., 2006; Naselaris et al., 2011). The voice identity information

available in the reconstructed stimuli was finally assessed by human listeners using both

machine learning classifiers and behavioral tasks (Fig. 4).

Results

Voice Information in the Voice Latent Space (VLS). In order to probe the informational content of the VLS, linear classifiers were trained to categorize the voice stimuli from 405 speakers by gender (2 classes), age (2 classes) or identity (119 classes, cf Methods) based on VLS coordinates, or their LIN features as control (Fig. 1c,d,e; we aggregated the stimuli from the 3 participants; for each model computed the latent space of each stimulus and averaged the latent spaces by speaker identity, leading to 405 128-dimensional vectors. We then trained linear classifiers using a 5-fold cross-validation scheme, see *Characterization of the autoencoder latent space*). The mean of the distribution of accuracies obtained for 100 random classifier initializations (as to account for variance; Bouthillier et al., 2021) was significantly above chance level (all ps < 1e-10) for all classifications (LIN: gender (mean accuracy ± s.d.) = 97.64±1.77%, $t(99)=266.94$; age: 64.39±4.54%, $t(99)=31.53$; identity: 40.52±9.14%, $t(99)=39.37$; VLS: gender: 98.59±1.19%, $t(99)=406.47$; age: 67.31±4.86%, $t(99)=35.41$; identity: 38.40±8.75%, $t(99)=38.73$). We then evaluated the difference in performance at preserving identity-related information between the VLS and LIN via one-way ANOVAs. Results showed a significant effect of Feature (LIN/VLS) in categories (all $F_s(1, 198) > 225.15$, all ps<.0001) but not in identity. Post-hoc paired t-tests showed that the VLS was better than the LIN at encoding information related to voice identity, as evidenced by a significant difference in means for gender ($t(99)=-6.11$, p<.0001), age ($t(99)=-6.10$, p<.0001) but not for identity classifications ($t(99)=1.71$).

Fig. 1 | DNN-derived Voice Latent Space (VLS). a, Variational autoencoder (VAE)

Architecture. Two networks learned complementary tasks. An encoder was trained using

182K voice samples to compress their spectrogram into a 128-dimension representation, the

voice latent space (VLS), while a decoder learned the reverse mapping. The network was

trained end-to-end by minimizing the difference between the original and reconstructed

spectrograms. **b,** Distribution of the 405 speaker identities along the first 2 principal

components of the VLS coordinates from all sounds, averaged by speaker identity. Each

disk represents a speaker's identity colored by gender. PC2 largely maps onto voice gender

(ANOVAs on the first two components: PC1: $F_{(1, 405)}=0.10$, $p=.74$; PC2: $F_{(1, 405)}=11.00$,

$p<.001$). Large disks represent the average of all male (black) or female (gray) speaker

coordinates, with their associated reconstructed spectrograms (note the flat fundamental

frequency (f_0) and formant frequencies contours caused by averaging). The bottom of the

spectrograms illustrates an interpolation between stimuli of two different speaker identities:

spectrograms at the extremes correspond to two original stimuli (A, B) and their VLS-

reconstructed spectrograms (A', B'). Intermediary spectrograms were reconstructed from

linearly interpolated coordinates between those two points in the VLS (red line) (cf.

Supplementary Audio 1). **c,d e,** Performance of linear classifiers at categorizing speaker

gender (chance level: 50%), age (young/adult, chance level: 50%), or identity (119 identities,

chance level: 0.84%) based on VLS or LIN coordinates. Error bars indicate the standard

error of the mean (s.e.m) across 100 random classifier initializations. All $ps<1e-10$. The

horizontal black dashed lines indicate chance levels. ****: $p<0.0001$.

Thus, despite its low number of dimensions (each input spectrogram has $401\times21=8421$

parameters and is summarized in the VLS by a mere 128 dimensions), the VLS appears to

meaningfully represent the different sources of voice information perceptually available in the

vocal stimuli. This representational space, therefore, constitutes a relevant candidate for

linearly modeling voice stimulus representations by the brain.

Brain Encoding. We used a linear voxel-based encoding model to test whether VLS linearly

maps onto cerebral responses to speaker identities measured with fMRI in the different

ROIs. A regularized linear regression model (cf. Methods) was trained on a subset of the

data (5-fold cross-validation scheme) to predict the voxel maps for each speaker identity. For

each fold, the trained model was tested on the held-out speaker identities (Fig. 2a). The

model's performance was assessed for each ROI using the Pearson correlation score

between each voxel's actual and predicted responses (Schrimpf et al., 2021). Similar

predictions were tested with features derived from LIN (cf. Methods). Fig. 2b shows the

distribution of correlation coefficients obtained for each of the ROIs for the 2 sets of features

across voxels, hemispheres, and participants.

One-sample t-tests showed that the means of Fisher z-transformed coefficients for both LIN

features and VLS were significantly higher than zero (LIN: A1 $t(197)=7.25$, $p<.0001$, pTVA

$t(175)=4.49$, $p<.0001$, mTVA $t(164)=9.12$, $p<.0001$ and aTVA $t(147)=6.81$, $p<.0001$; VLS: A1

$t(197)=4.76$, $p<.0001$, mTVA $t(164)=10.12$, $p<.0001$ and aTVA $t(147)=5.52$, $p<.0001$ but not

pTVA $t(175)=-1.60$) (Supplementary Tables 2-3).

A mixed ANOVA performed on the Fisher z-transformed coefficients with Feature (VLS, LIN)

and ROI (A1, pTVA, mTVA, aTVA) as factors showed a significant effect of Feature ($F(3,$

$683)=56.65$, $p<.0001$), a significant effect of ROI ($F(3, 683)=18.50$, $p<.0001$), and a

moderate interaction Feature x ROI ($F(3, 683)=5.25$, $p<.01$). Post-hoc comparisons revealed

that the mean of correlation coefficients was higher for LIN than for VLS in A1 ($t(197)=4.02$,

$p<.0001$), pTVA ($t(175)=6.64$, $p<.0001$), aTVA ($t(147)=3.78$, $p<.001$) but not in mTVA

($t(164)=0.58$) (Supplementary Table 4); and that the voxel patterns are better predicted in

mTVA than in A1 for both models (LIN: $t(361)=2.36$, $p<.05$; VLS: $t(361)=4.91$, $p<.0001$)

(Supplementary Table 5). However, inspecting the distribution of model-voxel correlations,

we found that both models account for different parts of the voice identity responses and

differ across ROIs (Fig. 2c).

Fig. 2 | Predicting brain activity from the VLS. a, Linear brain activity prediction from VLS

for ~135 speaker identities in the different ROIs. We first fit a GLM to predict the BOLD

responses to each voice speaker identity. Then, using the trained encoder, we computed the

average VLS coordinates of the voice stimuli presented to the participants based on speaker

identity. Finally, we trained a linear voxel-based encoding model to predict the speaker voxel

activity maps from the speaker VLS coordinates. The cube illustrates the linear relationship

between the fMRI responses to speaker identity and the VLS coordinates. The left face of

the cube represents the activity of the voxels for each speaker's identity, with each line

corresponding to one speaker. The right face displays the VLS coordinates for each

speaker's identity. The cube's top face shows the encoding model's weight

vectors. **b,** Encoding results. For each region of interest, the model's performance was

assessed using the Pearson correlation score between the true and the predicted responses

of each voxel on the held-out speaker identities. Pearson's correlation coefficients were

computed for each voxel on the speakers' axis and then averaged across hemispheres and

participants. Similar predictions were tested with the LIN features. Error bars indicate the

standard error of the mean (s.e.m) across voxels. $*p < 0.05$; $**p < 0.01$; $**p < 0.001$; $****p <$

0.0001. **c,** Venn diagrams of the number of voxels in each ROI with the LIN, the VLS, or

both models. For each ROI and each voxel, we checked whether the test correlation was

higher than the median of all participant correlations (intersection circle), and if not, which

model (LIN or VLS) yielded the highest correlation (left or right circles).

Representational Similarity Analysis. For RSA, we built speaker x speaker

representational dissimilarity matrices (RDMs), capturing for each ROI the dissimilarity in

voxel space between each pair of speaker voxel maps ('brain RDMs'; cf. Methods) using

Pearson's correlation (Walther et al., 2016). We compared these four bilateral brain RDMs

(A1, aTVA, mTVA, pTVA) to two 'model RDMs' capturing speaker pairwise feature

differences predicted by LIN and the VLS (Fig. 3a) built using cosine distance (Xing et al.,

2015; Bhattacharya et al., 2017; Wang et al., 2018). Fig. 3b shows for each ROI the

Spearman correlation coefficients between the brain RDMs and the two model RDMs for

each participant and hemisphere (Kriegeskorte et al., 2008; Fig. 3c for an example of brain-

model correlation).

These brain-model correlation coefficients were compared to zero using a 'maximum

statistics' approach based on random permutations of the model RDMs' rows and columns

(Maris & Oostenveld, 2007; cf. Methods; Fig. 3b). For the LIN model, only one brain-model

RDM correlation was significantly different from zero (one-tailed test): in mTVA, right

hemisphere in S3 (p=.0500). For the VLS model, in contrast, 5 significant brain-model RDM

correlations were observed in all four ROIs: in A1, right hemisphere in S3 (p=.0142); pTVA:

right hemisphere in S3 (p=.0160); mTVA: left hemisphere in S3 (p=.007); aTVA: left

hemispheres in S1 (p=.0417) and S3 (p=.0001) (Supplementary Table 6).

A two-way repeated-measures ANOVA with Feature (VLS, LIN) and ROI (A1, pTVA, mTVA,

aTVA) as factors performed on the Fisher z-transformed correlation coefficients showed a

tendency towards a significant effect of Feature ($F(1, 2)=22.53$, p=.04), and no ROI ($F(3,$

$6)=1.79$, p=.30) or interaction effects ($F(3, 6)=1.94$, p=.22). We compared the correlation

coefficients between the VLS and LIN models within participants and hemispheres using

one-tailed tests, based on the a priori hypothesis that the VLS models would exhibit greater

brain-model correlations than the LIN models (cf. Methods). The results revealed two

significant differences in one of the three participants, both favoring the VLS model (S3: right

pTVA, p=.0366; left aTVA, p=.00175) (Supplementary Table 7).

Fig. 3 | The VLS better explains representational geometry for voice identities in the TVAs than the linear model. a, Representational dissimilarity matrices (RDMs) of pairwise speaker dissimilarities for ~135 identities (arranged by gender, cf. sidebars), according to LIN and VLS. **b,** Spearman correlation coefficients between the brain RDMs for A1, the 3 TVAs, and the 2 model RDMs. Error bars indicate the standard error of the mean (s.e.m) across brain-model correlations. **c,** Example of brain-model RDM correlation in the TVAs. The VLS RDM and the brain RDM yielding one of the highest correlations (LaTVA) are shown in the insert.

Decoding and Reconstruction. We finally inverted the brain-VLS relationship to predict

linearly VLS coordinates based on fMRI measurements (Fig. 4a; see 'Brain decoding' in

Methods) and reconstructed via the trained decoder the spectrograms of 18 Test Stimuli (3

participants x 6 stimuli per participant; see Fig. 4b, and Supplementary Audio 2; audio

estimated from spectrogram through phase reconstruction).

Fig. 4 | Reconstructing voice identity from brain recordings. a, A linear voxel-based

decoding model was used to predict the VLS coordinates of 18 Test Stimuli based on fMRI

responses to ~12,000 Train stimuli in the different ROIs. To reconstruct the audio stimuli

from the brain recordings, the predicted VLS coordinates were then fed to the trained

decoder to yield reconstructed spectrograms, synthesized into sound waveforms using the

Griffin-Lim phase reconstruction algorithm (Griffin & Lim, 1983). **b,** Reconstructed

spectrograms of the stimuli presented to the participants. The left panels show the

spectrogram of example original stimuli reconstructed from the VLS, and the right panels show brain-reconstructed spectrograms via LIN and the VLS (cf. Supplementary Audio 2).

We first assessed the nature of the reconstructed stimuli by using a DNN trained to categorize natural audio events (Howard et al., 2017): all reconstructed versions of the 18 Test Stimuli were categorized as 'speech' (1 class out of 521 - no 'voice' classes). To evaluate the preservation of voice identity information in the reconstructed voices, pre-trained linear classifiers were used to classify the speaker gender (2 classes), age (2 classes), and identity (17 classes; one identity was shared across participants) of the 18 reconstructed Test Stimuli. The mean of the accuracy distribution obtained across random classifier initializations (20 per ROI) used on the stimuli reconstructed from the induced brain activity was significantly above chance level for gender (LIN: pTVA (mean accuracy ± s.d.): 72.08±5.48, t(39)=25.15; VLS: A1: 61.11±2.15, t(39)=32.25; pTVA: 63.89±2.78, t(39)=31.22), age (LIN: pTVA: 54.58±4.14, t(39)=6.90; aTVA: 63.96±12.55, t(39)=6.94; VLS: pTVA: 65.00±7.26, t(39)=12.89; aTVA: 60.42±5.19, t(39)=12.54) and identity (LIN: A1: 9.20±9.23, t(39)=2.24; pTVA: 9.48±4.90, t(39)=4.59; aTVA: 9.41±6.28, t(39)=3.51; VLS: pTVA: 16.18±7.05, t(39)=9.11; aTVA: 8.23±4.70, t(39)=3.12) (Fig. 5a-c; Supplementary Tables 8-10).

Two-way ANOVAs with Feature (VLS, LIN) and ROI (A1, pTVA, mTVA, aTVA) as factors performed on classification accuracy scores (gender, age, identity) revealed for gender classifications significant effects of Feature $F(1, 312)=12.82$, p<.0005) and ROI (gender: $F(3, 312)=245.06$, p<.0001; age: $F(3, 312)=64.49$, p<.0001; identity: $F(3, 312)=14.49$, p<.0001), as well as Feature x ROI interactions (gender: $F(3, 312)=56.74$, p<.0001; age: $F(3, 312)=4.31$, p<.001; identity: $F(3, 312)=8.82$, p<.0001). Post-hoc paired t-tests indicated that the VLS was better than LIN in preserving gender, age and identity information in at least one TVA compared with A1 (gender: aTVA: t(39)=5.13, p<.0001; age: pTVA: t(39)=9.78, p<.0001; identity: pTVA: t(39)=4.01, p<.0005) (all tests in Supplementary Table 11). Post-hoc two sample t-tests comparing ROIs revealed significant differences in all classifications,

in particular with pTVA outperforming other ROIs in gender (LIN: pTVA vs A1: $t(78)=22.40$,

$p<.0001$; pTVA vs mTVA: $t(78)=10.92$, $p<.0001$; pTVA vs aTVA: $t(78)=31.47$, $p<.0001$; VLS:

pTVA vs A1: $t(78)=4.94$, $p<.0001$; pTVA vs mTVA: $t(78)=13.96$, $p<.0001$; pTVA vs aTVA:

$t(78)=22.06$, $p<.0001$), age (LIN: pTVA vs A1: $t(78)=7.26$, $p<.0001$; pTVA vs mTVA:

$t(78)=10.11$, $p<.0001$; VLS: pTVA vs A1: $t(78)=5.71$, $p<.0001$; pTVA vs mTVA: $t(78)=10.11$,

$p<.0001$; pTVA vs aTVA: $t(78)=3.21$, $p<.005$) and identity (LIN: pTVA vs mTVA: $t(78)=2.27$,

$p<.05$; VLS: pTVA vs A1: $t(78)=6.45$, $p<.0001$; pTVA vs mTVA: $t(78)=6.62$, $p<.0001$; pTVA

vs aTVA: $t(78)=5.85$, $p<.0001$) (Supplementary Table 12).

We further evaluated voice identity information in the reconstructed stimuli by testing human

participants (n=13) in a series of 4 online experiments assessing the reconstructed stimuli on

(i) naturalness judgment, (ii) gender categorization, (iii) age categorization, and (iv) speaker

categorization (cf. Methods). The naturalness rating task showed that the VLS-reconstructed

stimuli sounded more natural compared to LIN-reconstructed ones, as revealed by a two-

way repeated-measures ANOVA (factors: Feature and ROI) with a strong effect of Feature

($F(1, 12)=53.72$, $p<.0001$) and a small ROI x Feature interaction ($F(3, 36)=5.36$, $p<.005$).

Post-hoc paired t-tests confirmed the greater naturalness of VLS-reconstructed stimuli in

both A1 and the TVAs (all $ps<.0001$) (Fig. 5g). For the gender task, one-sample t-tests

showed that categorization of the reconstructed stimuli was only significantly above chance

level for the VLS (A1: (mean accuracy ± s.d.) 55.77±10.84, $t(25)=2.66$, $p<.01$; pTVA:

61.75±7.11, $t(25)=8.26$, $p<.0001$; aTVA: 55.13±9.23, $t(25)=2.78$, $p<.01$). Regarding the age

and speaker categorizations, results also indicated that both the LIN- and VLS-reconstructed

stimuli yielded above-chance performance in the TVAs (age: LIN: aTVA, 55.77±14.95,

$t(25)=1.93$, $p<.05$; VLS: aTVA, 63.14±11.82, $t(25)=5.56$, $p<.0001$; identity: LIN: pTVA:

54.38±9.34, $t(17)=1.93$, $p<.05$; VLS: pTVA: 63.33±6.75, $t(17)=8.14$, $p<.0001$)

(Supplementary Tables 13-15). Two-way repeated-measures ANOVAs revealed a significant

effect of ROI for all categories (gender: $F(3, 27)=5.90$, $p<.05$; age: $F(3, 36)=14.25$, $p<.0001$;

identity: $F(3, 24)=38.85$, $p<.0001$), and a Feature effect for gender ($F(1, 9)=43.61$, $p<.0001$)

and identity (F(1, 8)=14.07, p<.001), but not for age (F(1, 12)=4.01, p=0.07), as well as a

ROI x Feature interaction for identity discrimination (F(3, 24)=3.52, p<.05) (Supplementary

Tables 16-17 for the model and ROI comparisons).

Fig. 5 | Behavioural and machine classification of the reconstructed stimuli.

a,b,c, Decoding voice identity information in brain-reconstructed spectrograms. Performance

of linear classifiers at categorizing speaker gender (chance level: 50%), age (chance level:

50%), and identity (17 identities, chance level: 5.88%). Error bars indicate s.e.m across 40

random classifier initializations per ROI (instance of classifiers; 2 hemispheres x 20 seeds).

The horizontal black dashed line indicates the chance level. The blue and yellow dashed

lines indicate the LIN and VLS ceiling levels, respectively. *p < .05; **p < .001, ***p < .001;

****p < .0001. **d,e,f,** Listener performance at categorizing speaker gender (chance level:

50%) and age (chance level: 50%), and at identity discrimination (2 forced choice task,

chance level: 50%) in the brain-reconstructed stimuli. Error bars indicate s.e.m across

participant scores. The horizontal black dashed line indicates the chance level, while the red,

blue, and yellow dashed lines indicate the ceiling levels for the original stimuli, the LIN-

reconstructed and the VLS-reconstructed, respectively. *p < .05; **p < .01; ***p < .001, ***p <

.0001. **g,** Perceptual ratings of voice naturalness in the brain-reconstructed stimuli' as

assessed by human listeners, between 0 and 100 (zoomed between 5-80). *p < .05, ****p <

.0001.

Discussion

In this study we examined to what extent the cerebral activity elicited by brief voice stimuli

can be explained by machine-learned representational spaces, specifically focusing on

identity-related information. We trained a linear model and a DNN model to reconstruct

100,000s of short voice samples from 100+ speakers, providing low-dimensional spaces

(LIN and VLS), which we related to fMRI measures of cerebral response to thousands of

these stimuli. We find: (i) that 128 dimensions are sufficient to explain a sizeable portion of

the brain activity elicited by the voice samples and yield brain-based voice reconstructions

that preserve identity-related information; (ii) that the DNN-derived VLS outperforms the LIN

space, particularly in yielding more brain-like representational spaces and more naturalistic

voice reconstructions; (iii) that different ROIs have different degrees of brain-model

relationship, with marked differences between A1 and the a, m, and pTVAs.

Low-dimensional spaces generated by machine learning have been used to approximate

cerebral face representations and reconstruct recognizable faces based on fMRI (VanRullen

& Reddy, 2019; Dado et al., 2022). In the auditory domain, however, they have mainly been

used with a focus on linguistic (speech) information, ignoring identity-related information (but

see Akbari et al., 2019). Here, we applied them to brief voice stimuli–with minimal linguistic

content but already rich identity-related information–and found that as little as 128

dimensions account reasonably well for the complexity of cerebral responses to thousands

of these voice samples as measured by fMRI (Fig. 2). LIN and VLS both showed brain-like

representational geometries, particularly the VLS in the aTVAs (Fig. 3). They made possible

what is, to our knowledge, the first fMRI-based voice reconstructions to preserve voice-

related identity information such as gender, age, or even individual identity, as indicated by

above-chance categorization or discrimination performance by both machine classifiers (Fig.

5a-c) and human listeners (Fig. 5d-f).

Estimation of fMRI responses (encoding) by LIN yielded correlations largely comparable to

those by VLS (Fig. 2b), although many voxels were only explained by one or the other space

(Fig. 2c). However, in the RSA, VLS yielded higher overall correlations with brain RDMs (Fig.

3), suggesting a representational geometry closer to that instantiated in the brain than LIN.

Further, VLS-reconstructed stimuli sounded more natural than the LIN-reconstructed ones

(Fig. 5g) and yielded both the best speaker discrimination by listeners (Fig. 5f) and speaker

classification by machine classifiers (Fig. 5c). Unlike LIN, which was generated via linear

transforms, VLS was obtained through a series of nonlinear transformations (Wetzel, 2017).

The fact that the VLS outperforms LIN in decoding performance indicates that nonlinear

transformation is required to better account for the brain representation of voices (Naselaris

et al., 2011; Cowen et al., 2014; Han et al., 2019).

Comparisons between ROIs revealed important differences between A1 and the a, m, and

pTVAs. For both LIN and VLS, fMRI signal (encoding) predictions were more accurate for

the mTVAs than for A1, and for A1 than for the pTVAs (Fig. 2b). The aTVAs yielded the

highest correlations with the models in the RSA (Fig. 3). Stimulus reconstructions (Fig. 4)

based on the TVAs also yielded better gender, age, and identity classification than those

based on A1, with gender and identity best preserved in the pTVA-, and to a lesser extent, in

the aTVA-based reconstructions (Fig. 5). These results show that the a and pTVAs not only

respond more strongly to vocal sounds than A1, but they also represent identity-related

information in voice better than mTVA, which was previously anticipated in some

neuroimaging studies (Gender: Charest et al., 2013; Identity: Belin & Zatorre, 2003;

Maguinness et al., 2018; Roswandowitz et al., 2018; Aglieri et al., 2021). Moreover, several

recent studies, using intracranial recordings, either through ECoG electrode grids (Zhang et

al., 2021) or sEEG recordings (Rupp et al., 2022), found evidence that supports the idea of a

hierarchical organization of voice patches in the temporal lobe, where the information flow

starts from the mTVA patches and moves in two directions: one from mTVA to the anterior

TVA (aTVA) and the other one from mTVA to posterior TVA (pTVA).

Overall, we show that a DNN-derived representational space provides an interesting

approximation of the cerebral representations of brief voice stimuli that can preserve identity-

related information. We find it remarkable that such results could be obtained to explain

sound representations despite the poor temporal resolution of fMRI. Future work combining

more complex architectures to time-resolved measures of cerebral activity, such as

magneto-encephalography (Défossez et al., 2023) or ECoG (Pasley et al., 2012), will likely

yield better models of the cerebral representations of voice information.

Methods

Experimental procedure overview

Three participants attended 13 MRI sessions each. The first session was dedicated to

acquire high-resolution structural data, as well as to identify the voice-selective areas of

each participant using a 'voice localizer' based on different stimuli than those in the same

experiment (Pernet et al., 2015; see below).

Functional scanning was done using a rapid event-related design with a jittered inter-

stimulus-interval (2.8-3.2 s). The next 12 sessions began with the acquisition of two fast

structural scans for inter-session realignment purposes, followed by six functional runs,

during which the main stimulus set of the experiment was presented. Each functional run

lasted approximately 12 minutes. Participants 1 and 2 attended all scanning sessions (72

functional runs in total); due to technical issues, Participant 3 only performed 24 runs.

Participants were instructed to stay in the scanner while listening to the stimuli. To maintain

participants' awareness during functional scanning, they were asked to press an MRI-

compatible button each time they heard the same stimulus two times in a row, a rare event

occurring 3% of the time (correct button hits (median accuracy ± s.d.): S1=96.67±7.10,

S2=100.00±0.89, S3=95.00±3.68).

Scanning sessions were spaced by at least two days to avoid possible auditory fatigue due

to the exposure to scanner noise. To ensure that participants' hearing abilities did not vary

across scanning sessions, hearing thresholds were measured before each session using a

standard audiometric procedure (Martin & Champlin, 2000; ISO 2004) and compared with

the thresholds obtained prior the first session.

Participants

This study was part of the project 'Réseaux du Langage' and was promoted by the National

Center for Scientific Research (CNRS). It has been given favorable approval by the local

ethics committee (Comité de Protection des Personnes Sud-Méditerranée) on the date of

13th February 2019. The National Agency for Medicines (ANSM) has been informed of this

study, which is registered under the number 2017-A03614-49. Three native French human

speakers were scanned (all females; 26-33 years old). Participants gave written informed

consent and received a compensation of 40€ per hour for their participation. All were right-

handed and no one had hearing disorder or neurological disease. All participants had normal

hearing thresholds of 15 dB HL, for octave frequencies between 0.125 and 8 kHz.

Stimuli

The auditory stimuli were divided into two sequences. One 'voice localizer' sequence to

identify the voice-selective areas of each participant (Pernet et al., 2015) and a main voice

stimuli.

Voice localizer stimuli. The voice localizer stimuli consisted of 96 complex sounds of 500ms

grouped in four categories of human voice, macaque vocalizations, marmoset vocalizations,

and complex non-vocal sounds (more details in Bodin et al., 2021).

Main voice stimuli. The main stimulus set consisted of brief human voice sounds sampled

from the Common Voice dataset (Ardila et al., 2020). Stimuli were organized into four main

category levels: language (English, French, Spanish, Deutch, Polish, Portuguese, Russian,

Chinese), gender (female/male), age (young/adult; young: teenagers and twenties; adult:

thirties to sixties included) and identity (S1: 135 identities; S2: 142 identities; S3: 128

identities; ~44 samples per identity). Throughout the manuscript, the term 'gender' rather

than 'sex' was utilized in reference to the demographic information obtained from the

participants of the Common Voice dataset (Ardila et al., 2020), as it was the terminology

employed in the survey ('male/female/other'). Stimulus sets were different for each

participant and the number of stimuli per set also varied slightly (number of unique stimuli:

Participant 1, N=6150; Participant 2, N=6148; Participant 3, N=5123). For each participant,

six stimuli were selected randomly among the sounds having a high energy (as measured

with the amplitude envelope) from their stimulus set and were repeated extensively (60

times), to improve the performance of the brain decoding (VanRullen & Reddy, 2019;

Horikawa & Kamitani, 2017; Chang et al., 2019); these will be called the "repeated" stimuli

hereafter, the remaining stimuli were presented twice. The third participant attended 5

BrainVoice sessions instead of 12, one BrainVoice session corresponding to 1030 stimuli

(1024 unique stimuli and 6 'test' stimuli). Specifically, 5270 stimuli were presented to the

third participant instead of ~12,000 for the two others. Among these 5270 stimuli, 5120

unique stimuli were presented once, as for the two other participants, 6 'test' stimuli were

presented 25 times (150 trials). The stimuli were balanced within each run according to

language, gender, age, and identity, as to avoid any potential adaptation effect. In addition,

identity was balanced across sessions.

All stimuli of the main set were resampled at 24414 Hz and adjusted in duration (250 ms).

For each stimulus, a fade-in and a fade-out were applied with a 15 ms cosine ramp to their

onset and offset, and were normalized by dividing the root mean square amplitude. During

fMRI sessions, stimulus presentations were controlled using custom Matlab scripts

(Mathworks, Natick, MA, USA) interfaced with an RM1 Mobile Processor (Tucker-David

Technologies, Alachua, USA). The auditory stimuli were delivered pseudo-randomly through

MRI-compatible earphones (S14, SensiMetrics, USA) at a comfortable sound pressure level

that allowed for clear and intelligible listening.

Computational models

We used two computational models to learn representational space for voice signals, Linear

Autoencoder (LIN) and Deep Variational Autoencoder (VAE; Kingma & Welling., 2014). Both

are encoder-decoder models that are learnt to reproduce at their output their input while

going through a low dimensional representation space usually called latent space (that we

will call *voice latent space* since they are learnt on voice data). The autoencoders were

trained on a dataset of 182K sounds from the Common Voice dataset (Ardila et al., 2020),

balanced in gender, language and identity to reduce the bias in the synthesis (Gutierrez et

al., 2021). Both models operate on sounds which were represented as spectrograms that we

describe below. These representations were tested in all the encoding/decoding and RSA

analyses.

Spectrograms

We used amplitude spectrograms as input of the models that we describe below. Short term

Fourier transforms of the waveform were computed using a sliding window of length 50 ms

with a hop size of 12.5 ms (hence an overlap of 37.5 ms) and applying a Hamming window

of size 800 samples before computing the Fourier transform of each slice. Only the

magnitude of the spectrogram was kept and the phase of the complex representation was

removed. At the end, a 250 ms sound is represented by a 21×401 matrix with 21 time steps

and 401 frequency bins.

We used a custom code based on $numpy.fft$ package (Harris et al., 2020). The size and

the overlap between the sliding windows of the spectrogram were chosen to conform with

the uncertainty principle between time and frequency resolution. The main constraint was to

find a trade-off between accurate phase reconstruction with the Griffin & Lim algorithm

(1983) and a reasonable size of the spectrogram.

We standardized each of the 401 frequency bands separately, by centering all the data

corresponding to each frequency band at every time step in all spectrograms, which involved

removing their mean, and dividing by their standard deviation. This separate standardization

of frequency bands resulted in a smaller reconstruction error compared to standardizing

across all the bands.

Deep neural network

We designed a deep variational autoencoder (VAE; Kingma & Welling, 2014) of 15 layers

with an intermediate hidden representation of 128 neurons that we refer to as the *voice*

latent space (VLS). In an autoencoder model, the two sub-network components, the *Encoder*

and the *Decoder*, are jointly learned on complementary tasks (Fig. 1a). The Encoder network

(noted Enc hereafter; 7 layers) learns to map an input, s (a spectrogram of a sound), onto a

(128-dimensional) *voice latent space* representation (z; in blue in the middle of Fig. 1a),

while the Decoder (noted Dec hereafter; 7 layers) aims at reconstructing the spectrogram s

from z. The learning objective of the full model is to make the output spectrogram

$Dec(Enc(s))$ as close as possible to the original one s. This reconstruction objective is

defined as the L2 loss, $||Dec(Enc(s)) - s||^2$. The parameters of the Encoder and of the

Decoder are jointly learned using gradient descent to optimize the average L2 loss

computed on the training set $\sum_{s \in Training\ Set} ||Dec(Enc(s)) - s||^2$. We trained this DNN on

the Common Voice dataset (Ardila et al., 2020) according to VAE learning procedure (as

explained in Kingma & Welling., 2019) until convergence (network architecture and

particularities of the training procedure are provided in Supplementary Table 1), using the

PyTorch python package (Paszke et al., 2019).

Linear autoencoder

We trained a linear autoencoder on the same dataset (described above) to serve as a linear

baseline. Both the *Encoder* and the *Decoder* networks consisted of a single fully-connected

layer, without any activation functions. Similar to the VAE, the latent space obtained from the

Encoder was a 128-dimensional vector. The parameters of both the *Encoder* and of the
25

553   *Decoder* were jointly learned using gradient descent to optimize the average L2 loss

554   computed on the training set.

Neuroimaging data acquisition

Participants were scanned using a 3 Tesla Prisma scanner (Siemens Healthcare, Erlangen,

Germany) equipped with a 64-channel receiver head-coil. Their movements were monitored

during the acquisition using the software FIRMM (Dosenbach et al., 2017). The whole-head

high-resolution structural scan acquired during the first session was a T1-weighted multi-

echo MPRAGE (MEMPRAGE) (TR = 2.5 s, TE = 2.53, 4.28, 6.07, 7.86 ms, TI=1000 ms flip

angle: 8°, matrix size = 208 × 300 × 320; resolution 0.8 × 0.8 × 0.8 mm^3, acquisition time:

8min22s). Lower resolution scans acquired during all other sessions were T1-weighted

MPRAGE scans (TR = 2.3 s, TE = 2.88 ms, TI=900ms, flip angle: 9°, matrix size = 192 ×

240 × 256; resolution 1 × 1 × 1 mm^3, sparse sampling with 2.8 times undersampling and

compressed sensing reconstruction, acquisition time: 2min37). Functional imaging was

performed using an EPI sequence (multiband factor = 5 , TR = 462 ms, TE = 31.2 ms, flip

angle: 45°, matrix size = 84 × 84 × 35, resolution 2.5 × 2.5 × 2.5 mm^3). Functional slices

were oriented parallel to the lateral sulci with a z-axis coverage of 87.5 mm, allowing it to

fully cover both the TVAs (Pernet et al., 2015) and the FVAs (Aglieri et al., 2018). The

physiological signals (heart rate and respiration) were measured with the external sensors of

Siemens.

Pre-processing of neuroimaging data and general linear modeling

Tissue segmentation and brain extraction was performed on the structural scans using the

default segmentation procedure of SPM 12 (Ashburner et al., 2012). The preprocessing of

the BOLD responses involved correcting motion, registering inter-runs, detrending and

smoothing the data. Each functional volume was realigned to a reference volume taken from

a steady period in the session that was spatially the closest to the average of all sessions.

Transformation matrices between anatomical and functional data were computed using

boundary-based registration (FSL; Smith et al., 2004). The data were respectively detrended

and smoothed using the *nilearn* functions $clean\_img$ and $smooth\_img$ (kernel size of 3mm)

(Abraham et al., 2014), resulting in the matrix $Y \in R^{S \times V}$, with S the number of scans and V

the number of voxels.

A first general linear model (GLM) was fit to regress out the noise by predicting Y from a

"denoised" design matrix, composed of $R = 38$ regressors of nuisance (Supplementary

Figure 3). These regressors of nuisance, also called covariates of no interest, included: 6

head motion parameters (3 variable for the translations, 3 variables for the rotations); 18

'RETROICOR' regressors (Glover et al., 2000) using the *TAPAS PhysIO* package (Kasper et

al., 2017) (with the hyperparameters set as specified in Snoek et al.) were computed from

the physiological signals; 13 regressors modeling slow artifactual trends (sines and cosines,

cut frequency of the high-pass filter = 0.01 Hz); and a confound-mean predictor. The design

matrix was convolved with an hemodynamic response function (HRF) with a peak at 6 s and

an undershoot at 16 s (Glover et al., 1999), we note the convolved design matrix as $X_d \in$

$R^{S \times R}$. The "denoise" GLM's parameters $\beta_d \in R^{R \times V}$ were optimized to minimize the

amplitude of the residual $\beta_d = argmin_{\beta \in R^{R \times V}} \; || \; Y \; - X_d \; \beta \; ||^2$. We used a lag-1

autoregressive model (ar(1)) to model the temporal structure of the noise (Friston et al.,

2002). The *denoised* BOLD signal Y_d was then obtained from the original one according to

$Y_d = Y - (X_d \; \beta_d) \in R^{S \times V}$.

A second "stimulus" GLM model was used to predict the denoised BOLD responses for each

stimulus using a design matrix $X_s \in R^{S \times (N_S + 1)}$ (which was convolved with an hemodynamic

response function, HRF as above) and a parameters matrix $\beta_s \in R^{(N_S + 1) \times V}$ where N_S stands

for the number of stimuli. The last row (resp. column) of β_s (resp. X_s) stands for a silence

condition. Again, β_s was learned to minimize the residual $\beta_s = argmin_{\beta \in R^{(N_S+1) \times V}} \; || Y_d -$

$X_s \beta \; ||^2$. Once learned, each of the first N_s line of β_s was corrected by subtracting the

$(N_s+1)^{th}$ line, yielding the contrast maps for stimuli $\tilde{\beta}_s \in R^{N_S \times V}$. We note hereafter $\tilde{\beta}_s[i, :] \in$

R^V the contrast map for a given stimulus, it is the i^{th} line of $\tilde{\beta}_s$.

A third "identity" GLM was fit to predict the BOLD responses of each voice speaker identity,

using a design matrix $\beta_i \in R^{(N_i+1) \times V}$ and a design matrix $X_i \in R^{S \times (N_i+1)}$ (which was again

convolved with an hemodynamic response function, HRF) where N_s stands for the number

of unique speakers. Again the last row/column in β_i and X_i stands for the silent condition. β_i

is learned to minimize the residual $\beta_i = argmin_{\beta \in R^{(N_i+1) \times V}} ||Y_d - X_i \beta||^2$ (Supplementary

Figure 2a). Again, the final speaker contrast maps were obtained by contrasting (i.e.,

subtracting) the regression coefficients in a row of β_i with the silence condition (last row;

Supplementary Figure 2a), yielding $\tilde{\beta}_i \in R^{N_s \times V}$. Here the j^{th} row of $\tilde{\beta}_i$, $\tilde{\beta}_i[j,:] \in R^V$,

represents the amplitude of the BOLD response of the contrast map for speaker j (i.e. to all

the stimuli from this speaker).

A fourth "localizer" GLM model was used to predict the denoised BOLD responses of each

sound category from the *Voice localizer stimuli* presented above. The procedure was similar

as described for the two previous GLM models. Once the GLM was learned, we contrasted

the human voice category with the other sound categories in order to localize for each

participant the posterior Temporal Voice Area (pTVA), medial Temporal Voice Area (mTVA)

and anterior Temporal Voice Area (aTVA) in each hemisphere. The center of each TVA

corresponded to the local maximum of the voice > non voice t-map whose coordinates were

the closest to the TVAs reported in (Pernet et al., 2015). The analyses were carried on for

each region of interest (ROI) of each hemisphere.

Additionally, we defined for each participant the primary auditory cortex (A1) as the

maximum value of the probabilistic map (non-linearly registered to each participant

functional space) of Heschl's gyri provided with the MNI152 template (Penhune et al., 1996),

intersected with the sound vs silence contrast map.

Identity-based and stimulus-based representations

We performed analyses either at the stimulus level, e.g. predicting the neural activity of a

participant listening to a given *stimulus* ($\tilde{\beta}_s$'s lines) from the *voice latent space* representation

of this stimuli, or at the speaker identity level, e.g. predicting the average neural activity in

response to stimuli of a given speaker *identity* ($\tilde{\beta}_i$'s lines) from this speaker's *voice latent*

space representation. The identity-based analyses were used for the characterization of the

voice latent space (Fig. 1), the brain encoding (Fig. 2), and the representational similarity

analysis (Fig. 3), while the stimulus-based analyses were used for the brain decoding

analyses (Fig. 4, 5).

We conducted stimulus-based analyses to examine the relationship between stimulus

contrast maps in neural activity ($\tilde{\beta}_s$) and the encodings of individual stimulus spectrograms

computed by the encoder of an autoencoder model (either linear or deep variational

autoencoder) on the computational side. We will note $z_s{}^{lin} \in R^{N_s \times 128}$ encodings of stimuli

by the LIN model and $z_s{}^{vae} \in R^{N_s \times 128}$ the encodings of stimuli computed by the VAE

model. The encoding of the k[th] stimuli by one of these models is the k[th] row of the

corresponding matrix and it is noted as $z_s{}^{model}[k,:]$.

For identity-based analyses we studied relationships between identity contrast maps in $\tilde{\beta}_i$ on

the neural activity side, and an encoding of speaker identity in the VLS implemented by an

autoencoder model (LIN or VAE) on the computational side, e.g. we note $z_i{}^{vae}[j]$ the

representation of speaker *j* as computed by the *vae* model. We chose to define a speaker

identity-based representation as the average of a set of sample-based representations for

stimuli from this speaker, e.g. $z_i{}^{model}[j] = 1/|S_j| \sum_{k \in S_j} z_s{}^{model}[k,:]$ where S_j stands for the

set of stimuli by speaker *j* and *model* stands for *vae* or *lin*. Averaging in the *voice latent*

space is expected to be much more powerful and relevant than averaging in the input space

spectrograms (VanRullen & Reddy, 2019).

Characterization of the autoencoder latent space

We characterized the organization of the *voice latent space* (VLS) and of the features

computed by the linear autoencoder (LIN) by measuring through classification experiments

the presence of information about speaker's gender, age, and identity in the representations

learned by these models.

We first computed the speaker's identity *voice latent space* representations for each of the

405 speakers in the main voice dataset (135+142+128 see *Stimuli* section) as explained

above.

Next we used these speakers' *voice latent space* representation to investigate if the gender,

age, identity were encoded in the VLS. To do so we divided the data in separate train and

test sets and learned classifiers to predict gender, age, or identity from the train set. The

balanced (to avoid the small effects associated with unbalanced folds) accuracy of the

classifiers were then evaluated on the test set. The higher the performance on the test set

the more we are confident that the information is encoded in the VLS. More specifically for

each task (gender, age, identity), we trained a Logistic Regression classifier (linear

regularized logistic regression; L2 penalty, tol=0.0001, fit_intercept=True,

intercept_scaling=1, max_iter=100) using the scikit-learn python package (Pedregosa et al.,

2018).

In order to statistically evaluate the significance of the results and to avoid a potential

overfitting, the classifications were repeated 20 times with 20 different initializations (*seed*)

and the metrics were then averaged for each voice category (gender, age). More

specifically, we repeated the following experiment 20 times with 20 different random seeds.

For each seed, we performed 5 train-test splits with 80% of the data in the training and 20%

in the test set. For each split we used 5-fold cross validation on the training set to select the

optimal value for the regularization hyperparameter C (searching between 10 values

logarithmically spaced on the interval [-3, +3]). We then computed the generalization

performance on the test set of the model trained on the full training set with the best

hyperparameter value. Reported results were then averaged over 20 experiments. Note that

data were systematically normalized with a scaler fitted on the training set. We used a robust

scaling strategy for these experiments (removing the median, then scaling to the quantile

range; 25[th] quantile and 75[th] quantile) which occurs to be more relevant with a small training

set.

To investigate how speaker identity information is encoded in the latent space

representations of speakers' voices, we computed speaker identity *voice latent space*

representations by averaging 20 stimulus-based representations, in order to obtain a limited

amount of data per identity that could be distributed across training and test datasets.

We first tested whether the mean of the distribution of accuracy scores obtained for 20

seeds was significantly above chance level using one-sample t-tests. We then evaluated the

difference in classification accuracy between the VLS and LIN via one-way ANOVAs

(dependent variable: test balance accuracy; between factor: Feature), for each category

(speaker gender, age, identity). We performed post-hoc planned paired t-tests between the

models to test the significance of the VLS-LIN difference.

Brain encoding

We performed encoding experiments on identity-based representations for each of the three

participants (Fig. 2). For each participant we explored the ability to learn a regularized linear

regression that predicts a speaker-based neural activity, e.g. the j^{th} speaker's contrast map

$\tilde{\beta}_i[j] \in R^V$, from this speaker's voice latent space representation, that we note $z_i^{model}[j] \in$

R^{128} (Fig. 2a). We carried out these regression analyses for each ROI (A1, pTVA, mTVA,

aTVA) in each hemisphere and participant, independently.

The regression model parameters $\widehat{W}_{encod} \in R^{128 \times V}$ were learned according to:

$$\widehat{W}_{encod} = argmin_{W_{encod} \in R^{128 \times V}} \sum_{j=1..N_i} (z_i^{model}[j] \times W_{encod} - \tilde{\beta}_i[j])^2 + \lambda \|W_{encod}\|^2$$

where λ is a hyperparameter tuning the optimal tradeoff between the data fit and the

penalization terms above. We used the ridge regression with built-in cross-validation as

implemented as $RidgeCV$ in the scikit-learn library (Pedregosa et al., 2018).

The statistical significance of each result was assessed with the following procedure. We

repeated the following experiment 20 times with different random seeds. Each time, we

performed 5 train-test splits with 80% of the data in the training and 20% in the test set. For

each split we used RidgeCV (relying on leave-one-out) on the training set to select the

optimal value for the hyperparameter λ (searching between 10 values logarithmically spaced

on the interval $[10^{-1}; 10^{8}]$). Following standard practice in machine learning, we then

computed the generalization performance on the test set of the model trained on the full

training set with the best hyperparameter value. Reported results are then averaged over 20

experiments. Note that here again with small training sets data were systematically

normalized in each experiment using robust scaling.

Evaluation relied on the 'brain score'-inspired procedure (Schrimpf et al., 2018) which

evaluates the performance of the ridge regression with a Pearson's correlation score.

Correlations between measured neural activities $\tilde{\beta}_i$ and predicted ones $z_i^{\widehat{model}} * W_{encod}$

were computed for each voxel and averaged over repeated experiments (folds and seeds)

yielding one correlation value for every voxel and for every setting. The significance of the

results was assessed with one-sample t-tests for the Fisher z-transformed correlation scores

(3 x participants x 2 hemispheres x V voxels). For each region of interest, the scores are

reported across participants and hemispheres (Fig. 2b). The exact same procedure was

followed for the LIN modeling.

In order to determine which of the two feature spaces (VLS, LIN) and which of the two ROI

(A1, TVAs) yielded the best prediction of neural activity, we compared the means of

distributions of correlations coefficients using a mixed ANOVA performed on the Fisher z-

transformed coefficients (dependent variable: correlation; between factor: ROI; repeated

measurements: Feature; between-participant identifier: voxel).

For each ROI, we then used t-tests to perform post-hoc contrasts for the VLS-LIN difference

in brain encoding performance (comparison tests in Fig. 2b; Supplementary Table 4). We

finally conducted two-sample t-tests between the brain encoding model's scores trained to

predict A1 and those trained to predict temporal voice areas to test the significance of the

A1-TVAs difference (Supplementary Table 5).

The statistical tests were all performed using the *pingouin* python package (Vallat, 2018).

Representational similarity analysis

The RSA analyses were carried out using the package *rsatoolbox* (Schütt et al., 2021;

https://github.com/rsagroup/rsatoolbox). For each participant, region of interest and

hemisphere, we computed the cerebral Representational Dissimilarity Matrix (RDM) using

the Pearson's correlation between the speaker identity-specific response patterns of the

GLM estimates $\tilde{\beta}_i$ (Walther et al., 2016) (Fig. 3a). The model RDMs were built using cosine

distance (Xing et al., 2015; Bhattacharya et al., 2017; Wang et al., 2018), capturing speaker

pairwise feature differences predicted by the computational models LIN and the VLS (Fig.

3a). For greater comparability with the rest of the analyses described here, the GLM

estimates and the computational models' features were first normalized using robust scaling.

We computed the Spearman correlations coefficients between the brain RDMs for each ROI,

and the two model's RDMs (Fig. 3b). We assessed the significance of these brain-model

correlation coefficients within a permutation-based 'maximum statistics' framework for

multiple comparison correction (one-tailed inference; N permutations = 10,000 for each test;

permutation of rows and columns of distance matrices, see Giordano et al., 2023 and Maris

& Oostenveld, 2007; see Fig. 3b). We evaluated the VLS-LIN difference using a two-way

repeated-measures ANOVA on the Fisher z-transformed Spearman correlation coefficients

(dependent variable: correlation; within factors: ROI and Feature; participant identifier:

756   participant hemisphere pair). The same permutation framework was also used to assess the

757   significance of the difference between the RSA correlation for the VLS and LIN models.

Brain decoding

Brain decoding was investigated at the stimulus level. The stimuli's voice latent space

representations $z_s{}^{model} \in R^{N \times 128}$ and voice samples' contrast maps $\tilde{\beta}_s \in R^{N \times V}$ were

divided into train and test splits, normalized across voice samples using robust scaling, then

fit to the training set. For every participant and each ROI, we trained a L_2-regularized linear

model $W \in R^{V \times 128}$ model to predict the voice samples' latent vectors from the voice

samples' contrast maps (Fig. 4a). The hyperparameter selection and optimization was done

similarly as in the Brain encoding scheme. Training was performed on non repeated stimuli

(see Stimuli section). We then used the trained models to predict for each participant the 6

repeated stimuli that were the most presented. Waveforms were estimated starting from the

reconstructed spectrograms using the Griffin-Lim phase reconstruction algorithm (Griffin &

Lim, 1983).

We then used classifier analyses to assess the presence of voice information (gender, age,

speaker identity) in the reconstructed latent representations (i.e., the latent representation

predicted from the brain activity of a participant listening to a specific stimulus) (Fig. 5a, b, c).

To this purpose, we first trained linear classifiers to categorize the training voice stimuli

(participant 1, N = 6144; participant 2, N = 6142; participant 3, N = 5117; total, N = 17403) by

gender (2 classes), age (2 classes) or identity (17 classes) based on VLS coordinates.

Secondly, we used the previously trained classifiers to predict the identity information based

on the VLS derived from the brain responses of the 18 Test voice stimuli (3 participants x 6

stimuli). We first tested using one-sample t-tests that the mean of the distribution of accuracy

scores obtained across random classifier initializations of classifiers (2 hemispheres x 20

seeds = 40) was significantly above chance level, for each category, ROI and model. We

then evaluated the difference in performance at preserving identity-related information

depending on the model or ROI via two-way ANOVAs (dependent variable: accuracy;

between factors: Feature and ROI). We performed post-hoc planned paired t-tests between

each model pair to test the significance of the VLS-LIN difference. Two-sample t-tests were

finally used to test the significance of the A1-TVAs difference.

Listening tests

We recruited 13 participants through the online platform Prolific (www.prolific.co) for a series

of online behavioral experiments. All participants reported having normal hearing. The

purpose of these experiments was to evaluate how well voice identity information and

naturalness are preserved in fMRI-based reconstructed voice excerpts. In the main session,

participants carried out 4 tasks, in the following order: 'speaker discrimination' (~120 min),

'perceived naturalness' (~30 min), 'gender categorization' (~30 min), 'age categorization'

(~30 min). The experiment lasted 3 hours and 35 minutes, and each participant was paid

£48. 12 participants performed the speaker discrimination task, and all participants

performed the other tasks.

Prior to the main experiment session, participants carried out a short loudness-change

detection task to ensure that they wore headphones, and that they were attentive and

properly set up for the main experiment (Woods et al., 2017). On each of 12 trials,

participants heard 3 tones and were asked to identify which tone was the least loud by

clicking on one of 3 response buttons: 'First', 'Second', or 'Third'. Participants were admitted

to the main experiment only if they achieved perfect performance in this task. We

additionally refined the participant pool by excluding those who performed badly on the

original stimuli, by retaining only the subjects whose performance was above the 25th

percentile of accuracy. (gender and age categorizations: as all participants performed well

(Fig. 5d, e, red dotted lines); speaker discrimination: 9/12 participants performed above the

threshold of 64%).

The next three tasks were each carried out on the same set of 342 experimental stimuli,

each presented on a different trial: 18 original stimuli, 36 stimuli reconstructed directly from

the LIN and the VLS models, and 18 stimuli x 2 models x 4 regions of interest x 2

hemispheres= 288 brain-reconstructed stimuli.

In the 'perceived naturalness' task, participants were asked to rate how natural the voice

sounded on a scale ranging from 'Not at all natural' to 'Highly natural' (i.e., similar to a real

recording), and were instructed to use the full range of the scale.

During the 'gender categorization' task, participants categorized the gender by clicking on a

'Female' or 'Male' button.

Finally, in the 'age categorization' task, participants categorized the age of the speaker by

clicking on a 'Younger' or 'Older' button.

In the 'speaker discrimination' task, participants carried out 684 trials (342 experimental

stimuli x 2) with short breaks in between. On each trial, they were presented with 2 short

sound stimuli, one after the other, and participants had to indicate whether they were from

the same speaker or not. The speech material was selected randomly and was different

between two stimuli.

To evaluate the performance of the participants, we firstly conducted one-sample t-tests to

examine whether the mean accuracy score calculated from their responses was significantly

higher than the chance level for each model and ROI. Next, we used two-way repeated-

measures ANOVAs to assess the variation in participants' performances in identifying

identity-related information (dependent variable: accuracy; between-participant factors:

Feature and ROI). To determine the statistical significance of the VLS-LIN difference, we

carried out post-hoc planned paired t-tests between each model pair. Finally, we employed

two-sample t-tests to evaluate the statistical significance of the A1-TVAs difference.

Data and code availability

All data and codes will be made publicly available upon the article publication.

References

Abraham, Alexandre, Fabian Pedregosa, Michael Eickenberg, Philippe Gervais, Andreas

Mueller, Jean Kossaifi, Alexandre Gramfort, Bertrand Thirion, and Gael Varoquaux.

2014. "Machine Learning for Neuroimaging with Scikit-Learn." *Frontiers in*

Neuroinformatics 8.

Aglieri, Virginia, Bastien Cagna, Lionel Velly, Sylvain Takerkart, and Pascal Belin. 2021.

"FMRI-Based Identity Classification Accuracy in Left Temporal and Frontal Regions

Predicts Speaker Recognition Performance." *Scientific Reports* 11(1):489. doi:

10.1038/s41598-020-79922-7.

Akbari, Hassan, Bahar Khalighinejad, Jose L. Herrero, Ashesh D. Mehta, and Nima

Mesgarani. 2019. "Towards Reconstructing Intelligible Speech from the Human

Auditory Cortex." *Scientific Reports* 9(1):874. doi: 10.1038/s41598-018-37359-z.

Ardila, Rosana, Megan Branson, Kelly Davis, Michael Henretty, Michael Kohler, Josh Meyer,

Reuben Morais, Lindsay Saunders, Francis M. Tyers, and Gregor Weber. 2020.

"Common Voice: A Massively-Multilingual Speech Corpus."

Ashburner, John. 2012. "SPM: A History." *NeuroImage* 62(2):791–800. doi:

10.1016/j.neuroimage.2011.10.025.

Barbero, Francesca M., Roberta P. Calce, Siddharth Talwar, Bruno Rossion, and Olivier

Collignon. 2021. "Fast Periodic Auditory Stimulation Reveals a Robust Categorical

Response to Voices in the Human Brain." *eNeuro* 8(3):ENEURO.0471-20.2021. doi:

10.1523/ENEURO.0471-20.2021.

Belin, Pascal, Patricia E. G. Bestelmeyer, Marianne Latinus, and Rebecca Watson. 2011.

"Understanding Voice Perception: Understanding Voice Perception." *British Journal of*

Psychology 102(4):711–25. doi: 10.1111/j.2044-8295.2011.02041.x.

Belin, Pascal, Clémentine Bodin, and Virginia Aglieri. 2018. "A 'Voice Patch' System in the

Primate Brain for Processing Vocal Information?" *Hearing Research* 366:65–74. doi:

10.1016/j.heares.2018.04.010.

Belin, Pascal, Shirley Fecteau, and Catherine Bédard. 2004. "Thinking the Voice: Neural

Correlates of Voice Perception." *Trends in Cognitive Sciences* 8(3):129–35. doi:

10.1016/j.tics.2004.01.008.

Belin, Pascal, and Robert J. Zatorre. 2003. "Adaptation to Speaker's Voice in Right Anterior

Temporal Lobe:" *NeuroReport* 14(16):2105–9. doi: 10.1097/00001756-200311140-

00019.

Belin, Pascal, Robert J. Zatorre, Philippe Lafaille, Pierre Ahad, and Bruce Pike. 2000.

"Voice-Selective Areas in Human Auditory Cortex." *Nature* 403(6767):309–12. doi:

10.1038/35002078.

Bhattacharya, Gautam, Jahangir Alam, and Patrick Kenny. 2017. "Deep Speaker

Embeddings for Short-Duration Speaker Verification." Pp. 1517–21 in *Interspeech*

2017. ISCA.

Blank, Helen, Nuri Wieland, and Katharina von Kriegstein. 2014. "Person Recognition and

the Brain: Merging Evidence from Patients and Healthy Individuals." *Neuroscience &*

Biobehavioral Reviews 47:717–34. doi: 10.1016/j.neubiorev.2014.10.022.

Bodin, Clémentine, Régis Trapeau, Bruno Nazarian, Julien Sein, Xavier Degiovanni, Joël

Baurberg, Emilie Rapha, Luc Renaud, Bruno L. Giordano, and Pascal Belin. 2021.

"Functionally Homologous Representation of Vocalizations in the Auditory Cortex of

Humans and Macaques." *Current Biology* S0960982221011477. doi:

10.1016/j.cub.2021.08.043.

Bouthillier, Xavier, Pierre Delaunay, Mirko Bronzi, Assya Trofimov, Brennan Nichyporuk,

Justin Szeto, Naz Sepah, Edward Raff, Kanika Madan, Vikram Voleti, Samira Ebrahimi

Kahou, Vincent Michalski, Dmitriy Serdyuk, Tal Arbel, Chris Pal, Gaël Varoquaux, and Pascal Vincent. 2021. "Accounting for Variance in Machine Learning Benchmarks."

Capilla, A., P. Belin, and J. Gross. 2013. "The Early Spatio-Temporal Correlates and Task Independence of Cerebral Voice Processing Studied with MEG." *Cerebral Cortex* 23(6):1388–95. doi: 10.1093/cercor/bhs119.

Caucheteux, Charlotte, Alexandre Gramfort, and Jean-Rémi King. 2022. "Deep Language Algorithms Predict Semantic Comprehension from Brain Activity." *Scientific Reports* 12(1):16327. doi: 10.1038/s41598-022-20460-9.

Caucheteux, Charlotte, Alexandre Gramfort, and Jean-Rémi King. 2023. "Evidence of a Predictive Coding Hierarchy in the Human Brain Listening to Speech." *Nature Human Behaviour* 1–12. doi: 10.1038/s41562-022-01516-2.

Caucheteux, Charlotte, and Jean-Rémi King. 2022. "Brains and Algorithms Partially Converge in Natural Language Processing." *Communications Biology* 5(1):1–10. doi: 10.1038/s42003-022-03036-1.

Chang, Nadine, John A. Pyles, Austin Marcus, Abhinav Gupta, Michael J. Tarr, and Elissa M. Aminoff. 2019. "BOLD5000, a Public fMRI Dataset While Viewing 5000 Visual Images." *Scientific Data* 6(1):49. doi: 10.1038/s41597-019-0052-3.

Charest, I., C. Pernet, M. Latinus, F. Crabbe, and P. Belin. 2013. "Cerebral Processing of Voice Gender Studied Using a Continuous Carryover fMRI Design." *Cerebral Cortex* 23(4):958–66. doi: 10.1093/cercor/bhs090.

Charest, Ian, Cyril R. Pernet, Guillaume A. Rousselet, Ileana Quiñones, Marianne Latinus, Sarah Fillion-Bilodeau, Jean-Pierre Chartrand, and Pascal Belin. 2009. "Electrophysiological Evidence for an Early Processing of Human Voices." *BMC Neuroscience* 10(1):127. doi: 10.1186/1471-2202-10-127.

Chen, Zijiao, Jiaxin Qing, Tiange Xiang, Wan Lin Yue, and Juan Helen Zhou. 2023. "Seeing

Beyond the Brain: Conditional Diffusion Model with Sparse Masked Modeling for Vision

Decoding." Pp. 22710–20 in *2023 IEEE/CVF Conference on Computer Vision and*

Pattern Recognition (CVPR). Vancouver, BC, Canada: IEEE.

Cowen, Alan S., Marvin M. Chun, and Brice A. Kuhl. 2014. "Neural Portraits of Perception:

Reconstructing Face Images from Evoked Brain Activity." *NeuroImage* 94:12–22. doi:

10.1016/j.neuroimage.2014.03.018.

Dado, Thirza, Yağmur Güçlütürk, Luca Ambrogioni, Gabriëlle Ras, Sander Bosch, Marcel

van Gerven, and Umut Güçlü. 2022. "Hyperrealistic Neural Decoding for Reconstructing

Faces from fMRI Activations via the GAN Latent Space." *Scientific Reports* 12(1):141.

doi: 10.1038/s41598-021-03938-w.

Défossez, Alexandre, Charlotte Caucheteux, Jérémy Rapin, Ori Kabeli, and Jean-Rémi King.

2023. "Decoding Speech Perception from Non-Invasive Brain Recordings." *Nature*

Machine Intelligence 5(10):1097–1107. doi: 10.1038/s42256-023-00714-5.

Diedrichsen, Jörn, and Nikolaus Kriegeskorte. 2017. "Representational Models: A Common

Framework for Understanding Encoding, Pattern-Component, and Representational-

Similarity Analysis." *PLOS Computational Biology* 13(4):e1005508. doi:

10.1371/journal.pcbi.1005508.

Dosenbach, Nico U. F., Jonathan M. Koller, Eric A. Earl, Oscar Miranda-Dominguez, Rachel

L. Klein, Andrew N. Van, Abraham Z. Snyder, Bonnie J. Nagel, Joel T. Nigg, Annie L.

Nguyen, Victoria Wesevich, Deanna J. Greene, and Damien A. Fair. 2017. "Real-Time

Motion Analytics during Brain MRI Improve Data Quality and Reduce Costs."

NeuroImage 161:80–93. doi: 10.1016/j.neuroimage.2017.08.025.

Friston, K. J., D. E. Glaser, R. N. A. Henson, S. Kiebel, C. Phillips, and J. Ashburner. 2002.
"Classical and Bayesian Inference in Neuroimaging: Applications." *NeuroImage*
16(2):484–512. doi: 10.1006/nimg.2002.1091.

Friston, K. J., A. P. Holmes, K. J. Worsley, J. P. Poline, C. D. Frith, and R. S. J. Frackowiak.
1994. "Statistical Parametric Maps in Functional Imaging: A General Linear Approach."
Human Brain Mapping 2(4):189–210. doi: 10.1002/hbm.460020402.

Gaziv, Guy, Roman Beliy, Niv Granot, Assaf Hoogi, Francesca Strappini, Tal Golan, and
Michal Irani. 2022. "Self-Supervised Natural Image Reconstruction and Large-Scale
Semantic Classification from Brain Activity." *NeuroImage* 254:119121. doi:
10.1016/j.neuroimage.2022.119121.

Giordano, Bruno L., Michele Esposito, Giancarlo Valente, and Elia Formisano. 2023.
"Intermediate Acoustic-to-Semantic Representations Link Behavioral and Neural
Responses to Natural Sounds." *Nature Neuroscience* 1–9. doi: 10.1038/s41593-023-
01285-9.

Glover, G. H., T. Q. Li, and D. Ress. 2000. "Image-Based Method for Retrospective
Correction of Physiological Motion Effects in fMRI: RETROICOR." *Magnetic Resonance
in Medicine* 44(1):162–67. doi: 10.1002/1522-2594(200007)44:1<162::aid-
mrm23>3.0.co;2-e.

Glover, Gary H. 1999. "Deconvolution of Impulse Response in Event-Related BOLD fMRI1."
NeuroImage 9(4):416–29. doi: 10.1006/nimg.1998.0419.

Griffin, D. and Jae Lim. 1983. "Signal Estimation from Modified Short-Time Fourier
Transform." Pp. 804–7 in *ICASSP '83. IEEE International Conference on Acoustics,
Speech, and Signal Processing*. Vol. 8. Boston, MASS, USA: Institute of Electrical and
Electronics Engineers.

Güçlü, Umut, Jordy Thielen, Michael Hanke, M. A. J. van Gerven, and Marcel A. J. van

Gerven. 2016. "Brains on Beats." *In Proceedings of the International Conference on*

Neural Information Processing Systems 2101–9. doi: null.

Gutierrez, Miren. 2021. "Algorithmic Gender Bias and Audiovisual Data: A Research

Agenda." *International Journal of Communication* 15:439–61.

Han, Kuan, Haiguang Wen, Junxing Shi, Kun-Han Lu, Yizhen Zhang, Di Fu, and Zhongming

Liu. 2019. "Variational Autoencoder: An Unsupervised Model for Encoding and

Decoding fMRI Activity in Visual Cortex." *NeuroImage* 198:125–36. doi:

10.1016/j.neuroimage.2019.05.039.

Harris, Charles R., K. Jarrod Millman, Stéfan J. van der Walt, Ralf Gommers, Pauli Virtanen,

David Cournapeau, Eric Wieser, Julian Taylor, Sebastian Berg, Nathaniel J. Smith,

Robert Kern, Matti Picus, Stephan Hoyer, Marten H. van Kerkwijk, Matthew Brett, Allan

Haldane, Jaime Fernández del Río, Mark Wiebe, Pearu Peterson, Pierre Gérard-

Marchant, Kevin Sheppard, Tyler Reddy, Warren Weckesser, Hameer Abbasi,

Christoph Gohlke, and Travis E. Oliphant. 2020. "Array Programming with NumPy."

Nature 585(7825):357–62. doi: 10.1038/s41586-020-2649-2.

Higgins, Irina, Le Chang, Victoria Langston, Demis Hassabis, Christopher Summerfield,

Doris Tsao, and Matthew Botvinick. 2021. "Unsupervised Deep Learning Identifies

Semantic Disentanglement in Single Inferotemporal Face Patch Neurons." *Nature*

Communications 12(1):6456. doi: 10.1038/s41467-021-26751-5.

Horikawa, Tomoyasu, and Yukiyasu Kamitani. 2017. "Generic Decoding of Seen and

Imagined Objects Using Hierarchical Visual Features." *Nature Communications*

8(1):15037. doi: 10.1038/ncomms15037.

Howard, Andrew G., Menglong Zhu, Bo Chen, Dmitry Kalenichenko, Weijun Wang, Tobias

Weyand, Marco Andreetto, and Hartwig Adam. 2017. "MobileNets: Efficient

Convolutional Neural Networks for Mobile Vision Applications." *arXiv:1704.04861 [Cs]*.

Kasper, Lars, Steffen Bollmann, Andreea O. Diaconescu, Chloe Hutton, Jakob Heinzle,

Sandra Iglesias, Tobias U. Hauser, Miriam Sebold, Zina-Mary Manjaly, Klaas P.

Pruessmann, and Klaas E. Stephan. 2017. "The PhysIO Toolbox for Modeling

Physiological Noise in fMRI Data." *Journal of Neuroscience Methods* 276:56–72. doi:

10.1016/j.jneumeth.2016.10.019.

Kell, Alexander J. E., Daniel L. K. Yamins, Erica N. Shook, Sam V. Norman-Haignere, and

Josh H. McDermott. 2018. "A Task-Optimized Neural Network Replicates Human

Auditory Behavior, Predicts Brain Responses, and Reveals a Cortical Processing

Hierarchy." *Neuron* 98(3):630-644.e16. doi: 10.1016/j.neuron.2018.03.044.

Khaligh-Razavi, Seyed-Mahdi, and Nikolaus Kriegeskorte. 2014. "Deep Supervised, but Not

Unsupervised, Models May Explain IT Cortical Representation" edited by J.

Diedrichsen. *PLoS Computational Biology* 10(11):e1003915. doi:

10.1371/journal.pcbi.1003915.

Kingma, Diederik P., and Max Welling. 2014. "Auto-Encoding Variational Bayes."

arXiv:1312.6114 [Cs, Stat].

Kingma, Diederik P., and Max Welling. 2019. "An Introduction to Variational Autoencoders."

Foundations and Trends® in Machine Learning 12(4):307–92. doi:

10.1561/2200000056.

Kriegeskorte, Nikolaus. 2008. "Representational Similarity Analysis – Connecting the

Branches of Systems Neuroscience." *Frontiers in Systems Neuroscience*. doi:

10.3389/neuro.06.004.2008.

Kriegstein, Katharina V., and Anne-Lise Giraud. 2004. "Distinct Functional Substrates along the Right Superior Temporal Sulcus for the Processing of Voices." *NeuroImage* 22(2):948–55. doi: 10.1016/j.neuroimage.2004.02.020.

von Kriegstein, Katharina, Evelyn Eger, Andreas Kleinschmidt, and Anne Lise Giraud. 2003. "Modulation of Neural Responses to Speech by Directing Attention to Voices or Verbal Content." *Cognitive Brain Research* 17(1):48–55. doi: 10.1016/S0926-6410(03)00079-X.

Lavan, Nadine. 2023. "The Time Course of Person Perception From Voices: A Behavioral Study." *Psychological Science* 34(7):771–83. doi: 10.1177/09567976231161565.

Le, Lynn, Luca Ambrogioni, Katja Seeliger, Yağmur Güçlütürk, Marcel van Gerven, and Umut Güçlü. 2022. "Brain2Pix: Fully Convolutional Naturalistic Video Frame Reconstruction from Brain Activity." *Frontiers in Neuroscience* 16.

LeCun, Yann, Yoshua Bengio, and Geoffrey Hinton. 2015. "Deep Learning." *Nature* 521(7553):436–44. doi: 10.1038/nature14539.

Liu, Dong, Yue Li, Jianping Lin, Houqiang Li, and Feng Wu. 2020. "Deep Learning-Based Video Coding: A Review and a Case Study." *ACM Computing Surveys* 53(1):11:1-11:35. doi: 10.1145/3368405.

Maguinness, Corrina, Claudia Roswandowitz, and Katharina von Kriegstein. 2018. "Understanding the Mechanisms of Familiar Voice-Identity Recognition in the Human Brain." *Neuropsychologia* 116:179–93. doi: 10.1016/j.neuropsychologia.2018.03.039.

Maris, Eric, and Robert Oostenveld. 2007. "Nonparametric Statistical Testing of EEG- and MEG-Data." *Journal of Neuroscience Methods* 164(1):177–90. doi: 10.1016/j.jneumeth.2007.03.024.

Martin, F. N., and C. A. Champlin. 2000. "Reconsidering the Limits of Normal Hearing."

Journal of the American Academy of Audiology 11(2):64–66.

Mcallister, Jan, Anne Potts, Kathryn Mason, and Geoffrey Marchant. 1994. "Word Duration

in Monologue and Dialogue Speech." *Language and Speech* 37(4):393–405. doi:

10.1177/002383099403700404.

Millet, Juliette, Charlotte Caucheteux, Pierre Orhan, Yves Boubenec, Alexandre Gramfort,

Ewan Dunbar, Christophe Pallier, and Jean-Remi King. 2022. *Toward a Realistic Model*

of Speech Processing in the Brain with Self-Supervised Learning. arXiv:2206.01685.

arXiv. doi: 10.48550/arXiv.2206.01685.

Mozafari, Milad, Leila Reddy, and Rufin VanRullen. 2020. "Reconstructing Natural Scenes

from fMRI Patterns Using BigBiGAN." *2020 International Joint Conference on Neural*

Networks (IJCNN) 1–8. doi: 10.1109/IJCNN48605.2020.9206960.

Nagrani, Arsha, Joon Son Chung, and Andrew Zisserman. 2017. "VoxCeleb: A Large-Scale

Speaker Identification Dataset." Pp. 2616–20 in *Interspeech 2017*.

Naselaris, Thomas, Kendrick N. Kay, Shinji Nishimoto, and Jack L. Gallant. 2011. "Encoding

and Decoding in fMRI." *NeuroImage* 56(2):400–410. doi:

10.1016/j.neuroimage.2010.07.073.

Pasley, Brian N., Stephen V. David, Nima Mesgarani, Adeen Flinker, Shihab A. Shamma,

Nathan E. Crone, Robert T. Knight, and Edward F. Chang. 2012. "Reconstructing

Speech from Human Auditory Cortex." *PLOS Biology* 10(1):e1001251. doi:

10.1371/journal.pbio.1001251.

Paszke, Adam, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory

Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban

Desmaison, Andreas Köpf, Edward Yang, Zach DeVito, Martin Raison, Alykhan Tejani,

Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. 2019.

"PyTorch: An Imperative Style, High-Performance Deep Learning Library."

Pedregosa, Fabian, Gaël Varoquaux, Alexandre Gramfort, Vincent Michel, Bertrand Thirion,

Olivier Grisel, Mathieu Blondel, Andreas Müller, Joel Nothman, Gilles Louppe, Peter

Prettenhofer, Ron Weiss, Vincent Dubourg, Jake Vanderplas, Alexandre Passos, David

Cournapeau, Matthieu Brucher, Matthieu Perrot, and Édouard Duchesnay. 2018.

"Scikit-Learn: Machine Learning in Python."

Penhune, V. B., R. J. Zatorre, J. D. MacDonald, and A. C. Evans. 1996. "Interhemispheric

Anatomical Differences in Human Primary Auditory Cortex: Probabilistic Mapping and

Volume Measurement from Magnetic Resonance Scans." *Cerebral Cortex (New York,*

N.Y.: 1991) 6(5):661–72. doi: 10.1093/cercor/6.5.661.

Pernet, Cyril R., Phil McAleer, Marianne Latinus, Krzysztof J. Gorgolewski, Ian Charest,

Patricia E. G. Bestelmeyer, Rebecca H. Watson, David Fleming, Frances Crabbe,

Mitchell Valdes-Sosa, and Pascal Belin. 2015. "The Human Voice Areas: Spatial

Organization and Inter-Individual Variability in Temporal and Extra-Temporal Cortices."

NeuroImage 119:164–74. doi: 10.1016/j.neuroimage.2015.06.050.

Petkov, Christopher I., Christoph Kayser, Thomas Steudel, Kevin Whittingstall, Mark Augath,

and Nikos K. Logothetis. 2008. "A Voice Region in the Monkey Brain." *Nature*

Neuroscience 11(3):367–74. doi: 10.1038/nn2043.

Roswandowitz, Claudia, Claudia Kappes, Hellmuth Obrig, and Katharina von Kriegstein.

2018. "Obligatory and Facultative Brain Regions for Voice-Identity Recognition." *Brain*

141(1):234–47. doi: 10.1093/brain/awx313.

Rupp, Kyle, Jasmine L. Hect, Madison Remick, Avniel Ghuman, Bharath Chandrasekaran,

Lori L. Holt, and Taylor J. Abel. 2022. "Neural Responses in Human Superior Temporal

Cortex Support Coding of Voice Representations." *PLOS Biology* 20(7):e3001675. doi: 10.1371/journal.pbio.3001675.

Santoro, Roberta, Michelle Moerel, Federico De Martino, Giancarlo Valente, Kamil Ugurbil, Essa Yacoub, and Elia Formisano. 2017. "Reconstructing the Spectrotemporal Modulations of Real-Life Sounds from fMRI Response Patterns." *Proceedings of the National Academy of Sciences* 114(18):4799–4804. doi: 10.1073/pnas.1617622114.

Schrimpf, Martin, Idan Asher Blank, Greta Tuckute, Carina Kauf, Eghbal A. Hosseini, Nancy Kanwisher, Joshua B. Tenenbaum, and Evelina Fedorenko. 2021. "The Neural Architecture of Language: Integrative Modeling Converges on Predictive Processing." *Proceedings of the National Academy of Sciences* 118(45):e2105646118. doi: 10.1073/pnas.2105646118.

Schrimpf, Martin, Jonas Kubilius, Ha Hong, Najib J. Majaj, Rishi Rajalingham, Elias B. Issa, Kohitij Kar, Pouya Bashivan, Jonathan Prescott-Roy, Franziska Geiger, Kailyn Schmidt, Daniel L. K. Yamins, and James J. DiCarlo. 2018. *Brain-Score: Which Artificial Neural Network for Object Recognition Is Most Brain-Like? preprint*. Neuroscience. doi: 10.1101/407007.

Schütt, Heiko H., Alexander D. Kipnis, Jörn Diedrichsen, and Nikolaus Kriegeskorte. 2021. "Statistical Inference on Representational Geometries."

Schweinberger, S. R., A. Herholz, and W. Sommer. 1997. "Recognizing Famous Voices: Influence of Stimulus Duration and Different Types of Retrieval Cues." *Journal of Speech, Language, and Hearing Research: JSLHR* 40(2):453–63. doi: 10.1044/jslhr.4002.453.

Smith, Stephen M., Mark Jenkinson, Mark W. Woolrich, Christian F. Beckmann, Timothy E. J. Behrens, Heidi Johansen-Berg, Peter R. Bannister, Marilena De Luca, Ivana Drobnjak, David E. Flitney, Rami K. Niazy, James Saunders, John Vickers, Yongyue

Zhang, Nicola De Stefano, J. Michael Brady, and Paul M. Matthews. 2004. "Advances

in Functional and Structural MR Image Analysis and Implementation as FSL."

NeuroImage 23:S208–19. doi: 10.1016/j.neuroimage.2004.07.051.

Snoek, Lukas, Maite M. van der Miesen, Tinka Beemsterboer, Andries van der Leij,

Annemarie Eigenhuis, and H. Steven Scholte. 2021. "The Amsterdam Open MRI

Collection, a Set of Multimodal MRI Datasets for Individual Difference Analyses."

Scientific Data 8(1):85. doi: 10.1038/s41597-021-00870-6.

Trapeau, Régis, Etienne Thoret, and Pascal Belin. 2022. "The Temporal Voice Areas Are

Not 'Just' Speech Areas." *Frontiers in Neuroscience* 16:1075288. doi:

10.3389/fnins.2022.1075288.

Tuckute, Greta, Jenelle Feather, Dana Boebinger, and Josh H. McDermott. 2023. "Many but

Not All Deep Neural Network Audio Models Capture Brain Responses and Exhibit

Correspondence between Model Stages and Brain Regions." *PLOS Biology*

21(12):e3002366. doi: 10.1371/journal.pbio.3002366.

Vallat, Raphael. 2018. "Pingouin: Statistics in Python." *Journal of Open Source Software*

3(31):1026. doi: 10.21105/joss.01026.

VanRullen, Rufin, and Leila Reddy. 2019. "Reconstructing Faces from fMRI Patterns Using

Deep Generative Neural Networks." *Communications Biology* 2(1):193. doi:

10.1038/s42003-019-0438-y.

Walther, Alexander, Hamed Nili, Naveed Ejaz, Arjen Alink, Nikolaus Kriegeskorte, and Jörn

Diedrichsen. 2016. "Reliability of Dissimilarity Measures for Multi-Voxel Pattern

Analysis." *NeuroImage* 137:188–200. doi: 10.1016/j.neuroimage.2015.12.012.

Wang, Xiaosha, Yangwen Xu, Yuwei Wang, Yi Zeng, Jiacai Zhang, Zhenhua Ling, and

Yanchao Bi. 2018. "Representational Similarity Analysis Reveals Task-Dependent

Semantic Influence of the Visual Word Form Area." *Scientific Reports* 8(1):3047. doi: 10.1038/s41598-018-21062-0.

Wetzel, Sebastian J. 2017. "Unsupervised Learning of Phase Transitions: From Principal Component Analysis to Variational Autoencoders." *Physical Review E* 96(2):022140. doi: 10.1103/PhysRevE.96.022140.

Woods, Kevin J. P., Max H. Siegel, James Traer, and Josh H. McDermott. 2017. "Headphone Screening to Facilitate Web-Based Auditory Experiments." *Attention, Perception, & Psychophysics* 79(7):2064–72. doi: 10.3758/s13414-017-1361-2.

Wu, Michael C. K., Stephen V. David, and Jack L. Gallant. 2006. "COMPLETE FUNCTIONAL CHARACTERIZATION OF SENSORY NEURONS BY SYSTEM IDENTIFICATION." *Annual Review of Neuroscience* 29(1):477–505. doi: 10.1146/annurev.neuro.29.051605.113024.

Xing, Chao, Dong Wang, Chao Liu, and Yiye Lin. 2015. "Normalized Word Embedding and Orthogonal Transform for Bilingual Word Translation." Pp. 1006–11 in *Proceedings of the 2015 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*. Denver, Colorado: Association for Computational Linguistics.

Yamins, Daniel L. K., and James J. DiCarlo. 2016. "Using Goal-Driven Deep Learning Models to Understand Sensory Cortex." *Nature Neuroscience* 19(3):356–65. doi: 10.1038/nn.4244.

Zäske, Romi, Marie-Christin Perlich, and Stefan R. Schweinberger. 2016. "To Hear or Not to Hear: Voice Processing under Visual Load." *Attention, Perception, & Psychophysics* 78(5):1488–95. doi: 10.3758/s13414-016-1119-2.

Zhang, Yang, Yue Ding, Juan Huang, Wenjing Zhou, Zhipei Ling, Bo Hong, and Xiaoqin Wang. 2021. "Hierarchical Cortical Networks of 'Voice Patches' for Processing Voices

1145   in Human Brain." *Proceedings of the National Academy of Sciences*

1146   118(52):e2113887118. doi: 10.1073/pnas.2113887118.

1147

Acknowledgements

We thank Bruno Nazarian for the design of an MRI-compatible button. We thank Jean-Luc

Anton and Kepkee Loh for useful discussions. This work was funded by the European

Research Council (ERC) under the European Union's Horizon 2020 research and innovation

program (grant agreement no. 788240). This work was performed in the Center IRM-

INT@CERIMED (UMR 7289, AMU-CNRS), platform member of France Life Imaging network

(grant ANR-11-INBS-0 0 06). This work, carried out within the Institute of Convergence ILCB

(ANR-16-CONV-0002), has benefited from support from the French government (*France

2030*), managed by the French National Agency for Research (ANR) and the Excellence

Initiative of Aix-Marseille University (A*MIDEX).