Effectiveness and efficiency: label-aware hierarchical subgraph learning for protein-protein interaction (laruGL-PPI)

Yuanqing Zhou[1,2], Haitao Lin[1], Yufei Huang[1], Lirong Wu[1], Stan Z. Li[1,3]

[1]AI Lab, Research Center for Industries of the Future, Westlake University

[2]Department of Food Science and Nutrition, College of Biosystems Engineering and Food Science, Zhejiang University, Hangzhou 310058, China

[3]Correspondence: Stan.ZQ.Li@westlake.edu.cn

Abstract

Protein-Protein interactions (PPIs) are crucial in various biological processes and their study has significant implications for drug development and disease diagnosis. Existing deep learning methods for PPIs prediction, suffer from remarkable performance degradation under complex real-world scenarios due to various factors, e.g., label scarcity and domain shift. Among these factors, topological shortcut of PPIs is considerable and limits model to capture the pattern of protein-protein structure, which makes generalization terrible. In addition, huge data growth of PPIs challenges computing device. In this paper, we propose a *l*abel-*a*ware hie*r*archical s*u*b*g*raph *l*earning framework (laruGL-PPI) that can effectively infer PPIs while being both interpretable and generalizable. In laruGL-PPI, we not only model the inner-outer connection of PPIs as a hierarchical graph but explore the label dependencies by constructing a label graph. Importantly, edge-based subgraph sampling is adopted to effectively alleviate the problems as topological shortcut and high computing cost. Extensive experiments on PPI datasets of different scales with various evaluation settings demonstrate that laruGL-PPI outperforms state-of-the-art PPI prediction methods, particularly in testing of unseen proteins. In addition, our model can recognize crucial sites of proteins, such as surface sites for binding and active sites for catalysis.

Keywords: protein-protein interaction, multiple graph learning, subgraph sampling, deep learning

1   Introduction

Biological functions are accomplished by interactions and chemical reactions among biomolecules.

Among them, protein-protein interactions(PPIs) are undoubtedly one of the most essential molecular

events in the human body and are an important source of therapeutic interventions against diseases.

A comprehensive dictionary of PPIs can help connect the dots in complicated biological pathways

and expedite the development of therapeutic[1, 2]. In past decades, high-throughput experimental

methods, e.g. yeast two-hybrid screens (Y2H)[3], and mass spectrometric protein complex

identification (MS-PCI)[4] have been developed to identify PPIs. Nevertheless, genome-scale

experiments are expensive, tedious, and time-consuming while suffering from high error rates and

low coverage[5]. Therefore, it is urgent to establish an interpretable computational approaches with

high accuracy to identify potential PPIs.

More recently, a large variety of computational approaches have been developed to detect PPIs,

consisting of classic machine learning (ML)-based [6-8] and deep learning (DL)-based methods[9-

12]. Compared with classic ML methods, DL algorithm has advantage in processing complicated

and large-scale data and extracting useful features automatically, achieving a huge success in

computational biology[13], including PPI prediction[14]. Previously, DL-based methods treated

interactions as independent instances, ignoring protein connections. To improve performance of

models, recent works construct a PPIs graph with proteins as nodes and connections as edges. And

various graph neural networks (GNN) architectures[15, 16] had been utilized to explore the PPIs

graph to facilitate inference of type of interactions[12, 17, 18]. Among these graph-based methods,

the HIGH-PPI is notable because of improvement in interpretability and accuracy. However, HIGH-

PPI suffer from intensive computational cost due to hierarchical graph with protein structures and

PPI network. More importantly, emergence of topological shortcut in PPI task, which is similar to

CPI[19], causes DL-based methods difficult to learning from protein itself. This topological shortcut

stemming from the PPIs annotation imbalance prompts DL models to leverage degree information

(positive and negative annotations) in making binding prediction instead of learning binding patterns

from the intrinsic protein structures.

Protein-Protein Interaction Prediction. Early works leverage machine learning (ML) techniques

to map pairs of handcrafted sequence features of proteins to interaction patterns[6, 8, 20, 21]. With

the development of deep learning (DL), recent works have applied deep neural networks to

automatically extract features from protein sequences for enhancing feature representation[10, 11,

22]. Furthermore, the latest works utilize graph neural networks (GNN) to model PPI network[12].

Among these works, the SemiGNN-PPI[17] establish a multi-graph learning framework to improve

the model performance and the HIGH-PPI[18] organize the structure-based internal graph for each

protein to enhance interpretability of model. However, all the PPI prediction models face a

topological shortcut problem due to annotation imbalance. Also, the framework using a hierarchical

graph with protein structure exert pressure on computational devices because of huge memory cost.

Topological Shortcut. In drug-target interaction (DTI) prediction, similar to PPI, DL models learn

a map from features to interaction labels in the training data. Features refer to the chemical structures

of proteins and ligands, which determine their physical and chemical properties. In an ideal scenario,

the ML model learns the patterns characterizing the features which drive the protein-ligand

interactions, capturing the physical and chemical properties of a protein and of a ligand that

determine the interaction. Nevertheless, multiple state-of-the-art deep learning models ignore the

features and depend largely on annotations, i.e., the degree information for each protein and ligand

in the drug-target interaction (DTI) network, as a shortcut to make new binding inference. In protein-

protein interaction prediction, the topological shortcut problem also exists in the PPI network.

Multi-Label Learning. MLL addresses the problem in assigning multiple labels to a single instance.

It has been applied successfully in various domains, e.g., computer vision[23, 24]. Traditional MLL

methods typically train independent classifiers for all labels but fail to pay attention to the potential

label interdependence, leading to suboptimal performance. Recent trends in MLL incorporate deep

learning to capture the label dependencies[25, 26]. As an example, CNN-RNN[25] make use of

recurrent neural networks (RNNs) to transform the label vectors into an embedded space to learn

label correlations implicitly. More recently, graph-based MLL approaches have gotten great

attention from scientific communities[27, 28]. Especially, the SemiGNN-PPI[17] successfully

makes use of Graph Convolutional Network (GCN) by constructing a directed graph over labels to

explicitly model the protein-protein interaction dependencies adaptively. In this regard, we add

graph-based MLL to hierarchical graph learning for more accurate PPI prediction.

Subgraph Sampling. In a GCN, data to be gathered for one output node comes from its neighbors

in the previous layer. Each of these neighbors in turn, gathers its output from the previous layer, and

so on. Clearly, the deeper we back track, the more multi-hop neighbors to support the computation

of the root. The number of support nodes (and thus the training time) potentially grows exponentially

with the GCN depth. To mitigate such "neighbor explosion", state-of-the-art methods use various

layer sampling techniques[29-31]. While these methods significantly speed up training, they face

challenges in scalability, accuracy or computation complexity. Recently, the GraphSAINT[32] was

presented to efficiently train deep GCNs. Instead of building a GCN on the full training graph and

then sampling across the layers, GraphSAINT samples the training graph first and then build a full

GCN on the subgraph, which is graph sampling based. In this work, we leverage edge-based

subgraph sampling to alleviate the topological shortcut problem in PPI network and computational

cost.

In this work, to tackle the above challenges and limitations, we proposed an interpretable and

generalizable PPI prediction framework with edge-based subgraph sampling, referred to as *l*abel-

*a*ware hie*r*archical s*u*b*g*raph *l*earning framework (laruGL-PPI). Firstly, we propose

leveraging graph structure to model protein correlations and label dependencies for multi-graph

learning. In detail, we derive an inter-dependent classifier to extract information from the label graph,

which are then employed to the protein representations aggregated by neighbors in the PPI network

for multi-type PPI prediction. Secondly, we also exploit graph to depict protein structure,

represented with nodes as residues and edges as contacts between them. Thirdly, we adopt edge-

based subgraph sampling to alleviate the topological shortcut and the pressure on computational

devices. To the best of our knowledge, this is the first study to investigate emergence of topological

shortcut and to mitigate it in PPI predictive task. Precisely, the main contributions of the work can

be summarized as follows:

● For multi-type PPI prediction, we first investigate phenomenon called the topological shortcut,

which limits learning ability of model. In order to this problem, we propose an effective *l*abel-

*a*ware hie*r*archical s*u*b*g*raph *l*earning-based PPI prediction (laruGL-PPI) framework

● In laruGL-PPI, we construct multiple graphs to learn protein structure, connections between

proteins and label dependencies simultaneously. We further advance subgraph sampling to

train model for enhancing generalization ability of model and reducing computational

pressure on devices.

● Extensive experiments on three PPI datasets with different settings demonstrate that laruGL-

PPI outperforms other state-of-the-art methods for multi-label PPI prediction under various

challenging scenarios and has a high interpretability for PPI type prediction.

118 2   Materials and methods

119 2.1 Task definition

Given a set of protein $P = \{p_0, p_1, ..., p_n\}$ and a set of PPIs

$E = \{e_{ij} = \{p_i, p_j\} \mid i \neq j, p_i, p_j \in P, I(e_{ij}) \in 0,1\}$, where $I(e_{ij})$ is a binary PPI indicator

function that is 1 if the PPI between proteins p_i and p_j has been confirmed, and 0 otherwise, the

types of PPI can be represented by the label space $C = \{c_1, c_2, ..., c_t\}$ with t different types of

interactions, and the labels for a confirmed PPI e_{ij} can be represented as $y_{ij} \subseteq C$. The goal of multi-

type PPI learning is to learn a function $f : e_{ij} \rightarrow \hat{y}_{ij}$ from the training set such that for any PPI

$e_{ij} \in E_{test}^s$, $\hat{y}_{ij}$ is the set of predicted labels for e_{ij} . To confirm the emergence of topological shortcut

in PPI prediction, we analyze annotations in three common PPI datasets (i.e., SHS27k, SHS148k,
and STRING).
129

130 2.2 Network architecture design of laruGL-PPI

Figure 1 depicts the overview of our proposed laruGL-PPI framework. We first construct the multi-

graph encoding module to effectively predict PPI types, consisting of a protein graph encoding

network for capture binding patterns, a PPI network graph encoding network for modeling protein-

protein correlations, and a label graph encoding network for learning label dependences. To mitigate

topological shortcut problem and computational pressure, we make use of edge-based subgraph

sampling approach to train the laruGL-PPI model.

137
138

139
140
Figure 1: The overall framework of laruGL-PPI. First, we construct protein graph with residues as
nodes and contacts as edges. And we treat physical and chemical properties of amino acid as
features of nodes. Then, GCN blocks are employed to characterize protein graph and all the output
features of nodes are aggregated to a feature vector as feature of protein node in the PPI network
graph, which is characterized by proteins as nodes and correlations as edges. Afterwards, we use
GIN blocks to model PPI network, leading a network-aware protein features. We arrange GCN
blocks on the label graph to learn a classifier, which is applied to the products of two protein
features for the protein-protein interaction prediction. Later on, laruGL-PPI is interpreted by
GNNExplainer.

2.2.1 Multi-Graph Encoding

Protein-Graph Encoding. We denote a set of amino acid residues in a protein as

$\mathrm{p}rot = \{r_1, r_2, ..., r_n\}$. Each residue is described with t kinds of physicochemical properties. For the

bottom inside-of-protein view, a protein graph $g_b = (V_b, A_b, X_b)$ is built to model the relationship

between residues in Prot, where $V_b \subseteq prot$ is the set of nodes, A_b is an $n \times n$ adjacency matrix

representing the connectivity in g_b, and $X_b \in R^{n \times \theta}$ is a feature matrix containing the properties

of all residues. The contact map is exactly equivalent to the adjacency matrix $A_b \in \{0,1\}^{n \times n}$ in the

protein graph. Contact maps are obtained with atomic level 3D coordinates of proteins. First, we

retrieve the predictive structures from the AlphaFold Protein Structure Database. Then we represent

the location of each residue by the 3D coordinates of its C_α atom. The presence or the absence of

contact between a pair of residues is determined by their $C_\alpha - C'_\alpha$ physical distance. In this work,

we choose the cutoff distance of 12 A. For a feature matrix X_b , each row stands for a set of

properties for one amino acid residue. In this context, seven residue-level properties are considered:

isoelectric point, polarity, acidity and alkalinity, hydrogen bond acceptor, hydrogen bond donor,

octanol-water partition coefficient, and topological polar surface area. We apply variant graph neural

networks to learn protein representations. Specifically, four GCN blocks are employed. Given the

adjacency matrix $A_b \in \{0,1\}^{n \times n}$ and the feature matrix $X_b \in R^{n \times \theta}$ of an arbitrary protein graph

g_b, we update residue representations with the neighbor aggregations based on the work of Kipf

and Welling:

170
$$H^{(l+1)} = BN(\mathrm{Re}\,LU(\tilde{D}^{-1/2}(A_b + I_n)\tilde{D}^{-1/2}H^{(l)}W^{(l)}))$$

where $I_n \in R^{n \times n}$ is the identity matrix, $\tilde{D} \in R^{n \times n}$ is the diagonal degree matrix with entries

$D_{ii} = \sum_j (A_b + I_n)_{ij}$, $W^{(l)}$ is a learnable weight matrix for the GCN layer l , ReLU, BN denotes

the ReLU activation function and batch normalization, respectively. In the first GCN layer, $H^{(0)}$

$= X_b$. After four rounds of iteration, we perform the readout operation with a self-attention graph

pooling layer and average aggregation to obtain the entire graph representation.

PPI-Graph Encoding. The PPI network structure determines the adjacency matrix $A_t \in \{0,1\}^{m \times m}$,

in which the i-th row and j-th column elements is 1 if the i-th protein interacts j-th. The i-th row

of the feature matrix X_t describes the representation vector for the i-th protein graph g_b. We use

graph isomorphism network (GIN) to learn PPI network information. Formally, we are given the

PPI graph $g_t = (V_t, A_t, X_t)$, where $X_t \in R^{m \times d}$ is defined as the feature matrix whose row vector

is a representation from protein graph. In the k-th GIN layer,

$$x_v^{(k)} = \mathrm{MLP}^{(k)}((1+\varepsilon) \bullet x_v^{(k-1)} + \sum_{u \in \mathrm{N}(v)} x_u^{(k-1)})$$

where $x_v^{(k)}$ denotes the representation of protein v after the k-th GIN layer, $\mathrm{N}(v)$ is a set of proteins

adjacent to v, and ε is a learnable parameter. After two GIN layers, we feed $x_v^{(2)}$ in a linear layer with

the ReLU activation to obtain final protein representation. For an arbitrary query pair containing the

i-th and j-th proteins, we adopt element-wise product to combine protein pair information. Then

the generated vector goes through a fully connected layer (FC) to come by protein-protein

representation.

Label-Graph Encoding. In multi-label PPI prediction, correlations exist among different types of

interactions, i.e., some PPI types may appear together frequently while others rarely appear together.

Following Chen et al, we model the interdependencies between different PPI types(labels) using a

graph and make model learn an inter-dependent classifier with the GCN, which is directly applied

to protein-protein representation for multi-type PPI prediction. The GCN aims to learn a function

$f(\cdot, \cdot)$ on the graph with t nodes. With the convolutional operation, $f(\cdot, \cdot)$ can be expressed

as:

$$C = \mathrm{BN}(\mathrm{ReLU}(\tilde{D}^{-1/2}(A_c + I_n)\tilde{D}^{-1/2} X_c W_c))$$

where $I_n \in R^{n \times n}$ is the identity matrix, $\tilde{D} \in R^{n \times n}$ is the diagonal degree matrix with entries

$D_{ii} = \sum_j (A_c + I_n)_{ij}$, $A_c \in R^{t \times t}$ and $X_c \in R^{t \times d_c}$ denotes adjacency and feature matrix in label

graph individually, W_c is a learnable weight matrix for the GCN, ReLU, BN denotes the ReLU

activation function and batch normalization, respectively. Considering that PPI type names are

semantic, we utilize the BioWordVec model pre-trained on the biomedical corpus for generating

word embedding X_c to better capture their semantics. To construct the label correlation matrix, we

compute the conditional probability of different labels within the dataset. To avoid noises, we

binarize the correlation matrix with a threshold τ to obtain A_c.

2.2.2   Multi-Graph Learning with Subgraph Sampling

206   By applying the learned classifier W from label graph encoding(LGE) to the learned

207   representations from hierarchical graph encoding (HGE) for PPI e_{ij}, we can obtain the predicted

208   scores $\hat{y}_{ij} = W(h_{p_i} \cdot h_{p_j})$. We use the traditional multi-label classification loss function to update

209   the whole network in an end-to-end manner. The loss function can be written as:

$$L = \sum_{c=1}^{t} (y^c \log(\sigma(\hat{y}^c)) + (1 - y^c) \log(1 - \sigma(\hat{y}^c)))$$

where $\sigma(\cdot)$ is the sigmoid function. Our model learns the aggregated features by combining

protein neighbors and models the label correlations by learning inter-dependent classifiers

simultaneously to improve the model generalization. With multi-graph learning, the learned

classifiers are expected to be neighborhood-aware at both feature and label levels. We select edge-

based sampler to build subgraph G_s due to the nature of protein-protein interaction. In detail, Given

training PPI-network graph G and edge budget m. Firstly, sampling probability $P((u, v))$ is

calculated by the following formula:

$$P((u,v)) := \left(\frac{1}{\deg(u)} + \frac{1}{\deg(v)} \right) \bigg/ \sum_{(u',v') \in \varepsilon} \left(\frac{1}{\deg(u')} + \frac{1}{\deg(v')} \right),$$

219   where $\deg(\cdot)$, ε are referred to as the degree of a protein node and a set of all edges in training

220   graph. Secondly, m edges are randomly sampled from ε according to P and sets of nodes that are

221   end-points of edges in ε_s are determined as V_s. Finally, subgraph G_s is derived from V_s with node

222   inducing.

224   2.2.3   Residue importance computation

We employ the method called GNNExplainer[33] to generate explanations for laruGL-PPI. By

taking the well-trained GNN model and its predictions as inputs, GNNExplainer returns the most

important subgraph by maximizing the mutual information MI between the model prediction and

possible subgraphs. Given protein graphs G_1 and G_2 that connect in the PPI network, our goal is to

identify a subgraph $G_s \subseteq G_1$ that is important for our model's prediction $\hat{y}$. The mutual information

MI is formulated as:

231
$$MI(Y, G_s) = H(Y) - H(Y \mid G = G_s)$$

232   MI_s represents importance of G_s, Y is a variable indicating the probability of PPI presence of G_1

233   and G_2, and $H(\bullet)$ is the entropy term. In effect, MI quantifies the change in the probability of

234   prediction $\hat{y} = \Phi(G_1, G_2)$ when computation graph is limited to explanation subgraph G_s. A

235   computationally efficient version of GNNExplainer's objective, which we optimize using Adam, is

236   as follow:

237
$$\min_{M} - \sum_{c=1}^{C} \mathbb{1}[y = c] \log P_{\Phi}(Y = y \mid G = A \odot \sigma(M))$$

238   Lastly, we compute the element-wise multiplication of $\sigma(M)$ and adjacency matrix A and set a

239   threshold to arrive at the explanation G_s for our model's prediction $\hat{y}$ at protein graph G_1.

240   2.2.4 Datasets and metrics

241   We perform extensive analyses and experiments on three benchmark datasets, i.e., SHS27k,

SHS148k, and STRING. Both SHS27k and SHS148k are subsets of the STRING datasets. These

are multi-label PPI data of Homo sapiens from the STRING database. We retrieve protein structures

from AlphaFold Protein Structure Database. In this work, SHS27k has 1553 proteins and 6660

protein-protein multi-type labels. SHS148k consists of 4072 proteins and 30067 labels. The PPIs

are annotated with 7 types, i.e., Activation, Binding, Catalysis, Expression, Inhibition, Post-

translational modification (Ptmod), and Reaction. Each PPI is labeled with at least one of them. The

micro-F1 score was applied to evaluate and compare the predictive performance of laruGL-PPI and

existing methods. We also use area under the precision-recall curve (AUPR) to estimate model with

regard to specific interaction type.

3   Results and discussion

3.1 Topological Shortcut Analysis.

In context of the PPI predictive task, ML models learn a map from features to labels as annotations

and then make inference for the likelihood of each node (protein) to bind to other nodes. Annotations

capture protein-protein interactions. Normally, known protein-protein interaction is denoted as 1,

while the unknown interaction is labeled as 0. Features refer to the chemical structures of proteins,

which determine their physical and chemical properties, and are expressed as amino acid sequences

or 3D structures for proteins. With success of network inference in various fields, many ML models

have considered PPI network and regard it as one of features externally. In an ideal scenario, the

ML model learns the patterns characterizing the features which drive the protein-protein interactions,

capturing the physical and chemical properties of protein pairs that determine the mutual binding

action. However, as we show next, multiple state-of-the-art deep learning models, such as HIGH-

PPI rely largely on the degree information for each protein in the protein-protein interaction network,

as a shortcut to make new binding predictions. We begin by noticing that the number of annotations

linked to a protein follows a fat-tailed distribution, indicating that the vast majority of proteins have

only a small number of annotations, which then coexist with a few hubs, nodes with an exceptionally

large number of binding records.

Distributions of the number of annotations in the SHS27k and SHS148k are shown in **Figure 2.** As an example, the number of annotations for proteins follows a power law distribution with

degree exponent $\gamma = 1.46$, maximum degree $k_{max} = 182$, minimum degree $k_{min} = 1$ on SHS27k

dataset. For the degree exponent, the second moment of the distribution diverges, implying that the

expected uncertainty in the binding information is highly significant, limiting our ability to predict

the binding between proteins in terms of intrinsic protein characteristics. Furthermore, it is found

that the number of annotation k and the average interaction per k, calculated as the average across

all links stemming from nodes of degree k, are associated with each other. In this work, there are

seven interaction types between proteins, consisting of reaction, binding, posttranslational

modification, activation, inhibition, catalysis and expression. For catalysis, they are positively

correlated with $r_{Spearman} = 0.37$ ($p < 0.01$), indicating stronger catalysis propensity for proteins

with more annotations. Whereas, they are negatively correlated with $r_{Spearman} = -0.34$ ($p < 0.01$)

for expression, implying stronger expression tendency for proteins with less annotations (Table 1).

As the annotations follow fat-tailed distributions, the observed correlation drives the hub proteins

to have disproportionately more interaction or non-interaction on average, whereas proteins with

fewer annotations have both interaction and non-interaction examples. This annotation imbalance

prompts the ML models to leverage degree information (positive and negative annotations) in

making interaction prediction instead of learning interaction patterns from the protein intrinsic

structures.

To investigate the emergence of topological shortcuts, for each node i with number of

annotations k_i, we quantify the balance of the available data information via the degree ratio,

$\rho_i = \dfrac{k_i^+}{k_i^+ + k_i^-} = \dfrac{k_i^+}{k_i}$, where, k_i^+ is the positive degree, corresponding to the number of known

binding annotations in the training data, and k_i^- is the negative degree, or the number of unknown

annotations in the training data. As most proteins lack either binding or unknown annotations for

interaction types (Table 1), the resulting p_i are close to 1 or 0 (See Figure 3), which represent the

annotation imbalance in the prediction problem. As many state-of-the-art deep learning models,

such as HIGH-PPI, uniformly sample the available positive and negative annotations, they tend to

assign higher binding probability to proteins with higher ρ. Consequently, their binding predictions

are driven by topological shortcuts in the protein-protein network, which are associated with the

positive and negative annotations present in the dataset rather than the structural features

characterizing proteins.

Figure 2 Distributions of the number of annotations in the SHS27k (a) and SHS148k (b)

Class	Has only positive labels	Has only negative labels	Has both labels	correlation
Reaction	275	737	541	0.06
	541	1903	1628	-0.09
Binding	502	370	681	-0.12
	1186	895	1991	-0.14
Ptmod	24	1216	313	0.10
	84	2854	1134	0.22
Activation	232	672	649	0.12
	455	1667	1950	0.12
Inhibition	48	1150	355	0.16
	72	2863	1137	0.10
Catalysis	206	781	566	0.37
	372	2044	1656	0.23
Expression	82	1151	320	-0.34
	189	2905	978	-0.45

Table 1 Statics of SHS27K and SHS148K. Most proteins in common datasets have either positive

or negative labels, which creates imbalance in the degree ratio.

Figure 3 The distribution of degree ratios for the proteins in SHS27K and SHS148K.

3.2 Comparison with competitive methods

In this section, we display the performances achieved by our laruGL-PPI and competitive baselines

on SHS27k and SHS148k datasets. Here, we ran each model five times independently to eliminate

bias caused by randomness and examine the robustness of laruGL-PPI. In table 2, we compare our

methods with other baseline methods under different partition schemes and various datasets. It is

observed that graph-based methods, i.e., GNN-PPI, SemiGNN-PPI, and HIGH-PPI exceed other

ML and DL models, even under more difficult BFS and DFS partitions with more unseen proteins.

It can be ascribed to graph learning, which can model correlations between proteins despite the

existence of more unknown proteins. Furthermore, our proposed method, which incorporates

multiple graph learning in conjunction with subgraph sampling, achieves competitive performance

in multi-type PPI prediction in common transductive setting. It is worth mentioning that our method

reaches state-of-the-art level in difficult data partition, i.e., DFS and BFS. In realistic application of

biology, models tend not to have seen predicted protein pairs in training process. In order to conform

with the reality, it is the first time to consider inductive setting in multi-type PPI prediction.

Apparently, when facing unseen protein, model cannot utilize degree information to conduct

prediction, leading to decreasing accuracy. The inductive setting requires models to more focus

protein structures instead of degree information. By subgraph sampling, our model improves

predictive performance and outperform state-of-the-art HIGH-PPI under the more difficult inductive

setting with SHS27k, regardless of partition mode (Table 2).

3.3 Performance on specific PPI types

327   For each of the six PPI types, we offer a separate performance analysis in terms of AUPR. It can be

328   found that our presented model with lower learning cost parallels with HIGH-PPI as shown in Figure

329   4. Notably, laruGL-PPI consistently beats previous state-of-the-art model in the most challenging

330   setting (i.e. inductive setting with BFS). This is reasonable as laruGL-PPI learns spatial-biological

patterns as possible as it can by sampling subgraph in multiple graph framework. When facing

unknown protein pairs, it is able to exploit these patterns to predict better than other.

Model	SHS27K			SHS148K		
	Random	DFS	BFS	Random	DFS	BFS
RF	0.7845	0.3555	0.3767	0.8210	0.4326	0.3896
	(0.0088)	(0.0222)	(0.0157)	(0.0020)	(0.0343)	(0.0194)
LR	0.7155	0.4851	0.4306	0.6700	0.5109	0.4745
	(0.0093)	(0.0187)	(0.0505)	(0.0007)	(0.0209)	(0.0142)
DPPI	0.7399	0.4612	0.4143	0.7748	0.5203	0.5212
	(0.0504)	(0.0302)	(0.0056)	(0.0139)	(0.0118)	(0.0870)
DNN-PPI	0.7789	0.5434	0.4890	0.8849	0.5842	0.5740
	(0.0497)	(0.0130)	(0.0724)	(0.0048)	(0.0205)	(0.0910)
PIPR	0.8331	0.5780	0.4448	0.9005	0.6398	0.6183
	(0.0075)	(0.0324)	(0.0444)	(0.0259)	(0.0076)	(0.1023)
GNN-PPI	0.8791	0.7472	0.6381	0.9226	0.8267	0.7137
	(0.0039)	(0.0526)	(0.0179)	(0.0010)	(0.0085)	(0.0533)
HIGH-PPI	0.8797	0.7884	0.6749	0.8909	0.7567	0.6798
	(0.0089)	(0.0052)	(0.0211)	(0.0245)	(0.0103)	(0.0397)
SemiGNN-PPI	0.8951	0.7832	0.7215	0.9240	0.8545	0.7178
	(0.0046)	(0.0315)	(0.0287)	(0.0022)	(0.0117)	(0.0356)
laruGL-PPI	0.8762	0.7972	0.7407	0.9069	0.8061	0.7307
	(0.0053)	(0.0160)	(0.0672)	(0.0039)	(0.0096)	(0.0259)
HIGH-PPI*	0.8480	0.7351	0.6665	0.8572	0.7127	0.6674
	(0.0067)	(0.0080)	(0.0452)	(0.0211)	(0.0277)	(0.0416)
laruGL-PPI*	0.8635	0.7657	0.7097	0.9013	0.7852	0.7311
	(0.0048)	(0.0371)	(0.0394)	(0.0035)	(0.0110)	(0.0374)

Table 2 Prediction accuracy of laruGL-PPI and other competing methods. The accuracy is

represented with micro-F1 score (mean±std). The optimal value in settings has been emphasized in

bold. The symbol * stands for inductive setting and the model without * means transductive.

Figure 4 Performance of laruGL-PPI in predicting specific PPIs on SHS27k, compared with HIGH-PPI. Blue and purple represents HIGH-PPI and laruGL-PPI, respectively. Error bars express standard deviation of the mean. Source data are provided as a Source Data file.

3.4 The results of training with various subgraph size

In this section, we display the results of comparison of HIGH-PPI and our laruGL-PPI with various subgraph size. Beginning by subgraph size of 200, we observe that our model has attained competing effectiveness in SHS27k under the transductive setting. From results of effect of subgraph size, using subgraph sampling is capable of reducing the memory cost of Graphics Processing Unit (GPU) significantly and having a comparable outcome at the same time (Table S1). It is indicated that taking size of 300, 400 or 500 can reach a greater performance and request a relatively smaller memory cost in SHS27k dataset (Figure 5).

Figure 5 F1-score and Memory cost of HIGH-PPI and laruGL-PPI with various size subgraphs under inductive setting (BFS) on SHS27k(left) and SHS148k(right).

3.5 Ablation study

We investigate the effectiveness of different components in laruGL-PPI in Table 3. It can be seen that model improves a lot (from 0.6749 to 0.7238) under relatively difficult circumstance (i.e. transductive setting with BFS) when considering adjacent residues in sequence. This implies that sequence information plays an important role on determining PPI types. What's more, label graph encoding brings plenty profits in a majority of scenarios, particularly under the most arduous condition (i.e. inductive setting with BFS, from 0.6652 to 0.7072). Finally, our model is getting more powerful when adopting edge-based sampling strategy on PPI graph. In particular, under transductive setting, performance in terms of DFS achieves 0.7972. While under inductive setting, more challenging scene, laruGL-PPI reaches the best F1-score in the light of all the partitions.

Model	Transductive setting			Inductive setting		
	Random	DFS	BFS	Random	DFS	BFS
HGL-origin	0.8797	0.7884	0.6749	0.8480	0.7351	0.6665
	(0.0089)	(0.0052)	(0.0211)	(0.0067)	(0.0080)	(0.0452)
HGL	0.8873	0.7743	0.7238	0.8369	0.7400	0.6652
	(0.0059)	(0.0149)	(0.0383)	(0.0058)	(0.0165)	(0.0797)
laHGL	0.8894	0.7819	0.7545	0.8405	0.7350	0.7072
	(0.0073)	(0.0226)	(0.0399)	(0.0040)	(0.0470)	(0.0543)
laruGL	0.8762	0.7972	0.7407	0.8635	0.7657	0.7097
	(0.0053)	(0.0160)	(0.0672)	(0.0048)	(0.0371)	(0.0394)

Table 3 Results of ablation studies on different components of laruGL-PPI using the SHS27k dataset.

3.6 Interpretability of our laruGL-PPI

3.6.1 Analysis of feature importance in residue-level （inductive random）

The feature importance in residue-level for overall (left-most column) and type-specific (right six

columns) PPI prediction calculated as the average z-score resulting from dropping each individual

feature dimension from our model and calculating changes of AUPR before and after.

For node features in protein graphs, we select seven important features in terms of laruGL-PPI.

Here, we list the selected seven residue-level physicochemical properties in Figure 5 and discuss

their importance for different types of PPIs to both better interpret our model and discover

enlightening biomarkers for PPI interface. The average z-score, which results from deleting each

feature dimension and analyzing changes in metrics before and after, is calculated to determine the

importance of a feature. From the results, laruGL-PPI regards topological polar surface area (TPSA)

and octanol-water partition coefficient (KOW) as dominant features in multiple types of PPIs. This

finding supports the conventional wisdom that TPSA and KOW play a key role in drug transport

process[34], protein interface recognition[35, 36], and PPI prediction[37].

Figure 5 The feature importance in residue-level for overall (left-most column, F1-score) and

type-specific (right seven columns, AUPR) PPI prediction.

3.6.2 laruGL-PPI identifies key residues constituting functional sites

Typically, functional sites are spatially clustered sets of residues. They control protein functions and

are thus important for PPI prediction. As our proposed model has the capacity to capture spatial-

biological arrangements of residues in the protein graph learning, this characteristic can be used to

explain the model's decision. It is meaningful to notice that laruGL-PPI can automatically learn the

residue importance without any residue-level annotations. In this section, we provide a case study

of predicting important residues for the binding surface and two cases of estimating key residues for

catalytic function.

First, a binding example between the query protein (PDB id: 2B6H) and its partner (PDB id:

2REY) is investigated, whose complex structure is generated by ZDOCK[38]. Subsequently, we

apply the GNN explanation approach on the laruGL-PPI model. As can be seen from Figure 6a.

LaruGL-PPI can accurately and automatically identify the residues belong to the binding domain.

Second, in order to evaluate the prediction of crucial sites of catalysis for PPIs, we utilize the

same GNN explanation approach in our model. The ground truth key sites, normally including

binding sites and active sites, are retrieved from the Universal Protein Knowledgebase (UniProt)[39].

We explore the prominent residues of catalytic function for query proteins (UniProt id: P62714,

Q9UMX6). As seen in Figure 6b, our proposed laruGL-PPI infers that ASN117 is important for

catalysis of P62714 known as catalytic subunit of protein phosphatase 2A, in terms of Q9Y4X3.

The coordinate bond between ASN117 and Mn^{2+} activates the enzyme to play a highly efficient

catalytic role. For Guanylyl cyclase-activating protein 2 (Q9UMX6), model can correctly predict

that Asp66 and Asp102 are key to perform catalysis on Q16270.

Protein functional site prediction sheds light on the model decisions and how to conduct

additional wet experiments for PPI investigation. Excellent model interpretability also demonstrates

that our approach can accurately describe biological evidence for proteins.

448   a

Figure 6 Automatic explanation for key residue without supervision. **a** Top: Depiction of a complex

protein (left, query protein, PDB id: 2B6H; right, interacted protein, PDB id: 2REY) modeled in

surface representation. Bottom: important residues of the query protein learned from laruGL-PPI

with pink. **b** Depiction of two proteins (top, UniProt id: P62714; bottom, UniProt id: Q9UMX6)

modeled in cartoon representations. Residues inferred by model, which are colored with brown, are

important for catalysis.

4. Conclusions

In this study, it was found that conventional machine learning is subject to the problem of topological

shortcuts. A new framework based on subgraph sampling was proposed to address this issue,

enabling the model to focus more on the protein structure itself. This framework improved

prediction accuracy and generalization, especially in challenging settings, where it exhibited

significant improvements in encountering new proteins. Additionally, subgraph sampling saved

computational resources. Through interpretable analysis of the model, it was found that the model

can identify key sites, binding surfaces, or active sites. This may also be attributed to the subgraph

sampling algorithm. Nevertheless, there is still room for improvement. For instance, the model does

not explicitly consider protein sequence information, and future research may consider sequence-

structure co-modeling. Another potential direction is to extend the model to protein all-atom graphs,

extracting more microscopic information about proteins and learning the essence of PPI, thereby

further enhancing the model's generalization ability and interpretability.

Data and code availability

The preprocessed data and model code associated with the study are available at

https://github.com/xxx.

Acknowledge

The research work was supported by xxx.

References

[1] Skrabanek L, Saini HK, Bader GD, Enright AJ. Computational prediction of protein-protein interactions. Molecular Biotechnology. 2008;38:1-17.

[2] Tavernier, Jan, Lievens, Sam, De, Bosscher, et al. Modulation of Protein-Protein Interactions for the Development of Novel Therapeutics. 2016;24:707-18.

[3] Fields S, Song OK. A NOVEL GENETIC SYSTEM TO DETECT PROTEIN PROTEIN INTERACTIONS. Nature. 1989;340:245-6.

[4] Ho Y, Gruhler A, Heilbut A, Bader GD, Moore L, Adams SL, et al. Systematic identification of protein complexes in Saccharomyces cerevisiae by mass spectrometry. 2002;415:180-3.

[5] Luo X, You ZH, Zhou MC, Li S, Leung H, Xia YN, et al. A Highly Efficient Approach to Protein Interactome Mapping Based on Collaborative Filtering Framework. Scientific Reports. 2015;5.

[6] Browne F, Wang H, Zheng H, Azuaje F. Supervised statistical and machine learning approaches to inferring pairwise and module-based protein interaction networks. 7th IEEE International Conference on Bioinformatics and Bioengineering. Boston, MA2007. p. 1365-9.

[7] Xiaotong, Lin, Xue-wen, Proteomics CJ. Heterogeneous data integration by tree-augmented naïve Bayes for protein-protein interactions prediction. 2012.

[8] Wong L, You ZH, Li S, Huang YA, Liu G. Detection of Protein-Protein Interactions from Amino Acid Sequences Using a Rotation Forest Model with a Novel PR-LPQ Descriptor. 11th International Conference on Intelligent Computing (ICIC). Fuzhou, PEOPLES R CHINA2015. p. 713-20.

[9] Sun TL, Zhou B, Lai LH, Pei JF. Sequence-based prediction of protein protein interaction using a deep-learning algorithm. Bmc Bioinformatics. 2017;18.

[10] Hashemifar S, Neyshabur B, Khan AA, Xu JB. Predicting protein-protein interactions through sequence-based deep learning. Bioinformatics. 2018;34:802-10.

[11] Chen MH, Ju CJT, Zhou GY, Chen XL, Zhang TR, Chang KW, et al. Multifaceted protein-protein interaction prediction based on Siamese residual RCNN. Bioinformatics. 2019;35:I305-I14.

[12] Lv G, Hu Z, Bi Y, Zhang S. Learning Unknown from Correlations: Graph Neural Network for Inter-novel-protein Interaction Prediction. 2021.

[13] Min S, Lee B, Yoon S. Deep learning in bioinformatics. Briefings in Bioinformatics. 2017;18:851-69.

[14] Soleymani F, Paquet E, Viktor H, Michalowski W, Spinello D. Protein-protein interaction prediction with deep learning: A comprehensive review. Computational and Structural Biotechnology Journal. 2022;20:5316-41.

[15] Kipf TN, Welling M. Semi-Supervised Classification with Graph Convolutional Networks. 2016.

[16] Xu K, Hu W, Leskovec J, Jegelka S. How Powerful are Graph Neural Networks? 2018.

[17] Zhao Z, Qian, P., Yang, X., Zeng, Z., Guan, C., Tam, W. L., & Li, X. SemiGNN-PPI: Self-Ensembling Multi-Graph Neural Network for Efficient and Generalizable Protein-Protein Interaction Prediction. IJCAI. 2023.

[18] Gao Z, Jiang C, Zhang J, Jiang X, Li L, Zhao P, et al. Hierarchical graph learning for protein–protein interaction. Nature Communications. 2023;14:1093.

[19] Chatterjee A, Walters R, Shafi Z, Ahmed OS, Sebek M, Gysi D, et al. Improving the generalizability of protein-ligand binding predictions with AI-Bind. Nature Communications. 2023;14:1989.

[20] Chen XW, Liu M. Prediction of protein-protein interactions using random decision forest framework. Bioinformatics. 2005;21:4394-400.

[21] Guo YZ, Yu LZ, Wen ZN, Li ML. Using support vector machine combined with auto covariance to predict proteinprotein interactions from protein sequences. Nucleic Acids Research. 2008;36:3025-30.

[22] Du XQ, Sun SW, Hu CL, Yao Y, Yan YT, Zhang YP. DeepPPI: Boosting Prediction of Protein-Protein Interactions with Deep Neural Networks. Journal of Chemical Information and Modeling. 2017;57:1499-510.

[23] Liu WW, Wang HB, Shen XB, Tsang IW. The Emerging Trends of Multi-Label Learning. Ieee Transactions on Pattern Analysis and Machine Intelligence. 2022;44:7955-74.

[24] Kaixin X, Liyang L, Ziyuan Z, Zeng Z, Veeravalli BJae-p. Object-Aware Self-supervised Multi-Label Learning. 2022.

[25] Wang J, Yang Y, Mao J, Huang Z, Huang C, Xu WJae-p. CNN-RNN: A Unified Framework for Multi-label Image Classification. 2016.

[26] Guo C, Mousavi A, Wu X, Holtmann-Rice DN, Kale S, Reddi SJ, et al. Breaking the Glass Ceiling for Embedding-Based Classifiers for Large Output Spaces. Neural Information Processing Systems2019.

[27] Chen ZM, Wei XS, Wang P, Guo Y. Multi-Label Image Recognition With Graph Convolutional Networks. 2019 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)2019.

[28] Wang Y, He D, Li F, Long X, Zhou Z, Ma J, et al. Multi-Label Classification with Label Graph Superimposing. 2019.

[29] Chen J, Ma T, Xiao CJae-p. FastGCN: Fast Learning with Graph Convolutional Networks via Importance Sampling. 2018.

[30] Hamilton WL, Ying R, Leskovec J. Inductive Representation Learning on Large Graphs. 2017.

[31] Huang W, Zhang T, Rong Y, Huang J. Adaptive Sampling Towards Fast Graph Representation Learning. 2018.

[32] Zeng H, Zhou H, Srivastava A, Kannan R, Prasanna V. GraphSAINT: Graph Sampling Based Inductive Learning Method. 2019.

[33] Ying R, Bourgeois D, You J, Zitnik M, Leskovec JJAinips. GNNExplainer: Generating Explanations for Graph Neural Networks. 2019;32:9240-51.

[34] Fernandes J, Gattass CR. Topological Polar Surface Area Defines Substrate Transport by Multidrug Resistance Associated Protein 1 (MRP1/ABCC1). Journal of Medicinal Chemistry. 2009;52:1214-8.

[35] Hu Z, Ma B, Wolfson H, Nussinov R. Conservation of polar residues as hot spots at protein interfaces.

2000;39:331-42.

[36] L., Young, R. L, Jernigan, D. G, Science CJP. A role for surface hydrophobicity in protein-protein

recognition. 1994.

[37] Alex, P., Korn, Dr., Roger, M., et al. Distribution and complementarity of hydropathy in mutisunit

proteins. 1991;9:37-55.

[38] Pierce BG, Wiehe K, Hwang H, Kim BH, Vreven T, Weng Z. ZDOCK server: interactive docking

prediction of protein-protein complexes and symmetric multimers. Bioinformatics. 2014;30:1771-3.

[39] Consortium TU. UniProt: the Universal Protein Knowledgebase in 2023. Nucleic Acids Research.

2022;51:D523-D31.