Effectiveness and efficiency: label-aware hierarchical subgraph learning for protein-protein interaction

Yuanqing Zhou[1,2], Haitao Lin[2], Yufei Huang[2], Lirong Wu[2], Stan Z. Li[2]* and Wei Chen[1]*

[1]Department of Food Science and Nutrition, College of Biosystems Engineering and Food Science, Zhejiang University, Hangzhou 310058, China.

[2]AI Lab, Research Center for Industries of the Future, Westlake University, Hangzhou 310024, China.

*Corresponding authors：

Prof. Wei Chen, Department of Food Science and Nutrition, College of Biosystems Engineering and Food Science, Zhejiang University, Hangzhou, 310058 China.

E-mail: zjuchenwei@zju.edu.cn

………………………………………………

Prof. Stan Z. Li, School of Engineering, Westlake University, Hangzhou, 310024 China.

E-mail: Stan.ZQ.Li@westlake.edu.cn

Abstract

Protein-protein interactions (PPIs) are crucial in various biological processes and their study has

significant implications for drug development and disease diagnosis. Existing deep learning

methods for PPIs prediction, including graph neural networks (GNNs), have been widely

employed as the solutions, while they usually suffer from performance degradation under complex

real-world scenarios. We claim that the topological shortcut is one of the key problems

contributing negatively to the performance, according to our analysis. By modeling the PPIs as a

graph with protein as nodes and interactions as edge types, the prevailing models tend to learn the

pattern of nodes' degrees rather than intrinsic sequence-structure profiles, leading to the problem

termed topological shortcut. In addition, with the emergence of high-throughput experimental

methods such as mass spectrometry and protein chip technology, the amount of available PPI data

is exploding. The huge data growth leads to intensive computational costs and challenges

computing devices, causing infeasibility in practice. To address the discussed problems, we

propose a **l**abel-**a**ware hie**r**archical s**u**bg**r**aph **l**earning method (laruGL-PPI) that can effectively

infer PPIs while being both interpretable and generalizable. Specifically, we introduced

edge-based subgraph sampling to effectively alleviate the problems of topological shortcuts and

high computing costs. Besides, the inner-outer connections of PPIs are modeled as a hierarchical

graph, together with the dependencies between interaction types constructed by a label graph.

Extensive experiments on PPI datasets of different scales demonstrate that laruGL-PPI

outperforms state-of-the-art PPI prediction methods, particularly in the testing of unseen proteins.

Also, our model can recognize crucial sites of proteins, such as surface sites for binding and active

sites for catalysis.

Keywords: Protein-protein interaction, Multiple graph learning, Subgraph sampling, Deep learning

1   Introduction

Biological functions are accomplished by interactions and chemical reactions among biomolecules. Among them, protein-protein interactions (PPIs) are undoubtedly one of the most essential molecular events in the human body and are an important source of therapeutic interventions against diseases. A comprehensive dictionary of PPIs can help connect the dots in complicated biological pathways and expedite the development of therapeutic[1, 2]. In past decades, high-throughput experimental methods, e.g. yeast two-hybrid screens (Y2H)[3], and mass spectrometric protein complex identification (MS-PCI)[4] have been developed to identify PPIs. Nevertheless, genome-scale experiments are expensive, tedious, and time-consuming while suffering from high error rates and low coverage[5]. Therefore, it is urgent to establish computational approaches with high accuracy and speed to identify potential PPIs.

Recently, a large variety of computational approaches have been developed to detect PPIs, consisting of classic machine learning (ML)-based [6-8] and deep learning (DL)-based methods[9-12]. Compared with classic ML methods, the DL algorithm has an advantage in processing complicated and large-scale data and extracting useful features automatically, achieving huge success in computational biology[13], including PPI prediction[14]. With the development in graph neural networks (GNNs), more recent works focus on modeling the PPIs as a graph, by constructing a PPIs graph with proteins as nodes and interactions as edge types, with various GNNs [15, 16] utilized to explore the PPIs graph to facilitate inference of type of

interactions[12, 17, 18]. Among these graph-based methods, the HIGH-PPI reaches state-of-the-art

performance with interpretability. However, HIGH-PPI suffers from intensive computational costs

due to hierarchical graphs with protein structures and PPI networks.

More importantly, we find out that topological shortcut (TS)[19] exists in multiple types PPI

prediction. The emergence of TS causes DL-based methods difficult to learn from protein. The TS

refers to the fact that, in the PPI network, the model easily learns simple topological patterns

during the training process, without fully exploiting the 1D protein sequences, 3D structures, and

physicochemical properties profiles closely related to PPI. As a result, in the inference process, the

model makes use of known topological knowledge to predict PPI, while seldom considering the

characteristics of the protein itself. This makes the model collapse when faced with 'unseen'

proteins. Experimental results demonstrate the unsatisfactory performance in inductive and BFS

scenarios for the previous models (See section 4).

In this work, to tackle the above problems, we proposed an interpretable and generalizable PPI

prediction framework with edge-based subgraph sampling, referred to as **l**abel-**a**ware hie**r**archical

s**u**b**g**raph **l**earning framework (laruGL-PPI). Firstly, we propose leveraging graph structure to

model protein relations and label dependencies for multi-graph learning. In detail, we derive an

inter-dependent classifier to extract information from the label graph, which is then employed to

the protein representations aggregated by neighbors in the PPI network for multi-type PPI

prediction. Secondly, we also exploit graphs to depict protein structure, represented with nodes as

residues and edges as contacts between them. Thirdly, we adopt edge-based subgraph sampling to

alleviate the topological shortcut and the computational cost. To the best of our knowledge, this is

the first study to investigate the emergence of topological shortcut and to mitigate it in PPI

predictive tasks. Precisely, the main contributions of the work can be summarized as follows:

● For multi-type PPI prediction, we first investigate topological shortcut, which limits

learning ability of model. An effective **l**abel-**a**ware hie**r**archical s**u**b**g**raph **l**earning-based

PPI prediction (laruGL-PPI) framework was proposed to address this problem.

● In laruGL-PPI, Multiple graphs were constructed to model protein structure, connections

between proteins and label dependencies simultaneously. Subgraph sampling was further

adopted to train model for enhancing generalization ability of model and reducing

computational pressure on devices.

● Extensive experiments on three PPI datasets with different settings demonstrate that

laruGL-PPI outperforms other state-of-the-art methods for multi-label PPI prediction under

various challenging scenarios and has a high interpretability for PPI type prediction.

2.   Problem statement and related work

Protein-Protein Interaction Prediction. Early works leverage machine learning (ML) techniques

to map pairs of handcrafted sequence features of proteins to interaction patterns[6, 8, 20, 21]. With

the development of deep learning (DL), recent works have applied deep neural networks to

automatically extract features from protein sequences for enhancing feature representation[10, 11,

22]. Furthermore, the latest works utilize graph neural networks (GNN) to model the PPI

network[12]. Among these works, the SemiGNN-PPI[17] establishes a multi-graph learning

framework to improve the model performance, and the HIGH-PPI[18] organizes the

structure-based internal graph for each protein to enhance the interpretability of the model.

However, all the PPI prediction models face a topological shortcut problem due to annotation

imbalance. Also, the framework using a hierarchical graph with protein structure exerts pressure

on computational devices because of the huge memory cost.

Topological Shortcut. In drug-target interaction (DTI) prediction, similar to PPI, DL models learn

a map from features to interaction labels in the training data. Features refer to the chemical

structures of proteins and ligands, which determine their physical and chemical properties. In an

ideal scenario, the ML model learns the patterns characterizing the features that drive the

protein-ligand interactions, capturing the physical and chemical properties of a protein and of a

ligand that determine the interaction. Nevertheless, multiple state-of-the-art deep learning models

ignore the features and depend largely on annotations, i.e., the degree information for each protein

and ligand in the drug-target interaction (DTI) network, as a shortcut to make new binding

inferences. In protein-protein interaction prediction, the topological shortcut problem also exists in

the PPI network.

Multi-Label Learning. MLL addresses the problem in assigning multiple labels to a single

instance. It has been applied successfully in various domains, e.g., computer vision[23, 24].

Traditional MLL

methods typically train independent classifiers for all labels but fail to pay attention to the

potential label interdependence, leading to suboptimal performance. Recent trends in MLL

incorporate deep learning to capture the label dependencies[25, 26]. As an example,

CNN-RNN[25] makes use of recurrent neural networks (RNNs) to transform the label vectors into

an embedded space to learn label correlations implicitly. More recently, graph-based MLL

approaches have gotten great attention from scientific communities[27, 28]. Especially, the

SemiGNN-PPI[17] successfully makes use of Graph Convolutional Network (GCN) by

constructing a directed graph over labels to explicitly model the protein-protein interaction

dependencies adaptively. In this regard, we add graph-based MLL to hierarchical graph learning

for more accurate PPI prediction.

Subgraph Sampling. In a GCN, data to be gathered for one output node comes from its neighbors

in the previous layer. Each of these neighbors, in turn, gathers its output from the previous layer,

and so on. Clearly, the deeper we back track, the more multi-hop neighbors to support the

computation of the root. The number of support nodes (and thus the training time) potentially

grows exponentially with the GCN depth. To mitigate such "neighbor explosion", state-of-the-art

methods use various layer sampling techniques[29-31]. While these methods significantly speed

up training, they face challenges in scalability, accuracy, or computation complexity. Recently, the

GraphSAINT[32] was presented to efficiently train deep GCNs. Instead of building a GCN on the

full training graph and then sampling across the layers, GraphSAINT samples the training graph

first and then builds a full GCN on the subgraph, which is graph sampling-based. In this work, we

leverage edge-based subgraph sampling to alleviate the topological shortcut problem in the PPI

network and computational cost.

3.   Materials and methods

3.1 Task definition

Given a set of protein $P = \{p_0, p_1, ..., p_n\}$ and a set of PPIs

$E = \{e_{ij} = \{p_i, p_j\} \mid i \neq j, p_i, p_j \in P, I(e_{ij}) \in 0,1\}$, where $I(e_{ij})$ is a binary PPI indicator

function that is 1 if the PPI between proteins p_i and p_j has been confirmed, and 0 otherwise, the

types of PPI can be represented by the label space $C = \{c_1, c_2, ..., c_t\}$ with t different types of

interactions, and the labels for a confirmed PPI e_{ij} can be represented as $y_{ij} \subseteq C$. The goal of

multi-type PPI learning is to learn a function $f : e_{ij} \rightarrow \hat{y}_{ij}$ from the training set such that for any

PPI $e_{ij} \in E_{test}$, $\hat{y}_{ij}$ is the set of predicted labels for e_{ij}. To confirm the emergence of topological

shortcuts in PPI prediction, we analyze annotations in three common PPI datasets (i.e., SHS27k,

SHS148k, and STRING).

3.2 Network architecture design of laruGL-PPI

Figure 1 depicts the overview of our proposed laruGL-PPI framework. We first construct the

multi-graph encoding module to effectively predict PPI types, consisting of a protein graph

encoding network for capturing binding patterns, a PPI network graph encoding network for

modeling protein-protein correlations, and a label graph encoding network for learning label

dependencies. To mitigate

topological shortcut problem and computational pressure, we make use of an edge-based subgraph

sampling approach to train the laruGL-PPI model.

168
169
170
Figure 1: The overall framework of laruGL-PPI. First, we construct a protein graph with residues
as nodes and contacts as edges. We treat the physical and chemical properties of amino acids as
features of nodes. Then, GCN blocks are employed to characterize the protein graph, and all the
output features of nodes are aggregated to a feature vector as a feature of the protein node in the
PPI network graph, which is characterized by proteins as nodes and correlations as edges.
Afterward, we use GIN blocks to model the PPI network, leading to network-aware protein
features. We arrange GCN blocks on the label graph to learn a classifier, which is applied to the
products of two protein features for protein-protein interaction prediction. Later on, laruGL-PPI is
interpreted by GNNExplainer.
180

3.2.1 Multi-Graph Encoding

Protein-Graph Encoding. We denote a set of amino acid residues in a protein as

$prot = \{r_1, r_2, ..., r_n\}$. Each residue is described with t kinds of physicochemical properties. For

the bottom inside-of-protein view, a protein graph $g_b = (V_b, A_b, X_b)$ is built to model the

relationship between residues in Prot, where $V_b \subseteq prot$ is the set of nodes, A_b is an $n \times n$

adjacency matrix representing the connectivity in g_b, and $X_b \in R^{n \times \theta}$ is a feature matrix

containing the properties of all residues. The contact map is exactly equivalent to the adjacency

matrix $A_b \in \{0,1\}^{n \times n}$ in the protein graph. Contact maps are obtained with atomic level 3D

coordinates of proteins. First, we retrieve the predictive structures from the AlphaFold Protein

Structure Database. Then we represent the location of each residue by the 3D coordinates of its

C_α atom. The presence or the absence of contact between a pair of residues is determined by

their $C_\alpha - C'_\alpha$ physical distance. In this work, we choose the cutoff distance of 12 A. For a

feature matrix X_b , each row stands for a set of properties for one amino acid residue. In this

context, seven residue-level properties are considered: isoelectric point, polarity, acidity and

alkalinity, hydrogen bond acceptor, hydrogen bond donor, octanol-water partition coefficient, and

topological polar surface area. We apply variant graph neural networks to learn protein

representations. Specifically, four GCN blocks are employed. Given the adjacency matrix A_b

$\in \{0,1\}^{n \times n}$ and the feature matrix $X_b \in R^{n \times \theta}$ of an arbitrary protein graph g_b, we update

residue representations with the neighbor aggregations based on the work of Kipf and Welling:

200
$$H^{(l+1)} = BN(\mathrm{Re}\,LU(\tilde{D}^{-1/2}(A_b + I_n)\tilde{D}^{-1/2}H^{(l)}W^{(l)}))$$

where $I_n \in R^{n \times n}$ is the identity matrix, $\tilde{D} \in R^{n \times n}$ is the diagonal degree matrix with entries

$D_{ii} = \sum_j (A_b + I_n)_{ij}$, $W^{(l)}$ is a learnable weight matrix for the GCN layer l, ReLU, and BN

denotes the ReLU activation function and batch normalization, respectively. In the first GCN layer,

$H^{(0)} = X_b$. After four rounds of iteration, we perform the readout operation with a

self-attention graph pooling layer and average aggregation to obtain the entire graph

representation.

PPI-Graph Encoding. The PPI network structure determines the adjacency matrix

$A_t \in \{0,1\}^{m \times m}$, in which the i-th row and j-th column elements are 1 if the i-th protein interacts

j -th. The i -th row of the feature matrix X_t describes the representation vector for the i -th

protein graph g_b. We use a graph isomorphism network (GIN) to learn PPI network information.

Formally, we are given the PPI graph $g_t = (V_t, A_t, X_t)$, where $X_t \in R^{m \times d}$ is defined as the

feature matrix whose row vector is a representation from protein graph. In the k -th GIN layer,

213
$$x_v^{(k)} = \mathrm{MLP}^{(k)}((1+\varepsilon) \mathrm{g} x_v^{(k-1)} + \sum_{u \in \mathrm{N}(v)} x_u^{(k-1)})$$

where $x_v^{(k)}$ denotes the representation of protein v after the k -th GIN layer, $\mathrm{N}(v)$ is a set of

proteins

adjacent to v, and ε is a learnable parameter. After two GIN layers, we feed $x_v^{(2)}$ in a linear layer

with
the ReLU activation to obtain the final protein representation. For an arbitrary query pair
containing the

i -th and j -th proteins, we adopt the element-wise product to combine protein pair information.

Then

the generated vector goes through a fully connected layer (FC) to come by protein-protein

representation.

Label-Graph Encoding. In multi-label PPI prediction, correlations exist among different types of

interactions, i.e., some PPI types may appear together frequently while others rarely appear

together. For example, post-translational modifications are often associated with catalysis in

biology. Following Chen et al, we model the interdependencies between different PPI types(labels)

using a graph and make the model learn an inter-dependent classifier with the GCN, which is

directly applied to protein-protein representation for multi-type PPI prediction. The GCN aims to

learn a function $f(\cdot, \cdot)$ on the graph with t nodes. With the convolutional operation, $f(\cdot, \cdot)$

can be expressed as:

232
$$C = \mathrm{BN}(\mathrm{ReLU}(\tilde{D}^{-1/2}(A_c + I_n)\tilde{D}^{-1/2} X_c W_c))$$

where $I_n \in R^{n \times n}$ is the identity matrix, $\tilde{D} \in R^{n \times n}$ is the diagonal degree matrix with entries

$D_{ii} = \sum_j (A_c + I_n)_{ij}$, $A_c \in R^{t \times t}$ and $X_c \in R^{t \times d_c}$ denotes adjacency and feature matrix in label

graph individually, W_c is a learnable weight matrix for the GCN, ReLU, BN denotes the ReLU

activation function and batch normalization, respectively. Considering that PPI type names are

semantic, we utilize the BioWordVec model pre-trained on the biomedical corpus for generating

word embedding X_c to better capture their semantics. To construct the label correlation matrix, we

compute the conditional probability of different labels within the dataset. To avoid noise, we

binarize the correlation matrix with a threshold τ to obtain A_c.

241   3.2.2   Multi-Graph Learning with Subgraph Sampling

242   By applying the learned classifier W from label graph encoding(LGE) to the learned

243   representations from hierarchical graph encoding (HGE) for PPI e_{ij}, we can obtain the predicted

244   scores $\hat{y}_{ij} = W(h_{p_i} \cdot h_{p_j})$. We use the traditional multi-label classification loss function to update

245   the whole network in an end-to-end manner. The loss function can be written as:

246
$$L = \sum_{c=1}^{t} (y^c \log(\sigma(\hat{y}^c)) + (1-y^c)\log(1-\sigma(\hat{y}^c)))$$

where $\sigma(\cdot)$ is the sigmoid function. Our model learns the aggregated features by combining

protein neighbors and models the label correlations by learning inter-dependent classifiers

simultaneously to improve the model generalization. With multi-graph learning, the learned

classifiers are expected to be neighborhood-aware at both feature and label levels. We select an

edge-based sampler to build a subgraph G_s due to the nature of protein-protein interaction. In

detail, Given training PPI-network graph G and edge budget m. Firstly, sampling probability

$P((u,v))$ is calculated by the following formula:

254
$$P((u,v)) := \left(\frac{1}{\deg(u)} + \frac{1}{\deg(v)} \right) / \sum_{(u',v') \in \mathcal{E}} \left(\frac{1}{\deg(u')} + \frac{1}{\deg(v')} \right),$$

255 where $\deg(\cdot)$, $\mathcal{E}$ are referred to as the degree of a protein node and a set of all edges in the

256 training graph. Secondly, m edges are randomly sampled from $\mathcal{E}$ according to P and sets of nodes

257 that are end-points of edges in $\mathcal{E}_s$ are determined as V_s. Finally, the subgraph G_s is derived from V_s

258 with node inducing.

3.2.3　Residue importance computation

We employ the method called GNNExplainer[33] to generate explanations for laruGL-PPI. By

taking the well-trained GNN model and its predictions as inputs, GNNExplainer returns the most

important subgraph by maximizing the mutual information MI between the model prediction and

possible subgraphs. Given protein graphs G_1 and G_2 that connect in the PPI network, our goal is to

identify a subgraph $G_s \subseteq G_1$ that is important for our model's prediction $\hat{y}$. The mutual

information MI is formulated as

267
$$MI(Y, G_s) = H(Y) - H(Y \mid G = G_s).$$

268 MI_s represents importance of G_s, Y is a variable indicating the probability of PPI presence of G_1

269 and G_2, and $H(g)$ is the entropy term. In effect, MI quantifies the change in the probability of

270 prediction $\hat{y} = \Phi(G_1, G_2)$ when the computation graph is limited to explanation subgraph G_s. A

271 computationally efficient version of GNNExplainer's objective, which we optimize using Adam,

272 is as follow:

273
$$\min_{M} - \sum_{c=1}^{C} 1[y = c] \log P_{\Phi}(Y = y \mid G = A \mathrm{e}\ \sigma(M))$$

274 Lastly, we compute the element-wise multiplication of $\sigma(M)$ and adjacency matrix A and set a

275 threshold to arrive at the explanation G_s for our model's prediction $\hat{y}$ at the protein graph G_1.

3.2.4 Datasets and metrics

We perform extensive analyses and experiments on three benchmark datasets, i.e., SHS27k, SHS148k, and STRING. Both SHS27k and SHS148k are subsets of the STRING datasets. These are multi-label PPI data of Homo sapiens from the STRING database. We retrieve protein structures from the AlphaFold Protein Structure Database. In this work, SHS27k has 1553 proteins and 6660 protein-protein multi-type labels. SHS148k consists of 4072 proteins and 30067 labels. The PPIs are annotated with 7 types, i.e., Activation, Binding, Catalysis, Expression, Inhibition, Post-translational modification (Ptmod), and Reaction. Each PPI is labeled with at least one of them. The micro-F1 score was applied to evaluate and compare the predictive performance of laruGL-PPI and existing methods. We also use the area under the precision-recall curve (AUPR) to estimate the model with regard to specific interaction type.

4   Results and discussion

4.1 Topological Shortcut Analysis.

In the context of the PPI predictive task, ML models learn a map from features to labels as annotations and then make inferences for the likelihood of each node (protein) to bind to other nodes. Annotations capture protein-protein interactions. Normally, known protein-protein interaction is denoted as 1, while the unknown interaction is labeled as 0. Features refer to the chemical structures of proteins, which determine their physical and chemical properties, and are expressed as amino acid sequences or 3D structures for proteins. With the success of network inference in various fields, many ML models have considered PPI network and regard it as one of

the features externally. In an ideal scenario, the ML model learns the patterns characterizing the

features that drive the protein-protein interactions, capturing the physical and chemical properties

of protein pairs that determine the mutual binding action. However, as we show next, multiple

state-of-the-art deep learning models, such as HIGH-PPI rely largely on the degree information for

each protein in the protein-protein interaction network, as a shortcut to make new binding

predictions. We begin by noticing that the number of annotations linked to a protein follows a

fat-tailed distribution, indicating that the vast majority of proteins have only a small number of

annotations, which then coexist with a few hubs, nodes with an exceptionally large number of

binding records.

Distributions of the number of annotations in the SHS27k and SHS148k are shown in **Figure**

2. As an example, the number of annotations for proteins follows a power law distribution with

degree exponent $\gamma = 1.46$, maximum degree $k_{max} = 182$, and minimum degree $k_{min} = 1$ on the

SHS27k dataset. For the degree exponent, the second moment of the distribution diverges,

implying that the expected uncertainty in the binding information is highly significant, limiting

our ability to predict the binding between proteins in terms of intrinsic protein characteristics.

Furthermore, it is found that the number of annotations k and the average interaction per k ,

calculated as the average across all links stemming from nodes of degree k , are associated with

each other. In this work, there are seven interaction types between proteins, consisting of reaction,

binding, posttranslational modification, activation, inhibition, catalysis, and expression. For

catalysis, they are positively correlated with $r_{Spearman} = 0.37$ ($p < 0.01$), indicating a stronger

catalysis propensity for proteins with more annotations. Whereas, they are negatively correlated

with $r_{Spearman} = -0.34$ ($p < 0.01$) for expression, implying a stronger expression tendency for

proteins with fewer annotations (Table 1). As the annotations follow fat-tailed distributions, the observed correlation drives the hub proteins to have disproportionately more interaction or non-interaction on average, whereas proteins with fewer annotations have both interaction and non-interaction examples. This annotation imbalance prompts the ML models to leverage degree information (positive and negative annotations) in making interaction predictions instead of learning interaction patterns from the protein intrinsic structures.

To investigate the emergence of topological shortcuts, for each node i with the number of annotations k_i, we quantify the balance of the available data information via the degree ratio,

$\rho_i = \frac{k_i^+}{k_i^+ + k_i^-} = \frac{k_i^+}{k_i}$, where, k_i^+ is the positive degree, corresponding to the number of known binding annotations in the training data, and k_i^- is the negative degree, or the number of unknown annotations in the training data. As most proteins lack either binding or unknown annotations for interaction types (Table 1), the resulting p_i are close to 1 or 0 (See Figure 3), which represents the annotation imbalance in the prediction problem. As many state-of-the-art deep learning models, such as HIGH-PPI, uniformly sample the available positive and negative annotations, they tend to assign a higher binding probability to proteins with higher ρ. Consequently, their binding predictions are driven by topological shortcuts in the protein-protein network, which are associated with the positive and negative annotations present in the dataset rather than the structural features characterizing proteins.

338   Figure 2 Distributions of the number of annotations in the SHS27k (a) and SHS148k (b)

Class	Has only positive labels	Has only negative labels	Has both labels	correlation
Reaction	275	737	541	0.06
	541	1903	1628	-0.09
Binding	502	370	681	-0.12
	1186	895	1991	-0.14
Ptmod	24	1216	313	0.10
	84	2854	1134	0.22
Activation	232	672	649	0.12
	455	1667	1950	0.12
Inhibition	48	1150	355	0.16
	72	2863	1137	0.10
Catalysis	206	781	566	0.37
	372	2044	1656	0.23
Expression	82	1151	320	-0.34
	189	2905	978	-0.45

344   Table 1 Statics of SHS27K and SHS148K. Most proteins in common datasets have either positive

345   or negative labels, which creates an imbalance in the degree ratio.

348   Figure 3 The distribution of degree ratios for the proteins in SHS27K and SHS148K.

4.2 Comparison with competitive methods

In this section, we display the performances achieved by our laruGL-PPI and competitive

baselines on SHS27k and SHS148k datasets. Here, we ran each model five times independently to

eliminate bias caused by randomness and examine the robustness of laruGL-PPI. In Table 2, we

compare our methods with other baseline methods under different partition schemes and various

datasets. It is observed that graph-based methods, i.e., GNN-PPI, SemiGNN-PPI, and HIGH-PPI

exceed other ML and DL models, even under more difficult BFS and DFS partitions with more

unseen proteins. It can be ascribed to graph learning, which can model correlations between

proteins despite the existence of more unknown proteins. Furthermore, our proposed method,

which incorporates multiple graph learning in conjunction with subgraph sampling, achieves

competitive performance in multi-type PPI prediction in a common transductive setting. It is

worth mentioning that our method reaches state-of-the-art levels in difficult data partition, i.e.,

DFS and BFS. In the realistic application of biology, models tend not to have seen predicted

protein pairs in the training process. To conform with reality, it is the first time to consider an

inductive setting in multi-type PPI prediction. When facing unseen protein, the model cannot

utilize degree information to conduct prediction, leading to decreasing accuracy. The inductive

setting requires models to more focus on protein structures instead of degree information. By

subgraph sampling, our model improves predictive performance and outperforms state-of-the-art

HIGH-PPI under the more difficult inductive setting with SHS27k, regardless of partition mode

(Table 2).

4.3 Performance on specific PPI types

For each of the six PPI types, we offer a separate performance analysis in terms of AUPR. It can

be found that our presented model with lower learning cost parallels with HIGH-PPI as shown in

Figure 4. Notably, laruGL-PPI consistently beats the previous state-of-the-art models in the most

challenging setting (i.e. inductive setting with BFS). This is reasonable as laruGL-PPI learns

spatial-biological patterns as possible as it can by sampling subgraphs in multiple graph

frameworks. When facing unknown protein pairs, it can exploit these patterns to predict better

than others.

Model	SHS27K			SHS148K		
	Random	DFS	BFS	Random	DFS	BFS
RF	0.7845	0.3555	0.3767	0.8210	0.4326	0.3896
	(0.0088)	(0.0222)	(0.0157)	(0.0020)	(0.0343)	(0.0194)
LR	0.7155	0.4851	0.4306	0.6700	0.5109	0.4745
	(0.0093)	(0.0187)	(0.0505)	(0.0007)	(0.0209)	(0.0142)
DPPI	0.7399	0.4612	0.4143	0.7748	0.5203	0.5212
	(0.0504)	(0.0302)	(0.0056)	(0.0139)	(0.0118)	(0.0870)
DNN-PPI	0.7789	0.5434	0.4890	0.8849	0.5842	0.5740
	(0.0497)	(0.0130)	(0.0724)	(0.0048)	(0.0205)	(0.0910)
PIPR	0.8331	0.5780	0.4448	0.9005	0.6398	0.6183
	(0.0075)	(0.0324)	(0.0444)	(0.0259)	(0.0076)	(0.1023)
GNN-PPI	0.8791	0.7472	0.6381	0.9226	0.8267	0.7137
	(0.0039)	(0.0526)	(0.0179)	(0.0010)	(0.0085)	(0.0533)
HIGH-PPI	0.8797	0.7884	0.6749	0.8909	0.7567	0.6798
	(0.0089)	(0.0052)	(0.0211)	(0.0245)	(0.0103)	(0.0397)
SemiGNN-PPI	0.8951	0.7832	0.7215	0.9240	0.8545	0.7178
	(0.0046)	(0.0315)	(0.0287)	(0.0022)	(0.0117)	(0.0356)
laruGL-PPI	0.8762	0.7972	0.7407	0.9069	0.8061	0.7307
	(0.0053)	(0.0160)	(0.0672)	(0.0039)	(0.0096)	(0.0259)
HIGH-PPI*	0.8480	0.7351	0.6665	0.8572	0.7127	0.6674
	(0.0067)	(0.0080)	(0.0452)	(0.0211)	(0.0277)	(0.0416)
laruGL-PPI*	0.8635	0.7657	0.7097	0.9013	0.7852	0.7311
	(0.0048)	(0.0371)	(0.0394)	(0.0035)	(0.0110)	(0.0374)

379   Table 2 Prediction accuracy of laruGL-PPI and other competing methods. The accuracy is
380   represented by the mean micro-F1 score (standard deviation). The optimal value in settings has
381   been emphasized in bold. The symbol * stands for inductive setting and the model without *
382   means transductive.

Figure 4 Performance of laruGL-PPI in predicting specific PPIs on SHS27k, compared with

HIGH-PPI. Blue and purple represents HIGH-PPI and laruGL-PPI, respectively. Error bars

express the standard deviation of the mean. Source data are provided as a Source Data file.

4.4 The results of training with different subgraph sizes

In this section, we display the results of the comparison of HIGH-PPI and our laruGL-PPI with

various subgraph sizes. Beginning with a subgraph size of 200, we observe that our model has

attained competing effectiveness in SHS27k under the transductive setting. From the results of the

effect of subgraph size, using subgraph sampling is capable of reducing the memory cost of the

Graphics Processing Unit (GPU) significantly and having a comparable outcome at the same time

(Table S1). It is indicated that taking the size of 300, 400, or 500 can reach a greater performance

under most scenarios (inductive setting with BFS segmentation) and request a relatively smaller

memory cost in the SHS27k dataset (Figure 5). For the bigger dataset SHS148k, the advantages of

models based on subgraph sampling are even more prominent. By sampling a subgraph of the size

of 200, our model significantly surpasses the sota model called HIGH-PPI in difficult inductive

scenarios with BFS. Specifically, our model achieves 0.7059 on the F1-score with 5.09 GB of

computer graphics memory consumption in this condition, while the sota HIGH-PPI has a value of

0.6674, costing 28.93 GB (Figure 5). Generally, our model can significantly surpass the sota

model in both transductive and inductive scenarios through suitable subgraph size (Table S2).

4.5 Ablation study

We investigate the effectiveness of different components in laruGL-PPI in Table 3. It can be seen

that the model improves a lot (from 0.6749 to 0.7238) under relatively difficult circumstances (i.e.

transductive setting with BFS) when considering adjacent residues in sequence. This implies that

sequence information plays an important role in determining PPI types. What's more, label graph

encoding brings plenty of profits in a majority of scenarios, particularly under the most arduous

condition (i.e. inductive setting with BFS, from 0.6652 to 0.7072). Finally, our model is getting

more powerful when adopting an edge-based sampling strategy on the PPI graph. In particular,

under a transductive setting, performance in terms of DFS achieves 0.7972. While under inductive

setting, a more challenging scene, laruGL-PPI reaches the best F1-score in the light of all the

partitions.

Model	Transductive setting			Inductive setting		
	Random	DFS	BFS	Random	DFS	BFS
HGL-origin	0.8797	0.7884	0.6749	0.8480	0.7351	0.6665
	(0.0089)	(0.0052)	(0.0211)	(0.0067)	(0.0080)	(0.0452)
HGL	0.8873	0.7743	0.7238	0.8369	0.7400	0.6652
	(0.0059)	(0.0149)	(0.0383)	(0.0058)	(0.0165)	(0.0797)
laHGL	0.8894	0.7819	0.7545	0.8405	0.7350	0.7072
	(0.0073)	(0.0226)	(0.0399)	(0.0040)	(0.0470)	(0.0543)
laruGL	0.8762	0.7972	0.7407	0.8635	0.7657	0.7097
	(0.0053)	(0.0160)	(0.0672)	(0.0048)	(0.0371)	(0.0394)

436 Table 3 Results of ablation studies on different components of laruGL-PPI using the SHS27k

437 dataset.

4.6 Interpretability of our laruGL-PPI

4.6.1 Analysis of feature importance in residue-level

The feature importance in residue-level for overall (left-most column) and type-specific (right six

columns) PPI prediction, which is calculated as the average z-score, resulting from dropping

individual feature dimension from our model and calculating changes of AUPR before and after.

For node features in protein graphs, we select seven important features in terms of

laruGL-PPI. Here, we list the selected seven residue-level physicochemical properties in Figure 5

and discuss their importance for different types of PPIs to both better interpret our model and

discover enlightening biomarkers for the PPI interface. The average z-score, which results from

deleting each feature dimension and analyzing changes in metrics before and after, is calculated to

determine the importance of a feature. From the results, laruGL-PPI regards topological polar

surface area (TPSA) and octanol-water partition coefficient (KOW) as dominant features in

multiple types of PPIs. This finding supports the conventional wisdom that TPSA and KOW play a

key role in the drug transport process[34], protein interface recognition[35, 36], and PPI

prediction[37].

Figure 5 The feature importance in residue-level for overall (left-most column, F1-score) and

type-specific (right seven columns, AUPR) PPI prediction.

4.6.2 laruGL-PPI identifies key residues constituting functional sites

Typically, functional sites are spatially clustered sets of residues. They control protein functions

and are thus important for PPI prediction. As our proposed model has the capacity to capture

spatial-biological arrangements of residues in protein graph learning, this characteristic can be

used to explain the model's decision. It is meaningful to notice that laruGL-PPI can automatically

learn the residue importance without any residue-level annotations. In this section, we provide a

case study of predicting important residues for the binding surface and two cases of estimating key

residues for catalytic function.

First, a binding example between the query protein (PDB id: 2B6H) and its partner (PDB id:

2REY) is investigated, whose complex structure is generated by ZDOCK[38]. Subsequently, we

apply the GNN explanation approach on the laruGL-PPI model. As can be seen from Figure 6a.

LaruGL-PPI can accurately and automatically identify the residues that belong to the binding

domain.

Second, to evaluate the prediction of crucial sites of catalysis for PPIs, we utilize the same

GNN explanation approach in our model. The ground truth key sites, normally including binding

sites and active sites, are retrieved from the Universal Protein Knowledgebase (UniProt)[39]. We

explore the prominent residues of catalytic function for query proteins (UniProt id: P62714,

Q9UMX6). As seen in Figure 6b, our proposed laruGL-PPI infers that ASN117 is important for

the catalysis of P62714 known as the catalytic subunit of protein phosphatase 2A, in terms of

Q9Y4X3. The coordinate bond between ASN117 and Mn^{2+} activates the enzyme to play a highly

efficient catalytic role. For Guanylyl cyclase-activating protein 2 (Q9UMX6), the model can

correctly predict that Asp66 and Asp102 are key to perform catalysis on Q16270.

Protein functional site prediction sheds light on the model decisions and how to conduct

additional wet experiments for PPI investigation. Excellent model interpretability also

demonstrates that our approach can accurately describe biological evidence for proteins.

485   a   b

Figure 6 Automatic explanation for key residue without supervision. **a** Top: Depiction of a

complex protein (left, query protein, PDB id: 2B6H; right, interacted protein, PDB id: 2REY)

modeled in surface representation. Bottom: important residues of the query protein learned from

laruGL-PPI with pink. **b** Depiction of two proteins (top, UniProt id: P62714; bottom, UniProt id:

Q9UMX6) modeled in cartoon representations. Residues inferred by the model, which are colored

with brown, are important for catalysis.

5. Conclusions

In this study, it was found that conventional machine learning is subject to the problem of

topological shortcuts. A new framework based on subgraph sampling was proposed to address this

issue, enabling the model to focus more on the protein structure itself. This framework improved

prediction accuracy and generalization, especially in challenging settings, where it exhibited

significant improvements in encountering new proteins. Additionally, subgraph sampling saved

computational resources. Through interpretable analysis of the model, it was found that the model

can identify key sites, binding surfaces, or active sites. This may also be attributed to the subgraph

sampling algorithm. Nevertheless, there is still room for improvement. For instance, the model

does not explicitly consider protein sequence information, and future research may consider

sequence-structure co-modeling. Another potential direction is to extend the model to protein

all-atom graphs, extracting more microscopic information about proteins and learning the essence

of PPI, thereby further enhancing the model's generalization ability and interpretability.

Data and code availability

The preprocessed data and model code associated with the study will then be uploaded to GitHub.

CRediT authorship contribution statement

Yuanqing Zhou: Writing – review & editing, Writing – original draft, Visualization, Validation, Software, Methodology, Investigation, Conceptualization. Haitao Lin: Writing – review & editing, Software, Methodology, Conceptualization. Yufei Huang: Validation, Methodology, Investigation. Lirong Wu: Investigation, Conceptualization. Stan Z. Li: Supervision, Project administration, Funding acquisition. Wei Chen: Supervision, Project administration.

Declaration of competing interest

None.

Acknowledgments

This work was supported by the National Key Research and Development Program of China (No. 2022YFF1100202), Ministry of Science and Technology of the People's Republic of China (No. 2021YFA1301603), National Natural Science Foundation of China Project (No. U21A20427), Project (No. WU2022A009) from the Center of Synthetic Biology and Integrated Bioengineering of Westlake University and Project (No. WU2023C019) from the Westlake University Industries of the Future Research Funding.

References

[1] L. Skrabanek, H.K. Saini, G.D. Bader, A.J. Enright, Computational prediction of protein-protein interactions, Mol. Biotechnol. 38 (2008) 1-17, https://doi.org/10.1007/s12033-007-0069-2.

[2] I. Petta, S. Lievens, C. Libert, J. Tavernier, et al., Modulation of protein-protein interactions for the development of novel therapeutics, Mol. Ther. 24 (2016) 707-718, https://doi.org/10.1038/mt.2015.214.

[3] S. Fields, O.K. Song, A novel genetic system to detect protein protein interactions, Nature 340 (1989) 245-246, https://doi.org/10.1038/340245a0.

[4] Y. Ho, A. Gruhler, A. Heilbut, G.D. Bader, et al., Systematic identification of protein complexes in
Saccharomyces cerevisiae by mass spectrometry, Nature 415 (2002) 180-183,
https://doi.org/10.1038/415180a.

[5] X. Luo, Z.H. You, M.C. Zhou, S. Li, et al., A highly efficient approach to protein interactome
mapping based on collaborative filtering framework, Sci. Rep. 5 (2015) 7702,
https://doi.org/10.1038/srep07702.

[6] F. Browne, H. Wang, H. Zheng, F. Azuaje, Supervised statistical and machine learning approaches
to inferring pairwise and module-based protein interaction networks, 7th IEEE International
Conference on Bioinformatics and Bioengineering (2007) 1365-1369,
https://doi.org/10.1109/BIBE.2007.4375748.

[7] X. Lin, X.W. Chen, Heterogeneous data integration by tree-augmented naïve Bayes for
protein-protein interactions prediction, Proteomics 13 (2013) 261-268,
https://doi.org/10.1002/pmic.201200326.

[8] L. Wong, Z.H. You, S. Li, Y.A. Huang, G. Liu, Detection of protein-protein interactions from amino
acid sequences using a rotation forest model with a novel PR-LPQ descriptor, 11th International
Conference on Intelligent Computing (2015) 713-720,
https://doi.org/10.1007/978-3-319-22053-6_75.

[9] T.L. Sun, B. Zhou, L.H. Lai, J.F. Pei, Sequence-based prediction of protein protein interaction using
a deep-learning algorithm, BMC Bioinformatics 18 (2017) 277,
https://doi.org/10.1186/s12859-017-1700-2.

[10] S. Hashemifar, B. Neyshabur, A.A. Khan, J.B. Xu, Predicting protein-protein interactions through
sequence-based deep learning, Bioinformatics 34 (2018) 802-810,
https://doi.org/10.1093/bioinformatics/bty573.

[11] M.H. Chen, C.J.T. Ju, G.Y. Zhou, X.L. Chen, et al., Multifaceted protein-protein interaction
prediction based on Siamese residual RCNN, Bioinformatics 35 (2019) 305-314,
https://doi.org/10.1093/bioinformatics/btz328.

[12] G. Lv, Z. Hu, Y. Bi, S. Zhang, Learning unknown from correlations: Graph neural network for
inter-novel-protein interaction prediction, International Joint Conference on Artificial
Intelligence(IJCAI-21) (2021) 3677-3683, https://www.ijcai.org/proceedings/2021/0506.

[13] S. Min, B. Lee, S. Yoon, Deep learning in bioinformatics, Brief. Bioinform. 18 (2017) 851-869,
https://doi.org/10.1093/bib/bbw068.

[14] F. Soleymani, E. Paquet, H. Viktor, W. Michalowski, D. Spinello, Protein-protein interaction
prediction with deep learning: A comprehensive review, Comput. Struct. Biotec. 20 (2022)

5316-5341, https://doi.org/10.1016/j.csbj.2022.08.070.

[15] T.N. Kipf, M. Welling, Semi-supervised classification with graph convolutional networks, arxiv

preprint arxiv:1609.02907, https://doi.org/10.48550/arXiv.1609.02907.

[16] K. Xu, W. Hu, J. Leskovec, S. Jegelka, How powerful are graph neural networks? arxiv preprint

arxiv: 1810.00826, https://doi.org/10.48550/arXiv.1810.00826.

[17] Z. Zhao, P. Qian, X. Yang, Z. Zeng, et al., SemiGNN-PPI: self-ensembling multi-graph neural

network for efficient and generalizable protein-protein interaction prediction, In Proceedings of

the Thirty-Second International Joint Conference on Artificial Intelligence (IJCAI-23) (2023)

4984–4992, https://doi.org/10.24963/ijcai.2023/554.

[18] Z. Gao, C. Jiang, J. Zhang, X. Jiang, et al., Hierarchical graph learning for protein–protein

interaction, Nat. Commun. 14 (2023) 1093, https://doi.org/10.1038/s41467-023-36736-1.

[19] A. Chatterjee, R. Walters, Z. Shafi, O.S. Ahmed, et al., Improving the generalizability of

protein-ligand binding predictions with AI-Bind, Nat. Commun. 14 (2023) 1989,

https://doi.org/10.1038/s41467-023-37572-z.

[20] X.W. Chen, M. Liu, Prediction of protein-protein interactions using random decision forest

framework, Bioinformatics 21 (2005) 4394-4400, https://doi.org/10.1093/bioinformatics/bti721.

[21] Y.Z. Guo, L.Z. Yu, Z.N. Wen, M.L. Li, Using support vector machine combined with auto

covariance to predict protein protein interactions from protein sequences, Nucleic Acids Res. 36

(2008) 3025-3030, https://doi.org/10.1093/nar/gkn159.

[22] X.Q. Du, S.W. Sun, C.L. Hu, Y. Yao, et al., DeepPPI: boosting prediction of protein-protein

interactions with deep neural networks, J. Chem. Inf. Model 57 (2017) 1499-1510,

https://doi.org/10.1021/acs.jcim.7b00028.

[23] W.W. Liu, H.B. Wang, X.B. Shen, I.W. Tsang, The emerging trends of multi-label learning, Ieee. T.

Pattern. Anal. 44 (2022) 7955-7974, https://doi.org/10.1109/TPAMI.2021.3119334.

[24] X. Kaixin, L. Liyang, Z. Ziyuan, Z. Zeng, et al., Object-aware self-supervised multi-label learning,

2022 IEEE International Conference on Image Processing (ICIP) (2022) 361-365,

https://doi.org/10.1109/ICIP46576.2022.9897968.

[25] J. Wang, Y. Yang, J. Mao, Z. Huang, et al., CNN-RNN: A unified framework for multi-label image

classification, Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition

(CVPR) (2016) 2285-2294.

[26] C. Guo, A. Mousavi, X. Wu, D.N. Holtmann-Rice, et al., Breaking the glass ceiling for

embedding-based classifiers for large output spaces, 33rd Conference on Neural Information

Processing Systems (NeurIPS) (2019) 32.

[27] Z.M. Chen, X.S. Wei, P. Wang, Y. Guo, Multi-label image recognition with graph convolutional

networks, Proceedings of the IEEE/CVF conference on computer vision and pattern recognition

(CVPR) (2019) 5177-5186.

[28] Y. Wang, D. He, F. Li, X. Long, Z. Zhou, J. Ma, S. Wen, Multi-label classification with label graph

superimposing, Proceedings of the AAAI Conference on Artificial Intelligence 34 (2020)

12265-12272.

[29] J. Chen, T. Ma, C. Xiao, FastGCN: fast learning with graph convolutional networks via

importance sampling, arxiv preprint arxiv: 1801.10247,

https://doi.org/10.48550/arXiv.1801.10247.

[30] W.L. Hamilton, R. Ying, J. Leskovec, Inductive representation learning on large graphs, Advances

in neural information processing systems 30 (2017).

[31] W. Huang, T. Zhang, Y. Rong, J. Huang, Adaptive sampling towards fast graph representation

learning, Advances in neural information processing systems 31 (2018).

[32] H. Zeng, H. Zhou, A. Srivastava, R. Kannan, V. Prasanna, GraphSAINT: graph sampling based

inductive learning method, arxiv preprint arxiv: 1907.04931,

https://doi.org/10.48550/arXiv.1907.0493.

[33] R. Ying, D. Bourgeois, J. You, M. Zitnik, et al., Gnnexplainer: generating explanations for graph

neural networks. Advances in neural information processing systems 32 (2019).

[34] J. Fernandes, C.R. Gattass, Topological polar surface area defines substrate transport by multidrug

resistance associated protein 1 (MRP1/ABCC1), J. Med. Chem. 52 (2009) 1214-1218,

https://pubs.acs.org/doi/abs/10.1021/jm801389m.

[35] Z. Hu, B. Ma, H. Wolfson, R. Nussinov, Conservation of polar residues as hot spots at protein

interfaces, Proteins: Structure, Function, and Bioinformatics 39 (2000) 331-342,

https://doi.org/10.1002/(SICI)1097-0134(20000601)39:4<331::AID-PROT60>3.0.CO;2-A.

[36] L., Young, L. R., Jernigan, D.G. Covell, A role for surface hydrophobicity in protein-protein

recognition, Protein Science. 3 (1994) 717-729, https://doi.org/10.1002/pro.5560030501.

[37] A.P. Korn, R.M. Burnett, Distribution and complementarity of hydropathy in mutisunit proteins,

Proteins: structure, function, and bioinformatics 9 (1991) 37-55,

https://doi.org/10.1002/prot.340090106.

[38] B.G. Pierce, K. Wiehe, H. Hwang, B.H. Kim, T. Vreven, Z. Weng, ZDOCK server: interactive

docking prediction of protein-protein complexes and symmetric multimers, Bioinformatics 30

(2014) 1771-1773, https://doi.org/10.1093/bioinformatics/btu097.

[39] T.U. Consortium, UniProt: the Universal Protein Knowledgebase in 2023, Nucleic Acids Res. 51

(2022) 523-531, https://doi.org/10.1093/nar/gkac1052.