Tribus: Semi-automated discovery of cell identities and phenotypes from multiplexed imaging and proteomic data

Ziqi Kang[1], Angela Szabo[1], Teodora Farago[1], Fernando Perez-Villatoro[1], Ada Junquera[1], Saundarya Shah[1], Inga-Maria Launonen[1], Ella Anttila[1], Julia Casado[1], Kevin Elias[2], Anni Virtanen[1], Ulla-Maija Haltia[1], Anniina Färkkilä[1, 3, 4, 5]

[1] Research Program in Systems Oncology, University of Helsinki, Finland

[2] Division of Gynecologic Oncology, Brigham and Women's Hospital, Harvard Medical School, MA, USA

[3] Institute for Molecular Medicine Finland, Helsinki Institute of Life Sciences, University of Helsinki, Finland

[4] Department of Obstetrics and Gynecology, Helsinki University Hospital, Finland.

[5] iCAN Digital Precision Cancer Medicine Flagship, Finland.

Correspondence should be addressed to A.F. (anniina.farkkila@helsinki.fi).

Abstract

Motivation: Multiplexed imaging and single-cell analysis are increasingly applied to investigate the tissue spatial ecosystems in cancer and other complex diseases. Accurate single-cell phenotyping based on marker combinations is a critical but challenging task due to (i) low reproducibility across experiments with manual thresholding, and, (ii) labor-intensive ground-truth expert annotation required for learning-based methods.

Results: We developed Tribus, an interactive knowledge-based classifier for multiplexed images and proteomic datasets that avoids hard-set thresholds and manual labeling. We demonstrated that Tribus recovers fine-grained cell types, matching the gold standard annotations by human experts. Additionally, Tribus can target ambiguous populations and discover phenotypically distinct cell subtypes. Through benchmarking against three similar methods in four public datasets with ground truth labels, we show that Tribus outperforms other methods in accuracy and computational efficiency, reducing runtime by an order of magnitude. Finally, we demonstrate the performance of Tribus in rapid and precise cell phenotyping with two large in-house whole-slide imaging datasets.

Availability: Tribus is available at https://github.com/farkkilab/tribus as an open-source Python package.

Introduction

Multiplexed imaging techniques at single-cell resolution, such as tissue-based cyclic immunofluorescence (t-CyCIF) (Lin et al., 2018), co-detection by indexing (CODEX) (Black et al., 2021), and multiplexed ion beam imaging by time of flight (MIBI-TOF) (Keren et al., 2019), offer significant advantages for studying tissue architecture. These techniques enable researchers to measure dozens of proteins at single-cell resolution while preserving spatial origin information in tissue sections, providing novel insights into cellular phenotypes and tissue behaviors (Spitzer & Nolan, 2016). Multiplexed images require a sequence of processes to extract single-cell measurements, including image registration, stitching, cell segmentation, and quantification (Schapiro et al., 2022). Cell phenotyping is typically the final step before downstream analyses and often serves as the bottleneck in realizing the full potential of multiplexed images. The main challenges in cell-type phenotyping from multiplexed images include reproducibility limitations and unexpected marker combinations.

Classic methods for cell phenotyping such as manual gating and clustering, are reproducibility-limited. Gating (Staats et al., 2019) requires visualizing and manually setting marker expression thresholds for each marker in each sample. These hard thresholds are experiment-specific and can't be reused across different batches. As the marker panel sizes and sample numbers increase, gating becomes time-consuming and unfeasible (Verschoor et al., 2015). Clustering algorithms, such as PhenoGraph (Levine et al., 2015), Leiden (Traag et al., 2019), and DBscan (Ester et al., 1996), have been applied for automatic data exploration (Liu et al., 2019). However, manual verification is still necessary to assign meaningful cell types to the resulting clusters. To achieve deeper profiling of cell types, over-clustering and subsequent merging of clusters is often required, a process that is both computationally intensive and time-consuming.

Several automated cell-type annotation approaches have been developed to overcome the reproducibility
limits. For example, CellSighter is a supervised deep convolutional neural network-based algorithm for
automatic cell phenotyping which requires expert-labeled images for training (Amitay et al., 2023). Another
similar solution, MAPS is a supervised deep learning-based method that is computationally lighter than
CellSighter (Shaban et al., 2024). These methods require pre-training on manually labeled datasets;
however, the measured protein combinations (marker panel design) are experiment-specific, making it
difficult to generate general reference populations for each cell type. In cases of unexpected marker
combinations, the algorithms are required to be retrained in different scenarios.

To address the above challenges, we introduce a novel cell-type caller named Tribus, which incorporates the
widely used self-organizing map (SOM) (Kohonen, 1982) unsupervised clustering method with a unique
scoring function to assign cell types according to prior biological knowledge. Tribus requires only a cell
measurement matrix and a prior knowledge table as inputs, without the need for training on expert
annotations, and enables reproducible, automatic cell phenotyping across various multiplexed imaging and
proteomic datasets. Tribus enables users to easily conduct analyses, visualize results, and perform quality
control through an integrated Napari widget. We validate Tribus's accuracy on four public multiplexed
imaging and suspension mass cytometry datasets. We then compare Tribus's performance to three other
similar prior knowledge-based cell-type identification approaches: ACDC (Lee et al., 2017), Astir (Geuenich
et al., 2021), and Scyan (Blampey et al., 2023), and demonstrate its utility in analyzing two large in-house t-
CyCIF datasets. Tribus represents a novel user-friendly framework for semi-automated cell-type calling in
multiplexed imaging and proteomics datasets.

Methods

76
Figure 1. Overview of Tribus architecture. Tribus processes multiplexed imaging data by using a Self-
Organizing Map (SOM) to cluster cells and a logic table based on panel knowledge to score and classify cell
phenotypes. Results can be visualized with a Napari plugin for interactive exploration and quality control.

Overview of Tribus
Tribus is a hierarchical framework for cell-type assignment in multiplexed image datasets based on prior
panel knowledge (Fig 1). Running Tribus requires a marker expression table and a prior knowledge-based
logic table. The logic table is defined as a data matrix $L(c_i, m_j)$ containing values $[-1,0,1]$, where c_i refers to
the cell type i_{th} and m_j refers to the marker j_{th}. If a marker is present in a specific cell type, the
corresponding value in the logic table is assigned 1. If a marker is supposed to be absent in a specific cell
type, the value in the logic table is set to -1. A score of 0 is assigned for neutral or unknown markers. Each
cell type must have at least one positive marker in the logic table (Supplementary Table 1-3).

Unsupervised clustering in Tribus
Tribus uses an unsupervised self-organizing map (SOM) method for clustering based on the MiniSOM
package (Vettigli, 2013/2023). SOM can represent a high-dimensional input space as a map consisting of
components called "nodes". Quantization error (Q) was used to evaluate the algorithm performance,
calculated by determining the average distance of the sample vectors ($\vec{x}$) to the cluster centroids ($\vec{w}$).

$$Q = \frac{1}{m}\sum_{q=1}^{m} \quad \|\vec{x}^{q} - \vec{w}_i^{q}\|^2$$

Quantization errors can only be compared under the same grid size (Pölzlbauer, n.d.). To determine the
optimal grid size, we used the approach of Vesanto (Vesanto & Alhoniemi, 2000): $G = 5\sqrt{N}$, where N is the
input data size (i.e., number of cells). The parameters of the SOM include σ (the spread of the neighborhood
function) and the learning rate. Those parameters can be set by users or optimized by minimizing the
quantization error with the hyperparameter tuning module based on the package hyperopt (Bergstra et al.,
2013), where the objective function was to minimize the quantization error, and the search space for σ and
the learning rate ranged from 0.001 to 5.
102
103 During analysis, Tribus first generates clusters/grids from the input data and then assigns each cluster to a
104 certain cell type based on the logic table. Cell type assignment is performed hierarchically, meaning Tribus
105 first assigns lower-level cell types followed by higher-level cell subtypes to create more precise categories. If
106 the number of cells in the subset exceeds the user-defined threshold, Tribus will still generate clusters.
107 Otherwise, Tribus directly calculates the scoring function for each cell type at the single-cell level.
108
109 **Cell type assignment by scoring functions**
110 After SOM clustering, a node matrix $N(n_k, v_j)$ is generated, where v_j is calculated as the median expression
111 of the marker m_j in n_k. We designed a scoring function based on the squared error concept, similar to the
112 QueryStarPlot function of the FlowSOM package (Van Gassen et al., 2015). This function calculates the
113 score s_i of a certain cell type i for each node k.

$$s_i(n_k) = \frac{1}{k}\sum_{j} \quad \left[1 - \left(v_{ij} - \widehat{v_{ij}}\right)^{2'}\right]$$

114 where,

$$\widehat{v_{ij}} = \{P_{99}(v_{ij}), \qquad L(c_i, m_j) = 1 \ min\ (v_{ij}), \qquad L(c_i, m_j) = -1$$

115
116 Instead of using the maximum value, the 99 percentile was chosen to make Tribus more robust to outliers.
117 Assigning node n_k to cell type c_i using: $c_i = argmax_{s_i} f(n_k, s_i)$. Note that the cell-type assignment process in
118 Tribus accounts for ambiguous results. If the maximum score of a cluster falls below a certain threshold, the
119 cluster is labeled as the "other" cell type. Similarly, if the difference between the maximum and second
120 maximum score is smaller than a certain threshold, the cluster will be labeled as "undefined".
121
Napari plug-in
To efficiently evaluate cell-type labeling results, we developed a custom plugin integrated with the Napari
(Ahlers, Jannis et al., 2023) framework. This plugin enables users to run Tribus on one sample at a time,
display results simultaneously, or load previously saved data. We incorporated the ZARR format to
overcome computational limitations associated with large datasets.
The key functionalities of the Napari plugin include:
(i) Cell-type mask visualization: The plugin sorts and displays different cell-type labels as separate layers
using visually distinct colors, allowing the user to overlay them with imaging data for quality control. This
function is also available in a stand-alone Jupyter Notebook.
(ii) Probability score visualization: cell masks are represented as a color gradient of the probability score
assigned by the algorithm. This allows the user to identify and review ambiguous cells and assess the
assigned "other" and "undefined" thresholds.
(iii) Marker intensity visualization: The median expression levels of the selected markers are represented
through gradient shading on the segmentation mask, enabling users to visually assess the results and
identify potential biases.
137

Methods for comparison and evaluation metrics
We compared the performance of Tribus with three similar prior knowledge-based cell-type calling tools:
ACDC, Astir, and Scyan. We evaluated overall cell type annotation performance by comparing the Rand
Index (Rand, 1971), accuracy, weighted F1 score (Powers, 2020), and Cohen's kappa coefficient. We also
compared the Matthews correlation coefficient (MCC), given the size variability of some cell types. All the
above metrics were calculated using functions provided by Scikit-learn (Pedregosa et al., 2011).
144
Benchmarking Datasets
Public datasets
We chose four public suspension mass cytometry and multiplexed imaging datasets with ground truth labels
to test the performance of Tribus (Table 1). The AML dataset contains single-cell proteomic profiles of
human bone marrow from patients with acute myeloid leukemia (AML) and healthy adult donors (Levine et
al., 2015). The "NotDebrisSinglets" cell type was excluded from the analysis. The BMMC dataset was
derived from bone marrow mononuclear cells (BMMCs) (Bendall et al., 2011). According to the research,
Erythroblasts, megakaryocyte platelets, and myelocytes were merged as an unknown population and
removed from the analysis. All "NotGated" cells were excluded (N = 61725 cells). The ductal carcinoma in
situ (DCIS) dataset containing 79 clinically annotated surgical resections (Risom et al., 2022), including
normal breast tissue (N = 9, reduction mammoplasty), primary DCIS (N = 58), and invasive breast cancer
(IBC) (N = 12). Cell types were merged into endothelial, epithelial, fibroblast, immune, and myoepithelial
during low-plex cell phenotyping. HuBMAP is a published co-detection by indexing (CODEX) imaging
dataset (Hickey et al., 2023). Only donor 004 was manually annotated and, therefore, used in this study. For
low-plex cell phenotyping, cell types were merged into epithelial, stromal, lymphoid, and myeloid.

In-house Datasets

We generated two in-house high-grade serous ovarian cancer (HGSC) datasets using t-CyCIF. The NACT
dataset contains three images: two tumor sections after neoadjuvant chemotherapy (NACT) and one
treatment-naive biopsy. The NACT dataset was stained using a 36-plex antibody panel (Supplementary
Table 4). The Oncosys-Ova dataset contains 21 HGSC samples stained with a 14-plex panel
(Supplementary Table 5). Marker expression tables were preprocessed using log transformation, z-score
normalization, 99.9 percentile outlier removal, and co-factor 5 arcsinh transformation (Hickey et al., 2021)
before phenotype assignment. In the NACT dataset, 976,082 cells were annotated using a cell phenotyping
logic table based on the panel design. For the Oncosys-Ova dataset, approximately 10.5M cells were
annotated. Following the ethical standards from the 1975 Declaration of Helsinki, every patient from
ONCOSYS-Ova trials provided informed written consent to the collection, storage, and analysis of the
samples and subsequent data. For the NACT dataset, the Mass General Brigham Institutional Review Board
approved using human tissue samples. Informed consent was waived due to the use of archival samples
and anonymization of the material.
174
Results
Tribus recovers fine-grained cell types as accurately as human experts
To evaluate Tribus's ability to recover canonical cellular populations, we applied it to the benchmark DCIS
dataset. Tribus successfully identified all populations highlighted in the study (Supplementary Fig. 1A), and
the mean marker intensities of cellular populations were similar to those of human-labeled populations (Fig.
2A). One notable difference was observed in the MACS (macrophages) population, where Tribus labels
displayed a lower median intensity of CD14 compared to manual gating. This discrepancy may be due to the
fact that CD14 was not used for MACS identification in DCIS research, and thus CD14 was not constrained
to be positive for MACS cells in the logic table. We mapped cell masks back to the original tiff images with a
nine-color overlay of cell identity-related markers. The cell masks were consistent across all major cell types
in Tribus labels and manual labels. False positive MACS in manual labels were corrected by Tribus (Fig 2B).
When comparing manual labels and Tribus labels, UMAP visualization of all cell types from DCIS datasets
showed that Tribus accurately annotated most cells (Fig. 2C). Using the manual labels as ground truth,
Tribus achieved precision scores between 0.7 and 0.8, average recalls around 0.6, and F1 scores between
0.6 and 0.7 across most cell types (Supplementary Fig. 1B). These results suggest that Tribus can recover
and annotate fine-grained cell types with a level of accuracy comparable to human experts.

Figure 2. Tribus applied on the public DCIS dataset. (A) Heatmaps showing the mean marker intensity of manually gated cell populations and Tribus classification from the DCIS dataset are similar. (B) Representative MIBI images. The upper image is from patient 3117 (DCIS tumor) with a nine-color overlay of markers related to major cell types. Cell-type masks from the manual label and Tribus show few differences. The lower image is from patient 2307 (Normal tissue) with a six-color overlay of MACS-related markers. Compared to the MACS cell masks of manual and Tribus, some MACS cells from manual labels do not have related marker expression, which was corrected in Tribus annotation (canonical marker combinations were observed). (C) UMAP representation of manual and Tribus labels on the DCIS dataset. Cell types were color-coded based on original and Tribus annotation, the same cell type label was assigned the same color. (D) Comparing (1) undefined and other cell populations with ground truth labels, (2) undefined cellular subpopulations from Tribus annotation with relevant manual labeled cell populations. (E) Heatmaps comparing the mean marker intensity of manually gated cell populations and the ambiguous cell populations from Tribus annotation.

Tribus can target ambiguous populations and discover phenotypically new subtypes
One challenge for prior knowledge-based cell-type calling methods is discovering ambiguous categories that are difficult to predefine in the logic table. For example, a group of unknown cells with low intensity across all markers. The DCIS dataset provides a good example for exploring ambiguous populations, as it includes the "IMMUNEOTHER" and "OTHER" cell types in the manual gating labels. The "OTHER" cell type has low intensities across all markers, while "IMMUNEOTHER" lacks specific immune subtype marker expression.

We verified that Tribus can successfully target ambiguous populations by adjusting the decision thresholds in the scoring function. We explored threshold settings and found Tribus is robust to different threshold values within a certain range (Supplementary Fig. 2A-B). We selected an undefined_threshold of 0.001 and an other_threshold of 0.04 for the analysis of the DCIS dataset. From the UMAP visualization, we observed that the same "IMMUNEOTHER" and "OTHER" clusters retained the same local structures (Fig. 2D). The marker expression heatmap demonstrates that Tribus-targeted ambiguous cell types share the same marker expression profiles as manually gated cell types (Fig. 2E). We also discovered new clusters, including undefined tumors, fibroblasts, T-cells, and DCs (Fig. 2D, Supplementary Fig. 1C). We found phenotypically new clusters of DCs, T-cells, and CD4 T cells using the mean marker expression heatmap (Fig. 2E). We observed novel marker expression combinations and cellular subtypes were validated by mapping cell

223 masks back to the original images. We successfully identified CD36+CD31+ fibroblasts, HER2-luminal
224 subtypes, and undefined T-cells which exhibit higher phenotypic marker expression than typical CD4 T-cells
225 (Supplementary Fig. 3 A-C). These findings demonstrate that Tribus is not only effective in identifying
226 ambiguous cell populations but also capable of discovering phenotypically novel cell subtypes. We suggest
227 that Tribus could serve as a starting point for uncovering novel cell states.
228

229 **Tribus outperforms other similar methods**
230 We benchmarked the performance of Tribus against three other approaches: ACDC, Scyan, and Astir. We
231 chose these tools for benchmarking because they are all prior knowledge-based cell phenotyping methods,
232 each designed for specific high-dimensional data types.

233
Figure 3. (A) Performance comparison of Tribus and other similar methods on four datasets (AML, BMMC,
DCIS-lowplex, DCIS, HubMAP-lowplex, HubMAP) using five metrics for each. All analyses were repeated
ten times. Using standard deviation for the error bar. (B) Models running time comparison. All analyses were
repeated ten times and used standard deviation as the error bar. (C) Compare Tribus performance under
different logic tables for the AML dataset, using standard deviation as the error bar. Each analysis was
repeated ten times. (D) Data complexity comparison over public benchmarking datasets, showing the
number of cells and Pielou's evenness index. Higher Pielou's evenness index represents high diversity and
high evenness of cell populations.

242
For AML and BMMC datasets, we used the knowledge tables provided by ACDC and Scyan. The knowledge
table was reformatted into the logic tables/YAML files accordingly for Tribus/Astir. Since no knowledge tables
were available for the DCIS and HubMAP datasets, we generated them for all methods based on the panel
information provided in the original study. The ACDC analysis was performed with the parameters
(n_neighbor = 10, thres = 0.5) from the example scripts. The parameters for the Astir analysis were chosen
(max_epochs = 1000, learning_rate = 2e-3, initial_epochs = 3) based on the tutorial provided in Colab. The
parameters for Scyan analysis were chosen based on the example provided in the GitHub repository.

250
Benchmarking experiments showed that Tribus outperformed the other methods in terms of efficiency and
accuracy. Tribus outperforms Astir, ACDC, and Scyan methods across metrics on highly multiplexed imaging
datasets, DCIS and HubMAP, in both high- and low-plex cell phenotyping. Tribus has comparable
performance on suspension mass cytometry AML and BMMC datasets compared to ACDC and Scyan,
which were designed specifically for mass cytometry datasets (Fig. 3A). On all benchmarking datasets,

Tribus exhibits a running time shorter by an order of magnitude compared to other methods (Fig. 3B). Tribus
successfully identified all cell types highlighted in the four public datasets (Supplementary Fig. 4 A-D).
258
We then explored how the structure of the logic table influenced performance. Using the AML dataset as an
example, we applied Tribus analysis with (1) a logic table with only one global level and (2) a logic table that
includes major cell types at the global level and sub-phenotypes (for example, CD16- and CD16+ NK cells)
at the second level (Supplementary Table 1-3). We repeated the Tribus analysis ten times, calculated the
average metrics, and visualized the results for each logic table configuration. When adjusting the logic table
for the AML dataset, using a hierarchical logic table improved accuracy and increased the F1 score by 0.1
(Fig. 3C).
266
267 Finally, we calculated Pielou's evenness index to illustrate the increasing complexity across benchmarking
268 datasets (Fig. 3D). Tribus's performance remained relatively good and stable from suspended single-cell
269 bone marrow datasets to highly complex human intestine slide datasets. In summary, Tribus outperformed
270 other similar methods in both accuracy and efficiency, particularly in highly multiplexed imaging datasets,
271 while maintaining robust results across different cell phenotyping contexts.
272

273 **Tribus yields rapid and accurate cell phenotyping in large whole-slide image datasets**

Figure 4. (A) Annotated barplot of the cell phenotype compositions per sample in the NACT dataset. (B) UMAP visualizes distinct cell populations colored by the major cell types in the NACT dataset. (C) UMAP visualizes distinct cell populations colored by the immune subtypes in the NACT dataset. (D) Representative tCyCIF image (sample 06) of the NACT dataset, showing the nuclei and representative tumor and immune markers. Tribus accurately identified the CD20+, CD8a+, and CD4+ populations within a Tertiary Lymphoid Structure (TLS) despite the dense organization of these sub-phenotypes. (E) The stacked barplot shows cellular proportion in all samples. (F) Stacked barplot shows various RCN proportions in samples. (G) The scatter plots show the local tissue architecture colored by cell types. (H) The Voronoi plot visualizes the structures of RCNs in the corresponding region of Figure G.

We evaluated the performance of Tribus on large in-house multiplexed image datasets. For the Oncosys-Ova dataset, we used a one-level logic table consistently across all 21 samples (Supplementary Fig. 5A). We applied a four-level logic table to the NACT dataset (Supplementary Fig. 5B).

In the NACT dataset, Tribus successfully identified major cell phenotypes and subtypes, which we characterized based on the available marker panel (Fig. 4A). The UMAP projection showed distinct cell-type populations in the NACT dataset (Fig. 4B-C) and minimal batch effects in phenotyping analysis (Supplementary Fig. 5C). The multiplexed t-CyCIF image from sample 06 of the NACT dataset displayed nuclei and representative tumor and immune markers. Tribus accurately identified the CD20+, CD8a+, and CD4+ cell populations within a Tertiary Lymphoid Structure (TLS) despite the dense organization of these sub-phenotypes (Fig. 4D). Tribus also annotated the proliferating subpopulation of tumor cells and tumor-infiltrating CD8+ cells from a dense area (Supplementary Fig. 5D), indicating that Tribus can generate accurate phenotype labels in complex tissue architectures.

In the Oncosys-Ova dataset, Tribus accurately identified six cell types with substantial cellular proportion heterogeneity among samples (Fig. 4E). UMAP projections showed separated cell populations and low batch effects (Supplementary Fig. 6A). The heatmap showed canonical marker expression combinations for each identified cellular population (Supplementary Fig. 6B). We used Scimap (Nirmal & Sorger, 2024) to calculate the fractions of neighboring cell types within a radius of 100 μm, then applied k-means clustering (k=10) on the neighborhood matrix and generated eight Recurrent cellular neighborhoods (RCN) (Fig. 4F). The RCNs are distinct spatial domains within the tissue and successfully capture relevant spatial biology based on Tribus cell phenotypes (Supplementary Fig. 6C). The representative presentation of the RCNs across tissue uncovered the complex tissue architecture such as the tumor-stromal interface and tumor-infiltrating lymphocytes cells (Supplementary Fig. 6D). Tribus-based spatial analysis enabled us to map the tumor-stromal interface in complex tumor-rich regions (Fig. 4G, Supplementary Fig.6D) and plot the stroma-resident immune cells in a stromal-rich region (Supplementary Fig.6D). These results suggested that Tribus adapts well in the workflow of cell phenotyping on large whole-slide images and downstream spatial pattern analysis.

DISCUSSION

Cell-type calling is a crucial step in high-dimensional image analysis. The growing complexity and increasing number of panels in high-dimensional data necessitate the development of reproducible and automated cell-type calling approaches. In this study, we developed Tribus, a semi-supervised cell-type calling analysis framework for multiplexed imaging datasets. Tribus offers advantages in efficiency, accuracy, user-friendliness, and reproducibility without the need for training using manual labels.

Tribus was generated as an automatic cell-type caller for high-dimensional multiplexed imaging data, incorporating biological knowledge from the panel design into the analysis. This was achieved through carefully designed scoring functions based on marker expression per grid, generated by unsupervised clustering to minimize bias. When the number of cells in the clusters was below the user-defined threshold, Tribus skipped generating the clusters and calculated scores at the single-cell level. This flexible scoring function calculation strategy enabled the discovery of rare cell types. Tribus was integrated with Napari, and a plugin was provided to enable one-click import of the cell-type identification results, significantly enhancing the simplicity of interactive quality control. This integration allows for convenient operation by users who are unfamiliar with programming.

Cell-type annotation from bioimages presents inherent challenges due to imperfect cell segmentation and collateral spillover. Expanding nuclei masks by a few pixels can enhance cytoplasmic marker visibility, as it allows better signal capture when cells express these markers. However, in dense tissue areas, this might increase spillover, highlighting the importance of the hierarchically structured logic table. Typically, mild spillover affects only part of a cell, whereas a true signal produces a more uniform expression pattern and a higher mean fluorescence intensity. Tribus was designed to account for both positive and negative components of the expected marker expression, and it also includes the option to set markers with expected false-positive expressions as neutral. Thus, careful design of the logic table and its hierarchy in Tribus can aid in cell phenotypic separation, as only a subset of cells is considered at the lower hierarchy levels during phenotype assignment.

However, Tribus is not without limitations. The performance of Tribus is strongly tied to the quality of the input dataset and the prior knowledge of expected cell types in the user-defined initial logic table. To assign a uniform logic table, the samples should have even staining patterns both within and across slides. Uneven staining patterns and antibodies with suboptimal signal-to-noise ratios can significantly affect the results. For such suboptimal datasets, users can create a hierarchical logic table where major cell phenotypes with clear marker signals are separated at higher levels. This can result in more accurate labeling if distinct areas of the image are affected. Additionally, Tribus cannot identify cell types not included in the input logic table, but it can return undefined- or other-cell types for further exploration.

Overall, we propose Tribus as a fast, accurate, and user-friendly cell-type identification method that can be integrated into multiplexed image analysis frameworks.

Competing interests
No competing interest is declared.

Author contributions statement
Z.K., A.S., T.F., and J.C. conceptualized, designed, and implemented the algorithm and software. Z.K. performed benchmarking analyses and analyzed the Oncosys-Ova dataset. A.S. analyzed the NACT in-house dataset. Z.K. and A.S. wrote the manuscript. I-M.L, F.P., E.A., and K.E. generated the in-house HRP dataset. A.V., U-M.H collected Oncosys-Ova samples. A.J., S.S. stained the Oncosys-Ova samples and performed the t-CyCIF experiment. A.F. conceived and supervised the study, provided resources, and wrote the manuscript. All authors have reviewed and approved the manuscript.

Funding
This study was co-funded by the European Union (ERC, SPACE 101076096). Views and opinions expressed are however those of the author(s) only and do not necessarily reflect those of the European Union or the European Research Council. Neither the European Union nor the granting authority can be held responsible for them. This study was also funded by the Sigrid Jusélius Foundation, Research Council of Finland (grant numbers 1339805, 350396), and Cancer Foundation Finland (A.F, F.P). The University of Helsinki Research Foundation (F.P.), Ida Montinin Säätiö (F.P.), and Biomedicum Helsinki Foundation (F.P.) also provide the funding.

Acknowledgments
We thank Prof. Sampsa Hautaniemi for his helpful feedback on the manuscript and the IT Center for Science (CSC) for the computational resources. The graphical overview was created with Biorender.com.

Data and code availability
The Tribus package is publicly available on Github: https://github.com/farkkilab/tribus. The datasets and scripts used to repeat the results are publicly available at Synapse: https://www.synapse.org/Synapse:syn53754523/files/.

REFERENCES

Abdelaal, T., van Unen, V., Höllt, T., Koning, F., Reinders, M. J. T., & Mahfouz, A. (2019). Predicting Cell Populations in Single Cell Mass Cytometry Data. *Cytometry Part A*, *95*(7), 769–781. https://doi.org/10.1002/cyto.a.23738

Ahlers, Jannis, Althviz Moré, Daniel, Amsalem, Oren, Anderson, Ashley, Bokota, Grzegorz, Boone, Peter, Bragantini, Jordão, Buckley, Genevieve, Burt, Alister, Bussonnier, Matthias, Can Solak, Ahmet, Caporal, Clément, Doncila Pop, Draga, Evans, Kira, Freeman, Jeremy, Gaifas, Lorenzo, Gohlke, Christoph, Gunalan, Kabilar, Har-Gil, Hagai, … Yamauchi, Kevin. (2023). *napari: A multi-dimensional image viewer for Python* (v0.4.18) [Computer software]. Zenodo. https://doi.org/10.5281/ZENODO.8115575

Amitay, Y., Bussi, Y., Feinstein, B., Bagon, S., Milo, I., & Keren, L. (2023). CellSighter: A neural network to classify cells in highly multiplexed images. *Nature Communications*, *14*(1), 4302. https://doi.org/10.1038/s41467-023-40066-7

Bendall, S. C., Simonds, E. F., Qiu, P., Amir, E. D., Krutzik, P. O., Finck, R., Bruggner, R. V., Melamed, R., Trejo, A., Ornatsky, O. I., Balderas, R. S., Plevritis, S. K., Sachs, K., Pe'er, D., Tanner, S. D., & Nolan, G. P. (2011). Single-Cell Mass Cytometry of Differential Immune and Drug Responses Across a Human Hematopoietic Continuum. *Science*, *332*(6030), 687–696. https://doi.org/10.1126/science.1198704

Bergstra, J., Yamins, D., & Cox, D. (2013). Making a Science of Model Search: Hyperparameter Optimization in Hundreds of Dimensions for Vision Architectures. *Proceedings of the 30th International Conference on Machine Learning*, 115–123. https://proceedings.mlr.press/v28/bergstra13.html

Black, S., Phillips, D., Hickey, J. W., Kennedy-Darling, J., Venkataraaman, V. G., Samusik, N., Goltsev, Y., Schürch, C. M., & Nolan, G. P. (2021). CODEX multiplexed tissue imaging with DNA-conjugated antibodies. *Nature Protocols*, *16*(8), Article 8. https://doi.org/10.1038/s41596-021-00556-8

Blampey, Q., Bercovici, N., Dutertre, C.-A., Pic, I., Ribeiro, J. M., André, F., & Cournède, P.-H. (2023). A biology-driven deep generative model for cell-type annotation in cytometry. *Briefings in Bioinformatics*, *24*(5), bbad260. https://doi.org/10.1093/bib/bbad260

Ester, M., Kriegel, H.-P., Sander, J., & Xu, X. (1996). A density-based algorithm for discovering clusters in large spatial databases with noise. *Proceedings of the Second International Conference on Knowledge Discovery and Data Mining*, 226–231.

Geuenich, M. J., Hou, J., Lee, S., Ayub, S., Jackson, H. W., & Campbell, K. R. (2021). Automated assignment of cell identity from single-cell multiplexed imaging and proteomic data. *Cell Systems*, *12*(12), 1173-1186.e5. https://doi.org/10.1016/j.cels.2021.08.012

Hickey, J. W., Becker, W. R., Nevins, S. A., Horning, A., Perez, A. E., Zhu, C., Zhu, B., Wei, B., Chiu, R., Chen, D. C., Cotter, D. L., Esplin, E. D., Weimer, A. K., Caraccio, C., Venkataraaman, V., Schürch, C. M., Black, S., Brbić, M., Cao, K., … Snyder, M. (2023). Organization of the human intestine at single-cell resolution. *Nature*, *619*(7970), Article 7970. https://doi.org/10.1038/s41586-023-05915-x

Hickey, J. W., Tan, Y., Nolan, G. P., & Goltsev, Y. (2021). Strategies for Accurate Cell Type Identification in CODEX Multiplexed Imaging Data. *Frontiers in Immunology*, *12*, 727626. https://doi.org/10.3389/fimmu.2021.727626

Keren, L., Bosse, M., Thompson, S., Risom, T., Vijayaragavan, K., McCaffrey, E., Marquez, D., Angoshtari, R., Greenwald, N. F., Fienberg, H., Wang, J., Kambham, N., Kirkwood, D., Nolan, G., Montine, T. J., Galli, S. J., West, R., Bendall, S. C., & Angelo, M. (2019). MIBI-TOF: A multiplexed imaging platform relates cellular phenotypes and tissue structure. *Science Advances*, *5*(10), eaax5851. https://doi.org/10.1126/sciadv.aax5851

Kohonen, T. (1982). Self-organized formation of topologically correct feature maps. *Biological Cybernetics*, *43*(1), 59–69. https://doi.org/10.1007/BF00337288

Lee, H.-C., Kosoy, R., Becker, C. E., Dudley, J. T., & Kidd, B. A. (2017). Automated cell type discovery and classification through knowledge transfer. *Bioinformatics*, *33*(11), 1689–1695. https://doi.org/10.1093/bioinformatics/btx054

Levine, J. H., Simonds, E. F., Bendall, S. C., Davis, K. L., Amir, E. D., Tadmor, M. D., Litvin, O., Fienberg, H. G., Jager, A., Zunder, E. R., Finck, R., Gedman, A. L., Radtke, I., Downing, J. R., Pe'er, D., & Nolan, G. P. (2015). Data-Driven Phenotypic Dissection of AML Reveals Progenitor-like Cells that Correlate with Prognosis. *Cell*, *162*(1), 184–197. https://doi.org/10.1016/j.cell.2015.05.047

Lin, J.-R., Izar, B., Wang, S., Yapp, C., Mei, S., Shah, P. M., Santagata, S., & Sorger, P. K. (2018). Highly
multiplexed immunofluorescence imaging of human tissues and tumors using t-CyCIF and
conventional optical microscopes. *eLife*, *7*, e31657. https://doi.org/10.7554/eLife.31657
Liu, X., Song, W., Wong, B. Y., Zhang, T., Yu, S., Lin, G. N., & Ding, X. (2019). A comparison framework and
guideline of clustering methods for mass cytometry data. *Genome Biology*, *20*(1), 297.
https://doi.org/10.1186/s13059-019-1917-7
Nirmal, A. J., & Sorger, P. K. (2024). SCIMAP: A Python Toolkit for Integrated Spatial Analysis of Multiplexed
Imaging Data. Journal of Open Source Software, 9(97), 6604. https://doi.org/10.21105/joss.06604
Pedregosa, F., Varoquaux, G., Gramfort, A., Michel, V., Thirion, B., Grisel, O., Blondel, M., Prettenhofer, P.,
Weiss, R., Dubourg, V., Vanderplas, J., Passos, A., Cournapeau, D., Brucher, M., Perrot, M., &
Duchesnay, É. (2011). Scikit-learn: Machine Learning in Python. *Journal of Machine Learning*
Research, *12*(85), 2825–2830.
Pölzlbauer, G. (n.d.). *Survey and Comparison of Quality Measures for Self-Organizing Maps*.
Powers, D. M. W. (2020). *Evaluation: From precision, recall and F-measure to ROC, informedness,*
markedness and correlation (arXiv:2010.16061). arXiv. https://doi.org/10.48550/arXiv.2010.16061
Rand, W. M. (1971). Objective Criteria for the Evaluation of Clustering Methods. *Journal of the American*
Statistical Association, *66*(336), 846–850. https://doi.org/10.1080/01621459.1971.10482356
Risom, T., Glass, D. R., Averbukh, I., Liu, C. C., Baranski, A., Kagel, A., McCaffrey, E. F., Greenwald, N. F.,
Rivero-Gutiérrez, B., Strand, S. H., Varma, S., Kong, A., Keren, L., Srivastava, S., Zhu, C., Khair, Z.,
Veis, D. J., Deschryver, K., Vennam, S., … Angelo, M. (2022). Transition to invasive breast cancer is
associated with progressive changes in the structure and composition of tumor stroma. *Cell*, *185*(2),
299-310.e18. https://doi.org/10.1016/j.cell.2021.12.023
Schapiro, D., Sokolov, A., Yapp, C., Chen, Y.-A., Muhlich, J. L., Hess, J., Creason, A. L., Nirmal, A. J.,
Baker, G. J., Nariya, M. K., Lin, J.-R., Maliga, Z., Jacobson, C. A., Hodgman, M. W., Ruokonen, J.,
Farhi, S. L., Abbondanza, D., McKinley, E. T., Persson, D., … Sorger, P. K. (2022). MCMICRO: A
scalable, modular image-processing pipeline for multiplexed tissue imaging. *Nature Methods*, *19*(3),
311–315. https://doi.org/10.1038/s41592-021-01308-y
Shaban, M., Bai, Y., Qiu, H., Mao, S., Yeung, J., Yeo, Y. Y., Shanmugam, V., Chen, H., Zhu, B., Weirather,
J. L., Nolan, G. P., Shipp, M. A., Rodig, S. J., Jiang, S., & Mahmood, F. (2024). MAPS: Pathologist-
level cell type annotation from tissue images through machine learning. *Nature Communications*,
15(1), 28. https://doi.org/10.1038/s41467-023-44188-w
Spitzer, M. H., & Nolan, G. P. (2016). Mass Cytometry: Single Cells, Many Features. *Cell*, *165*(4), 780–791.
https://doi.org/10.1016/j.cell.2016.04.019
Staats, J., Divekar, A., McCoy, J. P., & Maecker, H. T. (2019). Guidelines for Gating Flow Cytometry Data for
Immunological Assays. In J. McCoy J. Philip (Ed.), *Immunophenotyping: Methods and Protocols* (pp.
81–104). Springer. https://doi.org/10.1007/978-1-4939-9650-6_5
Traag, V. A., Waltman, L., & van Eck, N. J. (2019). From Louvain to Leiden: Guaranteeing well-connected
communities. *Scientific Reports*, *9*(1), Article 1. https://doi.org/10.1038/s41598-019-41695-z
Van Gassen, S., Callebaut, B., Van Helden, M. J., Lambrecht, B. N., Demeester, P., Dhaene, T., & Saeys, Y.
(2015). FlowSOM: Using self-organizing maps for visualization and interpretation of cytometry data.
Cytometry Part A, *87*(7), 636–645. https://doi.org/10.1002/cyto.a.22625
Verschoor, C. P., Lelic, A., Bramson, J. L., & Bowdish, D. M. E. (2015). An Introduction to Automated Flow
Cytometry Gating Tools and Their Implementation. *Frontiers in Immunology*, *6*.
https://www.frontiersin.org/articles/10.3389/fimmu.2015.00380
Vesanto, J., & Alhoniemi, E. (2000). Clustering of the self-organizing map. *IEEE Transactions on Neural*
Networks, *11*(3), 586–600. https://doi.org/10.1109/72.846731
Vettigli, G. (2023). *MiniSom* [Python]. https://github.com/JustGlowing/minisom (Original work published
2013)
Xie, B., Jiang, Q., Mora, A., & Li, X. (2021). Automatic cell type identification methods for single-cell RNA
sequencing. *Computational and Structural Biotechnology Journal*, *19*, 5874–5887.
https://doi.org/10.1016/j.csbj.2021.10.027