Fast and accurate imputation of genotypes from noisy low-coverage sequencing data in bi-parental populations

Cécile Triay[1,§] & Alice Boizet[2,§], Christopher Fragoso[3,4], Anestis Gkanogiannis[5], Jean-François Rami[2], Mathias Lorieux[1,5,*]

[1]DIADE, University of Montpellier, IRD, Cirad, Montpellier, France
[2]AGAP, University of Montpellier, Cirad, INRAE, Montpellier SupAgro, Montpellier, France
[3]Verinomics, Inc., 5 Science Park, New Haven, CT 06511, USA
[4]Department of Molecular, Cellular, and Developmental Biology, Yale University, New Haven, Connecticut 06511
[5]Agrobiotechnology Unit, Alliance Bioversity-CIAT, International Center for Tropical Agriculture, Cali, Colombia.
[*]Corresponding author
[§]Equivalent contribution

Abstract

Motivation: Genotyping of bi-parental populations can be performed with low-coverage next-generation sequencing (LC-NGS). This allows the creation of highly saturated genetic maps at reasonable cost, precisely localized recombination breakpoints (i.e., the crossovers), and minimized mapping intervals for quantitative-trait locus analysis.

The main issues with these low-coverage genotyping methods are (1) poor performance at heterozygous loci, (2) high percentage of missing data, (3) local errors due to erroneous mapping of sequencing reads and reference genome mistakes, and (4) global, technical errors inherent to NGS itself.

Recent methods like Tassel-FSFHap or LB-Impute are excellent at addressing issues 1 and 2, but nonetheless perform poorly when issues 3 and 4 are persistent in a dataset (i.e., "noisy" data). Here, we present a new algorithm for imputation of LC-NGS data that eliminates the need of complex pre-filtering of noisy data, accurately types heterozygous chromosomal regions, precisely estimates crossover positions, corrects erroneous data, and imputes missing data. The imputation of genotypes and recombination breakpoints is based on maximum-likelihood estimation. We compare its performance with Tassel-FSFHap and LB-Impute using simulated data and two real datasets. Furthermore, the algorithm is much faster than Hidden Markov Model methods.

Availability: NOISYmputer and its source code are available as a multiplatform (Linux, macOS, Windows) Java executable at the URL
https://gitlab.cirad.fr/noisymputer/noisymputerstandalone/-/tree/1.0.0-RELEASE?ref_type=tags.

Introduction

In genetic studies, bi-parental genetic populations can be created from inbred parental lines using various crossing systems, e.g., F_2 intercross issued from F_1 self-pollination (F_2) and recombinant inbred lines by single seed descent (SSD). These populations are used to create recombination maps and, if phenotypes are available, to find gene or quantitative-trait locus (QTL) genomic positions.

To do so, each individual of the population under study has to be characterized for its genomic content – or "genotyped" at many loci. This can be done using different molecular biology techniques, including various types of molecular markers. The gold standard for genetic variant discovery is obtained by different next-generation sequencing (NGS) techniques like restriction site-associated DNA sequencing (RADseq) (Davey and Blaxter 2010), genotyping by sequencing (GBS) (Elshire *et al.* 2011), and whole-genome sequencing (WGS) (Huang *et al.* 2009). These techniques provide very large numbers of markers and therefore facilitate the construction of highly saturated genetic maps. This provides accurate locations of recombination breakpoints in each individual, which is important for a number of applications, e.g., studies of

local recombination rate, genetic maps comparison, or QTL detection. Though NGS is less and less expensive to implement, sequencing a large number of samples can still be costly, and is commonly applied via reduced representation (RRS-NGS) or low-coverage (LC-NGS) strategies to reduce genotyping costs.

Reducing sequencing costs through minimized per-sample coverage has an important experimental downside: LC-NGS mechanically introduces a series of issues, the main ones being:

- **Issue 1:** *Low power to detect heterozygosity under low coverage*: For example, if only one sequencing read is generated at a locus, only one of the two alleles is revealed. As each additional read has a 0.5 probability of detecting the second allele, even 3 reads have only 0.75 probability of detecting a heterozygous call. Spread over thousands of sites, extensive inaccuracy in heterozygous regions becomes highly problematic.

- **Issue 2:** *Extensive genotype missingness*: The sparse distribution of reads at low coverage (3X coverage, for example, only implies an *average* of 3 reads per site) results in a complete lack of reads at some variant loci. Even in plants, which contain more genetic variation than humans, there are 6-22 SNPs per 1 Kb, resulting in abundant opportunity for non-reference variant missingness under low coverage (Xu *et al.* 2017).

- **Issue 3:** *Errors due to erroneous mapping of sequencing reads*: NGS technologies are based on short reads (e.g., 150 base pair, paired-end Illumina technology). Due to the combinatorial limitation of the sequence contained in short reads, multiple mapping locations may be identified, especially in plant genomes which exhibit much more repetitive content than human genomes. Additionally, in plants, such as rice, structural variation specific to subpopulations may be completely missing in single reference genomes. These assembly errors, omissions, and challenges posed by repetitious regions are sources of erroneous variants. Moreover, outright assembly errors may cause consistent, yet locally encountered genotyping errors.

- **Issue 4:** *Technical errors inherent to NGS methodology*: Sequencing errors may be globally introduced at a variety of stages in the NGS pipeline, from errors incurred in PCR-dependent library construction to NGS sequencing itself. The initial GBS protocol is known to generate libraries contaminated by chimeric inserts (Heffelfinger *et al.* 2014). Although rare, these errors may become problematic at low coverage, as additional reads refuting an erroneous call may not be available at a given locus.

Common imputation algorithms implemented in computer programs like Beagle (Browning and Browning 2007; Browning *et al.* 2021) or Impute2 (Howie *et al.* 2012), although very accurate in diversity panels, are not well adapted to the bi-parental context since they rely on large databases to infer haplotypes. Efficient methods have been recently developed to impute genotypic data derived from LC-NGS assays in bi-parental populations. For instance, Tassel-FSFHap (thereafter simply FSFHap) (Swarts *et al.* 2014) and LB-Impute (Fragoso *et al.* 2016) can all address issues 1 and 2 accurately. Yet, these methods can produce inaccurate results when the errors mentioned in issues 3 and 4 – thereafter called "noisy data" – are too frequent. Thus, these methods might require additional bioinformatic steps to filter out low-quality markers before and after imputation. Even then, troublesome markers might not be detected easily and could alter dramatically the quality of the imputation and the final genetic map.

In this work, we present NOISYmputer, a maximum likelihood estimation algorithm for imputation of LC-NGS data that eliminates the need of complex pre-filtering of noisy data, accurately finds heterozygous chromosomal regions, corrects erroneous data, imputes missing data and precisely locates the recombination breakpoints (i.e., the meiotic crossovers). We test its accuracy using simulated data and we compare its performance with FSFHap, LB-Impute using three datasets: (1) a rice F_2 population sequenced by WGS, (2) a maize F_2 population sequenced by GBS and (3) 84 simulated F_2 populations with controlled depth, error rate and marker density. The algorithm is implemented in NOISYmputer, a multiplatform Java command line program (see "Availability" section).

91 Design and implementation

92 Imputation method

In this section we describe the main imputation algorithm, which is applied separately to each chromosome.
The imputation can be preceded or followed by different filtering options in NOISYmputer (details in next
section) that can be applied to reduce or eliminate the noise in the data (Figure 1).

By imputation, we mean here guessing, confirming or correcting the genotype at a SNP site in a sample.
LC-NGS generates poor information in heterozygous regions (see explanation on the confounding effect in
SNPs with one or few reads – issue 1 of the Introduction section). Conversely, homozygous regions are much
less prone to these confounding effects. Yet, missing data (issue 2), noisiness (issue 3) and sequencing errors
(issue 4) can lower the power to identify homozygous diplotypes (*i.e.,* the combination of two gametic
haplotypes). The general idea of the algorithm is, like in Hidden Markov Model (HMM), to use information of
various SNPs around the imputed SNP, leaving unimputed the regions surrounding the recombination
breakpoints laying between the two diplotypes. The locations of the recombination breakpoints are then
inferred. Furthermore, instead of modeling error rates, we take an iterative approach to estimate them (Figure
1).

106 Imputation - Step 1: Genotype calling

Let's consider a chromosome of an F_2 individual with one single recombination breakpoint that separates a
homozygous diplotype (AA; BB) from a heterozygous diplotype (AB, or BA, equivalent thereafter). Let's also
consider a set of SNPs evenly dispersed on the physical genome, say, every 500 base pairs (bp). In the AA
diplotype, and far from the breakpoint location, all SNPs should be genotyped as AA, except from the different
kinds of errors cited above. To determine the genotype of a particular SNP, and due to these errors, one must
consider not only its score in the VCF, but also its immediate "environment", that is, the SNPs that are located
just before and just after it along the chromosome. Those surrounding SNPs help identify a potential error in
the SNP scoring. Different approaches can be taken to look at the SNP environment. In segregating
populations, the vast majority of the genome is exempt from crossing overs. Indeed, when implementing a
sliding window method like described hereby, the expected proportion of the genome with no recombination
in the window is $P_{noXO} \approx 1 - \left(\frac{1}{100N}\right)D(8m - 2)$, where m is the number of SNPs in the sliding window, N is
the total number of SNPs, and D is the expected genome size in centimorgans (cM). Hence, in almost the entire
genome except the breakpoint regions there are only two or three possible diplotypes, depending on the
population type. Thus, instead of calculating all the likelihoods of possible paths (like in Hidden Markov Model
methods), the problem is reduced to calculate the likelihoods of the data for the three possible diplotypes.
Furthermore, there is no need to include transition (*i.e.*, recombination) probabilities. The main advantage of
this approach is its computation time, which increases linearly according to the diplotype size, while the time
complexity is $O(T \times S^2)$ for the Viterbi algorithm applied to resolve fully connected Hidden Markov Model
processes, with T being the length of the sequence of observations and S being the number of hidden states.
We now describe the algorithm with the example of an F_2 population.

In practice, one defines starting values for error rates for reads A (e_A) and B (e_B), being respectively the
probability of observing a B read (O_B) whereas the genotype is truly AA and observing an A read (O_A) whereas
the genotype is truly a BB

$$e_A = p\left(O_B|AA\right) \qquad e_B = p\left(O_A|BB\right)$$

131 We allow different error rates for A and B reads since the A and B parents are generally not equally
132 (genetically) distant from the reference genome. For example, once could set $e_A = 0.005$ and $e_B = 0.003$ if
133 Parent B is closer genetically to the Reference genome than Parent A is. Those values will be automatically
134 refined after one or several rounds of imputation.

135 Thus, at homozygous sites, the probability of observing an A read if the true genotype is AA is

$$p\left(O_A|AA\right) = 1 - e_A$$

Figure 1. NOISYmputer's workflow. It is composed of three major phases: pre-imputation, imputation and post-imputation. Some steps are optional (dashed borders) while others are required for the algorithm to complete.

140 and the probability of observing a B read if the true genotype is BB is

141
$$p\left(O_B|BB\right) = 1 - e_B$$

142 At heterozygous (AB) sites, and assuming that the A and B reads have the same chance to occur, the
143 probabilities of observing A and B reads are

144
$$p\left(O_A|AB\right) = \frac{1}{2} p(O_A|AA) + \frac{1}{2} p(O_A|BB) = \frac{1}{2}(1 - e_A) + \frac{1}{2} e_B$$

145
$$p\left(O_B|AB\right) = \frac{1}{2} p(O_B|BB) + \frac{1}{2} p(O_B|AA) = \frac{1}{2}(1 - e_B) + \frac{1}{2} e_A$$

Let's consider a chromosome with n SNPs. For each site SNP_j of the chromosome, we define a symmetrical
window (W_j) containing the SNP_j at its center, m SNPs before it in the sequence and m SNPs after it (with read
count > 0). SNPs that are located in chromosome ends are omitted, since it is not possible to define
symmetrical windows around them. This case is discussed later on.

For each site SNP_i of the W_j window three situations are possible: i) the genotype G_i of the SNP_i is AA
(homozygous for parent A allele), ii) the genotype G_i is BB (homozygous for parent B allele) or iii) the
genotype G_i is AB (heterozygous).

By using the binomial distribution with sample size equal to n_i and the number of successes equal to nA_i (and
thus of fails equal to nB_i), we estimate the likelihood of observing a given combination of reads (nA_i and nB_i
as $n_i = nA_i + nB_i$) at SNP_i, knowing already the probability of observing A reads under the three possible
genotypes:

157
$$P[nA_i | p(O_A| AA)] = \binom{n_i}{nA_i} p(O_A | AA)^{nA_i} (1 - p(O_A | AA))^{n_i - nA_i} = \binom{n_i}{nA_i} p(O_A | AA)^{nA_i} p(O_B | AA)^{nB_i}$$

158
$$P[nA_i | p(O_A| BB)] = \binom{n_i}{nA_i} p(O_A | BB)^{nA_i} (1 - p(O_A | BB))^{n_i - nA_i} = \binom{n_i}{nA_i} p(O_A | BB)^{nA_i} p(O_B | BB)^{nB_i}$$

159
$$P[nA_i | p(O_A| AB)] = \binom{n_i}{nA_i} p(O_A | AB)^{nA_i} (1 - p(O_A | AB))^{n_i - nA_i} = \binom{n_i}{nA_i} p(O_A | AB)^{nA_i} p(O_B | AB)^{nB_i}$$

160 Since the binomial factor is the same for the three possible genotypes, it can be omitted in the calculations.
161 Then, individual relative probabilities that the genotype G_i of the SNP_i is AA, BB or AB are defined as:

162
$$p\left(G_i = X\right) = P[nA_i | p(O_A | X)] / \sum_X P[nA_i | p(O_A | X)], \text{ with } X = AA, BB, AB$$

163 The probabilities for the window's diplotype around the SNP_j to be AA, BB or AB are obtained by multiplying
164 the individual probabilities of all the SNPs in the window. As multiplication of probabilities can result in very
165 small numbers, we add their logarithms instead to avoid reaching the precision limit of the computer:

166
$$\rho_X = \sum_{i = SNP_j - m}^{SNP_j + m} log\left[p\left(G_i = X\right)\right], \text{ with } X = AA, BB, AB$$

167 Finally, the relative probabilities for the window's W_j around the SNP_j to be AA, BB or AB are defined as:

168
$$P\left(W_j = AA\right) = exp\left(\rho_{AA}\right)/\left(exp\left(\rho_{AA}\right) + exp\left(\rho_{BB}\right) + exp\left(\rho_{AB}\right)\right)$$

169
$$P\left(W_j = BB\right) = exp\left(\rho_{BB}\right)/\left(exp\left(\rho_{AA}\right) + exp\left(\rho_{BB}\right) + exp\left(\rho_{AB}\right)\right)$$

170
$$P\left(W_j = AB\right) = exp\left(\rho_{AB}\right)/\left(exp\left(\rho_{AA}\right) + exp\left(\rho_{BB}\right) + exp\left(\rho_{AB}\right)\right)$$

A genotype is assigned to the SNP j if the relative probability of its surrounding window is superior to a given
threshold α. To guarantee that no SNP is falsely genotyped, the α threshold is set to a very stringent value
(0.999 by default). SNPs with $P\left(W_j\right) < α$ for all genotypes are assigned a missing data value.

We repeat the process for each SNP j of the chromosome. For chromosome ends, the procedure is similar
except that the half-window on the end side is smaller due to the lack of sites available to the left or right of
SNP_j.

This leaves two types of chromosomal regions unimputed and filled with missing data: 1) regions between
imputed chromosome segments with identical diplotypes and for which none of the criteria are matched to
assign a genotype, and 2) regions near recombination breakpoints.

Imputation - Step 2: Gap filling and error rate estimation

Step 2 consists in (i) filling the unimputed regions with the surrounding genotype, with the condition that they
are surrounded (left and right) by identical imputed genotypes, then (ii) re-estimating error rates.

The filling procedure assumes that a double recombination event is very unlikely. The maximum region size
that is allowed for data filling can be calculated using the local recombination rate, which is calculated from
the data of the entire F_2 population, imputed from Step 1. So, regions larger than the maximum size are left
unimputed. It is desirable to use an interference model to estimate the distances (in cM), for instance the one
implemented in the Kosambi mapping function (Kosambi 1944). The method employed in NOISYmputer to
estimate recombination fractions in F_2 populations is the standard Expectation-Maximization algorithm
(Dempster *et al.* 1977).

Let's take the example of two SNPs A and C that define the bounds of such a region. They are separated by the
genetic distance d (cM). The maximum probability of a double crossover can be calculated as follows. We first
search for the SNP B that is the closest to the middle point between A and C (in cM). Then, we calculate the
recombination fractions r_{AB} and r_{BC} from d_{AB} and d_{BC} using the inverse of the Kosambi mapping function

194
$$r = \frac{1}{2}tanh(2d/100)$$

195 Note that $r \approx \frac{d}{100}$ when $d < 15$ cM. In the case of highly saturated maps, this formula can be used in most
196 intervals.

197 Then the maximum probability of the missing data to be different to the surrounding genotype is

198
$$r_{ABC} = r_{AB}r_{BC} + r_{AB}^2 r_{BC}^2 \approx r_{AB}r_{BC} \text{ if SNPs A and C are homozygous}$$

199
$$r_{ABC} = 2\,r_{AB}r_{BC} + r_{AB}^2 r_{BC}^2 \approx 2\,r_{AB}r_{BC} \text{ if SNPs A and C are heterozygous}$$

200 The regions for which $r_{ABC} \leq α$ are filled with the surrounding genotype; α is set to 0.001 by default.

201 This step leaves the breakpoint regions unimputed.

202 We can then estimate new values for e_A and e_B by comparing the observed data with the newly imputed

203 regions. This is done by simply counting the proportion of A reads in BB-imputed segments, and the
204 proportion of B reads in AA-imputed segments.

Imputation - Step 3: Locating recombination breakpoints

Step 3 consists in imputing the SNP genotypes in the regions near the recombination breakpoints – i.e.,
between diplotypes of different states. The general idea is to determine an interval of high probability of
presence (loose support interval) of the breakpoint, then to calculate the likelihood of the data under the
hypothesis of a recombined segment.

This procedure allows determining with high confidence a loose support interval where the recombination
breakpoint is located. Here we take the example of a segment BB to the left of the breakpoint and a segment
AB to the right. Since we already know from Step 1 which are the two genotypes at the left and the right of the
breakpoint, we only need to consider the only two possible diplotypes, BB and AB. This saves one degree of
freedom.

If k defines the closest SNP position to the point where $p(W_j = BB) = p(W_j = AB)$ in Step 1, we take $k - 2m$
and $k + 2m$ as starting points to guarantee that the breakpoint is covered by the interval. Then, for each SNP_j
of the scanned area, we recalculate $p(W_j = BB)$ and $p(W_j = AB)$, but this time in asymmetric windows of size
m, that is, for BB, we define a window from SNP_j to $SNP_j + m$ and for AB a window from $SNP_j - m$ to SNP_j.
And then, following calculations similar to Step 1 but omitting the probabilities for the AA genotype:

$$p(W_j = BB) = exp(\rho_{BB})/(exp(\rho_{BB}) + exp(\rho_{AB})) \text{ in the B window}$$

$$p(W_j = AB) = exp(\rho_{AB})/(exp(\rho_{BB}) + exp(\rho_{AB})) \text{ in the H window}$$

Starting from $k - 2m$, and progressing to the right, we look for the first site SNP_j for which :

$$P_{SI} = (1 - p(W_j = BB))(1 - p(W_j = AB)) > \alpha_{SI}, \text{ with } \alpha_{SI} = 0.05 \text{ by default.}$$

The breakpoint loose support interval is defined between the first position from the left (k_L) and from right
(k_R) where $P_{SI} > \alpha_{SI}$.

The breakpoint support interval and position are then estimated within the loose support interval. To do so,
for each SNP_j in the breakpoint interval k_L to k_R, a probability P_{bkp} that the diplotype's window contains a
breakpoint in its middle is estimated. We define a left window for $p_{bkp}(W_j = BB)$ that includes the SNP_j and
goes to the left until the window's data count reaches $m/2$ SNPs with at least one read (the left boundary of
this window is called m_L) and a right window for $p_{bkp}(W_j = AB)$ that starts at $SNP_j + 1$ and goes to the right
until the window's data count reaches $m/2$ SNPs with at least one read (the right boundary of this window is
called m_R). Values of m_L and m_R are recalculated for each SNP_j.

The log-probabilities for the left and right segments are:

$$\rho_{bkp}(W_j = BB) = \sum_{i=m_L}^{j} log[p(G_i = BB)]$$

$$\rho_{bkp}(W_j = AB) = \sum_{i=j+1}^{m_R} log[p(G_i = AB)]$$

Then, the probability that the SNP_j and SNP_{j+1} are surrounding the breakpoint is:

$$p_{bkp}(BK_j) = exp(\rho_{bkp}(W_j = BB) + \rho_{bkp}(W_j = AB))$$

And after normalization:

$$P_{bkp}(BK_j) = p_{bkp}(BK_j) / max(p_{bkp}(BK_z): z = k_L, ..., k_R)$$

The breakpoint is estimated in the middle of the interval defined by the SNP having the maximal $P_{bkp}(BK_j)$
and the next SNP to its right.

Finally, the unimputed genotypes in the breakpoint area are completed in assigning the BB genotype to the
SNPs to the left of the SNP with the max $P_{bkp}(BK_j)$ (included) and AB to the right.

Imputation of breakpoint positions for the other types of homozygous-heterozygous transitions (AB→BB,

AA→AB, AB→AA) are easily derived from the example beforehand.

The support interval for the breakpoint around its most likely position can be defined in searching for the
SNPs (left and right starting from the SNP with the maximum $P_{bkp}(BK_j)$) for which $- log_{10}\left(P_{bkp}\left(BK_j\right)\right) \geq \alpha_{drop}$
, where α_{drop} is the dropping value of P_{bkp}. α_{drop} is set to 1 by default, corresponding to ten-fold decrease of
P_{bkp} compared with $P_{bkp}\left(BK_j\right)$.

250 Filtering options – before imputation

251 Genotypic frequencies, heterozygosity, missing data

The program can filter out SNPs for parental genotypes, and progeny heterozygosity, percentage of missing
data and parental genotypic frequencies. Min and max filtering values can be manually entered (though
usually not recommended), or the program can calculate them from the genotype matrix imported from the
VCF. In this case, genotypic frequencies are calculated for each SNP, and the filter values are derived from the
extreme percentiles of the frequency distribution. Correction factors can be applied to the percentiles, to avoid
too small or too large values.

258 Read counts

259 SNPs with too few or too many reads can be eliminated. This can be useful to, for instance, remove SNPs in
260 duplicated regions.

261 Incoherent SNPs

In sequence-based genetic mapping, it is common to observe SNPs that do not segregate the same way as their
immediate environment, indicating a probable mapping error due to, for instance, structural variation
between the reference genome and the population parents, or between the parents, or both. As segregation
distortion is a frequent phenomenon in many organisms, the Mendelian expected frequencies cannot be used
to analyze the SNP segregation. Instead, the procedure defines a window of n SNPs around each tested locus.
By default, n=1% the number of SNPs in the largest chromosome. For each window/SNP couple, it calculates
the genotypes AA, BB and AB frequencies and the reads A and B frequencies across the population from the
genotypes called in the VCF and compares the SNP with the window segregation of genotypes and reads using
a chi-square test, where expected counts are the observed frequencies in the window multiplied by the
population size. It then filters out SNPs for which the chi-square statistic exceeds a defined threshold for
genotypes or reads frequencies.

273 Filtering options – after imputation

274 Incoherent chromosome segments (single individual)

Even after imputation and the different filtering operations, some few, improbable chromosome short
diplotypes can still remain in the imputed matrix – we call them "small chunks". The procedure identifies each
small chunk composed of identical alleles, embedded in a homogeneous genomic environment that has a
different allele. The method resembles the one used in Imputation - Step2.

Consider two SNPs A and C that define the bounds of a region imputed as H and surrounded by regions
imputed as A or B. Search for the SNP B that is the closest to the middle point between A and C (in cM). Also
search for an SNP D before the SNP A so that $d_{DA} \sim d_{AB}$, and an SNP E *after* the SNP C so that $d_{CE} \sim d_{BC}$.

Then, calculate the recombination fractions r_{DB} and r_{BE} from d_{DB} and d_{BE} using the inverse of the Kosambi
mapping function. Then the maximum probability of the "chunk" to be different to the surrounding genotype
is

$$285 \qquad\qquad\qquad\qquad r_{ABC} = r_{DB} r_{BE}$$

286 The chunks for which $r_{ABC} \leq \alpha$ are restored with the surrounding genotype; α is set to 0.001 by default.

287 Incoherent chromosome segments (cross-population)

Entire chromosome segments can be misplaced due to different kinds of genomic structural variation such as
translocation, or duplication in one of the two parents that is not present in the reference genome. Such
segments are called "aliens" in the program. If their size is too large, the chi-square procedure that filters out
the incoherent SNPs may fail to identify them since it is run *before* the imputation. Alien segments are easily
detected, as they produce severe map expansion. The procedure searches for SNPs that mark rapid changes in
the slope of the cumulated centimorgans of the genetic map calculated from the imputed matrix. If a SNP
marker is detected, the procedure then searches for the next SNP that is closely linked (by default $r < 0.01$) to
the SNP located just before the slope change. It then eliminates all the SNPs that are in-between.

296 Running the program

297 Algorithm implementation

The program is implemented in Java, as a Spring Boot (v2.6.7) project. Spring Boot is an open-source Java
framework used to create standalone java applications. The executable .jar has been built with JDK 8 using
Maven (v3.9.6), an open-source build tool.

Paths to datafiles and working folders paths, as well as parameters for imputation and filtering can be entered
in a config file or directly in the command line. A "NOISYmputerResults" folder is automatically created, where
the program writes all the output files.

304 Data specifications

In this current version, NOISYmputer is built and extensively tested to perform on F_2 intercross data, that is,
the progeny from F_1 self-fertilization (F_2). NOISYmputer can also be used on recombinant inbred lines by
single seed descent from the F_2 (SSD).

Input data for NOISYmputer are standard Variant Call Format (VCF) files, with chromosome coordinates.
Genotypes (GT field) and allele depths (AD field) must be present in the VCFs. The data should be low
coverage, that is, the sum of all sequences produced per sample is equivalent to 1-3 times (1-3 X) the size of
the reference genome used. Ideally, the VCF should contain only bi-allelic single-nucleotide polymorphisms
(SNPs), however NOISYmputer automatically filters out the other types of sites. Small indels are not handled.
Parental lines need to be included in the VCF file with the prefix "Parent" in their name. Compressed ".gz" VCFs
are accepted.

315 Results

316 NOISYmputer, FSFHap and LB-Impute were run on the IFB Core cluster (specs. available at
317 https://ifb-elixirfr.gitlab.io/cluster/doc/cluster-desc/) with one allocated node per job and 32GB to 64GB of
318 RAM to make sure that the tested programs are fully efficient.

319 Details on parameters used for the three imputation methods are provided in Supplementary Data 1.

320 Using simulations for calibration

To test NOISYmputer's accuracy and precision in breakpoints estimation, we used simulated F_2 datasets
generated using PopSimul (https://forge.ird.fr/diade/recombination_landscape/popsimul). A set of 84 VCFs
with $n = 300$ samples and varying values of marker density, mean depth and error rate were generated for a
final expected map size of 180 cM (corresponding to an average of 3.6 breakpoints per sample) to mimic the
chromosome 1 of rice. Using five different imputation window sizes, we compared the outputs of
NOISYmputer to the known positions of breakpoints in the simulated data. In total, a set of 420 combinations

Table 1. Parameter values used in PopSimul to generate simulated F_2 VCFs: marker density, mean depth and error rate. All
possible combinations of these parameters were tested and imputed using a range of imputation windows in NOISYmputer.

Parameters	Marker density (in number of markers along the chromosome)	Mean depth (in X)	Error rate	NOISYmputer impute half window size
Tested values	220,000 180,000 100,000 66,000	0.5 1 1.5 2 2.5 3 4	0.05 0.01 0.005	15 20 30 50 100

were analyzed. All combinations and tested parameters are listed in Table 1. The results of these analyses
confirmed that NOISYmputer efficiently detects the recombination breakpoints and precisely estimates their
positions.

Breakpoint detection power

We assessed NOISYmputer's ability to correctly detect all breakpoints within samples by comparing positions
of breakpoints found by NOISYmputer to those of simulated datasets. We considered a breakpoint correct
when the simulated breakpoint position falls within NOISYmputer's loose support interval, along with the
correct transition type.

Across all 420 VCFs, representing an average of 455,000 breakpoints, NOISYmputer demonstrated robust
detection power, correctly finding 99.5% of simulated breakpoints (median at 99.6%). NOISYmputer also
displayed high accuracy as, on average, 98.9% of breakpoints identified correspond to actual breakpoints
(with a median at 100%). Thus, NOISYmputer presents an overall excellent accuracy and power in detecting
breakpoints.

To better understand the impact of each parameter and their interaction on NOISYmputer performance, we
performed a principal component analysis (PCA) on parameters and performance indicators. Accuracy was
primarily influenced by error rates, but was also affected by the imputation window size when excessively
large. Conversely, smaller window sizes enhanced detection power. Also, higher marker density correlated
with improved detection power, as lower densities limit NOISYmputer's ability to identify breakpoints in
regions with high recombination rates.

Some specific combinations decreased NOISYmputer detection accuracy and/or power but overall the lower
performances were still acceptable. For instance, the lowest accuracy was of 72.3% (with error rates at 0.05
and smaller imputation window size of 15), and the lowest power was of 96.9% (with larger imputation
window size of 100). This is expected as small windows with high levels of noise are prone to false positive
breakpoints. On the other hand, large windows (especially if coupled with low depth or marker density) may
miss double recombination events, leading to false negatives (Figure 2 A and C). In more realistic conditions,
error rates as high as 0.05 are not typically observed in Illumina sequencing and alignments. When removing
runs with the 0.05 error rate, the average breakpoint accuracy reached 99.9%, with a median of 100%.
Similarly, the average detection power was 99.6%, with a median of 99.5% (Figure 2B).

The data in the VCF files, such as sequencing depth or marker density or species model, depend on the model
species or sequencing type and are generally not under the user's control. We thus looked for the imputation
window size producing the best results for both breakpoint detection accuracy and power with the VCF that
mimicked best the real F_2 rice data we had. In both cases, the optimal results were obtained by the imputation
half window size of 30. Thus, we used this value of 30 later on when exposing NOISYmputer to real datasets.

Precision of breakpoint position

NOISYmputer's precision was estimated by computing the difference between the simulated breakpoints positions and the estimated ones by NOISYmputer. We considered the size of the support interval and its marker density to estimate discrepancy (in number of SNPs) with the actual breakpoint position.

Across all 420 VCFs, a difference of 1,427 bp on average (equivalent to a discrepancy of ~2 SNPs) was observed. The median difference was even lower, with only 245 bp (< 1 SNP discrepancy). This disparity between the median and mean is mainly due to extreme combinations, particularly low depth combined with high error rate. Notably, variance is higher in 0.5X coverage VCFs, becoming more homogeneous at 1X coverage.

Regarding the imputation window, smaller half-windows resulted in lower average differences between NOISYmputer and simulated positions but increased the median difference. Consequently, smaller windows enhanced overall precision while potentially increasing the occurrence of extreme discrepancies.

Error rate estimations

Error rates (e_A and e_B), are recalculated after a first iteration of imputation step 1. NOISYmputer correctly estimated the error rates in 100% of the cases, with an average difference between simulated and estimated error rates of $9.8 \ 10^{-7}$ (standard deviation $4.8 \ 10^{-5}$) (Supplementary Table S1). This reflects the accuracy of the imputation, even with starting values for error rates far from the true values.

Figure 2. Most impacting parameters and data characteristics on NOISYmputer results based on 420 simulated F_2 populations. **A)** Representation of NOISYmputer's detection accuracy (proportion of NOISYmputer breakpoints being actual breakpoints from simulated data) in function of NOISYmputer's detection power (proportion of simulated breakpoints correctly found by NOISYmputer). NOISYmputer shows excellent power detection and accuracy with at least 72.3% and 96.9% respectively. **B)** Zoom on the upper part of the A plot of detection accuracy and power, ignoring the error rate of 0.05. **C)** PCA Biplot of NOISYmputer showing VCFs characteristics and imputation window size influencing detection accuracy and precision with simulated VCFs. The lowest detection powers are observed when high error rates are coupled with a small imputation half-window size in NOISYmputer. The lowest accuracies correspond to VCFs imputed with a large imputation half-window size in NOISYmputer and can be accentuated by very low depth (≤ 1X) and/or low marker density (< 66,000 sites / 44 Mb).

Confirmed efficiency on real data and comparison with other methods

We assessed the performance of NOISYmputer on two real datasets: i) a maize F_2 population in GBS with 91 samples, including the parents, and ii) a rice F_2 population with 3X coverage in whole-genome sequencing (WGS) comprising 222 samples, including the parents sequenced at ~30X. Details of how the real dataset for rice was generated are summarized in the Supplementary Data. The maize dataset is described in the LB-Impute publication (Fragoso *et al.* 2016).

In real data, direct estimation of imputation accuracy may be challenging due to the unknown true state at each locus. However, it is possible to assess the quality of the imputation indirectly by comparing the final genetic map to, for instance, existing high-quality maps. A correctly imputed dataset should yield a map size – in centimorgans (cM) – consistent with those derived from high-quality marker data. Conversely, datasets with a high rate of genotyping errors will exhibit map expansion, resulting in a longer genetic map due to falsely imputed recombination breakpoints.

Using map size estimates in centimorgans (cM) of chromosome 1 of these datasets, we compared the results of NOISYmputer to those of LB-Impute and FSFhap (Figure 3 and Table 2). Concerning the maize GBS dataset, LB-Impute and FSFhap strongly overestimated the map size expected from high-quality datasets (respectively 633 cM and 13,271 cM), whereas NOISYmputer's map was in range with the expected map size (203 cM). Regarding the Rice WGS dataset, while both LB-Impute and FSFhap yielded maps much larger than expected (23,436 cM and 337,750 cM respectively), NOISYmputer estimated a map size close to the expected value (213 cM). Also, results from FSFhap on PopSimul data produced very large map size estimations for high error rates (5%) VCF, while they were qualitatively similar to NOISYmputer's for lower (1% and .5%) error rates.

To further estimate the performance of NOISYmputer on real datasets we also performed comparisons on breakpoint detection accuracy, detection power, and position estimate in the 222 F_2 Rice population. This dataset includes 20 samples sequenced at ~20X depth, and artificially subsetted to 3X (that we call pseudo-3X). These 20 samples allow for a more robust evaluation as their breakpoints are well estimated thanks to their better depth. We processed similarly to the simulated analyses and compared breakpoint detection accuracy, power, and precision of breakpoint estimates for NOISYmputer against the accurately estimated breakpoints at 20X coverage. Unfortunately, we were not able to compare NOISYmputer results to those of FSFHap and LB-impute as, even if we managed to retrieve each breakpoint position estimate, we could not easily check which were actual breakpoints and which were false positives, as TASSEL FSFHap and LB-impute do not provide support intervals for breakpoints.

Overall, NOISYmputer demonstrated excellent results with, on average, 99% accuracy and 97% detection power. Regarding precision, on average the difference in position was of 10,219 bp, while the median was of only 415 bp. The large difference between the average and the median is due to a few breakpoints estimated far from their true position. Indeed, 80% of the breakpoints were still estimated at less than 1,669 bp from their true position. In terms of number of SNPs, the discrepancy was of 2 SNPs on average (median: 1) (Supplementary Table S2).

Overestimation of map sizes was mostly due to misinterpretation of noisy data by FSFHap and LB-Impute. These discrepancies frequently arise in regions corresponding to structural variations between parental genomes. Such variations can occur, for instance, when attempting to map onto regions found exclusively in the Parent A genome, which serves as the reference. In such cases, reads from B regions might map to the most similar A regions available resulting in false recombination events according to imputation softwares. This phenomenon is accentuated in WGS data compared to GBS data as the complete genome is sequenced and mapped, thus increasing the number of markers. Including more sites, inducing sites belonging to peculiar genomic structures, can hinder the quality of imputation if the software does not take into account the coherence of a marker with its surrounding environment in the population. Though FSFHap and LB-impute might be precise in the estimated breakpoints positions, their lack of accuracy in breakpoints detection leads to results, on whole genome datasets, difficult to use without the help of complex filtering steps. NOISYmputer, on the contrary, is very efficient at correcting mapping issues or divergence between parental genome structures.

Table 2. Comparison of estimated and expected map sizes for three different datasets using NOISYmputer, FSFHap and LB-Impute. The 84 VCFs generated using PopSimul have varying numbers of markers (66,000, 100,000, 180,000 or 220,000), depending on the settings used to generate the VCFs. Overall, NOISYmputer is showing considerably higher accuracy in map size estimation compared to FSFHap and LB-Impute.

Dataset	Software	Estimated map size (cM)	Expected map size (cM)	Initial number of markers in VCF
F_2 Maize GBS n = 91 samples including parents	NOISYmputer	203		
	FSFHap	13,271	~200	17,945
	LB-Impute	633		
F_2 Rice WGS n = 222 samples including 30X parents	NOISYmputer	213		
	FSFHap	337,750	183	254,095
	LB-Impute	23,436		
84 PopSimul F_2s n = 300 samples each including parents	NOISYmputer	180		Different number of markers depending on the simulation settings
	FSFHap	479,399	180	
	LB-Impute	N/A		

A resource-optimized software, CPU- and RAM-efficient

In our comparative analysis of the NOISYmputer with established counterparts, we conducted comprehensive benchmarks, focusing on execution time and RAM usage (Table 3 and Figure 3). To do so, we ran NOISYmputer, FSFHap and LB-Impute on simulated and real datasets. We then retrieved their CPU time, "wall clock" execution time and RAM usage using the *seff* command on the IFB computing cluster.

Concerning the F_2 Maize GBS dataset, NOISYmputer ran ~10 and ~45 times faster than FSFhap and LB-Impute, respectively. It also used less RAM (~3.4 GB), ~3 times less than FSFHap and ~21 times less than LB-Impute.

Regarding the F_2 Rice WGS dataset, NOISYmputer used slightly less RAM than FSFHap and was ~13 times faster (< 6 min vs. 1h19m). LB-Impute showed poor CPU and RAM efficiency as NOISYmputer used ~9 times less RAM and ran ~145 times faster.

Due to the excessive computation time on this single smaller dataset, LB-Impute was excluded from the remaining comparisons with the 84 PopSimul VCFs with 300 samples. It is interesting to note that FSFHap resource efficiency is better on simulated than on real datasets even though they have more samples. Indeed, FSFHap used on average 1.93 GB of RAM, whereas NOISYmputer was stable at 3.61 GB. NOISYmputer was still faster than FSFHap on average, with ~5 min, while FSFHap ran in ~9 min. This underlies the difficulty that FSFHap has to impute noisy data, partly due to structural variants and calling errors. These results underscore NOISYmputer's efficiency improvement in processing imputation tasks, especially compared to existing software for bi-parental population imputation.

Figure 3. Barplot of CPU time and RAM resource usage for NOISYmputer (orange), LB-Impute (gray) and FSFHap (blue) on three datasets. Rice_WGS is an F_2 Rice WGS dataset with $n = 222$ samples including parents; PopSimul_84 values are averages across 84 VCFs generated with PopSimul, each VCF containing $n = 300$ samples including parents, simulated using ranges of depth, marker density and error rate to mimic different characteristics of F_2 VCFs; Maize_GBS is an F_2 Maize GBS dataset with $n = 91$ samples including parents (with a lower marker density than Rice_WGS). NOISYmputer is overly faster and more RAM-efficient in all conditions than FSFHap and LB-Impute, with the exception for RAM usage on simulated VCF files of PopSimul. No data is shown for PopSimul_84/LB-Impute, as LB-Impute was not benchmarked due to excessive CPU time.

Availability and Future Directions

Availability

NOISYmputer is available as a multiplatform (Linux, macOS, Windows) Java executable at the URL https://gitlab.cirad.fr/noisymputer/noisymputerstandalone/-/tree/1.0.0-RELEASE?ref_type=tags. The source code and the documentation are available at the same URL. A Quarto markdown companion (compatible with R markdown and Jupyter notebooks IDE) that allows to display graphics of statistics (e.g., genotypic frequencies on SNPs and samples) and graphical genotypes from NOISYmputer output files was developed and is also available.

NOISYmputer and its companion are distributed under the GNU Affero General Public License V3.0.

Future directions

NOISYmputer's strengths

Although previous methods have made significant advances in addressing the challenges listed above, the noisiness of imputed datasets are still producing expanded genetic maps, excess heterozygosity, and probabilistically unlikely recombination events contained within a short physical interval. Here, we introduce an algorithm which, in a series of steps, addresses each source of error to create higher-quality datasets for improved trait mapping and genomics-assisted breeding. Our algorithm represents a step to systematically address all sources of NGS genotyping error and even errors in the reference genome, and hopefully the corrections brought here will be integrated into future algorithm development. Indeed, key features of NOISYmputer are its pre- and post-filtering steps that other currently available software does not perform. In filtering SNPs and segments that are incoherent with their environment and with the population local recombination landscape, NOISYmputer efficiently eliminates errors of genotype calling, sequencing errors, or errors generated by structural variants. The pre-imputation and post-imputation stages of NOISYmputer, in

Table 3. CPU and RAM usage of NOISYmputer, FSFHap and LB-Impute for three datasets based on the output of the *seff* command on the IFB cluster. NOISYmputer 1st and 2nd Runs are displayed as NOISYmputer shows better CPU time usage for the second run since the conversion of the raw VCF file has already been done. For LB-Impute, as imputation is processed in two steps, CPU time and execution time results are the sum of the two steps; RAM usage corresponds to the highest RAM usage of the two steps (offspring imputation). For the 84 PopSimul VCFs section, results correspond to the average of resource usage for each of the 84 PopSimul VCFs for an imputation half-window of 30 SNPs with NOISYmputer and the default window size (50) of FSFHap. All tests were conducted on the IFB Core cluster. *As LB-impute showed excessive time and RAM consumption on the Rice_WGS dataset, we did not benchmark the 84 PopSimul VCFs with LB-impute.

Datasets	Software		CPU time (h:m:s)	Total execution time (h:m:s)	RAM (GB)
F2 Maize GBS **n = 91 samples** **including parents**	**NOISYmputer**	**2nd Run**	00:00:07	00:00:09	1.00
		1st Run	00:00:27	00:00:28	1.00
	FSFHap		00:06:49	00:04:35	3.42
	LB-Impute		00:20:59	00:21:04	21.61
F2 Rice WGS **n = 222 samples** **including 30X parents**	**NOISYmputer**	**2nd Run**	00:06:49	00:04:35	3.42
		1st Run	00:09:47	00:06:44	3.36
	FSFHap		01:19:00	01:19:06	4.02
	LB-Impute		16:18:52	16:19:21	31.48
84 PopSimul VCFs **with n = 300 samples** **each including parents**	**NOISYmputer**	**1st Run**	00:05:18	00:05:39	3.61
	FSFHap		00:09:20	00:09:24	1.93
	LB-Impute*		NA	NA	NA

particular, address artifacts of imputation caused by presence-absence variation misrepresented by the reference assembly and assembly errors from inaccurate or misordered contigs. These imputation artifacts, such as those caused by collapsed structural variants (incoherent sites or false heterozygosity) or misassembled "chunks", are not systematically addressed by other imputation methods, such as LB-Impute (Fragoso *et al.* 2016), and otherwise must be parsed through manual filtering of the imputed dataset.

NOISYmputer is a resource-effective software developed in Java, allowing its integration in bioinformatics pipelines. NOISYmputer is parallelizing computation at the sample level in several steps of the algorithm, which increases its speed considerably. The use of a Java standalone executable also allows to simulate parallelization in running each chromosome on a separate core of a server/cluster. Moreover, NOISYmputer employs a maximum likelihood method, instead of hidden Markov models, which considerably reduces computational complexity, compared to FSFHap (Swarts *et al.* 2014) and LB-impute (Fragoso *et al.* 2016), while enhancing result accuracy and flexibility across diverse datasets. Indeed, NOISYmputer is less sensitive to noisy regions (due to mapping artifacts for example) as it can handle large windows without being greedy in RAM and computation time to overpass complex regions.

Notably, NOISYmputer's speed allows iterative refinement of parameter settings. For example, the size of the imputation window (in number of SNPs), like in other imputation programs (e.g., FSFhap, LB-Impute), is arbitrarily fixed by the user. The most appropriate value for m depends on several factors, including depth and SNP density. A convenient way to determine which value for m to use is to run the imputation several times with different values until reaching the expected distribution of the number of recombination breakpoints per sample across the population (if previously known). Often, saturated genetic maps generated with other types of markers are available in the literature, from which the expected distribution is easily derived. With our rice

data, the imputation algorithm gave the best results with $m = 30$, so even a few runs should provide a
satisfying window size.

Furthermore, NOISYmputer generates a .json file from the VCF during the initial run, that is used by the
consecutive runs, eliminating the redundant tasks of converting the input VCF file, thus enhancing speed for
subsequent launches on the same dataset.

Its robust performance extends to various VCF characteristics, accommodating differences in SNP quality,
marker density, error rates, and sequencing depths. This is partly due to its low sensitivity to the SNP calling
step used to generate the input VCF, as NOISYmputer is re-estimating the probabilities of genotypes using the
allele depth at each site, along with information of the surrounding environment and of the whole population.
This results in maintenance of overall excellent detection accuracy, detection power and position precision on
recombination breakpoints even with very low coverage datasets ($\leq$1X). However, users should exercise
caution in selecting an appropriate imputation window size to mitigate the risk of false positives and
negatives.

In addition to its performance benefits, NOISYmputer provides users with several comprehensive breakpoint
confidence information allowing to further filter the identified breakpoints. This is a feature that is innovative
and useful and not available in other software, to our knowledge. NOISYmputer also outputs statistics on
genotypic/allelic frequencies, samples and genetic map among others.

Suggestions for Improvement

NOISYmputer could benefit from several improvements. The first one is including more population types. In
the next version, we will implement F_2 backcross, or BC_1F_1, the progeny of the F_1 hybrid crossed with one of
the parents (BC_1) ; doubled haploid of F_1 gametes (DH) ; F_2 intercross, that is, the progeny from F_1
self-fertilization (F_2); recombinant inbred lines by single seed descent from the the BC_1F_1 (BCSSD); the
unconventional mating design (UMD) BC_1F_3, derived by two generations of self-fertilization of BC_1F_1
individuals. For now, it has been extensively tested and optimized for F_2 crosses between distant parents
which might be one of the hardest designs to estimate breakpoints from. We thus are confident that the
algorithm can be adapted to these other types of crosses.

Breakpoint detection and accuracy could benefit from a more complex modeling of the likelihood. Currently,
we test for the existence of a single transition within the loose support interval in imputation Step 3. Testing
for one, two or even three transitions in a single interval could increase the probability of finding close double
recombination events if they happened to have a higher probability in the tested region. Breakpoint position
estimation, on the other hand, might be improved by using a combination of NOISYmputer's current algorithm
with a hidden markov model occurring in the Step 3 of imputation. This way, a smaller window size could be
applied and the region to scan would be reduced to a very limited percentage of the genome only, resulting in a
considerable gain of time.

NOISYmputer is robust on a broad range of samples and its computation time makes it very convenient. Part of
the success of NOISYmputer lies in the fact that it performs pre- and post-imputation filtering steps that
remove, among other things, incoherent SNPs, meaning SNPs that do not segregate the same way as its
immediate environment, often indicating mapping errors. This filtering of incoherent SNPs step uses a
Chi-square test to evaluate if the observed pattern is reasonable. Unfortunately, Chi-square test thresholds are
dependent on sample sizes. Thus, when imputing many samples (e.g., m=2000) with NOISYmputer, the user
has to adapt the Chi-square threshold to the sample size, which is not convenient. A solution to this would be
to use a "Cramér's V" statistic instead (Cramér 1999), which would be independent of the sample number in
the VCF.

Unlike FSFHap or LB-Impute, NOISYmputer does not impute the parental genotypes, which might result in the
loss of SNPs, especially in datasets derived from very low-coverage sequencing. Although we recommend
sequencing the parents at high coverage (> 20X), it is not always possible – for instance, when re-analyzing
historical data. The next version of NOISYmputer will impute the parental genotypes when necessary.

Finally, as pointed in the Results section, the imputation half-window size can have an impact on the outputs of
NOISYmputer. NOISYmputer could benefit from an iterative process that would check for different window

sizes and analyze the convergence of the results to select the appropriate window size and thus to achieve the
best compromise between detection accuracy and power, along with precision.

576 Acknowledgements

We thank Karine Labadie (CEA, Institut de Génomique, Genoscope, Evry, France) for sharing the WGS data for
the sequencing of rice populations, Christine Tranchant-Dubreuil (IRD, Montpellier, France) for her help with
retrieving the Rice_WGS data and François Sabot (IRD, Montpellier, France) for coordinating the IRIGIN
project. We are grateful to the Institut Français de Bioinformatique (IFB) for providing computing resources.
We also thank the Yale Center for Research Computing for guidance and use of the research computing
infrastructure. The following programs supported parts of this initiative: the French ANR project "LANDSREC"
(ANR-21-CE20-0012-03), the French Government France Génomique program through its International RIce
Genome INitiative "IRIGIN" project, and the CGIAR Research Program "RICE".

585 Author's contributions

CT participated to the algorithm development, designed and ran the bioinformatics pipeline to call SNPs for
the WGS dataset (F_2 and SSD), benchmarked and compared all softwares, wrote the quarto markdown
companion, tested the program for debugging and took part in the manuscript conception. AB participated in
the algorithm development and implemented it in Java, took part in the manuscript conception. CF helped
with running LB-Impute for the Rice_WGS dataset for the previous version of NOISYmputer and edited the
manuscript. AG designed and ran the bioinformatics pipeline to call SNPs for the Rice_WGS dataset for the
previous version of NOISYmputer. JFR took part in the initial design and definition of specifications for
NOISYmputer. ML conceptualized the initial imputation algorithm for NOISYmputer, participated in its further
development and took part in the manuscript conception.

595 References

596 Browning S. R., and B. L. Browning, 2007 Rapid and Accurate Haplotype Phasing and Missing-Data Inference

597   for Whole-Genome Association Studies By Use of Localized Haplotype Clustering. The American

598   Journal of Human Genetics 81: 1084–1097. https://doi.org/10.1086/521987

599 Browning B. L., X. Tian, Y. Zhou, and S. R. Browning, 2021 Fast two-stage phasing of large-scale sequence data.

600   The American Journal of Human Genetics 108: 1880–1890.

601   https://doi.org/10.1016/j.ajhg.2021.08.005

602 Cramér H., 1999 *Mathematical Methods of Statistics*. Princeton University Press.

603 Davey J. W., and M. L. Blaxter, 2010 RADSeq: next-generation population genetics. Briefings in Functional

604   Genomics 9: 416–423. https://doi.org/10.1093/bfgp/elq031

605 Dempster A. P., N. M. Laird, and D. B. Rubin, 1977 Maximum Likelihood from Incomplete Data via the EM

606   Algorithm. Journal of the Royal Statistical Society. Series B (Methodological) 39: 1–38.

607 Elshire R. J., J. C. Glaubitz, Q. Sun, J. A. Poland, K. Kawamoto, *et al.*, 2011 A Robust, Simple

608   Genotyping-by-Sequencing (GBS) Approach for High Diversity Species, (L. Orban, Ed.). PLoS ONE 6:

609   e19379. https://doi.org/10.1371/journal.pone.0019379

Fragoso C. A., C. Heffelfinger, H. Zhao, and S. L. Dellaporta, 2016 Imputing Genotypes in Biallelic Populations

from Low-Coverage Sequence Data. Genetics 202: 487–495.

https://doi.org/10.1534/genetics.115.182071

Heffelfinger C., C. A. Fragoso, M. A. Moreno, J. D. Overton, J. P. Mottinger, *et al.*, 2014 Flexible and scalable

genotyping-by-sequencing strategies for population studies. BMC Genomics 15: 979.

https://doi.org/10.1186/1471-2164-15-979

Howie B., C. Fuchsberger, M. Stephens, J. Marchini, and G. R. Abecasis, 2012 Fast and accurate genotype

imputation in genome-wide association studies through pre-phasing. Nat Genet 44: 955–959.

https://doi.org/10.1038/ng.2354

Huang X., Q. Feng, Q. Qian, Q. Zhao, L. Wang, *et al.*, 2009 High-throughput genotyping by whole-genome

resequencing. Genome Res. 19: 1068–1076. https://doi.org/10.1101/gr.089516.108

Kosambi D. D., 1944 The Estimation of Map Distances from Recombination Values, pp. 125–130 in *D.D.*

Kosambi: Selected Works in Mathematics and Statistics, edited by Ramaswamy R. Springer India, New

Delhi.

Swarts K., H. Li, J. A. Romero Navarro, D. An, M. C. Romay, *et al.*, 2014 Novel Methods to Optimize Genotypic

Imputation for Low-Coverage, Next-Generation Sequence Data in Crop Plants. The Plant Genome 7:

plantgenome2014.05.0023. https://doi.org/10.3835/plantgenome2014.05.0023

Xu C., Y. Ren, Y. Jian, Z. Guo, Y. Zhang, *et al.*, 2017 Development of a maize 55 K SNP array with improved

genome coverage for molecular breeding. Mol Breeding 37: 20.

https://doi.org/10.1007/s11032-017-0622-z