Dissecting AlphaFold's Capabilities with Limited Sequence Information

Jannik Adrian Gut[1,2] and Thomas Lemmin[1, *]

[1]Institute of Biochemistry and Molecular Medicine, University of Bern
[2]Graduate School for Cellular and Biomedical Sciences (GCB), University of Bern
*Corresponding author: thomas.lemmin@unibe.ch

March 14, 2024

Abstract

Protein structure prediction, a fundamental challenge in computational biology, aims to predict a protein's 3D structure from its amino acid sequence. This structure is pivotal for elucidating protein functions, interactions, and driving innovations in drug discovery and enzyme engineering. AlphaFold, a powerful deep learning model, has revolutionized this field by leveraging phylogenetic information from multiple sequence alignments (MSAs) to achieve remarkable accuracy in protein structure prediction. However, a key question remains: how well does AlphaFold understand protein structures? This study investigates AlphaFold's capabilities when relying primarily on high-quality template structures, without the additional information provided by MSAs. By designing experiments that probe local and global structural understanding, we aimed to dissect its dependence on specific features and its ability to handle missing information. Our findings revealed AlphaFold's reliance on sterically valid C-β atoms for correctly interpreting structural templates. Additionally, we observed its remarkable ability to recover 3D structures from certain perturbations. Collectively, these results support the hypothesis that AlphaFold has learned an accurate local biophysical energy function. However, this function seems most effective for local interactions. Our work significantly advances under-standing of how deep learning models predict protein structures and provides valuable guidance for researchers aiming to overcome limitations in these models.

1 Introduction

Proteins serve as nano-machines within cells, orchestrating a plethora of vital functions essential for life. Their remarkable versatility arises from their unique three-dimensional (3D) structures, dictated by the specific sequence of amino acids they are built from. This fundamental principle, known as Anfinsen's dogma [3], underpins modern biology and fuels research in areas like drug discovery and enzyme engineering. However, progress in elucidating protein structures has been hindered by the labor-intensive nature of *in vitro* experiments required for atomic structure determination, resulting in only approximately 200,000 structures being resolved to date [7].

To surmount this bottleneck, researchers have increasingly turned to computational methodologies to unravel the intricacies of protein folding. Established in 1994, the Critical Assessment of Techniques for Protein Structure Prediction (CASP)[9] has played a crucial role in tracking advancements in this field. Recent years have been particularly transformative, fueled by two key factors: the exponential growth of

sequential and structural protein data [8, 7] and the emergence of powerful machine learning methodologies, particularly deep learning, capable of harnessing this data more effectively. Notably, AlphaFold [14], a deep neural network unveiled in 2020, has revolutionized the field. This innovative model has achieved remarkable accuracy in predicting protein structures, marking a significant leap forward in our understanding of protein structure and function. Freely available to the scientific community, AlphaFold has become an indispensable tool for structural biologists. In addition, a database [35] of high-confidence structures derived from previously unsolved proteins has been established. This resource enables utilization for theoretical analysis, informed experiment design, and training data development, thereby bolstering research efforts in structural biology.

The AlphaFold pipeline follows a two-step process for predicting protein structures. First, it searches various protein sequence databases [24, 7, 8, 32, 23] using dedicated tools [31, 11, 17] to find similar sequences to the target protein across. This information gets compiled into a multiple sequence alignment (MSA), capturing the evolutionary relationships between the proteins. Simultaneously, AlphaFold identifies suitable 3D structures (templates) from closely related proteins to serve as initial structural models. These two sources of information, MSA and templates, are initially processed separately within the AlphaFold model. However, their representations are continuously refined through an iterative exchange of information, allowing the model to learn from both sources simultaneously. Finally, the refined representations of the MSA and templates are combined in the structure module of AlphaFold to generate the final protein structure and assign a confidence score (pLDDT) for each individual amino acid.

The MSA has been observed to play a more significant role in predicting protein structure quality compared to templates. Notably, several pipelines leveraging AlphaFold [10, 36], and three out of the five default models of AlphaFold, ignore the information from templates altogether. Intriguingly, contrary to previous pipelines, AF2Rank [27] showed that simply providing AlphaFold with a protein structure, without any sequence information, can be used to evaluate

its plausibility and discriminate between real structures and decoys. The authors hypothesized that the structure module within AlphaFold has learned a robust biophysical energy function, and the MSA input might primarily serve to guide the model towards the correct energy minimum.

To further evaluate this hypothesis, we conducted an extensive investigation into the influence of the template input on AlphaFold's predictive accuracy. Through a comprehensive series of ablation studies, we assessed the model's capability to reconstruct protein structures solely based on templates, without relying on deep MSAs. Specifically, we examined AlphaFold's performance in side-chain packing and its resilience in recovering from artificially perturbed proteins. Our experimental code is openly accessible on GitHub[1] and we have contributed new methods to the OpenFold [2] project[2].

Our findings offer valuable insights for both AlphaFold users and developers who integrate the tool into their workflows. By enhancing the understanding of the model's limitations and providing guidance on result interpretation, our work aims to empower users to critically assess results and leverage complementary tools when necessary. Additionally, it encourages exploration of existing tools or the development of innovative solutions to address these limitations, ultimately contributing to more accurate and reliable protein structure predictions.

2 Materials and methods

2.1 Datasets

The data used for the experiments was sourced from CASP13 [15] and CASP14 [16]. CASP13 was included in the analysis to evaluate potential bias and overfitting, given that AlphaFold was trained on proteins within the CASP13 dataset. Consequently, we anticipate observing higher scores compared to CASP14, which serves as a more realistic benchmark for assessing the model's performance on unseen targets. This distinction is crucial for accurately gaug-

---

[1]https://github.com/ibmm-unibe-ch/template-analysis
[2]https://github.com/aqlaboratory/openfold/pull/408

ing the model's generalizability and effectiveness in predicting structures of novel protein sequences.

2.2 AlphaFold

We primarily employed the LocalColabFold[3] [21] implementation of AlphaFold in our experiments, as it offers a user-friendly command-line interface and faster inference enabled by the MMseqs webserver [22]. Given that AlphaFold largely ignores template information when provided with a deep MSA, a minimal MSA comprising only the query sequence (single sequence) was supplied to the model, unless otherwise specified. Furthermore, we developed a protocol, OF2Rank, within the OpenFold [2] framework similar to AF2Rank that was previously used to assess the quality of protein structures [27]. This method involves replacing all original amino acid information in the template with glycine residues extended with a C-β atom. The sequence information is provided either as an all-gap multiple sequence alignment (*Gaps*) or as a single sequence MSA (*Single*). Unlike AF2Rank, OF2Rank supplies the sequence to the model, which updates the template residues. We evaluated this protocol's effectiveness in recovering templates subjected to various structural perturbations.

2.3 Side-chain packing

To assess AlphaFold's ability to reconstruct side chains accurately, we designed four test cases using CASP13 and CASP14 data. In each case, all side chain atoms were removed from the target proteins. In addition, to providing just the backbone as a template, we also positioned the C-β atom in three different ways:

i. *Non-informative C-β*: Placed next to the origin for a baseline comparison , ii. *Heuristic C-β*: Predicted using a rule-based approach based on the backbone atoms [27], iii. *Template C-β*: Maintained the original C-β position from the template

We extended our assessment to explore AlphaFold's ability to refine side chain predictions using three external side-chain packing strategies: the

---

lowest energy conformation provided by the widely used CHARMM 36 force field (*C36*), FASPR [12], a structure-based side-chain packing method and AttnPacker, a neural network-based side-chain packing method [19].

The modified templates and single sequences were then inputted into LocalColabFold without relaxation and without recycling, ensuring that the backbone remained more similar to the input template. Only the predictions from the first two AlphaFold models were considered, as they are the ones where template input is utilized.

2.4 Structural perturbation

Three distinct techniques were employed to generate controlled perturbations to the template structures (Figure 1). The refinement of perturbed structures was conducted using LocalColabFold with either a single sequence or MSA. In addition, we tested the newly implemented protocol within OpenFold to evaluate a more sequence-agnostic refinement.

2.4.1 Gaussian noise

The simplest perturbation method involved adding Gaussian noise to the template coordinates. We independently sampled values from a standard normal distribution (mean = 0Å) for each atomic coordinate dimension. A predefined standard deviation of 1Å determined the magnitude of the introduced noise. These sampled values were then added to the original coordinates, introducing controlled deviations from the initial structure.

2.4.2 Principal component analysis

Principal Component Analysis (PCA) [6] was employed to transform and project the protein into an orthogonal reference frame that explains the most variance. Separate PCAs were computed for each protein in the CASP13 and CASP14 datasets. Subsequently, each structure was projected onto the subspace defined by the first principal component (*1 PC*) or the first two principal components (*2 PC*). This

Figure 1: Illustration of structural perturbations. Ground truth protein structure (T1026, PDB id: 6s44) is shown in yellow, 10 partial RFdiffusion steps in blue, Gaussian noise in pink and 2D projection in green. All structures were rendered using ChimeraX [20].

effectively captured the major structural variations within each protein structure.

2.4.3   RFdiffusion

RFdiffusion [37] leverages diffusion techniques [30] to generate new proteins from noise. Instead of executing the complete diffusion process, which generates entirely new backbones conformations, we ran RFdiffusion for a limited number of partial steps (1, 5 and 10 steps) [33]. This strategy produced backbones that remained closer to the starting structure, with the degree of variability increasing with the number of steps. Subsequently, side chains were reconstructed using FASPR or AttnPacker.

2.5   Evaluation metrics

To assess the accuracy of the predicted protein structures, we employed a variety of metrics. These metrics can be broadly categorized into three classes based on the level of detail they capture.

The first class of accuracy metrics focuses solely on the α-carbon atom from the backbone. This includes the Template Modeling (TM)-score [38, 5], which quantifies the structural similarity between predicted and reference structures, and the α-RMSD [5], measuring the difference between the C-α positions of the predicted and reference structures after optimal superposition using the Kabsch algorithm.

The next class of accuracy metrics encompasses RMSD and the Local Distance Difference Test (lDDT) [18, 5], which evaluates all atom pairs (backbone and side-chain) within a predefined radius excluding those belonging to the same residue. In addition, AlphaFold predicts a score called pLDDT, which estimates the lDDT value of its generated structures and helps guide the selection of the best model among multiple predictions. Individual per-residue lDDT scores can be combined to generate a single, global lDDT score. To accommodate potentially invalid protein structures with steric clashes, stereochemical checks were disabled during lDDT calculations.

The last class of metrics evaluates the accuracy of side-chain packing with the Mean Absolute Error

(MAE) for the first four dihedral angles of the side chains [19].

Pdb-tools [26], the MAXIT suite, ProDy [4], Scikit-learn [25] were used for implementing the experiments and analyzing the results.

3   Results

To assess AlphaFold's [14] understanding of protein structure, we designed two complementary tasks. The first task assessed AlphaFold's local understanding by testing its ability to rebuild and pack side-chains onto a provided backbone template. This evaluated AlphaFold's ability to handle individual amino acid interactions within the protein structure. The second task investigated the global understanding by evaluating AlphaFold's effectiveness in recovering the correct protein structure from a perturbed template. Previous studies have indicated that AlphaFold largely disregards template input when provided with a deep multiple sequence alignment (MSA) [1]. Therefore, to isolate its capability in utilizing structural information, we primarily employed a single sequence along with the template as input for AlphaFold in most experiments. To assess potential overfitting concerns, we compared results on proteins from CASP13 (part of AlphaFold's training data) to those from CASP14 (unseen data). Since we did not observe any major differences between these two datasets, we will focus on presenting the results from CASP14 in this section, but report data of both datasets in supplementary information Section A and supplementary information Section C for side-chain packing and structural refinement respectively.

3.1   Side-chain packing

Side-chain packing is a critical process in protein structure prediction, involving the prediction of the three-dimensional positions of amino acid side chains relative to the protein backbone. This task is essential for accurate modeling of protein structures and for understanding their biological functions.

Our initial evaluation focused on AlphaFold's ability to pack side chains using only the backbone atoms and different approaches for the placement of C-β atoms: all close to the origin (*Non-informative C-β*), using a heuristic (*Heuristic C-β*), or preserving the correct position from the template (*Template C-β*). When the template lacked C-β information (either missing or Non-informative C-β), the predicted structures suffered significant accuracy loss. The average TM-score dropped to approximately 0.41 ± 0.20 and 0.32 ± 0.20, respectively, indicating a failure to preserve the 3D structure. Providing more informative C-β positions, either through heuristics or the template, significantly improved the results. The average TM-score remained very high (nearly 0.97 ± 0.03) when using the heuristic C-β placement, indicating minimal alterations of the backbone structure from the template. It's worth noting that this score is higher than the average TM-score achieved by AlphaFold predictions using a full MSA without a template (approximately 0.8 ± 0.18).

These high TM-scores suggest that side-chain packing metrics can be reliably analyzed, since the overall protein fold is mostly maintained. The heuristic C-β placement achieved a promising average lDDT score of 0.89 ± 0.05, exceeding the baseline method (standard pipeline with full MSA) which had an average lDDT of 0.74 ± 0.15.

Next, we assessed AlphaFold's potential to enhance the predictions of three different methods for side-chain placement: predefined conformations from the CHARMM36 force field, FASPR [12], and AttnPacker [19]. We employed the AutoPSF plugin from VMD [13] to assign a single, predefined side-chain structure to each residue based on the CHARMM36 force field (*C36*). While fast and simple, it neglects the local environment, leading to clashes and sub-optimal packing. FASPR [12] utilizes a tree search algorithm to identify energetically favorable placements for predefined rotamers [28]. This approach offers better balance between speed and accuracy by using a predefined library of conformations but allowing for optimization based on energy minimization. Finally, AttnPacker is a deep learning-based method that directly predicts side-chain coordinates without relying on predefined rotamers. This

Figure 2: Average lDDT scores for side-chain packing task. Violin plots show the distribution of average lDDT scores for various AlphaFold template configurations. *MSA*: full MSA, but no template, *Template*: full template, *Backbone*: the protein backbone *Heuristic C-β*: template with heuristically placed C-β, *Template with C-β*: backbone and C-β from the ground truth, *AttnPacker* and *AttnPacker (AF)*: ground truth backbone with side chains placed by AttnPacker before and after AF refinement

approach offers greater flexibility in side-chain placement compared to rotamer-based methods.

Refining the repacked protein structures through AlphaFold resulted in a slight decrease in the average TM-score to 0.98 ± 0.03, indicating again minimal backbone alteration. Interestingly, refining the packing with AlphaFold significantly boosted the average lDDT scores when the initial packing was poor (e.g., predefined rotamers from the CHARMM36 force field). However, for methods like FASPR and AttnPacker, which already produced good initial packing, the lDDT scores remained similar or even decreased slightly after AlphaFold refinement (Figure 2).

Analyzing the mean RMSD revealed similar effects of AlphaFold refinement on different packing methods. Notably, competitive side-chain packing methods like FASPR and AttnPacker see a marginal change in performance after post-processing with AlphaFold. Conversely, when using only the default low energy conformation from the CHARMM36 force field, which initially performs poorly (RMSD: 1.77 Å ± 0.15), exhibited a significant improvement in side-chain placement (RMSD: 0.88 Å ± 0.25) after AlphaFold refinement. When provided with only the heuristic C-β, AlphaFold is able to predict the side chain position with a similar precision as FASPR, RMSD 0.91 Å ± 0.25 and 0.89 Å ± 0.27 respectively. While providing the correct C-β information leads to a marginal improvement (RMSD: 0.86 Å ± 0.27) over the heuristic approach.

Furthermore, we noticed a slight decrease in confidence and precision as residues become more exposed at the protein surface (Section B in the supplementary information). This decrease is consistent across all template-informed protocols, but is notably steeper for the standard AlphaFold protocol relying solely on MSAs.

3.2 Structural refinement

Next, we assessed AlphaFold's ability to refine perturbed templates. Three perturbation protocols were implemented and tested: introducing random Gaussian noise to atom coordinates (*Gaussian*), projecting the entire structure onto a 1D or 2D space defined

(a) Violin plot of selected perturbation strategies. *(AF)* is used to identify the post-processing by AlphaFold, *MSA* uses the vanilla AlphaFold pipeline with a full MSA and no pipelines, while *Single* uses only the single sequence, *Gaussian* adds Gaussian noise to the coordinates, *1 PC* reduces proteins to the first principal component, *2 PC* reduces targets to the first two principal components

(b) Change in TM-score after AlphaFold refinement of RFdiffusion-perturbed templates. Each point represents a single target from the CASP14 dataset. The TM-score of the RFdiffusion-perturbed structure before refinement is displayed on the x-axis, with separate plots for 1 and 10 partial steps on the left and right, respectively. The y-axis shows the TM-score after refinement using AlphaFold. The side chains were packed using FASP.

Figure 3: CASP14 TM-scores plots discussed in Section 3.2, 3a shows the effect of selected perturbation strategies, 3b shows the effect of more RFdiffusion steps.

by principal components (*1 PC* and *2 PC* respectively), and partially denoising the structure using RFdiffusion (*RFDiff*). The full table with scores can be found in Supplementary Information Section C.

Despite struggling to fully recover the original structure for several perturbations, AlphaFold generated sterically valid structures in most cases. This is evident in the necessity to disable stereochemical checks from OpenStructure [5] when calculating lDDT for templates perturbed with the Gaussian noise and projected in to the PCA eigenspace. These checks ensure proper atomic interactions, and the initial violation by a majority of residues suggests significant structural distortion. However, the fact that these checks would not be needed for post-processed structures implies that AlphaFold, while not achieving complete fold recovery, produces structures with proper atomic interactions.

AlphaFold demonstrated good recovery capabilities for templates perturbed with Gaussian noise (Figure 3a). The average TM-score increased from 0.90 ± 0.05 to 0.92 ± 0.06, and the lDDT score improved from 0.66 ± 0.00 to 0.82 ± 0.07. Notably, AlphaFold excelled at recovering structures projected onto the two-dimensional PCA space. Here, refinement significantly boosted accuracy, with the average TM-score rising from a low 0.49 ± 0.08 to 0.86 ± 0.15 and the mean lDDT increasing from 0.53 ± 0.09 to 0.79 ± 0.12. While refinement also improved results for one-dimensional projections, the final refined scores (average TM-score: 0.44 ± 0.21 and mean lDDT: 0.39 ± 0.20) remained relatively low.

For the RFdiffusion based perturbation, we observed a gradual decrease in both TM-score and lDDT, as the number of partial diffusion steps increased. The average TM-score dropped from 0.97 ± 0.01 with one diffusion step to 0.87 ± 0.05 with 10 steps (Figure 3b), while the average lDDT fell from 0.80 ± 0.02 to 0.67 ± 0.04. These scores suggest that despite the perturbation, the protein remained within the same general fold. This implies that the starting point for refinement by AlphaFold was still favorable for recovery of the correct structure, rather than collapsing into an alternative fold. Interestingly, while the average TM-score remained relatively unchanged after AlphaFold refinement for all diffu-

sion steps, the average lDDT score consistently improved by around 0.04. This finding suggests that in this configuration, AlphaFold primarily refines local structures, with minimal adjustments to the protein backbone, as reflected by the stable TM-scores.

Previous research has shown that AlphaFold can estimate template quality more precisely by replacing all residues in the template with glycine extended with a C-β atom, and providing the sequence with all gaps and an empty multiple sequence alignment (AF2Rank) [27]. We implemented a similar method within OpenFold, which we term OF2Rank. Interestingly, while OF2Rank achieved lower performance compared to AlphaFold when recovering structures from templates perturbed with Gaussian noise or projected into 1D/2D PCA space, it showed comparable effectiveness for RFdiffusion-perturbed templates. Furthermore, the advantages of OF2Rank became more pronounced with increasing numbers of RFdiffusion steps. At 10 partial diffusion steps, OF2Rank increased the average lDDT reached by 0.03. Intriguingly, using an all-gap MSA yielded slightly better predictions compared to the single sequence MSA, mirroring observations from AF2Rank [27]. The average difference between the all-gap and single sequence pipelines for both average TM-score and average lDDT was approximately 0.03 each. However, overall, AlphaFold pipeline generally outperformed OF2Rank for the refinement of perturbed templates.

4   Discussion

This study investigated capabilities and limitations of AlphaFold's ability to understand protein structures. We designed a series of experiments to investigate how AlphaFold handles both local features, like side-chain packing, and global features, like perturbations to the backbone.

Our findings suggest that C-β atoms are crucial for AlphaFold to recognize a template as a valid protein structure. When C-βs are present, AlphaFold prioritizes side-chain packing and only marginally alters the backbone if the phylogenic signal is weak. Interestingly, a simple heuristic for C-β placement achieves performance comparable to providing the

original position of the C-β. However, providing more side-chain information of seemingly lower quality, like the predefined conformations from the CHARMM36 force field, did not significantly improve the side-chain packing performance. Furthermore, pre-packing the template with dedicated side-chain packing algorithms like FASPR and AttnPacker only marginally impacted the final packing performance by AlphaFold. This would further suggest that AlphaFold's understanding of the protein structure relies more on the presence of stereochemically valid C-β atoms than the detailed packing of the entire side chain.

We also observed that AlphaFold's side-chain packing performance remained nearly consistent regardless of residue burial depth, while the performance dropped significantly for surface residues when AlphaFold relied solely on the MSA. This finding underlines the importance of high-quality templates, especially when dealing with shallow MSAs.

Perturbing the input template with various methods revealed insightful details regarding AlphaFold's capabilities in recovering three-dimensional protein structures. AlphaFold efficiently recovered structures perturbed with Gaussian noise, which primarily involves local adjustments to bond lengths and angles within residues. This ease of recovery hints at AlphaFold potentially having learnt a biophysical energy model for proper steric interactions, similar to classical optimization methods that utilize molecular force fields. Even more striking is AlphaFold's ability to recover details of a three-dimensional protein structure from 2D-like templates. This suggests that AlphaFold can effectively navigate the transition from a limited structural representation to a full 3D structure. Research on OpenFold, a reimplementation of AlphaFold, showed that it first predicts a 2D representation during early stages of training before transitioning to 3D [2]. This finding raises the intriguing possibility that AlphaFold has preserved a similar internal representation of a protein structure.

A significant difference in relative performance was observed between AF and the OF2Rank method when refining templates perturbed with Gaussian noise or projected into 1D/2D PCA space, compared to those perturbed with RFdiffusion. The key distinction lies in the nature of the perturbations. RFdiffusion typically introduces realistic modifications that maintain valid protein structures, whereas other methods often generate structures with steric clashes and other imperfections.

The markedly lower performance of OF2Rank on these unrealistic protein structures highlights a potential strength of the underlying approach. By struggling with these templates, OF2Rank might be more adept at identifying unreliable starting points. This aligns with the notion that AlphaFold was trained on the assumption of structurally sound templates. When presented with corrupted starting structures and lacking a reliable MSA for guidance, AlphaFold's performance will decline as it grapples with reconciling the conflicting information.

Prior research on AlphaFold using MSA-free protocols suggests the structure module might have learned a valid biophysical energy function, independent of MSAs [27]. AlphaFold would then act as an unrolled optimizer and make iterative adjustments guided by the learned potential to find a low-energy state, corresponding to a refined protein structure. Our results support this hypothesis, but suggest limitations. This optimization likely operates within a restricted neighborhood that requires both the backbone and stereochemically valid C$-\beta$ atoms. Additionally, the function appears most effective for local molecular interactions, as evidenced by its successful handling of side-chain packing and Gaussian noise perturbations.

Our work provides valuable guidance for users to critically evaluate AlphaFold's predictions and identify scenarios where complementary tools might be necessary. These insights pave the way for further exploration of existing methods or the development of novel strategies to overcome AlphaFold's limitations, ultimately leading to more robust and reliable protein structure prediction.

5 Competing interests

No competing interest is declared.

6 Author contributions statement

J.A.G. and T.L. conceived the experiment(s), J.A.G. conducted the experiment(s), J.A.G. and T.L. analyzed the results. J.A.G. and T.L. wrote and reviewed the manuscript.

7 Acknowledgements

We thank Axel Giottonini for feedback on the manuscript.

This work is supported by funds from the FreeNovation 2023 grant and the Swiss National Science Foundation (PCEFP3_194606).

References

[1] Recep Adiyaman, Nicholas S Edmunds, Ahmet G Genc, Shuaa MA Alharbi, and Liam J McGuffin. Improvement of protein tertiary and quaternary structure predictions using the refold refinement method and the alphafold2 recycling process. *Bioinformatics Advances*, page vbad078, 2023.

[2] Gustaf Ahdritz, Nazim Bouatta, Sachin Kadyan, Qinghui Xia, William Gerecke, Timothy J O'Donnell, Daniel Berenberg, Ian Fisk, Niccolò Zanichelli, Bo Zhang, et al. Openfold: Retraining alphafold2 yields new insights into its learning mechanisms and capacity for generalization. *bioRxiv*, pages 2022–11, 2022.

[3] Christian B Anfinsen. Principles that govern the folding of protein chains. *Science*, 181(4096):223–230, 1973.

[4] Ahmet Bakan, Lidio M Meireles, and Ivet Bahar. Prody: protein dynamics inferred from theory and experiments. *Bioinformatics*, 27(11):1575–1577, 2011.

[5] Marco Biasini, Tobias Schmidt, Stefan Bienert, Valerio Mariani, Gabriel Studer, Jürgen Haas, Niklaus Johner, Andreas Daniel Schenk, Ansgar Philippsen, and Torsten Schwede. Openstructure: an integrated software framework for computational structural biology. *Acta Crystallographica Section D: Biological Crystallography*, 69(5):701–709, 2013.

[6] Christopher M. Bishop. *Pattern Recognition and Machine Learning (Information Science and Statistics)*. Springer, 1 edition, 2007.

[7] Stephen K Burley, Helen M Berman, Gerard J Kleywegt, John L Markley, Haruki Nakamura, and Sameer Velankar. Protein data bank (pdb): the single global macromolecular structure archive. *Protein crystallography: methods and protocols*, pages 627–641, 2017.

[8] UniProt Consortium. Uniprot: a worldwide hub of protein knowledge. *Nucleic acids research*, 47(D1):D506–D515, 2019.

[9] Tom Defay and Fred E Cohen. Evaluation of current techniques for ab initio protein structure prediction. *Proteins: Structure, Function, and Bioinformatics*, 23(3):431–445, 1995.

[10] Diego Del Alamo, Davide Sala, Hassane S Mchaourab, and Jens Meiler. Sampling alternative conformational states of transporters and receptors with alphafold2. *Elife*, 11:e75751, 2022.

[11] Robert D Finn, Jody Clements, and Sean R Eddy. Hmmer web server: interactive sequence similarity searching. *Nucleic acids research*, 39(suppl_2):W29–W37, 2011.

[12] Xiaoqiang Huang, Robin Pearce, and Yang Zhang. Faspr: an open-source tool for fast and accurate protein side-chain packing. *Bioinformatics*, 36(12):3758–3765, 2020.

[13] William Humphrey, Andrew Dalke, and Klaus Schulten. Vmd: visual molecular dynamics. *Journal of molecular graphics*, 14(1):33–38, 1996.

[14] John Jumper, Richard Evans, Alexander Pritzel, Tim Green, Michael Figurnov, Olaf Ronneberger, Kathryn Tunyasuvunakool, Russ

Bates, Augustin Žídek, Anna Potapenko, et al. Highly accurate protein structure prediction with alphafold. *Nature*, 596(7873):583–589, 2021.

[15] Andriy Kryshtafovych, Torsten Schwede, Maya Topf, Krzysztof Fidelis, and John Moult. Critical assessment of methods of protein structure prediction (casp)—round xiii. *Proteins: Structure, Function, and Bioinformatics*, 87(12):1011–1020, 2019.

[16] Andriy Kryshtafovych, Torsten Schwede, Maya Topf, Krzysztof Fidelis, and John Moult. Critical assessment of methods of protein structure prediction (casp)—round xiv. *Proteins: Structure, Function, and Bioinformatics*, 89(12):1607–1617, 2021.

[17] Timo Lassmann. Kalign 3: multiple sequence alignment of large datasets, 2020.

[18] Valerio Mariani, Marco Biasini, Alessandro Barbato, and Torsten Schwede. lddt: a local superposition-free score for comparing protein structures and models using distance difference tests. *Bioinformatics*, 29(21):2722–2728, 2013.

[19] Matthew McPartlon and Jinbo Xu. An end-to-end deep learning method for protein side-chain packing and inverse folding. *Proceedings of the National Academy of Sciences*, 120(23):e2216438120, 2023.

[20] Elaine C Meng, Thomas D Goddard, Eric F Pettersen, Greg S Couch, Zach J Pearson, John H Morris, and Thomas E Ferrin. Ucsf chimerax: Tools for structure building and analysis. *Protein Science*, 32(11):e4792, 2023.

[21] Milot Mirdita, Konstantin Schütze, Yoshitaka Moriwaki, Lim Heo, Sergey Ovchinnikov, and Martin Steinegger. Colabfold: making protein folding accessible to all. *Nature methods*, 19(6):679–682, 2022.

[22] Milot Mirdita, Martin Steinegger, F Breitwieser, Johannes Söding, and E Levy Karin. Fast and sensitive taxonomic assignment to metagenomic contigs. *Bioinformatics*, 37(18):3029–3031, 2021.

[23] Milot Mirdita, Lars Von Den Driesch, Clovis Galiez, Maria J Martin, Johannes Söding, and Martin Steinegger. Uniclust databases of clustered and deeply annotated protein sequences and alignments. *Nucleic acids research*, 45(D1):D170–D176, 2017.

[24] Alex L Mitchell, Alexandre Almeida, Martin Beracochea, Miguel Boland, Josephine Burgin, Guy Cochrane, Michael R Crusoe, Varsha Kale, Simon C Potter, Lorna J Richardson, et al. Mgnify: the microbiome analysis resource in 2020. *Nucleic acids research*, 48(D1):D570–D578, 2020.

[25] Fabian Pedregosa, Gaël Varoquaux, Alexandre Gramfort, Vincent Michel, Bertrand Thirion, Olivier Grisel, Mathieu Blondel, Peter Prettenhofer, Ron Weiss, Vincent Dubourg, et al. Scikit-learn: Machine learning in python. *the Journal of machine Learning research*, 12:2825–2830, 2011.

[26] João PGLM Rodrigues, João MC Teixeira, Mikaël Trellet, and Alexandre MJJ Bonvin. Pdb-tools: a swiss army knife for molecular structures. *F1000Research*, 7, 2018.

[27] James P Roney and Sergey Ovchinnikov. State-of-the-art estimation of protein model accuracy using alphafold. *Physical Review Letters*, 129(23):238101, 2022.

[28] Maxim V Shapovalov and Roland L Dunbrack. A smoothed backbone-dependent rotamer library for proteins derived from adaptive kernel density estimates and regressions. *Structure*, 19(6):844–858, 2011.

[29] Andrew Shrake and John A Rupley. Environment and exposure to solvent of protein atoms. lysozyme and insulin. *Journal of molecular biology*, 79(2):351–371, 1973.

[30] Jascha Sohl-Dickstein, Eric Weiss, Niru Maheswaranathan, and Surya Ganguli. Deep unsupervised learning using nonequilibrium thermodynamics. In *International conference on machine learning*, pages 2256–2265. PMLR, 2015.

[31] Martin Steinegger, Markus Meier, Milot Mirdita, Harald Vöhringer, Stephan J Haunsberger, and Johannes Söding. Hh-suite3 for fast remote homology detection and deep protein annotation. *BMC bioinformatics*, 20(1):1–15, 2019.

[32] Baris E Suzek, Yuqi Wang, Hongzhan Huang, Peter B McGarvey, Cathy H Wu, and UniProt Consortium. Uniref clusters: a comprehensive and scalable alternative for improving sequence similarity searches. *Bioinformatics*, 31(6):926–932, 2015.

[33] Susana Vázquez Torres, Philip JY Leung, Isaac D Lutz, Preetham Venkatesh, Joseph L Watson, Fabian Hink, Huu-Hien Huynh, Andy Hsien-Wei Yeh, David Juergens, Nathaniel R Bennett, et al. De novo design of high-affinity protein binders to bioactive helical peptides. *Biorxiv*, pages 2022–12, 2022.

[34] Wouter G Touw, Coos Baakman, Jon Black, Tim AH Te Beek, Elmar Krieger, Robbie P Joosten, and Gert Vriend. A series of pdb-related databanks for everyday needs. *Nucleic acids research*, 43(D1):D364–D368, 2015.

[35] Mihaly Varadi, Stephen Anyango, Mandar Deshpande, Sreenath Nair, Cindy Natassia, Galabina Yordanova, David Yuan, Oana Stroe, Gemma Wood, Agata Laydon, et al. Alphafold protein structure database: massively expanding the structural coverage of protein-sequence space with high-accuracy models. *Nucleic acids research*, 50(D1):D439–D444, 2022.

[36] Björn Wallner. Afsample: improving multimer prediction with alphafold using massive sampling. *Bioinformatics*, 39(9):btad573, 2023.

[37] Joseph L Watson, David Juergens, Nathaniel R Bennett, Brian L Trippe, Jason Yim, Helen E Eisenach, Woody Ahern, Andrew J Borst, Robert J Ragotte, Lukas F Milles, et al. De novo design of protein structure and function with rfdiffusion. *Nature*, 620(7976):1089–1100, 2023.

[38] Yang Zhang and Jeffrey Skolnick. Scoring function for automated assessment of protein structure template quality. *Proteins: Structure, Function, and Bioinformatics*, 57(4):702–710, 2004.