Biophysics-based protein language models for protein engineering

Sam Gelman[1, 2]**, Bryce Johnson**[1, 2]**, Chase Freschlin**[3]**, Sameer D'Costa**[3]**, Anthony Gitter**[1, 2, 4, *]**, and Philip A. Romero**[3, *]

[1]Department of Computer Sciences, University of Wisconsin-Madison
[2]Morgridge Institute for Research
[3]Department of Biochemistry, University of Wisconsin-Madison
[4]Department of Biostatistics and Medical Informatics, University of Wisconsin-Madison
[*]These authors contributed equally to this work

ABSTRACT

Protein language models trained on evolutionary data have emerged as powerful tools for predictive problems involving protein sequence, structure, and function. However, these models overlook decades of research into biophysical factors governing protein function. We propose Mutational Effect Transfer Learning (METL), a protein language model framework that unites advanced machine learning and biophysical modeling. Using the METL framework, we pretrain transformer-based neural networks on biophysical simulation data to capture fundamental relationships between protein sequence, structure, and energetics. We finetune METL on experimental sequence-function data to harness these biophysical signals and apply them when predicting protein properties like thermostability, catalytic activity, and fluorescence. METL excels in challenging protein engineering tasks like generalizing from small training sets and position extrapolation, although existing methods that train on evolutionary signals remain powerful for many types of experimental assays. We demonstrate METL's ability to design functional green fluorescent protein variants when trained on only 64 examples, showcasing the potential of biophysics-based protein language models for protein engineering.

Introduction

Just as words combine to form sentences that convey meaning in human languages, the specific arrangement of amino acids in proteins can be viewed as an information-rich language describing molecular structure and behavior. Protein language models (PLMs) harness advances in natural language processing to decode intricate patterns and relationships within protein sequences [1]. These models learn meaningful, low-dimensional representations that capture the semantic organization of protein space and have broad utility in protein engineering [2]. PLMs can be adapted to specific protein properties like enzyme activity or stability with limited training examples [3, 4], and they can be used in predictive or generative settings to design custom-made proteins with desired characteristics [5, 6].

PLMs such as UniRep [7] and Evolutionary Scale Modeling (ESM) [8] are trained on vast repositories of natural protein sequences distributed across the evolutionary tree. The training process typically involves self-supervised autoregressive next token prediction or masked token prediction [1]. Through this process, PLMs learn context-aware representations of amino acids within proteins. Training on examples of natural proteins produces PLMs that implicitly capture protein structure, biological function, and other evolutionary pressures. While these models are powerful, they do not take advantage of the extensive knowledge of protein biophysics and molecular mechanisms acquired over the last century, and thus, they are largely unaware of the underlying physical principles governing protein function.

We introduce Mutational Effect Transfer Learning (METL), a pretraining strategy that integrates biophysical knowledge into PLMs. We use molecular modeling to generate large-scale synthetic data across diverse protein sequences and folds, and we pretrain a transformer-based PLM on this data to capture the underlying biophysical knowledge. We finetune the pretrained model using experimental sequence-function data, producing biophysics-aware models that can predict specific protein properties. METL excels in protein engineering tasks like generalizing from small training sets and extrapolating to mutations not observed in the training data. We demonstrate METL's ability to design functional green fluorescent protein (GFP) variants when trained on only 64 examples. METL provides a general framework for incorporating biophysical knowledge into PLMs and will become increasingly powerful with advances in molecular modeling and simulation methods.

Results

Pretraining protein language models with synthetic data generated from molecular modeling

Deep neural networks and language models are revolutionizing protein modeling and design, but these models struggle in low data settings and when generalizing beyond their training data. Although neural networks have proven capable in learning complex sequence-structure-function relationships, they largely ignore the vast accumulated knowledge of protein biophysics, limiting their ability to perform the strong generalization needed for protein engineering, which is the process of modifying a protein to improve its properties [9]. We introduce a framework that incorporates synthetic data from molecular simulations as a means to augment experimental data with biophysical information (Fig. 1). Molecular modeling can generate large datasets revealing mappings from amino acid sequences to protein structure and energetic attributes. Pretraining on this data imparts fundamental biophysical knowledge that can be connected with experimental observations.

We introduce the METL framework for learning protein sequence-function relationships. METL operates in three steps: synthetic data generation, synthetic data pretraining, and experimental data finetuning. First, we generate synthetic pretraining

Figure 1. Mutational Effect Transfer Learning (METL). (a) METL combines sparse experimental protein sequence-function data with dense biophysical simulation data to learn biophysics-informed sequence-function landscapes. **(b)** The pretraining phase involves generating millions of protein sequence variants and computing biophysical attributes for them with Rosetta, which are then used to pretrain a protein language model. The model is subsequently finetuned with experimental sequence-function data to predict protein properties such as binding, enzyme activity, thermostability, and expression. **(c)** The METL architecture consists of a transformer encoder with a structure-based relative position embedding. **(d)** METL-Local and METL-Global differ in the sequences included in the pretraining data. METL-Local trains on the local sequence space around a protein of interest, learning a representation specific to that protein. METL-Global trains on diverse sequences across protein fold space, learning a general-purpose protein representation.

data via molecular modeling with Rosetta [10] to model the structures of millions of protein sequence variants. For each modeled structure, we extract 55 biophysical attributes including molecular surface areas, solvation energies, van der Waals interactions, and hydrogen bonding (Table S1). Second, we pretrain a transformer encoder [11] to learn relationships between amino acid sequences and these biophysical attributes and to form an internal representation of protein sequences based on their underlying biophysics. The transformer utilizes a protein structure-based relative positional embedding [12] that considers the three-dimensional distances between residues. Finally, we finetune the pretrained transformer encoder on experimental sequence-function data to produce a model that integrates prior biophysical knowledge with experimental data. The finetuned models input new sequences and predict the particular property learned from the sequence-function data.

We implement two pretraining strategies, METL-Local and METL-Global, that specialize across different scales of protein sequence space (Fig. 1d). METL-Local learns a protein representation targeted to a specific protein of interest. We start with the protein of interest, generate 20M sequence variants with up to 5 random amino acid substitutions, model the variants' structures using Rosetta, compute the biophysical attributes, and train a transformer encoder to predict the biophysical attributes from sequence. METL-Local demonstrates strong predictive performance on these attributes (Fig. S1a), achieving a mean Spearman correlation of 0.96 for Rosetta's *total score* energy term across the seven METL-Local source models we trained. Although METL-Local accurately recapitulates the biophysical attributes, the primary purpose of pretraining is to learn an information-rich protein representation that can be finetuned on experimental data.

METL-Global extends the pretraining to encapsulate a broader protein sequence space, learning a general protein representation applicable to any protein of interest. We select 148 diverse base proteins [13] and generate 200k sequence variants with up to 5 random amino acid substitutions for each. We then model the approximately 30M resulting structures with Rosetta, extract biophysical attributes, and train a transformer encoder, following a similar methodology to METL-Local. With METL-Global, we observed a substantial difference in predictive ability for in-distribution structures (those included in the METL-Global pretraining data, Rosetta *total score* Spearman correlation of 0.85) and out-of-distribution structures (those not included, Rosetta *total score* Spearman correlation of 0.17) (Fig. S1b), indicating METL-Global overfits to the 148 base proteins present in the pretraining data. However, we find it still captures biologically relevant amino acid embeddings (Fig. S2) that are informative for protein engineering tasks even on the out-of-distribution proteins.

Generalization abilities of biophysics-based protein language models

Generalizing to new data is challenging for neural networks trained with small or biased datasets. This issue is crucial in protein engineering because experimental datasets often have few training examples and/or skewed mutation distributions. These factors impact the accuracy and utility of learned models when using them to design new protein variants.

We rigorously evaluated the predictive generalization performance of METL on eight experimental datasets, representing proteins of varying sizes, folds, and functions: GFP, DLG4, GB1, GRB2-Abundance, GRB2-Binding, Pab1, TEM-1, and Ube4b (Table S2). We compared METL to established baseline methods, including Rosetta's *total score* as a standalone prediction, evolutionary model of variant effect (EVE) [14] as a standalone prediction, linear regression with a one hot amino acid sequence encoding (Linear), an augmented EVE model that includes the EVE score as an input feature to linear regression in combination with the amino acid sequence (Linear-EVE) [15], and the ESM-2 [16] PLM finetuned on experimental sequence-function data. We created comprehensive train, validation, and test splits, encompassing small training set sizes and difficult extrapolation tasks, and we tested multiple split replicates to account for variation in the selection of training examples.

We evaluated the models' ability to learn from limited data by sampling reduced training sets and evaluating performance as a function of training set size (Fig. 2). METL-Local and Linear-EVE consistently and substantially outperformed the other supervised methods on small training sets. The relative merits of METL-Local versus Linear-EVE partly depend on the respective correlations of Rosetta *total score* and EVE with the experimental data. For instance, GFP has the highest correlation with Rosetta *total score*, and METL-Local is the best performing model. However, as the number of training examples increases, the METL-Local performance becomes dominated by dataset-specific effects rather than Rosetta *total score* relevance (Fig. S3). The general protein representation models, METL-Global and ESM-2, were outperformed by the protein-specific models, METL-Local and Linear-EVE. METL-Global and ESM-2 were competitive with each other for small to mid-size training sets, but METL-Global had an advantage on GFP, GRB2-A, and TEM-1. ESM-2 sometimes surpassed

Figure 2. Comparative performance of Linear, Rosetta *total score*, EVE, Linear-EVE, ESM-2, METL-Global, and METL-Local across different training set sizes. Learning curves for eight datasets showing the test set Spearman correlation between true and predicted protein function scores across a number of training set sizes ranging from 8 to 16,384 examples. We tested multiple replicates for each training set size, starting with 101 replicates for the smallest train set size and decreasing to 3 replicates for the largest size. We show the median Spearman correlation across these replicates. The top left panel ("Average") shows the mean of the learning curves across the eight datasets.

METL-Global by a small margin as the training set size increased.

We implemented four challenging extrapolation tasks — mutation, position, regime, and score extrapolation — to simulate realistic protein engineering scenarios, such as datasets lacking mutations at certain positions, having biased score distributions with predominantly low-scoring variants, and consisting of solely single-substitution variants (Fig. 3). Mutation extrapolation evaluates a model's ability to generalize across the 20 amino acids and make predictions for specific amino acid substitutions not present in the training data [17] (Fig. 3a). The model observes some amino acid types at a given position and must infer the effects of the other unobserved amino acids. We found METL-Local and ESM-2 displayed the strongest performance for mutation extrapolation, achieving an average Spearman correlation of 0.77 across datasets. Position extrapolation evaluates a model's ability to generalize across sequence positions and make predictions for amino acid substitutions at sites that do not vary in the training data [17–19] (Fig. 3b). This task is more challenging than mutation extrapolation and requires the model to possess substantial prior knowledge or a structural understanding of the protein [20]. METL-Local displayed the strongest overall performance for position extrapolation, with EVE and Linear-EVE also performing well. METL-Local's success in mutation and position extrapolation is likely the result of the local pretraining data, which includes all mutations at all positions, providing the model with comprehensive prior knowledge of the local landscape.

Regime extrapolation tests a model's ability to predict how mutations combine by training on single amino acid substitutions and predicting the effects of multiple substitutions [18, 19, 21, 22] (Figs. 3c and S4). All the supervised models, including

Figure 3. Comparative performance across extrapolation tasks. Correlation performance of Linear, Rosetta *total score*, EVE, Linear-EVE, ESM-2, METL-Global, and METL-Local on position, mutation, regime, and score extrapolation. We tested 9 replicates for each type of extrapolation and show the median.

linear regression, perform well at regime extrapolation, indicating the functional landscape is dominated by additive effects. Score extrapolation tests a model's ability to train on variants with lower-than-wild-type scores and predict variants with higher-than-wild-type scores [22] (Fig. 3d). This proves to be a challenging extrapolation task, with all models achieving a Spearman correlation less than 0.3 for most data sets. GB1 is an exception, where all supervised models achieve Spearman correlations of at least 0.55, and both METL-Local and METL-Global display correlations above 0.7. The difficulty of score extrapolation might be attributed to the fact that the mechanisms to break a protein are distinctly different than those to enhance its activity. It is notable that Rosetta *total score* and EVE, which are not trained on experimental data, perform worse at score extrapolation than they do at the other extrapolation tasks. This indicates these methods are largely capturing whether a sequence is active or inactive, rather than the finer details of protein activity.

We performed the above prediction and extrapolation tasks with several additional baselines, including METL-Local with random initialization (Fig. S5), augmented linear regression with Rosetta's *total score* as an input feature (Fig. S6), and sequence convolutional networks and fully connected networks (Fig. S7). METL-Local outperformed these additional baselines on nearly every prediction task for every dataset or provided much better scalability. Further, we conducted a systematic evaluation of the METL architecture to investigate one-dimensional (sequence-based) versus three-dimensional (structure-based) relative position embeddings (Fig. S8), feature extraction versus finetuning (Fig. S9), global model sizes (Figs. S10 and S11), and the extent of overfitting to the pretraining biophysical data (Fig. S12).

Relative information value of simulated versus experimental data

METL models are trained on both simulated and experimental data. Generating simulated data is orders of magnitude faster and less expensive than experimental data. We wanted to understand how these two sources of data interact and if simulated data can partially compensate for a lack of experimental data. To quantify the relative information value of simulated versus experimental data, we measured the performance of the GB1 METL-Local model pretrained on varying amounts of simulated data and finetuned with varying amounts of experimental data (Fig. 4). Increasing both data sources improves model performance, and there are eventually diminishing returns for adding additional simulated and experimental data. The shaded regions of Fig. 4 define iso-performance lines with simulated and experimental data combinations that perform similarly. For instance, a METL-Local model pretrained on 1,000 simulated data points and finetuned on 320 experimental data points performs similarly to one pretrained on 8,000 simulated data points and finetuned on only 80 experimental data points. In this example, adding 7,000 simulated data points is equivalent to adding 240 experimental data points, and thus ~29 simulated data points give the same performance boost as a single experimental data point. Ultimately, the information value from adding additional simulated or experimental data depends on the model's current performance and the effects of diminishing returns at that point.

Figure 4. Relationship between experimental and simulated data quantities for GB1. The contour plot illustrates the test set Spearman's correlation resulting from training METL-Local with varying amounts of simulated (pretraining) and experimental (finetuning) data. The plot displays a grid of Spearman's correlation values corresponding to discrete combinations of experimental and simulated dataset sizes. The model benefits from larger quantities of experimental and simulated data, with the latter producing diminishing returns after approximately 128k examples.

Synthetic data pretraining imparts biophysical knowledge

The purpose of METL's pretraining is to learn a useful biophysics-informed protein representation. To further probe METL's pretraining and gain insights into what the PLM has learned, we examined attention maps and residue representations for the GB1 METL-Local model after pretraining on molecular simulations but before finetuning on experimental data (Fig. 5). Our METL PLMs with 3D relative position embeddings start with a strong inductive bias and include the wild-type protein structure as input. After pretraining, the METL attention map for the wild-type GB1 sequence closely resembles the residue distance matrix of the wild-type GB1 structure (Fig. 5ab). In contrast, an alternative METL model with 1D relative position embeddings that does not use the GB1 structure while training fails to learn an attention map that resembles the GB1 contacts (Fig. 5c). The 3D relative position embedding and pretraining successfully allows METL to focus attention on residue pairs that are close in 3D space and may be functionally important.

We further explored the information encoded in the pretrained GB1 METL model by visualizing residue-level representations at each sequence position, averaged across amino acid types (Fig. 5d). These residue-level representations show strong clustering based on a residue's solvent accessibility and weaker organization based on a residue's location in the three-dimensional structure. This suggests the pretrained METL model has an underlying understanding of protein structure and important factors like residue burial, even before it has seen any experimental data.

Figure 5. METL attention maps and residue representations relate to structure and biophysical properties. (a) The residue distance matrix shows $C\beta$ distances between residues for the wild-type GB1 structure. **(b-c)** The attention maps show the mean attention across layers and attention heads for the wild-type GB1 sequence when it is fed as input to the pretrained GB1 METL-Local model. The 3D structure-based relative position embeddings (RPEs) enable the network to focus attention on residues that are close in 3D space, effectively capturing GB1's structural contacts. The 1D sequence-based RPEs do not. **(d)** Principal component analysis (PCA) of the residue representations output by the pretrained GB1 METL-Local model, averaged across the 20 possible amino acids at each sequence position. Points are colored according to relative solvent accessibility (RSA) computed from the wild-type GB1 structure.

Function-specific synthetic data improves pretrained METL representations

METL models are pretrained on general structural and biophysical attributes but are not tailored to any particular protein property such as ligand binding, enzyme activity, or fluorescence. There is a great body of research using molecular simulations to model protein conformational dynamics, small molecule ligand and protein docking, enzyme transition state stabilization, and other function-specific characteristics [23–27]. These function-specific simulations can be used to generate METL pretraining data that is more closely aligned with target functions and experimental measurements. Similarity between pretraining and target tasks is important to achieve strong performance and avoid detrimental effects in transfer learning [28].

To demonstrate how function-specific simulations can improve the initial pretrained METL model and its performance after finetuning, we customized the GB1 simulations to more closely match the experimental conditions. The GB1 experimental data measured the binding interaction between GB1 variants and Immunoglobulin G (IgG) [29]. To match this experimentally characterized function, we expanded our Rosetta pipeline to model the GB1-IgG complex and compute 17 attributes related to energy changes upon binding (Table S3). These function-specific attributes are more correlated with the experimental data than the general biophysical attributes (Fig. S13), showing how they can improve model pretraining.

We pretrained a METL PLM that incorporates the IgG binding attributes into its pretraining data and refer to it as METL-

Bind (Fig. 6a). METL-Bind outperformed a standard METL-Local PLM, pretrained only with GB1 biophysical attributes, when finetuned on limited experimental data (Fig. 6b-c). Pretraining on the additional GB1-IgG complex attributes successfully improved the model's learned representation. We calculated the predictive error for each residue position in the GB1 sequence to understand if the two models specialize on distinct structural regions (Fig. 6d-e). METL-Bind performed better across most residue positions and was notably better at predicting mutation effects at the GB1-IgG interface. The residue where METL-Bind showed the largest improvement was glutamate 27, an interface residue vital for the formation of a stable GB1-IgG complex [30]. Pretraining on function-specific simulations provides METL with an initial awareness of protein function that can be integrated with experimental data.

Figure 6. Function-specific simulations improve METL pretraining for GB1. (a) METL-Local pretrains on general Rosetta biophysical attributes from the standalone GB1 structure. METL-Bind pretrains on both general biophysical attributes from the standalone GB1 structure and binding-specific scores from the GB1-IgG complex structure. **(b-c)** Learning curves and extrapolation performance for Linear, METL-L, and METL-Bind on the GB1 dataset. We pretrained METL-L and METL-Bind on the same variants, differing only in the Rosetta score terms. We used the same finetuning dataset splits and replicates as in Figure 2. The vertical red bar denotes the median of the extrapolation replicates, and the square brackets indicate the median Spearman correlation. **(d-e)** The heatmap shows the fraction of test set variants for which METL-Bind has lower error than METL-L, broken down by sequence position. Results are shown for training set size 32 and averaged across replicates. Position 1 is marked with an "X" because the dataset does not contain variants with mutations in that position. The structure shows the GB1-IgG interface with the GB1 structure colored using same error fraction as the heatmap.

METL generalization to design diverse GFP variants

Predictive models can guide searches over the sequence-function landscape to enhance natural proteins or design new proteins [6, 31, 32]. However, these models often face the challenge of making predictions based on limited training data or extrapolating to unexplored regions of sequence space. To demonstrate METL's potential for real protein engineering applications, we tested METL-Local's ability to prioritize fluorescent GFP variants in these challenging design scenarios. We used METL-Local to design 20 GFP sequences that were not part of the original dataset, and we experimentally validated the resulting variants to measure their fluorescence brightness (Fig. 7).

We intentionally set up the design tasks to mimic real protein engineering settings with limited data and extrapolation. We

finetuned a METL-Local PLM on only 64 GFP variants randomly sampled from the full dataset. The 64 sampled variants had an average of 3.9 amino acid substitutions and a fitness distribution similar to the full dataset (Figs. S14 and S15). We designed variants with either 5 or 10 amino acid substitutions, forcing the model to perform regime extrapolation. Furthermore, we tested two design scenarios, *Observed AA* and *Unobserved AA*, in which designed variants were constrained to either include or exclude amino acid substitutions observed in the training set, respectively. The Unobserved AA setting forces the model to perform mutation extrapolation. We designed five variants at each extrapolation distance (5- and 10-mutants) and design setting (Observed AA and Unobserved AA) (Fig. S16 and Table S4). We used simulated annealing to search sequence space for GFP designs that maximize METL-Local's predicted fitness and clustered the designs to select diverse sequences.

We had the genes for the 20 GFP designs synthesized and cloned into an expression vector as a fusion protein with the fluorescent protein mKate2, emulating the conditions used to collect the training data [33]. The mKate2 is constant in each fusion protein, while the GFP sequence varies. The ratio of a GFP variant's fluorescence to mKate2's fluorescence provides an intrinsic measure of the GFP variant's "relative brightness" that is independent of the absolute protein expression level [34]. Overall, METL was successful at designing functional GFP variants, with 16 of the 20 designs exhibiting measurable fluorescence (Fig. 7c). Each design setting had notable differences in the success rates and fluorescence characteristics of the designed GFP sequences. The Observed design setting was 100% successful at designing fluorescent five (5/5) and ten (5/5) mutants, demonstrating METL's robust ability to learn from very limited data and extrapolate to higher mutational combinations. The more challenging Unobserved design setting had an 80% (4/5) hit rate with five mutants and a 40% (2/5) hit rate with ten mutants. The Unobserved designs were less bright than wild-type GFP and the Observed designs.

The mKate2 fluorescence signal provides additional insight into the designs (Fig. S17). The mKate2 protein is constant, so changes in its fluorescence signal are caused by changes in mKate2-GFP fusion protein concentration and thus provide an indirect readout of the GFP designs' folding, stability, solubility, and aggregation. The Observed designs all exhibit higher mKate2 fluorescence than wild-type GFP, possibly indicating moderate stabilization, while the Unobserved designs mostly exhibit lower mKate2 fluorescence than wild-type GFP, suggesting destabilization.

Figure 7. Low-N GFP Design. (a) Overview of the GFP design experiment. We used METL-Local to guide GFP design in a low-N setting with only $N = 64$ experimental training examples. We tested two different design constraints: *Observed AA*, where sequences contain only amino acid substitutions observed in the training set, and *Unobserved AA*, where sequences exclude any amino acid substitutions observed in the training set. **(b)** Multidimensional scaling (MDS) sequence space visualization of the wild-type GFP sequence, the 64 GFP training sequences, and the 20 designed proteins. The designed sequences contain either 5 or 10 amino acid substitutions from wild-type. Training set sequences are colored on a gradient according to their experimental brightness score. Designed sequences are colored according to whether they exhibited fluorescence, which we define as having at least 10% of wild-type GFP's brightness. **(c)** Experimentally characterized brightness (multiple replicates) of the designed sequences, the best training set sequence (BT), and the wild-type sequence (WT).

Discussion

Motivated by decades of research into biophysics, molecular dynamics, and protein simulation [10, 23, 24, 27, 35], we present METL, which leverages synthetic data from molecular simulations to pretrain biophysics-aware PLMs. These biophysical pretraining signals are in contrast to existing PLMs or multiple sequence alignment-based methods that train on natural sequences and capture signals related to evolutionary selective pressures [2, 7, 8, 14, 36, 37]. By pretraining on large-scale molecular simulations, METL builds a comprehensive map of protein biophysical space. This biophysically-informed representation provides valuable context for understanding protein sequence-function relationships. Pretrained METL models can be finetuned on experimental data to produce models that integrate biophysical knowledge and are capable of predicting properties such as binding, thermostability, and expression. METL excels at challenging protein engineering tasks such as learning from limited data and extrapolating to mutations not observed in the training data, enabling the design of new proteins with desired properties.

Our results highlight important differences between evolutionary data and biophysical simulations, especially in terms of their effectiveness for pretraining PLMs to understand sequence-function relationships and predict experimental functions. Evolutionary data, consisting of massive collections of naturally evolved protein sequences, captures information relevant to organismal fitness, including protein expression, folding, stability, and biological function. However, the precise selective pressures for each protein are different and largely unknown, and evolutionary patterns can be confounded by historical events, phylogenetic biases, and unequal sequence sampling [38]. In contrast, biophysical simulations allow precise control of the input sequence distribution, even sequences with non-natural amino acids [39, 40], and capture fundamental properties of protein structure and energetics. Yet, biophysical simulations are only imperfect approximations of the true physics.

Generally, we found that the evolution-based Linear-EVE outperformed the other approaches, followed by biophysics-based METL-Local and METL-Global, and lastly, the evolution-based ESM-2. The substantial performance difference between Linear-EVE and ESM-2 may be attributed to the fact that EVE is trained on a specific protein family while ESM-2 is a general PLM, and the benefits of augmented regression with EVE relative to PLM finetuning are consistent with prior work [15]. METL-Local outperformed the evolution-based models for the GFP and GB1 datasets. The relative performance of Linear-EVE and METL-Local was partly determined by a dataset's correlation with EVE and Rosetta *total score*, respectively. Certain protein properties and experimental measurements more closely align with either evolutionary or biophysical signals [41–43], providing guidance on where different models may excel. One of METL's key strengths is its ability to incorporate function-specific molecular modeling and simulations. For instance, pretraining on GB1-IgG binding data led to improved performance compared to our standard METL-Local model, which was pretrained only on GB1 structure-derived data. This opens the door to incorporating more sophisticated simulations, such as dynamic simulations of conformational transitions in allosteric regulation, quantum mechanics/molecular mechanics (QM/MM) studies of enzyme catalysis, coarse grained models of macromolecular machines, and small molecule docking to assess binding specificity.

Prior studies have integrated biophysics and machine learning either by using biophysics-based features as input to machine learning models or approximating biophysical simulations with machine learning. Rosetta and FoldX stability, energy, and docking terms have been provided as features for an augmented linear regression model [15], random forests [44, 45], a 2D CNN [46], and on nodes and edges in a graph neural network [47] for antibody and protein property prediction. Function-value-prior augmented-Bayesian Neural Networks can incorporate Rosetta stability as a prior on protein function prediction in regions where a Bayesian Neural Network has high epistemic uncertainty [48]. Nordquist et al. include both Rosetta- and molecular dynamics-derived features in their supervised learning models of big potassium channels [49]. Wittmann et al. evaluate Triad ΔΔG predictions for selecting initial variants for machine learning-guided directed evolution [50]. Unlike a finetuned METL-Local model, all of these approaches must run the biophysics calculations for each sequence prediction, which could limit their scalability to search sequence space for protein design. Other related work uses machine learning to approximate molecular simulations, usually with the goal of obtaining much faster approximate models. This scenario is similar to METL's pretraining stage. These methods include the Epistasis Neural Network that has been used to engineer xylanases [51] and GFP variants [52], molecular dynamics approximations to minimize energy and match a target structure [53], and learning to predict Rosetta protein-ligand binding energy to speed up variant scoring [54]. ForceGen trains a protein language diffusion model on molecular dynamics simulations of mechanical unfolding responses [55]. METL's pretraining on biophysical attributes for protein engineering is also related to the long-standing problem of predicting protein stability [56–67].

Machine learning-guided protein engineering is often data-limited due to experimental throughput constraints, with datasets sometimes containing as few as tens to hundreds of sequence-function examples [31, 68–73]. We demonstrated METL's performance in realistic protein engineering settings with limited data (low-N) and extrapolation. PLMs are an important component in many existing methods for low-N protein engineering. They have been used to extract protein sequence representations [3, 74–76], for finetuning on the low-N function data [76–78], and to generate auxiliary training data in more complex models [78–80]. Other computational strategies for addressing the low-N problem include Gaussian processes [75, 81, 82], augmenting regression models with sequence-based [15, 83] or structure-based [84] scores, custom protein

representations that can produce pretraining data [85], representations of proteins' 3D shape [86], meta learning [87], and contrastive finetuning [88].

Our GFP design experiments showcased METL's ability to learn from only 64 training examples and generalize to distant and unexplored regions of sequence space. METL's success in the Unobserved AA design setting was especially remarkable because it requires the model to infer the effects of mutations it has not observed and predict how these mutations combine in 5- and 10-mutants. It is notable that none of the designed GFPs appeared brighter than wild-type GFP. We estimated brightness as the ratio of GFP fluorescence to mKate2 fluorescence. We noticed many of the designed variants exhibited absolute GFP and mKate2 fluorescence signals higher than wildtype, indicating that the mKate2-GFP fusion protein may have increased expression levels and improved stability in these variants. In limited data settings, METL-Local's strong biophysical prior may indirectly improve designs through stabilizing effects rather than directly improving the brightness.

Examples across diverse scientific domains have demonstrated the power of combining simulations and machine learning [89], spanning topics such as gene regulatory network reconstruction [90], chemical foundation model pretraining [91], climate emulation [92], and quantum chemistry approximation [27, 93]. METL fits within this broader trend and represents a significant step toward effectively integrating biophysics insights with machine learning-based protein fitness prediction. The METL framework pretrains PLMs on molecular simulations to capture accumulated biophysical knowledge, and this pretraining strategy will benefit from continued advances in computation and molecular simulation. METL can pretrain on general structural and energetic terms or more focused function-specific terms, offering the potential to model completely non-natural protein functions with nonexistent evolutionary signals. PLMs fluent in fundamental biophysical dialect will push the boundaries of protein design to new realms of sequence-function space.

Methods

Generating Rosetta pretraining data

The Rosetta pretraining data consists of protein sequences and their corresponding score terms, computed by modeling the sequences with Rosetta. We refer to the METL models pretrained on the Rosetta biophysical attributes as source models. The data used for local and global source models differs in what sequences are included. Rosetta data for local source models contains protein variants within the local sequence space surrounding the protein of interest. Rosetta data for global source models contains protein variants from a diverse range of base sequences and structures.

We generated local Rosetta datasets for each target protein from the experimental datasets (Table S2). We acquired the target protein structures from RCSB Protein Data Bank [94] and AlphaFold Protein Structure Database [95]. For cases where the acquired structure did not match the reference sequence of the target protein, we used Rosetta comparative modeling or truncated the acquired structure to match the reference sequence. For each local pretraining dataset, we generated ~20M protein sequence variants with a maximum of 5 amino acid substitutions. See Table S5 for additional details regarding local Rosetta dataset structures and variants, including exceptions to the above.

We generated the global Rosetta dataset based on 150 diverse protein structures identified in Supplementary Table 1 of Kosciolek and Jones [13]. We downloaded the 150 structures from RCSB Protein Data Bank [94]. Some structures contained modified or missing residues. We replaced modified residues with canonical amino acids and used the RosettaRemodel application to fill in the structure of missing residues. We were unable to remodel PDB IDs 1J3A and 1JBE, thus we excluded these structures from the final dataset. For each of the remaining 148 structures, we generated ~200K variants with a maximum of 5 amino acid substitutions, for a total of ~30M variants.

We implemented a custom sub-variants sampling algorithm to generate the variants for both the local and global datasets. The algorithm iteratively samples a random variant with 5 amino acid substitutions from the wild-type sequence then generates all possible 4-, 3-, 2- and 1-substitution sub-variants with the same amino acid substitutions as the 5-substitution variant. Duplicate variants generated through this process are discarded. The iterations terminate when the target number of variants is reached. For the global dataset, we used the sub-variants sampling algorithm to generate all of the ~200K variants per base sequence. For the local datasets, we first generated all possible 1-substitution or 1- and 2-substitution variants, and then we used the sub-variants sampling algorithm to generate the remainder of the ~20M variants per target protein (Table S5).

Once sequence variants were generated, we used Rosetta to compute biophysical attributes for each variant sequence. We first prepared each base PDB file for use with Rosetta by following the recommendation in the Rosetta documentation. We ran Rosetta's *clean_pdb.py* and relaxed the structure with all-heavy-atom constraints. We generated 10 structures and selected the lowest energy structure to serve as the base structure for subsequent steps.

We used Rosetta v3.13 [10] to compute full-atom energy terms (ref2015 score function), centroid-atom energy terms (score3 score function), and custom filter terms based on Rocklin et al. [96]. For each variant, we introduced the variant's mutations to the corresponding base structure using a Rosetta resfile. Then, to generate the full-atom energy terms, we used FastRelax to relax the mutated structure using the ref2015 score function, only repacking residues within 10Å of the mutated residues, with 1 repeat. To generate the centroid-atom energy terms, we used score_jd2 to score the resulting structure using the score3 score

function. Finally, to generate the remainder of the score terms used in the standard version of METL, we used a RosettaScript to compute custom filter terms on the relaxed structure. To calculate additional binding scores for METL-Bind, we used the Rosetta InterfaceAnalyzer protocol. See Tables S1 and S3 for a list and description of each term. We designed a computing workflow based on HTCondor [97] to orchestrate the Rosetta scoring on the Open Science Pool [98].

Preprocessing Rosetta pretraining data

Prior to training neural networks, we preprocessed the raw Rosetta data by dropping variants with NaN values for any of the biophysical attributes, removing duplicates by randomly selecting one of the duplicates to keep, and filtering out variants with outlier *total_score* values. We grouped variants by base PDB and removed outliers independently for each group using a modified z-score method, which uses the median and median absolute deviation instead of the mean and standard deviation. For each data point i, we calculated the modified z-score using the following equation:

$$ s_i = \frac{|x_i - \tilde{x}|}{\text{MAD}}, \tag{1} $$

where s_i is the modified z-score, x_i is the Rosetta *total_score*, $\tilde{x}$ is the median *total_score* of the group, and MAD is the Median Absolute Deviation, defined as $\text{MAD} = \text{median}(|x_j - \tilde{x}|) \, \forall \, x_j \in \{x\}$, or the median of the absolute deviations of all data points from the median of the group. We removed variants with $s_i > 6.5$ from the dataset.

Additionally, we standardized the Rosetta scores to equalize the contribution of each score term to the model's loss function and to ensure score terms are comparable across different base PDBs in the global dataset. Once again, we grouped variants by base PDB, and then we standardized each group and score term independently by subtracting the mean and dividing by the standard deviation. We calculated the mean and standard deviation using only the training set data. This process scales the score terms to have zero mean and a standard deviation of one.

We excluded the following score terms from the final dataset because the values were zero for a large portion of base PDBs: dslf_fa13 (from ref2015 score function), linear_chainbreak and overlap_chainbreak (from score3 score function), and filter_total_score (custom filter term). We also discarded res_count_all (custom filter term that counts the residues in the protein) because it did not vary among variants of an individual protein. After these removals, 55 score terms remained (Table S1).

METL source model architecture

The METL source model architecture accepts amino acid sequences as input and outputs predictions for each of the 55 Rosetta score terms. The main component of the source model architecture is a transformer encoder based on the original transformer architecture [11], with the notable differences being the use of a relative positional embedding [12] instead of a sinusoidal positional encoding and pre-layer normalization instead of post-layer normalization [99]. METL-Local source models total ~2.5M parameters and have transformer encoders consisting of a 256 embedding size, 3 encoder layers, 4 attention heads, a 1024 feed forward hidden size, and 0.1 dropout. METL-Global source models total ~20M parameters and have transformer encoders consisting of a 512 embedding size, 6 encoder layers, 8 attention heads, a 2048 feed forward hidden size, and 0.1 dropout. We also evaluated a METL-Global source model with ~50M parameters, consisting of a similar architecture as the 20M parameter METL-Global source model but with 16 encoder layers instead of 6 encoder layers. After the transformer encoder, source models implement an additional layer normalization layer, a global average pooling layer, a nonlinear fully-connected layer, and a linear output layer with 55 output nodes corresponding to the 55 Rosetta score terms. The global average pooling layer computes the mean of the per-residue encodings, which are output from the encoder, to produce a sequence-level representation of the same size as the embedding dimension. This sequence-level encoding is fed into a fully-connected layer with 256 hidden nodes for the local model and 512 hidden nodes for the global model. We used the rectified linear unit (ReLU) activation function for the transformer encoder and final fully connected layer.

We implemented relative position embeddings as described by Shaw et al. [12]. In contrast to the absolute position encoding used in the original transformer architecture [11], the relative position embedding enables the network to consider positional representations of the inputs in terms of distances between sequence positions. We consider two distinct ways to encode relative distances, generating what we refer to as 1D positional embeddings and 3D positional embeddings. In the 1D approach, relative distances are based on the protein amino acid sequence alone. This approach is identical to the implementation of relative position embeddings described by Shaw et al. In the 3D approach, relative distances are based on the 3D protein structure.

In the 1D approach, we calculate relative distances by determining the offset between each pair of sequence positions (i, j) in the input. The relative distance is defined as $d = j - i$, representing how far sequence position j is relative to position i. A negative value signifies that j precedes i in the sequence, and a positive value signifies that j succeeds i. We map each of the possible relative distances to a pair of learnable embedding vectors, corresponding to attention keys and values. When calculating attention between sequence positions i and j, we add the key and value positional embedding vectors to the keys

and values, respectively. As was hypothesized by Shaw et al., precise relative position information might not be useful beyond a certain distance. Thus, we clipped the possible relative distances to ± 8.

In the 3D approach, we calculate relative distances using the protein 3D structure instead of the amino acid sequence. When using 3D relative position embeddings, the model requires a protein structure in the form of a PDB file, corresponding to the base protein that the input variant sequence is based on. We first represent the protein structure as an undirected graph, where each node corresponds to a residue. We place an edge between any pair of nodes if the beta carbon atoms ($C\beta$) of the residues are within 8Å of each other in the 3D space. We define the relative distance between residues (i, j) as the minimum path length from node i to node j in the graph. Unlike the 1D approach, relative distances computed using the 3D approach cannot be negative values. We clip the 3D relative distances at 3, effectively transforming distances greater than 3 into a relative distance of 3. A relative distance of 0 represents a node with itself, 1 signifies direct neighbors, 2 signifies second degree neighbors, and 3 encapsulates any other node not covered by the previous categories. As in the 1D approach, each possible relative distance in the 3D approach is mapped to a pair of embedding vectors corresponding to keys and values. These vectors are learned during training and are added to keys and values during the attention calculation.

METL source model training

We split the Rosetta source data into randomly sampled train, validation, test, and withheld sets. For each dataset, we first withheld 5% of the data to be used for final evaluations. We split the remaining data into 80% train, 10% validation, and 10% test sets.

We trained source models for 30 epochs using the AdamW optimizer [100] with a learning rate of 0.001. We applied a linear warm-up learning rate scheduler, with a warm-up period of 2% of the total training steps. Additional AdamW hyperparameters were $weight\_decay = 0.01$, $\beta_1 = 0.9$, $\beta_2 = 0.999$, and $\varepsilon = 1e-8$. We computed mean squared error loss independently for each of the 55 prediction tasks (corresponding to the 55 Rosetta biophysical attributes) and took the sum to compute the final loss for the network. We applied gradient norm clipping with a max norm of 0.5. We employed distributed data parallel (DDP) training with 4 GPUs using PyTorch Lightning [101, 102]. We trained local source models with an effective batch size of 2048 (512 x 4 GPUs) and global source models with an effective batch size of 1024 (256 x 4 GPUs). For the METL-Bind experiment, we trained both standard METL-Local and METL-Bind using the same process, except using 2 GPUs instead of 4 and a batch size of 1024 instead of 512, which yielded an effective batch size 2048, identical to the source models trained for the main experiment. METL-Bind was trained on 17 additional binding scores, for a total of $55 + 17 = 72$ tasks, but was otherwise identical to the standard METL-Local model.

The global source data contains variants of 148 base sequences, with most having different sequence lengths. This complicates the process of encoding data into a single fixed-length batch. Padding is a commonly employed approach in such scenarios. However, incorporating different sequence lengths and base structures in a single batch would negatively impact efficiency of computing attention with our implementation of relative position embeddings. Thus, we implemented a PDB-based data sampler that ensures each batch only contains variants from a single base PDB structure. Due to the use of DDP training with 4 GPUs, each aggregated training batch effectively contains variants from 4 base PDBs.

Experimental datasets for target model training

The METL target model architecture accepts amino acid sequences as input and outputs predictions for one specific protein function. We evaluated METL on experimental datasets representing proteins of varying sizes, folds, and functions: GFP [33], DLG4-2021 [103], DLG4 [104], GB1 [29], GRB2-Abundance [104], GRB2-Binding [104], Pab1 [105], TEM-1 [106], and Ube4b [107] (Table S2). We acquired raw datasets from published manuscript supplements, MaveDB [108], and NCBI GEO [109]. We transformed raw data into a standardized format, making sure that functional scores were log-transformed, normalized so that the wild-type score is 0, and rounded to 7 decimal places. We removed variants with mutations to stop codons and converted variant indexing to be 0-based. For DLG4-2021 and GB1, we filtered variants to ensure a minimum number of reads. See Table S6 for additional details about dataset transformations. We opted to use the DLG4 dataset instead of the DLG4-2021 dataset in our main analysis due to weak correlation between the two datasets (Fig. S18) and because linear regression yielded better results on the DLG4 dataset, suggesting a cleaner signal.

We used GB1 as an exploratory dataset during method development to make modeling decisions such as at what size validation set to enable model selection, where to place the prediction head on the source model, whether to use a linear or nonlinear prediction head, and others. Due to this, there is potential we overfit to GB1 and that our final results are optimistic for GB1. That said, we took precautions to limit the potential impact of using GB1 as our development dataset. The results presented for the small training set size experiment use an evaluation dataset that was completely held out, even during method development. The randomly sampled train and validation sets used to generate the final results are also different splits than the ones we used during method development. Additionally, the results presented for the extrapolation experiments use different splits than the ones we used to test extrapolation during method development.

We adjusted the GFP dataset preprocessing after seeing early small training set size results. Performance was lower than expected, which led us to realize that the dataset scores were not normalized so wild-type is 0. We modified the GFP dataset to normalize the scores and set wild-type to 0 by subtracting the wild-type score from all the scores. All our other datasets were already normalized so wild-type is 0.

METL target model architecture

METL target models are made up of a backbone and a head. The backbone contains network layers from the METL source model, pretrained to predict Rosetta biophysical attributes. The head is a new, randomly-initialized linear layer placed on top of the backbone to predict experimental functional scores. We also added a dropout layer with dropout rate 0.5 between the backbone and the head. For METL-Local source models, we attach the head immediately after the final fully connected layer. For METL-Global source models, we attach the head immediately after the global pooling layer. METL target models have a single output node corresponding to the experimental functional score prediction.

METL target model training

We implemented two training strategies for PLM target models: feature extraction and finetuning. Feature extraction is a training strategy where only the head is trained, and the backbone weights are not updated during the training process. In contrast, finetuning is a training strategy where both the backbone and head weights are updated during training. For feature extraction, we trained the head using scikit-learn [110] ridge regression with $alpha = 1.0$ and the cholesky solver. This provides a closed-form solution for the ridge regression weights.

For finetuning, we implemented a dual-phase finetuning strategy [111]. In the first phase, we froze the backbone and trained only the head for 250 epochs. In the second phase, we trained both the backbone and the head for an additional 250 epochs at a reduced learning rate. We used the AdamW optimizer with a learning rate of 0.001 in the first phase and 0.0001 in the second phase. We applied a learning rate scheduler with linear warm-up and cosine decay to each phase, with a warm-up period of 1% of the total training steps. Additional AdamW hyperparameters were set as follows: $weight\_decay = 0.1$, $\beta_1 = 0.9$, $\beta_2 = 0.999$, and $\varepsilon = 1e - 8$. We used a batch size of 128 and mean squared error loss. We applied gradient norm clipping with a max norm of 0.5.

After the full training period, we selected the model from the epoch with the lowest validation set loss. We only performed model selection if the validation set size was ≥ 32 for METL-Local and ≥ 128 for METL-Global and ESM. We found the optimization was more stable for METL-Local than METL-Global and ESM, thus smaller validation sets were still reliable. For validation sets smaller than those thresholds, we did not perform model selection. Instead we used the model from the last epoch of training. We determined these thresholds using the GB1 dataset, which we designated as our development dataset, by selecting the dataset size along the learning curve where using model selection started to outperform not using model selection. In retrospect, these thresholds were too low for other datasets, leading to the dips in METL-Global correlations observed in Figure 2.

Target model dataset splits

We created comprehensive train, validation, and test splits to evaluate performance with small training set sizes and a range of extrapolation tasks, including position, mutation, regime, and score extrapolation. For small training set sizes, we first sampled a random 10% test set from each full dataset. Then, from the remaining data, we sampled datasets of sizes 10, 20, 40, 80, 160, 320, 640, 1280, 2560, 5120, 10240, and 20480. To account for especially easy or difficult training sets that may be sampled by chance, we generated multiple replicates for each dataset size. The number of replicates decreases as the dataset size increases: 101 replicates for the smallest dataset size, followed by 23, 11, 11, 11, 7, 7, 5, 5, 3, and 3 replicates for the largest dataset size. We split the sampled datasets into 80% train and 20% validation sets. We used the same test set across all dataset sizes and replicates. We report median performance metrics across replicates.

Whereas the small dataset splits are sampled randomly, the extrapolation splits are specially designed to assess the models' ability to generalize to more challenging test sets. For position, mutation, and score extrapolation, we randomly resampled any datasets with > 50000 variants down to 50000 variants before generating the extrapolation splits. To account for random effects, we generated 9 replicate splits for each extrapolation type. We report the median across the 9 replicates.

Position extrapolation tests the ability of a model to generalize to sequence positions not present in the training data. To generate position extrapolation splits, we first randomly designated 80% of sequence positions as train and the other 20% as test. Then, we divided variants into training and testing pools depending on whether the variants contain mutations only in positions designated as train or only in positions designated as test. We discarded variants that had mutations in both train and test positions. To create the final train, validation, and test sets, we split the train pool into a 90% train set and a 10% validation set. We used the entire test pool as the test set.

Mutation extrapolation tests the ability of a model to generalize to mutations not present in the training data. To generate mutation extrapolation splits, we followed a similar procedure as position extrapolation, except with mutations instead of

sequence positions. We randomly designated 80% of mutations present in the dataset as train and the other 20% as test. We divided variants into training and testing pools depending on whether the variants contain only mutations designated as train or only designated as test. We split the train pool into a 90% train and a 10% validation set and used the entire test pool as the test set.

Regime extrapolation tests the ability of the model to generalize from lower numbers of amino acid substitutions to higher numbers of amino acid substitutions. For datasets with single and double substitution variants, we divided the variants into a train pool comprising of the single substitution variants and a test pool comprising of the double substitution variants. We split the train pool into into an 80% train and a 20% validation set. We sampled a 10% test set from the test pool. For datasets containing greater than double substitution variants, we also implemented another regime extrapolation split where the train pool was comprised of single and double substitution variants and the test pool was comprised of variants with three or more substitutions.

Score extrapolation tests the ability of a model to generalize from low-scoring variants to high-scoring variants. We divided variants into train and test pools depending on whether the variant had a score less than wild-type (train pool) or greater than wild-type (test pool). We split the train pool into a 90% train and a 10% validation set and used the entire test pool as the test set.

Baseline models

We implemented and evaluated additional baseline models: Linear, a fully connected neural network (FCN), a sequence convolutional neural network (CNN), METL-Local with random initialization, Rosetta's *total score* as a standalone prediction, and linear regression with Rosetta *total score* (Linear-RTS).

Linear is a linear regression model that uses one hot encoded sequences as inputs. One hot encoding captures the specific amino acid at each sequence position. It consists of a length 21 vector where each position represents one of the possible amino acids or the stop codon. All positions are zero except the position of the amino acid being encoded, which is set to a value of one. Note that we removed variants containing mutations to the stop codon during dataset preprocessing, so this feature was not used in our analysis. We implemented linear regression using scikit-learn's ridge regression class, which incorporates L2 regularization. We set the solver to *cholesky* to calculate a closed-form solution for the ridge regression weights. We set *alpha*, the constant that controls regularization strength, to the default value of 1.0. We set all other parameters to the default scikit-learn values.

For baseline neural networks, we tested an FCN, a CNN, and a transformer encoder with a similar architecture as METL-Local, but with a random initialization. The FCN and CNN used one hot encoded sequences as input. The FCN consisted of 1 hidden layer with 1024 nodes followed by a dropout layer with a dropout rate of 0.2. The CNN consisted of 1 convolutional layer with kernel size 7, 128 filters, and zero-padding to ensure the output has the same shape as the input (padding mode "same" in PyTorch's Conv2d class). Following the convolutional layer, we placed a fully connected layer with 256 nodes and a dropout layer with a dropout rate of 0.2. We used the ReLU activation function for both models. In addition to the FCN and CNN, we tested a randomly initialized transformer encoder neural network with a similar architecture as METL-Local. Unlike METL-Local, this randomly initialized version was set up with a single output node corresponding to the experimental functional score instead of multiple output nodes corresponding to Rosetta scores.

We trained the FCN, CNN, and randomly initialized METL-Local for 500 epochs using the AdamW optimizer with a base learning rate of 0.001. We applied a learning rate scheduler with linear warm-up and cosine decay, with a warm-up period of 2% of the total training steps. Additional AdamW hyperparameters were set as follows: $weight\_decay = 0.1$, $\beta_1 = 0.9$, $\beta_2 = 0.999$, and $\varepsilon = 1e - 8$. We used a batch size of 128 and mean squared error loss. We applied gradient norm clipping with a max norm of 0.5. Similar to METL-Local finetuning, we selected the model from the epoch with the lowest validation loss when the validation set size was ≥ 32. Otherwise, we used the model from the last epoch of training.

We evaluated Rosetta's *total score* as a standalone, unsupervised prediction, as well as an additional input feature for linear regression, which we refer to as Linear-RTS. By default, the lower Rosetta's *total score*, the more stable the structure is predicted to be. Thus, when using Rosetta's *total score* as an unsupervised prediction, we multiplied it by -1 before computing correlation with the experimental functional score. We also tested Rosetta's *total score* as part of a supervised learning framework. Linear-RTS is identical to Linear, but it uses Rosetta *total score* as an additional input feature in combination with the one hot encoded sequence in an augmented regression setting [15]. We standardized the *total score* for use as an input feature by first calculating its mean and standard deviation in the train set. Then, we subtracted the mean and divided by the standard deviation.

Comparison to ESM-2

We used the ESM-2 [16] 35M parameter model with identifier esm2_t12_35M_UR50D as our default ESM model so that the comparisons with the 20M parameter METL-Global model would primarily emphasize their different pretraining strategies rather than model size. We incorporated several additional layers to match the METL architecture, including a global mean

pooling layer, a dropout layer with dropout rate 0.5, and a linear prediction head. We attached these additional layers immediately after layer 12. We trained the ESM-2 models using the same training procedures we used for the METL models. We also explored feature extraction with larger 150M and 650M parameter ESM-2 models (identifiers esm2_t30_150M_UR50D and esm2_t33_650M_UR50D). For these larger models, we attached the additional layers after layers 30 and 33, respectively.

Comparison to EVE

We obtained multiple sequence alignments (MSAs) for GB1, Ube4b, GFP, and Pab1 from the EVcouplings web server [112] in March 2023. We obtained MSAs for TEM-1, GRB2, and DLG4 in July 2023. We queried the UniRef100 database with search parameters consistent with those in EVMutation [113]: a position sequence filter of 70 percent, a sequence fragment filter of 50 percent, 100 percent removal of similar sequences, and 80 percent down weighting of similar sequences. We started our bitscore value at 0.5 bits per residue. If we did not have 80 percent sequence coverage, we increased the threshold by 0.05 bits per residue until the constraint was satisfied. If the number of effective sequences in the alignment was less than 10 times the length of the protein, we decreased the bits per residue until the requirement was satisfied. We prioritized the number of effective sequences objective if the two were in conflict. We trained EVE using the default training parameters of 40,000 training iterations, sampling 20,000 evolutionary indices, and a default theta reweighting value of 0.2 to preprocess the MSA. We made mutation effect predictions for every position in the sequence by capitalizing all amino acids in the MSA.

In addition to using EVE as a standalone zero-shot method, we incorporated the EVE score into a supervised learning model. We selected EVE for augmented regression instead of the models evaluated by Hsu et al. [15] because EVE outperforms them in ProteinGym's zero-shot substitution deep mutational scanning evaluation [43], therefore providing a stronger baseline. The augmented regression model Linear-EVE is identical to the Linear model described above, but it uses the EVE score as an additional input feature in combination with the one hot encoded protein sequence. We standardized the EVE score for use as an input feature by first calculating its mean and standard deviation in the train set. Then, we subtracted the mean and divided by the standard deviation.

GFP sequence design

We finetuned a pretrained METL-Local model on 64 randomly sampled variants from the GFP dataset. The selected variants had 1 to 11 mutations, and their experimental score distribution was bimodal (Fig. S14), similar to the distribution of the full GFP dataset. We refer to the finetuned METL-Local GFP model in this low-N setting as METL-L-GFP. We inspected the extrapolation behaviors of the METL-L-GFP model for increasing number of mutations. For increasing numbers of mutations selected with simulated annealing, the predicted brightness approximately stabilized at a positive value (Fig. S19), in contrast to what has been observed in convolutional neural networks [114]. Conversely, for increasing numbers of randomly selected mutations, the predicted brightness stabilized at a negative value (Fig. S20). That the predicted scores did not continue to increase positively or negatively with the number of mutations was a basic verification of the METL-L-GFP model's extrapolation properties.

We performed in silico optimization with METL-L-GFP to design a total of 20 variants distributed evenly across 4 different design criteria. These criteria are the product of 2 primary design categories: the number of mutations (either 5 or 10) and the constraints on mutation selection (either Observed or Unobserved). In the Observed constraint, the designed sequences contain only amino acid substitutions found in the 64-variant training set. Conversely, in the Unobserved constraint, the designed sequences exclude any amino acid substitutions found in the 64-variant training set. The combinations of these categories resulted in the 4 design criteria: Observed 5-mutant, Unobserved 5-mutant, Observed 10-mutant, and Unobserved 10-mutant. We designed 5 sequences for each criterion, resulting in a total of 20 designed sequences.

To perform the in silico optimization, we ran simulated annealing 10,000 times for each design criterion. For each simulated annealing run, we changed the random seed and executed the Monte Carlo optimization for 10,000 steps. Each step consisted of suggesting a mutation for the currently sampled variant and deciding whether to accept the new variant according to the Metropolis-Hastings criteria. We decreased the optimization temperature according to a logarithmic gradient beginning at 10^1 and ending at 10^{-2}. The initial temperature was chosen by randomly sampling 10,000 variants, predicting their brightness with METL-L-GFP, and calculating the absolute value of the difference between the lowest and highest predicted brightness, rounded to the nearest power of 10. The final temperature was determined by calculating the absolute value of the smallest difference in predicted brightness between any two variants in the 64 variant training set, rounded to the nearest power to 10. The initial temperature encouraged acceptance of all variants, while the final temperature meant that only variants better than the current ones would be accepted.

The simulation began by randomly selecting a variant with the necessary number of mutations depending on the design criterion. We determined how many mutations to change at each step by sampling from a Poisson distribution. To generate a new variant from an existing one, we first determined the difference between the number of mutations to change and the maximum allowable mutations, which indicated the number of current mutations to keep, m. We randomly sampled which m mutations to keep, and reset the other mutations to wild type. Subsequently, we compiled all feasible single mutations of the

sequence with the *m* existing mutations and randomly sampled new mutations without replacement until the variant mutation count reached the maximum allowable mutations.

The optimization process described above yielded 10,000 designs for each criterion, which we downsampled to 5 designs for each criterion via clustering. Our downsampling approach prioritized diversity and was predicated on the idea that repeated convergence to similar sequences may correlate with higher true fitness values, as these regions of the fitness landscape would have broader peaks and allow more room for error in the model predictions or optimization process. We clustered the 10,000 designs using scikit-learn's agglomerative clustering with complete linkage and a BLOSUM62-based distance metric. Because selecting 10, 20, or 50 clusters did not substantially impact the diversity of the selected mutations, we chose 20 clusters. We then removed clusters that contained less than 100 sequences, which represented 1% of the simulated annealing solutions.

To select 5 (or 10) clusters from those remaining, we employed an iterative, greedy approach. We identified a representative sequence for each cluster, choosing the one with the lowest average BLOSUM62-based distance to all other sequences within the same cluster. To initialize, we selected the largest cluster. We then proceeded iteratively, selecting additional clusters one at a time. In each iteration, we calculated the distances between the representative sequences of the already selected clusters and the remaining unselected clusters. We selected the cluster with the largest mean distance to the already selected clusters to promote sequence diversity. The GFP sequence designs were the representative sequences from the selected clusters.

Cloning and experimental validation of GFP variants

We modeled our expression system on that used in Sarkysian et al. [33], which uses a pQE-30 vector (Qiagen) to express GFP as a fusion protein with mKate2. To generate the expression construct, we used the vector backbone from a related pQE-30 system that expresses KillerOrange (Addgene 74748) and ordered the mKate2-GFP fusion protein as a gene fragment from Twist Biosciences. We first removed a BsaI restriction site in the AmpR gene from the backbone using site directed mutagenesis (NEB M0554S) and then used Golden Gate cloning to replace KillerOrange with the fusion protein. We incubated (1 hr, 37 C) the backbone and insert with BsaI (15 U, NEB: R3733), T4 Ligase (1,000 U, NEB M0202), and T4 Ligase Buffer (NEB B0202) to assemble the vector. The assembly was cleaned up with a PCR Clean and Concentrate column (Zymogen D4003) and transformed into in-house DH5a cells. Plasmid stock was purified from an overnight culture starting from a single colony using a Qiagen Miniprep kit (Qiagen 27104), and the vector was on-boarded with Twist Biosciences. All GFP variants were ordered as clonal genes from Twist Biosciences wherein the wild-type GFP sequence was replaced with the variant sequence. For each variant, the nucleotide sequence was kept the same as the wild-type sequence except at mutated residues. We selected new codons for mutated residues based on an *E. coli* codon usage index [115] to mitigate poor expression due to rare codons.

Clonal genes ordered from Twist Biosciences were transformed into NEBExpress Iq Competent *E. coli* (NEB C3037I) cells and plated on Luria Broth (LB) plates with carbenecillin selection (0.1 mg/mL). Proteins were expressed as previously described in Sarkysian et al. [33]. Briefly, freshly plated transformants were incubated overnight at 37 °C and then moved to 4 °C the following day. After 24 hours, plates were washed with 4 mL LB and normalized to 1 OD. This wash was used to create triplicate expression cultures where protein expression was induced for 2 hours with 1 mM IPTG at 23 °C. An empty pQE-30 vector was used as a negative expression control.

To prepare cultures for fluorescence measurement, expression cultures were pelleted (3,000xg, 5 mins) and re-suspended in sterile 1X PBS to a concentration of 1 OD. Cells were diluted 2-fold into 96-well plates to measure fluorescence and culture density with the Tecan Spark 10M. Measurements for GFP (ex. 405 nm, em. 510 nm), mKate2 (ex. 561 nm, em. 670 nm), and OD600 (abs. 600 nm) were collected.

Relative brightness was reported as the ratio of GFP fluorescence to mKate2 fluorescence averaged across replicates. First, raw fluorescent measurements were normalized to cell density by dividing by the sample's OD600 value. The background fluorescence signal was subtracted out of each sample. The background fluorescence signals for GFP and mKate2 were measured from negative control cells containing no fluorescent protein. A sample's relative brightness was calculated for each sample by dividing the normalized background-subtracted GFP fluorescence by the normalized background-subtracted mKate2 fluorescence.

Visualizations

We used FreeSASA [116] to compute GB1 (PDB: 2QMT) relative solvent accessibility (RSA), which was used to color the points in Figure 5d. We used Multidimensional Scaling (MDS) from scikit-learn to visualize GFP designs in Figure 7b. MDS is a dimensionality reduction technique that preserves relative distances between observations [117]. We used Hamming distance between sequences, which had the effect of making variants show up in concentric circles around the wild-type sequence based on the number of mutations from wild-type.

Software and data availability

We provide a collection of METL software repositories to reproduce the results of this manuscript and run METL on new data:

Acknowledgements

This research was supported by National Science Foundation awards 2226383 and 2226451, National Institutes of Health awards R01GM135631 and R35GM119854, the John W. and Jeanne M. Rowe Center for Research in Virology at the Morgridge Institute for Research, and the University of Wisconsin–Madison Office of the Vice Chancellor for Research and Graduate Education with funding from the Wisconsin Alumni Research Foundation. We thank Ben Gelman for insightful discussions regarding the transformer architecture, attention mechanism, and effects of data normalization; Jerry Duan for the initial molecular simulations implementation; Brian Aydemir for testing and feedback on the molecular simulation workflow; and Kaustubh Amritkar for collecting and processing PDB files for METL-Global. The research was performed using the computing resources and assistance of the University of Wisconsin-Madison Center for High Throughput Computing [118] and services provided by the OSG Consortium [98, 119, 120], which is supported by National Science Foundation awards 2030508 and 1836650.

References

1. Chandra, A., Tünnermann, L., Löfstedt, T. & Gratz, R. Transformer-based deep learning for predicting protein properties in the life sciences. *eLife* **12**, e82819. doi:10.7554/eLife.82819 (2023).
2. Bepler, T. & Berger, B. Learning the protein language: Evolution, structure, and function. *Cell Syst.* **12**, 654–669.e3. doi:10.1016/j.cels.2021.05.017 (2021).
3. Biswas, S., Khimulya, G., Alley, E. C., Esvelt, K. M. & Church, G. M. Low-N protein engineering with data-efficient deep learning. *Nat. Methods* **18**, 389–396. doi:10.1038/s41592-021-01100-y (2021).
4. Yang, K. K., Wu, Z., Bedbrook, C. N. & Arnold, F. H. Learned protein embeddings for machine learning. *Bioinformatics* **34**, 2642–2648. doi:10.1093/bioinformatics/bty178 (2018).
5. Munsamy, G., Lindner, S., Lorenz, P. & Ferruz, N. ZymCTRL: a conditional language model for the controllable generation of artificial enzymes. *Mach. Learn. Struct. Biol. Work. at 36th Conf. on Neural Inf. Process. Syst.* (2022).
6. Madani, A. *et al.* Large language models generate functional protein sequences across diverse families. *Nat. Biotechnol.* 1–8. doi:10.1038/s41587-022-01618-2 (2023).
7. Alley, E. C., Khimulya, G., Biswas, S., AlQuraishi, M. & Church, G. M. Unified rational protein engineering with sequence-based deep representation learning. *Nat. Methods* **16**, 1315–1322. doi:10.1038/s41592-019-0598-1 (2019).
8. Rives, A. *et al.* Biological structure and function emerge from scaling unsupervised learning to 250 million protein sequences. *Proc. Natl. Acad. Sci.* **118**, e2016239118. doi:10.1073/pnas.2016239118 (2021).
9. Bornscheuer, U. T. *et al.* Engineering the third wave of biocatalysis. *Nature* **485**, 185–194. doi:10.1038/nature11117 (2012).
10. Alford, R. F. *et al.* The Rosetta All-Atom Energy Function for Macromolecular Modeling and Design. *J. Chem. Theory Comput.* **13**, 3031–3048. doi:10.1021/acs.jctc.7b00125 (2017).
11. Vaswani, A. *et al.* Attention Is All You Need. *arXiv:1706.03762 [cs]* doi:10.48550/arXiv.1706.03762 (2017).
12. Shaw, P., Uszkoreit, J. & Vaswani, A. Self-Attention with Relative Position Representations. In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 2 (Short Papers)*, 464–468. doi:10.18653/v1/N18-2074 (Association for Computational Linguistics, New Orleans, Louisiana, 2018).
13. Kosciolek, T. & Jones, D. T. De Novo Structure Prediction of Globular Proteins Aided by Sequence Variation-Derived Contacts. *PLOS ONE* **9**, e92197. doi:10.1371/journal.pone.0092197 (2014).

14. Frazer, J. *et al.* Disease variant prediction with deep generative models of evolutionary data. *Nature* **599**, 91–95. doi:10.1038/s41586-021-04043-8 (2021).

15. Hsu, C., Nisonoff, H., Fannjiang, C. & Listgarten, J. Learning protein fitness models from evolutionary and assay-labeled data. *Nat. Biotechnol.* **40**, 1114–1122. doi:10.1038/s41587-021-01146-5 (2022).

16. Lin, Z. *et al.* Evolutionary-scale prediction of atomic-level protein structure with a language model. *Science* **379**, 1123–1130. doi:10.1126/science.ade2574 (2023).

17. Gelman, S., Fahlberg, S. A., Heinzelman, P., Romero, P. A. & Gitter, A. Neural networks to learn protein sequence–function relationships from deep mutational scanning data. *Proc. Natl. Acad. Sci.* **118**, e2104878118. doi:10.1073/pnas.2104878118 (2021).

18. Chen, L. *et al.* Learning protein fitness landscapes with deep mutational scanning data from multiple sources. *Cell Syst.* **14**, 706–721.e5. doi:10.1016/j.cels.2023.07.003 (2023).

19. Michael, R. *et al.* Assessing the performance of protein regression models. *bioRxiv* 2023.06.18.545472. doi:10.1101/2023.06.18.545472 (2023).

20. Mater, A. C., Sandhu, M. & Jackson, C. The NK Landscape as a Versatile Benchmark for Machine Learning Driven Protein Engineering. *bioRxiv* 2020.09.30.319780. doi:10.1101/2020.09.30.319780 (2020).

21. Luo, Y. *et al.* ECNet is an evolutionary context-integrated deep learning framework for protein engineering. *Nat. Commun.* **12**, 5743. doi:10.1038/s41467-021-25976-8 (2021).

22. Dallago, C. *et al.* FLIP: Benchmark tasks in fitness landscape inference for proteins. *bioRxiv* 2021.11.09.467890. doi:10.1101/2021.11.09.467890 (2022).

23. Villà, J. & Warshel, A. Energetics and Dynamics of Enzymatic Reactions. *The J. Phys. Chem. B* **105**, 7887–7907. doi:10.1021/jp011048h (2001).

24. Borrelli, K. W., Vitalis, A., Alcantara, R. & Guallar, V. PELE: Protein Energy Landscape Exploration. A Novel Monte Carlo Based Technique. *J. Chem. Theory Comput.* **1**, 1304–1311. doi:10.1021/ct0501811 (2005).

25. Cross, J. B. *et al.* Comparison of Several Molecular Docking Programs: Pose Prediction and Virtual Screening Accuracy. *J. Chem. Inf. Model.* **49**, 1455–1474. doi:10.1021/ci900056c (2009).

26. Trott, O. & Olson, A. J. AutoDock Vina: Improving the speed and accuracy of docking with a new scoring function, efficient optimization, and multithreading. *J. Comput. Chem.* **31**, 455–461. doi:10.1002/jcc.21334 (2010).

27. Eastman, P. *et al.* OpenMM 8: Molecular Dynamics Simulation with Machine Learning Potentials. *The J. Phys. Chem. B* **128**, 109–116. doi:10.1021/acs.jpcb.3c06662 (2024).

28. Wang, Z., Dai, Z., Póczos, B. & Carbonell, J. Characterizing and Avoiding Negative Transfer. In *2019 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 11285–11294. doi:10.1109/CVPR.2019.01155 (2019).

29. Olson, C. A., Wu, N. C. & Sun, R. A Comprehensive Biophysical Description of Pairwise Epistasis throughout an Entire Protein Domain. *Curr. Biol.* **24**, 2643–2651. doi:10.1016/j.cub.2014.09.072 (2014).

30. Sloan, D. J. & Hellinga, H. W. Dissection of the protein G B1 domain binding site for human IgG Fc fragment. *Protein Sci.* **8**, 1643–1648. doi:10.1110/ps.8.8.1643 (1999).

31. Bedbrook, C. N., Yang, K. K., Rice, A. J., Gradinaru, V. & Arnold, F. H. Machine learning to design integral membrane channelrhodopsins for efficient eukaryotic expression and plasma membrane localization. *PLOS Comput. Biol.* **13**, e1005786. doi:10.1371/journal.pcbi.1005786 (2017).

32. Johansson, K. E., Lindorff-Larsen, K. & Winther, J. R. Global Analysis of Multi-Mutants to Improve Protein Function. *J. Mol. Biol.* **435**, 168034. doi:10.1016/j.jmb.2023.168034 (2023).

33. Sarkisyan, K. S. *et al.* Local fitness landscape of the green fluorescent protein. *Nature* **533**, 397–401. doi:10.1038/nature17995 (2016).

34. Cranfill, P. J. *et al.* Quantitative assessment of fluorescent proteins. *Nat. Methods* **13**, 557–562. doi:10.1038/nmeth.3891 (2016).

35. Hollingsworth, S. A. & Dror, R. O. Molecular Dynamics Simulation for All. *Neuron* **99**, 1129–1143. doi:10.1016/j.neuron.2018.08.011 (2018).

36. Elnaggar, A. *et al.* ProtTrans: Toward Understanding the Language of Life Through Self-Supervised Learning. *IEEE Transactions on Pattern Analysis Mach. Intell.* **44**, 7112–7127. doi:10.1109/TPAMI.2021.3095381 (2022).

37. Yang, K. K., Fusi, N. & Lu, A. X. Convolutions are competitive with transformers for protein sequence pretraining. *Cell Syst.* doi:10.1016/j.cels.2024.01.008 (2024).

38. Ding, F. & Steinhardt, J. N. Protein language models are biased by unequal sequence sampling across the tree of life.

bioRxiv 2024.03.07.584001. doi:10.1101/2024.03.07.584001 (2024).

39. Renfrew, P. D., Choi, E. J., Bonneau, R. & Kuhlman, B. Incorporation of Noncanonical Amino Acids into Rosetta and Use in Computational Protein-Peptide Interface Design. *PLOS ONE* **7**, e32637. doi:10.1371/journal.pone.0032637 (2012).

40. Li, Y. & Dalby, P. A. Engineering of enzymes using non-natural amino acids. *Biosci. Reports* **42**, BSR20220168. doi:10.1042/BSR20220168 (2022).

41. Høie, M. H., Cagiada, M., Frederiksen, A. H. B., Stein, A. & Lindorff-Larsen, K. Predicting and interpreting large-scale mutagenesis data using analyses of protein stability and conservation. *Cell Reports* **38**. doi:10.1016/j.celrep.2021.110207 (2022).

42. Gerasimavicius, L., Livesey, B. J. & Marsh, J. A. Correspondence between functional scores from deep mutational scans and predicted effects on protein stability. *Protein Sci.* **32**, e4688. doi:10.1002/pro.4688 (2023).

43. Notin, P. *et al.* ProteinGym: Large-Scale Benchmarks for Protein Fitness Prediction and Design. *Adv. Neural Inf. Process. Syst.* **36**, 64331–64379 (2023).

44. Clark, T. *et al.* Machine Learning-Guided Antibody Engineering That Leverages Domain Knowledge To Overcome The Small Data Problem. *bioRxiv* 2023.06.02.543458. doi:10.1101/2023.06.02.543458 (2023).

45. Yutzy, L. *et al.* Augmentation of Structure Information to the Sequence-Based Machine Learning-Assisted Directed Protein Evolution. *ChemRxiv* doi:10.26434/chemrxiv-2023-llpnk (2023).

46. Harmalkar, A. *et al.* Toward generalizable prediction of antibody thermostability using machine learning on sequence and structure features. *mAbs* **15**, 2163584. doi:10.1080/19420862.2022.2163584 (2023).

47. Wang, A., Amini, A. P., Lu, A. X. & Yang, K. K. Learning from physics-based features improves protein property prediction. In *Machine Learning for Structural Biology Workshop at the 36th Conference on Neural Information Processing Systems* (2022).

48. Nisonoff, H., Wang, Y. & Listgarten, J. Coherent Blending of Biophysics-Based Knowledge with Bayesian Neural Networks for Robust Protein Property Prediction. *ACS Synth. Biol.* **12**, 3242–3251. doi:10.1021/acssynbio.3c00217 (2023).

49. Nordquist, E. *et al.* Incorporating physics to overcome data scarcity in predictive modeling of protein function: A case study of BK channels. *PLOS Comput. Biol.* **19**, e1011460. doi:10.1371/journal.pcbi.1011460 (2023).

50. Wittmann, B. J., Yue, Y. & Arnold, F. H. Informed training set design enables efficient machine learning-assisted directed protein evolution. *Cell Syst.* **12**, 1026–1045.e7. doi:10.1016/j.cels.2021.07.008 (2021).

51. Lipsh-Sokolik, R. *et al.* Combinatorial assembly and design of enzymes. *Science* **379**, 195–201. doi:10.1126/science.ade9434 (2023).

52. Weinstein, J. Y. *et al.* Designed active-site library reveals thousands of functional GFP variants. *Nat. Commun.* **14**, 2890. doi:10.1038/s41467-023-38099-z (2023).

53. Omar, S. I., Keasar, C., Ben-Sasson, A. J. & Haber, E. Protein Design Using Physics Informed Neural Networks. *Biomolecules* **13**, 457. doi:10.3390/biom13030457 (2023).

54. Ramírez-Palacios, C. & Marrink, S. J. Super High-Throughput Screening of Enzyme Variants by Spectral Graph Convolutional Neural Networks. *J. Chem. Theory Comput.* **19**, 4668–4677. doi:10.1021/acs.jctc.2c01227 (2023).

55. Ni, B., Kaplan, D. L. & Buehler, M. J. ForceGen: End-to-end de novo protein generation based on nonlinear mechanical unfolding responses using a language diffusion model. *Sci. Adv.* **10**, eadl4000. doi:10.1126/sciadv.adl4000 (2024).

56. Capriotti, E., Fariselli, P. & Casadio, R. I-Mutant2.0: predicting stability changes upon mutation from the protein sequence or structure. *Nucleic Acids Res.* **33**, W306–W310. doi:10.1093/nar/gki375 (2005).

57. Folkman, L., Stantic, B., Sattar, A. & Zhou, Y. EASE-MM: Sequence-Based Prediction of Mutation-Induced Stability Changes with Feature-Based Multiple Models. *J. Mol. Biol.* **428**, 1394–1405. doi:10.1016/j.jmb.2016.01.012 (2016).

58. Cao, H., Wang, J., He, L., Qi, Y. & Zhang, J. Z. DeepDDG: Predicting the Stability Change of Protein Point Mutations Using Neural Networks. *J. Chem. Inf. Model.* **59**, 1508–1514. doi:10.1021/acs.jcim.8b00697 (2019).

59. Chen, Y. *et al.* PremPS: Predicting the impact of missense mutations on protein stability. *PLOS Comput. Biol.* **16**, e1008543. doi:10.1371/journal.pcbi.1008543 (2020).

60. Li, B., Yang, Y. T., Capra, J. A. & Gerstein, M. B. Predicting changes in protein thermodynamic stability upon point mutation with deep 3D convolutional neural networks. *PLOS Comput. Biol.* **16**, e1008291. doi:10.1371/journal.pcbi.1008291 (2020).

61. Wang, S., Tang, H., Zhao, Y. & Zuo, L. BayeStab: Predicting effects of mutations on protein stability with uncertainty quantification. *Protein Sci.* **31**, e4467. doi:10.1002/pro.4467 (2022).

62. Blaabjerg, L. M. *et al.* Rapid protein stability prediction using deep learning representations. *eLife* **12**, e82593. doi:10.7554/eLife.82593 (2023).

63. Hummer, A. M., Schneider, C., Chinery, L. & Deane, C. M. Investigating the Volume and Diversity of Data Needed for Generalizable Antibody-Antigen ΔΔG Prediction. *bioRxiv* 2023.05.17.541222. doi:10.1101/2023.05.17.541222 (2023).

64. Zhou, Y., Pan, Q., Pires, D. E. V., Rodrigues, C. H. M. & Ascher, D. B. DDMut: predicting effects of mutations on protein stability using deep learning. *Nucleic Acids Res.* **51**, W122–W128. doi:10.1093/nar/gkad472 (2023).

65. Dieckhaus, H., Brocidiacono, M., Randolph, N. Z. & Kuhlman, B. Transfer learning to leverage larger datasets for improved prediction of protein stability changes. *Proc. Natl. Acad. Sci.* **121**, e2314853121. doi:10.1073/pnas.2314853121 (2024).

66. Boyer, S., Money-Kyrle, S. & Bent, O. Predicting protein stability changes under multiple amino acid substitutions using equivariant graph neural networks. *arXiv:2305.19801 [q-bio.BM]* doi:10.48550/arXiv.2305.19801 (2023).

67. Sun, J., Zhu, T., Cui, Y. & Wu, B. Structure-based self-supervised learning enables ultrafast prediction of stability changes upon mutation at the protein universe scale. *bioRxiv* 2023.08.09.552725. doi:10.1101/2023.08.09.552725 (2023).

68. Liao, J. *et al.* Engineering proteinase K using machine learning and synthetic genes. *BMC Biotechnol.* **7**, 16. doi:10.1186/1472-6750-7-16 (2007).

69. Saito, Y. *et al.* Machine-Learning-Guided Mutagenesis for Directed Evolution of Fluorescent Proteins. *ACS Synth. Biol.* **7**, 2014–2022. doi:10.1021/acssynbio.8b00155 (2018).

70. Wu, Z., Kan, S. B. J., Lewis, R. D., Wittmann, B. J. & Arnold, F. H. Machine learning-assisted directed protein evolution with combinatorial libraries. *Proc. Natl. Acad. Sci.* **116**, 8852–8858. doi:10.1073/pnas.1901979116 (2019).

71. Saito, Y. *et al.* Machine-Learning-Guided Library Design Cycle for Directed Evolution of Enzymes: The Effects of Training Data Composition on Sequence Space Exploration. *ACS Catal.* **11**, 14615–14624. doi:10.1021/acscatal.1c03753 (2021).

72. Greenhalgh, J. C., Fahlberg, S. A., Pfleger, B. F. & Romero, P. A. Machine learning-guided acyl-ACP reductase engineering for improved in vivo fatty alcohol production. *Nat. Commun.* **12**, 5825. doi:10.1038/s41467-021-25831-w (2021).

73. Wait, S. J., Rappleye, M., Lee, J. D., Smith, N. & Berndt, A. Machine Learning Ensemble Directed Engineering of Genetically Encoded Fluorescent Calcium Indicators. *bioRxiv* doi:10.1101/2023.04.13.536801 (2023).

74. Yamaguchi, H. & Saito, Y. Evotuning protocols for Transformer-based variant effect prediction on multi-domain proteins. *Briefings Bioinforma.* **22**, bbab234. doi:10.1093/bib/bbab234 (2021).

75. Hoffbauer, T. & Strodel, B. TransMEP: Transfer learning on large protein language models to predict mutation effects of proteins from a small known dataset. *bioRxiv* 2024.01.12.575432. doi:10.1101/2024.01.12.575432 (2024).

76. Shanehsazzadeh, A., Belanger, D. & Dohan, D. Is Transfer Learning Necessary for Protein Landscape Prediction? *arXiv:2011.03443 [q-bio.BM]* doi:10.48550/arXiv.2011.03443 (2020).

77. Barbero-Aparicio, J. A., Olivares-Gil, A., Rodríguez, J. J., García-Osorio, C. & Díez-Pastor, J. F. Addressing data scarcity in protein fitness landscape analysis: A study on semi-supervised and deep transfer learning techniques. *Inf. Fusion* **102**, 102035. doi:10.1016/j.inffus.2023.102035 (2024).

78. Zhou, Z. *et al.* Enhancing the efficiency of protein language models with minimal wet-lab data through few-shot learning. *arXiv:2402.02004 [q-bio.BM]* doi:10.48550/arXiv.2402.02004 (2024).

79. Li, M. *et al.* SESNet: Sequence-structure feature-integrated deep learning method for data-efficient protein engineering. *J. Cheminformatics* **15**, 12. doi:10.1186/s13321-023-00688-x (2023).

80. Notin, P., Weitzman, R., Marks, D. S. & Gal, Y. ProteinNPT: Improving Protein Property Prediction and Design with Non-Parametric Transformers. *bioRxiv* 2023.12.06.570473. doi:10.1101/2023.12.06.570473 (2023).

81. Romero, P. A., Krause, A. & Arnold, F. H. Navigating the protein fitness landscape with Gaussian processes. *Proc. Natl. Acad. Sci.* **110**, E193–E201. doi:10.1073/pnas.1215251110 (2013).

82. Vornholt, T. *et al.* Enhanced Sequence-Activity Mapping and Evolution of Artificial Metalloenzymes by Active Learning. *bioRxiv* doi:10.1101/2024.02.06.579157 (2024).

83. Illig, A.-M., Siedhoff, N. E., Schwaneberg, U. & Davari, M. D. A hybrid model combining evolutionary probability and machine learning leverages data-driven protein engineering. *bioRxiv* doi:10.1101/2022.06.07.495081 (2022).

84. Boca, A. & Mathis, S. Predicting protein variants with equivariant graph neural networks. *arXiv:2306.12231 [cs.LG]* doi:10.48550/arXiv.2306.12231 (2023).

85. Wirnsberger, G., Pritišanac, I., Oberdorfer, G. & Gruber, K. Flattening the curve - How to get better results with small

deep-mutational-scanning datasets. *bioRxiv* 2023.03.27.534314. doi:10.1101/2023.03.27.534314 (2023).

86. Qiu, Y. & Wei, G.-W. Persistent spectral theory-guided protein engineering. *Nat. Comput. Sci.* **3**, 149–163. doi:10.1038/s43588-022-00394-y (2023).

87. Minot, M. & Reddy, S. T. Meta learning addresses noisy and under-labeled data in machine learning-guided antibody engineering. *Cell Syst.* **15**, 4–18.e4. doi:10.1016/j.cels.2023.12.003 (2024).

88. Zhao, J., Zhang, C. & Luo, Y. Contrastive Fitness Learning: Reprogramming Protein Language Models for Low-N Learning of Protein Fitness Landscape. *bioRxiv* 2024.02.11.579859. doi:10.1101/2024.02.11.579859 (2024).

89. Cranmer, K., Brehmer, J. & Louppe, G. The frontier of simulation-based inference. *Proc. Natl. Acad. Sci.* **117**, 30055–30062. doi:10.1073/pnas.1912789117 (2020).

90. Wu, Z. & Sinha, S. SPREd: a simulation-supervised neural network tool for gene regulatory network reconstruction. *Bioinforma. Adv.* **4**, vbae011. doi:10.1093/bioadv/vbae011 (2024).

91. Ahmad, W., Simon, E., Chithrananda, S., Grand, G. & Ramsundar, B. ChemBERTa-2: Towards Chemical Foundation Models. *arXiv:2209.01712* doi:10.48550/arXiv.2209.01712 (2022).

92. Yu, S. *et al.* ClimSim: A large multi-scale dataset for hybrid physics-ML climate emulation. *arXiv:2306.08754* doi:10.48550/arXiv.2306.08754 (2023).

93. Eastman, P. *et al.* SPICE, A Dataset of Drug-like Molecules and Peptides for Training Machine Learning Potentials. *Sci. Data* **10**, 11. doi:10.1038/s41597-022-01882-6 (2023).

94. Berman, H. M. *et al.* The Protein Data Bank. *Nucleic Acids Res.* **28**, 235–242. doi:10.1093/nar/28.1.235 (2000).

95. Varadi, M. *et al.* AlphaFold Protein Structure Database: Massively expanding the structural coverage of protein-sequence space with high-accuracy models. *Nucleic Acids Res.* **50**, D439–D444. doi:10.1093/nar/gkab1061 (2022).

96. Rocklin, G. J. *et al.* Global analysis of protein folding using massively parallel design, synthesis, and testing. *Science* **357**, 168–175. doi:10.1126/science.aan0693 (2017).

97. Thain, D., Tannenbaum, T. & Livny, M. Distributed computing in practice: the Condor experience. *Concurr. Comput. Pract. Exp.* **17**, 323–356. doi:10.1002/cpe.938 (2005).

98. Pordes, R. *et al.* The Open Science Grid. *J. Physics: Conf. Ser.* **78**, 012057. doi:10.1088/1742-6596/78/1/012057 (2007).

99. Xiong, R. *et al.* On Layer Normalization in the Transformer Architecture. *arXiv:2002.04745 [cs]* doi:10.48550/arXiv.2002.04745 (2020).

100. Loshchilov, I. & Hutter, F. Decoupled Weight Decay Regularization. In *7th International Conference on Learning Representations* (2019).

101. Paszke, A. *et al.* PyTorch: An Imperative Style, High-Performance Deep Learning Library. In *Advances in Neural Information Processing Systems*, vol. 32, 8024–8035 (Curran Associates, Inc., 2019).

102. Falcon, W. & The PyTorch Lightning team. PyTorch Lightning. *GitHub* doi:10.5281/zenodo.3828935 (2022).

103. Nedrud, D., Coyote-Maestas, W. & Schmidt, D. A large-scale survey of pairwise epistasis reveals a mechanism for evolutionary expansion and specialization of PDZ domains. *Proteins: Struct. Funct. Bioinforma.* **89**, 899–914. doi:10.1002/prot.26067 (2021).

104. Faure, A. J. *et al.* Mapping the energetic and allosteric landscapes of protein binding domains. *Nature* **604**, 175–183. doi:10.1038/s41586-022-04586-4 (2022).

105. Melamed, D., Young, D. L., Gamble, C. E., Miller, C. R. & Fields, S. Deep mutational scanning of an RRM domain of the Saccharomyces cerevisiae poly(A)-binding protein. *RNA* **19**, 1537–1551. doi:10.1261/rna.040709.113 (2013).

106. Gonzalez, C. E. & Ostermeier, M. Pervasive Pairwise Intragenic Epistasis among Sequential Mutations in TEM-1 β-Lactamase. *J. Mol. Biol.* **431**, 1981–1992. doi:10.1016/j.jmb.2019.03.020 (2019).

107. Starita, L. M. *et al.* Activity-enhancing mutations in an E3 ubiquitin ligase identified by high-throughput mutagenesis. *Proc. Natl. Acad. Sci.* **110**, E1263–E1272. doi:10.1073/pnas.1303309110 (2013).

108. Esposito, D. *et al.* MaveDB: An open-source platform to distribute and interpret data from multiplexed assays of variant effect. *Genome Biol.* **20**, 223. doi:10.1186/s13059-019-1845-6 (2019).

109. Barrett, T. *et al.* NCBI GEO: Archive for functional genomics data sets—update. *Nucleic Acids Res.* **41**, D991–D995. doi:10.1093/nar/gks1193 (2013).

110. Pedregosa, F. *et al.* Scikit-learn: Machine Learning in Python. *J. Mach. Learn. Res.* **12**, 2825–2830 (2011).

111. Kumar, A., Raghunathan, A., Jones, R. M., Ma, T. & Liang, P. Fine-Tuning can Distort Pretrained Features and Underperform Out-of-Distribution. In *10th International Conference on Learning Representations* (2022).

112. Hopf, T. A. *et al.* The EVcouplings Python framework for coevolutionary sequence analysis. *Bioinformatics* **35**,

1582–1584. doi:10.1093/bioinformatics/bty862 (2019).

113. Hopf, T. A. *et al.* Mutation effects predicted from sequence co-variation. *Nat. Biotechnol.* **35**, 128–135. doi:10.1038/nbt.3769 (2017).

114. Fahlberg, S. A., Freschlin, C. R., Heinzelman, P. & Romero, P. A. Neural network extrapolation to distant regions of the protein fitness landscape. *bioRxiv* 2023.11.08.566287. doi:10.1101/2023.11.08.566287 (2023).

115. Boël, G. *et al.* Codon influence on protein expression in E. coli correlates with mRNA levels. *Nat. 2016 529:7586* **529**, 358–363. doi:10.1038/nature16509 (2016).

116. Mitternacht, S. FreeSASA: An open source C library for solvent accessible surface area calculations. doi:10.12688/f1000research.7931.1 (2016).

117. Borg, I. & Patrick J. F. Groenen. *Modern Multidimensional Scaling*. Springer Series in Statistics (Springer New York, NY, 2005).

118. Center for High Throughput Computing. Center for High Throughput Computing. doi:10.21231/GNT1-HW21 (2006).

119. Sfiligoi, I. *et al.* The Pilot Way to Grid Resources Using glideinWMS. In *2009 WRI World Congress on Computer Science and Information Engineering*, vol. 2, 428–432. doi:10.1109/CSIE.2009.950 (2009).

120. OSG. Open Science Pool. doi:10.21231/906P-4D78 (2006).

Supplementary Information: Biophysics-based protein language models for protein engineering

Sam Gelman, Bryce Johnson, Chase Freschlin, Sameer D'Costa, Anthony Gitter, Philip A. Romero

Figure S1. Performance of pretrained METL source models in predicting Rosetta scores. This figure shows Spearman correlations between true and predicted Rosetta scores for each of the 55 Rosetta score terms. (a) Correlation of METL-Local models predicting Rosetta biophysical attributes for the protein-specific pretraining data test sets. (b) Correlation of METL-Global in predicting Rosetta scores for protein variants originating from in-distribution base PDBs (those included in METL-Global pretraining) and out-of-distribution base PDBs (those not included). We show the mean Spearman correlation across base PDBs. To evaluate in-distribution PDBs, we used variants in the pretraining data test set. To evaluate out-of-distribution PDBs, we used variants from the eight deep mutational scanning datasets included in this study. METL-Global performs substantially better for in-distribution PDBs, suggesting there is overfitting to the PDBs present in the training data.

Figure S2. **METL-Global amino acid embeddings** We applied principal component analysis (PCA) to reduce the METL-Global length 512 amino acid embeddings down to 2 dimensions, capturing 33% of the variance in data. This scatter plot of the 2-dimensional amino acid embeddings is annotated with amino acid properties. METL-Global groups amino acids with similar biochemical properties in the embedding space, like protein language models (PLMs) trained on millions of natural protein sequences [1].

Figure S3. Relationship between METL-Local performance and the relatedness of Rosetta and experimental scores.
The figure displays a series of scatterplots showing the relationship between METL-Local performance and the relatedness of Rosetta and experimental scores, across multiple experimental datasets and training set sizes. The x-axis shows the Spearman correlation between Rosetta total score and the experimental functional score for the entire dataset, representing the similarity between the Rosetta total score and the experimental functional score. The y-axis shows the METL-Local performance for the respective training set size, as determined by the Spearman correlation on the test set. As the similarity between Rosetta total score and the experimental functional score increases, so does the METL-Local performance, at least for small training set sizes. However, with increasing experimental training set sizes, the similarity between Rosetta total score and experimental functional score becomes less important to the METL-Local performance, suggesting a shift in METL-Local away from the Rosetta pretraining data and more toward the experimental finetuning data.

Figure S4. Regime extrapolation for GFP and Ube4b datasets. The GFP and Ube4b datasets contain variants with higher order mutations, enabling us to test two types of regime extrapolation: Train 1 and Train 1+2. The bar plots (left) show the counts of variants with the specified number of mutations for each dataset. The strip plots (right) show the performance of regime extrapolation for Train 1, where we train on single substitution variants and evaluate on variants with 2+ substitutions, and Train 1+2, where we train on variants with single or double substitutions, and evaluate on variants with 3+ substitutions. The strip plots show the performance of 9 test set replicates, and the red vertical line denotes the median.

Figure S5. Performance of METL-Local with and without pretraining. These plots show the correlation performance of Linear, METL-Local (random init), and METL-Local. METL-Local (random init) is a model with the same architecture as METL-Local but without pretraining on Rosetta scores. (a) The learning curves show that METL-Local (random init) substantially underperforms both Linear and pretrained METL-Local, emphasizing the impact pretraining on Rosetta scores has on this transformer-based architecture. Given enough experimental training data, METL-Local (random init) converges to the performance of the other models for most datasets. (b) METL-Local (random init) outperforms Linear for position extrapolation due to the fact that Linear is not able to perform position extrapolation but is substantially worse than METL-Local. For the other types of extrapolation, METL-Local (random init) performs about the same or worse than Linear.

Figure S6. Performance of baseline models directly using Rosetta total score. Rosetta *total score* is the score term from Rosetta with no supervised training on experimental data. Linear-RTS is a linear ridge regression model trained on experimental data with one hot encoding features augmented with the Rosetta *total score* as an additional input feature. Both of these models require running Rosetta to compute the *total score* for every variant, even during inference. For comparison, this figure also shows the performance of Linear and METL-Local. (a) For small training set sizes, incorporating Rosetta *total score* as an additional input feature for ridge regression greatly improved performance over solely using one hot encoding features, as demonstrated by the difference in performance between Linear and Linear-RTS. While Linear-RTS sometimes matched METL-Local's performance and even exceeded it on the GRB2-A dataset, METL-Local still outperformed Linear-RTS on average by a small amount and is much faster. (b) METL-Local outperformed Linear-RTS across most datasets and extrapolation tasks. The performance differences were sometimes substantial, such as for position extrapolation with GB1. In other cases, the performance differences were much smaller, such as for regime extrapolation.

Figure S7. Performance of additional baseline models. Correlation performance of Linear, fully connected networks (FC), sequence convolutional networks (CNN), and METL-Local. (a) METL-Local has strong advantages over the fully connected network and CNN on nearly every dataset. The CNN performed about the same as Linear across different sized training sets. The fully connected network typically performed about the same or worse than Linear, especially for mid-size training sets. (b) METL-Local exhibits much better position extrapolation capabilities than all three baseline models as well as substantially better GFP regime extrapolation.

Figure S8. Performance of one-dimensional and three-dimensional relative position embeddings. This figure shows the performance of METL-Local and METL-Global with one-dimensional (1D) sequence-based and three-dimensional (3D) structure-based relative position embeddings. (a) Learning curves showing Spearman correlation between true and predicted scores across a range of training set sizes. (b) Spearman correlation between true and predicted scores for position, mutation, score, and regime extrapolation. Overall, METL-Local does not benefit much from three-dimensional embeddings over one-dimensional, while METL-Global shows consistent improvement with the three-dimensional embeddings.

Figure S9. Performance of PLM finetuning and feature extraction. This figure shows the performance of METL-Local, METL-Global, and ESM-2 with both finetuning (FT) and feature extraction (EX). To perform feature extraction, we saved outputs from the appropriate internal layer of each model and then used those features as inputs to train linear ridge regression. Finetuning consistently outperformed feature extraction for METL-Local and METL-Global across (a) different training set sizes and (b) extrapolation tasks. For ESM-2, there were several instances where feature extraction substantially outperformed finetuning when applied to (a) small training set sizes, namely for the DLG4, GRB2-B, Pab1, and TEM-1 datasets. Notably, the performance of ESM-2 feature extraction exceeded the performance METL-Local finetuning for DLG4 and Pab1 with the smallest training set sizes. For (b) extrapolation tasks, ESM-2 finetuning generally performed better than feature extraction.

Figure S10. Feature extraction performance of ESM-2 models with 35M, 150M, and 650M parameters. (a) Across the range of training set sizes, the 150M parameter model consistently outperformed the 35M parameter model, with the exception of the DLG4 dataset, where the 35M parameter model performed better. Surprisingly, for small training set sizes, the 650M parameter model performed worse than both the 35M and 150M parameter models with the GFP, DLG4, and Pab1 datasets. For larger training set sizes, the 650M parameter model offered some improvement over the 35M and 150M parameter models with the GB1, GRB2-A, and GRB2-B datasets. However, in all cases Linear was the best model with larger datasets. (b) Across extrapolation tasks, the 35M parameter model tended to perform worse than the 150M and 650M parameter models. The 650M parameter model often performed the best, but not in all instances, and the differences between the models were minor in some cases. The Linear baseline was better than the feature extraction ESM-2 models on average for score and regime extrapolation.

Figure S11. Performance of METL-Global with 20M and 50M parameters (a) Across different training set sizes, the 50M parameter model performed similarly to the 20M parameter model on average. (b) For position, mutation, and regime extrapolation, the 50M parameter model performed slightly better on average than the 20M parameter model. For score extrapolation, the two models performed similarly on average.

Figure S12. **Performance of METL-Global source models predicting Rosetta** *total score*. This figure shows the performance of 20M and 50M parameter METL-Global source models on predicting Rosetta *total score* for both in-distribution and out-of-distribution PDBs. In-distribution PDBs are the 148 PDBs that were used as part of the METL-Global pretraining data, while out-of-distribution PDBs consist of the experimental dataset PDBs, which were not used for METL-Global pretraining. The 50M parameter METL-Global model overfits more than the 20M parameter model when predicting Rosetta *total score* on in-distribution PDBs, and it generalizes worse to out-of-distribution PDBs.

Figure S13. Pairwise correlations between GB1 DMS score and Rosetta scores. Heatmap showing pairwise Spearman correlations between the GB1 experimental functional score (DMS Score) and Rosetta score terms. Rosetta scores are color coded, with green representing all-atom REF15 scores, blue representing filter scores, orange representing centroid score3 scores, and red representing InterfaceAnalyzer binding scores. Correlations were computed using the GB1 DMS variants.

Figure S14. Score distribution of the 64 GFP variants. The 64 GFP variants randomly selected for METL-L-GFP training were split by score into three bins for visualization purposes. The bins were manually defined based on one threshold separating the two main modes of the distribution and another at the wild type score of 0. There are only eight variants in the bin with positive scores. The score represents the variant's brightness.

Figure S15. The positions of all 209 unique mutations for the 64 GFP variants The mutations are divided using the same binning procedure and bin labels as Fig. S14. If there were multiple mutations at a position within a bin, it is marked with a numeric label. White indicates that no mutation is present at that position. A bar with no numeric label indicates there is only one mutation present at that position.

Figure S16. The 20 engineered GFP variants. Each row corresponds to a variant, where if a mutation was made it is shown in bold at the corresponding sequence position. O5 corresponds to Observed 5 mutant designs, U5 Unobserved 5 mutants, O10 Observed 10 mutants, and U10 Unobserved 10 mutants. The wild-type GFP sequence is shown in the top row.

Figure S17. Experimental GFP and mKate2 fluorescence for engineered GFP variants. We expressed the GFP variants as fusion proteins with mKate2. The mKate2 sequence remained constant across the different GFP variants. These plots show GFP and mKate2 fluorescence normalized to optical density and with background fluorescence in negative control subtracted out. Variants are colored according to whether they exhibited GFP fluorescence. Multiple replicates are shown. Because the mKate2 sequence remained constant, variation in mKate2 fluorescence may be due to changes in GFP stability.

Figure S18. Correlation between DLG4 and DLG4-2021 dataset scores for 3,825 intersecting variants. These datasets both assayed PSD-95 PDZ3 binding to CRIPT, yet they disagree on scores, suggesting differences in methodology. We used DLG4 in our main analysis.

Figure S19. Distribution of METL-L-GFP predicted brightness of best variant found when increasing number of optimized mutations. We ran simulated annealing at different mutational distances from wild type using the same procedure used to design the 20 GFP variants with one exception. Instead of running simulated annealing 10,000 times for each mutation distance, we only ran it 100 times. The distribution of METL-L-GFP predicted brightness scores does not continue to increase as the number of mutations increases.

Figure S20. Distribution of METL-L-GFP predicted brightness for increasing number of random mutations. For each mutational distance from wild type, we randomly selected 10,000 variants and calculated their predicted brightness scores. At higher mutational distances, METL-L-GFP predicts lower brightness scores. However, the predicted brightness scores stabilize and do not continue decreasing.

Rosetta score term	Description	Rosetta score term	Description
total_score	REF15	exposed_np_AFIMLWVY	Custom
fa_atr	REF15	exposed_polars	Custom
fa_dun	REF15	exposed_total	Custom
fa_elec	REF15	one_core_each	Custom
fa_intra_rep	REF15	pack	Custom
fa_intra_sol_xover4	REF15	res_count_buried_core	Custom
fa_rep	REF15	res_count_buried_core_boundary	Custom
fa_sol	REF15	res_count_buried_np_core	Custom
hbond_bb_sc	REF15	res_count_buried_np_core_boundary	Custom
hbond_lr_bb	REF15	ss_contributes_core	Custom
hbond_sc	REF15	ss_mis	Custom
hbond_sr_bb	REF15	total_hydrophobic	Custom
lk_ball_wtd	REF15	total_hydrophobic_AFILMVWY	Custom
omega	REF15	total_sasa	Custom
p_aa_pp	REF15	two_core_each	Custom
pro_close	REF15	unsat_hbond	Custom
rama_prepro	REF15	centroid_total_score	Centroid
ref	REF15	cbeta	Centroid
yhh_planarity	REF15	cenpack	Centroid
buried_all	Custom	env	Centroid
buried_np	Custom	hs_pair	Centroid
contact_all	Custom	pair	Centroid
contact_buried_core	Custom	rg	Centroid
contact_buried_core_boundary	Custom	rsigma	Centroid
degree	Custom	sheet	Centroid
degree_core	Custom	ss_pair	Centroid
degree_core_boundary	Custom	vdw	Centroid
exposed_hydrophobics	Custom		

Table S1. Rosetta score terms. The Rosetta score terms used to train METL.

	Description	Organism	Molecular Function	Selection	Length	Variants	Ref.
GFP	Green fluorescent protein	A. victoria	Fluorescence	Brightness	237	51714	[2]
DLG4	Postsynaptic density protein 95 PDZ3 domain	H. sapiens	Synaptic organization	CRIPT binding	84	8251	[3]
GB1	Protein G B1 domain	Streptococcus sp.	Antibody binding	IgG-Fc binding	56	536084	[4]
GRB2-A	Growth factor receptor-bound protein 2 SH3 domain	H. sapiens	Signaling adaptor	Abundance	56	63366	[3]
GRB2-B	Growth factor receptor-bound protein 2 SH3 domain	H. sapiens	Signaling adaptor	GAB2 binding	56	33441	[3]
Pab1	Pab1 RNA recognition motif (RRM) domain	S. cerevisiae	Poly(A) binding	mRNA binding	75	37710	[5]
TEM-1	TEM-1 β-lactamase	E. coli	Antibiotic hydrolysis	Ampicillin resistance	286	12374	[6]
Ube4b	Ubiquitination factor E4B U-box domain	M. musculus	Ubiquitin activation	Ubiquitin ligase activity	102	88375	[7]

Table S2. Experimental datasets. We evaluated METL on experimental datasets representing proteins of varying sizes, folds, and functions.

Rosetta score term	Description
complex_normalized	InterfaceAnalzyer
dG_cross	InterfaceAnalzyer
dG_cross/dSASAx100	InterfaceAnalzyer
dG_separated	InterfaceAnalzyer
dG_separated/dSASAx100	InterfaceAnalzyer
dSASA_hphobic	InterfaceAnalzyer
dSASA_int	InterfaceAnalzyer
dSASA_polar	InterfaceAnalzyer
delta_unsatHbonds	InterfaceAnalzyer
hbond_E_fraction	InterfaceAnalzyer
hbonds_int	InterfaceAnalzyer
nres_int	InterfaceAnalzyer
per_residue_energy_int	InterfaceAnalzyer
side1_normalized	InterfaceAnalzyer
side1_score	InterfaceAnalzyer
side2_normalized	InterfaceAnalzyer
side2_score	InterfaceAnalzyer

Table S3. Binding score terms. The Rosetta binding score terms, calculated on the GB1-IgG complex structure and used in addition to the standard score terms to train METL-Bind.

ID	Constraint	# Muts	Mutations
1	Observed	5	S26R,K164R,Q175L,N196Y,G226W
2	Observed	5	S26R,I126V,K164R,Q175L,D195Y
3	Observed	5	K164R,Q175L,N196Y,A204T,G226R
4	Observed	5	S26R,S70G,Q175L,G226W,Y235H
5	Observed	5	K164R,Q175L,N196Y,G226R,I227F
6	Unobserved	5	N103I,I150W,V161I,G230K,K236R
7	Unobserved	5	L42V,N162R,L176W,D195C,L219F
8	Unobserved	5	D34W,F97Y,L176R,N183V,G230R
9	Unobserved	5	I12L,S26T,Q175V,A225R,G226K
10	Unobserved	5	P11R,N103I,V161M,G230W,L234M
11	Observed	10	S26R,I121V,I126V,K164R,Q175L,N196Y,S200N,S203T,A225G,G226W
12	Observed	10	S26R,F97S,N103S,I121V,K164R,Q175L,N196Y,G226R,I227F,Y235H
13	Observed	10	S26R,S70G,D100G,K105E,I126V,Q175L,N196Y,S203T,G226R,Y235H
14	Observed	10	S26R,K39R,S70G,I126V,Q175L,S200N,S203T,A225G,G226W,I227F
15	Observed	10	S26R,K105E,I126T,E140V,K164R,Q175L,N196Y,S203T,G226W,Y235H
16	Unobserved	10	F97W,V161M,S173E,Q175Y,Q182R,S200M,A204C,L219I,V222L,G230R
17	Unobserved	10	V9I,S28R,F97Y,N103I,L176R,N183V,H197F,L219W,A225W,G230Q
18	Unobserved	10	V9R,V91M,E93W,K105R,N162R,T184V,L193M,S203Q,G230M,L234W
19	Unobserved	10	D34W,I126E,L139M,E140R,Q175V,L193F,A204W,T228S,G230N,E233Q
20	Unobserved	10	P11H,E15N,S26E,S28I,I96W,S173K,Q175M,H197F,A225R,G230R

Table S4. GFP designed sequences. The sequences designed in the GFP low-N design experiment.

Dataset	Structure Acquired From	Notes	Num Variants
GFP	RosettaCM		18,681,329
DLG4-2021	PDB: 6QJI	Structure not truncated.	20,270,692
DLG4	PDB: 6QJI	Structure not truncated. Dataset is based on the DLG4-2021 dataset but contains approximately 2M additional variants to cover additional residues present in the reference sequence.	22,221,845
GB1	PDB: 2QMT		12,556,374
GRB2-A/B	AlphaFold DB: AF-P62993-F1-model_v4	Structure truncated to match DMS sequence.	20,294,793
Pab1	RosettaCM		19,667,539
TEM-1	AlphaFold DB: AF-Q6SJ61-F1-model_v4		19,441,290
Ube4b	RosettaCM		19,734,229

Table S5. Rosetta datasets for METL-Local. Information about the Rosetta datasets used to train the METL-Local source models, including PDB origin and the final number of variants in each dataset. The DLG4-2021 dataset was not used in the main analysis.

	Acquired from	Files / URN / Accession	Variant filtering	Score transformation	Ref.
GFP	Paper supplement	amino_acid_genotypes_to_brightness.tsv	Drop variants with mutations to stop codons	Normalized to WT by subtracting WT score	[2]
DLG4-2021	MaveDB	urn:mavedb:00000053-a	Keep if (inp >= 200) or (inp > 10 and sel >= 1)	N/A	[8]
DLG4	NCBI GEO	GSE184042	N/A	Normalized to WT by subtracting WT score	[3]
GB1	Paper supplement	mmc2.xlsx	Keep if input_count + sel_count >= 5	Computed from read counts using Enrich2 [9]	[4]
GRB2-Abundance	NCBI GEO	GSE184042	N/A	Normalized to WT by subtracting WT score	[3]
GRB2-Binding	NCBI GEO	GSE184042	N/A	Normalized to WT by subtracting WT score	[3]
Pab1	Paper supplement	Supplementary tables 2 and 5	N/A	Converted to log scores by taking log base 2	[5]
TEM-1	Paper supplement	mmc2.xlsx	N/A	Converted to log scores by taking log base 2	[6]
Ube4b	MaveDB	urn:mavedb:00000004-a-3	Drop variants with mutations to stop codons	N/A	[7]

Table S6. Experimental dataset preprocessing. This table specifies the experimental datasets used in this study, where we acquired them from, and any filtering or transformations we applied to standardize the dataset format. The DLG4-2021 dataset was not used in the main analysis.

References

1. Rives, A. *et al.* Biological structure and function emerge from scaling unsupervised learning to 250 million protein sequences. *Proc. Natl. Acad. Sci.* **118**, e2016239118. doi:10.1073/pnas.2016239118 (2021).

2. Sarkisyan, K. S. *et al.* Local fitness landscape of the green fluorescent protein. *Nature* **533**, 397–401. doi:10.1038/nature17995 (2016).

3. Faure, A. J. *et al.* Mapping the energetic and allosteric landscapes of protein binding domains. *Nature* **604**, 175–183. doi:10.1038/s41586-022-04586-4 (2022).

4. Olson, C. A., Wu, N. C. & Sun, R. A Comprehensive Biophysical Description of Pairwise Epistasis throughout an Entire Protein Domain. *Curr. Biol.* **24**, 2643–2651. doi:10.1016/j.cub.2014.09.072 (2014).

5. Melamed, D., Young, D. L., Gamble, C. E., Miller, C. R. & Fields, S. Deep mutational scanning of an RRM domain of the Saccharomyces cerevisiae poly(A)-binding protein. *RNA* **19**, 1537–1551. doi:10.1261/rna.040709.113 (2013).

6. Gonzalez, C. E. & Ostermeier, M. Pervasive Pairwise Intragenic Epistasis among Sequential Mutations in TEM-1 β-Lactamase. *J. Mol. Biol.* **431**, 1981–1992. doi:10.1016/j.jmb.2019.03.020 (2019).

7. Starita, L. M. *et al.* Activity-enhancing mutations in an E3 ubiquitin ligase identified by high-throughput mutagenesis. *Proc. Natl. Acad. Sci.* **110**, E1263–E1272. doi:10.1073/pnas.1303309110 (2013).

8. Nedrud, D., Coyote-Maestas, W. & Schmidt, D. A large-scale survey of pairwise epistasis reveals a mechanism for evolutionary expansion and specialization of PDZ domains. *Proteins: Struct. Funct. Bioinforma.* **89**, 899–914. doi:10.1002/prot.26067 (2021).

9. Rubin, A. F. *et al.* A statistical framework for analyzing deep mutational scanning data. *Genome Biol.* **18**, 150. doi:10.1186/s13059-017-1272-5 (2017).