CLigOpt: Controllable Ligand Design through Target-Specific Optimisation

Yutong Li
Department of Informatics
King's College London
UK

Pedro Henrique da Costa Avelar
Department of Informatics
King's College London
UK

Xinyue Chen
Department of Informatics
King's College London
UK

Li Zhang
Infocomm Research
A*STAR
Singapore

Min Wu
Infocomm Research
A*STAR
Singapore

Sophia Tsoka
Department of Informatics
King's College London
UK

ABSTRACT

Motivation: Key challenge in deep generative models for molecular design is to navigate random sampling of the vast molecular space, and produce promising molecules that compromise property controls across multiple chemical criteria. Fragment-based drug design (FBDD), using fragments as starting points, is an effective way to constrain chemical space and improve generation of biologically active molecules. Furthermore, optimisation approaches are often implemented with generative models to search through chemical space, and identify promising samples which satisfy specific properties. Controllable FBDD has promising potential in efficient target-specific ligand design.
Results: We propose a controllable FBDD model, CLigOpt, which can generate molecules with desired properties from a given fragment pair. CLigOpt is a Variational AutoEncoder-based model which utilises co-embeddings of node and edge features to fully mine information from molecular graphs, as well as a multi-objective Controllable Generation Module to generate molecules under property controls. CLigOpt achieves consistently strong performance in generating structurally and chemically valid molecules, as evaluated across six metrics. Applicability is illustrated through ligand candidates for hDHFR and it is shown that the proportion of feasible active molecules from the generated set is increased by 10%. Molecular docking and synthesisability prediction tasks are conducted to prioritise generated molecules to derive potential lead compounds.
Availability and Implementation: The source code is available via `https://github.com/yutongLi1997/CLigOpt-Controllable-Ligand-Design-through-Target-Specific-Optimisation`.

***K*eywords** Ligand Design · Deep Learning · Generative Model

1 Introduction

The development of novel drugs is dependent on the efficient discovery of novel molecules [1]. A critical challenge in this process is the difficulty in navigating the immense molecular space. Traditional methods, such as high-throughput screening, are inefficient as they require large resources and only result in a small number of hits [2]. Attention has been drawn to powerful generative deep learning techniques for efficient drug design due to their ability to learn a distribution for a given dataset and produce novel synthetic data from it. Deep generative models can explore chemical space efficiently through formulating a mapping between desired properties and corresponding molecular structures [3]. Attributed to the success of syntactic pattern recognition in language modelling tasks, early molecular generative models are designed on the basis of SMILES, a line notation that describes chemical structures using ASCII strings. However, SMILES representation is limited by its intrinsic instability in describing molecular structural information, as structurally similar molecules can result in dissimilar SMILES strings [4].

Graph-based generative models are considered particularly suitable for molecular generation, as molecular structures are naturally well-represented by graphs [5]. With success in applications of generative models and Graph Neural Networks (GNNs), many popular generative architectures such as Variational Autoencoder (VAE) [6], Flow-based models [7], are adapted to graph data structures and applied on molecule generation tasks. A common generation strategy starts with a latent representation with no atoms and bonds, building molecular graphs through autoregressive or one-shot generation. However, such generation strategy utilises random sampling to introduce novelty in the generated molecular structures. As molecule generation is extremely strict with precise validity and biological constraints, the basic graph-based molecular generation is unreliable and requires further control, which leads to the adoption of chemistry-aware constrained generation steps (e.g.[6]).

Fragment-based drug design (FBDD) approaches, which generate molecules conditioned on pre-existing sub-molecular units, constitute effective means to further constrain chemical space and improve generation of biologically active compounds [8]. Compared to random sampling schemes widely applied in exploring novel structures, using chemically meaningful fragments in molecular generation keeps search space chemically relevant and reduces the number of generation steps needed for frequent molecular motifs [9]. Moreover, FBDD strategies can utilise information obtained from structure-activity relationship analysis, and can preserve such useful biological activity properties in the synthesised molecules. FBDD strategies have been introduced and successfully applied in fragment-to-lead studies via different techniques, such as scaffold hopping [10], linker/PROTAC design [11], and R-group optimisation [7].

Optimisation approaches are often integrated with generative models to navigate through the search space and identify promising initial seeds which can generate molecules with specified properties. Such optimisation is usually implemented through heuristic optimisation techniques, such as, Bayesian Optimisation (BO) [12], or Reinforcement Learning (RL) [13]. However, these methods require additional computation while balancing exploration and exploitation within the explored space. For instance, BO may struggle with high-dimensional search spaces as the number of features increases and the search space becomes increasingly sparse, thereby requiring more time and training data to find promising regions to sample. RL is limited in multi-objective optimisation, as it requires large volume of data and involves a lot of computation. Whereas for molecular generation problem, the more conditions added to optimisation objective, the less suitable molecules are for policy training. Therefore, controlling multiple attributes in molecular design efficiently remains challenging.

To generate molecules that preserve chemically meaningful fragments and combine multiple attributes relating to different properties, we propose a controllable graph-based deep generative model for fragment linking, CLigOpt, towards target-specific ligand generation. CLigOpt takes two substructures with desired chemical functions and generates a linker that connect them, resulting in a valid molecule. CLigOpt incorporates a Controllable Generation Module (CGM), which evaluates an initial sample with respect to its chemical properties before generation, so that linkers satisfy multiple chemical property requirements. Our model exhibits consistent and strong performance across six evaluation metrics in both structural feasibility assessment and chemical usefulness. A case study on designing inhibitors for hDHFR is used to demonstrate applicability, and the quality of generated inhibitors is assessed via molecular docking simulations and retrosynthesis reaction estimation. The top prioritised molecules are provided as potential leads for hDHFR inhibition, together with the predicted retrosynthesis reactions.

The main contributions of our work are as follows: (i) a VAE-based model for linker design, where co-embeddings of nodes and edges are utilised to improve the information learned from molecular graphs, is developed and evaluated, (ii) a multi-objective controllable molecular generation module, CGM, is introduced to generate promising target-specific ligands, (iii) comparisons with state-of-the-art methods and multiple metrics are reported to evaluate results of the generative process.

2 Methodology

2.1 Data

The processed and filtered ZINC [14] and CASF [15] datasets were used as previously described [11] for general-purpose model training and testing (4174,997 examples from ZINC for training, 400 examples from ZINC and 309 examples from CASF for testing). Each example consisted of two fragments and a linker with size between 3 and 12 atoms. For target-specific linker design, 814 inhibitors and their binding affinities (pIC50) were obtained from ChEMBL [16], targeting human dihydrofolate reductase (hDHFR). The inhibitors were processed and fragmented following the procedure described in [17], resulting in 1576 fragment pairs, 80% of which were used for training affinity predictors, and 20% selected for target-specific controllable generation.

Figure 1: A diagrammatic representation of CLigOptCensNet. (A) shows an overview of the CensNet encoder, two fragments and a complete molecule are encoded into latent space, from where an initial representation for decoder is formed through the weighted sum of the average fragment representation and a sample is how the model Encoder encodes two molecules into the latent space, which is then decoded by our Decoder. (B) shows an overview of CensNet decoder, where the initial representation is applied through a sequential edge prediction process joining the two fragments. (C) the Controllable Generation Module (CGM) where our trained encoder is used to encode molecules into the latent space to fit an explicit density model and attribute classifiers, and then sample from the fitted density model and attribute classifiers before decoding each point into the final molecule.

2.2 Model Framework

The proposed CLigOpt methodology is a graph-based Variational Autoencoder (VAE) framework which takes two molecular fragments as input and generates a linker to form a complete plausible molecule. CLigOpt contains two components, a generative network θ that maps from a latent representation z to a sample x, providing a joint distribution on

$$p_\theta(x, z) = p_\theta(x|z)p(z) \tag{1}$$

where $p(z)$ is a smooth distribution, $p_\theta(x|z)$ is the decoder that maps from z to x. An encoder ϕ maps from x to z, which is approximated by $q_\phi(z|x)$ to reduce the computational cost. Our training and generative procedures are outlined in Figure 1 and Algorithms S1 and S2.

Encoder The workflow of encoder is shown in Figure 1 (A). Two models (GCN [18] and CensNet [19]) are employed as encoders and their ability to learn representations from hidden graph embeddings is investigated. Specifically, GCN is one of the most commonly used GNN architectures and its convolutions can be seen as message-passing through the node adjacency matrix, using only edge information to determine which nodes are adjacent to update node features. CensNet defines two types of layers, i.e. node and edge layer, which employ convolutions on line graphs, enabling the roles of nodes and edges to switch. Through convolution operations, co-embeddings of nodes and edges can be learned. Owing to this alternative updating rule, CensNet allows embedding nodes and edges to latent feature space simultaneously, as well as mutual enrichment over node and edge information.

We developed two version of CLigOpt models based on the two aforementioned networks. CLigOptGCN used three layers of GCNs as encoder, while the CLigOptCensNet encoder contained two node CensNet layers and one edge CensNet layer (see Figure 1 (A)). The means and variances, denoted as (μ_f, σ_f) and (μ_m, σ_m), of fragment G_F and molecule G_M are obtained by the encoder, which can be formulated as:

$$(\mu_f, \sigma_f) = CensNet(G_F); \ (\mu_m, \sigma_m) = CensNet(G_M) \tag{2}$$

Then, the initial graph representation for decoder, z, is the sum of μ_f and the combination of z_m sampled from either the distribution $N_m(\mu_m, \sigma_m)$ (for training) or $N(0, 1)$ (for generation), and a latent node representation τ derived from z_m through a linear layer.

$$z = \mu_f + a_f * [z_m, \tau] \tag{3}$$

where $[,]$ represents the operation of concatenation.

Decoder Our training and generative procedures are explained in Algorithms S1 and S2. The decoder utilises a similar sequential generation scheme inspired by CGVAE [6] where GNNs are applied to predict edge connection through a bond-by-bond manner (see Figure 1 (B)). We utilise the same graph embedding network engaged in **Encoder** (GCN and CensNet) to learn an informative representation of the generated graph. Networks are improved by adding layer normalisation and dropout unit for each layer to reduce the impact of internal co-variate shift and prevent overfitting.

During generation, a set of nodes is initialised between the two fragments from which a linker is built through an iterative node update, edge selection and edge labelling process. At the beginning of each iteration, a focus node u is first selected for the decoder to predict its connectivity to the graph, including a pseudo stop node, subject to the valency constraints. The initial graph representation z is first be updated via a graph encoder layer. The graph representation z^t at the $t - th$ step (iteration) is represented by,

$$z^t = CensNet(z, Adj_{n\_f}^{t-1}, x_{e\_f}^{t-1}, Adj_{e\_f}^{t-1}) \tag{4}$$

Then, for each remaining node v, a feature vector is constructed to predict the probability of an edge existing between u and v and the type of this edge. The feature vector integrates node-level information on the focus node and its edge candidates, as well as graph-level information for the initial graph representation and the current graph states. The feature vector for predicting the probability of an edge between u and v is provided by:

$$\Phi_{u,v}^t = [s_u^t, s_v^t, d_{u,v}, H^0, H^t, D] \tag{5}$$

where s_u^t and s_v^t are the concatenation of hidden state z^t and atomic label representations of the focus node u and the remaining nodes v at step t, $d_{v,u}$ is the graph distance between v and u, H^0 is the average initial graph representation, H^t is the average representation of the current graph state, D represents the 3D structural information of the two input fragments, and the vectors inside square brackets are concatenated.

At the end of each step, the edge with the highest predicted probability is selected to connect to the focus node. The probability of an edge connecting to the stop node is also predicted through the same procedure. When the stop node is

selected, the current focus node is finished and the nodes it connects then become the next nodes to focus. For step t, new status $Adj^t_{n\_f}$, $x^t_{e\_f}$ and $Adj^t_{e\_f}$ are updated by edge prediction module MLP_E.

$$(z, Adj^t_{n\_f}, x^t_{e\_f}, Adj^t_{e\_f}) = MLP_E(\Phi^t_{u,v}) \tag{6}$$

Such process is repeated until every remaining node is visited. The largest connected component is returned as the predicted molecule. After predicting all edges, the node symbols $\hat{x}_M$ is generated by a node prediction module MLP_N.

$$\hat{x}_M = MLP_N(z) \tag{7}$$

The reconstructed molecule $\hat{G}_M$ is then formed by $\hat{x}_M$ and $Adj^t_{n\_f}$.

Training. Our model is trained with a standard VAE objective. For a given pair of fragments G_F and a molecule G_M, the model is trained to reconstruct G_M from (G_F, z) using Teacher Forcing [20], while enforcing the regularisation constraint on the encodings of G_F and G_M. Thus, the objective function comprises two components, a reconstruction loss and a regularisation loss:

$$L(\theta, \phi) = L_{recon}(\theta, \phi) + L_{KL}(\phi) \tag{8}$$

2.3 Target-Specific Controllable Generation.

We built a Controllable Generation Module (CGM) referring to CLaSS [21] that optimises molecule generation for desirable properties. Given an initial sample z, and a set of independent attributes $a \in \{0,1\}^n = \{a_1, a_2, ..., a_n\}$, CLaSS trains a set of classifiers that predicts the probability of z getting accepted on each attribute a_i. The process of conditional generation of a molecule x given attributes the independent attributes, $p(x|a)$, can then be formulated as:

$$p(x|a) = \mathbb{E}_z[p(z|a)p(x|z)] \approx \mathbb{E}_z[\hat{p}_\xi(z|a)p_\theta(x|z)] \tag{9}$$

where $\hat{p}_\xi(z|a)$ is derived using a density model $Q_\xi(z)$, in combination with a per-attribute classifier model $q_\xi(a_i|z)$, based on Bayes' rule and conditional independence of the attributes, leveraging rejection sampling from parametric approximations to $p(z|a)$. By enforcing multiple attribute constraints, the acceptance probability is the product of the scores from the attribute predictors, while sampling from the explicit density $Q_\xi(z)$.

Controllable Generation Module We adapt CLaSS as our Controllable Generation Module, CGM, aiming to generate molecules with high drug-likeness, high synthetic accessibility and high binding affinity to a target protein. A schematic representation of our module is illustrated in Figure 1 (C). A Gaussian mixture density model is fitted over known molecules to estimate the posterior distribution of latent space z. From there, we design three classifiers in parallel, which take in a given latent embedding z and a pair of fragments encoded by CLigOpt, to evaluate the Quantitative Estimate of Druglikeness (QED), Synthetic Accessibility (SA) score, and the negative logarithm of IC50 (pIC50) respectively, aligning with the aforementioned three standards. Rejection sampling then operates through sampling from the fitted density model. CGM evaluates whether an initial sample is likely to satisfy certain standards on selected attributes through the previously mentioned classifiers, and thus decides whether to proceed with generation with this seed or not.

3 Results

The performance of CLigOpt was measured in different aspects of molecular generation, i.e. (i) fragment linking and forming plausible molecules, assessed through benchmark linker design (Benchmark Evaluation on Test Sets) and (ii) generating target-specific drug-like molecules (Controllable Target-Specific Ligand Generation), measured through a case study of generating lead candidates for hDHFR. Generated molecules were then prioritised and binding potential of the generated molecule set was evaluated via docking (Evaluation via Molecular Docking). Finally, synthesisability via specific reaction steps of promising molecules are indicated (Synthesisability of Generated Molecules).

3.1 Benchmark Evaluation on Test Sets

The ability of CLigOpt in generating reasonable molecules was evaluated on two benchmark datasets, namely ZINC and CASF, and compared with two baseline models for fragment linking, namely DeLinker [11] and FFLOM [7]. DeLinker is a VAE-based model that generates molecules in bond-by-bond manner, whereas FFLOM is a flow-based model that carries out one-shot generation of molecules. For each test set, 250 molecules were generated for each fragment pair, the quality of generated molecules was assessed on the basis of (i) structural usefulness via validity, novelty and uniqueness metrics, and (ii) chemical usefulness, i.e. Synthetic Accessibility (SA) score, ring aromaticity, and Pan-Assay Interference compounds (PAINS). The results are shown in Figure 2 and Table S1.

Figure 2: A radar plot showing the performance of our model as well as the two baselines. Although our model does not outperform the best model in each category, CLigOptCensNet achieves the best average performance.

Model Comparison. CLigOpt shows comparative but more consistent performance across all metrics compared to baseline models on ZINC test set. All models achieve similar performance in terms of validity, ring aromaticity and PAINS. CLigOptCensNet attains the best overall performance with high scores in every metric, while CLigOptGCN performs slightly worse in uniqueness. While DeLinker underperforms in uniqueness and novelty (30.21% and 49.44% less molecules compared to CLigOptCensNet), FFLOM underperfroms in SA filter (59.38% less molecules). Similar results are observed on CASF test set (see Figure S1), where CLigOpt outperforms DeLinker (58.42% on uniqueness, 48.58% on novelty) and FFLOM (49.34% on SA).

This indicates that DeLinker is able to generate molecules that are synthesisable and have good potential as drug candidates, but the generated set is repetitive and underperforms in novelty. On other hand, FFLOM can generate highly novel and unique molecules, however mostly difficult to synthesise. As a trade-off between these two cases, CLigOpt demonstrates competitive performance across all evaluation aspects.

3.2 Controllable Target-Specific Ligand Generation

A potential anticancer agent, hDHFR, is employed as target for a case study to investigate the ability of CGM to generate molecules with desired properties. QED, SA and pIC50 were used as the optimisation goals, aiming to generate molecular structures that fulfil pre-set conditions for three properties, (i) druglikeness, (ii) synthesisability and (iii) binding activity to hDHFR. The three conditions correspond to three classifiers predicting from an initial sampling of the latent space, to evaluate whether CLigOpt can generate a molecule with QED > 0.6, SA < 3, and pIC50 > 6. The classifiers can be used together or independently to generate molecules with different property control. We take the test set of hDHFR inhibitors described in Data, and generate 10 molecules for each pair of fragments for random sampling and rejection sampling.

Ground Truth Property Estimation. To evaluate the ability of CLigOpt in filtering out samples that did not meet the pre-set conditions, tools are employed to compute the true properties for the generated molecules as a guide. Due to concerns of introducing biases from overfitting, we utilise two pre-defined algorithms from rdkit [22] instead of neural networks, to compute the QED and SA score. Three machine learning approaches with diverse architectures were explored to predict pIC50: (i) transformer-CNN [23], a SMILES-based Quantitative Structure-Activity Relationship (QSAR) model that learns molecular embeddings from a transformer encoder, and predicts the corresponding activity

	QED>0.6	SA<3	pIC50>6	QED>0.6 & SA<3 & pIC50>6
GCN				
Random	9.78%	16.27%	53.32%	1.48%
Accepted	57.71%	31.58%	58.49%	18.92%
CensNet				
Random	11.17%	13.23%	56.99%	1.33%
Accepted	49.47%	22.07%	62.78%	10.35%

Table 1: The proportion of molecules that pass certain filters when sampling randomly versus when sampling using the CLaSS accepted set. More results for each individual property can be seen in Tables S2, S3, and S4

.

	Pred Aff	$E(kcal/mol)$	Min
ChEMBL	8.970	-8.606 ± 0.711	-10.168
GCN	6.671	-8.256 ± 0.581	-9.930
CensNet	7.058	-8.272 ± 0.902	-9.732

Table 2: Results summarising molecular dcking simulation.

using CharNN, (ii) modSAR [24, 25, 26], a two-stage QSAR model that involves detecting clusters of molecules, and applying mathematical optimisation-based piecewise linear regression to link molecular structures to their biological activities, and (iii) DeepAffinity [27], a semi-supervised deep learning model that utilises a unified RNN and CNN model to predict binding affinity. We compare Transformer-CNN and modSAR that are trained on a subset of hDHFR inhibitors, and DeepAffinity with the provided pre-trained parameters to select the most accurate model for predicting binding affinity.

Comparisons of the three models via the RMSE metric is shown in Table S5. Transformer-CNN outperforms Deep-Affinity and modSAR with RMSE = 0.82, and is selected to predict pIC50 for the generated molecules as a reference to evaluate the performance of CLaSS module. The results of the normalised fraction of molecules that meet the pre-set conditions, for a specific property as well as balancing all three properties, in a random generated set compared with CLaSS generated set are shown in Table 1. Evaluation on how CLaSS performs in a single property with different thresholds is shown in Table S2, S3, and S4.

Controllable Generation. Results show that CGM excels in efficiently generating more useful molecules. Table 1, S2, S3, and S4 report higher percentage of molecules meeting the pre-set conditions in CLaSS-generated set compared to the randomly sampled set, indicating that CLigOpt is able to identify the latent embeddings that result in molecules with desired properties. Table S2, S3, and S4 illustrates that, for QED and SA control, CLigOpt can generate a molecule set that contains three times more qualified molecules than random sampling. CLigOpt is less effective in pIC50 control, yet still better than random sampling. CLigOpt is also capable of multi-objective control, generating molecules that satisfy requirements for different goals. Moreover, the accepted set maintains a certain level of similarity to the original set in terms of QED and LogP (see Figure S2).

3.3 Evaluation via Molecular Docking

AutoDock docking [28] was employed, as developed by DeepChem [29], to further evaluate the binding of CLigOpt generated molecules. Molecular docking is conducted with the 3D structure of hDHFR on the CLaSS generated molecules with 10 highest-predicted pIC50. We compare the Binding Free Energy (BFE) of the generated molecules with 10 hDHFR inhibitors with highest binding affinities. Table 2 shows the results of average (E) and minimum (Min) BFE of these molecules, with respect to their binding affinities. Results indicate that CLigOpt is able to generate promising molecules that bind the druggable pocket of the 3D target structure with similar BFEs compared to known hDHFR inhibitors.

3.4 Synthesisability of Generated Molecules

The number of reaction steps required to complete the synthesis of a given molecule provides an indication of its complexity with respect to commercially available materials. We randomly selected 100 molecules from CLigOptGCN and CLigOptCensNet generated set obtained in Controllable Target-Specific Ligand Generation, as well as the ChEMBL set as a baseline, to compute and compare the percentages of synthesisable molecules within each set. The retrosynthetic

Figure 3: A histogram showing the proportion of molecules that could have a retrosynthetic path predicted by the model in [30]. Random samples of 100 molecules from each of our models and from 100 random molecules drawn from ChEMBL were used.

Figure 4: The two-step predicted retrosynthesis route for the best prioritised molecule (confidence: 0.92) in CLigOpt-CensNet. The molecule was prioritised according to its QED (0.655439), pIC50 (7.231879), and SA (2.643538)

routes for each molecule were assessed using a Molecular Transformer-based [31] model [30], and it was observed that the generated molecules have higher successful retrosynthesis prediction than the ChEMBL set, with success rate of 84% molecules from the ChEMBL set, 96% from both generated sets. The distribution of the number of steps needed for each set is shown in Figure 3.

Overall, compared to the baseline set, CLigOpt generated molecules exhibit promising results in synthesisability regarding retrosynthetic analysis. Most molecules can be synthesised within 4 reaction steps. CLigOptCensNet-generated molecules show better synthesisability, managing most retrosynthetic routes in 1 or 3 steps. ChEMBL and CLigOptGCN generated molecules show similar results in the amount of molecules that can be made with in 2 steps, both achieving a peak at 3 steps. In comparison, more CLigOptGCN generated molecules require an additional step to synthesise than the ChEMBL molecules. We prioritise molecules from the two generated sets according to their QED, SA score, and pIC50, and provide the predicted retrosynthesis route for the best prioritised molecule in CLigOptCensNet in Figure 4.

4 Conclusion

In this work, a pipeline is introduced for efficient optimised molecule generation, CLigOpt, containing a Controllable Generation Module, where the generative process is restricted via rejection sampling. CLigOpt shows advantages over existing optimisation approaches in terms of reduced computational complexity, as it does not require heavy pre-training, surrogate model fitting, or policy learning. From comparing the quality of CLigOpt generated molecules with and without the property control module, we show that CLigOpt is an effective yet simple sampling scheme that improves the generation performance significantly and can handle multi-objective criteria well.

Evaluation of results is based on a variety of metrics that reflect the chemical and structural properties of the generated molecules. CLigOpt obtains consistent and strong performance across all six metrics. Performance of CLigOpt is evaluated with two encoders, GCN and CensNet. CLigOptCensNet shows slightly better performance than CLigOptGCN in novelty, uniqueness, and ring aromaticity, suggesting that employing co-embedding for nodes and edges provides more information than sole node embedding, and can also improve performance for the ensuing generative model.

The applicability of CLigOpt is illustrated via a case study on generating hDHFR ligands, evaluated through binding free energy simulation and retrosynthesis prediction. Generated molecules show similar binding compared to known hDHFR inhibitors, indicating the potential of CLigOpt to generate promising lead candidates. Future work can focus on a set of systematic optimisation objectives to further restrict and optimise searching molecular space.

Acknowledgments

YL and XC are funded by the China Scholarship Council. PHdCA acknowledges funding through KCL/A*STAR (to MW and ST). MW is partially supported by A*STAR's Decentralised Gap funding (I23D1AG081). ST acknowledges funding from the British Skin Foundation and the UK Royal Society.

References

[1] Camille Bilodeau, Wengong Jin, Tommi Jaakkola, Regina Barzilay, and Klavs F. Jensen. Generative models for molecular discovery: Recent advances and challenges. *WIREs Computational Molecular Science*, 12(5), September 2022.

[2] Xiangxiang Zeng, Fei Wang, Yuan Luo, Seung-gu Kang, Jian Tang, Felice C Lightstone, Evandro F Fang, Wendy Cornell, Ruth Nussinov, and Feixiong Cheng. Deep generative molecular design reshapes drug discovery. *Cell Rep. Med.*, 3(12), 2022.

[3] Camille Bilodeau, Wengong Jin, Tommi Jaakkola, Regina Barzilay, and Klavs F Jensen. Generative models for molecular discovery: Recent advances and challenges. *Wiley Interdisciplinary Reviews: Computational Molecular Science*, 12(5):e1608, 2022.

[4] Chao Pang, Jianbo Qiao, Xiangxiang Zeng, Quan Zou, and Leyi Wei. Deep generative models in de novo drug molecule generation. *J. Chem. Inf. Model.*, 2023.

[5] Yu Cheng, Yongshun Gong, Yuansheng Liu, Bosheng Song, and Quan Zou. Molecular design in drug discovery: a comprehensive review of deep generative models. *Briefings in bioinformatics*, 22(6):bbab344, 2021.

[6] Qi Liu, Miltiadis Allamanis, Marc Brockschmidt, and Alexander Gaunt. Constrained graph variational autoencoders for molecule design. *Advances in neural information processing systems*, 31, 2018.

[7] Jieyu Jin, Dong Wang, Guqin Shi, Jingxiao Bao, Jike Wang, Haotian Zhang, Peichen Pan, Dan Li, Xiaojun Yao, Huanxiang Liu, et al. Fflom: A flow-based autoregressive model for fragment-to-lead optimization. *Journal of Medicinal Chemistry*, 66(15):10808–10823, 2023.

[8] Muhetaer Mukaidaisi, Andrew Vu, Karl Grantham, Alain Tchagang, and Yifeng Li. Multi-objective drug design based on graph-fragment molecular representation and deep evolutionary learning. *Frontiers in Pharmacology*, 13:920747, 2022.

[9] Krzysztof Maziarz, Henry Richard Jackson-Flux, Pashmina Cameron, Finton Sirockin, Nadine Schneider, Nikolaus Stiefl, Marwin Segler, and Marc Brockschmidt. Learning to Extend Molecular Scaffolds with Structural Motifs. In *International Conference on Learning Representations*, 2022.

[10] Fergus Imrie, Thomas E Hadfield, Anthony R Bradley, and Charlotte M Deane. Deep generative design with 3d pharmacophoric constraints. *Chemical science*, 12(43):14577–14589, 2021.

[11] Fergus Imrie, Anthony R Bradley, Mihaela van der Schaar, and Charlotte M Deane. Deep generative models for 3d linker design. *Journal of chemical information and modeling*, 60(4):1983–1995, 2020.

[12] Rafael Gómez-Bombarelli, Jennifer N. Wei, David Duvenaud, José Miguel Hernández-Lobato, Benjamín Sánchez-Lengeling, Dennis Sheberla, Jorge Aguilera-Iparraguirre, Timothy D. Hirzel, Ryan P. Adams, and Alán Aspuru-Guzik. Automatic Chemical Design Using a Data-Driven Continuous Representation of Molecules. *ACS Central Science*, 4(2):268–276, February 2018.

[13] Mariya Popova, Olexandr Isayev, and Alexander Tropsha. Deep reinforcement learning for de novo drug design. *Science Advances*, 4(7), July 2018.

[14] Teague Sterling and John J Irwin. Zinc 15–ligand discovery for everyone. *Journal of chemical information and modeling*, 55(11):2324–2337, 2015.

[15] Minyi Su, Qifan Yang, Yu Du, Guoqin Feng, Zhihai Liu, Yan Li, and Renxiao Wang. Comparative assessment of scoring functions: the casf-2016 update. *Journal of chemical information and modeling*, 59(2):895–913, 2018.

[16] Anna Gaulton, Anne Hersey, Michał Nowotka, A Patricia Bento, Jon Chambers, David Mendez, Prudence Mutowo, Francis Atkinson, Louisa J Bellis, Elena Cibrián-Uhalte, et al. The chembl database in 2017. *Nucleic acids research*, 45(D1):D945–D954, 2017.

[17] Jameed Hussain and Ceara Rea. Computationally efficient algorithm to identify matched molecular pairs (mmps) in large data sets. *Journal of chemical information and modeling*, 50(3):339–348, 2010.

[18] Thomas N Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. *arXiv preprint arXiv:1609.02907*, 2016.

[19] Xiaodong Jiang, Ronghang Zhu, Sheng Li, and Pengsheng Ji. Co-embedding of nodes and edges with graph neural networks. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2020.

[20] Ronald J. Williams and David Zipser. A Learning Algorithm for Continually Running Fully Recurrent Neural Networks. *Neural Comput.*, 1(2):270–280, June 1989.

[21] Payel Das, Tom Sercu, Kahini Wadhawan, Inkit Padhi, Sebastian Gehrmann, Flaviu Cipcigan, Vijil Chenthamarakshan, Hendrik Strobelt, Cicero Dos Santos, Pin-Yu Chen, et al. Accelerated antimicrobial discovery via deep generative models and molecular dynamics simulations. *Nature Biomedical Engineering*, 5(6):613–623, 2021.

[22] A Patrícia Bento, Anne Hersey, Eloy Félix, Greg Landrum, Anna Gaulton, Francis Atkinson, Louisa J Bellis, Marleen De Veij, and Andrew R Leach. An open source chemical structure curation pipeline using rdkit. *Journal of Cheminformatics*, 12:1–16, 2020.

[23] Pavel Karpov, Guillaume Godin, and Igor V Tetko. Transformer-cnn: Swiss knife for qsar modeling and interpretation. *Journal of cheminformatics*, 12:1–12, 2020.

[24] Yutong Li, Jonathan Cardoso-Silva, John M Kelly, Michael J Delves, Nicholas Furnham, Lazaros G Papageorgiou, and Sophia Tsoka. Optimisation-based modelling for explainable lead discovery in malaria. *Artificial intelligence in medicine*, 147:102700, 2024.

[25] Jonathan Cardoso-Silva, Lazaros G Papageorgiou, and Sophia Tsoka. Network-based piecewise linear regression for qsar modelling. *Journal of Computer-Aided Molecular Design*, 33(9):831–844, 2019.

[26] Jonathan Cardoso-Silva, George Papadatos, Lazaros G Papageorgiou, and Sophia Tsoka. Optimal piecewise linear regression algorithm for qsar modelling. *Molecular informatics*, 38(3):1800028, 2019.

[27] Mostafa Karimi, Di Wu, Zhangyang Wang, and Yang Shen. Deepaffinity: interpretable deep learning of compound–protein affinity through unified recurrent and convolutional neural networks. *Bioinformatics*, 35(18):3329–3338, 2019.

[28] Oleg Trott and Arthur J Olson. Autodock vina: improving the speed and accuracy of docking with a new scoring function, efficient optimization, and multithreading. *Journal of computational chemistry*, 31(2):455–461, 2010.

[29] Bharath Ramsundar, Peter Eastman, Patrick Walters, Vijay Pande, Karl Leswing, and Zhenqin Wu. *Deep Learning for the Life Sciences*. O'Reilly Media, 2019.

[30] Philippe Schwaller, Riccardo Petraglia, Valerio Zullo, Vishnu H Nair, Rico Andreas Haeuselmann, Riccardo Pisoni, Costas Bekas, Anna Iuliano, and Teodoro Laino. Predicting retrosynthetic pathways using a combined linguistic model and hyper-graph exploration strategy. *arXiv preprint arXiv:1910.08036*, 2019.

[31] Philippe Schwaller, Teodoro Laino, Théophile Gaudin, Peter Bolgar, Christopher A Hunter, Costas Bekas, and Alpha A Lee. Molecular transformer: a model for uncertainty-calibrated chemical reaction prediction. *ACS central science*, 5(9):1572–1583, 2019.

(A) Encoder

Molecular Structure Graphs

Fragments G_F

Molecules G_M

Node Symbol Encodings

C N C O

Node Adjacency Matrix

Edge Type Encodings

e1 e2 e3 e4 e7

Edge Adjacency Matrix

e1 e2 e3 e4 e5 e6 e7

CensNet Encoder

Node Layer / Edge Layer / Node Layer

x_{n_f1}, x_{e_f1}
Adj_{n_f1}, Adj_{e_f1}
x_{n_f2}, x_{e_f2}
Adj_{n_f2}, Adj_{e_f2}

x_{n_m}, x_{e_m}
Adj_{n_m}, Adj_{e_m}

x_f

x_m

Distribution Learning

Linear Layers

μ_f, σ_f

$N_f(\mu_f, \sigma_f)$

Fragment Latent Representation

Linear Layers

μ_f

a_f

Linear Layers

μ_m, σ_m

$N_m(\mu_m, \sigma_m)$

Sampled Initial Linker Graph Representation

$z_m \sim N_m$

Linear Layers

τ

Linker Node

Initial Molecular Graph Latent Representation $z = \mu_f + a_f * \mathrm{CONCAT}(z_m, \tau)$

(B) Decoder

Update Graph Representation

Input / Node Layer / Edge Layer / Node Layer

z
$Adj_{n\_f}^{t-1}$

$x_{e\_f}^{t-1}$
$Adj_{e\_f}^{t-1}$

Edge Prediction

z^t
$\Phi_{u,v}^t$

update adjacency matrix

Node Symbol Prediction

Output

$\hat{x}_M$

$\hat{G}_M = (\hat{x}_M, Adj_{n\_f}^t)$

Novel Molecule Structure

Update Latent Graph Representation

(C) Controllable Generation Module

CLASS Training

Training Data

Mol 1

Mol 2

Mol 3

CLigOpt Encoder

$q_\theta(z|x)$

Fit explicit density model $Q_\xi(z) \approx q_\theta(z)$

Fit classifier for each attribute $q_\xi(a|z)$

a_1 — Classifier a_1
a_2 — Classifier a_2
a_3 — Classifier a_3

Controllable Generation

Sample $z \sim Q_\xi(z)$

Compute acceptance probability:

$$\prod_i q_\xi(a_i|z)$$

a_1 — $q_\xi(a_1|z)$
a_2 — $q_\xi(a_2|z)$
a_3 — $q_\xi(a_3|z)$

Accept → Decoder ...

Reject → Resample