A brain-to-text framework of decoding natural tonal sentences

Daohan Zhang[1,2,3#], Zhenjie Wang[4#], Youkun Qian[1,2,3#], Zehao Zhao[1,2,3], Yan Liu[1,2,3], Xiaotao Hao[1,2,3], Wanxin Li[1,2,3], Shuo Lu[5], Honglin Zhu[6], Luyao Chen[7], Kunyu Xu[8], Yuanning Li[4,9*], Junfeng Lu[1,2,3,8,10*]

Author affiliations:

[1]Department of Neurosurgery, Huashan Hospital, Shanghai Medical College, Fudan University, Shanghai 200040, China

[2]Shanghai Key Laboratory of Brain Function Restoration and Neural Regeneration, Shanghai 200040, China

[3]National Center for Neurological Disorders, Huashan Hospital, Shanghai Medical College, Fudan University, Shanghai 200040, China

[4]School of Biomedical Engineering, ShanghaiTech University, Shanghai 201210, China

[5]Department of Chinese Language and Literature, Sun Yat-sen University, Guangzhou 510080, China

[6]Faculty of Life Sciences and Medicine, King's College London, London SE1 1UL, UK

[7]School of International Chinese Language Education, Beijing Normal University, Beijing 100875, China

[8]Institute of Modern Languages and Linguistics, Fudan University, Shanghai 200433, China

[9]State Key Laboratory of Advanced Medical Materials and Devices, ShanghaiTech University, Shanghai 201210, China

[10]MOE Frontiers Center for Brain Science, Huashan Hospital, Fudan University, Shanghai 200040, China

[#] These authors contributed equally to this work.

[*] Corresponding authors: Junfeng Lu (junfeng_lu@fudan.edu.cn), Yuanning Li (liyn2@shanghaitech.edu.cn)

Abstract

Speech brain-computer interfaces (BCIs) directly translate brain activity into speech sound and text, yet decoding tonal languages like Mandarin Chinese poses a significant, unexplored challenge. Despite successful cases in non-tonal languages, the complexities of Mandarin, with its distinct syllabic structures and pivotal lexical information conveyed through tonal nuances, present challenges in BCI decoding. Here we designed a brain-to-text framework to decode Mandarin tonal sentences from invasive neural recordings. Our modular approach dissects speech onset, base syllables, and lexical tones, integrating them with contextual information through Bayesian likelihood and the Viterbi decoder. The results demonstrate accurate tone and syllable decoding under variances in continuous naturalistic speech production, surpassing previous intracranial Mandarin tonal syllable decoders in decoding accuracy. We also verified the robustness of our decoding framework and showed that the model hyperparameters can be generalized across participants of varied gender, age, education backgrounds, pronunciation behaviors, and coverage of electrodes. Our pilot study shed lights on the feasibility of more generalizable brain-to-text decoding of natural tonal sentences from patients with high heterogeneities.

Key words

Introduction

Sentence is the basic language unit embodies our construal of representational meaning and interpersonal meaning, which constitutes the basis for daily communication[1]. Recent investigations have demonstrated the possibility of synthesis and decoding sentences in non-tonal languages [2-11] using intracranial neural recordings such as electrocorticography (ECoG) and Utah array. These studies have primarily relied on decoding the spatiotemporal neural patterns associated with articulatory movements—such as those of the lips, tongue, and larynx—in the ventral sensorimotor cortex during intended speech production. These advancements provided novel approaches for treating anarthria[12] and enhanced the communication efficacy of speech brain-computer interfaces (BCIs)[13].

However, decoding tonal sentences is still a largely-unexplored work. More than 60% of the languages in the world are tonal[14], with approximately 2 billion people speaking tonal languages, including most Sino-Tibetan languages and the entire Tai-Kadai family[15]. Pitch in these languages is used to distinguish lexical and grammatical meaning[13]. While prior research has investigated decoding stereotypical instances of lexical tones from neural activity for monosyllabic speech[13], decoding continuous tonal sentences is still a challenging issue. Unlike the relatively stable acoustic cues in canonical forms, natural speech introduces substantial variability in tone components. According to Fujisaki model, these components, typically represented by base frequency (F0) contours, encompass base frequency, phrase variations, and accent components[16,17]. Furthermore, the influence of tone sandhi—alterations in a morpheme's tone due to syntactic context—adds an additional layer of complexity[18]. Altogether, these variances make decoding tonal sentences more complicated than both non-tonal sentences and isolated tonal syllables.

Besides, existing invasive language BCI usually reported success in individual cases, usually with

intense hyperparameter optimizing[5,9,10]. Few studies have tested the replication or generalization

of the decoding framework. It remains uncertain whether the same set of model design

hyperparameters—such as the number of convolution and recurrent blocks, hidden variables per

layer, and onset detection thresholds—will generalize across different subjects. Consequently,

verifying the generalizability of these published frameworks, especially when applied to patients

exhibiting high heterogeneity, remains elusive. In clinical settings, different patients need to

restore speech function via speech BCI have varied pronunciation behaviors, which is especially

obvious among tonal languages such as Mandarin Chinese. Mandarin speakers, influenced by

regional dialects such as Northern, Jianghuai, and subgroups like Wu-Tai, Shanghainese-

influenced, Northeastern Mandarin, demonstrate distinct tonal and syllabic variations[19]. Though

sharing the same written form of Chinese word, speakers of these mandarin branches have distinct

pronunciation behaviors on both tones and syllables. While these distinct pronunciation behaviors

or preferences do not affect speakers' daily communication, they add significant challenges to the

decoding task. In addition to the variance in pronunciation behaviors, the inherent variations in

language-functional cortical areas also contribute to the inter-subject variances. It is impossible

for invasive devices to collect identical neural signals from different patients even if the placement

of invasive electrodes is stringently controlled. Whether and to what extent these bias from both

language behaviors and varied neural signals will affect the robustness of language decoding

framework remain unknown. This uncertainty challenges the eventual generalization of speech

BCI across patients with high heterogeneity.

In this study, we aim to decode Mandarin tonal sentences from invasive neural recordings using

high-density ECoG. Targeting functionally separate neural populations within speech-related brain

regions, we tailored distinct neural network modules which detected the onsets of the utterance of

each individual Chinese character and then decode tone labels and syllable labels in parallel,

reflecting the inherent parallel coding previously observed in tonal language articulation[13,20-22].

Subsequently, a language model was used to calculate the Bayesian likelihood of the entire

sentence from the probability distribution of tonal syllable sequences, integrating the contextual

and prior information (**Fig.1**). Moreover, we established a versatile framework using a set of

standardized hyperparameters, eliminating additional needs for hyperparameter optimization, and

assessed its potential for generalization by testing across multiple patients. This approach decoded

Mandarin tonal sentences across diverse patient profiles without specific hyperparameter

adjustments.

Fig 1 Schematic overview of the brain-to-text decoder for natural speech of a tonal language.

a. Schematic overview of the tonal speech production task. Each participant was guided by a visual cue to produce one of the ten sentences. Each trial began with a fixation cross at the center of the screen for 3 seconds, and the sentence was shown in the middle of the screen in grey text. With each word turning black for 1.2 seconds consecutively from the beginning to the end of the sentence, the participant was instructed to pronounce the sentence following these go cues, the pace of the speech was not strictly aligned with the visual cues.

b. During the experiment, neural activity from speech-related cortex was recorded using implanted high-density electrocorticography array when the participant was instructed to read sentences consisted of words from a predefined vocabulary set of 40 words. The preprocessed neural signals from responsive electrodes were sampled by sliding window and was sent to the speech detection module (speech detector) to detect the onsets of words. The peri-onset neural activity within a fixed time window was used to compute the base syllable probability (across 10 possible syllables) and lexical tone probability (across 4 tones) of the word via a tone decoder and a syllable decoder respectively. A Viterbi decoding algorithm used these probabilities in conjunction with word-sequence probabilities from a pre-trained natural language model to decode the most likely sentence given the current neural activity.

Results

In this study, we recorded the neural activity of five native Mandarin-speaking participants who underwent awake surgery to treat brain tumors. Each participant was guided by sequential visual cues to produce 10 sentences consisted of 5-8 Chinese characters from a corpus of 40 Chinese characters with varied tones (**Fig. 1a**). Among 5 participants, PA1-4 completed the speech production task using normal articulating, while PA5 completed the speech production task using whispering. Participants' brain activity was recorded by temporally placed high-density ECoG grids. Subsequently, we assessed the efficacy of our proposed brain-to-text speech decoder across these 5 participants.

Decoder overview

Our brain-to-text decoder comprises interconnected modules: a speech detector, tone decoder,

syllable decoder, and a language model, functioning in a sequential stream. To decode Mandarin

tonal sentences from high-density ECoG neural recordings, our brain-to-text decoder starts with a

speech detector, which takes in sequence of neural activity recordings of pre-selected speech-

responsive electrodes and predicts whether each timepoint belongs to speech production or resting-

state. The output of the speech detector was used to identify speech production epochs, where each

epoch corresponding to the time interval of one Chinese character. Based on the decoded speech

production epochs, our tone and syllable decoders then decode tone label and syllable label from

neural signals of pre-selected tone and syllable discriminative electrodes during each epoch.

For PA1 to PA4, we identified 108,144,199, and129 speech responsive electrodes, 30,28,68, and

75 syllable discriminative electrodes and 10,12,21, and 48 tone discriminative electrodes,

respectively. For PA5, we found 118 speech responsive electrodes, 47 syllable discriminative

electrodes and 14 tone discriminative electrodes. The coverage and overlapping relationship of

these electrodes were shown in **Fig. 2a-e**.

For onset predicting, the neural activity across all speech-responsive electrodes was processed time

point by time point by an artificial neural network (ANN) containing sequentially arranged

Convolutional Neural Network (CNN) structure, a stack of Gated Recurrent Unit (GRU) layers

and a single dense (fully connected) layer, capturing both forward and backward temporal

dependencies in neural signals, which was designated for inference on dynamic temporal processes.

The dense layer projected the latent dimensions of the last GRU layer into probability space for

two event classes: speech and rest. **(Fig. 2f)** For simplify, all the hyperparameters in this step was

fixed. After that, the curve of the predicted probabilities along the dimension of time was smoothed

and binarized according to undefined smoothing window (S) and probability threshold (P_t), the

onset of each utterance was then predicted if a lasting silence states (T_{off}) before the onset and a

lasting speech state (T_{on}) after it, while slightly errors labels within an undefined error permissive

rate (**EPR**) was also allowed **(Fig. 3b)**. These five undefined hyperparameters need further tuning

through grid search for each participant.

As for tone and syllable decoder, a 1.2-second time window for syllable and 0.8-second time

window for tone of high gamma activity was processed by an ensemble of 5 pairs (10 total)

ensemble ANN models. ANNs in tone and syllable decoder share the same architecture but

different in their own hyperparameters. Within each ANN, the high gamma activity was processed

by an initial convolution with initial filter length (**FL_{ini}**), stride of convolution (**ST_{conv}**). This initial

layer was followed by undefined number (**C_{layer}**) of CNN unit[2]. Each CNN unit constituted of a

temporal convolution with undefined kernel length (**FL_{conv}**), aforementioned stride length and

dimension (**C_{dim}**), a batch normalization, ELU activating function[23], a dropout layer with dropout

rate (**D**) and maxpooling layer with max-pooling kernel length (**L_{pool}**) and max-pooling stride

(**ST_{pool}**). After that, data was processed by undefined number (**R_{layer}**) of stacked bidirectional gated

recurrent unit (GRU) layers with undefined number of dimension (**R_{dim}**) [24]. A dense layer projected

the final GRU layer into probability of syllable and tone of each of the words from the 10-syllable

set or 4-tone classes. Finally, we averaged these probability distributions from ensembled ANN

models to get the predicted syllable and tone probabilities. **(Fig. 2g)** It is worth noting that all the

aforementioned undefined hyperparameters required further tuning for each participant.

Subsequently, a language model integrates these decoded tone and syllable labels, along with prior

information of their transitional probabilities, to compute the Bayesian likelihood of entire word

sequences.

Fig 2 Electrode coverage, category and decoding model schematics

a-e.   Anatomical reconstructions of PA1-PA5 (from a to e). The locations of the ECoG electrodes were plotted with colored discs. The colors indicated the electrode categories.

Yellow: responsive electrodes; red: tone-discriminative electrodes; blue: syllable-
discriminative electrodes. Electrodes with combined feature were plotted with mixed
colors, nonresponsive electrodes were plotted as small black dot. Venn diagrams showed
the number of electrodes in each category for each participant.

f.   Speech detection model schematic. Predefined hyperparameters in ANN and their values
were shown in italic.

g.   Syllable classification model schematic. CNN unit shown in green frame while RNN unit
shown in yellow. All of the undefined hyperparameters were shown in Italic, which can be
roughly divided into time-dimension-related group and size-related group. Former group
includes initial convolution filter length (FL_{ini}), stride of convolution (ST_{conv}), filter length
of following convolutional blocks (FL_{conv}), max-pooling kernel length (L_{pool}) and max-
pooling stride (ST_{pool}). Later one including number of sequential convolutional blocks
(C_{layer}), number of layers of RNN (R_{layer}), number of filters in each convolutional process
(C_{dim}), number of dimensions in each RNN process (R_{dim}), and dropout value (D)) The tone
classification model shared the same architecture with syllable classification model but
different hyperparameters.

Independent performance of speech detector, tone decoder and syllable decoder

First, we evaluated the performance of each individual decoder module. Since these decoder

modules work in sequential order, the performance of the tone and syllable decoders would rely

on the output of the speech detector. To evaluate the independent performance of these decoder

modules, we first calculate the decoding accuracies of syllable, tone, tonal syllable, and Chinese

characters on manually aligned speech onsets rather than onsets predicted by the speech detector.

Each of the participants completed 158 to 160 sentences in the speech production task. Using

nested cross-validation, we trained the brain-to-text decoder for each participant and evaluated the

decoding performance. Among five participants, our speech detector reached an area under curve

(AUC) of 0.96 to 0.99 **(Fig. 3a)**. The tone decoder reached an accuracy of 57%±12% (mean [±

SD] classification accuracy across the 4 target tones in 5 participants, chance 25%) on manually

aligned neural signals **(Fig. 3c)**. Syllable decoder reached an accuracy of 69%±5% (mean [±SD]

classification accuracy across the 10 target syllables in 5 participants, chance 10%) on manually

aligned neural signals **(Fig. 3d)**. When multiply raw predicted probability of tone and syllable, we

acquired raw decoding accuracy of all the predicted tonal-syllables, which reaches $46\% \pm 8\%$

(mean [$\pm$SD] classification accuracy across the 40 tonal syllables on 5 participants, chance 3.0%)

at the level of tonal syllable **(Fig. 3e)**. After applying language model to calculate corresponding

Chinese words, the accuracy at the level of Chinese words reaches $87\% \pm 4\%$ (mean [$\pm$SD]

classification accuracy across the 40 Chinese words on 5 participants, chance 2.5%) **(Fig. 3f)**.

Overall decoding performance of tonal-sentences

After evaluated the independent performance, we then tested the performance of all the modules

when they were interconnected and worked in a stream. Aligned with speech onsets detected by

speech detector, tone decoder achieved an accuracy of $56\% \pm 13\%$ (mean [$\pm$SD], **Fig. 3g)**, while

syllable decoder achieved an accuracy of $64\% \pm 6\%$ (mean [$\pm$SD] , **Fig. 3h)**. Accuracy at the level

of raw tonal syllable reached $44\% \pm 7\%$ (mean [$\pm$SD], **Fig. 3i)**, while the final accuracy at the level

of Chinese words reaches $82\% \pm 4\%$ (mean [$\pm$SD], **Fig. 3j)**. These results were consistent with the

independent module performance, when actual speech onsets were manually aligned. We also

calculated the word error rate (WER) of each decoded sentence. Decoding accuracy was consistent

across participants (one way-ANOVA, $F(4, 45) = 0.65$, p=0.63), as the overall WER was $25\% \pm$

6%, $21\% \pm 5\%$, $21\% \pm 6\%$, $14\% \pm 3\%$, $18\% \pm 4\%$ (mean [$\pm$SE]) from PA1 to PA5. For each

individual sentence, WER ranged from 1% to 52%. 47.74% of all the sentences (95/199) were

decoded correctly (WER=0) **(Fig. 3k)**. There was no significant difference (Pearson's correlation,

$r = -0.03$, $P = 0.61$) between the decoding accuracy and the complexity (number of words or

phrases) of the sentence (**Fig. 3m**), suggesting that our proposed method worked for both short

and long sentences.

 Fig 3. **Evaluation of the overall neural-to-text decoding performance of the decoder.**

a.   Receiver Operating Characteristic (ROC) curves and corresponding area under curve
(AUC) of speech detectors in each participant.

b.   One example trial, in which the participant produced the sentence "他哥不理他" (His elder
brother ignores him). The raw speech sound waveform was plotted in black. The time
course of the predicted speech probability was plotted blue, while speech probability after
smoothing and binarized was plotted red and orange. Finally, the detected speech event
onsets from the neural decoder was plotted as yellow dotted vertical lines. All of the
undefined hyperparameters were shown in Italic.

c-f. Confusion matrices of c) the tone labels, d) the syllable labels, e) the tonal syllables, and f)
the words (with language model), evaluated on the test set, using manually aligned actual
speech onsets.

g-j. Confusion matrices of g) the tone labels, h) the syllable labels, i) the tonal syllables, and j)
the words (with language model), evaluated on the test set, using decoded speech onsets
from the onset decoder.

k.   The averaged word error rate (WER) of decoded sentences in 5 participants, mean [±sem],
the vertical dotted line indicated the overall averaged performance across all 5 participants.

l.   Performances of the speech detector, the tone decoder, the syllable decoder and the overall
performances of each participant (in the same color keys as panel **k**), shown by AUC of
speech-silent classifier (AUC_onset), tone accuracy (Acc_tone), syllable accuracy
(Acc_sylb), word accuracy (Acc_word) and WER respectively.

m.   The averaged WER of each individual sentence across all 5 participants, mean [±SE],
dotted line indicated the average performance across all sentences.

Robustness of the speech decoder under tonal variance in natural speech

In natural speech, the actual pitch trajectories of lexical tones often deviate from their canonical

forms, due to accent, emotions, and other contextual effect such as coarticulation and tone sandhi[25].

For example, all the patient articulated the tone of "不" in "不计得失" with a pitch trajectory more

similar to tone 2 rather than tone 4 in single syllable form or in other phrases such as "不得不",

due to the rule of tone sandhi (Fig 4a). Even the same tonal syllable with different phonological

context would result in different pitch trajectories (Fig 4b). This suggests that the underlying neural

code commanding tone articulation may also encounter great variance. Therefore, the decoding

algorithm should not only consider the stereotypical canonical monosyllable instances of lexical

tones, but also able to account for such significant variance during natural speech and robustly

decode lexical tones regardless of the variance.

First, we quantify the variance caused by tonal sentence context and tone sandhi behaviorally. We

performed tone intelligibility assessment (IA) test through which native mandarin speaking

participants listening to audio of each tonal Chinese word clipped from the natural tonal sentences

and judging the tone. We find the accuracy of the tone IA test only reached 70%±2% (mean [±SE]),

significantly lower (t-test, $t(38) = 7.38$, $p = 7.6e-9$) than behavioral performance under full natural

context (tone IA accuracy 91%±1%, mean [±SE], Fig 4c). Therefore, using contextual information

is important for listeners to overcome tonal variances in natural speech production.

Similarly, given only monosyllabic information, the tone decoder would perform suboptimal. To

show this, we adopted a baseline monosyllable decoder model previously used in Liu et al[13]. The

monosyllable decoder only took in the neural activity aligned to the current syllable utterance and

did not consider contextual syllables. In our test dataset, the monosyllable baseline decoder model

achieved an averaged tone decoding accuracy of 35%±3% (mean [±SE], Fig. 4**c**).

Finally, we tested the performance our proposed sentence decoder. We compared our tone-decoder

(without the language model) with our previous published tone decoder designed for

monosyllable[13]. Our framework (decoding accuracy 58%±9%, mean [±SE]) outperformed (t-test,

$t(30) = -4.62$, $p = 6.9×10-5$) previous monosyllable tone-decoder (decoding accuracy 32%±3%,

mean [±SE]) on tonal sentence decoding task, which suggests our framework is more robust on

decoding tone components from natural language settings with multiple and unbalanced syllables.

Furthermore, after introducing language model to our decoding framework, a tone decoding

accuracy of 93%±3% (mean [±SE]) was achieved, which significantly exceed (t-test, $t(34) = 7.12$,

$P = 3.1 \times 10\text{-}8$, **Fig. 4c**) the accuracy of monosyllable tone IA results (70%±2%, mean [±SE]), and

approximate the actual behavioral performance of native speakers under natural context (91%±

1%,). Hence, applying language model will largely eliminate the tone variance in natural language

by introducing contextual relationships, which is a promising solution of decoding tone in natural

tonal sentences accurately.

Speech decoding during non-intelligible tonal speech production

To further evaluate the robustness of our proposed decoder under different speech production

scenario, we tested if the decoder could decode from patient who did not produce intelligible

speech. In particular, PA5 completed the speech production task using whispering and the

produced tonal speech was largely non-intelligible. We first plot the Mel-spectrograms of Chinese

words clipped from whispering natural tonal sentences, finding no obvious base frequency (F0)

and consonant peak (**Fig. 4b**). Furthermore, the tone IA score of PA5 was 23%±2% (mean [±SE]),

which was significantly lower than tone IA scores of normal articulating audios (t-test, $t(28) = $ -

12.18, $p = 1.1 \times 10\text{-}12$) and within the range of chance level (**Fig. 4c**). Therefore, behaviorally PA5

was not able to produce intelligible tonal speech during the task.

We then compared the tone-decoding accuracy of our framework on both participant PA5 and

other normal articulating participant, the intended speech was consistently decoded, the average

accuracy was 93%±3% and 95%±2% (mean [±SE]) with language model, 58%±9% and 51%±

2% (mean [±SE]) with language model, no significant difference was observed (t-test, with

language model: $t(18) = 0.48$, $p = 6.4 \times 10\text{-}1$, without language model: $t(18) = -0.79$, $p = 4.4 \times 10\text{-}$

1).

Finally, tone decoding accuracy and the tone IA scores of each syllable in the 4 articulating

participants were significantly correlated (Pearson's correlation $r = 0.61$, $p = 2.9 \times 10{-5}$), indicating

our tone decoder learned from behaviorally-relevant tone-related neural features, rather than other

co-variants (**Fig. 4d**).

a

"不(not)" bu4 PA1

"不(not)" bu4 PA2

他 哥　　　　不理 (bu4li3)　　　　 他
His elder.brother does not pay.attention.to(=ignores) him.

他 其实　　不止(bu4zhi3)　　 七十
He is virtually not merely(=more than) seventy(-year-old).

哥哥　　　 不时地(bu4shi2de4)　　　 激励 他
Elder.brother sometimes not but sometimes will(=often) encourages him.

记者　　　　不得不(bu4de2bu4) 离职
To.record person(=The journalist) cannot.not.to(=have to) resign.

智者　　　 不计得失(bu2[tone sandhi]ji4de2shi1)
Wise person(=The sage) does.not.care.about.gains.and.losses.

b

ji4 PA1

ji4 PA2

记者(ji4zhe3)　　　　 不得不　　　 离职
To.record person(The journalist) cannot.not.to(=have to) resign.

这里的　　　　 塔　 是个 奇迹 (qi2ji4)
Here DE(structure aux.) pagoda is a miraculous sign(=miracle).

智者　　　 不计得失(bu2ji4de2shi1)
Wise person(=The sage) does.not.care.about.gains.and.losses.

c

sentence_tone_IA (speech) 0.91±0.01
sentence_model+LM (speech) 0.93±0.03
tone_IA (speech) 0.70±0.02
sentence_model (speech) 0.58±0.09
monosyllabic_model (speech) 0.32±0.03

P=7.6e-09 ***
P=3.1e-08 ***
P=6.9e-05 ***

Acc(mean±SE)

d

zhi1 "织"　　zhi2 "职"　　zhi3 "止"　　zhi4 "智"

e

sentence_model+LM (speech) 0.93±0.03
sentence_model+LM (whisper) 0.95±0.02
tone_IA (speech) 0.70±0.02
tone_IA (whisper) 0.23±0.02
sentence_model (speech) 0.58±0.09
sentence_model (whisper) 0.51±0.02

P=6.4e-01 ns
P=1.1e-12 ***
P=4.4e-01 ns

Acc(mean±SE)

f

R = 0.61, P_value = 2.9e-05

Acc_IA
Acc_pred

PA1 PA2 PA3 PA4 PA5

287　　**Fig 4. Evaluation of tonal decoding under natural contextual variances and whispering.**

a-b) Averaged pitch contours (mean [±SE]) of different Chinese characters of the same tonal syllables (a: bu4, also the same Chinese character "不" which represents negative meanings such as "not", b: ji4), black dots indicated time points with significant mean difference (one-way ANOVA, $p < 0.05$). The text transcriptions were shown in the bottom with the specific words highlighted in the corresponding colors. Corresponding Chinese characters, *Pinyin*, and English translation of the choosen syllables were shown in the same color as the pitch contour at the right part of the figures. In the last sentence of the subplot **a**, the tone 4 of "ji" (also shown in color) leads to the change in the tone of previous "bu", due to the rule of tone sandhi.

c) Tone decoding performances (mean [±SE]) of previous monosyllabic neural decoding model (monosyllabic_model), our sentence-based neural decoding model without language model (sentence_model), our sentence-based neural decoding model with language model (speech_sentence+LM), the accuracy of tone intelligible analysis (tone IA score) by 20 volunteers using the corresponding speech audio syllable clips (tone_IA), and speech audio of each full sentences (speech_tone_IA). Blue dotted line indicated chance level (25%); *** $p < 0.001$, t-test, two-sided.

d) The mel-spectrograms of participant (PA1) spoke aloud four tones of "zhi" (upper row), compared to the mel-spectrograms of participant (PA5) whispering four tones of "zhi" (bottom).

e) Tone decoding performances using our proposed sentence decoder without language model (sentence_model) and with language model (sentence_model + LM), and the tone IA scores (mean [±SE]) evaluated on the speech and whisper participants.

f) Scatterplot showing the correlation between of tone decoding accuracy (Acc_pred) and tone IA score (Acc_IA) of articulating participants (Pearson's correlation, $r = 0.61$, $p = 2.9×10–5$). Whispering data shown in purple, which was not included in the linear regression due to randomly distributed tone IA scores.

Universal decoding framework with predefined hyperparameters is applicable on participants with great variations

ANN-based BCI decoders often encounter model hyperparameters such as depth and width of the network, kernel size and strides, dropout rate, etc. Training these models usually require optimization of these hyperparameters for each individual subject. A key factor of the generalizability of the BCI decoder is how robust the model performance is regarding different sets of hyper-parameters across participants. To get an overall understanding of heterogeneity

across participants, we computed their best hyperparameter combinations of speech detector, tone

decoder and syllable decoder chosen by the optimization process. These hyperparameters include

smoothing window (S), the probability threshold value (P_t), the off-time threshold (T_{off}) and on-

time threshold (T_{on}), and the error permissive rate (EPR) which are related to the thresholding

utterance onsets; filter lengths (FL_{ini} for the first convolutional layer, FL_{conv} for the rest

convolutional layers, and L_{pool} for max-pooling kernel) and strides (ST_{conv} for convolutional

layers and ST_{pool} for max-pooling layers) which determined the temporal feature of neuro-decoders;

as well as depths (C_{layer} for sequential convolutional blocks and R_{layer} for stacked recurrent layers)

and widths (C_{dim} for number of filters for convolutional process, R_{dim} for number of dimensions in

each RNN process, D for dropout value) which determined the overall model architecture.. Very

few optimized hyperparameter remained the same across all participants, while most optimal

hyperparameters varied across participants with variations of age, gender, speech behaviors and

electrodes coverage **(Fig. 5a-e)**. To figure out the impact of such heterogeneity on decoding

performance in our framework, we picked the medium value of each hyperparameter and

constructed a fixed pre-defined hyperparameter set. We then applied a universal decoder (UNI) on

all the participants using this fixed pre-defined hyperparameter set. We found this universal

decoder performed similar to (pair-wise t-test,PA1: $t(9) = -0.62$, $p = 5.5 \times 10\text{-}1$, PA2: $t(9) = 0.05$, p

$= 9.6 \times 10\text{-}1$, PA3: $t(9) = -2.00$, $p = 7.6 \times 10\text{-}2$, PA4: $t(9) = 0.23$, $p = 8.3 \times 10\text{-}1$, PA5: $t(9) = -0.55$, p

$= 5.9 \times 10\text{-}1$) individually-optimized frameworks with hyperparameters optimized on individual

participants **(Fig. 5f)**. Also, the decoding performance of universal framework across participants

was stable (oneway ANOVA, $F(4, 45) = 1.11$, $p = 3.6 \times 10\text{-}1$). The UNI decoder even outperformed

four control models only contained RNN and CNN part of the framework (CNN and RNN) with

optimized hyperparameters. Mean WERs of decoding sentences through UNI remained lowest in

all participants (**Fig. 5g**). Though the advantage was not significant in each individual participant

due to relatively small sample size, it was significant after combining data of all the participants

(paired t-test, UNI with CNN, $t(98) = -3.29$, $p = 1.8 \times 10^{-3}$, UNI with RNN, $t(98) = -4.97$, $p =$

8.3×10^{-6}).

Fig 5. Evaluation of the neural decoder model hyperparameters across different

participants.

a) The optimal combinations of hyperparameters for speech detector in 5 different subjects
(colors consistent in **f** and **g**): S represents the smoothing size, P_t represents probability
threshold, T_{off} represents off-time threshold and T_{on} for on-time threshold, EPR represents
error permissive rate (detailed description of these hyperparameters see **Methods Section**.

b-c) The optimal combinations of hyperparameters for the tone decoder: **b)** FL_{ini} and FL_{conv}
represents the filter length of the initial convolutional layer and all following convolutional
layers, ST_{conv} represents for stride of all convolutional layers. L_{pool} and ST_{pool} represent for
pooling length and stride of all pooling layers; **c)** R_{layer} and R_{dim} represent numbers of layers
and hidden units of bidirectional Gated Recurrent Unit (GRU). C_{layer} and C_{dim} represent

number of convolutional-pooling blocks and number of filters in each convolutional layer.
D represents dropout value of each drop-out layers.

d-e)   The optimal combinations of hyperparameters for syllable decoder, similar to **b, c**.

f)   Comparison of decoding performances on each individual participant between individually-
optimized decoders and the universal decoder with shared hyperparameters. In all the participants,
universal decoder showed no significant difference from individually-optimized decoder (pair-
wise t-test,PA1: $t(9) = -0.62$, $p = 5.5 \times 10^{-1}$, PA2: $t(9) = 0.05$, $p = 9.6 \times 10^{-1}$, PA3: $t(9) = -$
2.00, $p = 7.6 \times 10^{-2}$, PA4: $t(9) = 0.23$, $p = 8.3 \times 10^{-1}$, PA5: $t(9) = -0.55$, $p = 5.9 \times 10^{-1}$).

g)   Comparison of decoding performances on each individual participant between universal
frameworks (UNI) and customized control frameworks with hyperparameters optimized.
In all the participants, UNI show lower WER than control models. In PA1, PA2 and PA4,
these is significance difference (pair-wise t-test, PA1_UNI with PA1_RNN: $t(9) = -3.38$, p
$= 8.1 \times 10^{-3}$, PA2_UNI with PA2_RNN: $t(9) = -7.00$, $p = 6.4 \times 10^{-5}$, PA2_UNI with
PA2_CNN: $t(9) = -2.33$, $p = 4.5 \times 10^{-2}$, PA4_UNI with PA4_CNN: $t(9) = -2.44$, $p = 3.7 \times 10^{-2}$
^{2})between decoding performances of UNI and control models.

Discussion

In this study, we present a brain-to-text framework capable of decoding natural tonal sentences

from high-density ECoG recordings. We adopted a modular approach to delineate speech onset,

base syllables, lexical tones, and leveraged contextual information through Bayesian likelihood

and the Viterbi algorithm to enhance the decoding process. For natural speech, our proposed

method achieved a tone decoding accuracy of 93%, similar to the behavioral performance of native

speakers. The overall word error rate of decoded natural speech was as low as 14% in the best

participant. Notably, we proposed a generalized spatiotemporal decoding framework for syllable

and tone decoders. The robustness of our framework was evident across diverse participant profiles,

including variations in gender, age, education, pronunciation behaviors, and electrode coverage,

indicating that our model hyperparameters possess a high degree of generalizability. Significantly,

the framework's standardization of hyperparameters negates the need for extensive individual

optimization, a step forward in practical application and scalability. Furthermore, our system

adeptly managed the inherent language heterogeneity encountered in Mandarin, effectively

handling the variances introduced by tone sandhi, regional dialects and individual speech patterns.

Our decoder even showed robust performance in whispering conditions. These results underscore

the potential for clinical applications in aiding patients with anarthria and broadening the

communicative efficiency of BCIs.

This work extends the scope of ECoG-based speech brain-computer interface to natural speech of

tonal languages. The past decade has witnessed significant breakthroughs in speech decoding and

brain-computer interfaces using intracranial neural recordings. Previous works have also used

ECoG to record local field potential directly from the sensorimotor cortex responsible for speech

production. These works diverge in their decoding targets: some directly decode neural activity

into speech sound or acoustics like spectrogram[2,26,27]; others map neural activity into discrete

linguistic units such as words or phonemes[5,10,28]. Here we adopted a brain-to-text framework

similar to the latter strategy where neural activity is first decoded into discrete syllables and lexical

tones. Although directly decoding speech sound allows for continuous and infinite speech output,

the quality of reconstructed speech is limited by the noisy neural signal. On the other hand,

decoding into a finite set of syllables and tones extracts the invariant information from the noisy

neural recordings. Furthermore, for cases like whispering or even completely covert speech, there

is no ground truth of explicit speech output. As a result, brain-to-text may be feasible to such silent

speech cases.

Our work underscores the importance of ventral sensory-motor cortex (vSMC) in speech

production and decoding, particularly for tonal languages. Similar to our previous work[13], we show

that tonal speech production can be reliably decoded from neural activity in vSMC. Previous

intracranial neurophysiology studies have investigated the spatiotemporal coding of the

articulatory movements responsible of pitch control and phonetics[20-22]. A theoretical foundation of

these studies is that there exist spatially distinct and distributed neural populations in the vSMC,

representing different articulatory gestures corresponding to phoneme and pitch articulation. High-

density ECoG recordings have proven to reliably cover the distributed network and dissociate these

fine-grained neural coding[13,29].

Our results demonstrate the excellent efficacy of our proposed light-weighted models in decoding

articulatory movements, which is in line with a recent discovery that shallow feedforward

networks achieve better performance on motor control than deeper and complex ones[30].

Articulatory movement is innervated via motor nerves which locates only one or two (considering

inhibitory interneurons) synapses downstreaming the large pyramidal neurons (corticonuclear tract)

originated from the motor cortex[31]. Based on intracranial neural recordings of higher signal-noise

ratio (SNR), it is quite reasonable that light-weighted ANN is capable enough to replace the signal-

processing function of such a few layers of synapses (including the lateral connections within the

layers of cortex) [32,33]. In our UNI frameworks, the numbers of trainable parameters in speech

detectors, tone decoders and syllable decoders range from 2.3M to 6.7M. Such light-weighted

frameworks not only showed less sensitivity to variations in hyperparameters, but also achieved

better performance when trained on very limited amount of training data[34]. Such frameworks also

reduce the responding-time and energy-consumption of computational infrastructures, which is a

promising candidate for practical neuroprosthetic systems.

Our framework also provides insights into critical design considerations essential for speech BCI

models. Previous studies of speech BCI typically relied on extensive hyperparameter optimization

for individual participants who undergo chronic implantation[5,9] . Such decoding models may not

be directly generalizable across different patients, resulting in repeated hyperparameters

optimizing procedures for each individual. In contrast, our study reveals the feasibility of a

universal, hyperparameter-optimization-free framework to five individuals, demonstrating its

robustness across a spectrum of ages, genders, educational backgrounds, pronunciation habits, and

variations in brain electrode coverage. Furthermore, as oppose to prior work where specific CNN

and Recurrent Neural Network (RNN) models were designed for tone and syllable decoding

respectively[13], we proposed a unified CNN-RNN framework for both the tone and the syllable

decoders in this study. Our discovery further validates that this combined CNN-RNN model

achieved better decoding performance compared with baseline frameworks that employ only one

of these network types. The benefits of our combined approach cannot be replicated through

hyperparameter optimization alone. Our research highlights the potential for developing a broadly

applicable, hyperparameter-independent framework for neural decoding. Although our universal

framework has yielded stable performance across five distinct participants, future works remain to

be done to consolidate its generalizability in patients with anarthria, across different Chinese

dialects, and potentially other tonal languages.

This brain-to-text framework represents a pioneering effort in language BCI, designed to decode

the full spectrum of Mandarin characters. Mandarin's linguistic complexity is reflected in its use

of over 6,000 commonly utilized characters, each a single syllable word. Yet, within this vast

lexicon, there are only 416 unique segmental combinations of consonants and vowels. These

unique combinations, combined with suprasegmental pitch features (4 different lexical tones),

define 1664 unique tonal syllables[35]. Although there are some important phonetic features to the

distinction standard 4 lexical tones such as turning point and ΔF0, amplitude, and speaker F0

range[36]. Other factors that determine the pitch contour in Chinese include the prosodic structure of

the language, the interaction between syntax and phonology, and paralinguistic factors such as

speech rate and tempo[18]. These factors can influence the pitch contour and contribute to the overall

tonal patterns in Chinese, confusing native listeners listening to audio of each syllable clipped from

natural sentences. Such bias obviously added challenges to speech BCI decoding tone exclusively

from clips of neural signals while producing each syllable in natural sentences. The present

decoding strategy inherently integrates the critical tonal features of Mandarin, effectively handling

the variances introduced by tone sandhi, regional dialects and individual speech patterns, which

are paramount for accurate speech communication, offering advantages over phoneme-level

decoding. Besides, the current findings also highlight a pivotal insight: the decoding performance

is not hindered by the length or complexity of the sentences, indicating the scalability of our

framework for broader applications and more general settings in tonal language communication.

Also, Mandarin characters are single syllable words usually consisted of only two or three

phonemes, which is far less discriminative than most English. For example, "ji" versus "qi", or

"zhi" versus "shi", as demonstrated in our study[2]. This structural intricacy of Mandarin, with its

concise phonemic diversity, renders the phoneme-level decoding strategies used in recent speech

BCI studies for non-tonal languages ineffective[7,8]. In response, our framework targets the decoding

of Mandarin speech at the mono-syllable word level, aligning more closely with the language's

inherent structure and providing a practical blueprint for decoding its entirety—potentially

expanding our current focus from the most frequently used 4×10 tonal syllables to all 4×416 tonal

syllables.

In addition to the established use of high-density ECoG in speech decoding, various neural

recording techniques offer distinct advantages in terms of coverage and temporal resolution.

Examples include the Utah array[9,37], stereoelectroencephalography (SEEG) [38], and neuropixels[39,40].

When choosing among these methods, a crucial consideration involves striking a balance between

obtaining high-resolution neural signals, such as investigating fine-grained spiking properties of

multiple single units or microcircuits underlying speech production within a limited area of the

cortex[9,40], and achieving broad coverage of cortical networks, such as collecting neural signals

across the entire vSMC, which depicts a comprehensive view of neurodynamics of the functional

regions[21,22,29]. Future works remain to be done to investigate the decoding capabilities of natural

tonal languages using signals of varying coverage and resolution scales. This entails identifying

the optimal trade-off point where high decoding performance aligns with decoding robustness

across patients with high heterogeneity.

Acknowledgements

Dr. Junfeng Lu is supported by STl 2030-Major Projects (2022ZD0212300) and the National
Natural Science Foundation of China General Program (32371146). Dr. Yuanning Li is supported
by the National Natural Science Foundation of China General Program (32371154) and Shanghai
Pujiang Program (22PJ1410500). Dr. Jinsong Wu receives funding from Innovation Program of
Shanghai Municipal Education Commission (2023ZKZD13) and National Social Science Fund of
China Major Program (No. 22&ZD299).

Competing interests

497 The authors report no competing interests.

Data availability

Data relevant to this study are accessible from the authors under restricted access according to our
clinical trial protocol, which enables us to share de-identified information with researchers from
other institutions but prohibits us from making it publicly available. Access can be granted upon
reasonable request. Any data provided must be kept confidential and cannot be shared with others
unless approval is obtained. To protect the participants' anonymity, any information that could
identify him or her will not be part of the shared data. Source data and code to recreate the figures
in the manuscript will be publicly released with code upon publication of the manuscript.

Code availability

507 Code and source data to replicate the main findings of this study can be found on GitHub at
508 https://github.com/yuanningli/tonal_BCI_decoding.

Author contributions

J.L. and Y.Li. conceived and supervised the project. J.L., Y.Li., D.Z., Y.Liu., Z.Z., and S.L.
designed the experiment. J.L, D.Z., Y.Q., and Z.Z. collected the data. D.Z., H.Z., X.H. finished
the phonetic and phonological transcription. Y.Li., D.Z. designed the neural network. Y.Li., Z.W.,

D.Z., and W.L. designed the language model. D.Z. and Z.W. analyzed the data. J.L., Y.Li., L.C.,
K.X., and D.Z., interpreted the data. D.Z., Z.W., Y.Li., and J.L. wrote and revised the manuscript.
All authors reviewed and approved the manuscript.

Methods

Participants

A total of five participants (a 41-year-old female, a 44-year-old female, a 54-year-old male, a 46-

year-old male and a 30-year-old female) participated in this study. They were all patients with

eloquent brain tumors who underwent awake surgery as part of normal clinical routine. Two 128

high-density electrode arrays were temporarily placed onto the lateral surface of the brain to

collect the neural signals, and the participants were instructed to perform the speech tasks. All

participants are native Mandarin speakers. An experienced neurosurgeon performed the grid

placement, and the location of grid was determined based on the exposure and avoiding tumor.

The protocol was approved by the Huashan Hospital Institutional Review Board of Fudan

University (HIRB, KY2019-538). All participants gave their written, informed consent prior to

the surgery.

Design of the sentence corpus

To have a representative set of phonological features in Mandarin and maximize the

representativeness of our speech task, we selected the top 10 most frequently used open syllables

with monophthong, which cover the pronunciation of nearly 25.9% of all Chinese characters[41].

Using these 10 syllables, we obtained 40 distinct Chinese characters with 4 lexical tones and

constructed 29 Chinese words and phrases from these 40 characters. Finally, 10 sentences were

constructed with these 29 phrases, which eventually consisted the sentence corpus used in our

decoding task.

The 10 syllables chosen for this work is:

1. 'shi', /ʂɚ/

2. 'de', /tɤ/

3. 'ji', /tɕi/

4. 'li', /li/

5. 'bu', /pu/

6. 'ge', /kɤ/

7. 'qi', /tɕʰi/

8. 'zhe', /tʂɤ/

9. 'ta', /tʰa/

10. 'zhi' /tʂɚ/

The 40 Chinese characters used in this work and their corresponding tonal syllables (five-level tone marks):

1. 失: shi55

2. 十: shi35

3. 时: shi35

4. 实: shi35

5. 是: shi51

6. 的: de

7. 地: de

8. 得: de35

9. 机: ji55

10. 激: ji55

11. 极: ji35

12. 记: ji51

13. 计: ji51

14. 迹: ji51

15. 离: li35

16. 里: li214

17. 理: li214

18. 励: li51

19. 荔: li51

20. 不: bu35/bu51

21. 布: bu51

22. 哥: ge55

23. 搁: ge55

24. 个: ge51

25. 七: qi55

26. 奇: qi35

27. 其: qi35

28. 起: qi214

29. 契: qi51

30. 折: zhe35

31. 者: zhe214

32. 这: zhe51

33. 他: ta55

34. 塔: ta214

35. 织: zhi55

36. 枝: zhi55

37. 职: zhi35

38. 止: zhi214

39. 置: zhi51

40. 智: zhi51

*to simplify the decoding process, we use T1 (-) to denote 55, T2 (/) to denote 35, T3 (\/) to

denote 214, and T4(\) to denote 51. The neutral tone syllables "的:de" and "地:de" were

marked as T1 or T4 according to the actual pronunciation of each individual patient.

The 29-Chinese phrases used in this work (with translation in English)：

1. 智者 sage

2. 记者 journalist

3. 荔枝 lichee

4. 七折起 thirty-precent off

5. 他 him/he

6. 他的 his

7. 他哥 his brother

8. 哥哥 elder brother

9. 不时地 often

10. 激励 encourage

11. 极其 extremely

12. 机智 smart

13. 织布机 loom

14. 这里的 here

15. 是 is

16. 的 DE (structure auxiliary)

17. 塔 pagoda

18. 不理 ignore

19. 是个 is a/an

20. 奇迹 miracle

21. 不计得失 do not care about gains and losses (Chinese Idiom)

22. 不得不 have to

23. 离职 resign

24. 搁置 shelve

25. 这个 this

26. 契机 opportunity

27. 其实 actually

28. 不止 more than

29. 七十 seventy

The 10 sentences used in this work:

1.   他哥不理他。

Tā   gē   bù   lǐ   tā

his   elder.brother   not   pay.attention.to   him

'His elder brother ignores him.'

2. 他的荔枝七折起。

Tā   de   lìzhī   qīzhé   qǐ

his   DE   lichee   30.percent.off   at.least

'His lichee is at least 30-percent off.'

3. 记者不得不离职。

Jìzhě   bùdébù   lízhí

to.record.person   cannot.not.to   resign

637   'The journalist has to resign.'

638  4. 他其实不止七十。

639   Tā  qíshí    bùzhǐ    qīshí

640   he  virtually  not.merely  seventy

641   'He is virtually more than seventy(-year-old).'

642  5. 哥哥不时地激励他。

643   Gēge   bùshíde         jīlì   tā

644   elder.brother  sometimes.not.but.sometimes will   encourage  him

645   'The elder brother often encourages him.'

646  6. 他极其机智。

647   Tā  jíqí    jīzhì

648   he  extremely  smart

649   'He is extremely smart.'

650  7. 织布机是这里的。

651   Zhībùjī   shì  zhèlǐ  de

652   loom    is  here  DE

653   'The loom belongs here.'

654  8. 这里的塔是个奇迹。

655   Zhèlǐ  de   tǎ    shì  gè  qíjì

656   here  DE  pagoda  is  a  miraculous.sign

657   'The pagoda here is a miracle.'

9. 智者不计得失。

Zhìzhě   bújìdéshī

wise.person   do.not.care.about.gains.and.losses

'The sage does not care about gains and losses.'

10. 搁置这个契机。

Gēzhì zhègè qìjī

shelve this   opportunity

'Shelve this opportunity

Task design

Participants were guided by sequential visual cues to produce one of the 10 sentences consisted of 5-8 Chinese characters from a corpus of 10 base syllables and 40 Chinese characters with varied tones (**Fig. 1a**). Within each trial, the participant was instructed to produce all 10 sentences once. These sentences were presented in a random order. Ideally, each participant produced 160 sentences (4 blocks × 4 trials/block × 10 sentences/trial), which yielded approximately 30 repetitions per tonal syllable. But not all participant completed the entire reading task (158-160 sentences were completed).

Each participant was guided by visual cues to perform block tasks. Each block started with a black cross at the center of white background on the screen, which lasted for 30 seconds. After that, the cross turned grey for 3 seconds, and one of the sentences in the sentence set was shown in the middle of the screen in grey text. With the individual Chinese characters turning black for 1.2 seconds in a sequential order from the beginning to the end of the sentence, the participant was instructed to pronounce the sentence in a relatively uniform speed following these go cues.

The inter-sentence time interval and the inter-trial interval were both 3 seconds.

The first four participants (PA1-4) performed the speech task articulating, while the last

participants (PA5) performed the speech task whispering. We synchronized audio recordings

with ECoG recordings by utilizing a mounted microphone concurrently. We collected two types

of blocks of the sentence task: first 3 optimization blocks (Trial 1-12, containing 118-120

sentences in total for each patient) and one evaluating block (Trial 13-16, containing 38-40

sentences for each patient).

Data acquisition and signal processing

For each participant, two 128-channel electrode grids were placed by an experienced

neurosurgeon. The anatomical positions to place the grids were chosen based on clinical exposure

and avoidance of the tumor. During the tasks, electrocorticography and audio sound were

simultaneously recorded using the Tucker-Davis Technologies ECoG system, at sampling rates of

3052 Hz and 24414 Hz, repectively. To exclude bad channels with artifacts or excessive noise,

ECoG signals on each channel were visually and quantitatively inspected. High-gamma (70-150

Hz) frequency component was extracted via Hilbert transform after ECoG signals got down-

sampled to 400 Hz[5,13].

Phonetic and phonological transcription

Transcriptions of the audio recordings, encompassing monosyllabic Chinese character, syllable,

and tone labels, were manually annotated by a native speaker at the syllable level using Praat

(Version 6.1.01, https://www.fon.hum.uva.nl/praat/) to ensure fidelity to the participants' actual

vocalizations [5,13]. Unexpected voicing unrelated to language task (such as communication with

clinicians) was excluded from samples used in training models.

Computational modeling infrastructure

The training and testing of the decoding models were performed offline using cluster of multiple

NVIDIA GPUs.

Data splitting

We splitted the data for speech detector and the syllable/tone decoder model testing from electrode

selection and hyperparameter searching. For responsive and discriminant electrode selection and

hyperparameter optimization, only the optimization blocks were used, which contain Trial 1-12

with each trial consists of randomly arranged 10 sentences. The evaluation block contains

remaining Trial 13-16.

During the optimization stage of the speech detector model, we used a six-fold nested cross

validation (CV) and each fold consisted of 2 trials. At evaluation stage, we used a similar cross

validation process, which leaves each trial in evaluation block for testing model, while the other

15 trials for training and validating. For speech detector models, we used 10% of non-testing data

as validation set to perform early-stopping, while the left 90% for training, in each CV runs (**Fig.**

S1A&B). For syllable/tone decoder model, we trained 5 (optimization stage) or 10 (evaluation

stage) sub-models in each CV runs, with different potions of data performing early-stopping while

left for training. The final model used for evaluation was an ensemble of 5 or 10 sub models. And

the overall decoding performance was evaluated by averaging the test performance in all the CV

runs (**Fig. S1C&D**).

Speech-responsive electrodes

Speech-responsive electrodes were identified using two-sample t-test. Specifically, each time point

in the [-400 ms, 800 ms] time window relative to the consonant onsets in each word was tested

against the [-1800ms, -400ms] baseline time window before the onset of each sentence. If the

results were significant (P < 0.01, Bonferroni corrected for the total number of electrodes and all

times points) in 40 consecutive time points (100 ms), the electrode would eventually be marked as

speech-responsive.

• **Tone discriminant electrodes**

To pinpoint electrodes exhibiting discriminative characteristics among lexical tones, we aligned

the high-gamma responses with the onsets of individual syllables again. Subsequently, we

employed a one-way ANOVA to assess the potential differences in mean high-gamma responses

across the four Mandarin tones. The time window for the average response spanned from -500 ms

to 500 ms relative to the onset, encompassing a total of 400 time points. Significant time points

were identified using a two-sided threshold of $P < 0.05$, with Bonferroni correction applied for

both the total number of electrodes and time points[13]. To account for electrodes with multiple peaks

of high-gamma activity discriminant for tone decoding, we set the following criterion: if there was

a continuous 200ms time window in which more than half of the time points were significant, the

electrode would be marked as tone-discriminant.

• **Syllable discriminant electrodes**

Similar to tone discriminant electrodes, the syllable discriminant electrodes were defined using

one-way ANOVA. We tested whether the mean high-gamma responses of the ten syllables were

significantly different. The time window for the average response spanned from -500 ms to 500

ms relative to the onset, encompassing a total of 400 time points. The significant time points were

determined via aforementioned criterion. Similarly, if there were a 200ms time window in which

more than half of the time points were significant, the electrode would be marked as syllable-

discriminant.

• **Cortical surface reconstruction and electrodes visualization**

Electrodes on each individual brain were marked on preoperative T1 MRI in BrainLab®

neuronavigation system, which were double-checked by a neurosurgeon via intra-operative

photos[13]. The reconstruction of cerebral surface, anatomical labeling and plotting were performed

via Freesurfer and customized python codes as previously reported[42].

Decoding framework

We built different neural network modules of speech detector, tone decoder and syllable decoder

to decode speech onsets and offsets, syllable labels and tone labels from the neural activity,

respectively. Inspired by previously published decoding models such as the EEGNet[43,44], our

decoders had separable CNN layers extracting within- and cross-electrodes spatiotemporal

features, followed by GRU layers extracting sequential information. Finally, similar to previous

brain-to-text works in non-tonal languages[5,9,10,37], we also used a natural language model and a

Viterbi decoder to combine the sequential outputs of the tone and syllable decoders and generate

the entire sentence using maximum a posteriori probability **(Fig. 1b)**.

Speech utterance detection model (speech detector)

The speech utterance detection model processed each time point of neural activity on speech

responsive electrodes using the time window spanning from 0.25 second before the time point to

0.25 seconds after the timepoint. The speech/silent state of each time point was decoded based on

the time-windowed neural activity.

We used the Torch 1.13.1+cu117 Python package to create and train the event classification

model[45]. The event classification architecture was a CNN structure followed by a stack of three

GRU layers with a latent dimension size of 256 and a dropout of 0.5 applied at each layer.

The initial CNN structure contains an 1D convolutional layer with a kernel size (FL_{ini}) of 3 and

a stride(ST_{conv}) of 1 followed by a Leaky ReLU activation function to introduce non-linearity,

and a max-pooling layer with kernel size (L_{pool}) of 2 for temporal downsampling[46]. The initial

processing, which involves convolution and pooling, enhances the model's ability to efficiently

extract local features from the input data. Subsequently, recurrent layers are incorporated to

maintain an internal state over time and assimilate new individual time samples of input data,

making them ideal for analyzing temporally dynamic processes. Additionally, the bidirectional

nature of the Gated Recurrent Unit (GRU) enables the model to grasp both forward and

backward temporal dependencies in the ECoG data, making it a fitting choice for event

classification tasks requiring a comprehensive understanding of sequential context. Following

the GRUs, we implemented a fully connected layer that projects the output of the last layer to

probabilities associated with two target events: rest and speech. During training, the model is

optimized to minimize weighted crossentrophy. The weighted crossentrophy loss was calculated

using the ratio of the number of all the speech time points and the number of all the rest time

points, to offset the bias caused by imbalanced samples. The batch size is 1024 and an Adam

optimizer was used with a learning rate of 0.001. The training process stops after the validation

loss no longer decreases for 10 epochs or after 50 epochs, ensuring that the model has

sufficiently learned the underlying patterns in the data but has not yet overfitted. A schematic

depiction of this architecture is given in **Fig. 2f**.

During testing, the neural network predicted probabilities for each speech event label (rest, speech)

given the input neural data. To convert these predicted probabilities into the time stamps of speech

onsets, thresholding of predicted speech probabilities is needed. A sliding window of smoothing

size (S) was used to smooth the decoded probability timecourse. Next, a probability threshold (P_t)

was applied to smooth probabilities to binarized values (with a value of 1 for speech and 0

otherwise). We then sliced these binarized values by applying time thresholds for both a minimum

continuous duration of silent period before the predicted onset, and a minimum duration of

continuous speech period after the predicted onset (off-time threshold (T_{off}) and on-time threshold

(T_{on})). Detailed examples of thresholding process see **Fig. 3b**.

But the required continuous state is not strict, we set an error permissive rate (***EPR***) to allow a

small portion of timepoints with incorrectly predicted speech event labels presented during both

continuous silent period before the predicted onset as well as the speech period after the predicted

onset. Besides, we will not predict two or more onsets within 0.5s, since normal speaking rate of

our task do not allow such short interval and this update in algorithm speed up the iteration process.

In all, this process of obtaining onset events from the predicted probabilities was parameterized by

five thresholding hyperparameters: the size of the smoothing window (S), the probability threshold

value (P_t), the off-time threshold (T_{off}) and on-time threshold (T_{on}), and the error permissive rate

(***EPR***). Hyperparameter optimization was performed to eventually determine the exact values for

these parameters for the evaluation stage.

Tone decoder

For each speech utterance onset that was detected or manually aligned, tone decoder computed

tone likelihood by processing the neural activity in tone- discriminant electrodes spanning from

0.2 second before to 0.6 seconds after the detected onset of speech.

The tone decoder consists of ten ensemble neural networks with the same hyper-parameters but

different validation sets and training sets (see **Fig. S1D**). The input was high gamma ECoG data

array shaped $N \times T$, N is the number of tone-discriminated electrodes, while $T = 320,$ which is

calculated by the time duration (0.8seconds) multiplies downsampled ECoG frequency (400 Hz).

Each network among 10 networks consists of the following stages:

- **Stage 1**

In the first stage, one-layer 2D convolution with the kernel size (FL_{ini}, N) and a stride of (ST_{conv},

0), followed by a batch normalization layer (momentum=0.1, affine=True, and eps=1e-5) applied

to the output of the spatial convolution. After an Exponential Linear Unit (ELU) activation

function. Max-pooling was then performed along the temporal axis with a kernel size of (L_{pool}, **1**)

and a stride of (ST_{pool}, **1**). During training, we applied a dropout layer a dropout value of D in the

end of each CNN block for regularization to prevent overfitting.

- **Stage 2**

In the second stage, C_{layer} convolutional pool blocks were applied after the aforementioned pooling

layer in series, each consisting of a dropout layer, a convolutional layer with kernel size (FL_{conv},

1) and a stride of (ST_{conv}, **1**), batch normalization, ELU activation, and max-pooling identical with

aforementioned ones. These blocks further processed and extracted features from the data. During

the first two stages, the filter number was set equal to C_{dim}.

- **Stage 3**

In the last stage, the output from the last convolutional pool block was fed into a stack of R_{layer}

bidirectional Gated Recurrent Unit (GRU) layers. Each GRU layer has R_{dim} hidden units. The final

hidden state of the last GRU layer was passed through a fully connected (dense) layer which project

to 10 output units, representing the number of syllable classes for classification. **(Fig. 2g)**.

The model was optimized to minimize crossentrophy loss using a batch size of 8 and an Adam

optimizer with a learning rate of 0.0005. The training process stoped after the validation loss no

longer decreases for 50 epochs. The weighted crossentrophy loss was calculated in the similar

same way as speech detector to offset the bias caused by imbalanced samples.

Syllable decoder

For each speech onset that was detected, the syllable decoder computed syllable likelihood by

processing the neural activity in syllable- discriminant electrodes spanning from 0.4 second before

to 0.8 seconds after the detected onset of speech utterance. The structure and training process of

syllable decoder was identical with the aforementional tone decoder, the only difference between

them was the crossentrophy loss was not weighted, since the syllable is almost balanced-

distributed in the task.

Hyperparameter optimization and the universal framework

The speech detector, the tone decoder and the syllable decoder include a total of 25

hyperparameters. To find the optimal combination of these hyperparameters, we used the

hyperopt Python package, which employs probabilistic sampling of hyperparameter

combinations during optimization[5]. Across our experimentation, we utilized three distinct types

of hyperparameter optimization procedures to fine-tune a total of 25 hyperparameters. (see **Fig. 5**

for undefined hyperparameters, their searching ranges and their optimal values in each patient).

During the optimization process, all the neural networks were tested through the six-fold (2 trials

per fold) cross-validation.

- **Speech detection optimization**

We used this procedure to optimize the size of the smoothing window (S), the probability

threshold value (P_t), the off-time threshold (T_{off}) and on-time threshold (T_{on}), and the error

permissive rate (EPR). These hyperparameters were not related to the training of the ANN

models. The predicted time points of speech onsets were derived from the available speech

probabilities through the current combination of thresholding hyperparameters during each

iteration of the optimization procedure. Subsequently, speech detection accuracy (Acc) was

calculated to quantify the performance of the current combination of hyperparameter values. For

timepoint of real onsets, we use $\hat{X}$ to represent the index of time points within 0.25s range of real

onsets ($t_i^*, i \in [1, \dots, n]$). For time point of predicted onsets, we use $\tilde{X}$ to represent the index of

time points within 0.25s range of real onsets. Then, we calculated the Acc of $\hat{X}$ and $\tilde{X}$. The

formal expression of this objective function was illustrated through following equations:

$$
866 \quad \hat{X}[t] = \begin{cases} 0, & \text{others} \\ 1, & \text{if } \min_{i \in [1,\dots,n]} |t - t_i^*| < 0.25 \end{cases}
$$

$$
867 \quad \tilde{X}[t] = \begin{cases} 0, & \text{others} \\ 1, & \text{if } \min_{i \in [1,\dots,n]} |t - t_i^*| < 0.25 \end{cases}
$$

$$
868 \quad \mathbb{1}(x) = \begin{cases} 0, & x \neq 0 \\ 1, & x = 0 \end{cases}
$$

$$
869 \quad Acc = \frac{\sum_t \mathbb{1}\left[\hat{X}[t] - \tilde{X}[t]\right]}{\sum t}
$$

Acc was calculated to qualify the performance of the speech detector with each hyperparameter

value combination. During the optimization process of one model, 500 hyperparameter value

combinations were evaluated.

Once the most optimized combination of hyperparameters was defined, we calculated the

predicted onset time list for all the 12 trials via six-fold prediction, we compared them with the

ground truth of onset of the 12 trials. If one onset time point in predicted list falls within 0.25s

range of real onsets, the labels (including tone, syllable and Chinese characteristic) belongs to the

manually aligned onset will be given to the predicted time point, which participated in the

following hyperparameter optimization. For those time points cannot match with any real onset

time points, no labels will be given and this part of the data will not participate in the following

hyperparameter optimization. The similar match process will be performed in the evaluating

stage, calculating confusion matrix for syllable, tone and word on the bases of onset detection.

Because some real onset time points do not match with any detected onset time point, the

number of syllables and tones that actually used in calculating confusion matrices of decoding

performance after automated onset detection is less than the number of onsets detected.

• **Tone and Syllable decoder optimization**

We used this procedure to optimize ten hyperparameters for both tone decoder and syllable

decoder. These hyperparameters can be divided into two major groups according to their

properties.

The first group includes initial convolution filter length (FL_{ini}), stride of convolution (ST_{conv}), filter

length of following convolutional blocks (FL_{conv}), max-pooling kernel length (L_{pool}), max-pooling

stride (ST_{pool}), which are five hyperparameters related to the time dimension.

The second group includes the number of sequential convolutional blocks (C_{layer}), number of layers

of RNN (R_{layer}), number of filters in each convolutional process (C_{dim}), number of dimensions in

each RNN process (R_{dim}), and dropout value (D), which are five hyperparameters related to model

architectures and sizes.

We performed model testing on manually-aligned-onset dataset and the dataset generated from

predicted onsets by the previously optimized speech detector. And the final loss is the average

value of loss on both datasets, in order to improve the model's robustness when countering

automatedly aligned neural signals in our final evaluation. Each optimization evaluated 500

different combinations of hyperparameter values. We used the same cross-entropy loss

functions to calculate the loss during the iteration.

• **The universal framework**

The universal framework shares a predefined set of hyperparameters when testing on all 5

participants. We used the median value of each optimized hyperparameters among 5 participants

as the predefined value of hyperparameters.

Conversion from tonal syllables to Chinese words

Many Chinese characters are homophones that share the same pronunciations (including syllable

and tone), which prevented us from directly generating Chinese sentences using decoded tonal

syllables. To eventually decoding sentences consists of actual Chinese characters rather than

sequences of tonal syllables, we designed a natural language model that computed the next-

character transition probabilities given the previous Chinese character in a sequence. We first

divided the sentences into the aforementioned 29 words and phrases consisting of 1 to 4 Chinese

characters. We trained this model on a collection of sentences from the CCL corpus[47] that included

transferring pairs (transfers) between those words from the 29-word set. After that, we used a

Viterbi decoder to determine the most likely sequence of words given the predicted tonal syllable

probabilities from the tone decoder and syllable decoder, as well as the word-sequence

probabilities from the natural language model[8]. With the incorporation of the language model, the

Viterbi decoder was capable of projecting sets of probability (likelihoods) of tonal syllable to exact

Chinese characters, which eventually decoded sentences from neural activity.

Language model

• **Collection of the corpus**

We used CCL corpus from Peking University[47] to distill training dataset for our domain-specific

language model. We first measure the number of transfers between each two phrases (the counts

of the previous phrase transferred to the first word of the next phrase in the whole CCL corpus).

Due to the inequality of Chinese language, we set a cut-off of 512 counts, and then performed a

ninth root for normalization. Since not all the transfers in our task appeared in CCL corpus, we

also incorporate the transfer probability of our own task corpus into our language model.

• **Model fitting**

We extracted all n-grams with n ∈ {1, 2, 3, 4}c from each phrase in our task corpus. An n-gram

refers a word lengthen n Chinese characters. For example, the n-grams (represented as tuples)

extracted from the longest phrases "不计得失" in this approach would be:

1. (不)

2. (不计)

3. (不计得)

4. (不计得失)

Then we expanded our transfer probability matrix into n-grams. We added the number of

transferring from q_{i-1} (such as (不计)) to q_i (such as (不计得)). Except for full phrases, n-grams

as partial components of phrases can only transfer from q_{i-1} to q_i . The calculation of number of

each transfering from a full phrase to the beginning of next phrases is aformentioned.

• **Hidden Markov Model (HMM) and Viterbi decoding**

In this study, we employed a Hidden Markov Model (HMM) for neural activity and speech

modeling similar to that used in previous research[5]. This model interprets neural activity within

each time window at index i as observed states y_i and treats the word spoken during this

period w_i, along with its context c_i, as hidden states q_i. The model assumed first-order Markov

property and the current hidden state was fully characterized by $p(q_i|q_{i-1}, y_i)$. The transition

probabilities, $p(q_i|q_{i-1})$, which represents the probability of transitioning from the n-gram at

index $i-1$ to the n-gram at index i, can be calculated by word counting from the corpus.

Viterbi decoder[5,48,49] was used to identify the most probable sequence of hidden states from the

observed neural activities. The algorithm used dynamic programming and considered the

probabilities of transitioning between hidden states and the likelihoods of observed states. In the

process of identifying the optimal hidden-state sequence, the algorithm calculated the

probabilities of different potential sequences of hidden states. Each potential sequence, or Viterbi

path, was defined by a unique sequence of hidden states (specific word sequence) and its

corresponding probability based on the neural signals observed.

Evaluation

• **Evaluation of independent decoding performances via Receiver Operating**
Characteristic (ROC) and Confusion Matrices

To evaluate the performance of our speech detector, we computed the Area Under the Curve

(AUC) of the Receiver Operating Characteristic (ROC) curve for each participant. To evaluate the

tone decoder and syllable decoder, we computed the classification accuracy and plotted the

confusion matrix, based on both the predicted and the manually aligned speech onsets. We also

calculated the classification accuracy and plotted confusion matrices of tonal-syllables and

Chinese characters, on both the predicted and the manually aligned speech onsets, in order to

further assess the capacity of the entire decoding system.

• **Evaluation of overall decoding performance via Word Error Rates (WERs)**

To evaluate the overall performance of our neural-to-text decoder, we analyzed the decoded

sentences using Word Error Rates (WERs) between the target and decoded sentences for each

sentence. WER is a widely-used metric for evaluating predicted word sequences[5,50,51]. WERs of

each decoded sentence in the evaluating blocks were calculated.

• **Comparison with published tone decoder**

To further validate the complexity of tone of sentences compared with tone of single syllable, we

applied our previously published monosyllabic tone decoder on tone decoding in sentence task. It

is a sequential CNN-LSTM structure to generate the syllable label based on manually aligned

neural activity when participants produce eight syllables "ma (tone1), ma (tone2), ma (tone3), ma

(tone4), mi (tone1), mi (tone2), mi (tone3), mi (tone4)" [13]. **(Fig. S2)**

• **Tone intelligibility assessment (IA)**

Crowdsourcing-based listening tests are conventional for evaluating the quality of outputs in

natural language processing[13]. To further validate the variance of lexical tones in natural sentences

compared with the canonical tones of single syllables, we extracted the audio clips of each syllable

utterance in the evaluation blocks of each participant, using the same timespan as the neural

decoder. We shuffled the sequence clips by syllables to avoid any possible of leakage of semantic

information. Evaluators were instructed to listen to the audio clip and then choose from the options

(four lexical tones) which tone they had just heard[13]. For sentence tone IA, we extracted the audio

clip of each sentence each patient pronounced in evaluation blocks. The evaluators listen to the

audio of the entire sentence and then choose from the options for each syllable in the sentence. 20

evaluators (native Mandarin speakers) were instructed to listen to the isolated audio clips and to

decide which tone they had just heard. For sentence tone IA, we extracted the audio clip of each

sentence each patient pronounced in evaluation blocks. The evaluators were instructed to listen to

the audio of the entire and then choose from the options which tone they had just heard for each

syllable in the sentence. We recruited 20 native Mandarin speakers from the Medical School of

Fudan University, which do not know the purpose of this test before the evaluation. The tone IA

score was defined as the average accuracy of evaluators' judgement.

993
$$IA = 1 - \frac{T}{A}$$

Where T is the number of error tone choices; A is the number of total tests[13].

• **Comparison with baseline models**

We evaluated the performance of our models and compared it against several baselines. The

baseline models include (1) CNN models, which do not contain RNN structure, all the other parts

remain identical with original optimized models. (2) RNN models, which do not contain CNN

structure, all the other parts remain identical with original optimized models (**Fig. S3**). WERs of

decoded sentences were calculated to evaluate the performance of these baselines.

• **Electrode contributions (saliences)**

To quantify the contribution of each ECoG electrode to the brain-to-text decoding, we performed

the electrode salience analysis . In particular, we backpropagated the final loss function of each

ANN module to each electrode in the input layer by computing the gradient. The magnitude of this

gradient would quantify the amount of influence that a unit perturbation in each electrode would

have on the final output of the neural network. We computed the Euclidean norm across time and

across evaluation blocks of the resulting gradient values for each electrode. Finally, we normalized

each set of electrode saliences by calculating their root mean square values **(Fig. S4)**.

Supplementary Information

Daohan Zhang[1,2,3#], Zhenjie Wang[4#], Youkun Qian[1,2,3#], Zehao Zhao[1,2,3], Yan Liu[1,2,3], Xiaotao Hao[1,2,3], Wanxin Li[1,2,3], Shuo Lu[5], Honglin Zhu[6], Luyao Chen[7], Kunyu Xu[8], Yuanning Li[4,9*], Junfeng Lu[1,2,3,8,10*]

Author affiliations:

[1]Department of Neurosurgery, Huashan Hospital, Shanghai Medical College, Fudan University, Shanghai 200040, China

[2]Shanghai Key Laboratory of Brain Function Restoration and Neural Regeneration, Shanghai 200040, China

[3]National Center for Neurological Disorders, Huashan Hospital, Shanghai Medical College, Fudan University, Shanghai 200040, China

[4]School of Biomedical Engineering, ShanghaiTech University, Shanghai 201210, China

[5]Department of Chinese Language and Literature, Sun Yat-sen University, Guangzhou 510080, China

[6]Faculty of Life Sciences and Medicine, King's College London, London SE1 1UL, UK

[7]School of International Chinese Language Education, Beijing Normal University, Beijing 100875, China

[8]Institute of Modern Languages and Linguistics, Fudan University, Shanghai 200433, China

[9]State Key Laboratory of Advanced Medical Materials and Devices, ShanghaiTech University, Shanghai 201210, China

[10]MOE Frontiers Center for Brain Science, Huashan Hospital, Fudan University, Shanghai 200040, China

[#]These authors contributed equally to this work.

[*]Corresponding authors: Junfeng Lu (junfeng_lu@fudan.edu.cn), Yuanning Li (liyn2@shanghaitech.edu.cn)

1040

Fig. S1. Schematic depiction of data organization

A. During the optimization stage of the speech detector model, we used a six-fold nested cross validation and each fold consisted of 2 trials, while 10% of data in each trial of the training set

1044   were separated as validation set in order to performing early-stopping.

1045  B. During the evaluation stage of the speech detector model, we used a similar cross validation.
1046   Still, 10% of data in each training trial were separated as validation set in order to performing
1047   early-stopping.

1048  C. During the optimization stage of the syllable/tone decoder model, we used a six-fold nested
1049   cross validation and each fold consisted of 2 trials. In each fold, we trained 5 sub-models with
1050   different potions of data performing early-stopping while left for training. The
1051   training/validation/test split was 4:1:1.

1052  D. During the evaluation stage of the syllable/tone decoder model, we used a similar cross
1053   validation process. In each fold, we trained 10 sub-models with different potions of data
1054   performing early-stopping while left for training. The training/validation/test split was 12:3:1.

1055 **Fig. S2. Schematic of control models for speech detector and tone/syllable decoder.**

1056  A. CNN baseline for speech detector, which do not contain RNN structures, and all the other parts
1057   remain unchanged.

1058  B. CNN baseline for tone/syllable decoder, which do not contain RNN structures, and all the other
1059   parts, including optimized hyperparameters, remain unchanged.

1060  C. RNN baseline for speech detector, which do not contain CNN structures, and all the other parts
1061   remain unchanged.

1062  D. RNN baseline for tone/syllable decoder, which do not contain CNN structures, and all the other
1063   parts, including optimized hyperparameters, remain unchanged.

1064

1065

1066

1067

1068

1069

1070

1071

Fig. S3. Schematic of our previously published tone decoder which successfully decoded tone from
intracranial neural signals while participants articulate isolated monosyllables of four target tones.

We applied our previously published monosyllabic tone decoder on tone decoding in sentence task. It is a
sequential CNN-LSTM structure to generate the syllable label based on manually aligned neural activity
when participants produce eight syllables "ma (tone1), ma (tone2), ma (tone3), ma (tone4), mi (tone1), mi
(tone2), mi (tone3), mi (tone4)"[13].

Fig. S4. Participants' brains reconstruction overlaid with the locations of the placed electrodes and their relative contribution of each selected electrodes in decoding onset/syllable and tone.

A-E shown PA1, PA2, PA3, PA4 and PA5. Left part shown speech responsive electrodes in yellow shadows, middle shown syllable discriminative electrodes in blue shadows, while right shown tone discriminative electrodes in red shadows. Radius of shadows around electrodes shown contribution normalized root mean square (RMS), with a scale shown at the upper left of each subplot. The colors of the electrodes themselves represent whether they are speech responsive or syllable/tone discriminative, which is the same as **Fig. 2a-e**.

References

Gilakjani, A. P. & Ahmadi, M. R. A study of factors affecting EFL learners' English listening comprehension and the strategies for improvement. (2011).

Anumanchipalli, G. K., Chartier, J. & Chang, E. F. Speech synthesis from neural decoding of spoken sentences. *Nature* **568**, 493-498, doi:10.1038/s41586-019-1119-1 (2019).

Moses, D. A., Leonard, M. K., Makin, J. G. & Chang, E. F. Real-time decoding of question-and-answer speech dialogue using human cortical activity. *Nat Commun* **10**, 3096, doi:10.1038/s41467-019-10994-4 (2019).

Makin, J. G., Moses, D. A. & Chang, E. F. Machine translation of cortical activity to text with an encoder-decoder framework. *Nat Neurosci* **23**, 575-582, doi:10.1038/s41593-020-0608-8 (2020).

Moses, D. A. *et al.* Neuroprosthesis for Decoding Speech in a Paralyzed Person with Anarthria. *N Engl J Med* **385**, 217-227, doi:10.1056/NEJMoa2027540 (2021).

Angrick, M. *et al.* Speech synthesis from ECoG using densely connected 3D convolutional neural networks. *J Neural Eng* **16**, 036019, doi:10.1088/1741-2552/ab0c59 (2019).

Willett, F. R. *et al.* A high-performance speech neuroprosthesis. *Nature*, 1-6 (2023).

Metzger, S. L. *et al.* A high-performance neuroprosthesis for speech decoding and avatar control. *Nature*, 1-10 (2023).

Willett, F. R. *et al.* A high-performance speech neuroprosthesis. *Nature* **620**, 1031-1036 (2023).

Metzger, S. L. *et al.* A high-performance neuroprosthesis for speech decoding and avatar control. *Nature* **620**, 1037-1046 (2023).

Komeiji, S. *et al.* in *ICASSP 2022-2022 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP).* 1311-1315 (IEEE).

Koch Fager, S., Fried-Oken, M., Jakobs, T. & Beukelman, D. R. New and emerging access technologies for adults with complex communication needs and severe motor impairments: State of the science. *Augmentative and Alternative Communication* **35**, 13-25 (2019).

Liu, Y. *et al.* Decoding and synthesizing tonal language speech from brain activity. *Science Advances* **9**, eadh0478 (2023).

Yip, M. *Tone*. (Cambridge University Press, 2002).

Dryer, M. S. & Haspelmath, M. The world atlas of language structures online. (2013).

Fons-ant, H. & Naessentialr, S. A model for the synthesis of pitch contours of connected speech. *annual report of the engineering research institute* **23** (1969).

Fujisaki, H., Hirose, K., Hallé, P. A. & Lei, H. in *ICSLP.* 841-844.

Chen, M. Y. An overview of tone sandhi phenomena across Chinese dialects. *Journal of Chinese Linguistics Monograph Series*, 111-156 (1991).

Ho, D.-a. The characteristics of Mandarin dialects. *The Sino-Tibetan languages*, 126-130 (2003).

20   Dichter, B. K., Breshears, J. D., Leonard, M. K. & Chang, E. F. The Control of Vocal Pitch in Human
Laryngeal Motor Cortex. *Cell* **174**, 21-31 e29, doi:10.1016/j.cell.2018.05.016 (2018).
21   Lu, J. *et al.* Neural control of lexical tone production in human laryngeal motor cortex. *Nature*
Communications **14**, 6917 (2023).
22   Bouchard, K. E., Mesgarani, N., Johnson, K. & Chang, E. F. Functional organization of human
sensorimotor cortex for speech articulation. *Nature* **495**, 327-332, doi:10.1038/nature11911
(2013).
23   Qiumei, Z., Dan, T. & Fenghua, W. Improved convolutional neural network based on fast
exponentially linear unit activation function. *Ieee Access* **7**, 151359-151367 (2019).
24   Zargar, S. Introduction to sequence learning models: RNN, LSTM, GRU. *Department of*
Mechanical and Aerospace Engineering, North Carolina State University, Raleigh, North Carolina
27606 (2021).
25   Chen, M. Y. *Tone sandhi: Patterns across Chinese dialects*. Vol. 92 (Cambridge University Press,
2000).
26   Pasley, B. N. *et al.* Reconstructing speech from human auditory cortex. *PLoS biology* **10**,
e1001251 (2012).
27   Martin, S. *et al.* Decoding spectrotemporal features of overt and covert speech from the human
cortex. *Frontiers in neuroengineering* **7**, 14 (2014).
28   Herff, C. *et al.* Generating natural, intelligible speech from brain activity in motor, premotor, and
inferior frontal cortices. *Frontiers in neuroscience* **13**, 1267 (2019).
29   Duraivel, S. *et al.* High-resolution neural recordings improve the accuracy of speech decoding.
Nature Communications **14**, 6938 (2023).
30   Willsey, M. S. *et al.* Real-time brain-machine interface in non-human primates achieves high-
velocity prosthetic finger movements using a shallow feedforward neural network decoder. *Nat*
Commun **13**, 6899, doi:10.1038/s41467-022-34452-w (2022).
31   Davidoff, M., Robert A. The pyramidal tract. *Neurology* **40**, 332-332 (1990).
32   Yazdan-Shahmorad, A., Kipke, D. R. & Lehmkuhle, M. J. High gamma power in ECoG reflects
cortical electrical stimulation effects on unit activity in layers V/VI. *Journal of neural engineering*
10, 066002 (2013).
33   Sanes, J. N. & Donoghue, J. P. Plasticity and primary motor cortex. *Annual review of*
neuroscience **23**, 393-415 (2000).
34   Myung, I. J. The importance of complexity in model selection. *Journal of mathematical*
psychology **44**, 190-204 (2000).
35   McCawley, J. D. in *Tone*   113-131 (Elsevier, 1978).
36   Jongman, A., Wang, Y., Moore, C. B. & Sereno, J. A. *Perception and production of Mandarin*
Chinese tones. (na, 2006).
37   Willett, F. R., Avansino, D. T., Hochberg, L. R., Henderson, J. M. & Shenoy, K. V. High-
performance brain-to-text communication via handwriting. *Nature* **593**, 249-254,
doi:10.1038/s41586-021-03506-2 (2021).
38   Cuisenier, P. *et al.* Relationship between direct cortical stimulation and induced high-frequency
activity for language mapping during SEEG recording. *J Neurosurg* **134**, 1251-1261,
doi:10.3171/2020.2.JNS192751 (2020).
39   Leonard, M. K. *et al.* Large-scale single-neuron speech sound encoding across the depth of
human cortex. *Nature*, 1-10 (2023).
40   Coughlin, B. *et al.* Modified Neuropixels probes for recording human neurophysiology in the
operating room. *Nature Protocols* **18**, 2927-2953 (2023).
41   Da, J. in *Proceedings of the fourth international conference on new technologies in teaching and*
learning Chinese. 501-511 (Citeseer).

42   Hamilton, L. S., Chang, D. L., Lee, M. B. & Chang, E. F. Semi-automated anatomical labeling and
1172   inter-subject warping of high-density intracranial recording electrodes in electrocorticography.
1173   *Frontiers in Neuroinformatics* **11**, 62 (2017).
1174   43   Lawhern, V. J. *et al.* EEGNet: a compact convolutional neural network for EEG-based brain–
1175   computer interfaces. *Journal of neural engineering* **15**, 056013 (2018).
1176   44   Makin, J. G., Moses, D. A. & Chang, E. F. Machine translation of cortical activity to text with an
1177   encoder–decoder framework. *Nature Neuroscience* **23**, 575-582, doi:10.1038/s41593-020-0608-
1178   8 (2020).
1179   45   Paszke, A. *et al.* Pytorch: An imperative style, high-performance deep learning library. *Advances*
1180   *in neural information processing systems* **32** (2019).
1181   46   Maas, A. L., Hannun, A. Y. & Ng, A. Y. in *Proc. icml.* 3 (Atlanta, Georgia, USA).
1182   47   Zhan, W., Guo, R., Chang, B., Chen, Y. & Chen, L. in *Corpus Linguistics.* 71-86.
1183   48   Fink, G. A. *Markov models for pattern recognition: from theory to applications*. (Springer Science
1184   & Business Media, 2014).
1185   49   Theodoridis, S. & Koutroumbas, K. *Pattern recognition*. (Elsevier, 2006).
1186   50   Bates, M. Models of natural language understanding. *Proceedings of the National Academy of*
1187   *Sciences* **92**, 9977-9982 (1995).
1188   51   Wang, Y.-Y., Acero, A. & Chelba, C. in *2003 IEEE workshop on automatic speech recognition and*
1189   *understanding (IEEE Cat. No. 03EX721).* 577-582 (IEEE).

1190