A brain-to-text framework of decoding natural tonal sentences

Daohan Zhang[1,2,3#], Zhenjie Wang[4#], Youkun Qian[1,2,3#], Zehao Zhao[1,2,3], Yan Liu[1,2,3], Xiaotao Hao[1,2,3], Wanxin Li[1,2,3], Shuo Lu[5], Honglin Zhu[6], Luyao Chen[7], Kunyu Xu[8], Yuanning Li[4,9*], Jinsong Wu[1,2,3*], Junfeng Lu[1,2,3,8,10*]

Author affiliations:

[1]Department of Neurosurgery, Huashan Hospital, Shanghai Medical College, Fudan University, Shanghai 200040, China

[2]Shanghai Key Laboratory of Brain Function Restoration and Neural Regeneration, Shanghai 200040, China

[3]National Center for Neurological Disorders, Huashan Hospital, Shanghai Medical College, Fudan University, Shanghai 200040, China

[4]School of Biomedical Engineering, ShanghaiTech University, Shanghai 201210, China

[5]Department of Chinese Language and Literature, Sun Yat-sen University, Guangzhou 510080, China

[6]Faculty of Life Sciences and Medicine, King's College London, London SE1 1UL, UK

[7]School of International Chinese Language Education, Beijing Normal University, Beijing 100875, China

[8]Institute of Modern Languages and Linguistics, Fudan University, Shanghai 200433, China

[9]State Key Laboratory of Advanced Medical Materials and Devices, ShanghaiTech University, Shanghai 201210, China

[10]MOE Frontiers Center for Brain Science, Huashan Hospital, Fudan University, Shanghai 200040, China

[#] These authors contributed equally to this work.

[*] Corresponding authors: Junfeng Lu (junfeng_lu@fudan.edu.cn), Jinsong Wu (wujinsong@huashan.org.cn), Yuanning Li (liyn2@shanghaitech.edu.cn)

Abstract

Speech brain-computer interfaces (BCIs) directly translate brain activity into speech sound and text, yet decoding tonal languages like Mandarin Chinese poses a significant, unexplored challenge. Despite successful cases in non-tonal languages, the complexities of Mandarin, with its distinct syllabic structures and pivotal lexical information conveyed through tonal nuances, present challenges in BCI decoding. Here we designed a brain-to-text framework to decode Mandarin tonal sentences from invasive neural recordings. Our modular approach dissects speech onset, base syllables, and lexical tones, integrating them with contextual information through Bayesian likelihood and the Viterbi decoder. The results demonstrate accurate tone and syllable decoding under variances in continuous naturalistic speech production, surpassing previous intracranial Mandarin tonal syllable decoders in decoding accuracy. We also verified the robustness of our decoding framework and showed that the model hyperparameters can be generalized across participants of varied gender, age, education backgrounds, pronunciation behaviors, and coverage of electrodes. Our pilot study shed lights on the feasibility of more generalizable brain-to-text decoding of natural tonal sentences from patients with high heterogeneities.

Key words

Electrocorticography (ECoG); Brain-Computer Interface (BCI); Tonal language; Natural speech; Neural Networks

Introduction

Sentence is the basic language unit embodies our construal of representational meaning and interpersonal meaning, which constitutes the basis for daily communication[1]. Several recent studies have shown the feasibility of decoding or synthesis sentences of non-tonal languages, such as English[2-10] and Japanese[11], using intracranial neural recordings, such as electrocorticography (ECoG). These studies have primarily relied on decoding the spatiotemporal neural patterns associated with articulatory movements—such as those of the lips, tongue, and larynx—in the ventral sensorimotor cortex during intended speech production. These advances not only provide new methods in anarthria treatment[12] but also increase the communication efficiency of speech brain-computer-interface (BCI).

However, decoding tonal sentences is still a largely-unexplored work. More than 60% of the languages in the world are tonal[13], with approximately 2 billion people speaking tonal languages, including most Sino-Tibetan languages and the entire Tai-Kadai family[14]. The distinct feature of these languages is the use of pitch to distinguish lexical and grammatical meaning. While prior research has investigated decoding stereotypical instances of lexical tones from neural activity for monosyllabic speech[15], decoding continuous tonal sentences is still a challenging issue. Unlike the relatively stable acoustic cues in canonical forms, natural speech introduces substantial variability in tone components. According to Fujisaki model, these components, typically represented by base frequency (F0) contours, encompass base frequency, phrase variations, and accent components[16,17]. Furthermore, the influence of tone sandhi—alterations in a morpheme's tone due to syntactic context—adds an additional layer of complexity[18]. Altogether, these variances make decoding tonal sentences more complicated than both non-tonal sentences and isolated tonal syllables.

Besides, existing invasive language BCI usually reported success in individual cases, usually with

intense hyperparameter optimizing[5,9,10]. Few studies have tested the replication or generalization

of the decoding framework. It remains uncertain whether the same set of model design

hyperparameters—such as the number of convolution and recurrent blocks, hidden variables per

layer, and onset detection thresholds—will generalize across different subjects. Consequently,

verifying the generalizability of these published frameworks, especially when applied to patients

exhibiting high heterogeneity, remains elusive. In clinical settings, different patients need to

restore speech function via speech BCI have varied pronunciation behaviors, which is especially

obvious among tonal languages such as Mandarin Chinese. Mandarin speakers, influenced by

regional dialects such as Northern, Jianghuai, and subgroups like Wu-Tai, Shanghainese-

influenced, Northeastern Mandarin, demonstrate distinct tonal and syllabic variations[19]. Though

sharing the same written form of Chinese word, speakers of these mandarin branches have distinct

pronunciation behaviors on both tones and syllables. While these distinct pronunciation behaviors

or preferences do not affect speakers' daily communication, they add significant challenges to the

decoding task. In addition to the variance in pronunciation behaviors, the inherent variations in

language-functional cortical areas also contribute to the inter-subject variances. It is impossible

for invasive devices to collect identical neural signals from different patients even if the placement

of invasive electrodes is stringently controlled. Whether and to what extent these bias from both

language behaviors and varied neural signals will affect the robustness of language decoding

framework remain unknown. This uncertainty challenges the eventual generalization of speech

BCI across patients with high heterogeneity.

In this study, we aim to decode Mandarin tonal sentences from invasive neural recordings using

high-density ECoG. We used different neural network modules targeting functionally distinct

neural populations in speech-related brain areas. These modules detected the onsets of the

utterance of each individual Chinese character and then decode tone labels and syllable labels in

parallel, mirroring the inherit parallel coding of the articulation process in tonal languages[20-22].

Subsequently, a language model was used to calculate the Bayesian likelihood of the entire

sentence from the probability distribution of tonal syllable sequences, integrating the contextual

and prior information (**Fig.1**). Moreover, we established a versatile framework using a set of

standardized hyperparameters, eliminating additional needs for hyperparameter optimization, and

assessed its potential for generalization by testing across multiple patients. This approach decoded

Mandarin tonal sentences across diverse patient profiles without specific hyperparameter

adjustments.

Fig 1 Schematic overview of the brain-to-text decoder for natural speech of a tonal language.

a. Schematic overview of the tonal speech production task. Each participant was guided by a visual cue to produce one of the ten sentences. Each trial began with a fixation cross at the center of the screen for 3 seconds, and the sentence was shown in the middle of the screen in grey text. With each word turning black for 1.2 seconds consecutively from the beginning to the end of the sentence, the participant was instructed to pronounce the sentence following these go cues, the pace of the speech was not strictly aligned with the visual cues.

b. During the experiment, neural activity from speech-related cortex was recorded using implanted high-density electrocorticography array when the participant was instructed to read sentences consisted of words from a predefined vocabulary set of 40 words. The preprocessed neural signals from responsive electrodes were sampled by sliding window and was sent to the speech detection module (speech detector) to detect the onsets of words. The peri-onset neural activity within a fixed time window was used to compute the base syllable probability (across 10 possible syllables) and lexical tone probability (across 4 tones) of the word via a tone decoder and a syllable decoder respectively. A Viterbi decoding algorithm used these probabilities in conjunction with word-sequence probabilities from a pre-trained natural language model to decode the most likely sentence given the current neural activity.

Results

In this study, we recorded the neural activity of five native Mandarin-speaking participants who underwent awake surgery to treat brain tumors. Each participant was guided by sequential visual cues to produce 10 sentences consisted of 5-8 Chinese characters from a corpus of 40 Chinese characters with varied tones **(Fig. 1a)**. Among 5 participants, PA1-4 completed the speech production task using normal articulating, while PA5 completed the speech production task using whispering. Participants' brain activity was recorded by temporally placed high-density ECoG grids. Subsequently, we assessed the efficacy of our proposed brain-to-text speech decoder across these 5 participants.

Decoder overview

Our brain-to-text decoder comprises interconnected modules: a speech detector, tone decoder,

syllable decoder, and a language model, functioning in a sequential stream. To decode Mandarin

tonal sentences from high-density ECoG neural recordings, our brain-to-text decoder starts with a

speech detector, which takes in sequence of neural activity recordings of pre-selected speech-

responsive electrodes and predicts whether each timepoint belongs to speech production or resting-

state. The output of the speech detector was used to identify speech production epochs, where each

epoch corresponding to the time interval of one Chinese character. Based on the decoded speech

production epochs, our tone and syllable decoders then decode tone label and syllable label from

neural signals of pre-selected tone and syllable discriminative electrodes during each epoch.

For PA1 to PA4, we identified 108,144,199, and129 speech responsive electrodes, 30,28,68, and

75 syllable discriminative electrodes and 10,12,21, and 48 tone discriminative electrodes,

respectively. For PA5, we found 118 speech responsive electrodes, 47 syllable discriminative

electrodes and 14 tone discriminative electrodes. The coverage and overlapping relationship of

these electrodes were shown in **Fig. 2a-e**.

For onset predicting, the high gamma activity across all speech-responsive electrodes was

processed time point by time point by an artificial neural network (ANN) consisting of

Convolutional Neural Network (CNN) structure following a stack of Gated Recurrent Unit (GRU)

layers and a single dense (fully connected) layer, capturing both forward and backward temporal

dependencies in neural signals, which was designated for inference on dynamic temporal processes.

The dense layer projected the latent dimensions of the last GRU layer into probability space for

two event classes: speech and rest. **(Fig. 2f)** For simplify, all the hyperparameters in this step was

fixed. After that, the curve of the predicted probabilities along the dimension of time was smoothed

and binarized according to undefined smoothing window (S) and probability threshold (P_t), the

onset of each utterance was then predicted if a lasting silence states (T_{off}) before the onset and a

lasting speech state (T_{on}) after it, while slightly errors labels within an undefined error permissive

rate (**EPR**) was also allowed **(Fig. 3b)**. These five undefined hyperparameters need further tuning

through grid search for each participant.

As for tone and syllable decoder, a 1.2-second time window for syllable and 0.8-second time

window for tone of high gamma activity was processed by an ensemble of 5 pairs (10 total)

ensemble ANN models. ANNs in tone and syllable decoder share the same architecture but

different in their own hyperparameters. Within each ANN, the high gamma activity was processed

by an initial convolution with initial filter length (FL_{ini}), stride of convolution (ST_{conv}). This initial

layer was followed by undefined number (C_{layer}) of CNN unit[12]. Each CNN unit constituted of

a temporal convolution with undefined kernel length (FL_{conv}), aforementioned stride length and

dimension (C_{dim}), a batch normalization, ELU activating function[23], a dropout layer with dropout

rate (**D**) and maxpooling layer with max-pooling kernel length (L_{pool}) and max-pooling stride

(ST_{pool}). After that, data was processed by undefined number (R_{layer}) of stacked bidirectional gated

recurrent unit (GRU) layers with undefined number of dimension (R_{dim}) [24]. A dense layer projected

the latent dimension from the final GRU layer into probability space, which contained the

probability of syllable and tone of each of the words from the 10-syllable set or 4-tone classes,

being the feature of target word during the speech production attempt associated with the neural

time window. The 10 or 4 probability distributions from the ensembled ANN models were

averaged together to obtain the final vector of predicted word probabilities. **(Fig. 2g)** It is worth

noting that all the aforementioned undefined hyperparameters required further tuning for each

participant.

Subsequently, a language model integrates these decoded tone and syllable labels, along with prior

information of their transitional probabilities, to compute the Bayesian likelihood of entire word

sequences.

154   **Fig 2 Electrode coverage, category and decoding model schematics**

155   a-e.   Anatomical reconstructions of PA1-PA5 (from a to e). The locations of the ECoG
156   electrodes were plotted with colored discs. The colors indicated the electrode categories.

Yellow: responsive electrodes; red: tone-discriminative electrodes; blue: syllable-
discriminative electrodes. Electrodes with combined feature were plotted with mixed
colors, nonresponsive electrodes were plotted as small black dot. Venn diagrams showed
the number of electrodes in each category for each participant.

f.   Speech detection model schematic. Predefined hyperparameters in ANN and their values
were shown in italic.

g.   Syllable classification model schematic. CNN unit shown in green frame while RNN unit
shown in yellow. All of the undefined hyperparameters were shown in Italic, which can be
roughly divided into time-dimension-related group and size-related group. Former group
includes initial convolution filter length (FL_{ini}), stride of convolution (ST_{conv}), filter length
of following convolutional blocks (FL_{conv}), max-pooling kernel length (L_{pool}) and max-
pooling stride (ST_{pool}). Later one including number of sequential convolutional blocks
(C_{layer}), number of layers of RNN (R_{layer}), number of filters in each convolutional process
(C_{dim}), number of dimensions in each RNN process (R_{dim}), and dropout value (D)) The tone
classification model shared the same architecture with syllable classification model but
different hyperparameters.

Independent performance of speech detector, tone decoder and syllable decoder

First, we evaluated the performance of each individual decoder module. Since these decoder

modules work in sequential order, the performance of the tone and syllable decoders would rely

on the output of the speech detector. To evaluate the independent performance of these decoder

modules, we first calculate the decoding accuracies of syllable, tone, tonal syllable, and Chinese

characters on manually aligned speech onsets rather than onsets predicted by the speech detector.

Each of the participants completed 158 to 160 sentences in the speech production task. Using

nested cross-validation, we trained the brain-to-text decoder for each participant and evaluated the

decoding performance. Among five participants, our speech detector reached an area under curve

(AUC) of 0.96 to 0.99 **(Fig. 3a)**. The tone decoder reached an accuracy of 57%±12% (mean [±

SD] classification accuracy across the 4 target tones in 5 participants, chance 25%) on manually

aligned neural signals **(Fig. 3c)**. Syllable decoder reached an accuracy of 69%±5% (mean [±SD]

classification accuracy across the 10 target syllables in 5 participants, chance 10%) on manually

aligned neural signals **(Fig. 3d)**. When multiply raw predicted probability of tone and syllable, we

acquired raw decoding accuracy of all the predicted tonal-syllables, which reaches $46\% \pm 8\%$

(mean [$\pm$SD] classification accuracy across the 40 tonal syllables on 5 participants, chance 3.0%)

at the level of tonal syllable **(Fig. 3e)**. After applying language model to calculate corresponding

Chinese words, the accuracy at the level of Chinese words reaches $87\% \pm 4\%$ (mean [$\pm$SD]

classification accuracy across the 40 Chinese words on 5 participants, chance 2.5%) **(Fig. 3f)**.

Overall decoding performance of tonal-sentences

After evaluated the independent performance, we then tested the performance of all the modules

when they were interconnected and worked in a stream. Aligned with speech onsets detected by

speech detector, tone decoder achieved an accuracy of $56\% \pm 13\%$ **(mean [$\pm$SD], Fig. 3g)**, while

syllable decoder achieved an accuracy of $64\% \pm 6\%$ **(mean [$\pm$SD] , Fig. 3h)**. Accuracy at the level

of raw tonal syllable reached $44\% \pm 7\%$ **(mean [$\pm$SD], Fig. 3i)**, while the final accuracy at the level

of Chinese words reaches $82\% \pm 4\%$ **(mean [$\pm$SD], Fig. 3j)**. These results were consistent with the

independent module performance, when actual speech onsets were manually aligned. We also

calculated the word error rate (WER) of each decoded sentence. Decoding accuracy was consistent

across participants (one way-ANOVA, $F(4, 45) = 0.65$, p=0.63), as the overall WER was $25\% \pm$

6%, $21\% \pm 5\%$, $21\% \pm 6\%$, $14\% \pm 3\%$, $18\% \pm 4\%$ (mean [$\pm$SE]) from PA1 to PA5. For each

individual sentence, WER ranged from 1% to 52%. 47.74% of all the sentences (95/199) were

decoded correctly (WER=0) **(Fig. 3k)**. There was no significant difference (Pearson's correlation,

$r = -0.03$, $P = 0.61$) between the decoding accuracy and the complexity (number of words or

phrases) of the sentence (**Fig. 3m**), suggesting that our proposed method worked for both short

and long sentences.

Fig 3. Evaluation of the overall neural-to-text decoding performance of the decoder.

a.   Receiver Operating Characteristic (ROC) curves and corresponding area under curve
(AUC) of speech detectors in each participant.

b.   One example trial, in which the participant produced the sentence "□ □ □ □ □" (His elder
brother ignores him). The raw speech sound waveform was plotted in black. The time
course of the predicted speech probability was plotted blue, while speech probability after
smoothing and binarized was plotted red and orange. Finally, the detected speech event
onsets from the neural decoder was plotted as yellow dotted vertical lines. All of the
undefined hyperparameters were shown in Italic.

c-f. Confusion matrices of c) the tone labels, d) the syllable labels, e) the tonal syllables, and f)
the words (with language model), evaluated on the test set, using manually aligned actual
speech onsets.

g-j. Confusion matrices of g) the tone labels, h) the syllable labels, i) the tonal syllables, and j)
the words (with language model), evaluated on the test set, using decoded speech onsets
from the onset decoder.

k.   The averaged word error rate (WER) of decoded sentences in 5 participants, mean [±sem],
the vertical dotted line indicated the overall averaged performance across all 5 participants.

l.   Performances of the speech detector, the tone decoder, the syllable decoder and the overall
performances of each participant (in the same color keys as panel **k**), shown by AUC of
speech-silent classifier (AUC_onset), tone accuracy (Acc_tone), syllable accuracy
(Acc_sylb), word accuracy (Acc_word) and WER respectively.

m.   The averaged WER of each individual sentence across all 5 participants, mean [±SE],
dotted line indicated the average performance across all sentences.

Robustness of the speech decoder under tonal variance in natural speech

In natural speech, the actual pitch trajectories of lexical tones often deviate from their canonical

forms, due to accent, emotions, and other contextual effect such as coarticulation and tone sandhi[25].

For example, all the patient articulated the tone of "不" in "不计得失" with a pitch trajectory more

similar to tone 2 rather than tone 4 in single syllable form or in other phrases such as "不得不",

due to the rule of tone sandhi (Fig 4a). Even the same tonal syllable with different phonological

context would result in different pitch trajectories (Fig 4b). This suggests that the underlying neural

code commanding tone articulation may also encounter great variance. Therefore, the decoding

algorithm should not only consider the stereotypical canonical monosyllable instances of lexical

tones, but also able to account for such significant variance during natural speech and robustly

decode lexical tones regardless of the variance.

First, we quantify the variance caused by tonal sentence context and tone sandhi behaviorally. We

performed tone intelligibility assessment (IA) test through which native mandarin speaking

participants listening to audio of each tonal Chinese word clipped from the natural tonal sentences

and judging the tone. We find the accuracy of the tone IA test only reached 70%±2% (mean [±SE]),

significantly lower (t-test, $t(38) = 7.38$, $p = 7.6e-9$) than behavioral performance under full natural

context (tona IA accuracy 91%±1%, mean [±SE], Fig 4c). Therefore, using contextual information

is important for listeners to overcome tonal variances in natural speech production.

Similarly, given only monosyllabic information, the tone decoder would perform suboptimal. To

show this, we adopted a baseline monosyllable decoder model previously used in Liu et al[15]. The

monosyllable decoder only took in the neural activity aligned to the current syllable utterance and

did not consider contextual syllables. In our test dataset, the monosyllable baseline decoder model

achieved an averaged tone decoding accuracy of 35%±3% (mean [±SE], Fig. 4**c**).

Finally, we tested the performance our proposed sentence decoder. We compared our tone-decoder

(without the language model) with our previous published tone decoder designed for

monosyllable[15]. Our framework (decoding accuracy 58%±9%, mean [±SE]) outperformed (t-test,

$t(30) = -4.62$, $p = 6.9×10-5$) previous monosyllable tone-decoder (decoding accuracy 32%±3%,

mean [±SE]) on tonal sentence decoding task, which suggests our framework is more robust on

decoding tone components from natural language settings with multiple and unbalanced syllables.

Furthermore, after introducing language model to our decoding framework, a tone decoding

accuracy of 93%±3% (mean [±SE]) was achieved, which significantly exceed (t-test, $t(34) = 7.12$,

$P = 3.1 \times 10\text{-}8$, **Fig. 4c**) the accuracy of monosyllable tone IA results (70%±2%, mean [±SE]), and

approximate the actual behavioral performance of native speakers under natural context (91%±

1%,). Hence, applying language model will largely eliminate the tone variance in natural language

by introducing contextual relationships, which is a promising solution of decoding tone in natural

tonal sentences accurately.

Speech decoding during non-intelligible tonal speech production

To further evaluate the robustness of our proposed decoder under different speech production

scenario, we tested if the decoder could decode from patient who did not produce intelligible

speech. In particular, PA5 completed the speech production task using whispering and the

produced tonal speech was largely non-intelligible. We first plot the Mel-spectrograms of Chinese

words clipped from whispering natural tonal sentences, finding no obvious base frequency (F0)

and consonant peak (**Fig. 4b**). Furthermore, the tone IA score of PA5 was 23%±2% (mean [±SE]),

which was significantly lower than tone IA scores of normal articulating audios (t-test, $t(28) = \text{-}$

12.18, $p = 1.1 \times 10\text{-}12$) and within the range of chance level (**Fig. 4c**). Therefore, behaviorally PA5

was not able to produce intelligible tonal speech during the task.

We then compared the tone-decoding accuracy of our framework on both participant PA5 and

other normal articulating participant, the intended speech was consistently decoded, the average

accuracy was 93%±3% and 95%±2% (mean [±SE]) with language model, 58%±9% and 51%±

2% (mean [±SE]) with language model, no significant difference was observed (t-test, with

language model: $t(18) = 0.48$, $p = 6.4 \times 10\text{-}1$, without language model: $t(18) = \text{-}0.79$, $p = 4.4 \times 10\text{-}$

1).

Finally, tone decoding accuracy and the tone IA scores of each syllable in the 4 articulating

participants were significantly correlated (Pearson's correlation $r = 0.61, p = 2.9 \times 10{-5}$), indicating

our tone decoder learned from behaviorally-relevant tone-related neural features, rather than other

co-variants (**Fig. 4d**).

a

"不(not)" bu4 PA1

"不(not)" bu4 PA2

他 哥 **不**理 (**bu4**li3) 他
His elder.brother does **not** pay.attention.to(=ignores) him.

他 其实 **不**止(**bu4**zhi3) 七十
He is virtually **not** merely(=more than) seventy(-year-old).

哥哥 **不**时地(**bu4**shi2de4) 激励 他
Elder.brother sometimes **not** but sometimes will(=often) encourages him.

记者 **不**得**不**(**bu4**de2**bu4**) 离职
To.record person(=The journalist) can**not**.**not**.to(=have to) resign.

智者 **不**计得失(**bu2[tone sandhi]**ji4de2shi1)
Wise person(=The sage) does.**not**.care.about.gains.and.losses.

b

ji4 PA1

ji4 PA2

记者(**ji4**zhe3) 不得不 离职
To.record person(The journalist) cannot.not.to(=have to) resign.

这里的 塔 是个 奇**迹** (qi2**ji4**)
Here DE(structure aux.) pagoda is a miraculous **sign**(=miracle).

智者 不**计**得失(bu2**ji4**de2shi1)
Wise person(=The sage) does.not.**care.about**.gains.and.losses.

c

d

zhi1 "织" zhi2 "职" zhi3 "止" zhi4 "智"

e

f

R = 0.61, P_value = 2.9e-05

290 **Fig 4. Evaluation of tonal decoding under natural contextual variances and whispering.**

a-b) Averaged pitch contours (mean [±SE]) of different Chinese characters of the same tonal syllables (a: bu4, also the same Chinese character "不" which represents negative meanings such as "not", b: ji4), black dots indicated time points with significant mean difference (one-way ANOVA, $p < 0.05$). The text transcriptions were shown in the bottom with the specific words highlighted in the corresponding colors. Corresponding Chinese characters, *Pinyin*, and English translation of the choosen syllables were shown in the same color as the pitch contour at the right part of the figures. In the last sentence of the subplot **a**, the tone 4 of "ji" (also shown in color) leads to the change in the tone of previous "bu", due to the rule of tone sandhi.

c) Tone decoding performances (mean [±SE]) of previous monosyllabic neural decoding model (monosyllabic_model), our sentence-based neural decoding model without language model (sentence_model), our sentence-based neural decoding model with language model (speech_sentence+LM), the accuracy of tone intelligible analysis (tone IA score) by 20 volunteers using the corresponding speech audio syllable clips (tone_IA), and speech audio of each full sentences (speech_tone_IA). Blue dotted line indicated chance level (25%); *** $p < 0.001$, t-test, two-sided.

d) The mel-spectrograms of participant (PA1) spoke aloud four tones of "zhi" (upper row), compared to the mel-spectrograms of participant (PA5) whispering four tones of "zhi" (bottom).

e) Tone decoding performances using our proposed sentence decoder without language model (sentence_model) and with language model (sentence_model + LM), and the tone IA scores (mean [±SE]) evaluated on the speech and whisper participants.

f) Scatterplot showing the correlation between of tone decoding accuracy (Acc_pred) and tone IA score (Acc_IA) of articulating participants (Pearson's correlation, $r = 0.61$, $p = 2.9 \times 10^{-5}$). Whispering data shown in purple, which was not included in the linear regression due to randomly distributed tone IA scores.

Universal decoding framework with predefined hyperparameters is applicable on participants with great variations

ANN-based BCI decoders often encounter model hyperparameters such as depth and width of the network, kernel size and strides, dropout rate, etc. Training these models usually require optimization of these hyperparameters for each individual subject. A key factor of the generalizability of the BCI decoder is how robust the model performance is regarding different sets of hyper-parameters across participants. To get an overall understanding of heterogeneity

across participants, we computed their best hyperparameter combinations of speech detector, tone

decoder and syllable decoder chosen by the optimization process. These hyperparameters include

smoothing window (S), the probability threshold value (P_t), the off-time threshold (T_{off}) and on-

time threshold (T_{on}), and the error permissive rate (EPR) which are related to the thresholding

utterrance onsets; filter lengths (FL_{ini} for the first convolutional layer, FL_{conv} for the rest

convolutional layers, and L_{pool} for max-pooling kernel) and strides (ST_{conv} for convolutional

layers and ST_{pool} for max-pooling layers) which determined the temporal feature of neuro-decoders;

as well as depths (C_{layer} for sequential convolutional blocks and R_{layer} for stacked recurrent layers)

and widths (C_{dim} for number of filters for convolutional process, R_{dim} for number of dimensions in

each RNN process, D for dropout value) which determined the overall model architecture.. Very

few optimized hyperparameter remained the same across all participants, while most optimal

hyperparameters varied across participants with variations of age, gender, speech behaviors and

electrodes coverage **(Fig. 5a-e)**. To figure out the impact of such heterogeneity on decoding

performance in our framework, we picked the medium value of each hyperparameter and

constructed a fixed pre-defined hyperparameter set. We then applied a universal decoder (UNI) on

all the participants using this fixed pre-defined hyperparameter set. We found this universal

decoder performed similar to (pair-wise t-test,PA1: $t(9) = -0.62$, $p = 5.5×10-1$, PA2: $t(9) = 0.05$, p

$= 9.6×10-1$, PA3: $t(9) = -2.00$, $p = 7.6×10-2$, PA4: $t(9) = 0.23$, $p = 8.3×10-1$, PA5: $t(9) = -0.55$, p

$= 5.9×10-1$) individually-optimized frameworks with hyperparameters optimized on individual

participants **(Fig. 5f)**. Also, the decoding performance of universal framework across participants

was stable (oneway ANOVA, $F(4, 45) = 1.11$, $p = 3.6×10-1$). The UNI decoder even outperformed

four control models only contained RNN and CNN part of the framework (CNN and RNN) with

optimized hyperparameters. Mean WERs of decoding sentences through UNI remained lowest in

all participants (**Fig. 5g**). Though the advantage was not significant in each individual participant

due to relatively small sample size, it was significant after combining data of all the participants

(paired t-test, UNI with CNN, $t(98)$ = -3.29, p = 1.8×10-3, UNI with RNN, $t(98)$ = -4.97, p =

8.3×10-6).

Fig 5. Evaluation of the neural decoder model hyperparameters across different

participants.

a)　The optimal combinations of hyperparameters for speech detector in 5 different subjects
(colors consistent in **f** and **g**): S represents the smoothing size, P_t represents probability
threshold, T_{off} represents off-time threshold and T_{on} for on-time threshold, EPR represents
error permissive rate (detailed description of these hyperparameters see **Methods Section**.

b-c)　The optimal combinations of hyperparameters for the tone decoder: **b)** FL_{ini} and FL_{conv}
represents the filter length of the initial convolutional layer and all following convolutional
layers, ST_{conv} represents for stride of all convolutional layers. L_{pool} and ST_{pool} represent for
pooling length and stride of all pooling layers; **c)** R_{layer} and R_{dim} represent numbers of layers
and hidden units of bidirectional Gated Recurrent Unit (GRU). C_{layer} and C_{dim} represent

number of convolutional-pooling blocks and number of filters in each convolutional layer.

D represents dropout value of each drop-out layers.

d-e)   The optimal combinations of hyperparameters for syllable decoder, similar to **b, c**.

f)   Comparison of decoding performances on each individual participant between individually-
optimized decoders and the universal decoder with shared hyperparameters. In all the participants,
universal decoder showed no significant difference from individually-optimized decoder (pair-
wise t-test,PA1: $t(9) = -0.62$, $p = 5.5 \times 10^{-1}$, PA2: $t(9) = 0.05$, $p = 9.6 \times 10^{-1}$, PA3: $t(9) = -$
2.00, $p = 7.6 \times 10^{-2}$, PA4: $t(9) = 0.23$, $p = 8.3 \times 10^{-1}$, PA5: $t(9) = -0.55$, $p = 5.9 \times 10^{-1}$).

g)   Comparison of decoding performances on each individual participant between universal
frameworks (UNI) and customized control frameworks with hyperparameters optimized.
In all the participants, UNI show lower WER than control models. In PA1, PA2 and PA4,
these is significance difference (pair-wise t-test, PA1_UNI with PA1_RNN: $t(9) = -3.38$, p
$= 8.1 \times 10^{-3}$, PA2_UNI with PA2_RNN: $t(9) = -7.00$, $p = 6.4 \times 10^{-5}$, PA2_UNI with
PA2_CNN: $t(9) = -2.33$, $p = 4.5 \times 10^{-2}$, PA4_UNI with PA4_CNN: $t(9) = -2.44$, $p = 3.7 \times 10^{-2}$)between decoding performances of UNI and control models.

Discussion

In this study, we present a brain-to-text framework capable of decoding natural tonal sentences

from high-density ECoG recordings. We adopted a modular approach to delineate speech onset,

base syllables, lexical tones, and leveraged contextual information through Bayesian likelihood

and the Viterbi algorithm to enhance the decoding process. For natural speech, our proposed

method achieved a tone decoding accuracy of 93%, similar to the behavioral performance of native

speakers. The overall word error rate of decoded natural speech was as low as 14% in the best

participant. Notably, we proposed a generalized spatiotemporal decoding framework for syllable

and tone decoders. The robustness of our framework was evident across diverse participant profiles,

including variations in gender, age, education, pronunciation behaviors, and electrode coverage,

indicating that our model hyperparameters possess a high degree of generalizability. Significantly,

the framework's standardization of hyperparameters negates the need for extensive individual

optimization, a step forward in practical application and scalability. Furthermore, our system

adeptly managed the inherent language heterogeneity encountered in Mandarin, effectively

handling the variances introduced by tone sandhi, regional dialects and individual speech patterns.

Our decoder even showed robust performance in whispering conditions. These results underscore

the potential for clinical applications in aiding patients with anarthria and broadening the

communicative efficiency of BCIs.

This work extends the scope of ECoG-based speech brain-computer interface to natural speech of

tonal languages. The past decade has witnessed significant breakthroughs in speech decoding and

brain-computer interfaces using intracranial neural recordings. Previous works have also used

ECoG to record local field potential directly from the sensorimotor cortex responsible for speech

production. These works diverge in their decoding targets: some directly decode neural activity

into speech sound or acoustics like spectrogram[2,26,27]; others map neural activity into discrete

linguistic units such as words or phonemes[5,10,28]. Here we adopted a brain-to-text framework

similar to the latter strategy where neural activity is first decoded into discrete syllables and lexical

tones. Although directly decoding speech sound allows for continuous and infinite speech output,

the quality of reconstructed speech is limited by the noisy neural signal. On the other hand,

decoding into a finite set of syllables and tones extracts the invariant information from the noisy

neural recordings. Furthermore, for cases like whispering or even completely covert speech, there

is no ground truth of explicit speech output. As a result, brain-to-text may be feasible to such silent

speech cases.

Our work underscores the importance of ventral sensory-motor cortex (vSMC) in speech

production and decoding, particularly for tonal languages. Similar to our previous work[15], we show

that tonal speech production can be reliably decoded from neural activity in vSMC. Previous

intracranial neurophysiology studies have investigated the spatiotemporal coding of the

articulatory movements responsible of pitch control and phonetics[20-22]. A theoretical foundation of

these studies is that there exist spatially distinct and distributed neural populations in the vSMC,

representing different articulatory gestures corresponding to phoneme and pitch articulation. High-

density ECoG recordings have proven to reliably cover the distributed network and dissociate these

fine-grained neural coding[15,29].

Our results demonstrate the excellent efficacy of our proposed light-weighted models in decoding

articulatory movements, which is in line with a recent discovery that shallow feedforward

networks achieve better performance on motor control than deeper and complex ones[30].

Articulatory movement is innervated via motor nerves which locates only one or two (considering

inhibitory interneurons) synapses downstreaming the large pyramidal neurons (corticonuclear tract)

originated from the motor cortex[31]. Based on intracranial neural recordings of higher signal-noise

ratio (SNR), it is quite reasonable that light-weighted ANN is capable enough to replace the signal-

processing function of such a few layers of synapses (including the lateral connections within the

layers of cortex) [32,33]. In our UNI frameworks, the numbers of trainable parameters in speech

detectors, tone decoders and syllable decoders range from 2.3M to 6.7M. Such light-weighted

frameworks not only showed less sensitivity to variations in hyperparameters, but also achieved

better performance when trained on very limited amount of training data[34]. Such frameworks also

reduce the responding-time and energy-consumption of computational infrastructures, which is a

promising candidate for practical neuroprosthetic systems.

Our framework also provides insights into critical design considerations essential for speech BCI

models. Previous studies of speech BCI typically relied on extensive hyperparameter optimization

for individual participants who undergo chronic implantation[5,9] . Such decoding models may not

be directly generalizable across different patients, resulting in repeated hyperparameters

optimizing procedures for each individual. In contrast, our study reveals the feasibility of a

universal, hyperparameter-optimization-free framework to five individuals, demonstrating its

robustness across a spectrum of ages, genders, educational backgrounds, pronunciation habits, and

variations in brain electrode coverage. Furthermore, as oppose to prior work where specific CNN

and Recurrent Neural Network (RNN) models were designed for tone and syllable decoding

respectively[15], we proposed a unified CNN-RNN framework for both the tone and the syllable

decoders in this study. Our discovery further validates that this combined CNN-RNN model

achieved better decoding performance compared with baseline frameworks that employ only one

of these network types. The benefits of our combined approach cannot be replicated through

hyperparameter optimization alone. Our research highlights the potential for developing a broadly

applicable, hyperparameter-independent framework for neural decoding. Although our universal

framework has yielded stable performance across five distinct participants, future works remain to

be done to consolidate its generalizability in patients with anarthria, across different Chinese

dialects, and potentially other tonal languages.

This brain-to-text framework represents a pioneering effort in language BCI, designed to decode

the full spectrum of Mandarin characters. Mandarin's linguistic complexity is reflected in its use

of over 6,000 commonly utilized characters, each a single syllable word. Yet, within this vast

lexicon, there are only 416 unique segmental combinations of consonants and vowels. These

unique combinations, combined with suprasegmental pitch features (4 different lexical tones),

define 1664 unique tonal syllables[35]. Although there are some important phonetic features to the

distinction standard 4 lexical tones such as turning point and ΔF0, amplitude, and speaker F0

range[36]. Other factors that determine the pitch contour in Chinese include the prosodic structure of

the language, the interaction between syntax and phonology, and paralinguistic factors such as

speech rate and tempo[18]. These factors can influence the pitch contour and contribute to the overall

tonal patterns in Chinese, confusing native listeners listening to audio of each syllable clipped from

natural sentences. Such bias obviously added challenges to speech BCI decoding tone exclusively

from clips of neural signals while producing each syllable in natural sentences. The present

decoding strategy inherently integrates the critical tonal features of Mandarin, effectively handling

the variances introduced by tone sandhi, regional dialects and individual speech patterns, which

are paramount for accurate speech communication, offering advantages over phoneme-level

decoding. Besides, the current findings also highlight a pivotal insight: the decoding performance

is not hindered by the length or complexity of the sentences, indicating the scalability of our

framework for broader applications and more general settings in tonal language communication.

Also, Mandarin characters are single syllable words usually consisted of only two or three

phonemes, which is far less discriminative than most English. For example, "ji" versus "qi", or

"zhi" versus "shi", as demonstrated in our study[2]. This structural intricacy of Mandarin, with its

concise phonemic diversity, renders the phoneme-level decoding strategies used in recent speech

BCI studies for non-tonal languages ineffective[7,8]. In response, our framework targets the decoding

of Mandarin speech at the mono-syllable word level, aligning more closely with the language's

inherent structure and providing a practical blueprint for decoding its entirety—potentially

expanding our current focus from the most frequently used 4×10 tonal syllables to all 4×416 tonal

syllables.

In addition to the established use of high-density ECoG in speech decoding, various neural

recording techniques offer distinct advantages in terms of coverage and temporal resolution.

Examples include the Utah array[9,37], stereoelectroencephalography (SEEG) [38], and neuropixels[39,40].

When choosing among these methods, a crucial consideration involves striking a balance between

obtaining high-resolution neural signals, such as investigating fine-grained spiking properties of

multiple single units or microcircuits underlying speech production within a limited area of the

cortex[9,40], and achieving broad coverage of cortical networks, such as collecting neural signals

across the entire vSMC, which depicts a comprehensive view of neurodynamics of the functional

regions[21,22,29]. Future works remain to be done to investigate the decoding capabilities of natural

tonal languages using signals of varying coverage and resolution scales. This entails identifying

the optimal trade-off point where high decoding performance aligns with decoding robustness

across patients with high heterogeneity.

Acknowledgements

Dr. Junfeng Lu is supported by STl 2030-Major Projects (2022ZD0212300) and the National
Natural Science Foundation of China General Program (32371146). Dr. Yuanning Li is supported
by the National Natural Science Foundation of China General Program (32371154) and Shanghai
Pujiang Program (22PJ1410500). Dr. Jinsong Wu receives funding from Innovation Program of
Shanghai Municipal Education Commission (2023ZKZD13) and National Social Science Fund of
China Major Program (No. 22&ZD299).

Competing interests

500 The authors report no competing interests.

Data availability

Data relevant to this study are accessible from the authors under restricted access according to our
clinical trial protocol, which enables us to share de-identified information with researchers from
other institutions but prohibits us from making it publicly available. Access can be granted upon
reasonable request. Any data provided must be kept confidential and cannot be shared with others
unless approval is obtained. To protect the participants' anonymity, any information that could
identify him or her will not be part of the shared data. Source data and code to recreate the figures
in the manuscript will be publicly released with code upon publication of the manuscript.

Code availability

510 Code and source data to replicate the main findings of this study can be found on GitHub at
511 https://github.com/yuanningli/tonal_BCI_decoding.

Author contributions

J.W., J.L. and Y.Li. conceived and supervised the project. J.L., Y.Li., D.Z., Y.Liu., Z.Z., and S.L.
designed the experiment. J.L, D.Z., Y.Q., and Z.Z. collected the data. D.Z., H.Z., X.H. finished
the phonetic and phonological transcription. Y.Li., D.Z. designed the neural network. Y.Li., Z.W.,

D.Z., and W.L. designed the language model. D.Z. and Z.W. analyzed the data. J.L., Y.Li., L.C.,
K.X., and D.Z., interpreted the data. D.Z., Z.W., Y.Li., J.L. and J.W. wrote and revised the
manuscript. All authors reviewed and approved the manuscript.

Methods

Participants

Five participants (a 41-year-old female, a 44-year-old female, a 54-year-old male, a 46-year-old

male and a 30-year-old female) were all patients with brain lesions who underwent awake

surgery and temporarily placed high-density, subdural electrode arrays covering the lateral

surface of the brain to collect the neural signal in speech task. All participants are native speakers

of Mandarin and perform daily communication in Mandarin without any difficulty. All protocols

approved by the Institutional Review Board of Huashan Hospital (KY2019-538), and the

conducting of research complied with all relevant ethical regulations. Participants were asked to

participate in this study only if there was clinical necessity to perform awake surgery for safe

resection of occupying lesions and protection of the eloquent area.

Design of the sentence corpus

To have a representative set of phonological features in Mandarin and maximize the

representativeness of our speech task, we selected the top 10 most frequently used open syllables

with monophthong, which cover the pronunciation of nearly 25.9% of all Chinese characters[41].

Using these 10 syllables, we obtained 40 distinct Chinese characters with 4 lexical tones and

constructed 29 Chinese words and phrases from these 40 characters. Finally, 10 sentences were

constructed with these 29 phrases, which eventually consisted the sentence corpus used in our

decoding task.

The 10 syllables chosen for this work is:

1. 'shi', /ʂɚ/

2. 'de', /tɤ/

3. 'ji', /tɕi/

4. 'li', /li/

5. 'bu', /pu/

6. 'ge', /kɤ/

7. 'qi', /tɕʰi/

8. 'zhe', /ʈʂɤ/

9. 'ta', /tʰa/

10. 'zhi' /ʈʂɚ/

The 40 Chinese characters used in this work and their corresponding tonal syllables (five-level

tone marks):

1. 失: shi55

2. 十: shi35

3. 时: shi35

4. 实: shi35

5. 是: shi51

6. 的: de

7. 地: de

8. 得: de35

9. 机: ji55

10. 激: ji55

11. 极: ji35

12. 记: ji51

13. 计: ji51

14. 迹: ji51

15. 离: li35

16. 里: li214

17. 理: li214

18. 励: li51

19. 荔: li51

20. 不: bu35/bu51

21. 布: bu51

22. 哥: ge55

23. 搁: ge55

24. 个: ge51

25. 七: qi55

26. 奇: qi35

27. 其: qi35

28. 起: qi214

29. 契: qi51

30. 折: zhe35

31. 者: zhe214

32. 这: zhe51

33. 他: ta55

34. 塔: ta214

35. 织: zhi55

36. 枝: zhi55

37. 职: zhi35

38. 止: zhi214

39. 置: zhi51

40. 智: zhi51

*to simplify the decoding process, we use T1 (-) to denote 55, T2 (/) to denote 35, T3 (∨) to

denote 214, and T4(\) to denote 51. The neutral tone syllables "的:de" and "地:de" were

marked as T1 or T4 according to the actual pronunciation of each individual patient.

The 29-Chinese phrases used in this work (with translation in English)：

1. 智者 sage

2. 记者 journalist

3. 荔枝 lichee

4. 七折起 thirty-precent off

5. 他 him/he

6. 他的 his

7. 他哥 his brother

8. 哥哥 elder brother

9. 不时地 often

10. 激励 encourage

11. 极其 extremely

12. 机智 smart

13. 织布机 loom

14. 这里的 here

15. 是 is

16. 的 DE (structure auxiliary)

17. 塔 pagoda

18. 不理 ignore

19. 是个 is a/an

20. 奇迹 miracle

21. 不计得失 do not care about gains and losses (Chinese Idiom)

22. 不得不 have to

23. 离职 resign

24. 搁置 shelve

25. 这个 this

26. 契机 opportunity

27. 其实 actually

28. 不止 more than

29. 七十 seventy

The 10 sentences used in this work:

1.　　他哥不理他。

Tā　　gē　　　　bù　　lǐ　　　　　　　　　　tā

his　　elder.brother　not　　pay.attention.to　　　　　him

'His elder brother ignores him.'

2. 他的荔枝七折起。

Tā　　de　　lìzhī　qīzhé　　　　qǐ

his　　DE　　lichee　30.percent.off　at.least

'His lichee is at least 30-percent off.'

3. 记者不得不离职。

Jìzhě　　　　　　bùdébù　　　lízhí

to.record.person　　cannot.not.to　resign

'The journalist has to resign.'

4. 他其实不止七十。

Tā   qíshí   bùzhǐ   qīshí

he   virtually   not.merely   seventy

'He is virtually more than seventy(-year-old).'

5. 哥哥不时地激励他。

Gēge   bùshíde   jīlì   tā

elder.brother   sometimes.not.but.sometimes will   encourage   him

'The elder brother often encourages him.'

6. 他极其机智。

Tā   jíqí   jīzhì

he   extremely   smart

'He is extremely smart.'

7. 织布机是这里的。

Zhībùjī   shì   zhèlǐ   de

loom   is   here   DE

'The loom belongs here.'

8. 这里的塔是个奇迹。

Zhèlǐ   de   tǎ   shì   gè   qíjì

here   DE   pagoda   is   a   miraculous.sign

'The pagoda here is a miracle.'

9. 智者不计得失。

Zhìzhě   bújìdéshī

wise.person   do.not.care.about.gains.and.losses

'The sage does not care about gains and losses.'

10. 搁置这个契机。

Gēzhì zhègè qìjī

shelve this   opportunity

'Shelve this opportunity

667   Task design

Experiments and data in this research abided by the relevant ethical regulations. Participants were

guided by sequential visual cues to produce one of the ten sentences consisted of 5-8 Chinese

characters from a corpus of 10 base syllables and 40 Chinese characters with varied tones **(Fig.**

1a). In every single trial, the participant was instructed to produce all ten sentences once. The ten

sentences were presented in a random order. Ideally, each participant produced 160 sentences (4

blocks × 4 trials/block × 10 sentences/trial), which yielded approximately 30 repetitions per tonal

syllable. But not all participant completed the entire reading task (158-160 sentences were

completed).

Each participant was guided by visual cues to perform block tasks. Each block started with a

black cross at the center of white background on the screen, which lasted for 30 seconds. After

that, the cross turned grey for 3 seconds, and one of the sentences in the sentence set was shown

in the middle of the screen in grey text. With the individual Chinese characters turning black for

1.2 seconds in a sequential order from the beginning to the end of the sentence, the participant

was instructed to pronounce the sentence in a relatively uniform speed following these go cues.

The inter-sentence time interval and the inter-trial interval were both 3 seconds.

Audio recordings were obtained synchronously with the ECoG recordings using a mounted

microphone. The first four participants (PA1-4) performed the speech task articulating, while the

last participants (PA5) performed the speech task whispering. We collected two types of blocks

of the sentence task: first 3 optimization blocks (Trial 1-12, containing 118-120 sentences in total

for each patient) and one evaluating block (Trial 13-16, containing 38-40 sentences for each

patient).

Data acquisition and signal processing

Electrocorticography and audio sound were recorded simultaneously using the Tucker-Davis

Technologies ECoG system. For each participant, two 128-channel electrode arrays were placed

by an experienced neurosurgeon, and the location was determined based on clinical exposure and

avoidance of the tumor. The arrays were connected to an amplifier. ECoG signals were recorded

at a sampling rate of 3052 Hz. The researcher visually and quantitatively inspected the channels

for artifacts or excessive noise (typically 50 Hz line noise). High-gamma frequency component

(70-150 Hz) was extracted via Hilbert transform and down-sampled to 400 Hz. Audio sound waves

were recorded at a sampling rate of 24414 Hz.

Phonetic and phonological transcription

For the audio recording, transcriptions and labels, including monosylabic Chinese characters,

consonants, vowels, and tones, were manually marked with praat (Version 6.1.01,

https://www.fon.hum.uva.nl/praat/) at the syllable level to ensure the label reflected the actual

sound the participant produced. Unexpected voicing unrelated to language task (such as

communication with clinicians) was excluded from samples used in training models.

Computational modeling infrastructure

The training and testing of the decoding models were performed offline using cluster of multiple

NVIDIA GPUs.

Data splitting

We split the data for speech detector and the syllable/tone decoder model testing from electrode

selection and hyperparameter searching. For responsive and discriminant electrode selection and

hyperparameter optimization, only the optimization blocks were used, which contain Trial 1-12

with each trial consists of randomly aranged 10 sentences. The evaluation block contains

remaining Trial 13-16.

During the optimization stage of the speech detector model, we used a six-fold nested cross

validation (CV) and each fold consisted of 2 trials. At evaluation stage, we used a similar cross

validation process, which leaves each trial in evaluation block for testing model, while the other

15 trials for training and validating. For speech detector models, we used 10% of non-testing data

as validation set to perform early-stopping, while the left 90% for training, in each CV runs (**Fig.**

S1A&B). For syllable/tone decoder model, we trained 5 (optimization stage) or 10 (evaluation

stage) sub-models in each CV runs, with different potions of data performing early-stopping while

left for training. The final model used for evaluation was an ensemble of 5 or 10 sub models. And

the overall decoding performance was evaluated by averaging the test performance in all the CV

runs (**Fig. S1C&D**).

Speech-responsive electrodes

Speech-responsive electrodes were identified using two-sample t-test. Specifically, each time point

in the [-400 ms, 800 ms] time window relative to the consonant onsets in each word was tested

against the [-1800ms, -400ms] baseline time window before the onset of each sentence. If the

results were significant (P < 0.01, Bonferroni corrected for the total number of electrodes and all

times points) in 40 consecutive time points (100 ms), the electrode would eventually be marked as

speech-responsive.

● Tone discriminant electrodes

To identify electrodes that were discriminative between lexical tones, we again aligned the high-

gamma responses to the onsets of single syllables. We then used the one-way ANOVA to test

whether the mean high-gamma responses of the four mandarin tones differed significantly. The

time window of the average response was [−500 ms, 500 ms] relative to the onset (400 total time

points). The significant time points were determined with a two-sided $P < 0.05$ threshold using

Bonferroni correction for the total number of electrodes and time points. To account for electrodes

with multiple peaks of high-gamma activity discriminant for tone decoding, we set the following

criterion: if there was a continous 200ms time window in which more than half of the time points

were significant, the electrode would be marked as tone-discriminant.

● Syllable discriminant electrodes

Similar to tone discriminant electrodes, the syllable discriminant electrodes were defined using

one-way ANOVA. We tested whether the mean high-gamma responses of the ten syllables were

significantly different. The time window of the average response was [−400 ms, 800 ms] relative

to the onset (480 total time points). The significant time points were determined with a two-sided

$P < 0.05$ threshold using Bonferroni correction for the total number of electrodes and time points.

Similarly, if there were a 200ms time window in which more than half of the time points were

significant, the electrode would be marked as syllable-discriminant.

● Cortical surface extraction and electrode visualization

Electrodes on each individual brain were marked by the BrainLab® neuronavigation system via

preoperative T1 MRI and validated via intro-operative photos by a neurosurgeon. The cerebral

surface was reconstructed using Freesurfer while anatomical labeling and plotting were performed via

customized python code[42].

Decoding framework

We built different neural network modules of speech detector, tone decoder and syllable decoder

to decode speech onsets and offsets, syllable labels and tone labels from the neural activity,

respectively. Inspired by previously published decoding models such as the EEGNet[43,44], our

decoders had separable CNN layers extracting within- and cross-electrodes spatiotemporal

features, followed by GRU layers extracting sequential information. Finally, we also used a natural

language model and a Viterbi decoder to combine the sequential outputs of the tone and syllable

decoders and generate the entire sentence using maximum a posteriori probability **(Fig. 1b)**.

Speech utterance detection model (speech detector)

The speech utterance detection model processed each time point of neural activity on speech

responsive electrodes using the time window spanning from 0.25 second before the time point to

0.25 seconds after the timepoint. The speech/silent state of each time point was decoded based on

the time-windowed neural activity.

We used the Torch 1.13.1+cu117 Python package to create and train the event classification

model[45]. The event classification architecture was a CNN structure followed by a stack of three

GRU layers with a latent dimension size of 256 and a dropout of 0.5 applied at each layer.

The initial CNN structure contains an 1D convolutional layer with a kernel size ($\textbf{\textit{FL}}_{\textit{ini}}$) of 3 and

a stride($\textbf{\textit{ST}}_{\textit{conv}}$) of 1 followed by a Leaky ReLU activation function to introduce non-linearity,

and a max-pooling layer with kernel size (L_{pool}) of 2 for temporal downsampling[46]. This initial

processing using convolution and pooling allows the model to extract local features from the

input data effectively, while following recurrent layers are capable of maintaining an internal

state through time that can be updated with new individual time samples of input data, making

them well suited for real-time inference with temporally dynamic processes. Also, the

bidirectional nature of the GRU enables the model to capture both forward and backward

temporal dependencies in the ECoG data, making it well-suited for event classification tasks that

require understanding the sequential context. The GRUs are followed by a fully connected layer

to project the last latent dimensions to probabilities across the two events (rest and speech).

During training, the model is optimized to minimize weighted crossentrophy. The weighted

crossentrophy loss was calculated using the ratio of the number of all the speech time points and

the number of all the rest time points, to offset the bias caused by imbalanced samples. The batch

size is 1024 and an Adam optimizer was used with a learning rate of 0.001. The training process

stops after the validation loss no longer decreases for 10 epochs or after 50 epochs, ensuring that

the model has sufficiently learned the underlying patterns in the data but has not yet overfitted. A

schematic depiction of this architecture is given in **Fig. 2f**.

During testing, the neural network predicted probabilities for each speech event label (rest, speech)

given the input neural data. To convert these predicted probabilities into the time of detected onsets,

we need to apply thresholding to the predicted speech probabilities. First, we smoothed the

probabilities using a sliding window average with a smoothing size (S). Next, we applied a

probability threshold (P_t) to the smoothed probabilities to binarize each frame (with a value of 1

for speech and 0 otherwise). Afterwards, we "debounced" these binarized values by applying time

thresholds for both a minimum continuous duration of silent period before the predicted onset, and

a minimum duration of continuous speech period after the predicted onset (off-time threshold (T_{off})

and on-time threshold (T_{on})). Detailed examples of thresholding process see **Fig. 3b**.

But the required continuous state is not strict, we set an error permissive rate (**EPR**) to allow a

small portion of timepoints with uncorrectly predicted speech event labels presented during both

continuous silent period before the predicted onset as well as the speech period after the predicted

onset. Besides, we will not predict two or more onsets within 0.5s, since normal speaking rate of

our task do not allow such short interval and this update in algorithm speed up the iteration process.

In all, this process of obtaining onset events from the predicted probabilities was parameterized by

five thresholding hyperparameters: the size of the smoothing window (**S**), the probability threshold

value (**P_t**), the off-time threshold (**T_{off}**) and on-time threshold (**T_{on}**), and the error permissive rate

(**EPR**). We used hyperparameter optimization to determine values for these parameters, which will

be described in later sections.

Tone decoder

For each speech utterance onset that was detected or manually aligned, tone decoder computed

tone likelihood by processing the neural activity in tone- discriminant electrodes spanning from

0.2 second before to 0.6 seconds after the detected onset of speech.

The tone decoder consists of ten ensumble neural networks with the same hyper-parameters but

different validation sets and training sets (see **Fig. S1D**). The input was high gamma ECoG

snippets with dimension $N \times T$, N is the number of tone-discriminated electrodes, while **$T = 320$,**

which is calculated by the time duration (0.8seconds) multiplies downsampled EcoG frequency

(400 Hz). Each network among 10 networks consists of the following stages:

• **Stage 1**

In the first stage, one-layer 2D convolution with the kernel size (FL_{ini}, N) and a stride of (ST_{conv}, 0), followed by a batch normalization layer (momentum=0.1, affine=True, and eps=1e-5) applied to the output of the spatial convolution. After an Exponential Linear Unit (ELU) activation function. Max-pooling is then performed along the temporal axis with a kernel size of (L_{pool}, 1) and a stride of (ST_{pool}, 1). During training, we applied a dropout layer a dropout value of D in the end of each CNN block for regularization to prevent overfitting.

- **Stage 2**

In the second stage, C_{layer} convolutional pool blocks are applied after the aforementioned pooling layer in series, each consisting of a dropout layer, a convolutional layer with kernel size (FL_{conv}, 1) and a stride of (ST_{conv}, 1), batch normalization, ELU activation, and max-pooling identical with aforementioned ones. These blocks further process and extract features from the data. During the first two stages, the filter number was set equal to C_{dim}.

- **Stage 3**

In the last stage, the output from the last convolutional pool block is fed into a stack of R_{layer} bidirectional Gated Recurrent Unit (GRU) layers. Each GRU layer has R_{dim} hidden units. The final hidden state of the last GRU layer is passed through a fully connected (dense) layer which project to 10 output units, representing the number of word classes for classification. **(Fig. 2g)**.

The model is optimized to minimize crossentrophy loss using a batch size of 8 and an Adam optimizer with a learning rate of 0.0005. The training process stops after the validation loss no longer decreases for 50 epochs. The weighted crossentrophy loss was calculated in the similar same way as speech detector to offset the bias caused by imbalanced samples.

Syllable decoder

For each speech onset that was detected, the syllable decoder computed syllable likelihood by

processing the neural activity in syllable- discriminant electrodes spanning from 0.4 second before

to 0.8 seconds after the detected onset of speech utterance. The structure and training process of

syllable decoder is identical with the aforemential tone decoder, the only difference between

them was the crossentrophy loss was not weighted, since the syllable is almost balanced-

distributed in the task.

Hyperparameter optimization and the universal framework

To find optimal values for the model hyperparameters used during performance evaluation, we

used hyperparameter optimization procedures to evaluate many possible combinations of

hyperparameter values, which were sampled from custom search spaces, with objective functions

that we designed to measure model performance. During each hyperparameter optimization

procedure, a desired number of combinations were tested, and the combination associated with

the best objective function value across all combinations was chosen as the optimal

hyperparameter value combination for that model and evaluation type. The data used to measure

the associated objective function values were distinct from the data that the optimal

hyperparameter values would be used to evaluate (hyperparameter values used during evaluation

of a test set were never chosen by optimizing on data in that test set). We used the *hyperopt*

Python package, which samples hyperparameter value combinations probabilistically during the

optimization procedure. And we used three types of hyperparameter optimization procedures to

optimize a total of 25 hyperparameters (see **Fig. 5** for undefined hyperparameters, their searching

ranges and their optimal values in each patient). During the optimization process, all the neural

networks were tested through the six-fold (2 trials per fold) cross-validation.

•   **Speech detection optimization**

We used this procedure to optimize the size of the smoothing window (S), the probability

threshold value (P_t), the off-time threshold (T_{off}) and on-time threshold (T_{on}), and the error

permissive rate (EPR). Because these thresholding hyperparameters were only applied after

speech probabilities were predicted, these hyperparameters did not affect training or evaluation

of the artificial neural network model driving the speech detector. In each iteration of the

optimization procedure, the current hyperparameter value combination was used to generate

detected speech events from the existing speech probabilities. We used an objective function to

calculate the performance. For time point of real onsets, we use $\hat{X}$ to represent the index of time

points within 0.25s range of real onsets ($t_i^*, i \in [1, \dots, n]$). For time point of predicted onsets, we

use $\tilde{X}$ to represent the index of time points within 0.25s range of real onsets. Then, we calculated

the accuracy (Acc) of $\hat{X}$ and $\tilde{X}$. The formal expression of this objective function was illustrated

through following equations:

873
$$\hat{X}[t] = \begin{cases} 0, & \text{others} \\ 1, & \text{if } \min_{i\in[1,\dots,n]} |t - t_i^*| < 0.25 \end{cases}$$

874
$$\tilde{X}[t] = \begin{cases} 0, & \text{others} \\ 1, & \text{if } \min_{i\in[1,\dots,n]} |t - t_i^*| < 0.25 \end{cases}$$

875
$$\mathbb{1}(x) = \begin{cases} 0, & x \neq 0 \\ 1, & x = 0 \end{cases}$$

876
$$\text{Acc} = \frac{\sum_t \mathbb{1}\left[\hat{X}[t] - \tilde{X}[t]\right]}{\sum t}$$

We use Acc to measure the model performance with each hyperparameter value combination. In

each detection hyperparameter optimization procedure, we evaluated 500 hyperparameter value

combinations before stopping.

Once the most optimized combination of hyperparameters was defined, we calculated the

predicted onset time list for all the 12 trials via six-fold prediction, we compare them with the

ground truth of onset of the 12 trials. If one onset time point in predicted list falls within 0.25s

range of real onsets, the labels (including tone, syllable and Chinese characteristic) belongs to the

mannually aligned onset will be given to the predicted time point, which participated in the

following hyperparameter optimization. For those time points can not match with any real onset

time points, no labels will be given and this part of the data will not participate in the following

hyperparameters. The similar match process will be performed in the evaluating stage,

calculating confusion matrix for syllable, tone and word on the bases of onset detection. Because

some real onset time points do not match with any detected onset time point, the number of

syllables and tones that actually used in calculating confusion matrices of decoding performance

after automated onset detection is less than the number of onsets detected.

• **Tone and Syllable decoder optimization**

We used this procedure to optimize ten hyperparameters for both tone decoder and syllable

decoder. These hyperparameters can be divided into two major groups according to their

properties.

The first group includes initial convolution filter length (FL_{ini}), stride of convolution (ST_{conv}), filter

length of following convolutional blocks (FL_{conv}), max-pooling kernel length (L_{pool}), max-pooling

stride (ST_{pool}), which are five hyperparameters related to the time dimension.

The second group includes the number of sequential convolutional blocks (C_{layer}), number of layers

of RNN (R_{layer}), number of filters in each convolutional process (C_{dim}), number of dimensions in

each RNN process (R_{dim}), and dropout value (D), which are five hyperparameters related to model

architectures and sizes.

We performed model testing on mannually-aligned-onset dataset and the dataset generated from

predicted onsets by the previously optimized speech detector. And the final loss is the average

value of loss on both datasets, in order to improve the model's robustness when countering

automatedly aligned neural signals in our final evaluation. Each optimization evaluated 500

different combinations of hyperparameter values. We used the same cross-entropy loss

functions to calculate the loss during the iteration.

• **The universal framework**

The universal framework shares a predefined set of hyperparameters when testing on all 5

participants. We used the median value of each optimized hyperparameters among 5 participants

as the predefined value of hyperparameters.

Conversion from tonal syllables to Chinese words

However, many Chinese characters are homophones that share the same pronunciations (including

syllable and tone), which prevented us from directly generating Chinese sentences using decoded

tonal syllables. To eventually decoding sentences consists of actual Chinese characters rather than

sequences of tonal syllables, we designed a natural language model that computed the next-

character transition probabilities given the previous Chinese character in a sequence. We first

divided the sentences into aforementional 29 words and phrases consisting of 1 to 4 Chinese

characters. We trained this model on a collection of sentences from the CCL corpus[47] that included

transfeing pairs (transfers) between those words from the 29-word set. After that, we used a Viterbi

decoder to determine the most likely sequence of words given the predicted tonal syllable

probabilities from the tone decoder and syllable decoder, as well as the word-sequence

probabilities from the natural language model[8]. With the incorporation of the language model, the

Viterbi decoder was capable of projecting sets of probability (likelihoods) of tonal syllable to exact

Chinese characters, which eventually decoded sentences from neural activity.

Language model

• **Collection of the corpus**

To train a domain-specific language model for the sentence task, we used CCL corpus from

Peking University[47]. We first measure the number of transfers between each two phrases (the

counts of the previous phrase transferred to the first word of the next phrase in the whole CCL

corpus). Due to the unequity of Chinese languge, we set a cut-off of 512 counts, and then

performed a ninth root for normalization. Since not all the transfers in our task appeared in CCL

corpus, we also incorperate the transfer probability of our own task corpus into our language

model.

• **Model fitting and word-sequence probabilities**

We extracted all n-grams with n ∈ {1, 2, 3, 4} from each phrase in our task corpus. Here, an n-

gram is a word sequence with a length of n Chinese characters. For example, the n-grams

(represented as tuples) extracted from the longest phrases "不计得失" in this approach would be:

1. (不)

2. (不计)

3. (不计得)

4. (不计得失)

Then we expand our transfer probability matrix into n-grams. We add the number of transfering

from q_{i-1} (such as (不计)) to q_i (such as (不计得)). Except for full phrases, n-grams as partial

components of phrases can only transfer from q_{i-1} to q_i . The calculation of number of each

transfering from a full phrase to the beginning of next phrases is aformentioned.

• **Hidden Markov model representation of the sentence decoding procedure**

During a sentence trial, the relationship between the sequence of words that the participant

produced and the sequence of neural activity time windows provided by the speech detector can

be represented as a hidden Markov model (HMM). In this HMM, each observed state y_i is the

time window of neural activity at index i within the sequence of detected time windows for any

particular trial, and each hidden state q_i is the n-gram containing the words that the participant

had attempted to produce from the first word to the word at index i in the sequence. Here, $q_i = $

$\{w_i, c_i\}$, where w_i is the word at index i in the sequence and c_i is the context of that word.

The emission probabilities for this HMM are $p(y_i|q_i)$, which specify the likelihood of observing

the neural time window y_i given the n-gram q_i. With the assumption that the time window of

neural activity associated with the production of w_i is conditionally independent of all of the

other attempted word productions given w_i ($y_i \perp w_j \mid w_i \; \forall \; j \neq i$), $p(y_i|q_i)$ simplifies to

$p(y_i|w_i)$. The word classifier provided the probabilities $p(w_i|y_i)$, which was used directly as the

values for $p(y_i|w_i)$ by applying Bayes' theorem and assuming a flat prior probability

distribution. The transition probabilities for this HMM are $p(q_i|q_{i-1})$, which specify the

probability that q_i is the n-gram at index i (the sequence of at most n words, containing w_i as the

final word, that the participant attempted to produce) given that the n-gram at index $(i-1)$ was

q_{i-1}. Here, q_{-1} can be defined as an empty set, indicating that q_0 is the first word in the

sequence. Because any elements in c_i will be contained in q_{i-1} and w_i is the only word in q_i that

is not contained in q_{i-1}, q_i simplifies to $p(w_i|c_i)$, which were the word sequence prior

probabilities provided by the language model. Implicit in this simplification is the assertion that

$p(q_i|q_{i-1}) = 0$ if q_i is incompatible with q_{i-1} (for example, if the final word in ci is not equal to

the second-to-last word in q_{i-1}).

• **Viterbi decoding implementation**

To predict the words that the participant attempted to produce during the sentence task, we

implemented a Viterbi decoding algorithm with this underlying HMM structure. The Viterbi

decoding algorithm uses dynamic programming to compute the most likely sequence of hidden

states given hidden-state prior transition probabilities and observed-state emission likelihoods[5].

To determine the most likely hidden-state sequence, this algorithm iteratively computes the

probabilities of various "paths" through the hidden-state sequence space (various combinations

of q_i values). Here, each of these Viterbi paths was parameterized by a particular path through

the hidden states (a particular word sequence) and the probability associated with that path given

the neural activity. The creation of new Viterbi paths from existing paths can be expressed using

the following recursive formula:

$$V_i = \{v_{i-1} + \log p(y_i \mid q_{i,v_{i-1}}) + L \log p(q_{i,v_{i-1}} \mid q_{i-1,v_{i-1}}) \mid v_{i-1} \in V_{i-1} \wedge w_i \in W\}$$

with the following variable definitions:

• V_j : The set of all Viterbi paths created after the word production attempt at index j within a

sentence trial.

• v_j : A Viterbi path within V_j . Each of these Viterbi paths was parameterized by the n-grams

$(q_0, \ldots, q_j)$ (or, equivalently, the words $(w_0, \ldots, w_j)$) and the log probability of that sequence

of words occurring given the neural activity, although these equations only describe the recursive

computation of the log probability values (the tracking of the words associated with each Viterbi

path is implicitly assumed).

• q_{j,v_k} : The n-gram q_j , containing the word w_j and the context of that word. This context is

determined from the most recent words within the hidden state sequence of Viterbi path v_k.

• $p(y_i \mid q_{i,v_{i-1}})$: The emission probability specifying the likelihood of the observed neural

activity y_i given the n-gram $q_{i,v_{i-1}}$.

• $p\left(q_{i,v_{i-1}} \mid q_{i-1,v_{i-1}} \right)$: The transition probability specifying the prior probability of

transitioning to the n-gram $q_{i,v_{i-1}}$ from the n-gram $q_{i-1,v_{i-1}}$.

• L : The language model scaling factor, which is a hyperparameter that we used to control the

weight of the transition probabilities from the language model relative to the emission

probabilities from the word classifier. In this study, we fixed it as 1.8.

• W : The 29 words set plus the end token.

• log: The natural logarithm.

Using the simplifications described in the previous section, the aforementional recursive

formula can be simplified to the following equation:

1004
$$V_i = \{v_{i-1} + \log p(w_i \mid y_i) + L \log p(w_i \mid c_{i-1}) \mid v_{i-1} \in V_{i-1} \wedge w_i \in W\}$$

where c_{j,v_k}, is the context of word w_j determined from the Viterbi path v_k, $p(w_i \mid y_i)$ are the

emission probabilities (obtained from the word classifier), and $p(w_i \mid c_{i-1})$ are the transition

probabilities (obtained from the language model). At the start of each sentence trial, the index i

was reset to zero (the first word in each trial was denoted w_0), and any existing Viterbi paths

from a previous trial were discarded. To initialize the recursion, we defined V_{-1} as a singleton

set containing a single Vitrbi path with the empty set as its hidden statezero. We used log

probabilities in practice for sequence and an associated log probability in practice for numerical

stability and computational efficiency.

Evaluation

• **Evaluation of independent decoding performances via Receiver Operating**

Characteristic (ROC) and Confusion Matrices

To evaluate the performance of our speech detector, we computed the Area Under the Curve

(AUC) of the Receiver Operating Characteristic (ROC) curve for each participant. To evaluate the

tone decoder and syllable decoder, we computed the classification accuracy and plotted the

confusion matrix, based on both the predicted and the manually aligned speech onsets. We also

calculated the classification accuracy and plotted confusion matrices of tonal-syllables and

Chinese characters, on both the predicted and the manually aligned speech onsets, in order to

further assess the capacity of the entire decoding system.

• **Evaluation of overall decoding performance via Word Error Rates (WERs)**

To evaluate the overall performance of our neural-to-text decoder, we analyzed the decoded

sentences using Word Error Rates (WERs) between the target and decoded sentences for each

sentence. WER is a commonly used metric

to measure the quality of predicted word sequences, computed by calculating the edit

(Levenshtein) distance between a reference (target) and decoded sentence and then dividing

the edit distance by the number of words in the reference sentence. Here, the edit distance

measurement can be interpreted as the number of word errors in the decoded sentence. It is

computed as the minimum number of insertions, deletions, and substitutions required to

transform the decoded sentence into the reference sentence. Below we demonstrate each type of

edit operation that can be used to transform an example decoded sentence (on the left side of

each arrow) into the target sentences. In each case, the example decoded sentence has an edit

distance of 1 to the target sentence.

• Insertion: 他哥不理他 → 他哥哥不理他

• Deletion: 他哥不理他 → 他哥理他

• Substitution: 他哥不理他 → 哥哥不理他

Lower edit distances and WERs indicated better performance. We computed WERs of each

sentence in the evaluating block using predictions made with the language model and Viterbi

decoder.

• **Comparison with published tone decoder**

To further validate the complexity of tone of sentences compared with tone of single syllable, we

applied our previously published monosyllabic tone decoder on tone decoding in sentence task. It

is a sequential CNN-LSTM structure to generate the syllable label based on manually aligned

neural activity when participants produce eight syllables "ma (tone1), ma (tone2), ma (tone3), ma

(tone4), mi (tone1), mi (tone2), mi (tone3), mi (tone4)" [15]. **(Fig. S2)**

• **Tone intelligibility assessment (IA)**

Listening tests using crowdsourcing are standard for evaluating the quality in natural language

processing. To further validate the variance of lexical tones in natural sentences compared with

the canonical tones of single syllables, we extracted the audio clips of each syllable utterance in

the evaluation blocks of each participant, using the same timespan as the neural decoder. We

shuffled the sequence clips by syllables to avoid any possible of leakage of sementic information.

The presented options included all tones. For sentence tone IA, we extracted the audio clip of each

sentence each patient pronounced in evaluation blocks. The evaluators were instructed to listen to

the audio of the entire and then choose from the options which tone they had just heard for each

syllable in the sentence. 20 evaluators (native Mandarin speakers) were instructed to listen to the

isolated audio clips and to decide which tone they had just heard. For sentence tone IA, we

extracted the audio clip of each sentence each patient pronounced in evaluation blocks. The

evaluators were instructed to listen to the audio of the entire and then choose from the options

which tone they had just heard for each syllable in the sentence. We recruited 20 native Mandarin

speakers from the Medical School of Fudan University, which do not know the purpose of this test

before the evaluation. The tone IA score was defined as the average accuracy of evaluators'

judgement.

1065
$$IA = 1 - \frac{T}{A}$$

Where T is the number of error tone choices; A is the number of total tests.

• **Comparison with baseline models**

We evaluated the performance of our models and compared it against several baselines. The

baseline models include (1) CNN models, which do not contain RNN structure, all the other parts

remain identical with optimized models. (2) RNN models, which do not contain CNN structure,

all the other parts remain identical with original optimized models (**Fig. S3**). WER of decoded

sentences were caluculated to evaluate the performance of these baselines.

• **Electrode contributions (saliences)**

To measure how much each electrode contributed to detection and classification performance, we

computed electrode contributions (saliences) with the artificial neural networks driving the speech

utterance detection model, the syllable and tone classification models, respectively. We used a

salience calculation method that has been used for identifing image regions that were useful for

image classification[48]. To compute electrode saliences for each type of ANN, we first calculated

the gradient of the loss function for the ANN with respect to the input features. The input features

were individual time samples of high gamma activity detected time windows for the speech event,

tone and syllable classifier. For each input feature, we backpropagated the gradient through the

ANN to the input layer. We then computed the Euclidean norm across time (within each evaluation

block) of the resulting gradient values associated with each electrode. Next, we computed the mean

across blocks of the Euclidean norm values, yielding a single salience value for each electrode.

Finally, we normalized each set of electrode saliences by calculating their root mean square values

(Fig. S4).

1087

1088

1089

1090

1091

1092

1093

1094

1095

1096

1097

1098

1099

1100

Supplementary Information

Daohan Zhang[1,2,3#], Zhenjie Wang[4#], Youkun Qian[1,2,3#], Zehao Zhao[1,2,3], Yan Liu[1,2,3], Xiaotao Hao[1,2,3], Wanxin Li[1,2,3], Shuo Lu[5], Honglin Zhu[6], Luyao Chen[7], Kunyu Xu[8], Yuanning Li[4,9*], Jinsong Wu[1,2,3*], Junfeng Lu[1,2,3,8,10*]

Author affiliations:

[1]Department of Neurosurgery, Huashan Hospital, Shanghai Medical College, Fudan University, Shanghai 200040, China

[2]Shanghai Key Laboratory of Brain Function Restoration and Neural Regeneration, Shanghai 200040, China

[3]National Center for Neurological Disorders, Huashan Hospital, Shanghai Medical College, Fudan University, Shanghai 200040, China

[4]School of Biomedical Engineering, ShanghaiTech University, Shanghai 201210, China

[5]Department of Chinese Language and Literature, Sun Yat-sen University, Guangzhou 510080, China

[6]Faculty of Life Sciences and Medicine, King's College London, London SE1 1UL, UK

[7]School of International Chinese Language Education, Beijing Normal University, Beijing 100875, China

[8]Institute of Modern Languages and Linguistics, Fudan University, Shanghai 200433, China

[9]State Key Laboratory of Advanced Medical Materials and Devices, ShanghaiTech University, Shanghai 201210, China

[10]MOE Frontiers Center for Brain Science, Huashan Hospital, Fudan University, Shanghai 200040, China

[#]These authors contributed equally to this work.

[*] Corresponding authors: Junfeng Lu (junfeng_lu@fudan.edu.cn), Jinsong Wu (wujinsong@huashan.org.cn), Yuanning Li (liyn2@shanghaitech.edu.cn)

1129

Fig. S1. Schematic depiction of data organization

A. During the optimization stage of the speech detector model, we used a six-fold nested cross validation and each fold consisted of 2 trials, while 10% of data in each trial of the training set

were separated as validation set in order to performing early-stopping.

B.   During the evaluation stage of the speech detector model, we used a similar cross validation.

Still, 10% of data in each training trial were separated as validation set in order to performing

early-stopping.

C.   During the optimization stage of the syllable/tone decoder model, we used a six-fold nested

cross validation and each fold consisted of 2 trials. In each fold, we trained 5 sub-models with

different potions of data performing early-stopping while left for training. The

training/validation/test split was 4:1:1.

D.   During the evaluation stage of the syllable/tone decoder model, we used a similar cross

validation process. In each fold, we trained 10 sub-models with different potions of data

performing early-stopping while left for training. The training/validation/test split was 12:3:1.

1144

1145

1146

Fig. S2. Schematic of control models for speech detector and tone/syllable decoder.

A.   CNN baseline for speech detector, which do not contain RNN structures, and all the other parts

remain unchanged.

B.   CNN baseline for tone/syllable decoder, which do not contain RNN structures, and all the other

parts, including optimized hyperparameters, remain unchanged.

C.   RNN baseline for speech detector, which do not contain CNN structures, and all the other parts

remain unchanged.

D.   RNN baseline for tone/syllable decoder, which do not contain CNN structures, and all the other

parts, including optimized hyperparameters, remain unchanged.

1156

1157

1158

1159

Fig. S3. Schematic of our previously published tone decoder which successfully decoded tone from intracranial neural signals while participants articulate isolated monosyllables of four target tones.

We applied our previously published monosyllabic tone decoder on tone decoding in sentence task. It is a sequential CNN-LSTM structure to generate the syllable label based on manually aligned neural activity when participants produce eight syllables "ma (tone1), ma (tone2), ma (tone3), ma (tone4), mi (tone1), mi (tone2), mi (tone3), mi (tone4)"[15].

A

B

C

D

E

Fig. S4. Participants' brains reconstruction overlaid with the locations of the placed electrodes and their relative contribution of each selected electrodes in decoding onset/syllable and tone.

A-E shown PA1, PA2, PA3, PA4 and PA5. Left part shown speech responsive electrodes in yellow shadows, middle shown syllable discriminative electrodes in blue shadows, while right shown tone discriminative electrodes in red shadows. Radius of shadows around electrodes shown contribution normalized root mean square (RMS), with a scale shown at the upper left of each subplot. The colors of the electrodes themselves represent whether they are speech responsive or syllable/tone discriminative, which is the same as **Fig. 2a-e**.

References:

Gilakjani, A. P. & Ahmadi, M. R. A study of factors affecting EFL learners' English listening comprehension and the strategies for improvement. (2011).
Anumanchipalli, G. K., Chartier, J. & Chang, E. F. Speech synthesis from neural decoding of spoken sentences. *Nature* **568**, 493-498, doi:10.1038/s41586-019-1119-1 (2019).
Moses, D. A., Leonard, M. K., Makin, J. G. & Chang, E. F. Real-time decoding of question-and-answer speech dialogue using human cortical activity. *Nat Commun* **10**, 3096, doi:10.1038/s41467-019-10994-4 (2019).
Makin, J. G., Moses, D. A. & Chang, E. F. Machine translation of cortical activity to text with an encoder-decoder framework. *Nat Neurosci* **23**, 575-582, doi:10.1038/s41593-020-0608-8 (2020).
Moses, D. A. *et al.* Neuroprosthesis for Decoding Speech in a Paralyzed Person with Anarthria. *N Engl J Med* **385**, 217-227, doi:10.1056/NEJMoa2027540 (2021).
Angrick, M. *et al.* Speech synthesis from ECoG using densely connected 3D convolutional neural networks. *J Neural Eng* **16**, 036019, doi:10.1088/1741-2552/ab0c59 (2019).
Willett, F. R. *et al.* A high-performance speech neuroprosthesis. *Nature*, 1-6 (2023).
Metzger, S. L. *et al.* A high-performance neuroprosthesis for speech decoding and avatar control. *Nature*, 1-10 (2023).
Willett, F. R. *et al.* A high-performance speech neuroprosthesis. *Nature* **620**, 1031-1036 (2023).
Metzger, S. L. *et al.* A high-performance neuroprosthesis for speech decoding and avatar control. *Nature* **620**, 1037-1046 (2023).
Komeiji, S. *et al.* in *ICASSP 2022-2022 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP).* 1311-1315 (IEEE).
Koch Fager, S., Fried-Oken, M., Jakobs, T. & Beukelman, D. R. New and emerging access technologies for adults with complex communication needs and severe motor impairments: State of the science. *Augmentative and Alternative Communication* **35**, 13-25 (2019).
Yip, M. *Tone*. (Cambridge University Press, 2002).
Dryer, M. S. & Haspelmath, M. The world atlas of language structures online. (2013).
Liu, Y. *et al.* Decoding and synthesizing tonal language speech from brain activity. *Science Advances* **9**, eadh0478 (2023).
Fons-ant, H. & Naessentialr, S. A model for the synthesis of pitch contours of connected speech. *annual report of the engineering research institute* **23** (1969).
Fujisaki, H., Hirose, K., Hallé, P. A. & Lei, H. in *ICSLP.* 841-844.
Chen, M. Y. An overview of tone sandhi phenomena across Chinese dialects. *Journal of Chinese Linguistics Monograph Series*, 111-156 (1991).
Ho, D.-a. The characteristics of Mandarin dialects. *The Sino-Tibetan languages*, 126-130 (2003).

20 Dichter, B. K., Breshears, J. D., Leonard, M. K. & Chang, E. F. The Control of Vocal Pitch in Human
Laryngeal Motor Cortex. *Cell* **174**, 21-31 e29, doi:10.1016/j.cell.2018.05.016 (2018).

21 Lu, J. *et al.* Neural control of lexical tone production in human laryngeal motor cortex. *Nature*
Communications **14**, 6917 (2023).

22 Bouchard, K. E., Mesgarani, N., Johnson, K. & Chang, E. F. Functional organization of human
sensorimotor cortex for speech articulation. *Nature* **495**, 327-332, doi:10.1038/nature11911
(2013).

23 Qiumei, Z., Dan, T. & Fenghua, W. Improved convolutional neural network based on fast
exponentially linear unit activation function. *Ieee Access* **7**, 151359-151367 (2019).

24 Zargar, S. Introduction to sequence learning models: RNN, LSTM, GRU. *Department of*
Mechanical and Aerospace Engineering, North Carolina State University, Raleigh, North Carolina
27606 (2021).

25 Chen, M. Y. *Tone sandhi: Patterns across Chinese dialects*. Vol. 92 (Cambridge University Press,
2000).

26 Pasley, B. N. *et al.* Reconstructing speech from human auditory cortex. *PLoS biology* **10**,
e1001251 (2012).

27 Martin, S. *et al.* Decoding spectrotemporal features of overt and covert speech from the human
cortex. *Frontiers in neuroengineering* **7**, 14 (2014).

28 Herff, C. *et al.* Generating natural, intelligible speech from brain activity in motor, premotor, and
inferior frontal cortices. *Frontiers in neuroscience* **13**, 1267 (2019).

29 Duraivel, S. *et al.* High-resolution neural recordings improve the accuracy of speech decoding.
Nature Communications **14**, 6938 (2023).

30 Willsey, M. S. *et al.* Real-time brain-machine interface in non-human primates achieves high-
velocity prosthetic finger movements using a shallow feedforward neural network decoder. *Nat*
Commun **13**, 6899, doi:10.1038/s41467-022-34452-w (2022).

31 Davidoff, M., Robert A. The pyramidal tract. *Neurology* **40**, 332-332 (1990).

32 Yazdan-Shahmorad, A., Kipke, D. R. & Lehmkuhle, M. J. High gamma power in ECoG reflects
cortical electrical stimulation effects on unit activity in layers V/VI. *Journal of neural engineering*
10, 066002 (2013).

33 Sanes, J. N. & Donoghue, J. P. Plasticity and primary motor cortex. *Annual review of*
neuroscience **23**, 393-415 (2000).

34 Myung, I. J. The importance of complexity in model selection. *Journal of mathematical*
psychology **44**, 190-204 (2000).

35 McCawley, J. D. in *Tone*   113-131 (Elsevier, 1978).

36 Jongman, A., Wang, Y., Moore, C. B. & Sereno, J. A. *Perception and production of Mandarin*
Chinese tones. (na, 2006).

37 Willett, F. R., Avansino, D. T., Hochberg, L. R., Henderson, J. M. & Shenoy, K. V. High-
performance brain-to-text communication via handwriting. *Nature* **593**, 249-254,
doi:10.1038/s41586-021-03506-2 (2021).

38 Cuisenier, P. *et al.* Relationship between direct cortical stimulation and induced high-frequency
activity for language mapping during SEEG recording. *J Neurosurg* **134**, 1251-1261,
doi:10.3171/2020.2.JNS192751 (2020).

39 Leonard, M. K. *et al.* Large-scale single-neuron speech sound encoding across the depth of
human cortex. *Nature*, 1-10 (2023).

40 Coughlin, B. *et al.* Modified Neuropixels probes for recording human neurophysiology in the
operating room. *Nature Protocols* **18**, 2927-2953 (2023).

41 Da, J. in *Proceedings of the fourth international conference on new technologies in teaching and*
learning Chinese. 501-511 (Citeseer).

42 Hamilton, L. S., Chang, D. L., Lee, M. B. & Chang, E. F. Semi-automated anatomical labeling and
inter-subject warping of high-density intracranial recording electrodes in electrocorticography.
Frontiers in Neuroinformatics **11**, 62 (2017).
43 Lawhern, V. J. *et al.* EEGNet: a compact convolutional neural network for EEG-based brain–
computer interfaces. *Journal of neural engineering* **15**, 056013 (2018).
44 Makin, J. G., Moses, D. A. & Chang, E. F. Machine translation of cortical activity to text with an
encoder–decoder framework. *Nature Neuroscience* **23**, 575-582, doi:10.1038/s41593-020-0608-
8 (2020).
45 Paszke, A. *et al.* Pytorch: An imperative style, high-performance deep learning library. *Advances
in neural information processing systems* **32** (2019).
46 Maas, A. L., Hannun, A. Y. & Ng, A. Y. in *Proc. icml.* 3 (Atlanta, Georgia, USA).
47 Zhan, W., Guo, R., Chang, B., Chen, Y. & Chen, L. in *Corpus Linguistics.* 71-86.
48 Simonyan, K., Vedaldi, A. & Zisserman, A. Visualising image classification models and saliency
maps. *Deep Inside Convolutional Networks* **2** (2014).

1276

1277