PPIscreenML: Structure-based screening for protein-protein interactions using AlphaFold

Victoria Mischley[1,2], Johannes Maier[3], Jesse Chen[3], and John Karanicolas[1,4*]

[1] Cancer Signaling & Microenvironment Program, Fox Chase Cancer Center,

Philadelphia PA 19111

[2] Molecular Cell Biology and Genetics, Drexel University, Philadelphia PA 19102

[3] Triana Biomedicines, Lexington MA 02421

[4] Moulder Center for Drug Discovery Research, Temple University School of Pharmacy,

Philadelphia PA 19140

*To whom correspondence should be addressed.

E-mail: **john.karanicolas@fccc.edu**, 215-728-7067

Abstract

Protein-protein interactions underlie nearly all cellular processes. With the advent of protein structure prediction methods such as AlphaFold2 (AF2), models of specific protein pairs can be built extremely accurately in most cases. However, determining the relevance of a given protein pair remains an open question. It is presently unclear how to use best structure-based tools to infer whether a pair of candidate proteins indeed interact with one another: ideally, one might even use such information to screen amongst candidate pairings to build up protein interaction networks. Whereas methods for evaluating quality of modeled protein complexes have been co-opted for determining which pairings interact (e.g., pDockQ and iPTM), there have been no rigorously benchmarked methods for this task. Here we introduce PPIscreenML, a classification model trained to distinguish AF2 models of interacting protein pairs from AF2 models of compelling decoy pairings. We find that PPIscreenML out-performs methods such as pDockQ and iPTM for this task, and further that PPIscreenML exhibits impressive performance when identifying which ligand/receptor pairings engage one another across the structurally conserved tumor necrosis factor superfamily (TNFSF). Analysis of benchmark results using complexes not seen in PPIscreenML development strongly suggest that the model generalizes beyond training data, making it broadly applicable for identifying new protein complexes based on structural models built with AF2.

Introduction

Cellular homeostasis is maintained by a complex protein interaction network that contributes to intricate signaling pathways within the cell [1]. As the human interactome is estimated to contain between 74,000 – 200,000 protein interactions [2], accurate and high-throughput methods to identify these interactions are crucial [3]. Classically, discovery and cataloguing of protein-protein interactions (PPIs) have most commonly employed yeast two-hybrid assays [4] and affinity purification assays [5]. More recently, proximity labeling techniques such as BioID [6] and TurboID [7] have gained popularity. However, each method has its own specific shortcomings, which further compounded due to sensitive dependence on experimental techniques and cellular conditions [1,8]. Collectively, the variabilities in these approaches ultimately lead to high rates of both false positives and false negatives [8,9]. For example, statistical analysis of representative interactome mapping data showed that recovering 65% of true protein interactions would require combining 10 distinct assays [1].

Computational predictions offer a natural means for complementing these experimental techniques. Early methods focused on inferring PPIs based on sequence information, by searching for gene pairs with correlated expression patterns, or distinct genes that can be found fused together in a different organism, or distinct genes that co-evolve with one another [10]. Drawing upon the exciting successes of large language models in many contexts, deep learning methods have also been applied to infer binary PPI pairings using protein sequences [11-13]. Results from such methods are extremely promising, however their lack of explainability make it difficult to determine how such models might perform on PPIs that are dissimilar from the training examples (i.e., their domain of applicability). Moreover, these models are inherently not designed to provide structural information about the bound pose: this information can be

extremely valuable, both to provide biological understanding that spurs further experimentation,

and as a starting point for developing new therapeutic agents that modulate the PPI [14].

Broad availability of AlphaFold2 (AF2) [15], especially through the ColabFold

framework [16], has provided the research community with unprecedented access to structural

information for monomeric proteins, in many cases at resolution comparable to experimentally-

determined structures. The startling accuracy of certain AlphaFold2 predictions, in turn, enabled

structure-based modeling for numerous new applications in biology and medicine [17,18].

Whereas the original AF2 could be adapted for highly successful predictions of oligomeric

assemblies, a subsequent re-trained release dubbed AF2-Multimer provided further enhanced

performance in this regime [19].

While AF2 provides often-accurate predictions for interacting protein pairs, there is not a

direct measure to evaluate the likelihood that a given query pair indeed interacts with one

another – a set of predicted output structures will be returned regardless. AF2 also provides

residue-level confidence measures of the predicted structures, specifically the predicted local-

distance difference test (pLDDT) [20], the predicted TM-score (pTM) [21], and the predicted

aligned error (PAE). The accuracy of structures for predicted protein complexes is often defined

using DockQ [22], a metric that combines three complementary and frequently-used quality

measures. By combining the number of interface residues with the pLDDT values of interface

residues, a confidence measure pDockQ was developed to define the likelihood of an accurate

binding mode in protein complexes predicted by AF2 [23]. Interestingly, pDockQ also provided

some ability to discriminate between "true" (interacting) versus "decoy" (non-interacting)

protein pairs [23] – performance for this task was only modest, however, presumably because

development of pDockQ was fundamentally focused elsewhere (recapitulating DockQ values).

In light of interest in using AF2 to distinguish between interacting and non-interacting

protein pairs, the AlphaPulldown [24] python package calculates several measures that have

been proposed for this task: iPTM [19], PI-score [25], and pDockQ [23]. While each of these

measures are intuitively reasonable, none were expressly developed for this classification task.

Here we describe PPIscreenML, a machine learning classifier that uses AF2 models to

distinguish interacting versus non-interacting protein pairs. To do so, PPIscreenML uses

descriptors drawn from AF2 confidence measures [15] and complements these with energetic

terms from the Rosetta scoring function [26]. In contrast to methods such as pDockQ, which was

trained as a means of evaluating model quality, PPIscreenML is deliberately and intentionally

trained/tested to distinguish between models of interacting proteins and compelling decoy pairs.

PPIscreenML exhibits superior performance to other methods for identifying interacting pairs in

a retrospective screen. Finally, using the tumor necrosis factor superfamily (TNFSF) as an

example of a structurally conserved family of ligand/receptor pairings, we demonstrate that

PPIscreenML can accurately recapitulate the selectivity profile in this challenging regime.

Computational Approach

Dataset for training/testing PPIscreenML

Critical to development of a useful classification model is compiling a set of "active" and

"decoy" examples that accurately reflect those that will be encountered in future prospective

applications. For PPIscreenML, we employed an overarching strategy that mirrors our previous

studies leading to a machine learning classifier that identifies active protein / small molecule

complexes likely to engage one another [27]. Specifically, our approach seeks to build highly

compelling decoy complexes, so that the resulting model is challenged to distinguish actives

from decoys that cannot be resolved using solely trivial criteria.

To build relevant and diverse structures of active protein pairings (**Figure 1a**), we used

the DockGround database [28] to assemble the complete set of heterodimeric protein complexes

in the PDB excluding homodimers, antibody/antigen complexes, and complexes that were either

very large or very small (see *Methods*). Upon filtering for a maximum of 30% sequence identity,

there remained 1,481 non-redundant protein-protein complexes with experimentally defined

structures. The planned application of PPIscreenML is to distinguish AF2 models of active pairs

from AF2 models of inactive pairs – thus, the model should be trained on AF2 actives, rather

than experimentally defined structures. Accordingly, we used the sequences of the component

proteins to build five AF2 models for each of these 1,481 non-redundant complexes.

Active protein-protein pairs that are mis-predicted by AF2 should not lead to predictions

of "active" from PPIscreenML, since the specific interactions in the AF2 are not those that lead

to binding. In the context of training, then, we sought to use only those models that were

correctly predicted by AF2: we therefore filtered the models and retained only those with a

DockQ score [22] of at least 0.23 relative to the corresponding experimentally defined structure

(0.23 is the quality cutoff defined to be an "acceptable" prediction for the MOAL and CAPRI

sets). Filtering on model quality in this manner excluded 932 models from training, leading to a

total of 6,473 active models with median DockQ value of 0.88 (**Figure S1a**).

In a prospective application of PPIscreenML, however, the DockQ score will not be

known *a priori* (since this requires an experimentally defined structure, which itself is evidence

of an interaction). To ensure a realistic estimate of the performance that can be expected in future

prospective experiments, complexes with structures that were mis-predicted by AF2 were *not*

excluded from the test set. Accordingly, active pairs that are not correctly classified by

PPIscreenML may occur either because AF2 builds a poor model, or because PPIscreenML fails

to recognize a well-built model as an interacting pair. While the test set performance thus reflects

more than the success of PPIscreenML, this strategy enhances confidence that the observed test

set performance will carry forward to prospective applications in future.

With respect to creating a set of decoy complexes (for both training and testing), it is

essential that the decoys suitably represent the types of inactive complexes expected to be

encountered in prospective applications. In particular, decoys that can be dismissed as inactive

based on trivial criteria offer little benefit in developing PPIscreenML: rather, we prioritized

building a set of extremely compelling decoys [27], so that training would be impelled to find a

more sophisticated and nuanced model for classification.

To build a set of compelling decoys (**Figure 1a**), we began by using each active complex

as a template. For each component protein in the complex, we identified its closest structural

analog (based on TM-score [29]) amongst all other proteins in our collection. Despite the fact

that homologs had been excluded from our dataset on the basis of sequence identity, close

structural matches could nonetheless be identified in most cases (**Figure S1b**): 87% of the

proteins in our set were paired with a structural analog having TM-score greater than 0.5, a

cutoff far beyond that which is observed between random protein pairs [30]. The structural

analog for each component protein was then superposed onto the template in the active complex,

providing a crude model of these two (presumably) non-interacting proteins that structurally

resembles an active complex (**Figure 1b**). As noted earlier, the planned application of

PPIscreenML is to distinguish AF2 models of active pairs from AF2 models of inactive pairs: as

for the active pairings, we therefore used the sequences of the component proteins in each of

these "decoy" complexes to build five AF2 models for each.

Figure 1: Building a challenging training/testing set for PPIscreenML. (A) A collection of 1,481 non-redundant active complexes with experimentally derived structures were obtained from DockGround, and five AF2 models were built from each of these. To build decoys, the same collection was screened to identify the closest structural matches (by TM-score) for each component protein. The structural homologs for each template protein were aligned onto the original complex, yielding a new (decoy) complex between two presumably non-interacting proteins. Five AF2 models were built for each of these 1,481 decoy complexes. **(B)** An example of a decoy complex (*blue/cyan*) superposed with the active complex from which is was generated (*brown/wheat*). **(C)** A suite of AlphaFold confidence metrics, structural properties, and Rosetta energy terms were used as input features for training PPIscreenML, a machine learning classifier built to distinguish active versus compelling inactive protein pairs.

135
136

To train PPIscreenML, data was partitioned using a 60/20/20 split. The data reserved for

testing was not used in any phase of training or validation. The dataset includes 5 AF2 models

for each (active or decoy) complex: training on one AF2 model of a given complex then using a

different model of the same complex in the test set would introduce obvious information leakage.

To avoid this, all 5 models for a given complex were *together* placed in either the training set or

the validation set or the test set [31]. As noted earlier, all five AF2 models for a given complex

were included in the validation and testing sets; however, only those AF2 models of active

complexes close to the experimentally derived structures were included in the training set

(**Figure S2**).

Having partitioned the AF2 models into training, validation, and test sets, a series of

quantitative features were extracted from each model. Specifically, three groups of features were

calculated from each model (**Figure 1c**): 7 features representing AF2 confidence measures, 33

structural "counting" features, and 17 features from the Rosetta energy function. This set of 57

features (**Figure S3**) was initially evaluated in development of PPIscreenML.

Developing the PPIscreenML model

Using the compiled collection of features for each complex, we evaluated seven standard

machine learning frameworks to build classification models. In each case, models were trained

using 5-fold cross validation within the test set, and applied to a validation set that was not

included in each fold of training. Models were then compared using the combined cross-fold

AUC score (*A*rea *U*nder the *C*urve of a *R*eceiver *O*perating *C*haracteristic (ROC) plot). All seven

models had similar performance, with XGBoost (an implementation of gradient-boosted decision

trees) yielding the highest AUC value of 0.924 (**Figure S4**).

The model was then applied to the test set, that had been completely held-out from model

training and evaluation. To better recapitulate a real-world use case, this experiment incorporates

two key differences from the earlier evaluation using the validation set (**Figure S2**). First, AF2

models of active complexes with poor DockQ scores relative to the corresponding PDB structure

are included in the test set, whereas these had been excluded from the validation set. This reflects

the reality that active complexes will occasionally be mis-docked by AF2, and these models

cannot be discarded in a true prospective application. Second, rather than evaluate performance

using the scores of individual AF2 models, the top-ranked model for each complex is drawn

from the scores of all five AF2 models. Here too, in a prospective screening application one

would mitigate the possibility that individual AF2 models may be mis-docked by simply using

the model that PPIscreenML finds most compelling. Applying the XGBoost model to the held-

out test set with these conditions yielded an AUC value of 0.892 (**Figure 2a**).

Figure 2: Training and feature reduction for PPIscreenML. (A) Receiver operating characteristic (ROC) plot demonstrating classification performance on a completely held-out test set, for an XGBoost model using 57 features. **(B)** The number of features was reduced using sequential backwards selection, from 57 features to 7 features. **(C)** Classification performance of PPIscreenML (7 features) on the same completely held-out test set.

172
173

To mitigate any potential overtraining, sequential backwards selection was applied to

reduce the number of features, using the validation set (*not* the test set, which is not used in any

model optimization). This approach provided a model with only seven features that maintained

the AUC of the model with all features when evaluated using the validation set (**Figure S5**).

Specifically, this model uses one feature from the AF2 confidence measures (the average of the

top ¼ of the interfacial PAE values), one structural "counting" feature (number of charged amino

acids in the interface), and five features from the Rosetta energy function (the average Lennard-

Jones attractive score for interfacial residues, the average Lennard-Jones repulsive score for

interfacial residues, the average solvation score for interfacial residues, the average electrostatic

score for interfacial residues, and the proportion of interfacial residues involved in beta-sheet

structures) (**Figure 2b**).

When applied to the test set that was completely held out from model training and

optimization, this 7-feature PPIscreenML model yields an AUC of 0.884, comparable to the full

57-feature model (**Figure 2c**).

Results

PPIscreenML out-performs other structure-based methods for identifying interacting protein pairs

Already several structure-based methods have been proposed as a means for

distinguishing between models of interacting versus non-interacting protein pairs: these include

iPTM [19], PI-score [25], and pDockQ [23]. To evaluate the performance of PPIscreenML

relative to these tools, we applied each method to the collection of AF2 models for active

pairings and compelling decoys that comprise our test set. As noted earlier, the test set does _not_

remove models of true pairings for which the structures have been incorrectly built by AF2, since

this would not be possible in a real-world setting. In each case we scored all five AF2 models for

a given pairing, and we took the highest score from each method as an indication of whether

each pairing is inferred to be active or decoy (**Figure S2**). We note that none of the complexes in

this test set have not been used in any phase of PPIscreenML development, but we cannot rule

out that some of the active complexes were used in training the other methods.

Figure 3: Classification performance of PPIscreenML relative to pDockQ and iPTM. The same
test set is used here. These complexes were not seen in any phase of developing PPIscreenML, but may
have been used in developing pDockQ or iPTM. **(A)** Receiver operating characteristic (ROC) plot
shows superior performance of PPIscreenML relative to these other two methods. **(B)** Overlaid
histograms show clear separation of actives and decoys scored using PPIscreenML. **(C)** Overlaid
histograms show overlapping distributions when models are scored with pDockQ or iPTM.

202
203

Applying each method to the same test set, we find that PPIscreenML out-performs the

other methods: its AUC value is 0.884, compared to AUC values of 0.843 and 0.710 for iPTM

and pDockQ, respectively (**Figure 3a**). The basis for these AUC values is evident from the

distribution of raw scores assigned to active / decoy complexes by each method. PPIscreenML

assigns (correct) scores very close to either 1 or 0 for most of the actives or decoys, with clear

separation between them (**Figure 3b**); on the other hand, the alternate methods both assign more

scores with intermediate values, and they also include many incorrect assignments (**Figure 3c**).

An advantage of using _R_eceiver _O_perating _C_haracteristic (ROC) plots for defining the

performance of binary classifiers is that one need not define a threshold score at which a given

input would be assigned the label of active or inactive; rather, all points in the test set are simply

ranked, and the ROC plot reflects the preponderance of actives that score ahead of decoys. To

facilitate adoption of PPIscreenML in different setting, we use the test set results to calculate

various performance measures (e.g. false positive rate, false negative rate) as a function of

threshold score used to assign the label (**Table 1**). The use of a high (stringent) threshold value

yields high precision but poor recall: this would be preferable in a very broad screening context

in which one seeks (for example) to identify new candidate interactions at proteome-wide scale,

and one wishes to test only the more confidently predicted pairings. Conversely, a lower (less

stringent) threshold value yields poorer precision but improved recall: this would be preferable

when screening in a more restricted space such as (for example) when seeking to identify

additional pairings for members of a protein family known to interact with one another.

PPIscreenML Threshold	FPR	TPR	FNR	TNR	Precision	Recall	F1 Score
0.98	0.00	0.00	1.00	1.00	1.00	0.00	0.01
0.95	0.01	0.16	0.84	0.99	0.96	0.16	0.27
0.9	0.07	0.39	0.61	0.93	0.85	0.39	0.54
0.85	0.11	0.60	0.40	0.89	0.85	0.60	0.70
0.8	0.15	0.74	0.26	0.85	0.83	0.74	0.78
0.75	0.18	0.80	0.20	0.82	0.82	0.80	0.81
0.7	0.21	0.85	0.15	0.79	0.80	0.85	0.83
0.64	0.23	0.88	0.12	0.77	0.80	0.88	0.84
0.6	0.24	0.89	0.11	0.76	0.79	0.89	0.84
0.56	0.24	0.92	0.08	0.76	0.79	0.92	0.85
0.5	0.27	0.93	0.07	0.73	0.78	0.93	0.85
0.47	0.27	0.93	0.07	0.73	0.77	0.93	0.84
0.4	0.29	0.95	0.05	0.71	0.76	0.95	0.85
0.38	0.30	0.95	0.05	0.70	0.76	0.95	0.85
0.28	0.33	0.95	0.05	0.67	0.75	0.95	0.84
0.21	0.35	0.95	0.05	0.65	0.73	0.95	0.83
0.18	0.35	0.96	0.04	0.65	0.73	0.96	0.83
0.08	0.43	0.96	0.04	0.57	0.69	0.96	0.81
0.05	0.48	0.97	0.03	0.52	0.67	0.97	0.79
0	1.00	1.00	0.00	0.00	0.50	1.00	0.67

Table 1: Performance of PPIscreenML using various threshold values. By adjusting the threshold score at which a test complex is assigned as active/decoy PPIscreenML can be used in regimes that prioritize returning only the most confident pairings (a high threshold score yields high precision but poor recall) or in exploratory regimes that return more speculative pairings as well (a lower threshold score yields high recall but poorer precision).

PPIscreenML recapitulates selectivity within a protein superfamily

As a challenging further benchmark for PPIscreenML performance, we sought to

evaluate whether it could recapitulate the pattern of binding interactions across a structurally

conserved protein superfamily. The tumor necrosis factor superfamily (TNFSF) comprises 18

protein ligands and 28 receptors in humans, leading to 504 potential pairings. However, only 36

of these pairings are reported to show productive binding to one another, as observed in a

comprehensive flow cytometry experiment [32].

The TNFSF ligands share a conserved fold, and they assemble into trimers. The TNFSF

receptors also share a conserved fold, and three copies of the cell-surface receptor independently

bind around the edges of the trimeric ligand. While AF2 typically provides highly accurate

structures of cognate ligand/receptor complexes, it also builds analogous models for

ligand/receptor pairings that do not actually interact (**Figure 4a**). Accordingly, this system

represents an ideal benchmark to evaluate whether PPIscreenML can use structural cues to

distinguish active pairings from close analogs that do not bind one another. Importantly for this

benchmark, no TNFSF ligands or receptors were included in the development of PPIscreenML

thus far, because the training and testing sets were restricted to dimeric complexes.

We used AF2 to build models of all 504 potential TNFSF ligand/receptor pairings, and

then evaluated these models using PPIscreenML. Overall, the ligand/receptor pairings that

scored most favorably with PPIscreenML indeed correspond to those which have been described

experimentally (**Figure 4b**). Of note, for 14 of the 18 TNFSF ligands, the receptor with the

highest PPIscreenML score is indeed a true interactor; of the two receptors with the highest

PPIscreenML score, a true interactor is found for 17 of the 18 ligands.

Analysis of these data via ROC plot confirms the outstanding performance of

PPIscreenML for identifying interacting pairs (**Figure 4c**). Further, the AUC value of 0.93 in this

new benchmark is similar to that observed when applying PPIscreenML to the held-out test set

of heterodimeric complexes (0.88), supporting the generality of PPIscreenML for application to

new data beyond the training regime.

Figure 4: Application of PPIscreenML to identify active pairings within the tumor necrosis factor superfamily (TNFSF). (A) Structurally-conserved TNFSF ligands bind to structurally-conserved TNFSF receptors; AF2 builds models of these complexes in the canonical pose for cognate pairings (RANKL/RANK are shown in *wheat/cyan*) but also in some cases for non-cognate pairings (RANKL/CD40 are shown in *brown/blue*). **(B)** Each ligand/receptor pairing was built with AF2 and scored with PPIscreenML (heatmap colored from low score in *red*, to high score in *green*). Ligand/receptor pairings observed in a comprehensive cellular assay are indicated with *white* checkmarks. **(C)** Receiver operating characteristic (ROC) plot demonstrating PPIscreenML classification of TNFSF ligand/receptor pairings.

Discussion

The availability of AlphaFold2 and related methods [15,16,19,33], has enabled structure-

based analysis of proteins and protein complexes to an extent that has rapidly transformed many

parts of biology and medicine [17,18]. Numerous studies have incorporated AF2 models to

justify or rationalize the structural basis for a particular protein-protein interaction, and in many

cases use either iPTM or pDockQ as further support for the relevance of the proposed

interaction. Such studies – which range from predicting protein quaternary structures to defining

biological functions of peptides and intrinsically disordered regions [34-40] – highlight the value

of using AF2 to nominate new candidate protein-protein interactions (i.e., in a screening setting),

extending it beyond simply providing structures for fully validated protein pairings.

While the early adoption of iPTM or pDockQ has spurred their use in this screening,

neither one was intended for this use-case. Rather, both were developed with the goal of

assessing model quality for AF2 structures, and the ability to distinguish between active and

inactive structures on the basis of model quality was a convenient secondary benefit [19,23]. Due

to this history, however, neither method was rigorously benchmarked in a manner that would set

expectations for their performance in real-world applications.

To lay the groundwork for this study, we began by building a set of non-redundant active

complexes, and from these a set of highly compelling decoy complexes. The overarching

philosophy behind construction of this set was to realistically mimic conditions that would be

encountered in future (prospective) screening applications. Notably, distinguishing actives from

decoys in this set is markedly more challenging than in other (less realistic) benchmarks: for

example, pDockQ provided an AUC value of 0.87 in its first-reported classification experiment

[23], but only 0.71 when applied to this newer set (**Figure 3a**).

Developing this challenging and realistic set allowed us to train PPIscreenML, a tool

expressly designed and optimized to be used in screening for protein-protein interactions. As

expected, performance of PPIscreenML is superior to that of iPTM or pDockQ for this screening

regime (**Figure 3a**). Moreover, PPIscreenML also makes use of subtle structural cues to provide

its discriminative power, as evidenced from its impressive performance on the TNFSF selectivity

benchmark (**Figure 4**).

Contemporaneously with our study, other groups have developed alternate methods for

predicting pairs of interacting proteins. For example, the AF2Complex method also shows

superiority over iPTM [41], albeit through testing on arbitrary collections of protein pairings

(rather than on compellingly-built decoys).

The natural extension of using AF2 and related methods to carry out structure-based

screening for protein-protein interactions, naturally, is using these methods to define whole

interactomes. Already certain studies have applied these tools either within targeted protein

families [42,43] for groups of proteins thought to belong together in large complexes [41,44,45].

Importantly, careful consideration of the statistical measures needed for productively scaling

assessments to whole proteomes must complement these studies; for example, this will allow for

defining thresholds that ideally balance precision and recall (**Table 1**), and also ensure that the

expected results justify these larger-scale analyses.

There is also ample reason for optimism that performance of PPIscreenML will further

improve as the underlying AF2 models improve. Specifically, older versions of the AF2 software

yielded slightly worse performance from PPIscreenML (**Figure S6, S7**), but the difference in

performance could be attributed to the fact that a (slightly) smaller proportion of the active

complexes were correctly built. Thus, the true bottleneck in extending PPIscreenML may not lie

with distinguishing correct versus incorrect interfaces. Rather, to screening for interactions at

whole-proteome scale may currently by instead limited by the fact that not all protein pairs are

correctly modeled by AF2, and active pairings cannot be reliably identified if their structures are

incorrectly built.

Methods

Model availability

All protein structures, code, and machine learning models described in this paper are

available on GitHub (https://github.com/victoria-mischley/PPIScreenML.git).

Set of active complexes

Heterodimeric protein complexes were downloaded from the DockGround database [28].

Complexes that were downloaded were published in the PDB [46] between up to 01/26/23 with a

maximum of 3 Å resolution. No homodimers or antibody/antigen complexes were included in

the dataset. The dataset was further filtered for a maximum of 30% sequence identity. Any

heterodimeric complex with a total length greater than 1,550 amino acids was filtered out of the

dataset, due to our modeling capabilities at the time. Finally, the dataset was separated based on

protein size. If a heterodimeric complex had at least one protein less than 50 amino acids, this

complex was included in the protein-peptide dataset and excluded from the protein-protein

dataset. After filtering, there were a total of 1,481 protein-protein complexes and 456 protein-

peptide complexes.

The sequences for these protein complexes were then downloaded directly from the PDB

[46]. Sequences were then used to model the complexes with ColabFold Batch [16] alphafold-

multimer v2 [19]. Templates were used in building AF2 models, each model was recycled 12

times, and the AMBER relax step was included.

To avoid including inaccurate structural models in the set of actives, DockQ score [22]

was used to filter out incorrect models. DockQ [22] is a continuous score that incorporates

information from three scoring metrics, allowing for a holistic view of the complex's accuracy:

the fraction of native interfaces (Fnat), the Ligand Root Mean Square Deviation (LRMS), and

iRMS. While DockQ is a continuous measure, a DockQ score of 0.23 or greater is considered at

least "acceptable" quality [22]. Therefore, we only included in the training set models with

DockQ scores greater than 0.23. Out of the five models provided by AlphaFold for each

heterodimeric complex, every model with a DockQ score greater than 0.23 was kept in the

training set (**Figure S1**). Keeping all models with a DockQ score greater than 0.23 rather than

taking only the model with the highest DockQ score allowed us to introduce some noise into our

training dataset. However, our test set included all five AF models, as we would not know the

correct multimeric structure a priori (**Figure S2**). Hence, utilizing all five models in the training

set provides a more meaningful readout of expected performance in future prospective

applications.

Set of compelling decoy complexes

The set of active complexes were separated into their individual component proteins. For

each protein, the TM-score [29] was calculated between that protein and every other protein. In

each complex, the two component proteins were replaced by their closest structural analogs: this

provided a simple means to generate new complexes that resemble known complexes, but that

are built using pairs of (presumably) non-interacting proteins. In cases for which pair of

structural analogs happened to come from the same alternate complex (i.e. the newly generated

pairing corresponds to one of the active pairings), the analogs with the second-best TM-scores

were used to generate a new decoy pairing.

After selection of the two proteins that would comprise a "decoy" pairing, their

sequences were used to build a set of AF2 models using the same settings as for the active

complexes.

We did note that this method for building compelling decoys, did give a slight bias

towards larger proteins being used (**Figure S8**): this arises because larger decoy proteins are

(slightly) more likely to have higher TM-score to the templates, and thus are slightly favored in

building decoy complexes. Because this artifact could be leveraged by features that explicitly

scale with the total size of the component proteins, such features were excluded from our study.

Feature extraction

Structural features were extracted from AF2 models using three python scripts (all

available on GitHub): one for AF2-based features, one for Rosetta-based features (implemented

using pyRosetta), and one for structural "counting" features (implemented using python package

BioPandas). Residues were classified as interface residues if the $C\beta$ atom (or $C\alpha$ for glycine)

was within 12 Å of a $C\beta$ atom on the other chain.

To calculate iPAE top ¼, PAE values were calculated for all interacting residue pairs

then the highest ¼ of these values were averaged. To calculate tPAE top ¼, all PAE values for

interchain residues-residue pairs were calculated then the highest ¼ of these values were

averaged.

 Data partitioning

Each protein pairing was randomly assigned to either training set / validation set / test set,

with an 60/20/20 split. To avoid information leakage, all AF2 models for a given protein pairing

were *together* placed in either training set / validation set / test set (rather than assign individual

AF2 models to different sets).

Training and validation sets

The active complexes in the training set were filtered to include only AF2 models with

greater than 0.23 DockQ score (relative to the corresponding crystal structure). Stratified kfold 5-

fold cross validation was used for the training and validation sets, such that all AF2 models for a

given complex were together placed in either the training set or the validation set.

Test set

Complexes used in the test set were separated from those in the training set, and not used

in any part of developing PPIscreenML.

Evaluation of PPIscreenML on the test set differed from the training/validation set in two

ways (**Figure S2**), both intended to ensure that model performance on the test set will extend to

future prospective applications. First, since experimentally derived structures will not be

available, AF2 models in the test set were not filtered based on DockQ. Thus, the test set

includes some active complexes for which the AF2 models are incorrectly built, as would occur

in a prospective context. Second, rather than evaluate PPIscreenML scores for individual AF2

models, performance was evaluated by using PPIscreenML to classify each complex.

Specifically, PPIscreenML was used to define scores for all five AF2 models, then the inferred

class for the complex was assigned based on the maximum value from the five models.

Machine learning classifier

Code for model training and optimization was adapted from a standard source [47].

PPIscreenML was built using the XGBoost framework [48]. Other machine learning

frameworks evaluated included decision trees, random forest, K-nearest neighbors, logistic

regression, AdaBoost, and Bagging (**Figure S4**). Sequential backwards selection was then used

to reduce the number of features from 57 to 7 (**Figure 2**). Finally, the model was hyperparameter

tuned on the following parameters: maximum depth, number of estimators, learning rate, gamma,

regularized lambda, and minimum child weight.

All model optimization (selecting the framework, feature reduction, and hyperparameter

tuning) was carried out using the validation set to define the best model, and not ever the test set.

Impact of AF2 version

Development of PPIscreenML and all performance benchmarking used models built with

AF-multimer v2.3. Performance is similar when PPIscreenML is applied to models built with

AF-ptm (**Figure S6**) or with AF-multimer v2.2 (**Figure S7**). In both cases the AUC values were

slightly worse than for AF-multimer v2.3, but analysis of incorrect predictions shows that this

difference can be traced to the fact that AF-ptm and AF-multimer v2.2 build mis-docked models

of active complexes slightly more often than AF-multimer v2.3 does.

TNFSF case study

All 18 TNFSF ligands were modeled against all 28 TNFSF receptors, for a total of 504

pairings (using sequences obtained from Uniprot). Given the shared arrangement of subunits in

all complexes described to date, a 3:3 stoichiometry was assumed in all cases. Because three

receptor subunits separately engage the outside edges of the trimeric ligand, AF2 models

included three copies of the ligand with one copy of the receptor.

Five models for each ligand/receptor pairing were built using the CF-batch alphafold-

multimer v2.3, with templates, 12 recycles and AMBER relax step. Features from each structural

model were extracted and used as input to PPIscreenML. Because PPIscreenML was trained on

heterodimeric complexes, the three copies of the trimeric ligand were considered as the first

entity and the receptor was considered as the second entity.

PPIscreenML results were compared to TNFSF binding specificity data drawn from a

previously published comprehensive survey using flow cytometry [32].

Computational resources

Approximately 7,700 GPU hours were used to build the AF2 models in this work. All

models were built on ACCESS San Diego Supercomputer's Expanse NVIDIA V100 GPU

processors [49].

Acknowledgements

Parts of several figures were created using BioRender.

This work was supported by the W.M. Keck Foundation and by the NIH National

Institute of General Medical Sciences (R01GM141513). This research was also funded in part

through the NIH/NCI Cancer Center Support Grant P30CA006927.

This work used the Extreme Science and Engineering Discovery Environment (XSEDE)

allocation MCB130049, which is supported by National Science Foundation grant number

1548562. This work also used computational resources through allocation MCB130049 from the

Advanced Cyberinfrastructure Coordination Ecosystem: Services & Support (ACCESS)

program, which is supported by National Science Foundation grants 2138259, 2138286,

2138307, 2137603, and 2138296.

References

1. Choi SG, Olivet J, Cassonnet P, Vidalain PO, Luck K, Lambourne L, Spirohn K, Lemmens I, Dos Santos M, Demeret C, Jones L, Rangarajan S, Bian W, Coutant EP, Janin YL, van der Werf S, Trepte P, Wanker EE, De Las Rivas J, Tavernier J, Twizere JC, Hao T, Hill DE, Vidal M, Calderwood MA, Jacob Y. Maximizing binary interactome mapping with a minimal number of assays. *Nat Commun*. 2019; 10:3907.

2. Venkatesan K, Rual JF, Vazquez A, Stelzl U, Lemmens I, Hirozane-Kishikawa T, Hao T, Zenkner M, Xin X, Goh KI, Yildirim MA, Simonis N, Heinzmann K, Gebreab F, Sahalie JM, Cevik S, Simon C, de Smet AS, Dann E, Smolyar A, Vinayagam A, Yu H, Szeto D, Borick H, Dricot A, Klitgord N, Murray RR, Lin C, Lalowski M, Timm J, Rau K, Boone C, Braun P, Cusick ME, Roth FP, Hill DE, Tavernier J, Wanker EE, Barabasi AL, Vidal M. An empirical framework for binary interactome mapping. *Nat Methods*. 2009; 6:83-90.

3. Elhabashy H, Merino F, Alva V, Kohlbacher O, Lupas AN. Exploring protein-protein interactions at the proteome level. *Structure*. 2022; 30:462-75.

4. Fields S, Song O. A novel genetic system to detect protein-protein interactions. *Nature*. 1989; 340:245-6.

5. Dunham WH, Mullin M, Gingras AC. Affinity-purification coupled to mass spectrometry: basic principles and strategies. *Proteomics*. 2012; 12:1576-90.

458   6.   Roux KJ, Kim DI, Burke B, May DG. BioID: A Screen for Protein-Protein Interactions. *Curr*

459   *Protoc Protein Sci*. 2018; 91:19 23 1-19 23 15.

461   7.   Cho KF, Branon TC, Udeshi ND, Myers SA, Carr SA, Ting AY. Proximity labeling in mammalian

462   cells with TurboID and split-TurboID. *Nat Protoc*. 2020; 15:3971-99.

464   8.   Qin W, Cho KF, Cavanagh PE, Ting AY. Deciphering molecular interactions by proximity

465   labeling. *Nat Methods*. 2021; 18:133-43.

467   9.   Deane CM, Salwinski L, Xenarios I, Eisenberg D. Protein interactions: two methods for assessment

468   of the reliability of high throughput observations. *Mol Cell Proteomics*. 2002; 1:349-56.

470   10.   Marcotte EM, Pellegrini M, Thompson MJ, Yeates TO, Eisenberg D. A combined algorithm for

471   genome-wide prediction of protein function. *Nature*. 1999; 402:83-6.

473   11.   Zhao N, Zhuo M, Tian K, Gong X. Protein-protein interaction and non-interaction predictions using

474   gene sequence natural vector. *Commun Biol*. 2022; 5:652.

476   12.   Jha K, Karmakar S, Saha S. Graph-BERT and language model-based framework for protein-protein

477   interaction identification. *Sci Rep*. 2023; 13:5663.

479   13.   Du X, Sun S, Hu C, Yao Y, Yan Y, Zhang Y. DeepPPI: Boosting Prediction of Protein-Protein

480   Interactions with Deep Neural Networks. *J Chem Inf Model*. 2017; 57:1499-510.

482   14.   Lu H, Zhou Q, He J, Jiang Z, Peng C, Tong R, Shi J. Recent advances in the development of

483   protein-protein interactions modulators: mechanisms and clinical trials. *Signal Transduct Target*

484   *Ther*. 2020; 5:213.

486   15.   Jumper J, Evans R, Pritzel A, Green T, Figurnov M, Ronneberger O, Tunyasuvunakool K, Bates

487   R, Zidek A, Potapenko A, Bridgland A, Meyer C, Kohl SAA, Ballard AJ, Cowie A, Romera-

488   Paredes B, Nikolov S, Jain R, Adler J, Back T, Petersen S, Reiman D, Clancy E, Zielinski M,

489   Steinegger M, Pacholska M, Berghammer T, Bodenstein S, Silver D, Vinyals O, Senior AW,

490   Kavukcuoglu K, Kohli P, Hassabis D. Highly accurate protein structure prediction with AlphaFold.

491   *Nature*. 2021; 596:583-9.

493   16.   Mirdita M, Schutze K, Moriwaki Y, Heo L, Ovchinnikov S, Steinegger M. ColabFold: making

494   protein folding accessible to all. *Nature Methods*. 2022; 19:679-+.

496   17.   Akdel M, Pires DEV, Pardo EP, Janes J, Zalevsky AO, Meszaros B, Bryant P, Good LL, Laskowski

497   RA, Pozzati G, Shenoy A, Zhu W, Kundrotas P, Serra VR, Rodrigues CHM, Dunham AS, Burke

498   D, Borkakoti N, Velankar S, Frost A, Basquin J, Lindorff-Larsen K, Bateman A, Kajava AV,

499   Valencia A, Ovchinnikov S, Durairaj J, Ascher DB, Thornton JM, Davey NE, Stein A, Elofsson A,

500   Croll TI, Beltrao P. A structural biology community assessment of AlphaFold2 applications. *Nat*

501   *Struct Mol Biol*. 2022; 29:1056-67.

503   18.   Yang Z, Zeng X, Zhao Y, Chen R. AlphaFold2 and its applications in the fields of biology and

504   medicine. *Signal Transduct Target Ther*. 2023; 8:115.

506   19.   Evans R, O'Neill M, Pritzel A, Antropova N, Senior A, Green T, Žídek A, Bates R, Blackwell S,

507   Yim J, Ronneberger O, Bodenstein S, Zielinski M, Bridgland A, Potapenko A, Cowie A,

Tunyasuvunakool K, Jain R, Clancy E, Kohli P, Jumper J, Hassabis D. Protein complex prediction

with AlphaFold-Multimer. In press 2021.

20.   Mariani V, Biasini M, Barbato A, Schwede T. lDDT: a local superposition-free score for comparing

protein structures and models using distance difference tests. *Bioinformatics*. 2013; 29:2722-8.

21.   Zhang Y, Skolnick J. TM-align: a protein structure alignment algorithm based on the TM-score.

Nucleic Acids Res. 2005; 33:2302-9.

22.   Basu S, Wallner B. DockQ: A Quality Measure for Protein-Protein Docking Models. *PLoS One*.

2016; 11:e0161879.

23.   Bryant P, Pozzati G, Elofsson A. Improved prediction of protein-protein interactions using

AlphaFold2 (vol 13, 1265, 2022). *Nature Communications*. 2022; 13.

24.   Yu D, Chojnowski G, Rosenthal M, Kosinski J. AlphaPulldown-a python package for protein-

protein interaction screens using AlphaFold-Multimer. *Bioinformatics*. 2023; 39.

25.   Malhotra S, Joseph AP, Thiyagalingam J, Topf M. Assessment of protein-protein interfaces in cryo-

EM derived assemblies. *Nat Commun*. 2021; 12:3399.

26.   Leman JK, Weitzner BD, Lewis SM, Adolf-Bryfogle J, Alam N, Alford RF, Aprahamian M, Baker

D, Barlow KA, Barth P, Basanta B, Bender BJ, Blacklock K, Bonet J, Boyken SE, Bradley P,

Bystroff C, Conway P, Cooper S, Correia BE, Coventry B, Das R, De Jong RM, DiMaio F, Dsilva

L, Dunbrack R, Ford AS, Frenz B, Fu DY, Geniesse C, Goldschmidt L, Gowthaman R, Gray JJ,

Gront D, Guffy S, Horowitz S, Huang PS, Huber T, Jacobs TM, Jeliazkov JR, Johnson DK, Kappel

K, Karanicolas J, Khakzad H, Khar KR, Khare SD, Khatib F, Khramushin A, King IC, Kleffner R, Koepnick B, Kortemme T, Kuenze G, Kuhlman B, Kuroda D, Labonte JW, Lai JK, Lapidoth G, Leaver-Fay A, Lindert S, Linsky T, London N, Lubin JH, Lyskov S, Maguire J, Malmstrom L, Marcos E, Marcu O, Marze NA, Meiler J, Moretti R, Mulligan VK, Nerli S, Norn C, O'Conchuir S, Ollikainen N, Ovchinnikov S, Pacella MS, Pan X, Park H, Pavlovicz RE, Pethe M, Pierce BG, Pilla KB, Raveh B, Renfrew PD, Burman SSR, Rubenstein A, Sauer MF, Scheck A, Schief W, Schueler-Furman O, Sedan Y, Sevy AM, Sgourakis NG, Shi L, Siegel JB, Silva DA, Smith S, Song Y, Stein A, Szegedy M, Teets FD, Thyme SB, Wang RY, Watkins A, Zimmerman L, Bonneau R. Macromolecular modeling and design in Rosetta: recent methods and frameworks. *Nat Methods*. 2020; 17:665-80.

27. Adeshina YO, Deeds EJ, Karanicolas J. Machine learning classification can reduce false positives in structure-based virtual screening. *Proc Natl Acad Sci U S A*. 2020; 117:18477-88.

28. Collins KW, Copeland MM, Kotthoff I, Singh A, Kundrotas PJ, Vakser IA. Dockground resource for protein recognition studies. *Protein Sci*. 2022; 31:e4481.

29. Zhang Y, Skolnick J. Scoring function for automated assessment of protein structure template quality. *Proteins*. 2004; 57:702-10.

30. Xu J, Zhang Y. How significant is a protein structure similarity with TM-score = 0.5? *Bioinformatics*. 2010; 26:889-95.

31. Ong WJG, Kirubakaran P, Karanicolas J. Poor Generalization by Current Deep Learning Models for Predicting Binding Affinities of Kinase Inhibitors. *bioRxiv*. 2023.

560   32.   Bossen C, Ingold K, Tardivel A, Bodmer JL, Gaide O, Hertig S, Ambrose C, Tschopp J, Schneider

561   P. Interactions of tumor necrosis factor (TNF) and TNF receptor family members in the mouse and

562   human. *J Biol Chem*. 2006; 281:13964-71.

564   33.   Baek M, DiMaio F, Anishchenko I, Dauparas J, Ovchinnikov S, Lee GR, Wang J, Cong Q, Kinch

565   LN, Schaeffer RD, Millan C, Park H, Adams C, Glassman CR, DeGiovanni A, Pereira JH,

566   Rodrigues AV, van Dijk AA, Ebrecht AC, Opperman DJ, Sagmeister T, Buhlheller C, Pavkov-

567   Keller T, Rathinaswamy MK, Dalwadi U, Yip CK, Burke JE, Garcia KC, Grishin NV, Adams PD,

568   Read RJ, Baker D. Accurate prediction of protein structures and interactions using a three-track

569   neural network. *Science*. 2021; 373:871-6.

571   34.   Lim Y, Tamayo-Orrego L, Schmid E, Tarnauskaite Z, Kochenova OV, Gruar R, Muramatsu S,

572   Lynch L, Schlie AV, Carroll PL, Chistol G, Reijns MAM, Kanemaki MT, Jackson AP, Walter JC.

573   In silico protein interaction screening uncovers DONSON's role in replication initiation. *Science*.

574   2023; 381:eadi3448.

576   35.   Bret H, Gao J, Zea DJ, Andreani J, Guerois R. From interaction networks to interfaces, scanning

577   intrinsically disordered regions using AlphaFold2. *Nat Commun*. 2024; 15:597.

579   36.   Danneskiold-Samsoe NB, Kavi D, Jude KM, Nissen SB, Wat LW, Coassolo L, Zhao M, Santana-

580   Oikawa GA, Broido BB, Garcia KC, Svensson KJ. AlphaFold2 enables accurate deorphanization

581   of ligands to single-pass receptors. *bioRxiv*. 2023.

583   37.   Marciano S, Dey D, Listov D, Fleishman SJ, Sonn-Segev A, Mertens H, Busch F, Kim Y, Harvey

584   SR, Wysocki VH, Schreiber G. Protein quaternary structures in solution are a mixture of multiple

585   forms. *Chem Sci*. 2022; 13:11680-95.

38.　Martin J. AlphaFold2 Predicts Whether Proteins Interact Amidst Confounding Structural

Compatibility. *J Chem Inf Model*. 2024.

39.　Teufel F, Refsgaard JC, Kasimova MA, Deibler K, Madsen CT, Stahlhut C, Gronborg M, Winther

O, Madsen D. Deorphanizing Peptides Using Structure Prediction. *J Chem Inf Model*. 2023;

63:2651-5.

40.　Pogozheva ID, Cherepanov S, Park SJ, Raghavan M, Im W, Lomize AL. Structural Modeling of

Cytokine-Receptor-JAK2 Signaling Complexes Using AlphaFold Multimer. *J Chem Inf Model*.

2023; 63:5874-95.

41.　Gao M, Nakajima An D, Parks JM, Skolnick J. AF2Complex predicts direct physical interactions

in multimeric proteins with deep learning. *Nat Commun*. 2022; 13:1744.

42.　Weeratunga S, Gormal RS, Liu M, Eldershaw D, Livingstone EK, Malapaka A, Wallis TP,

Bademosi AT, Jiang A, Healy MD, Meunier FA, Collins BM. Interrogation and validation of the

interactome of neuronal Munc18-interacting Mint proteins with AlphaFold2. *J Biol Chem*. 2024;

300:105541.

43.　Baryshev A, La Fleur A, Groves B, Michel C, Baker D, Ljubetic A, Seelig G. Massively parallel

protein-protein interaction measurement by sequencing (MP3-seq) enables rapid screening of

protein heterodimers. *bioRxiv*. 2023.

44.　Burke DF, Bryant P, Barrio-Hernandez I, Memon D, Pozzati G, Shenoy A, Zhu W, Dunham AS,

Albanese P, Keller A, Scheltema RA, Bruce JE, Leitner A, Kundrotas P, Beltrao P, Elofsson A.

Towards a structurally resolved human protein interaction network. *Nat Struct Mol Biol*. 2023;
30:216-25.

45. Humphreys IR, Pei J, Baek M, Krishnakumar A, Anishchenko I, Ovchinnikov S, Zhang J, Ness TJ,
Banjade S, Bagde SR, Stancheva VG, Li XH, Liu K, Zheng Z, Barrero DJ, Roy U, Kuper J,
Fernandez IS, Szakal B, Branzei D, Rizo J, Kisker C, Greene EC, Biggins S, Keeney S, Miller EA,
Fromme JC, Hendrickson TL, Cong Q, Baker D. Computed structures of core eukaryotic protein
complexes. *Science*. 2021; 374:eabm4805.

46. Burley SK, Bhikadiya C, Bi C, Bittrich S, Chao H, Chen L, Craig PA, Crichlow GV, Dalenberg K,
Duarte JM, Dutta S, Fayazi M, Feng Z, Flatt JW, Ganesan S, Ghosh S, Goodsell DS, Green RK,
Guranovic V, Henry J, Hudson BP, Khokhriakov I, Lawson CL, Liang Y, Lowe R, Peisach E,
Persikova I, Piehl DW, Rose Y, Sali A, Segura J, Sekharan M, Shao C, Vallat B, Voigt M, Webb
B, Westbrook JD, Whetstone S, Young JY, Zalevsky A, Zardecki C. RCSB Protein Data Bank
(RCSB.org): delivery of experimentally-determined PDB structures alongside one million
computed structure models of proteins from artificial intelligence/machine learning. *Nucleic Acids*
Res. 2023; 51:D488-D508.

47. Raschka S, Liu Y, Mirjalili V. Machine Learning with PyTorch and Scikit-Learn: Packt Publishing
Ltd; 2022.

48. Chen T, Guestrin C, editors. XGBoost. Proceedings of the 22nd ACM SIGKDD International
Conference on Knowledge Discovery and Data Mining; 2016 2016-08-13: ACM.

49. Strande S, Cai H, Tatineni M, Pfeiffer W, Irving C, Majumdar A, Mishin D, Sinkovits R, Norman
M, Wolter N, Cooper T, Altintas I, Kandes M, Perez I, Shantharam M, Thomas M, Sivagnanam S,

638  Hutton T. Expanse: Computing without Boundaries. Practice and Experience in Advanced

639  Research Computing2021. p. 1-4.

Supplemental Figures

Figure S1: Composition of active and decoy datasets. (A) For the set of actives, the distribution of DockQ scores are shown (calculated relative to the PDB structure for each complex). Complexes are included in the dataset only if their DockQ scores are at least 0.23, but most DockQ scores for these active pairings are much higher. **(B)** Compelling decoy complexes are assembled by drawing an alternate protein with high TM score relative to the components of the parental (active) complex. In most cases decoy complexes are assembled using component proteins with TM-scores of at least 0.5, corresponding to close structural matches.

655
656

Figure S2: Overview of dataset construction and evaluation. Each active complex was used to generate one compelling decoy complex. Complexes were divided into training / validation / test sets, and 5 AF2 models were built for each complex. Key differences in how the sets were constructed / evaluated are highlighted in *white*. First, the AF2 models of active complexes in the training and validation sets were filtered to keep only correctly-docked models (DockQ>0.23); by contrast, *all* models were retained in the test set with no filtering. Second, performance of the validation set was evaluated by ranking all AF2 models independently; by contrast, performance of the test set was evaluated by ranking each *complex*, using the best-scoring AF2 model for each complex.

657
658

AF2 confidence measures

- PTM score
- pIDDT
- iplDDT
- iPAE
- iPAE top ¼
- tPAE
- tPAE top ¼

Structural "counting" features

- Number of interface (IF) contacts
- Number of residues comprising the IF
- Number polar uncharged amino acids in IF
- Number nonpolar amino acids in IF
- Number of negative amino acids in IF
- Number of positive amino acids in IF
- Number of charged amino acids in IF
- Number of polar-polar contacts in IF
- Number of polar uncharged-polar uncharged contacts in IF
- Number of charged-charged contacts in IF
- Number of nonpolar-nonpolar contacts in IF
- Number of positive-negative contacts in IF
- Number of negative-positive contacts in IF
- Number of each individual amino acid type (20 features)

Rosetta energy function

- Total bound – unbound energy
- LJatr contribution to bound-unbound
- LJrep contribution to bound-unbound
- Solvation contribution to bound-unbound
- Electrostatic contribution to bound-unbound
- Lk_ball_wtd contribution to bound-unbound
- Number of interfacial hydrogen bonds
- Average LJatr of IF residues
- Average LJrep of IF residues
- Average sol of IF residues
- Average elec of IF residues
- Average fa_dun of IF residues
- Average hydrogen bonds energy of backbone side chains
- Proportion of IF secondary structure in helix
- Proportion of IF secondary structure in beta sheet
- Proportion of IF secondary structure in loop
- Interfacial buried solvent accessible surface area (bound – unbound)

Figure S3: List of 57 total features considered when training PPIscreenML. A list of features extracted from the structural models are shown and grouped into three categories: features from AF2 confidence measures, structural "counting" features extracted using the python package Biopandas, and features from the Rosetta energy function.

Figure S4: Comparisons of different machine learning classifiers. ROC plots for classifiers built using different machine learning frameworks (each uses all 57 features).

Figure S5: Feature reduction for PPIscreenML. Sequential backwards selection was used to characterize models with diminishing numbers of features. Performance of each candidate model was evaluated on the validation set (drawn from the training set). The vertical dashed line indicates the model selected for PPIscreenML (7 features).

Figure S6: PPIscreenML performance on models generated with AF-ptm. (A) ROC curve of PPIscreenML and pDockQ tested on models built with AF-ptm. iPTM is not included because it is not available for this version of AF. (B) DockQ distribution for actives in the test set. (C) Among actives that were incorrectly classified by PPIscreenML as "not interacting", most were mis-docked by AF-ptm.

Figure S7: PPIscreenML performance on models generated with AF-multimer version 2.2.
(A) ROC curve of PPIscreenML and pDockQ tested on models built with **AF-multimer-2.2**.
(B) DockQ distribution for actives in the test set. **(C)** Among actives that were incorrectly classified by PPIscreenML as "not interacting", most were mis-docked by AF-multimer-2.2.

Figure S8: Overlaid histogram of total sequence length between actives and decoys. The method we describe for building compelling decoy complex does exhibit a slight bias for building decoys pairs from component proteins larger than the starting template. This arises from the use of TM-align to define structural analogs, because large query proteins are slightly more likely to yield high scores than small query proteins (for a given template protein). This artifact can allow a model to "cheat" if it includes any features that can serve as a proxy for the total number of residues in a model; accordingly, we ensured that no such features were included in developing PPIscreenML. Importantly, this artifact does not affect the composition or structural features of the generated decoy complexes, which are not systematically different from the active complexes.