Eye-movement artifact correction in infant EEG

Diksha Srishyla[a,b,c,d], Sara Jane Webb[e], Mayada Elsabbagh[a], Christian O'Reilly[a,b,c,d], The BASIS Team[f]

[a]Montreal Neurological Institute, McGill University, Montreal, Quebec, Canada
[b]Computer Science and Engineering, University of South Carolina, Columbia, South Carolina, USA
[c]Artificial Intelligence Institute, University of South Carolina, Columbia, South Carolina, USA
[d]Carolina Autism and Neurodevelopment Research Center, University of South Carolina, Columbia, South Carolina, USA
[e]Center on Child Health, Behavior and Development, Seattle Children's Research Institute, Seattle, Washington, USA
[f]Centre for Brain and Cognitive Development, London, UK

Abstract

Background

Independent Component Analysis (ICA) is a well-established approach to clean EEG and remove the impact of signals of non-neural origin, such as those from muscular activity and eye movements. However, evidence suggests that ICA removes artifacts less effectively in infants than in adults. This study systematically compares ICA and Artifact Blocking (AB), an alternative approach proposed to improve eye-movement artifact correction in infant EEG.

Methods

We analyzed EEG collected from 50 infants between 6 and 18 months of age as part of the International Infant EEG Data Integration Platform (EEG-IP), a longitudinal multi-study dataset. EEG was recorded while infants sat on their caregivers' laps and watched videos. We used ICA and AB to correct for eye-movement artifacts in the EEG and calculated the proportion of effectively corrected segments, signal-to-noise ratio (SNR), power-spectral density (PSD), and multiscale entropy (MSE) in manually selected segments with and without eye-movement artifacts.

Results

On the one hand, the proportion of effectively corrected segments indicated that ICA corrected eye-movement artifacts (sensitivity) better than AB. SNR and PSD indicated that both AB and ICA correct eye-movement artifacts with equal sensitivity. MSE gave mixed results. On the other hand, AB caused less distortion to the clean segments (specificity) for SNR, PSD, and MSE.

Conclusions

Our results suggest that ICA is more sensitive (i.e., it better removes artifacts) but less specific (it distorts clean signals) than AB for correcting eye-movement artifacts in infant EEG.

Keywords: Independent Component Analysis, Artifact Blocking, Electroencephalogram, Eye-Movement Artifact, Infants

---

1. Introduction

EEG recordings contain high amounts of signals unrelated to cortical processing, such as muscular and ocular artifacts. This problem is particularly acute with recordings from infants, which are often not long enough for well-established approaches such as Independent Component Analysis (ICA) to work effectively [1]. Depending on the research question, a minimum recording length of 3.2 minutes has been suggested to apply ICA [2]. Yet, collecting >3.2 minutes of usable EEG is often challenging in infants due to movement and emotional state. The length is specified by $30 * N^2/f_s$, where N is the number of channels and f_s is the sampling frequency [2].For example, for a recording using 128 channels with a sampling rate of 500 Hz, 983.04 s would be required, an expectation often unrealistic for infant EEG recording. Further, ICA may not identify components related to eye movement in infant EEG [1].

Significant progress has been made in developing preprocessing pipelines addressing these issues. For example, the Maryland Analysis of Developmental EEG (MADE) pipeline removes residual eye-movement artifacts by first epoching the continuous data, then rejecting any epochs where the electrooculogram (EOG) channels exceed a certain voltage threshold [3]. Epochs are then examined and rejected if more than 10% of the EEG channels exceed

a fixed voltage threshold. For the remaining epochs, EEG channels exceeding this threshold are interpolated.

The Lossless pipeline from the EEG Integrated Platform (EEG-IP-L) applies a voltage-based criterion to identify periods where the data would not be corrected effectively by ICA due to non-stationary artifacts. It also tests for invalid channels based on extreme correlations between nearest neighbors and ensures a robust re-referencing on a consistent average reference regardless of the recording montage. It then applies multiple ICA decompositions, followed by an automated classification of components as neural or artifactual according to ICLabels – a classifier for independent components trained on adult data [4] – and an optional visual confirmation. This procedure for artifact removal is compatible with short recording durations, as is often the case with infant EEG, and can process epoched or continuous EEG alike [5]. This pipeline has recently been refactored and ported to Python to increase its usability and user-friendliness [6].

The Newborn EEG Artifact Removal (NEAR) pipeline relies on Artifact Subspace Reconstruction (ASR), an approach designed originally for mobile adult EEG. It detects invalid channels and adapts ASR to infant EEG by including a bad-channel detection, a necessary step for ASR effectiveness. ASR requires users to specify a parameter called 'k' and can either correct or remove artifacts. NEAR calibrates these parameters for effective artifact removal in infant EEG. This approach is more effective than ICA in removing artifacts with variable patterns of scalp topography and temporal dynamics [7]. The HAPPE (Harvard Automated Processing Pipeline for Electroencephalography) pipeline uses wavelet-thresholding ICA to mitigate distortions to spectral power estimates caused by ICA [2]. However, only a subset of channels can be used in high-density recordings (e.g., 128 channels) if the recording is not long enough for reliable ICA decomposition. This length is specified by the formula $30 * N^2/f_s$, where N is the number of channels and f_s is the sampling frequency [2]. For example, for a recording with a sampling rate of 500 Hz, 983.04 s would be required, an expectation often unrealistic for infant EEG recording.

Efforts have been also made to adapt the ICLabels classifier to infant EEG for automatic independent component labeling. The ADJUST classifier automatically identifies independent components by simultaneously calculating multiple features associated with the topographical and spectral properties of eye-movement artifacts [8]. However, this classifier is designed to work with event-related EEG paradigms, making it incompatible with continuous EEG

processing. The Multiple Artifact Rejection Algorithm (iMARA) successfully classifies components into neural and artifactual categories when applied to both event-related and continuous (e.g., naturalistic) EEG recordings from infants [9].

As can be concluded from this overview, many pipelines rely on ICA for artifact identification and correction. As this approach has not been optimized for short infant EEG sessions, it is unclear to what extent ICA distorts the neural signals in EEG. A previous study suggested that Artifact Blocking (AB) distorts less clean EEG than ICA while effectively correcting for high amplitude artifacts [10]. However, this demonstration was qualitative and used only one EEG recording. In this study, we compare ICA with AB to quantitatively benchmark the performance of the two methods. We analyze resting state EEG recordings from 50 typically developing infants by manually annotating saccadic eye-movement artifacts, applying ICA and AB, and comparing the effectiveness of these algorithms based on i) visual inspection, ii) signal-to-noise ratio (SNR), iii) power spectral density (PSD), and iv) multiscale entropy (MSE) [10]. With this investigation, we aim to provide critical empirical evidence to help researchers decide which artifact correction method to use for future studies.

2. Methods

2.1. Participants

Recordings from the International Infant EEG Data Integration Platform (EEG-IP) were used for our analysis [5, 11]. EEG-IP includes EEG recordings from longitudinal infant-sibling studies conducted separately at two sites, London and Seattle [12, 13, 14, 15, 16]. EEG was recorded at ages 6-7 months and 12-14 months at both sites and 18 months in Seattle. Each site contributed raw EEG and behavioral data to this repository. Participants in these studies were grouped as having an elevated likelihood of ASD if they had an older sibling diagnosed with ASD or as controls with a typical likelihood of ASD if they did not. The repository comprises 420 recordings from 191 (94 females) infants.

For this study, we used recordings from the comparison group to benchmark these algorithms on a sample representative of the overall infant population. We selected randomly 50 recordings for analysis. This sample was considered sufficient given that differences between methods tend to be reliable and systematic. Further, given this sample size, we can expect to detect

Site	6 months (male)	12 months (male)	18 months (male)
Seattle	14 (11)	16 (8)	8 (6)
London	12 (11)	0	0

Table 1: Number of EEG recordings included in analysis by age, site and sex

80% of the time with a 95% confidence an effect of 0.40 (Cohen's d; paired t-test), which corresponds to an effect size small (0.2) to medium (0.5) [17]. We argue this is reasonable because very small effect sizes would mean that the difference between the approaches would be negligible in practice, so we are mostly interested in effect sizes that are at least medium.

2.2. Recordings and pre-processing

EEG was recorded with an EGI 128-channel Hydrocel net while infants sat on their caregivers' laps and watched videos of brightly colored toys producing sounds or an adult woman singing nursery rhymes.

Open-source software was used to preprocess, standardize the data, and minimize differences across studies/sites. Specifically, we adopted the Brain Imaging Data Structure (BIDS) extension to EEG [18, 19] and used the EEG-IP Lossless Pipeline to standardize the preprocessing [5]. This pipeline includes a semi-automatic systematic preprocessing procedure to identify unreliable EEG signals and build comprehensive data quality annotations. It first addresses differences across datasets by executing a *staging script* specific to each project, including procedures for the co-registration of electrode coordinates to a common shared head surface, a robust average reference, and a 1Hz high-pass and notch filter (London: 49-51Hz; Seattle: 59-61Hz). The staging scripts then flag noisy time periods and channels based on consistently outlying variance values to make files more comparable for later stages of the pipeline. Following the staging scripts, the pipeline assesses signal quality using confidence intervals of signal properties within each file to flag unusual time periods and channels. Each time a problematic channel is flagged, the data are re-referenced using an average reference computed using channels interpolated on the shared co-registered head surface. The standard average reference ensures that differences in channel distributions (e.g., a 128-channel EGI net covers head regions not covered by less comprehensive montages) do not systematically impact the properties of the average reference. Following channel assessment, a robust Adaptive Mixture Independent Component Analysis (AMICA) procedure [20] is performed, and

components are automatically classified as being or not of neural origin. The automatic classification relies on a crowd-sourced database (ICLabels) of labeled components, including 200,000 independent components from more than 6000 EEG recordings. A manual quality control step follows the automated classification.

After the preprocessing, the EEG recordings retaining enough signal were post-processed and assessed for comparability [11]. The proportion of time removed from data due to artifact or technical issues (extreme voltage variance, low correlation with neighboring channels, artifact identified by ICA decomposition) was similar across sites. The average channel retention (range: 77%-82%), the spatial variance in the retained and rejected independent components, and the power spectrum profile were also similar across sites.

2.3. Annotations of segments with eye-movement artifact and clean EEG

2.3.1. Eye-movement segments

We used an interactive plot generated with MNE-Python (version 1.3.1) [21, 22] to manually annotate the EEG recordings for clean and eye-movement segments (Fig. 1). We selected segments with eye-movement artifacts (orange windows in Fig. 1) based on previous experience and reference images from prior studies [23]. These annotations were made using the channels that are most susceptible to eye-movement artifacts in the EGI 128-channel Hydrocel Geodesic net (E1, E8, E14, E21, E32, E125, E126, E127, and E128). Video recordings or direct measurements of eye movements (i.e., eye-tracking) were not available. To verify the accuracy of the annotated eye-movement windows, we plotted scalp topographic plots of amplitude. The amplitude for ocular artifacts is expected to be higher in the frontal regions [24], with a left-to-right polarity inversion in the case of lateral saccades. The final selection was based on both temporal and topological profiles.

2.3.2. Clean segments

We used an adult EEG atlas and a guide for labeling independent components corresponding to various artifact types and brain activity [25]. We evaluated clean segments by also considering the activity on channels Fz (E11), Cz, Pz (E62), and Oz (E75). Segments without discernible artifacts were marked as clean (blue windows in Fig. 1). We followed the recommendation from a previous study evaluating artifacts in pediatric EEG [24] and included a minimum of 30s of clean segments per recording.

Figure 1: Interactive window used to annotate eye-movement segments (light orange sections) and clean segments (blue sections). Channels used to annotate eye movements are indicated by the blue lines, while clean segment reference channels are indicated by the black lines.

2.4. ICA-based artifact correction

ICA can be used to correct artifacts but depends on three assumptions: i) Signals (S) captured by the electrodes reflect multiple linearly mixed and statistically independent components (sources) of brain activity and artifacts; ii) the number of channels is greater than the number of components; iii) there are negligible volume conduction delays [26]. The linear model for S obtained through ICA is given as:

$$X = AS \tag{1}$$

where X stands for the linear mixture of signals s_i in $S = (s_1, s_2, s_3, \ldots, s_n)$, and A is the unknown mixing matrix. S is approximated by finding the unmixing matrix A^{-1} (see [20] for details):

$$S = A^{-1}X \tag{2}$$

ICA was computed and visually validated before this study as part of the EEG-IP project [11, 5]. All components indicative of artifacts (not specific to eye movements) were selected for rejection.

2.5. AB-based artifact correction

The AB algorithm relies on a threshold θ_{opt} to distinguish between brain signals and high amplitude artifacts. Since this threshold likely depends on recordings and subjects (e.g., due to differences in electrode impedance or head tissue conductivities causing systematic biases in EEG amplitude), we developed a procedure to calculate the optimal threshold θ_{opt}. We define this threshold as the voltage at which artifacts due to eye movements are maximally removed while minimizing distortion to clean segments. Before starting the calculation, we examined clean and eye-movement segments for each recording and chose only channels with sufficient data (i.e., more than 30 seconds of clean EEG) for analysis. For each channel, the following procedure was followed:

1. The maximum amplitude in each annotated segment (eye-movement and clean) was calculated. These maximum amplitudes were used to construct a range of amplitudes as thresholds to be tested. The range consisted of all thresholds, in increments of 1 μV, from the lowest to the highest maximum amplitude recorded across channels.

2. For each threshold, the mean absolute error (MAE) was calculated for each annotation as follows:

$$e_{tik} = \frac{1}{N_{ik}} \sum_{j=1}^{N_{ik}} |x_O^{ijk} - x_{AB}^{ijk}| \tag{3}$$

   where e_{tik} is the total error, t is the threshold index, i denotes the index of the annotation, k identifies the channel, N_{ik} stands for the number of time samples in annotation i for channel k, j is the time sample index, and x_O and x_{AB} represent the amplitude of the original and the AB-processed signal, respectively.

3. The average MAE across all clean and eye-movement segments was calculated.

4. The average MAE for each type of segment was normalized to be on the same scale (Fig. 2A):

$$\widetilde{e_{tik}} = \frac{e_{tik} - \min_{t} e_{tik}}{\max_{t} e_{tik} - \min_{t} e_{tik}} \tag{4}$$

5. The total error (E_{tk}) at each threshold takes into account the average MAE (e_{tik}) for segments with and without artifacts and is defined as follows

$$E_{tk} = 1 - \frac{1}{N_{Ek}} \sum_{i\epsilon\Theta_{Ek}} \widetilde{e}_{tik} + \frac{1}{N_{Ck}} \sum_{i\epsilon\Theta_{Ck}} \widetilde{e}_{tik} \tag{5}$$

where Θ_{Ek} and Θ_{Ck} stand for the set of segments with eye movements and clean EEG, respectively, and N_{Ek} and N_{Ck} stand for the number of segments in these two sets. Note that a large "error" for eye-movement segments is desirable (i.e., the cleaned signals should be different than the raw signals) whereas a small error is desirable for the clean segments (i.e., the artifact rejection should not distort the signals in such epochs), hence the subtraction of the former and the addition of the latter type of errors. Also, note that an equal weight for the contribution of both types of errors is implicitly used by not further weighting these two types of errors.

6. The optimal threshold for the channel k corresponds to the minimum of all total errors calculated (Fig.2B):

$$\theta_{opt\_k} = \operatorname*{argmin}_{t} E_{tk} \tag{6}$$

7. Since the original algorithm uses a common threshold for all channels, the optimal threshold for the recording was calculated as the average optimal threshold of all selected channels using

$$\theta_{opt} = \frac{1}{N_k} \sum_{k=1}^{N_k} \theta_{opt\_k} \tag{7}$$

where N_k stands for the number of channels used for threshold evaluation.

Given a two-dimensional EEG matrix X of sizes $n \times T$, with n being the number of channels and T being the number of time points, a matrix Y is constructed from X by zeroing values exceeding θ_{opt} [27, 28]. Then, a blocking matrix B_{opt} is constructed as follows:

$$B_{opt} = \operatorname*{argmin}_{B} \mathbb{E} \left[\|Bx_t - y_t\|_2^2 \right] \tag{8}$$

Figure 2: A) Normalized MAE across all tested thresholds for channel E1 in a typical recording. B) The optimal threshold for this channel is 17 μV, i.e., the threshold corresponding to the minimum of all total errors calculated for this channel, θ_{opt_k}.

where x_t and y_t refer to the t^{th} column of matrices X and Y, respectively, and $\mathbb{E}$ stands for the expectation operator. Additional details on the calculation of B_{opt} are available in [29].

The smoothing matrix B_{opt} utilizes information from the reference matrix Y indicating the EEG samples exceeding θ_{opt}. It 'blocks' these samples while preserving the samples not exceeding θ_{opt}.

We used the MATLAB script for AB shared by the original authors [10]. We exported to Python the results from MATLAB for comparison with ICA. Portions of code written in MATLAB were integrated into the Python pipeline by running them from Python using the MATLAB engine.

2.6. Performance metrics

2.6.1. Proportion of segments effectively corrected by AB and ICA

For each epoch with eye movement, we selected the channel with the most visible artifacts and categorized the application of AB and ICA as either effective or insufficient (i.e., under-correction). The rater was blind to the signal origin (i.e., from AB or ICA). To make this annotation procedure

systematic and efficient, we implemented a custom interactive window displaying the corresponding time series and accepting sequential annotations through keystrokes. The following procedure was used:

1. For each annotated eye-movement segment, time series plots of the original signal, signal corrected with ICA, and signal corrected with AB were overlaid.
2. For each segment, AB- and ICA-corrected traces were randomly assigned a color (red or blue).
3. The red and blue plots were rated as effectively or insufficiently corrected for an eye-movement artifact. The authors (DS and COR) discussed various examples and agreed on criteria for effective correction vs under-correction. An epoch was rated as under-corrected if an eye-movement artifact was still discernible on the plot after correction.
4. At the end of this procedure, blinded scores were automatically associated with their true labels (i.e., ICA or AB) based on a log of the random draws. The proportions of segments where AB and ICA effectively or insufficiently corrected for eye movements were calculated.

We did not manually annotate clean segments as the ideal outcome is known in this case (i.e., it is identical to the original signal since these segments are considered free from artifacts). Any deviation from the original signal is considered an over-correction, and this deviation can be measured quantitatively, e.g., through the SNR. We hypothesized that AB and ICA would correct equally effectively for eye-movement artifacts, i.e., $Pe_{AB} \approx Pe_{ICA}$, where Pe stands for the proportion of effectively corrected eye-movement segments.

2.6.2. Signal-to-noise ratio (SNR)

The SNR measures the relative amount of noise present in a signal. In our calculations, the signal refers to the processed EEG after applying a cleaning algorithm (i.e., AB or ICA) while noise refers to the portion of EEG removed during preprocessing. This definition implies that large SNRs are desirable for clean segments, while small SNRs are desirable for segments with artifacts. We calculated SNR for each segment by first calculating the root-mean-square (RMS) for the segment processed with AB or ICA, using (9) with y_i being the processed segment (signal) and n the number of samples in the segment. Then, we calculated the RMS for the noise using (10) with x_i being the original, unprocessed segment.

$$RMS_{Signal} = \sqrt{\frac{1}{n}\sum_{i=1}^{n} y_i^2} \tag{9}$$

$$RMS_{Noise} = \sqrt{\frac{1}{n}\sum_{i=1}^{n} (y_i - x_i)^2} \tag{10}$$

Finally, the SNR was calculated as the quotient of the two RMS values, using a base 10 logarithmic scale and multiplying by 10 to express this ratio in decibels (dB), as is usual:

$$SNR = 10 * log_{10}\left(\frac{RMS_{signal}}{RMS_{noise}}\right) \tag{11}$$

SNR calculations were implemented in Python. An SNR of 0 dB indicates signal and noise RMS values of equal amplitude, whereas a value of $10 * 2 = 20$ dB indicates a signal $10^2 = 100$ times as large as the noise. Since we defined the noise as what is removed from the raw data by the artifact correction algorithm, a large "noise" (hence a low SNR) is desirable when assessing the performance of the algorithm on epochs with artifacts, while this "noise" would ideally be zero (hence large, theoretically infinite, SNR) for epochs without artifacts, indicating that the algorithm did not distort clean signals. We hypothesized that AB and ICA would correct equally effectively for eye-movement artifacts ($SNR_{AB} \approx SNR_{ICA}$), but AB would cause less distortion to the clean segments compared to ICA ($SNR_{AB} > SNR_{ICA}$).

2.6.3. Power spectral density (PSD)
The PSD measures the energy contained in a signal at different frequencies. We calculated this value from averaged-reference EEG for all segments, channels, and recordings. For each recording, we cropped individual segments and concatenated them into separate EEG matrices for clean and eye-movement segments. We used the *psd_welch* function in MNE-Python [22] to estimate the spectrum with the Welch method. In short, a Hamming window was applied on the segmented windows with 50% overlap. Then, for each channel, we averaged the periodograms calculated for every window. PSD values were log_{10}-transformed to account for skewed distributions. For our analyses, we computed the total PSD power for the following frequency

bands: delta (2-4 Hz), theta (4-6 Hz), low alpha (6-9 Hz), high alpha (9-13 Hz), beta (13-30 Hz), and gamma (30-48 Hz) [30].

We hypothesize that AB and ICA will correct equally effectively for eye-movement artifacts and, consequently, that we will observe an equivalent change in PSD for both algorithms with respect to the original signal (i.e., $|PSD_{ICA} - PSD_{original}| \approx |PSD_{AB} - PSD_{original}|$). We also hypothesize that AB will cause less distortion to the clean segments compared to ICA, which will be visible as a lower change in PSD (i.e., $|PSD_{ICA} - PSD_{original}| > |PSD_{AB} - PSD_{original}|$).

2.6.4. Multiscale Entropy (MSE)

MSE is a non-linear measure of signal complexity. We calculated MSE using the *entropy_multiscale* function from the Python neurokit2 package [31]. The calculation first coarse grains the EEG signal for multiple scales [32]:

$$y_j^{(\tau)} = \frac{1}{\tau} \sum_{i=(j-1)\tau+1}^{j\tau} x_i, 1 \leq j \leq \frac{N}{\tau} \tag{12}$$

where $y = \{y_1, ..., y_j, ..., y_N\}$ is the coarse-grained time series, τ is the scale factor, and $x = \{x_1, ..., x_i, ..., x_N\}$ is the original signal. We calculated the number of scales per signal using the following formula:

$$\tau_{max} = \frac{N}{m + 10} \tag{13}$$

where N is the length of the signal. The m coefficient is called the embedding dimension, and it refers to the number of consecutive time points accounted for in the equation of sample entropy. An examination of entropy using cardiac and respiratory data found that an $m = 2$ or 3 yielded optimal results [33]. Using $m = 2$, we calculated the sample entropy [33, 34] for the coarse-grained signal at each scale using the following equation:

$$SampEn(m, r, N) = -log \left(\frac{\sum_{i=1}^{N-m} \sum_{j=1,j\neq i}^{N-m} a_{ij}}{\sum_{i=1}^{N-m} \sum_{j=1,j\neq i}^{N-m} b_{ij}} \right) \tag{14}$$

where

$$a_{ij} = \begin{cases} 1 & if \quad d\left(x_{m+1}(i), x_{m+1}(j)\right) < r \\ 0 & else \end{cases} \tag{15}$$

$$b_{ij} = \begin{cases} 1 & if \quad d\left(x_m(i), x_m(j)\right) < r \\ 0 & else \end{cases} \tag{16}$$

with $d(x,y) = \max_i(|x_i - y_i|)$ is the Chebyshev distance between time series x and y, and $x_m(i)$ is a segment of the signal x defined as the time series $\{x_i, x_{i+1}, x_{i+1}, ..., x_{i+m-1}\}$. The factor r is known as the tolerance, and it limits the distance between the two points x and y. Based on tests with heart rate and neural data, an r value between 0.1 and 0.25 times the standard deviation of the data is recommended. We calculated MSE as the sum of the sample entropy across all scales and focused on its value in ten channels well-distributed across the scalp (Fig.3).

Figure 3: EGI 128-channel Hydrocel sensors net. Sensors circled in red were used for multiscale entropy analyses.

As for the other metrics, we hypothesize that an equivalent efficiency of AB and ICA for artifact correction will be reflected in similar changes in MSE for eye-movement segments (i.e., $|MSE_{AB} - MSE_{original}| \approx MSE_{ICA} - MSE_{original}|$), but that a lesser distortion from AB will result in $|MSE_{AB} - MSE_{original}| < |MSE_{ICA} - MSE_{original}|$ for clean segments.

2.7. Statistical analyses

To compare the difference in proportions of under-corrected and effectively corrected artifacts for each algorithm, we performed a McNemar's test for difference in proportions. We used the non-parametric Wilcoxon signed-rank test to determine the statistical significance of differences in means between artifact correction methods for SNR, PSD, and MSE. A cluster-based permutation test using the physical layout of the EEG electrodes to build an adjacency matrix was applied to correct for multiple comparisons. We set a cluster forming threshold at t=434, corresponding to an alpha=0.05 and n=50 for the Wilcoxon signed rank distribution [35]. We computed 1000 random permutations of data between processed (AB or ICA) and original signals. We defined clusters of SNR values as groups of tests exceeding the significance threshold in the channel space, yielding 129 comparisons. For PSD, we defined clusters in the channel and frequency band space (129 x 6 comparisons), while we defined them in the channel and scale space for MSE (129 x 20 comparisons). We used the Python libraries StatsModels and SciPy [36, 37] for statistical analyses and MNE-Python [22] for cluster-permutation tests.

3. Results

We compared eye-movement artifact removal and clean segment preservation by AB and ICA based on the proportion of eye-movement segments effectively corrected, SNR, PSD and MSE.

3.1. Proportion of eye-movement segments effectively corrected by AB and ICA

We performed a blinded comparison of the level of correction achieved by AB and ICA for eye-movement segments. To compare the difference in proportions of under-corrected and effectively corrected artifacts by each algorithm, we performed a two-tailed McNemar's test for difference in proportions. In segments with eye movements, there was a lower proportion of instances where AB (0.34 ± 0.02) effectively corrected for ocular artifacts compared to ICA (0.54 ± 0.02). This difference was statistically significant ($\chi^2 = 32.52$, $df = 1$, $p = 1.182 \times 10^{-8}$). These findings suggest that ICA corrects eye-movement artifacts better than AB, not supporting our prediction of equal effectiveness of AB and ICA for artifact correction.

3.2. SNR

We calculated the SNR in clean and eye-movement segments to assess the efficacy of ICA and AB in the time domain. In both cases, the SNR increased more for AB than ICA (Fig. 4). The difference is most pronounced in the left frontal, central, and right-posterior regions. To compare the SNR following AB and ICA processing, we performed a two-tailed Wilcoxon signed-rank test followed by a cluster-based permutation test. We found one significant cluster including all 128 channels ($p < 0.001$, permutation test, family-wise error controlled) for both segment types. These trends suggest that ICA corrects better than AB for eye movements (i.e., stronger artifact suppression in ICA increases the "noise" denominator, reducing the SNR). However, the higher SNR for AB in clean segments indicates that this algorithm causes less distortion for EEG compared to ICA (i.e., less artifact removal in artifact-free segments is associated with less signal distortion and higher SNR). Our findings do not support our first prediction that the SNR following ICA and ICA would be similar in the eye-movement segments. However, they support our second prediction that the SNR would be greater after AB than ICA in the clean segments.

Figure 4: Scalp topographic plots of average SNR following artifact correction using AB and ICA, for segments with eye movements and clean EEG.

3.3. PSD

To assess the efficacy of AB and ICA in the frequency domain, we compared the change in PSD associated with AB and ICA. We calculated $\log_{10}$PSD in the eye-movement and clean segments for the original, AB-corrected, and ICA-corrected signals across different frequency bands between 2 and 48Hz. For each recording, clean and eye-movement segments were concatenated before calculating $\log_{10}$PSD. The average length of concatenated segments was 3.29s for eye movements and 27.37s for clean EEG.

Fig. 5 shows the difference in $\log_{10}$PSD between the original and the corrected signals for both segment types. In the eye-movement segments, except for the gamma band, a qualitatively similar change in PSD was observed across all frequency bands, in keeping with our hypothesis that both methods would perform equally. However, a cluster-based permutation test between $log_{10}|PSD_{ICA} - PSD_{original}|$ and $log_{10}|PSD_{AB} - PSD_{original}|$ revealed a significant cluster ($p < 0.001$, permutation tests, family-wise error controlled) containing 86 electrodes distributed across the scalp and all six frequency bands.

For clean segments, $log_{10}|PSD_{ICA} - PSD_{original}|$ in the beta and gamma bands is greater than $log_{10}|PSD_{AB} - PSD_{original}|$. This observation suggests that ICA distorts more clean segments than AB, as per our prediction. The corresponding cluster-based permutation test revealed a single significant cluster ($p < 0.001$, permutation tests, family-wise error controlled) containing 107 electrodes across the scalp and all six frequency bands.

Figure 5: Scalp topographic plots depicting the differences in $\log_{10}$PSD between processed and original signals for both segment types. $\log_{10}$PSD values have been calculated by averaging across 50 participants for each frequency band and channel.

3.4. MSE

In eye-movement segments, $|MSE_{ICA} - MSE_{original}|$ and $|MSE_{AB} - MSE_{original}|$ are similar in channels F8, Fp1, Oz, and T6. There are variations by scale, in the other channels (Fig. 6). These findings partially support our prediction that entropy would change by a similar amount following correction by both algorithms. We use a cluster-based permutation to compare between $|MSE_{ICA} - MSE_{original}|$ and $|MSE_{AB} - MSE_{original}|$ and found a single significant cluster ($p < 0.001$, permutation tests, family-wise error controlled) containing 32 electrodes distributed across the frontal and central regions and all 8 scales.

In the clean segments, all channels show that $|MSE_{AB} - MSE_{original}|$ is lower than $|MSE_{ICA} - MSE_{original}|$. These findings support our hypothesis that AB would cause less distortion in the clean segments compared to ICA.

The corresponding cluster-based permutation test found one significant cluster ($p < 0.001$, permutation tests, family-wise error controlled) containing all 128 electrodes and all 20 scales.

Figure 6: Scale-wise change in MSE following correction by ICA and AB for eye-movement and clean segments. Shaded regions indicate the 95% confidence intervals.

4. Discussion

This study applied AB and ICA on infant EEG to compare their effectiveness for removing eye-movement artifacts without distorting neural signals. The proportion of effectively corrected segments indicated that ICA corrected eye-movement artifacts better than AB, that is, ICA has better sensitivity to eye-movement artifacts. SNR and PSD suggested that AB and ICA correct

for eye-movement artifacts effectively, i.e., both are equally sensitive, while MSE results were mixed. Results suggests that AB has better specificity (causes less distortion to clean segments) than ICA, as assessed via SNR, PSD, and MSE.

Our results on the proportion of effectively corrected segments are contrary to a prior qualitative comparison of AB and ICA that found AB to be more effective than ICA for removing eye-movement artifacts in infant EEG [29]. However, since this previous study relied only on one recording, results from that prior study are likely unreliable.

In agreement with the expectation for the eye-movement artifacts to be dominant in the frontal regions, the amount of artifact correction performed by both algorithms depended on the regions of the scalp, with lower SNR (i.e., more artifacts removed) in frontal channels than in central, parietal, and temporal channels. Many studies evaluating ICA and other ocular artifact removal algorithms have calculated the SNR on simulated rather than real EEG to benefit from a known ground truth about the composition of the signal and noise. While a comparison with real EEG is essential because of its ecological validity, simulations provide complementary evidence by characterizing how well the algorithm performs according to the ground truth about the (simulated) brain activity and eye activity [38]. A potential next step to strengthen our analyses is to compare AB and ICA using simulated EEG generated using ocular artifacts extracted from a real dataset. Simulated recordings could be generated by extracting segments of eye artifacts from EEG recordings [39].

Due to differences in definitions of SNR, values from prior studies are not directly comparable with those reported here [40]. We also believe this study to be the first to calculate the difference in MSE between the original and corrected versions of eye-movement artifact segments.

PSD is one of the metrics most commonly evaluated in studies assessing the performances of artifact removal algorithms on real EEG. The change in PSD following ICA in the eye-movement segments was notable in frontal channels across all frequencies. The difference was approximately $1-1.5\mu V^2/Hz$, a value close to previous results in adults [38]. However, we also found a noticeable change in power in the beta and gamma bands for frontal channels in clean EEG, as opposed to previous reports [41]. The reduction in power at these higher frequencies may be related to components associated with other sources of noise, such as muscle movement [42]. Unfortunately, the manual rejection of independent components for cleaning the signals was done before

this work and was not specific to EOG artifacts.

This study aims to provide critical information to support researchers in deciding between ICA and AB for artifact removal. Using these four metrics, we have provided a comprehensive comparative analysis of the performance of these two approaches in terms of their effectiveness at removing eye-movement artifacts (sensitivity) and their ability not to distort clean signals (specificity).

Our study is limited by the absence of an independent measure of eye movements. Hence, manual annotations of segments with eye movements were performed based on templates of the characteristic appearance of these artifacts. Moreover, only one rater performed these annotations. The visual inspection used to calculate the proportion of effectively corrected eye-movement segments was discussed and validated between the authors (DS and COR), and we iteratively improved the annotation process. However, we did not comprehensively duplicate the scoring and computed inter-rater agreement. Besides using multiple raters, a future study could use concurrent EEG and eye-tracking to provide a more objective classification.

5. Conclusion

Our results suggest that ICA might correct better for eye-movement artifacts than AB, while AB causes less distortion to clean EEG than ICA in infant EEG. Our analysis yielded some new insights on methods for benchmarking artifact removal algorithms. Follow-up from future work is needed to identify more definitively what approach performs best overall, for infant EEG.

Future work should evaluate AB and ICA using infant EEG with eye-tracking or involve multiple raters for artifact annotation. Further, since we found ICA to be more sensitive (better reject artifacts) and AB to be more specific (distort less non-artifact signals) to eye-movement artifacts, automating the assessment of artifact rejection performance in terms of these two metrics (i.e., sensitivity and specificity) and computing these performances across a range of decision threshold could allow computing receiver-operating characteristics (ROC) curves. Such curves could identify more definitively what approach performs best overall, for example, by comparing the area under the ROC curve for these two approaches.

6. Acknowledgements

We want to thank Drs. Julie Scorah and Tim Smith for reviewing drafts of this work. We want to acknowledge James Desjardins, Scott Huberty, and colleagues at Dr. Elsabbagh's lab for their feedback on the preliminary results. We would like to thank Professor Joseph Rochford for help with statistical analyses. EEG-IP was supported by funding from Brain Canada and FRQ-S. Christian O'Reilly and Diksha Srishyla are supported through startup funds from the University of South Carolina. Diksha Srishyla was also supported by the Maysie Macsporran fellowship from the Faculty of Medicine of McGill.

Original data acquisition was funded by NIH P50 HD055782 (Webb) and the UK Medical Research Council (Johnson).

References

[1] Valdas Noreika et al. "14 challenges for conducting social neuroscience and longitudinal EEG research with infants". In: *Infant Behavior and Development* 58.Art. 101393 (2019).

[2] Laurel J Gabard-Durnam et al. "The Harvard Automated Processing Pipeline for Electroencephalography (HAPPE): standardized processing software for developmental and high-artifact data". In: *Frontiers in neuroscience* 12 (2018), p. 97.

[3] Ranjan Debnath et al. "The Maryland analysis of developmental EEG (MADE) pipeline". In: *Psychophysiology* 57.6 (2020), e13580.

[4] Luca Pion-Tonachini, Ken Kreutz-Delgado, and Scott Makeig. "ICLabel: An automated electroencephalographic independent component classifier, dataset, and website". en. In: *NeuroImage* 198 (Sept. 2019), pp. 181–197. ISSN: 10538119. DOI: 10.1016/j.neuroimage.2019.05.026. URL: https://linkinghub.elsevier.com/retrieve/pii/S1053811919304185 (visited on 07/16/2023).

[5] James A Desjardins et al. "EEG Integrated Platform Lossless (EEG-IP-L) pre-processing pipeline for objective signal quality assessment incorporating data annotation and blind source separation". In: *Journal of Neuroscience Methods* 347 (2021), p. 108961.

[6] Scott Huberty et al. "PyLossless: A non-destructive EEG processing pipeline". In: *bioRxiv* (2024), pp. 2024–01.

[7] Velu Prabhakar Kumaravel et al. "NEAR: An artifact removal pipeline for human newborn EEG data". In: *Developmental Cognitive Neuroscience* 54 (2022), p. 101068.

[8] Stephanie C Leach et al. "Adjusting ADJUST: Optimizing the ADJUST algorithm for pediatric data using geodesic nets". In: *Psychophysiology* 57.8 (2020), e13566.

[9] I Marriott Haresign et al. "Automatic classification of ICA components from infant EEG using MARA". In: *Developmental cognitive neuroscience* 52 (2021), p. 101024.

[10] Nasser Mourad et al. "A simple and fast algorithm for automatic suppression of high-amplitude artifacts in EEG data". In: *2007 IEEE International Conference on Acoustics, Speech and Signal Processing-ICASSP'07*. Vol. 1. IEEE. 2007, pp. I–393.

[11] Stefon van Noordt et al. "EEG-IP: an international infant EEG data integration platform for the study of risk and resilience in autism and related conditions". In: *Molecular Medicine* 26.1 (2020), pp. 1–11.

[12] Elena V Orekhova et al. "EEG hyper-connectivity in high-risk infants is associated with later autism". In: *Journal of neurodevelopmental disorders* 6 (2014), pp. 1–11.

[13] Emily JH Jones et al. "Developmental changes in infant brain activity during naturalistic social experiences". In: *Developmental psychobiology* 57.7 (2015), pp. 842–853.

[14] Mayada Elsabbagh et al. "Infant neural sensitivity to dynamic eye gaze is associated with later emerging autism". In: *Current biology* 22.4 (2012), pp. 338–342.

[15] Emily JH Jones et al. "Reduced engagement with social stimuli in 6-month-old infants with later autism spectrum disorder: a longitudinal prospective study of infants at high familial risk". In: *Journal of neurodevelopmental disorders* 8 (2016), pp. 1–20.

[16] Emily JH Jones et al. "Infant social attention: an endophenotype of ASD-related traits?" In: *Journal of Child Psychology and Psychiatry* 58.3 (2017), pp. 270–281.

[17] Jacob Cohen. *Statistical power analysis for the behavioral sciences*. Academic press, 2013.

[18] Cyril R Pernet et al. "EEG-BIDS, an extension to the brain imaging data structure for electroencephalography". In: *Scientific data* 6.1 (2019), p. 103.

[19] Krzysztof J Gorgolewski et al. "The brain imaging data structure, a format for organizing and describing outputs of neuroimaging experiments". In: *Scientific data* 3.1 (2016), pp. 1–9.

[20] Jason A Palmer, Ken Kreutz-Delgado, and Scott Makeig. "AMICA: An adaptive mixture of independent component analyzers with shared components". In: *Swartz Center for Computatonal Neursoscience, University of California San Diego, Tech. Rep* (2012).

[21] Eric Larson et al. *MNE-Python*. Version v1.3.1. Feb. 2023. DOI: 10.5281/zenodo.7671973. URL: https://doi.org/10.5281/zenodo.7671973.

[22] Alexandre Gramfort et al. "MEG and EEG data analysis with MNE-Python". In: *Frontiers in neuroscience* (2013), p. 267.

[23] Alberto López, Francisco Ferrero, and Octavian Postolache. "An affordable method for evaluation of ataxic disorders based on electrooculography". In: *Sensors* 19.17 (2019), p. 3756.

[24] Kevin McEvoy et al. "Physiologic artifacts in resting state oscillations in young children: methodological considerations for noisy data". In: *Brain imaging and behavior* 9 (2015), pp. 104–114.

[25] *EEG atlas online*. https://eegatlas-online.com/index.php/en/..

[26] Ruhi Mahajan and Bashir I Morshed. "Unsupervised eye blink artifact denoising of EEG data with modified multiscale sample entropy, kurtosis, and wavelet-ICA". In: *IEEE journal of Biomedical and Health Informatics* 19.1 (2014), pp. 158–165.

[27] Laurel J Gabard-Durnam et al. "Longitudinal EEG power in the first postnatal year differentiates autism outcomes". In: *Nature communications* 10.1 (2019), p. 4188.

[28] Michael Plöchl, José P Ossandón, and Peter König. "Combining EEG and eye tracking: identification, characterization, and correction of eye movement artifacts in electroencephalographic data". In: *Frontiers in human neuroscience* 6 (2012), p. 278.

[29] Takako Fujioka et al. "Comparison of artifact correction methods for infant EEG applied to extraction of event-related potential signals". In: *Clinical Neurophysiology* 122.1 (2011), pp. 43–51.

[30] Scott Huberty et al. "Association between spectral electroencephalography power and autism risk and diagnosis in early development". In: *Autism Research* 14.7 (2021), pp. 1390–1403.

[31] Dominique Makowski et al. "NeuroKit2: A Python toolbox for neurophysiological signal processing". In: *Behavior research methods* (2021), pp. 1–8.

[32] Madalena Costa, Ary L Goldberger, and C-K Peng. "Multiscale entropy analysis of complex physiologic time series". In: *Physical review letters* 89.6 (2002), p. 068102.

[33] Joshua S Richman and J Randall Moorman. "Physiological time-series analysis using approximate entropy and sample entropy". In: *American journal of physiology-heart and circulatory physiology* 278.6 (2000), H2039–H2049.

[34] Alfonso Delgado-Bonal and Alexander Marshak. "Approximate entropy and sample entropy: A comprehensive tutorial". In: *Entropy* 21.6 (2019), p. 541.

[35] *Wilcoxon table.* https://real-statistics.com/statistics-tables/wilcoxon-signed-ranks-table/.

[36] Skipper Seabold and Josef Perktold. "Statsmodels: Econometric and statistical modeling with python". In: *Proceedings of the 9th Python in Science Conference.* Vol. 57. 61. Austin, TX. 2010, pp. 10–25080.

[37] Pauli Virtanen et al. "SciPy 1.0: fundamental algorithms for scientific computing in Python". In: *Nature methods* 17.3 (2020), pp. 261–272.

[38] MA Mañanas. "A comparative study of automatic techniques for ocular artifact reduction in spontaneous EEG signals based on clinical target variables: a simulation case". In: (2008).

[39] Qiuxia Shi et al. "High-speed ocular artifacts removal of multichannel EEG based on improved moment matching". In: *Journal of Neural Engineering* 18.5 (2021), p. 056038.

[40] Gabriella Tamburro et al. "A new ICA-based fingerprint method for the automatic removal of physiological artifacts from EEG recordings". In: *PeerJ* 6 (2018), e4380.

[41] Sergio Romero, Miguel A Mañanas, and Manel J Barbanoj. "A comparative study of automatic techniques for ocular artifact reduction in spontaneous EEG signals based on clinical target variables: a simulation case". In: *Computers in biology and medicine* 38.3 (2008), pp. 348–360.

[42] Stanimira Georgieva et al. "Toward the understanding of topographical and spectral signatures of infant movement artifacts in naturalistic EEG". In: *Frontiers in neuroscience* 14 (2020), p. 452947.