Article

A comparative study of plant phenotyping workflows based

on three-dimensional reconstruction from multi-view images

Daiki Someno[1], Koji Noshita[1, 2, 3,4]*

[1]Department of Biology, Kyushu University, Fukuoka, Fukuoka 819–0395, Japan

[2]Graduate Program of Mathematics for Innovation, Kyushu University, Fukuoka 819–

0395, Japan

[3]Graduate School of Science, Nagoya University, Nagoya 464-8601, Japan

[4]Nara National Research Institute for Cultural Properties, Nara, 630-8002, Japan

* **Corresponding author**: Koji Noshita

16   Affiliation: Kyushu University

17   Address: Fukuoka, Fukuoka 819–0395, Japan

18   Email: noshita@morphometrics.jp, Phone: +81-92-802-4316

Abstract

With the world facing escalating food demand, limited agricultural land, and environmental change, there is a growing need for data-driven sustainable agricultural management. Advances in sequencing and sensor networks have reduced costs of acquiring genomic and environmental data; however, collecting phenotypic data, crucial for monitoring plant growth and detecting pests and diseases, remains labor-intensive. Technological advances have enabled efficient collection of three-dimensional (3D) data, yet this process currently involves intricate steps. Therefore, developing effective phenotyping methods is essential. In this study, we developed a phenotyping process based on 3D data, including mask image generation using deep neural network models, 3D reconstruction using the Structure from Motion/Multi-View Stereo (SfM/MVS) pipeline, and surface reconstruction for leaf area estimation. Using soybean datasets, we found that a 1/5.4× magnification effectively generated mask images. Among four mask image usage scenarios in SfM/MVS, applying soybean-and-stage masks before SfM and only soybean masks after SfM yielded the highest-quality point cloud data with the second shortest processing time. Finally, we compared Poisson reconstruction and B-spline surface fitting in leaf area estimation; B-spline fitting showed greater correlation with destructive measurements. We propose an optimal workflow for estimating leaf area and provide tools and datasets for future phenotyping research.

40   **Keywords:** photogrammetry, multi-view image, phenomics, morphometrics, open science

Introduction

The rise in global food demand [1,2], limited agricultural land [3,4], and climate change [5,6] have heightened the necessity for the quantitative evaluation of crop phenotypic information [7,8]. This approach would facilitate the development of efficient and robust agricultural management approaches, which are essential for addressing the abovementioned challenges in a data-driven manner [9,10]. Recent technological breakthroughs, particularly in next-generation sequencing, have facilitated the accumulation of omics data, including genomic and transcriptomic information [11,12]. In addition, advancements in Internet of Things (IoT) sensor technologies have improved the acquisition of environmental data [13,14]. However, despite the significance of phenotypic information in understanding plant growth and physiological responses in various environments [15,16], the acquisition of phenotypic data remains labor-intensive and yields limited data [17,18]. Consequently, there has been increasing interest in plant phenotyping technologies among researchers and agricultural producers [7,8,17–19]. Several studies have reported that the monitoring of three-dimensional morphological properties of plants provides insights for improving cultivation management, including optimizing the timing of pesticide and fertilizer application [20,21].

High-resolution 3D morphological data can be acquired efficiently and cost-effectively using 3D laser scanners [22,23], depth cameras [24,25], and photogrammetry [26,27]. A

pipeline using structure from motion (SfM) [28,29] and multi-view stereo (MVS) [30,31], which

reconstructs a 3D surface as point cloud data from a set of two-dimensional (2D) images

captured from different angles, is widely available and implemented in several libraries and

software products (e.g., [28,31,32]). Based on the resultant high-resolution point cloud data, a

three-dimensional morphological model can be constructed to yield phenotypic data (e.g.,

leaf number, plant height, and leaf area index (LAI) [33,34]).

Optimizing the measurement process for three-dimensional morphological data

directly facilitates the efficient acquisition of phenotypic data. Various approaches have been

proposed for the acquisition of high-quality three-dimensional point cloud data using the

SfM/MVS pipeline (e.g., [35,36]). Mask images offer several advantages in the SfM/MVS

pipeline, such as reduced processing time by limiting the region of interest (ROI) and

suppressing noise derived from background textures [37,38]. Moreover, there are several

choices for creating morphological models for estimating phenotypic data from point cloud

data acquired using SfM/MVS and 3D laser scanners, depending on the assumptions (e.g.,

target traits, precision requirements, and data acquisition conditions). Several methods have

been proposed to provide robust quantification of leaf morphology, such as modeling the

leaf surface as a triangular mesh [39], a set of small patches [40], and a piecewise polynomial

function [41]. Although Poisson surface reconstruction [42] is often used to reconstruct the target

surface based on point cloud data in various fields [43], it is not ideal for leaf surface

reconstruction [44,45]. This is because it assumes that the target surface is closed (i.e.,

topologically equivalent to a sphere). Although various techniques for improving the

phenotyping processes have been proposed, as noted above, it is difficult to say that methods

for optimizing each step in the process or the entire process for the target trait are well

established.

In this study, we aimed to optimize the processes for acquiring phenotypic

information based on 3D morphological data of plants. Through comparative analyses of

various procedures on individual soybean plants, including mask image generation,

SfM/MVS pipelines, and leaf surface reconstruction to estimate the leaf area (Fig. 1), we

formulated an optimal phenotyping process. To generate mask images using a DNN-based

semantic segmentation model, we proposed an ideal scale of input images for the two types

of mask images. Within the SfM/MVS pipeline, we compared the processing time and

reconstructed point-cloud data quality for the four mask image usage scenarios. Finally, we

evaluated the leaf surface reconstruction methods to estimate the area of each leaf by

comparing the two general methods. We propose an optimal 3D reconstruction-based plant

phenotyping process and provide tools and data to accelerate these comparisons. Such

comprehensive comparisons for optimizing plant phenotyping processes can also be applied

to other phenotyping procedures. Overall, these optimization processes can yield insights

that contribute to the improvement of crop yield, quality, and the cultivation of various target

crops.

Materials and Methods

Multi-view image datasets of individual soybeans

We used three multi-view image datasets of soybean (*Glycine max*) plants to train the DNN-

based semantic segmentation model ($dataset_t$), evaluate different SfM/MVS scenarios based

on the quality of the reconstructed point cloud data and their processing time ($dataset_m$), and

evaluate the accuracy of leaf area estimation with two different morphological modeling

methods against destructive measurements ($dataset_v$). Soybean plants were grown from

seeds provided by the National Agriculture and Food Research Organization (NARO) in the

greenhouse (25°C) at the Environmental Control Center for Experimental Biology, Kyushu

University, Japan.

The $dataset_t$ consisted of four individuals from four different cultivars (Enrei, Zairai

51-2, Aoakimame, and Saga zairai), with each individual represented using 256 or 264

multiview images. All images were annotated in a pixel-wise manner across four classes

(soybean, stake, stage/pot, and background) using Labelbox (Labelbox, Inc., San Francisco,

CA, USA), a web application for generating training data.

The $dataset_m$ consisted of six individuals of three cultivars, namely, Seita, N2295,

and Keumdu, across different growth stages (4, 8, and 12 weeks after sowing, respectively).

The cultivars each included two replicates, with each individual represented using 256, 264,

or 272 multi-view images (Table 1).

The $dataset_v$ consisted of 256 or 264 images per soybean individual obtained from

two cultivars (Hime daizu and Shiro mitsu mame) at two growth stages (6 and 12 weeks

after sowing) with two replicates. After acquiring multi-view images, all leaves were

sampled from individual plants, and their positions were recorded. The sampled leaves were

captured as two-dimensional images at 600 dots per inch (DPI) using a flatbed scanner

(CanoScan LiDE 400; Canon, Tokyo, Japan). The region of interest (ROI) for each leaf was

set semi-manually using the Selection Brush Tool in Affinity Photo 2 (Serif (Europe) Ltd.,

Nottingham, UK) to generate mask images for destructive leaf area measurements. These

mask images were processed using OpenCV via Python; specifically, this processing

involved binarization and the counting of pixels corresponding to each leaf for leaf area

measurements. The leaves of Shiro mitsu mame tended to have a smaller area (approximately

1000 mm^2) than those of Hime daizu (1000–3000 mm^2).

All multiview images were obtained using a simple photogrammetry studio

consisting of a rotating table (MT320RL40, ComXim, Shenzhen, China), eight digital

single-lens reflex (DSLR) cameras (EOS Rebel SL1, Canon, Tokyo, Japan), coded markers,

and blue screen-like background sheets (Fig. S1). The focal length of each camera was set

to 24 mm, and the images were captured approximately every 11° until the rotating table

reached 360 °(256, 264, or 272 images per soybean individual).

Mask image generation using U-Net

U-Net [46], a DNN model for semantic segmentation, was used to generate the mask images

in the SfM/MVS pipeline. The U-Net was trained for two classification tasks: three-

(soybean, stake, and background) and four-class classification (soybean, stake, stage, and

background) (Fig 2A). These different classes of mask images can be used across different

SfM/MVS scenarios (see **SfM/MVS pipelines** for details).

We used U-Net with ResNet34 [47] pre-trained on ImageNet as the encoder block and

the softmax function as the activation function on the last layer. To train and predict using

high-resolution images, each input image was divided into a certain number of tiles,

depending on magnification, and resized to 512×512 pixels; each tile was segmented into

three or four classes and merged into an entire image. An overlap-tile strategy that excluded

outer pixels that did not exceed a threshold during merging was adopted to avoid border

effects in each tile (Fig. 2B). Class-weighted dice loss was used as a loss function, and we

adopted the weights calculated based on the occurrences of the pixels corresponding to each

class in the training data (Table 2). The number of epochs is set to 200. Adam, with a learning

rate of 0.0001, was initially used as the optimizer; this rate was then changed to 0.00001

after 150 epochs.

Performance, i.e., intersection over union (IoU) and processing time, of U-Net, were

evaluated across six different magnifications of the input images ($1/2\times$, $1/3\times$, $1/4\times$, $1/5.4\times$,

$1/6\times$ and $1/6.75\times$) (Fig 3); each image was divided into 30, 15, 6, 4, 4, and 2 tiles on the

magnifications $1/2\times$, $1/3\times$, $1/4\times$, $1/5.4\times$, $1/6\times$ and $1/6.75\times$, respectively (Fig. 2B). We

conducted a group four-fold cross-validation on a dataset$_t$; images belonging to a single

individual were excluded as test images, and other images were randomly divided into

training (80%) and validation (20%) images. In the training step, we used the Python

package Albumentations [48] for data augmentation, including random resizing and cropping

(i.e., while retaining the aspect ratio of the original images), geometrical transformation (i.e.,

vertical and horizontal flipping, and random rotation by 90° zero or more times), changing

color, elastic transformation, and random noise (i.e., Gaussian noising, blurring, motion

blurring, and color jittering). The abovementioned steps were conducted using a CPU

(Intel(R) Core(TM) i7-6950X CPU @ 3.00GHz) and a GPU GeForce GTX 1080 Ti $\times 2$.

In subsequent analyses, we generated mask images using the U-Net model trained

on the entire dataset$_t$.

Web application for generating mask images

We developed a web application for mask generation based on the trained U-Net models

(Fig. 4). This application allows users to easily manipulate several parameters (scale, overlap,

and mask type) through a simple user interface using Streamlit, which is a Python framework

for developing web applications (https://streamlit.io). The web application, operating

without a GPU, is hosted on the Streamlit Community Cloud (https://mask-prediction-

app.streamlit.app/), and its source code will be made publicly available on the GitHub

repository.

SfM/MVS pipelines

We adopted the Structure from Motion (SfM) and Multi-View Stereo (MVS) methods to

generate 3D point cloud data. SfM is a photogrammetric method for simultaneously

estimating the camera parameters and depth of the corresponding points (i.e., sparse point

clouds) from multiview images. The SfM was conducted as per the following steps: (1) key

points (characteristic points to be candidates of tie points) were obtained from each image

in multi-view images using local features (e.g., SIFT[49]); (2) the tie points, which are

corresponding points between images (based on key point matching and outlier removal with

epipolar constraints), were selected; (3) an essential matrix for each image pair based on tie

points was calculated, and then the extrinsic camera parameters (position, orientation) and

the depth of the tie points (sparse point cloud) were estimated; finally, (4) the bundle

adjustment was conducted to optimize the extrinsic camera parameters and the depth of the

tie points by minimizing the reprojection error. After SfM, the MVS generates dense point-

cloud data based on the estimated camera parameters and tie points. Several algorithms have

been proposed, e.g., SUrface REconstruction from imagery (SURE)[50] and patch-based

multiview stereo (PMVS) [51]. We used Metashape v1.8.4 (Agisoft, St. Petersburg, Russia), to

conduct the SfM/MVS pipeline. Metashape adopts a SURE-like algorithm to implement the

MVS. SURE can offer a depth map, which is the distance from each pixel in a 2D image to

the object or scene captured in each image using a semiglobal matching (SGM) -based

algorithm[52], and convert the depth maps into 3D coordinates using a fusion method based

on geometric constraints [53].

We evaluated four scenarios based on SfM/MVS: (i) no mask, (ii) masks before

SfM, (iii) masks after SfM, and (iv) two masks (Fig 5). The basic procedure for the

SfM/MVS implementation for each scenario was as follows: (1) multi-view images of a

soybean individual were imported, (2) the coded markers were detected, (3) scale bars were

created from the pairs of detected coded markers, (4) sparse point clouds were generated

based on SfM, with the maximum number of key points set to 200,000 and the maximum

number of tie points set to 80,000 in this study, (5) a depth map was created, and (6) dense

point clouds were generated based on MVS. In scenarios (ii) and (iii), the soybean mask

images were imported before and after step (4), respectively. In scenario (iv), the

soybean/stage mask images were imported before step (4) and replaced with the soybean

mask images before step (6). These four scenarios were implemented using the Metashape

Python API.

In addition, the abovementioned four scenarios were evaluated for each soybean

individual of dataset$_m$. In the implemented script, the processing time for each step was

measured using the time function in the time module of the standard Python library. The

Mann-Whitney U test with Bonferroni correction was subsequently performed to investigate

the differences in processing times among the four scenarios.

Leaf surface reconstruction

To estimate phenotypic values from the reconstructed point-cloud data, we employed two

prevalent methods for leaf surface reconstruction: (1) Poisson surface reconstruction and (2)

B-spline surface fitting.

Poisson surface reconstruction [42] is widely used to estimate surfaces from point-

cloud data using their normal vectors (i.e., oriented points). Assume that we will reconstruct

the boundary ∂A of a target structure A from the given oriented points. If a function (called

indicator function χ), which returns one if the point is located inside of the A, otherwise 0,

is given, the boundary is approximated by its isosurface. The best-fitted boundary will be

estimated by minimizing the differences between the gradient of the indicator function $\nabla\chi$

and the vector field defined by the oriented points $\vec{P}$ (i.e., $\min_{\chi}||\nabla\chi - \vec{P}||$). To solve the

problem, this equation is transformed into the Poisson equation as follows: $\Delta\chi = \nabla \cdot \vec{P}$.

Finally, the isosurface is extracted from the estimated χ. Additionally, the reconstructed

surface is filtered based on the point density (i.e., only parts of the surface supported by a

sufficient number of points remain) because the method potentially reconstructs a surface in

which points are distributed with low density, including the outer region of the leaf surface

(i.e., extrapolation). In this study, we used the create_from_point_cloud_poisson function

implemented in Open3D[54] to estimate the leaf surface from the point-cloud data using

Poisson surface reconstruction. Vertices of the reconstructed surface were filtered if less

than 6.5 points supported them.

B-spline surface fitting is widely used for surface reconstruction from point-cloud

data. In this study, we adopted the B-spline surface fitting and B-spline curve trimming

approaches [55] to reconstruct the leaf surface. A B-spline basis function of degree d is defined

by the de Boor-Cox recursion formula [56]:

243
$$b_{i,0}(l) = \begin{cases} 1 & \text{if } \tau_i \leq l < \tau_{i+1} \\ 0 & \text{otherwise} \end{cases},$$

244
$$b_{i,d}(l) = \frac{l - \tau_i}{\tau_{i+d} - \tau_i} b_{i,d-1}(l) + \frac{\tau_{i+d+1} + l}{\tau_{i+d+1} - \tau_{i+1}} b_{i+1,d-1}(l),$$

245   where $(\tau_1, \tau_2, \cdots, \tau_{n+d+1})$ is a knot vector that divides the parameter space into subintervals,

246   and n is the number of basis functions used for the approximation. A continuous surface is

247   approximated by a linear combination of the tensor products of the B-spline basis functions,

248   as follows:

249
$$\mathbf{p}_s(u, v) = \sum_i^{n_u} \sum_j^{n_v} \mathbf{w}_{ij} b_{i,d}^u(u) b_{j,d}^v(v),$$

where $\mathbf{w}_{ij}$ is a coefficient vector called a control point, and $b_{i,d}^u(u)$ and $b_{j,d}^v(v)$ are B-spline

basis functions of degree d along the independent parameters (u, v) of the parameter space.

In this study, we parameterized the leaf surface by applying a principal component analysis

(PCA), and the 2D parameter space was defined using the 1st and the 2nd PC axes. The $\mathbf{w}_{ij}$

is estimated by minimizing the sum of the squared distances between the B-spline surface

and point cloud data. Based on the reconstructed surface, the parameter space is trimmed

using a closed B-spline curve to exclude the outer region of the leaf. The closed B-spline

curve was fitted to the point cloud data projected into the parameter space using the

asymmetric distance with a penalty for concavity and error-adaptive knot insertion (EAKI)

[55]. In this study, we used the surface/on_nurbs submodule [57] in the Point Cloud Library (PCL;

https://pointclouds.org/) to reconstruct leaf surfaces using B-spline surface fitting and B-

spline curve trimming. In the B-spline surface fitting, we estimated the 3-degree B-spline

surface by incrementally adding knots three times using the following parameter values: the

surface smoothness, boundary smoothness, and boundary weight were 0.8, 0.5, and 0.2,

respectively. In the B-spline curve trimming, the 3-degree B-spline curve was estimated with

a maximum of 100 iterations using the following parameter values for the penalty for

concavity (0.2) and for EAKI: iterations without knot insertion and the maximum number of

control points were 4 and 100, respectively.

268   Based on both methods, leaf area was estimated using $dataset_v$ through scenario iv.

Each leaflet was cropped from the point-cloud data using Cloud Compare v2.12.4

(CloudCompare), software for visualizing and manipulating point-cloud data. We then

applied color thresholding (i.e., excluding points with $0.3 < hue < 0.7$, saturation < 0.2, and

value > 0.8 in the HSV color space) and statistical outlier removal (i.e., excluding outlier

points for which the mean distance calculated from their 30 neighbor points is greater than

three standard deviations by using the statistical_outlier_removal function in Open3D).

Results

Optimizing image magnification for mask image generation

We identified the optimal magnification of input images for multiview images of soybean

individuals by evaluating the IoU and processing time of segmentation.

For both three- and four-class segmentations, the IoU increased with decreasing

magnification, peaking at approximately 1/4×, followed by a gradual decrease (Fig. 3A, F).

The IoU by class showed the same pattern (Fig. 3B-D, G-J); however, several classes peaked

at 1/5.4×: stake (three-class segmentation) 0.8670, background (four-class segmentation)

0.9939, and stage (four-class segmentation) 0.9903 (Fig. 3C, H-J). There is a tradeoff: as the

magnification of the input images decreases, a single input tile to the U-Net covers larger

plant structures; conversely, as the magnification increases, the resolution decreases. In our

dataset, a magnification of 1/4× or 1/5.4× reached the optimal IoU.

The processing times for both the three- and four-class segmentations decreased

with decreasing magnification. This is because the total number of input tiles decreased (Fig.

2C, 3E, and 3K). Although a marginal increase in processing time was shown to be linked

to reductions in the magnification (i.e., the expansion of the field of view), almost all the

processing times per image fall between 0.015–0.02 s (Fig. S2).

The U-Net models for the three- and four-class segmentations were trained using

the images of all four cultivars in the $dataset_t$ (see Fig. S3). These models generated high-

resolution mask images for SfM/MVS, in which the background was excluded (Fig. 2D):

soybean mask images (soybean pixels were the foreground, whereas others were the

background) and soybean/stage mask images (soybean and stage pixels were the foreground,

whereas others were the background).

Moreover, we developed a web application for mask generation based on the trained

U-Net models. This application helps generate mask images with arbitrary scales and

overlapping thresholds via a simple user interface (Fig. 4). The processing time was 126 s

on the GPU device for predicting 256 mask images of 5184 × 3456 pixels divided into two

columns and two rows of 2900 × 2900 pixel tiles (approximately 1/5.4×) with at least 10%

overlap using a four-class segmentation model.

306   Quality of reconstructed point cloud data through SfM/MVS with 307   four mask image usages

We reconstructed the dense point cloud data of six individuals of three cultivars at three

different growth stages of the $dataset_m$ based on SfM/MVS, following four possible scenarios

of mask image usage (Fig. 5). Masking during SfM/MVS effectively suppressed the noise

derived from the background textures (Fig.5B-D, 5F-H, 5K, and 5L) compared to scenario

(i) without mask images (Fig. 5A, 5E, 5I), as noted in previous studies (e.g., [37,38]).

The quality of the reconstructed point-cloud data varied depending on the mask type

and timing of the setting. Although in scenario (ii), setting soybean mask images before SfM

was able to suppress the noise derived from the background textures, the reconstructed points

along the leaf edges seemed inaccurate (Fig. 5B, 5F) and often failed to reconstruct the leaf

surfaces for the small soybean plants (Fig. 5J). These inaccurate reconstructions without

background texture-derived noise were a consequence of the low accuracy of camera

extrinsic parameter estimation in SfM, not using markers on the stage and corresponding

points on the pot, because the ROIs based on the mask images were limited to soybeans. In

scenario (ii), key points and tie points were located only in the region corresponding to

soybean (Fig. 5N), and their detected numbers were lower than those in the other scenarios

(Table 3). There were few qualitative differences between scenarios (iii) and (iv), except for

the noise derived from the abaxial side of the leaves and the background textures (Fig. 5C,

5D, 5G, 5H, 5K, and 5L). In both scenarios, leaf surfaces were well-reconstructed because

SfM precisely estimated extrinsic camera parameters using the markers on the stage and the

corresponding points on the pot.

329   Evaluation of the throughput of SfM/MVS on four mask image

usages

The processing times, including those for mask image generation, SfM, and MVS, were measured for the four scenarios (Fig. 6). Scenarios (ii), (iv), and (iii) achieved the first, second, and third shortest processing times, respectively (.A). The decrease in the area of the ROIs caused by setting mask images contributed to the processing time. The longest mean processing time was 34.0 min for scenario (i), and the shortest one was 15.8 min for scenario (ii).

The processing time of mask image generation for scenario (iv) was 3.61 min, approximately double that for 1.74 min of scenario (ii) and 1.74 min of scenario (iii) (Fig. 6B), because two types of mask images (soybean and soybean/stage) were generated.

The processing times of SfM and MVS increased in the order of the ROIs, except for scenarios (ii) and (iii) of MVS (Fig. 6C and 6D). There was no significant difference between the processing times of SfM in scenarios (i) and (iii), and the mean processing times were ~5.4 min. The shortest mean processing time was 3.3 min for scenario (ii). The majority of processing times came from the MVS; the longest mean processing time was 27.6 min in scenario (i) and the shortest one was 9.6 min in scenario (ii). Although the ROIs for MVS were the same between scenarios (ii) and (iii), scenario (ii) showed a shorter processing time for MVS because fewer key points were detected in SfM in scenario (ii) (Table 3).

We adopted scenario (iv) for the following analysis because (1) it generated the

highest-quality point cloud data, and (2) its entire processing time was the second shortest.

Leaf surface reconstruction methods for evaluating phenotypic

values

We reconstructed the leaf surfaces of 190 leaflets from dataset$_v$, excluding dead leaves, using

both Poisson surface reconstruction and B-spline surface fitting, and then estimated their

leaf areas (Table S1). The estimated leaf area had the following correlation coefficients with

the results of the destructive measurements: Poisson surface reconstruction ($\rho = 0.9123$;

Fig. 7A) and B-spline surface fitting ($\rho = 0.9943$; Fig. 7B). The approach based on B-spline

surface fitting enabled accurate estimation of leaf area ($R^2 = 0.9871$; Fig. 7B). Using the

Poisson surface reconstruction, the leaf area was overestimated, particularly for larger leaves.

Leaf surface reconstruction based on B-spline surface fitting achieved higher

accuracy than Poisson surface reconstruction for the leaf area estimation in almost all cases.

Both methods successfully reconstructed leaf surfaces and estimated areas on high-quality

point cloud data (Fig. 7C); the Poisson surface reconstruction method enabled a more

detailed reconstruction of leaf surfaces, yet showed nearly equivalent performance in leaf

area estimation. Although the Poisson surface reconstruction occasionally produced the leaf

surface as dual layers for the point cloud data to reconstruct the abaxial side over the adaxial

side, the B-spline surface fitting consistently reconstructed a singular surface (Fig. 7D).

However, when a single leaflet was reconstructed as multi-leaf-like point cloud data, neither

method could accurately reconstruct the surface, resulting in an overestimation of the area

(Fig. 7E); we found four leaflets corresponding to this case (Table 4). Three of the four

leaflets were leaflets of the same individual plant, which implied blurring associated with

the motion of the target plants while capturing the multi-view images, which caused low

accuracy of the camera parameter estimation. This is different from the decrease in accuracy

in camera parameter estimation owing to the mask images observed for the small individuals

in scenario (ii) (Fig. 5J); in fact, the quality of the reconstructed point cloud data is similar

across scenarios (ii) and (iv) (Fig. 7F).

378   Discussion

Even though using mask images improves the quality of point cloud data reconstructed via

the SfM/MVS pipeline and decreases the processing time, it remains crucial to understand

which objects should be masked and in which operations these mask images should be

applied. As noted in previous studies [37,38], the reconstructed point-cloud data based on

SfM/MVS were improved for large individuals by masking the target objects (Fig. 5A-H).

However, the point cloud was not comprehensively reconstructed by setting the mask images

before SfM for small individuals (Fig. 5J), although they were reconstructed properly

without mask images (Fig. 5I). We found that appropriate point clouds were reconstructed

either by setting soybean mask images after SfM (scenario iii) or by setting soybean/stage

mask images before SfM and then soybean mask images after SfM (scenario iv) (Fig. 5C, D,

G, H, K, and L). This implies the importance of setting mask images, which ensures a

sufficient number and accuracy of detected key points and tie points (Fig. 5M-P, Table 3).

There are several considerations for generating the mask images used in this study, one of

which is the magnification rate of the input images. As a result of different scales of input

images to the U-Net, a magnification of 5.4× achieved the first or second optimal IoU for all

classes (Fig. 3). However, there was a trade-off between low magnification (i.e., long-range

context is available with low resolution) and high magnification (i.e., only local context is

available with high resolution) (Fig. 2C). Setting a larger input image size could resolve this

issue; however, in practice, balancing them for the target objects is necessary because of

various constraints (e.g., available GPU memory).

In plant phenotyping, it is advantageous to introduce known morphological

constraints to the target shape. In this study, we assumed that a leaf constitutes a single

bounded surface in a three-dimensional space during leaf surface reconstruction, which

enabled more robust measurements of leaf area (Fig. 7). Thus, the surface was reconstructed

using Poisson surface reconstruction; this approach resulted in an overestimation of leaf area

(Fig. 7A). It is worth noting that point cloud data derived from actual plants often contain

noise that is difficult to eliminate, even with denoising filters. In cases where B-spline

surface fitting is ineffective for reconstruction, methods exclusively derived for

characterizing leaf morphology could prove useful (e.g., [39–41,44,45]). The results of leaf area

estimation using B-spline surface fitting showed a high correlation with the results of

destructive measurements (Fig. 7B), indicating its utility in the phenotyping process. In some

cases, the B-spline surface fitting did not reconstruct precisely (Fig. 7E). However, this issue

often stems from the difficulty underlying camera parameter estimation in SfM (Fig. 7F),

demonstrating that improvements in measurement devices can yield improvements in

accuracy. Concerning the qualitatively noted shortcomings in previous studies of the B-

spline surface fitting approach in reconstructing leaf surfaces [44,45], it is considered that these

issues do not significantly impact leaf area estimation as long as the point cloud is

reconstructed with high accuracy. Consequently, we propose an optimal workflow for

estimating leaf area of soybean plants, including mask image generation using U-Net with

1/5.4× magnification, 3D point cloud reconstruction based on scenario (iv) of SfM/MVS,

and leaf surface reconstruction by B-spline surface fitting to estimate leaf area. The optimal

values and methods depend on the target objects and constraints on the measurement

processes, and the optimal configurations are explored through comparative experiments, as

demonstrated in this study. The reconstructed leaf surfaces also allow for quantification of

leaf orientation in three-dimensional space; the resultant outputs can be used for functional

assessments, including light interception [58,59]. Utilizing this method in functional structural

plant models (FSPM) and other areas is a subject for future research on sustainable food

systems using data-driven approaches [7,8,60].

Moreover, we offer a tool and data that can be applied toward enhancing the

efficiency at which plant phenotyping can be conducted. Specifically, our web application

facilitates the generation of mask images through a trained U-Net model, and is designed to

allow the replacement of models, enabling its use in various subjects (Fig. 4). We also

published the multiview soybean images used in model training as open data, including their

mask images and images from destructive measurements. These data will be available to

developers of future methodologies as benchmark datasets. We believe that disseminating

such tools and datasets will contribute to the field of phenomics, where data acquisition is

currently labor-intensive and slow.

Conclusion

Here, we investigated 3D reconstruction-based phenotyping processes including

mask image generation using U-Net models, 3D reconstruction based on the SfM/MVS

pipeline, and leaf surface reconstruction for leaf area estimation. Through comparative

experiments using soybean data, we proposed an optimal workflow for estimating leaf area

and generating mask images. The workflow entailed using U-Net models with $1/5.4\times$

magnification, 3D point cloud reconstruction based on the SfM/MVS pipeline setting

soybean/stage mask images before SfM and soybean mask images after SfM (scenario iv),

and leaf surface reconstruction by B-spline surface fitting to estimate leaf area. However, it

is important to note that in some cases, greater accuracy was achieved with 1/4 magnification

in the U-Net model, and that high-quality point clouds can also be obtained by setting only

the soybean mask images after SfM (scenario iii). The processes outlined in this study can

be adapted as required. Moreover, we offer a web application for mask generation, a

command-line tool for leaf surface reconstruction, and validation datasets to facilitate future

plant phenotyping research and methodological development.

References

1. Tilman, D., Balzer, C., Hill, J. & Befort, B. L. Global food demand and the sustainable intensification of agriculture. *Proc Natl Acad Sci U S A* **108**, 20260–20264 (2011).

2. van Dijk, M., Morley, T., Rau, M. L. & Saghai, Y. A meta-analysis of projected global food demand and population at risk of hunger for the period 2010–2050. *Nat Food* **2**, 494–501 (2021).

3. Wu, W. *et al.* Global cropping intensity gaps: Increasing food production without cropland expansion. *Land use policy* **76**, 515–525 (2018).

4. Potapov, P. *et al.* Global maps of cropland extent and change show accelerated cropland expansion in the twenty-first century. *Nat Food* **3**, 19–28 (2022).

5. Zhao, C. *et al.* Temperature increase reduces global yields of major crops in four independent estimates. *Proc Natl Acad Sci U S A* **114**, 9326–9331 (2017).

6. Wang, X. *et al.* Emergent constraint on crop yield response to warmer temperature from field experiments. *Nat Sustain* **3**, 908–916 (2020).

7. Herrero, M. *et al.* Innovation can accelerate the transition towards a sustainable food system. *Nat Food* **1**, 266–272 (2020).

8. Fiorani, F. & Schurr, U. Future Scenarios for Plant Phenotyping. *Annu Rev Plant Biol* **64**, 267–291 (2013).

9. van Etten, J. *et al.* Data-driven approaches can harness crop diversity to address heterogeneous needs for breeding products. *Proc Natl Acad Sci U S A* **120**, (2023).

10. Coppens, F., Wuyts, N., Inzé, D. & Dhondt, S. Unlocking the potential of plant phenotyping data through integration and data-driven approaches. *Curr Opin Syst Biol* **4**, 58–63 (2017).

11. Goodwin, S., McPherson, J. D. & McCombie, W. R. Coming of age: Ten years of next-generation sequencing technologies. *Nat Rev Genet* **17**, 333–351 (2016).

12. Stark, R., Grzelak, M. & Hadfield, J. RNA sequencing: the teenage years. *Nat Rev Genet* **20**, 631–656 (2019).

13. Sathyamoorthy, S. & Okafor, N. Advances and Challenges in IoT Sensors Data Handling and Processing in Environmental Monitoring Systems. *TechRxiv* 1–8 (2023) doi:10.36227/techrxiv.24045951.v1.

14. Ullo, S. L. & Sinha, G. R. Advances in Smart Environment Monitoring Systems Using IoT and Sensors. *Sensors* **20**, 3113 (2020).

15. Granier, C. & Tardieu, F. Multi-scale phenotyping of leaf expansion in response to environmental changes: The whole is more than the sum of parts. *Plant Cell Environ* **32**, 1175–1184 (2009).

16. Langstroff, A., Heuermann, M. C., Stahl, A. & Junker, A. Opportunities and limits of
controlled-environment plant phenotyping for climate response traits. *Theoretical*
and Applied Genetics vol. 135 Preprint at https://doi.org/10.1007/s00122-021-
03892-1 (2022).

17. Araus, J. L. & Cairns, J. E. Field high-throughput phenotyping: The new crop
breeding frontier. *Trends Plant Sci* **19**, 52–61 (2014).

18. Yang, W. *et al.* Crop Phenomics and High-Throughput Phenotyping: Past Decades,
Current Challenges, and Future Perspectives. *Mol Plant* **13**, 187–214 (2020).

19. Campbell, Z. C., Acosta-Gamboa, L. M., Nepal, N. & Lorence, A. Engineering
plants for tomorrow: how high-throughput phenotyping is contributing to the
development of better crops. *Phytochemistry Reviews* **17**, 1329–1343 (2018).

20. Dammer, K.-H., Wollny, J. & Giebel, A. Estimation of the Leaf Area Index in cereal
crops for variable rate fungicide spraying. *European Journal of Agronomy* **28**, 351–
360 (2008).

21. Addai, I. K. & Alimiyawo, M. Graphical determination of leaf area index and its
relationship with growth and yield parameters of Sorghum (Sorghum bicolor L.
Moench) as affected by fertilizer application. *Journal of Agronomy* **14**, 272–278
(2015).

22. Paulus, S., Behmann, J., Mahlein, A.-K., Plümer, L. & Kuhlmann, H. Low-Cost 3D
Systems: Suitable Tools for Plant Phenotyping. *Sensors* **14**, 3001–3018 (2014).

23. Lin, Y. LiDAR: An important tool for next-generation phenotyping technology of
high potential for plant phenomics? *Comput Electron Agric* **119**, 61–73 (2015).

24. Chéné, Y. *et al.* On the use of depth camera for 3D phenotyping of entire plants.
Comput Electron Agric **82**, 122–127 (2012).

25. Milella, A., Marani, R., Petitti, A. & Reina, G. In-field high throughput grapevine
phenotyping with a consumer-grade depth camera. *Comput Electron Agric* **156**,
293–306 (2019).

26. An, N. *et al.* Plant high-throughput phenotyping using photogrammetry and imaging
techniques to measure leaf length and rosette area. *Comput Electron Agric* **127**, 376–
394 (2016).

27. Santos, T. T. & Rodrigues, G. C. Flexible three-dimensional modeling of plants
using low- resolution cameras and visual odometry. *Mach Vis Appl* **27**, 695–707
(2016).

28. Schonberger, J. L. & Frahm, J.-M. Structure-from-Motion Revisited. in *2016 IEEE*
Conference on Computer Vision and Pattern Recognition (CVPR) vols 2016-Decem
4104–4113 (IEEE, 2016).

29. Snavely, N., Seitz, S. M. & Szeliski, R. Modeling the World from Internet Photo

Collections. *Int J Comput Vis* **80**, 189–210 (2008).

30. Seitz, S. M., Curless, B., Diebel, J., Scharstein, D. & Szeliski, R. *A Comparison and*
Evaluation of Multi-View Stereo Reconstruction Algorithms.
http://vision.middlebury.edu/mview. (2006).

31. Schönberger, J. L., Zheng, E., Frahm, J. M. & Pollefeys, M. Pixelwise view
selection for unstructured multi-view stereo. in *Lecture Notes in Computer Science*
(including subseries Lecture Notes in Artificial Intelligence and Lecture Notes in
Bioinformatics) (eds. Leibe, B., Matas, J., Sebe, N. & Welling, M.) vol. 9907 LNCS
501–518 (Springer International Publishing, Cham, 2016).

32. Cernea, D. OpenMVS: Multi-View Stereo Reconstruction Library. Preprint at
(2020).

33. Lu, X. *et al.* Reconstruction method and optimum range of camera-shooting angle
for 3D plant modeling using a multi-camera photography system. *Plant Methods* **16**,
118 (2020).

34. Zermas, D., Morellas, V., Mulla, D. & Papanikolopoulos, N. Estimating the Leaf
Area Index of crops through the evaluation of 3D models. in *IEEE International*
Conference on Intelligent Robots and Systems vols 2017-Septe 6155–6162 (IEEE,
2017).

35. Koutsoudis, A., Ioannakis, G., Vidmar, B., Arnaoutoglou, F. & Chamzas, C. Using
noise function-based patterns to enhance photogrammetric 3D reconstruction
performance of featureless surfaces. *J Cult Herit* **16**, 664–670 (2015).

36. Zhao, J., Monno, Y. & Okutomi, M. Polarimetric Multi-View Inverse Rendering.
IEEE Trans Pattern Anal Mach Intell **45**, 8798–8812 (2023).

37. Nooruddin, M. & Rahman, M. Improved 3D reconstruction for images having
moving object using semantic image segmentation and binary masking. in *4th*
International Conference on Electrical Engineering and Information and
Communication Technology, iCEEiCT 2018 32–37 (IEEE, 2018).
doi:10.1109/CEEICT.2018.8628064.

38. Tanabata, T., Isobe, S., Hayashi, A. & Kochi, N. Development of a semi-automatic
3D modeling system for phenotyping morphological traits in plants. in *Proceedings:*
IECON 2018 - 44th Annual Conference of the IEEE Industrial Electronics Society
5439–5444 (IEEE, 2018). doi:10.1109/IECON.2018.8592904.

39. Dornbusch, T., Wernecke, P. & Diepenbrock, W. A method to extract morphological
traits of plant organs from 3D point clouds as a database for an architectural plant
model. *Ecol Modell* **200**, 119–129 (2007).

40. Pound, M. P., French, A. P., Murchie, E. H. & Pridmore, T. P. Automated recovery of
three-dimensional models of plant shoots from multiple color images. *Plant Physiol*

166, 1688–1698 (2014).

41. Kempthorne, D. M. *et al.* Surface reconstruction of wheat leaf morphology from
three-dimensional scanned data. *Functional Plant Biology* **42**, 444–451 (2015).

42. Kazhdan, M., Bolitho, M. & Hoppe, H. *Poisson Surface Reconstruction.*
Eurographics Symposium on Geometry Processing (2006).

43. Yang, M. Der, Chao, C. F., Huang, K. S., Lu, L. Y. & Chen, Y. P. Image-based 3D
scene reconstruction and exploration in augmented reality. *Autom Constr* **33**, 48–60
(2013).

44. Zhu, F. *et al.* 3D Reconstruction of Plant Leaves for High-Throughput Phenotyping.
in *Proceedings - 2018 IEEE International Conference on Big Data, Big Data 2018*
4285–4293 (IEEE, 2018). doi:10.1109/BigData.2018.8622428.

45. Ando, R., Ozasa, Y. & Guo, W. Robust Surface Reconstruction of Plant Leaves from
3D Point Clouds. *Plant Phenomics* **2021**, (2021).

46. Ronneberger, O., Fischer, P. & Brox, T. U-net: Convolutional networks for
biomedical image segmentation. in *Lecture Notes in Computer Science (including*
subseries Lecture Notes in Artificial Intelligence and Lecture Notes in
Bioinformatics) vol. 9351 234–241 (2015).

47. He, K., Zhang, X., Ren, S. & Sun, J. Deep Residual Learning for Image
Recognition. in *2016 IEEE Conference on Computer Vision and Pattern*
Recognition (CVPR) vols 2016-Decem 770–778 (IEEE, 2016).

48. Buslaev, A. *et al.* Albumentations: Fast and flexible image augmentations.
Information (Switzerland) **11**, (2020).

49. Lowe, D. G. Distinctive image features from scale-invariant keypoints. *Int J Comput*
Vis **60**, 91–110 (2004).

50. Rothermel, M., Wenzel, K., Fritsch, D. & Haala, N. SURE - Photogrammetric
Surface Reconstruction from Imagery. in *Proceedings LC3D Workshop* (Berlin,
2012).

51. Furukawa, Y., Curless, B., Seitz, S. M. & Szeliski, R. Towards internet-scale multi-
view stereo. in *Proceedings of the IEEE Computer Society Conference on Computer*
Vision and Pattern Recognition 1434–1441 (IEEE, 2010).
doi:10.1109/CVPR.2010.5539802.

52. Hirschmuller, H. Stereo Processing by Semiglobal Matching and Mutual
Information. *IEEE Trans Pattern Anal Mach Intell* **30**, 328–341 (2008).

53. Remondino, F., Spera, M. G., Nocerino, E., Menna, F. & Nex, F. State of the art in
high density image matching. *The Photogrammetric Record* **29**, 144–166 (2014).

54. Zhou, Q.-Y., Park, J. & Koltun, V. Open3D: A Modern Library for 3D Data
Processing. (2018).

55. Mörwald, T., Balzer, J. & Vincze, M. Modeling connected regions in arbitrary planar
point clouds by robust B-spline approximation. *Rob Auton Syst* **76**, 141–151 (2016).

56. de Boor, C. On calculating with B-splines. *J Approx Theory* **6**, 50–62 (1972).

57. Mörwald, T. Object modelling for cognitive robotics. (Technische Universität Wien,
2013).

58. Pearcy, R. W., Muraoka, H. & Valladares, F. Crown architecture in sun and shade
environments: assessing function and trade-offs with a three-dimensional simulation
model. *New Phytologist* **166**, 791–800 (2005).

59. Niinemets, Ü. Photosynthesis and resource distribution through plant canopies.
Plant Cell Environ **30**, 1052–1071 (2007).

60. Evers, J. B., Letort, V., Renton, M. & Kang, M. Computational botany: Advancing
plant science through functional-structural plant modelling. *Ann Bot* **121**, 767–772
(2018).

Acknowledgements

We thank Horiguchi, R., Inbe, N., Suzuki, M., and Kudo, Y. for their assistance in making multi-view image datasets. We acknowledge the National Agriculture and Food Research Organization (NARO) for providing the seeds used in this study. The Environmental Control Center for Experimental Biology at Kyushu University provides cultivation space.

Author contributions

KN conceived and designed this study. DS and KN performed the implementation and analyzed the results. DS and KN were major contributors to writing the manuscript. All authors read and approved the final manuscript.

Competing interests

The authors declare no competing interests.

Funding Declaration

This study was supported by Japan Society for the Promotion of Science (JSPS) KAKENHI Grant Numbers 20H01381, 21K14947, 22H04727, 25K09354 (to K.N.), Japan Science and Technology Agency (JST) PRESTO Grant Number JPMJPR16O5 (to K.N.), JST MIRAI Grant Number JPMJMI20G6 (to K.N.); Moonshot R&D Grant Number JPMJMS2021 (to K.N.), and Bio-oriented technology Research Advancement InstitusioN (BRAIN) Moonshot R&D Grant Number JPJ009237 (to K.N.).

Data availability

The datasets and source code used during the current study are available in Zenodo (https://doi.org/10.5281/zenodo.10065546, https://doi.org/10.5281/zenodo.10488045, https://doi.org/10.5281/zenodo.10489251, https://doi.org/10.5281/zenodo.10489292, and https://doi.org/10.5281/zenodo.10489326), GitHub (https://github.com/MorphometricsGroup/mask-prediction-app), and DockerHub (https://hub.docker.com/r/noshita/leaf-surf-recon).

Supplementary Information

Figure S1. Photogrammetry system.

Figure S2. Processing times of mask image generation per single 512×512 tile.

Figure S3. Time series data of class-weighted Dice loss and IoU of the U-Net models during training on the entire dataset$_t$.

Table S1. Leaf area.

Figures and Tables

Fig 1. A phenotyping workflow based on the 3D reconstruction. From multi-view images of a target plant individual, mask images are generated for the (A) SfM/MVS pipeline (B). The 3D morphological data is obtained as point cloud data using SfM/MVS pipeline. Several phenotypic values (e.g., leaf area) are estimated through morphological modeling (C).

Fig 2. Mask image generation using U-Net model. Results of the semantic segmentation using the U-Net models for (A) three-class segmentation (soybean, stake, and background) and (B) four-class segmentation (soybean, stake, stage, and background) on an individual soybean (Saga zairai). Ground truth data was generated by manual annotation. Each color in the ground truth and the prediction corresponds to each class. (C) Each image in multi-view images was divided and resized into multiple 512×512 tiles with the six different magnifications (1/2×, 1/3×, 1/4×, 1/5.4×, 1/6× and 1/6.75×), for input images to the U-Net models. Lower magnification input image contains larger region (lower row). (D) Soybean mask images (foreground: soybean, background: stake and background) and soybean/stage mask images (foreground: soybean and stage, background: stake and background) were generated based on the predictions of three- and four-class segmentation models, respectively. The examples were mask images of a soybean individual (N2295 #1).

Fig 3. The performance of U-Net models on different magnifications of input image.

The IoU scores three-class segmentation for (A) all classes, and each class; (B) soybean, (C)

stake, and (D) background. (E) The processing time of three-class segmentation for an

individual plant. The IoU scores four-class segmentation for (F) all classes, and each class;

(G) soybean, (H) stake, (I) stage, and (J) background. (K) The processing time of four-class

segmentation for an individual soybean.

Fig 4. User interface of the web application for mask image generation. (1) Images for

generating masks are uploaded via file uploader widget. User sets (2) input image size and

(3) overlapping ratio, and (4) selects an image for showing an example for dividing. Finally,

(5) one of the mask types is selected, and (6) start prediction. Once processing is complete,

the mask images can be downloaded as a zip file.

Fig 5. The 3D reconstruction based on SfM/MVS pipeline with the four different mask

usage scenarios. Each column corresponds to (i) no masks, (ii) masks before SfM, (iii)

masks after SfM, and (iv) two masks. The reconstructed point clouds of a soybean individual

(Keumdu #1) at 12 WAS (the second row), 8 WAS (the third row), and 4 WAS (the fourth

row). The black bars represent 20 cm. (A-L) Leaflets corresponding to red circles in the first

left column. (M-P) Key points and tie points detected in the four different scenarios.

Fig 6. The processing times on the four different mask usage scenarios. The processing

times of (A) total of mask image generation (MIG), SfM, and MVS, (B) MIG, (C) SfM, and

(D) MVS. Multiple comparison was conducted on the processing times among four scenarios

(Mann-Whitney U test, **: $0.001 < p <= 0.01$, ***: $0.0001 < p <= 0.001$, ****: $p <= 0.0001$).

Fig 7. Leaf surface reconstruction and leaf area estimation. Scatter diagrams of leaf area

estimated by (A) Poisson surface reconstruction and (B) B-spline surface fitting, against the

destructive measurements. (C) Both methods estimated leaf area consistent with the

destructive measurements (Hime daizu #7 S01_t). (D) Poisson surface reconstruction

overestimated leaf area while B-spline surface fitting estimated accurately (Hime daizu #7

S07_t). (E) Both methods failed to reconstruct leaf surface well, then overestimated leaf area

(Shiro mitsu mame #3 S06_r). (F) The reconstructed 3D point cloud data (Shiro mitsu mame

#3 S07_t) based on scenario (i) and (iv).

Table 1. Specimen list in the dataset$_m$.

Table 2. Cross-validations of the U-Net models for three- and four-class segmentation.

For each fold, different values of class weights were used for calculating class-weighted Dice

loss.

Table 3. The average numbers of key points and tie points. The number of key points and

tie points detected in SfM/MVS pipeline were counted for $dataset_m$ across four scenarios.

Table 4. The four leaflets which were overestimated leaf area using B-spline surface

fitting. The leaf areas of 190 leaflets were overestimated when B-spline surface fitting

against the destructive measurements was used.

multi-view images

A
mask image
generation

mask images

B SfM/MVS

point cloud data

phenotypic values

• ITEM A
• ITEM B
• ITEM C
⋮

C morphological modeling

e.g. leaf surface reconstruction

Fig. 1

Fig. 2

Fig. 3

Soybean Mask Prediction

Please upload your image files

Drag and drop files here
Limit 200MB per file • PNG, JPG, JPEG ① Browse files

📄 SSP_032_00256_01_71074004861.JPG 6.1MB ✕

📄 SSP_032_00255_05_31074008483.JPG 5.9MB ✕

📄 SSP_032_00254_04_71074003363.JPG 6.1MB ✕

Showing page 1 of 86 ‹ ›

Uploading images 256

Input an integer number from 512 to 3456

② | 512 — + |

The input number is `512`

Input an overlap ratio from 0.05 to 0.95

③ | 0.05 — + |

Select an image of all you uploaded

④ | 0 ⌄ |

Each cropped image will be resized into 512x512

Image Name : SSP_001_00001_08_71074003452.JPG

Image Size : (width, height) = (5184 px, 3456 px)

The number of cropped images with blue color : n_column = 11, n_row = 8

The size of the cropped image with red color : (width, height) = (512 px, 512 px)

The overlapping value : horizontal direction = 44 px, vertical direction = 91 px

Please select which mask type you want to predict

⑤ 🔴 soybean
⭕ soybean & stage

You selected "soybean".

Fig. 4 ⑥ | Start prediction |

Fig. 5