Violated predictions enhance the representational fidelity of visual features in perception

Reuben Rideaux[1,2*], Phuong Dang[2], Luke Jackel-David[2], Zak Buhmann[2], Dragan Rangelov[2,4] & Jason B Mattingley[2,3]

[1]School of Psychology, The University of Sydney, Camperdown, Australia

[2]Queensland Brain Institute, The University of Queensland, St Lucia, Australia

[3]School of Psychology, The University of Queensland, St Lucia, Australia

[4]School of Economics, The University of Queensland, St Lucia, Australia

*corresponding author: reuben.rideaux@sydney.edu.au

Acknowledgements: This work was supported by Australian Research Council (ARC) Discovery Early Career Researcher Awards awarded to RR (DE210100790). RR was also supported by a National Health and Medical Research Council (NHMRC; Australia) Investigator Grant (2026318). JBM was supported by a NHMRC Investigator Grant (GNT2010141)

The authors declare no competing interests

SUMMARY

Predictive coding theories argue that recent experience establishes expectations that generate prediction errors when violated[1,2]. In humans, brain imaging studies have revealed unique signatures of violated predictions in sensory cortex[3–6], but the perceptual consequences of these effects remain unknown. We had observers perform a dual-report task on the orientation of briefly presented gratings within predictable or random sequences, while we recorded their pupil size as an index of surprise. Observers first made a speeded response to categorize grating orientation (clockwise or counterclockwise from vertical), then reproduced the orientation without time pressure by rotating a bar. This allowed us to separately assess response speed and precision for the same stimuli. Critically, on half the trials, the target orientation deviated from the spatiotemporal structure established by the preceding gratings. Observers responded faster and more accurately to unpredicted gratings, and pupillometry provided physiological evidence of observers' surprise in response to these events. In a second experiment, we cued the spatial location and timing of the grating and found the same pattern of results, demonstrating that unpredicted orientation information is sufficient to produce faster and more precise responses, even when the location and timing of the relevant stimuli are fully expected. These findings reveal the perceptual consequences of prediction errors and indicate that unexpected events are prioritized by the visual system both in terms of processing speed and representational fidelity.

RESULTS & DISCUSSION

Predictive coding theories argue that *prediction errors* are generated when bottom-up sensory inputs deviate from top-down expectations[2]. There is broad consensus that prediction errors are associated with increased neural activation[5–9], which is typically observed during the initial processing cascade in sensory cortices associated with the unexpected stimulus[4,10], but has also been reported in subcortical regions[11]. By contrast, it remains unclear how these modulations reshape the pattern activity that represents the unexpected stimulus.

One might hypothesize that expected events should produce more precise representations, because the brain can anticipate incoming sensory signals and provide an optimized neural environment to receive them; for example, by increasing the gain of neurons tuned to the expected stimulus features. Such benefits of anticipation are evident in sequential dependency experiments, where observers respond faster and more accurately to events that comply with a recent history of alternations and repetitions between two states (e.g., reporting on state "A" after exposure to states ABAB) than those that violate this pattern (e.g., reporting on state "A" after exposure to states BABA; Remington, 1969). There is also behavioural evidence that memory recall is more precise for expected visual objects then unexpected [13]. By contrast, it seems equally reasonable to hypothesize that *unexpected* events might produce more precise representations. Unexpected or 'surprising' events are more likely to have harmful consequences than expected ones precisely because they have not been anticipated and thus an appropriate response has not been prepared. On this account, prioritizing the speed and fidelity with which unexpected events are represented may have adaptive value. Similarly, prioritizing unexpected events to effectively update internal predictive models may support adaptive future behaviours, e.g., caution after narrowly avoiding an obstruction on the road[14,15].

Neuroimaging studies addressing the question of how prediction errors shape sensory representations have produced inconsistent findings. Evidence from functional magnetic resonance imaging (fMRI) suggests that neural representations formed by unexpected stimuli are less precise than those of expected stimuli[5]. In direct contrast, evidence from electroencephalography (EEG) in humans and two-photon

calcium (Ca^{2+}) imaging in mice indicates that neural representations formed by unexpected stimuli are more precise than those of expected stimuli[4,10]. Adding further uncertainty to this question, a recent study found no difference between the neural representations formed by expected and unexpected stimuli[16]. The hierarchical nature of predictive coding, combined with the multitude of approaches for studying brain function, likely contributes to the tangle of inconsistent findings on how prediction errors shape sensory representations. These discrepancies might be due to stimulus and experimental design choices (e.g., some designs may not sufficiently establish sensory predictions), but they might also be explained by biophysical differences between neural recording techniques (e.g., fMRI and EEG) or analytic tools for estimating representational precision from neural activity (e.g., linear discriminant analysis versus inverted encoding)[17–19]. To test the influence of prediction errors on the representation of stimuli, here we sought to measuring perception directly, rather than indirectly via neural recordings. Specifically, we measured how quickly and precisely human observers reported the orientation of unexpected visual stimuli relative to identical stimuli presented randomly such that no predictive information was available.

To test whether perception is different for unexpected stimuli relative to stimuli for which no expectation has been formed, we had observers (N = 60 adults) perform a dual-report task on the orientation of briefly presented gratings embedded within sequences that were either predictable (consistent clockwise or counterclockwise rotation) or random (see **Fig. 1**). A similar presentation sequence was previously used previously to measure prediction errors in single neurons in mouse visual cortex[10]. Observers first made a speeded binary response to categorize grating orientation (clockwise or counterclockwise from vertical), then reproduced the orientation without time pressure by rotating a bar. This allowed us to separately assess response speed and precision for the same stimulus. Critically, while the target grating orientation was selected at random, the orientations of the preceding gratings were either sequential (rotating at 30º per grating) or random. Thus, in the sequential condition, an expectation was established and subsequently violated by the target grating. By contrast, in the random condition observers had no stimulus information on which to establish an expectation of grating orientation (**Fig. 1a**). To control for motion

transients, we matched the penultimate and target grating orientations between random and sequential conditions. As shown in **Figure 1b-c**, observers responded faster and more precisely to unexpected grating stimuli than to random stimuli (response time, $F_{1,51}=26.17$, $P=4.78e^{-6}$; precision, $F_{1,51}=34.05$, $P=3.717e^{-7}$).

Figure 1. Unexpected stimuli provoke faster and more precise responses. a) An illustration of the trial design. Observers viewed a sequence of gratings and were tasked with making a speeded response (clockwise or counterclockwise from vertical) about the target grating before precisely reproducing its orientation. Critically, while the target grating orientation was selected at random, the orientations of the preceding gratings were either sequential (rotating at 30º per grating; blue sequence) or random (black sequence). Thus, in the sequential condition, an expectation was established and subsequently violated by the target grating, whereas in the random condition there was no expectation. **b, c)** The average (**b**) (speeded) response times and (**c**) (reproduction) precision in the random (black) and sequential (blue) conditions. Asterisks indicate significant differences of $P<.001$.

Response times are typically inversely related to accuracy, such that faster responses are associated with less accurate judgements, i.e., the speed-accuracy trade-off[20]. By contrast, here, using a dual-response task, we found that unexpected stimuli provoked both *faster* and *more precise* responses. We tested the inter-individual relationship between response time and precision and found positive correlations in both random and sequential conditions (random, $r=.59$, $P=4.20e^{-6}$; sequential, $r=.55$, $P=2.68e^{-5}$; **Fig. 2a**). This is likely explained by individual differences in factors that influence general task performance, such as fatigue and motivation. To control for these factors and isolate the behavioural changes associated with processing unexpected stimuli, we tested whether the difference in response times associated with unexpected stimuli was related to the difference in precision. We found these changes were positively correlated ($r=.459$, $P=6.28e^{-4}$; **Fig. 2b**), suggesting that improvements in response time and precision associated with unexpected stimuli are supported by a common underlying mechanism.

Figure 2. Shared mechanisms and tuning properties for visual predictions. The relationship between (**a**) response time and (**b**) precision across observers in the random and sequential conditions. **c**) The relationship between the difference (random – sequential) in response time and precision across observers. Black lines indicate line-of-best-fit. **d**) Response time and **e**) precision as a function of the magnitude of expectation violation (operationalized as the angular difference between the expected and target orientation) in the random and sequential conditions. Note that while there was no clear expectation in the random condition, the trials in this condition were also grouped according to the angular difference between the penultimate and target grating. Filled circles indicate magnitudes at which there was a significant difference between conditions.

The orientation of the target grating was randomized, which means that the target violated the expectation established by the preceding gratings on most of the sequential condition trials. However, the magnitude of this violation (operationalized as the angular difference between the expected and target orientation) ranged between ±90°; thus, on some trials the target grating effectively satisfied, rather than violated, this expectation. If improved response time and precision are due to violations of expectation, these improvements should vary as a function of violation magnitude. In line with this reasoning, for both response time and precision, we found a main effect of condition (response time, $F_{1,51}=23.82$, $P=1.07e^{-5}$; error, $F_{1,51}=31.00$, $P=9.65e^{-7}$) and an interaction between violation magnitude and condition (response time, $F_{7,51}=12.19$, $P=5.44e^{-14}$; error, $F_{7,51}=12.65$, $P=1.59e^{-14}$; **Fig. 2d, e**). Pairwise comparisons revealed that response time and precision were worst when expectations were satisfied and best when expectations were violated by >=45°. Indeed, when stimuli were expected (i.e., 0° angular offset in the sequential condition), response

time and precision were worse than when there was no clear expectation (response time, t_{51}=5.14, P=4.45e^{-6}; error, t_{51}=5.89, P=3.04e^{-7}). Thus, the curve formed by the data from the sequential condition effectively represent the tuning function of observers' predictions. Interestingly, the tuning curve appears to be suppressive, that is, it reflects slower and less precise responses for expected stimuli, consistent with an inhibitory predictive signal. Given that no consistent expectation is generated by random sequences, performance in the random condition should be invariant to the difference between the penultimate and target gratings. However, we observed faster and more precise responses when the penultimate and target gratings were similar. This is likely explained by temporal integration, since the stimuli were presented briefly (250 ms) and in rapid succession (32 ms inter-stimulus interval, ISI). When similar gratings appeared one after another, observers receive a clearer sensory signal from which to encode orientation. We note that this finding was incidental to the purpose of our investigation, and responses for unexpected stimuli were nevertheless faster and more precise when compared with the flat profile of responses in the random condition.

Here and in previous neuroimaging studies of prediction errors[4,5,10], the spatiotemporal structure of visual stimuli was manipulated to establish and violate expectations. It is unclear, however, whether these stimuli sufficiently establish and violate expectation. Pupil dilation is an involuntary physiological marker of arousal/surprise[21]. If observers' expectations were violated by the target gratings, we would expect their pupils to dilate in response to these stimuli. For both the sequential and random sequences, we observed increased pupil diameter in response to the target grating, which may be explained by either surprise in response to all stimuli or a reduction in luminance between the blank ISI and the target grating (**Fig. 3a, b**). Critically, when we examined the difference between random and sequential conditions, pupil diameter was significantly larger following target gratings with larger expectation violations (>±30° from the expected orientation; **Fig. 3c**) from 563 – 1100 ms after target onset. This timing is consistent with previous pupillometry work[21], and provides physiological evidence that observers were surprised by gratings that violated the spatiotemporal expectation established in the sequential condition. Critically, there was also a positive relationship between pupil diameter and faster response time in this condition (r=.39, P=.0098; **Fig. 3d**), suggesting a link between

violated expectations and improved performance. The positive relationship between pupil diameter and precision did not reach significance ($r=.25$, $P=.1119$; **Fig. 3e**), which may be because there was a longer delay between the unpredicted stimulus and the reproduction response than the speeded response. In addition to previous work showing increased cortical activity in response to unexpected events[5,7–9], recent fMRI work has found increased pupil diameter and increased activity in subcortical regions (including the locus coeruleus), which are associated with neuromodulatory systems (dopamine, serotonin, and acetylcholine)[11]. Our findings complete the characterization of this coordinated response to unexpected events, by revealing the perceptual consequences of potentially related cortical and subcortical activity, and their relationship with physiological markers of surprise.

Figure 3. Changes in pupil diameter associated with expectation violation. a) Change in pupil size in response to the target grating in the random condition, for trials with smaller and larger than ±30º expectation violation. The inset disk indicates the colours used to show the data for target gratings with orientations that were near to (gray) or far from (black) the expected orientation (white dashed line). **b**) Same as (**a**), but for the sequential condition. **c**) The difference in pupil size between random and sequential condition trials with larger and smaller expectation violations; colour mapping is the same as in (**a**, **b**). **d, e**) The difference in average response time (**d**) and precision (**e**) between random and sequential conditions as a function of the difference in pupil size. Note that while there was no clear expectation in the random condition, the trials in this condition were also grouped according to the angular difference between the penultimate and target grating. Shaded regions indicate ±SEM and the horizontal bar in (**c**) indicates a cluster corrected period of significant differences between random and sequential conditions. Solid and dashed rectangles in (**a-c**) indicate the target and preceding stimulus presentations, respectively.

Prioritization of unexpected events may be operationalized through neuromodulator-mediated engagement of attention systems[22–24]. To motivate observers to attend to all presented stimuli, we displayed a variable number (5-12) of gratings, such that the identity of the target grating was unknown until the response bar appeared. Thus, on most trials in the sequential condition, both the temporal identity and feature-specific (orientation) properties of the target grating were unexpected. To isolate the contribution of the feature-specific violation, we ran a further study (Experiment 2) in which the gratings not only rotated but also translated around the display in a circle, such that the target grating was either presented at a cued or uncued location (**Fig. 4a**). Thus, on half the trials observers were validly cued to the temporal identity and location of the target grating before it was presented. We assessed the influence of cueing by comparing performance between random and sequential sequences on trials where the target identity was cued validly or invalidly (**Fig. 4b**). For both response time and precision, we found significant effects of orientation, target identity, and their interaction (all $P<.05$). Paired t-tests revealed that the results from the uncued condition replicated those from the main experiment (response time, $t_8=4.85$, $P=.001$; error, $t_8=7.64$, $P=6.08e^{-5}$; **Fig. 4c, d**). Critically, we also found faster and more precise responses in the sequential condition when the target identity was cued (response time, $t_8=5.41$, $P=6.38e^{-4}$; error, $t_8=6.87$, $P=1.29e^{-4}$; **Fig. 4e, f**). Taken together, these results confirm that unexpected features of stimuli (i.e., orientation) are sufficient to produce faster and more precise responses, even when the location and timing of the relevant stimuli are expected.

Figure 4. Unexpected stimulus features provoke faster and more precise responses. An illustration of the trial design for Experiment 2, which was the same as in the first experiment, except that stimuli moved around the display such that the target grating was presented either **b**) before (uncued) or at a predefined location (cued, illustrated by dashed red line). Thus, observers were cued to the identity of the target grating before it was presented in the predictable condition. **c**) Response time and **d**) precision as a function of expectation violation, for random and sequential sequences, when the target location was uncued. **e,f**) Same as (**c,d**), but when the target location was cued.

Our findings reveal the perceptual consequences of prediction errors and indicate that unexpected events in the environment are prioritized by the visual system both in terms of processing speed and representational fidelity. Prioritizing unexpected events likely supports immediate and future adaptive behaviours through multiple operations, e.g., rapid responses to potentially harmful events and precise updating of internal predictive models[14,15], and may be operationalized through subcortically regulated attention systems[22–24].

The finding that unexpected events are reproduced more precisely is consistent with EEG data from humans[4] and Ca[2+] imaging data from mice[10], but appears to contradict previous fMRI data in humans[5]. The former two studies employed an analytic method known as inverted encoding, which takes inspiration from single-unit physiology to combine measurements of neural activity and known stimulation properties to yield a set of hypothetical tuning functions (from which estimates of representational bias, amplitude, and precision can be derived). By contrast, the latter

fMRI study used multivariate pattern classification, which employs linear discrimination to identify a border between two classes in multivariate space (from which a measure of classification accuracy is derived). The classification accuracy between two stimuli (e.g., clockwise and counterclockwise oblique gratings) may not be as indicative of representational precision as the width of a tuning curve formed by neural responses to a range of stimuli along the same feature dimension. The discrepancy may also be due to biophysical differences between the different recording techniques.

How do our findings fit with previous behavioural studies? Sequential dependency paradigms, which establish expectations differently from those typically used to study prediction errors, show that expected events are responded to faster and more accurately than unexpected events[12]. By contrast, here we found that observers responded faster to unexpected than expected stimuli. This suggests distinct mechanisms drive the behavioural consequences of expectancy associated with classic two-state sequential dependency paradigms and those observed here. Indeed, our finding that unexpected events are processed faster provide some support for the claim that the differences observed in sequential dependency paradigms are a result of motor priming, rather than a change in sensory encoding[25]. Abreo et al. (2023)[13] used a similar design to that employed here (**Supplementary Fig. 1a**), but concluded that expected gratings were reproduced more precisely, which seems to be in direct conflict with our findings. However, re-analysis of their data revealed that their results may have been driven by temporal integration of the penultimate and target gratings, and that the number of stimuli used by Abreo et al. (4-7) – approximately half the number used here (6-13) – did not establish a sufficiently reliable expectation.

In summary, here we resolve inconsistent findings on the influence of prediction errors on sensory encoding by showing that unexpected events are responded to faster and reproduced more precisely than those that are either expected or occur randomly and thus without any explicit expectation. These findings offer empirical evidence for neural prioritization of unexpected events, which support immediate adaptive responses and updating of future predictions.

STAR METHODS

Participants. Sixty neurotypical human adults (mean±standard deviation age, 24.8±3.9 years; 43 females) participated in Experiment 1 and ten in Experiment 2 (mean±standard deviation age, 24.1±2.3 years; 8 females). Observers were recruited from The University of Queensland, had normal or corrected-to-normal vision (assessed using a standard Snellen eye chart). All but three participants (authors PD, LJ and ZB) were naïve to the aims of the experiment and all gave informed written consent. The experiment was approved by The University of Queensland Human Research Ethics Committee.

Apparatus. The experiment was conducted in a dark room. The stimuli were presented on a 32-inch Display++ LCD monitor (Cambridge Research Systems Ltd., Rochester, UK) with 1920 x 1080 resolution and a refresh rate of 120 Hz. Viewing distance was maintained at 48 cm using a chin and head rest, meaning the screen subtended 62.21º x 34.99º (each pixel 3.2' x 3.2'). Stimuli were generated in MATLAB v2020a (The MathWorks, Inc., Matick, MA) using Psychophysics Toolbox [26,27] v3.0.18.13 (see http://psychtoolbox.org/). Gaze direction and pupil diameter were recorded monocularly (right eye) at 1 kHz using an EyeLink 1000 (SR Research Ltd., Ontario, Canada).

Stimuli, task, and procedure. The stimuli comprised sinewave gratings (1 cycle/º, full contrast, phase randomized between trials) presented centrally within a circular aperture (radius 4º), which was smoothed at the edges, on a mid-grey background. A centrally positioned green fixation dot (radius 0.25º) was presented to reduce eye movements.

Trials consisted of 5-12 (counterbalanced across trials) sequentially presented grating stimuli (initial sequence) followed by 2 additional gratings (penultimate and target; **Fig. 1a**). The orientations of the gratings in the initial sequence were either randomly selected between 0-180º (random condition) or rotated consistently by ±30º from a random start orientation (sequential condition; rotation direction counterbalanced across trials). The orientations of the penultimate and target gratings were matched between trials of the two conditions, such that for each sequential condition trial there was a random condition trial with the same penultimate and target gratings. In the sequential condition, the penultimate grating orientation was consistent

with the rotation of the preceding expectation sequence (i.e., ±30° from the final grating in the sequence), while the target grating was selected at random (1-180°). Each grating was presented for 250 ms, separated by a blank 32 ms inter-stimulus-interval. Following the presentation of the target grating and a 32 ms blank period, a black vertical bar (length 3.2°) was displayed and observers were given 2 s to indicate whether the target grating was oriented clockwise or counterclockwise from vertical using the right or left mouse button, respectively. Upon responding, the black bar was displayed at a random orientation (between 0-180°) and the observers were then required to use the mouse to reproduce the orientation of the target grating (no time limit). Observers were instructed to respond quickly for the two-alternative forced choice (2AFC) task and precisely for the reproduction task. A variable number of gratings were presented in each trial to motivate observers to attend to the entire sequence. This was repeated 24 times per block and observers performed 16 blocks of trials (~60 min), with equal numbers of random and sequential orientation trials interleaved pseudo-randomly across the session.

Experiment 2 was conducted with a similar design to that of Experiment 1, except that the position of the gratings was manipulated (**Fig. 4a, b**). Specifically, on each trial, gratings were positioned such that the stimulus appeared to translate around an imaginary circle (radius 6°, step size 12.85°, direction counterbalanced across trials) in the center of the screen. On half of the trials, the target grating was presented on a cardinal axis aligned to the center of the screen (i.e., above, below, left, or right). The target axis was randomized between blocks and indicated throughout the experiment by a white dot (radius 0.25°) positioned at 10° from center along the corresponding axis; black dots were presented at the same eccentricity on the three remaining axes. On the other half of the trials, the target grating was presented before it reached the target axis. Thus, observers were aware that gratings presented on the target axis were target gratings. The response bar was presented at the location of the target grating. This was repeated 24 times per block and observers performed between 48 and 60 blocks of trials (~240 min, spread across multiple sessions).

Eye tracking. Pupil size recordings were epoched to between -500 ms to 1500 ms around target stimulus presentation, normalized to each observer's average pupil size

across the experiment, and a linear model fit to the 500 ms period prior to stimulus presentation was used to baseline each epoch. Partially missing data (e.g., due to blinks) was interpolated. Pupil data from two observers were not collected due to hardware issues and observers with an average pupil diameter >3 standard deviations from the group mean were omitted from further analyses (n=3).

We found a single period when observers' pupil diameter was significantly influenced by our experimental manipulation of expectation. To test the relationship between pupil diameter and behaviour, we calculated the average difference in pupil diameter during this period, for each observer, and correlated this with behavioural performance.

Re-analysis of published data. To understand the discrepancy between our results and those of Abreo et al. (2023), we re-analyzed their data. We computed response precision as a function of expectation violation magnitude (unexpected condition) and angular distance between penultimate and target grating (random condition). We also computed precision in the expected condition, which is the same as data in the unexpected condition, at zero expectation violation.

Statistical analyses. Statistical analyses were performed in MATLAB v2020a using CircStat Toolbox v1.12.0.0[28]. Observers' proportion correct and average response time on the 2AFC (speeded) task was calculated; data from observers who scored <.75 correct across all trials were omitted from further analyses (main experiment, n=8; control, n=1). Average error on the reproduction task was calculated as the angular standard deviation between the target and response orientations. We only included trials on which the speeded task was answered correctly (91.1%), but this did not change the pattern of results. Repeated measures analysis of variance (ANOVA) and paired *t*-tests were applied to test for differences between conditions. The robust correlation toolbox[29] was used to compute skipped Pearson correlations (default boxplot rule used to identify outliers) to test the relationship between measurements.

When testing the difference in pupil diameter between conditions across time, a cluster correction was applied to mitigate the inflated risk of false positives associated with conducting multiple tests. We began by calculating the *t*-statistic at each time point. Next, we calculated the summed value of these statistics (separately for positive and negative values) within contiguous temporal clusters of significant

values. We then simulated the null distribution of the maximum summed cluster values using permutation (n=1000) of the condition labels, from which we derived the 95% percentile threshold value. Clusters identified in the data with a summed effect-size value less than the threshold were considered spurious and removed. A one-tailed t-test was used to test for increased pupil diameter, as we had (a priori) hypothesised that pupil dilation would increase in "surprising" trials. Two-tailed tests were used for all other comparisons.

REFERENCES

1. Rao, R.P.N., and Ballard, D.H. (1999). Predictive coding in the visual cortex: a functional interpretation of some extra-classical receptive-field effects. Nat Neurosci *2*, 79–87. 10.1038/4580.

2. Friston, K. (2005). A theory of cortical responses. Philosophical Transactions of the Royal Society B: Biological Sciences *360*, 815–836. 10.1098/rstb.2005.1622.

3. Ouden, H.E.M. den, Daunizeau, J., Roiser, J., Friston, K.J., and Stephan, K.E. (2010). Striatal Prediction Error Modulates Cortical Coupling. J. Neurosci. *30*, 3210–3219. 10.1523/JNEUROSCI.4458-09.2010.

4. Tang, M.F., Smout, C.A., Arabzadeh, E., and Mattingley, J.B. (2018). Prediction error and repetition suppression have distinct effects on neural representations of visual information. eLife *7*, e33123. 10.7554/eLife.33123.

5. Kok, P., Jehee, J.F.M., and de Lange, F.P. (2012). Less Is More: Expectation Sharpens Representations in the Primary Visual Cortex. Neuron *75*, 265–270. 10.1016/j.neuron.2012.04.034.

6. Alink, A., Schwiedrzik, C.M., Kohler, A., Singer, W., and Muckli, L. (2010). Stimulus Predictability Reduces Responses in Primary Visual Cortex. J. Neurosci. *30*, 2960–2966. 10.1523/JNEUROSCI.3730-10.2010.

7. Den Ouden, H., Kok, P., and De Lange, F. (2012). How Prediction Errors Shape Perception, Attention, and Motivation. Frontiers in Psychology *3*.

8. Meyer, T., and Olson, C.R. (2011). Statistical learning of visual transitions in monkey inferotemporal cortex. Proceedings of the National Academy of Sciences *108*, 19401–19406. 10.1073/pnas.1112895108.

9. Todorovic, A., Ede, F. van, Maris, E., and Lange, F.P. de (2011). Prior Expectation Mediates Neural Adaptation to Repeated Sounds in the Auditory Cortex: An MEG Study. J. Neurosci. *31*, 9118–9123. 10.1523/JNEUROSCI.1425-11.2011.

10. Tang, M.F., Kheradpezhouh, E., Lee, C.C.Y., Dickinson, J.E., Mattingley, J.B., and Arabzadeh, E. (2023). Expectation violations enhance neuronal encoding of sensory information in mouse primary visual cortex. Nat Commun *14*, 1196. 10.1038/s41467-023-36608-8.

11. Mazancieux, A., Mauconduit, F., Amadon, A., Willem de Gee, J., Donner, T.H., and Meyniel, F. (2023). Brainstem fMRI signaling of surprise across different types of deviant stimuli. Cell Reports *42*, 113405. 10.1016/j.celrep.2023.113405.

12. Remington, R.J. (1969). Analysis of sequential effects on choice reaction times. Journal of Experimental Psychology *82*, 250. 10.1037/h0028122.

13. Abreo, S., Gergen, A., Gupta, N., and Samaha, J. (2023). Effects of satisfying and violating expectations on serial dependence. Journal of Vision *23*, 6–6. 10.1167/jov.23.2.6.

14. Friston, K. (2009). The free-energy principle: a rough guide to the brain? Trends in Cognitive Sciences *13*, 293–301. 10.1016/j.tics.2009.04.005.

15. Soltani, A., and Izquierdo, A. (2019). Adaptive learning under expected and unexpected uncertainty. Nat Rev Neurosci *20*, 635–644. 10.1038/s41583-019-0180-y.

16. den Ouden, C., Zhou, A., Mepani, V., Kovács, G., Vogels, R., and Feuerriegel, D. (2023). Stimulus expectations do not modulate visual event-related potentials in probabilistic cueing designs. NeuroImage *280*, 120347. 10.1016/j.neuroimage.2023.120347.

17. Brouwer, G.J., and Heeger, D.J. (2009). Decoding and reconstructing color from responses in human visual cortex. Journal of Neuroscience *29*, 13992–14003. 10.1523/JNEUROSCI.3577-09.2009.

18. Harrison, W.J., Bays, P.M., and Rideaux, R. (2023). Neural tuning instantiates prior expectations in the human visual system. Nat Commun *14*, 5320. 10.1038/s41467-023-41027-w.

19. Rideaux, R., West, R.K., Rangelov, D., and Mattingley, J.B. (2023). Distinct early and late neural mechanisms regulate feature-specific sensory adaptation in the human visual system. Proceedings of the National Academy of Sciences *120*, e2216192120. 10.1073/pnas.2216192120.

20. Woodworth, R.S. (1899). Accuracy of voluntary movement. The Psychological Review: Monograph Supplements *3*, i–114. 10.1037/h0092992.

21. Preuschoff, K., 't Hart, B., and Einhauser, W. (2011). Pupil Dilation Signals Surprise: Evidence for Noradrenaline's Role in Decision Making. Frontiers in Neuroscience *5*.

22. Feldman, H., and Friston, K. (2010). Attention, Uncertainty, and Free-Energy. Frontiers in Human Neuroscience *4*.

23. Hohwy, J. (2012). Attention and Conscious Perception in the Hypothesis Testing Brain. Front. Psychol. *3*, 21186. 10.3389/fpsyg.2012.00096.

24. Sara, S.J., and Bouret, S. (2012). Orienting and Reorienting: The Locus Coeruleus Mediates Cognition through Arousal. Neuron *76*, 130–141. 10.1016/j.neuron.2012.09.011.

25. Jentzsch, I., and Sommer, W. (2002). Functional localization and mechanisms of sequential effects in serial reaction time tasks. Perception & Psychophysics *64*, 1169–1188. 10.3758/BF03194765.

26. Brainard, D.H. (1997). The Psychophysics Toolbox. Spatial Vision *10*, 433–436. 10.1163/156856897X00357.

27. Pelli, D.G. (1997). The VideoToolbox software for visual psychophysics: Transforming numbers into movies. Preprint, 10.1163/156856897X00366 10.1163/156856897X00366.

28. Berens, P. (2009). CircStat: A MATLAB Toolbox for Circular Statistics. J. Stat. Soft. *31*. 10.18637/jss.v031.i10.

29. Pernet, C.R., Wilcox, R., and Rousselet, G.A. (2013). Robust Correlation Analyses: False Positive and Power Validation Using a New Open Source Matlab Toolbox. Front. Psychology *3*. 10.3389/fpsyg.2012.00606.

SUPPLEMENTARY MATERIAL

Abreo et al. (2023) used a similar design to that employed in Experiment 1 of the current study (**Supplementary Fig. 1a**), but concluded that expected gratings were reproduced more precisely than random or expected gratings, which seems to be in direct conflict with our findings. How can we resolve this discrepancy? We re-analyzed their data to test if precision changed as a function of the magnitude of expectation violation (**Supplementary Fig. 1b**). While there was a significant effect of violation magnitude ($F_{1,35}=15.96$, $P=3.61e^{-4}$), there was no effect of (random/unexpected) condition ($F_{7,35}=0.78$, $P=.384$) and a borderline significant interaction ($F_{7,35}=2.05$, $P=.049$). These results may indicate that the number of stimuli used by Abreo et al.) (4-7) – approximately half the number used here (6-13) – did not establish a sufficiently reliable expectation. This is further supported by the precision in the expected condition of their study (**Supplementary Fig. 1b**, pink marker), which is equivalent to the precision in the matched violation magnitude category for the random and unexpected conditions. Rather, the difference in precision across violation magnitudes in the study of Abreo et al. (2023) is likely the result of temporal integration of the penultimate and target gratings. This phenomenon appears to be less prominent in the random condition of our experiment, probably because Abreo et al. (2023) backward masked their target stimulus. Backward masking reduces the time afforded to process the target, thus increasing the relative benefit of congruent temporal integration with the penultimate grating. This backward masking also likely explains why the responses of their observers were less precise, on average, than those in our study.

Supplementary Figure 1. Re-analysis of published data supports prioritization of unexpected events. a) An illustration of the trial design used by Abreo et al. (2023), which was the same as that used in our first experiment, except they: 1) used fewer gratings to establish an expectation, 2) backward masked the target grating, and 3) did not include a speeded response. **b**) Re-analysis of data from Abreo et al. (2023) showing precision as a function of the magnitude of expectation violation (operationalized as the angular difference between the expected and target orientation) in the random and sequential conditions. The pink marker indicates data from a third "expectation" condition, where the target grating always satisfied the expectation established in the preceding sequence. Note that while there was no clear expectation in the random condition, the trials in this condition were also grouped according to the angular difference between the penultimate and target grating. Filled circles indicate magnitudes at which there was a significant difference between conditions.