Establishing the foundations for a data-centric AI approach for virtual drug

screening through a systematic assessment of the properties of chemical data

Allen Chong[1,2,*,^], Ser-Xian Phua[1,2,*], Yunzhi Xiao[2,*], Woon Yee Ng[4], Hoi Yeung Li[2],

Wilson Wen Bin Goh[1,2,3,5,6^]

[1]Lee Kong Chian School of Medicine, Nanyang Technological University, Singapore 636921

[2]School of Biological Science, Nanyang Technological University, Singapore 637551

[3]Center for Biomedical Informatics, Nanyang Technological University, Singapore 636921

[4]School of Computer Science and Engineering, Nanyang Technological University, Singapore 639798

[5]Center for AI in Medicine, Nanyang Technological University, Singapore 636921

[6]Division of Neurology, Department of Brain Sciences, Faculty of Medicine, Imperial College London

London W12 0NN

[*]These authors contributed equally to this work

[^]Corresponding authors

Goh, W.W.B (wilsongoh@ntu.edu.sg), ORCID: 0000-0003-3863-7501,

https://gohwils.github.io/biodatascience/

Chong, A. (chongallen@yahoo.com; kimsanallen.chong@ntu.edu.sg), ORCID: 0000-

0002-4049-8080

Summary

Researchers have adopted model-centric artificial intelligence (AI) approaches in
cheminformatics by using newer, more sophisticated AI methods to take advantage of
growing chemical libraries. It has been shown that complex deep learning methods
outperform conventional machine learning (ML) methods in QSAR and ligand-based
virtual screening[1-3] but such approaches generally lack explanability. Hence, instead of
developing more sophisticated AI methods (i.e., pursuing a model-centric approach), we
wanted to explore the potential of a data-centric AI paradigm for virtual screening. A
data-centric AI is an intelligent system that would automatically identify the right type of
data to collect, clean and curate for later use by a predictive AI and this is required
given the large volumes of chemical data that exist in chemical databases – PubChem
alone has over 100 million unique compounds. However, a systematic assessment of
the attributes and properties of suitable data is needed. We show here that it is not the
result of deficiencies in current AI algorithms but rather, poor understanding and
erroneous use of chemical data that ultimately leads to poor predictive performance.
Using a new benchmark dataset of BRAF ligands that we developed, we show that our
best performing predictive model can achieve an unprecedented accuracy of 99% with
a conventional ML algorithm (SVM) using a merged molecular representation (Extended
+ ECFP6 fingerprints), far surpassing past performances of virtual screening platforms
using sophisticated deep learning methods. Thus, we demonstrate that it is not
necessary to resort to the use of sophisticated deep learning algorithms for virtual
screening because conventional ML can perform exceptionally well if given the right
data and representation. We also show that the common use of decoys for training
leads to high false positive rates and its use for testing will result in an over-optimistic
estimation of a model's predictive performance. Another common practice in virtual
screening is defining compounds that are above a certain pharmacological threshold as
inactives. Here, we show that the use of these so-called inactive compounds lowers a
model's sensitivity/recall. Considering that some target proteins have a limited number
of known ligands, we wanted to also observe how the size and composition of the
training data impact predictive performance. We found that an imbalance training
dataset where inactives outnumber actives led to a decrease in recall but an increase in
precision, regardless of the model or molecular representation used; and overall, we
observed a decrease in the model's accuracy. We highlight in this study some of the
considerations that one needs to take into account in future development of data-centric
AI for CADD.

Introduction

The discovery and development of a new drug and subsequently, bringing it onto the
market is challenging and a major burden on time and finances. In a study of 63 drugs
developed by 47 companies (between 2009 and 2018), it was estimated that the
average cost of bringing a new drug to market is USD 1.33 billion[4]. To reduce cost and
time, attention has shifted to using computer-aided drug design (CADD) methods, which
has been relatively successful[5]. CADD allows researchers to better focus on drug
experiments that have a higher likelihood of success.

In recent years, interest in AI/ML, particularly deep learning methods for CADD has
grown. Deep neural networks have been shown to outperform machine learning (ML)
algorithms like random forest (RF) and support vector machine (SVM) for quantitative
structure-activity relationship (QSAR) and ligand-based virtual screening (LBVS). An
example being Dahl et al.'s multi-task deep neural network (MT-DNN) which was the
best performing architecture in the Merck Molecular Activity Kaggle Challenge[2,3]. A
molecule is normally tested in multiple assays and their MT-DNN was trained so that the
multiple output neurons each predicts the activity of the input molecule in a different
assay. Following the Merck Challenge, researchers performed a detailed study that
specifically compared the performance of deep neural nets (DNN) models to RF models
and showed that DNN models routinely made better predictions on a series of large,
diverse QSAR datasets generated as part of Merck's drug discovery efforts[2]. However,
contrary to findings of the above studies, when using DNN, RF and variable nearest
neighbour (one of the simplest ML methods) to predict the molecular activities of 21 *in
vivo* and *in vitro* datasets, Liu et al. reported that the overall performance of the three
methods were similar[6]. This work leads us to question whether this trend to develop
more advanced and complex AI methods would really result in any further significant
improvements for QSAR/virtual screening.

In 2021, Dr Andrew Ng proposed that AI scientists should attempt to develop data-
centric AI approaches instead of the currently pursued model-centric AI approaches[7,8].

A model-centric AI approach involves improving/building on the AI algorithm to improve
the model's predictive performance [8–10]. In contrast, a data-centric AI approach is one
where automated methods are developed to improve data quality or to tune the data
used by the predictive model – for example, such methods could check for consistency
in the labelling of the data and automatically flag mislabelled data – and in so doing,
improve the model's predictive performance.

With some chemical databases like PubChem containing well over 100 million compounds[11] and with the urgent need for large, clean datasets for deep learning methods, cheminformaticians are challenged to manually curate clean and consistent benchmark chemical datasets from large chemical libraries. Thus, it makes sense to develop data-centric AI approaches that can automatically do this for CADD. However, before we can develop such an approach, we need to understand what attributes/properties constitute good data for CADD. We believe there are four pillars of cheminformatics data that drives AI performance – namely, data representation, data quality, data quantity and data composition – and we were keen to investigate how each of these pillars contribute to an improved AI performance.

AI research generally begins with the extraction and acquisition of high quality data. But as data sets become larger and more sophisticated, manual data cleaning, restructuring and feature engineering becomes more challenging[12–14]. In a recent study, Northcutt et al.[15] found label errors in the test sets of 10 of the most commonly-used computer vision, natural language, and audio benchmark datasets. On average, they found 3.3% errors across the 10 datasets - for example, the ImageNet validation set contained 6% (over 2,900 errors) label errors. Poor data quality can lead to biased AI models while insufficient data results in non-representative models that are unable to generalize and accurately predict from real-world data. However, in cheminformatics, it would appear that the latter is not an issue as there has been an exponential growth in chemical data: in 2010, PubChem contained 27,443,646 records of unique chemical structure compounds and by 2021, this had grown to around 111 million unique chemical structures (~four-fold) [16,17].

Given Northcutt et al.'s findings, we felt that it was important for us to build a new benchmark chemical dataset that we could be confident of and which could be used with an AI to achieve superior performance. Only when we have a superior AI model that gives exceptional performance can we be certain that any change in the AI's performance is indeed due to perturbations in our data and not because of an imperfect AI model. Thus, we carefully curated a new dataset of BRAF actives and inactives that we used for developing LBVS AI models for BRAF ligands. BRAF ligands are a well-studied class of drugs and there is much interest to develop potent BRAF antagonists that will suppress the actions of the constitutively-active mutant BRAF protein found in cancers like colorectal cancer and lung adenocarcinoma [18–21]. Our results showed that that models trained on our BRAF dataset could attain near-perfect accuracy and so, this

allowed us to design a set of experiments to test how each of the four pillars of
cheminformatics data impacts on AI performance.

Enhancing data is not just about increasing the size (and representativeness) of the
dataset but also about choosing the right data representation for a learning task. We
tested the performance of different ML algorithms employing various molecular
representations to evaluate how molecular representations affect ML algorithm
performances. There have also been studies that have proposed the use of merged
molecular representations[22–24]. This multi-representation of molecular information is
powerful, and constitutes a form of multi-view learning[25], an emerging direction in AI/ML
with implications for improved generalization performance. We systematically tested if
paired fingerprint combinations can do a better job of describing a molecule and
outperform a single (standalone) fingerprint in LBVS. For this, we tested 10 standalone
fingerprints and their 45 paired combinations to shed light on (1) what is the best type of
molecular representation for virtual screening (i.e., substructure key-based, topological,
path-based or circular fingerprints, and single or merged fingerprints) and (2) how the
interplay between molecular representations and different ML algorithms contributes to
the changes (if any) in predictive performance. In all, we developed and assessed 1,375
predictive models for LBVS of BRAF ligands.

Next, we investigated the impact that data quality, data quantity and data composition
have on predictive performance. Using four top predictive models that utilizes only a
single molecular fingerprint, namely, [i] SVM+ECFP6, [ii] RF+ECFP6, [iii]
SVM+Daylight-like, and [iv] RF+Extended, we show how current conventional usage of
data in CADD can be improved to enhance data quality. For example, a common
practice in CADD is the use of DUD-E decoys as inactives but a recent study showed
that a hidden bias in these decoys affects predictions for structure-based virtual
screening (SBVS) [28,29]. Thus, we wanted to see if this hidden bias also affects LBVS. In
addition, we also explored how dataset size and composition impacts the performance
of the AI models.

Results

Assessment of machine learning algorithms for ligand-based screening

Five balanced training datasets of BRAF actives and inactives were used to train five
conventional machine learners: k-nearest neighbours (kNN), Naïve Bayes (NBayes),

gradient-boosted decision tree (GBDT), RF and SVM. We created in total 1,375
predictive models - 5 predictive models for each ML algorithm using one of 55 different
molecular representations. For all predictive models, we observe that no real difference
between the average accuracy achieved in cross-validation and that achieved on the
hold-out test set, for all 55 molecular representations used (Figure 1 and Supplemental
Table 1); for example, for the SVM model trained with Estate fingerprint (the worst
performing SVM model), cross-validation attained an accuracy of 85.2% while testing
gave an accuracy of 85.7% and in some cases, the average accuracy achieved in
cross-validation and testing were the same (SVM using either CATS2D
[accuracy=97.1%] or Extended [accuracy=98.1%]). This suggest no overfitting,
regardless of the ML algorithm or molecular representation used, and that our training
and testing sets are representative of the BRAF class of drugs.

The best performance was achieved by an SVM model using the paired
(ECFP6+Extended) fingerprints with an average percentage accuracy of 99.05% on the
hold-out test set, followed very closely by the RF model using only the ECFP6
fingerprint that gave a 98.48% accuracy. SVM and RF had previously been shown to
perform well in virtual screenings for BACE1 inhibitors when compared against other
conventional machine learners (RF achieving AUC-ROC of 0.867)[26–28] but to the best of
our knowledge, the level of accuracy achieved here for our BRAF ligand dataset is
unprecedented for a LBVS platform.

In general, all five ML algorithms tested were able to achieve similar levels of predictive
performance, with the best performing models for each ML algorithm all achieving an
accuracy of above 97%. We should also highlight that there was no feature selection
performed on our training data prior to its use. In fact, the RF models were able to give
a superior performance without even needing to tune the default parameters.

Among all predictive models, the worst performing model was the Naïve Bayes model
using the Estate fingerprint (accuracy = 59.4%). But this shouldn't come as a surprise.
The conditional independence assumption of Naïve Bayes classifiers means that it can
use high-dimensional features with limited training data compared to more sophisticated
methods. And here we can see that this is indeed the case with the feature-rich
molecular representations, ECFP6 and FCFP6 (each containing 2^{32} bits), being able to
achieve an accuracy of above 98% with Naïve Bayes (comparable to levels attained by
the other ML algorithms). Conversely, we should avoid using Naïve Bayes if the feature
space for the molecular representation is small or sparse, like Estate (79 bits).

Assessment of molecular representations for ligand-based screening

For all ML algorithms that we tested, the worst performing predictive models were derived from those that had used only the Estate fingerprint to represent the molecules. This is unsurprising considering that the Estate fingerprint is a 79-bit vector which serves as an atom-centred index that describes the arrangement/connectivity and electronic environment of atoms in a molecule[29,30]. However, what is surprising is that a relatively simple 79-bit molecular representation can achieve a predictive performance of above 85% accuracy on all but one ML algorithm – this result is almost on par with some Tox21 challenge winners, for example, dmlab which achieved an AUC-ROC of 0.828 for their screening of androgen receptor agonist and microsomes which achieved an AUC-ROC of 0.827 for their prediction of small molecule agonists of the estrogen receptor alpha (ER-alpha) signaling pathway[31,32].

For predictive models using only a standalone fingerprint, ECFP6 consistently ranked among the top 3 fingerprints for all ML algorithms (Table 1). All models generated using ECFP6 as a standalone fingerprint managed to achieve an accuracy of above 96% with ECFP6 performing best with RF (98.48%) and SVM (98.93%). Furthermore, in all but one ML algorithm, the best performing models for these machine learners employed ECFP6 either in a paired fingerprint combination or as a standalone fingerprint. Even in the case of GBDT where the best model used a paired combination of AtomPair and Daylight-like fingerprints (97.36% accuracy), it should be noted that a model using a combination of ECFP6 with the AtomPair fingerprint followed closely with a 97.16% accuracy. Overall, the best predictive model was obtained from a paired combination of ECFP6 and Extended fingerprints in a SVM model (99.05%). Considering that ECFP6 occupies a feature space of 2^{32} bits, this fingerprint obviously provides a very detailed representation of a molecule and so, would undoubtedly be able to describe a molecule accurately and therefore, be useful in a classification task. These results suggest ECFP6 can be an effective molecular representation for LBVS regardless of whether it is used on its own or in combination with another fingerprint and would perform well irrespective of the ML algorithm in a data-driven approach.

So, is there any advantage in using a paired fingerprint combination to train our machines? As we can see with SVM, the pairing of Extended fingerprint with ECFP6 gave a slight improvement in accuracy and in fact, produced the best predictive model (Figure 1a and Supplemental Table 1). But more is not always better; there are instances where combining two molecular fingerprints offers no synergistic benefit and

in fact, one might even observe a poorer performance from a paired fingerprint
compared to the performance obtained by one of the standalone fingerprints that make
up the pair. For example, the topological torsion fingerprint can achieve an average of
98.34% accuracy on its own but when combined with PubChem fingerprint, this drops to
97.86%. However, in some cases, this drop in accuracy may, in fact, offer an
advantage; using ECFP6 on its own in the RF models, we obtain a 98.48% accuracy
but pairing it with the Daylight-like fingerprint, this drops very slightly to 98.44%, but by
sacrificing some accuracy, we attain near perfect precision for the model (increasing
from 0.9892 to 0.9976) (Supplemental Table 1). For wet lab validation, compromising on
accuracy to attain a high level of precision is desirable because it means that the
chances of wasting time and resource validating a compound that is likely to be false
positive is low.

The role that dataset composition and size plays in performance

Current leading approaches in AI are data-hungry, requiring access to big data to
accomplish its training tasks[33]. This may not work well in cheminformatics. For LBVS,
we rely solely on prior knowledge of known ligands to train our models to predict
potential hits, however, some targets have only a limited number of ligands. To illustrate
this point, ChEMBL contained information for 6778 human protein targets at the time of
writing (April, 2023) but more than half have 500 or less associated ligands[34]. Such
targets may not benefit from model-centric approaches as the requisite large datasets
are unavailable.

Although known ligands for a protein target is limited, the wealth of information in
chemical databases like ChEMBL offer an almost unlimited opportunity to mine
inactives for use in AI training for quantitative structure-activity relationship (QSAR) and
LBVS. We wanted to see how the relative numbers of actives to inactives would impact
performance and particularly, if an overabundance of inactives in the training dataset
could compensate for a lack of actives on our four chosen predictive models: (i)
SVM+ECFP6, (ii) RF+ECFP6, (iii) SVM+Daylight-like, and (iv) RF+Extended. We
hypothesized that the use of a large dataset of inactives could improve performance
when presented with a finite number of actives.

Model performance was tested in two different scenarios where: (1) the number of
inactives increased equally with the number of actives in the training dataset and (2) the
ratio of the number of inactives to actives increases for the training dataset. For this

latter scenario, the number of inactives were fixed at 3600 while the number of actives
were successively decreased from 3600 to 500 actives in the training dataset.

For the SVM models, when the number of actives is fixed, increasing the number of
inactives did not have a significant impact on accuracy. With training datasets
containing only 500 actives, increasing the number of inactives from 500 to 3600
resulted in a drop in the accuracy drop from 96.42% (Table 2b) to 95.73% (Table 2a) for
the SVM+Daylight-like model - a difference of 0.69% in accuracy.

However, for the RF models, the difference in accuracy was conspicuous: the accuracy
for the RF+ECFP6 model fell from 98.4% for the full training dataset (3600 actives, 3600
inactives) to 94.71% with the imbalanced (500 actives, 3600 inactives) training dataset.
In fact, the performance of the model trained on a balanced (500 actives, 500 inactives)
dataset still managed an accuracy of 97.2%. In other words, where the number of
actives was fixed at 500, increasing the number of inactives from 500 to 3600 in the
RF+ECFP6 model saw a drop in accuracy from 97.2% to 94.71% - a difference of
2.49%.

In short, our study shows that, given a finite number of actives, having a large number
of inactives in the training dataset does not improve model accuracy. Furthermore,
certain algorithms (like RF) are more sensitive to imbalanced training data than others
(SVM) (Tables 2a and 2b) due to stronger affectations on the recall/sensitivity of RF
models than SVM models (Table 2c).

Regardless of the ML model and/or molecular representation used, recall/sensitivity
decreases as the size of inactives in the training dataset increases (relative to the size
of actives) while precision increases (Tables 2c and 2d). In a previous study where the
number of actives were kept constant while increasing the number of inactives,
Rodríguez-Pérez et al. had also found that precision improves as the ratio of inactives
to actives increases [35]. They also found that they needed at least 100 actives and 500
inactives to achieve near maximal recall (they achieved a mean recall of 87%) for their
SVM model [35] but we found that the same cannot be said to be true for RF models –
recall for RF models suffered greatly when the number of actives fall below 1000: for the
RF+Extended model, recall fell from 93.41% when trained on (1000 actives, 3600
inactives) to 87.82% for the model trained on (500 actives, 3600 inactives) (Table 2c).

Although recall fell considerably, all SVM and RF models were able to achieve near-perfect (>99%) or perfect precision when we trained with only 500 actives but provided over seven times the number of inactives (3600 inactives) (Table 2c). It is also interesting to note that with a balanced training dataset, there was only a slight change in recall and precision for SVM and RF models even when both the number of actives and inactives in the training dataset drops from 3600 to 500, compared to models trained on the imbalanced datasets – in general, all models trained on a balanced dataset were able to attain >96% for both recall and precision (Tables 2c and 2d).

Despite the drop in recall and accuracy, we recommend that when faced with a limited number of actives for a target, one should increase the number of inactives used in training to lessen false positive predictions. It should be noted that no class weights were introduced when we trained our AI models on the imbalance datasets. Finally, the SVM+ECFP6 model was the most robust among the four models tested as its accuracy, recall and precision were little affected by the change in data composition or size.

Choice of inactives is crucial for training

(i) *Less active versus inactive*

In many QSAR and LBVS studies, we often see the use of an arbitrary IC50 threshold to divide ligands into 2 classes, actives and inactives – for example, compounds that have an IC50 below 10 µM for a target protein are considered "actives" and those that have an IC50 of 10 µM or more are considered "inactives"[28,36–41]. We hypothesized that the use of such "inactive" ligands in training could reduce the model's predictive performance since it is likely that these "inactives" are not really inactive but perhaps, just "less active". We also recognise that the measurement of IC50 is dependent on the assay and condition under which it is tested. An IC50 curve shifts to the right if the expression/concentration of the protein is high in the cell/assay used to test the drug, thereby making what may be an "active" compound appear to be "inactive". Here, we set out to see whether the use of these "less actives" affects a model's predictive performance.

Before proceeding with our comparative studies with the "less actives", we set out to first establish the baseline accuracy for our 4 predictive models. We created 10 new balanced, hold-out test sets to allow for an unbiased assessment of the 4 predictive

models. The accuracy of each model is fairly consistent across all ten test sets,
averaging at around 97% for the 4 predictive models (Table 3 and Supplemental Table
2). This suggests that the original test set used was not biased and that the assessment
of the ML models in above study (Figures 1a-d) was valid. These results provide further
evidence that the curated BRAF dataset used for training is of high quality and can be
used as a reliable benchmark for future virtual screening methods. Finally, these results
also form the baseline for the comparative studies below.

To test how "less actives" compounds would affect the predictive performance of the
models, we identified 510 BRAF ligands in ChEMBL whose IC50 were more than 10
μM. We used these in a "spike-in" experiment to see if the introduction of these "less
actives" in the original training dataset for our ML models would change their
performance. We created 3 training datasets in which 5% (180), 10% (360) and 14%
(510) of the inactives in the original training dataset were replaced with these "less
actives". In every instance, our results show that the level of accuracy of the model falls
as the number of "less actives" in the training dataset increases (Table 3 and
Supplemental Table 2). Not surprisingly, this drop in performance is due in large part to
a drop in recall, meaning that the models trained on "less actives" are less able to
correctly recognise certain actives (true positives) in the test set, probably because
some of these actives share certain similarity to the "less actives" which were labelled
as "inactive" in the training dataset. This demonstrates that the design and composition
of the input data is important.

(ii)   *Using DUD-E decoys as inactives*

The DUD-E benchmark dataset is commonly used for the development of SBVS
methods[42]. Briefly, in DUD-E, a diverse set of actives is built for a target protein. Each
active molecule is paired with a set of property matched decoys (PMD). PMDs are
selected to be similar to each other and to known actives with respect to certain
physico-chemical descriptors (e.g., molecular weight, hydrogen bond donors and
acceptors) while being topologically dissimilar. It is believed that topological dissimilarity
supports the assumption that the decoys are likely to be inactives because they are
chemically different from the actives. The DUD-E database has 9,950 decoys for BRAF.
Although originally developed for molecular docking screens, DUD-E's decoys are also
used as inactives in LBVS[43–48]. A recent study showed that the superior enrichment
efficiency in convolutional neural network models for SBVS was achieved in the DUD-E
dataset because of hidden bias in this dataset rather than a successful generalization of

the pattern of protein-ligand interactions[49]. Therefore, could this hidden bias also have
an impact on LBVS?

As with our spike-in studies with "less actives", we wanted to see how the introduction of
some decoys in training might affect model performance. Therefore, we selected at
random 510 BRAF decoys and carried out the same spike-in experiments as described
for the "less actives" experiment above. Unlike our models trained on datasets with "less
actives" spiked-in, our models trained on datasets with decoys spiked-in do not show
much difference in accuracy from our baseline models trained without any decoys. For
example, for the RF+ECFP6 model trained on a dataset where 14% of the inactives
were replaced with 510 decoys, the average accuracy on the 10 test datasets dropped
by a mere 0.09% when compared with the baseline model (Table 4A); this is a stark
contrast to the nearly 2% drop in accuracy when we used a dataset spiked-in with 510
"less actives" (Table 3). This is probably because decoys, unlike the "less actives", are
in fact topologically dissimilar from the BRAF actives and so, the use of some decoys to
represent inactives does not severely compromise the performance of the model.
However, the results for models trained on only actives and decoys was surprising.

For ML models trained on 3600 actives plus 3600 decoys, their accuracy when tested
on a balanced test dataset of 1000 BRAF actives and decoys is near-perfect (above
99% for all ML models) (Table 4B; Supplemental Table 3). However, these models gave
an average accuracy of around 94% when we tested it against our 10 balanced test
datasets of 1000 BRAF actives and inactives (Table 4A; Supplemental Table 3). The
drop in accuracy for models trained on 3600 BRAF actives plus 3600 decoys on our 10
test datasets is due to a fall in precision rather than recall. While recall for these models
are above 98%, their precision drops by about 5% when compared with their
corresponding baseline model. This means that models trained on only actives and
decoys tend to give more false positive predictions. Conversely, when we tested our
original ML models trained on our training dataset of 3600 BRAF actives plus 3600
BRAF inactives, we found that they gave an accuracy ranging from 96.85 to 97.74% on
our 10 test datasets of BRAF actives and inactives but performed even better on the
BRAF actives plus decoys test set, achieving near-perfect accuracy of 99% (Tables 4A
& 4B; Supplemental Table 3). This is expected when we consider the fact that decoys
are topologically dissimilar to BRAF actives, therefore, making it easy for our original ML
models to discern between the BRAF actives and decoys. In summary, training with
decoys is not recommended because it would result in a model that has a higher false
positive rate. Testing with a dataset containing decoys is also not advisable because it
may give an over-optimistic assessment of the predictive performance of the model.

Discussion

"*Garbage in, garbage* out" or GIGO, is a concept familiar to all computer scientists
denoting the importance and value of data quality in predictive modelling. But despite
this wide acknowledgement, prevailing AI approaches tend to be model-centric,
focusing more on the sophistication of the AI/ML architecture than the input. Such
approaches may not pay enough heed towards resolving issues of data quality, data
representativeness (not to be confused for data representations which is investigated in
this study), and perhaps even feature-compatibility with the AI/ML models used. By
adopting a model-centric AI approach, one hopes to tweak and improve the AI
algorithms to improve its predictive performance while also enhancing model
explainability or justifiability.

To pursue a data-centric AI approach, Dr Ng advocated developing a systematic
approach to mine and clean large volumes of data in order to produce accurately-
labelled data which is of high quality, consistent and error-free[7,8]. Data-centric AI appear
to be gaining traction in the AI community[9,10,50,51]. It is also important that we do not
confuse data-centric AI for data-driven AI: data-centric AI is an emerging science that
studies techniques to improve the quality of datasets (that will be used to train the AI/ML
models), whereas, data-driven AI is simply a paradigm that encourages the analysis of
large datasets to improve AI performance. Many AI researchers have written to give a
general perspective on the principles and critical considerations for the data
construction process in data-centric AI [9,10] but to the best of our knowledge, there has
been little or no attempts to determine and evaluate the parameters that are necessary
for data construction in a data-centric AI approach for CADD. In fact, we can see that
cheminformaticians still favour a model-centric AI approach when we look at studies
published previously comparing the use of different ML or deep learning methods on
different datasets [27,28,37]. This emphasis on a model-centric AI approach for
cheminformatics is also shared by authors of recent reviews surveying the current
research landscape of CADD [52–54].

Whang et al. proposed that data acquisition, data labelling, data
augmentation/improvement, data validation, data cleaning and data sanitization as key
considerations in the practice of data-centric AI [10]. However, we need to recognise that
there are other considerations which are unique to chemistry and cheminformatics. A
chemical's property and structure need to be encoded in a meaningful manner so that a
predictive AI can learn the salient features of a class of drugs for QSAR and virtual

screening and this has given rise to various types of data representations for a molecule
(that is, molecular descriptors and fingerprints). Thus, data representation is an
important consideration that is somewhat unique to data construction for QSAR and
virtual screening.

We believed that good data representation might be equally as important as high-quality
data and so, we wanted to see how best to represent a molecule to the machine. In
recent years, many newly created molecular representations have been proposed [55–58].
However, instead of reinventing the wheel and creating another novel molecular
representation, we tested to see if currently available molecular fingerprints are up to
the task for virtual drug screening. Our study shows that certain molecular fingerprints
are clearly superior and, in some cases, two molecular fingerprints can be combined to
produce a performance which surpasses the performance of the individual molecular
fingerprint, as seen when Extended and ECFP6 fingerprints were used with SVM.
However, broadly speaking, there is very little difference in performance across different
fingerprints. For example, looking at the RF models, most models trained using a single
fingerprint could achieve a level of accuracy close to 97% or higher. The most surprising
result came from the RF model using EState fingerprint which could achieve an
accuracy of ~92% - it is surprising because EState is only 79 bits but it was
outperforming previously developed virtual drug screeners that used a more feature-rich
molecular representation with deep learning methods [28,59]. This suggests that current
molecular fingerprints are more than up to the task for CADD if one can provide a high-
quality dataset for training and testing.

Our study also demonstrates that one cannot pursue a data-centric AI approach to the
exclusion of a model-centric approach because there are clearly certain AI models that
perform better on certain AI task. Comparing between ML models, we see that although
Estate fingerprint paired with RF achieves ~92% accuracy, SVM with the same
fingerprint achieves only 85% accuracy. This, however, does not suggest that SVM is
not a good ML model for virtual screening because when given the "right" molecular
representation (Extended and ECFP6 fingerprints), SVM can offer a predictive
performance that surpasses all other predictive models that we tested. Thus, having the
right model is just as important as having the right data and we cannot ignore the
importance of a model-centric approach --- both model and data-centric approaches
should be seen as complimentary than mutually exclusive. In future, in-depth studies to
understand complementariness between models and data should be performed.

Interest in deep learning methods for QSAR and virtual screening have been on the rise
following the success of Dahl et al.'s MT-DNN in the Merck Molecular Activity
Challenge[2,3] and subsequently, Mayr et al.'s DeepTox deep neural networks in the
Tox21 Challenge[59]. Studies have shown that deep learning methods consistently
outperform conventional ML methods for rational drug discovery[1]. For example,
DeepTox (the overall winner of the Tox21 Challenge) which used a deep neural network
for toxicity prediction could achieve AUC-ROCs of between 0.793-0.942 for 12 nuclear
receptor (NR) and stress response (SR) pathway assays[59]. The best ligand-based
screening model for DeepTox was achieved for ligands of the aryl hydrocarbon receptor
(AhR) which gave an AUC-ROC of 0.928. However, we need to recognise certain
limitations of deep learning methods. In comparison to conventional ML algorithms,
deep neural networks require a much larger amount of data to ensure model
generalizability and prevent overfitting. This presents a problem for LBVS because
many druggable protein targets have very few known ligands. To illustrate this point,
ChEMBL contains information for 6778 human protein targets (as of April, 2023) but
more than half (~3800) have 100 or less compounds/ligands associated with each
protein[34]. For this reason, we chose to focus only on conventional ML algorithms and
we show here that conventional ML models can give superior performance for virtual
screening, without the need to resort to more data-hungry deep learning methods. This
limitation of deep neural networks also makes it clear that alternative paradigms such as
data-centricity, favouring quality over quantity, is more likely to be successful in novel
drug discovery using AI/ML.

Until recently, it has been difficult to give a reliable assessment of what constitutes best
practice for LBVS since there are no benchmark datasets that can produce ML models
capable of giving near-perfect predictive performance. In the absence of a high-quality
benchmark dataset, evaluating experiments such as the ones carried out here would be
difficult because any observed change in performance could be attributed to the
behaviour of an imperfect model rather than a reflection of the use of inappropriate data.
We have now generated a high-quality benchmark dataset and were able to show that
current practices and use of data lead to serious shortcomings in the state-of-the-art
predictive models which, in turn, calls for a reassessment of these model's true
performance. Our work indicates that there is little or no shortcomings with either
current predictive AI/ML algorithms or most molecular representations when used in
LBVS because the differences in their performance are minimal. Ultimately, the biggest
impact on predictive performance comes from data size, composition and poor data
quality.

Through this work, we hope to use a single case study to demonstrate the power of
data-centric paradigm. As this approach becomes more widespread and better
understood across use cases, a foundation for data-centric AI approaches in
cheminformatics could eventually be laid. With the exponential growth in chemical
databases like ChEMBL and PubChem, it becomes increasingly difficult to manually
curate a high-quality dataset when we are dealing with large numbers of
compounds/ligands. It is therefore important for us to consider how data-centric AI
approaches can help. We propose that pursuing data-centricity require first
understanding the nature of our data across 4 pillars: data representation, data quality,
data quantity, and data composition on a model's predictive performance (i.e., what
attributes or properties of these 4 pillars contribute to high-quality data for training and
testing). If, for example, we do not know what type of data diminishes data quality, then
how can we be expected to build a data-centric AI approach for cheminformatics? Our
study demonstrates that manipulation of these pillars of data-centricity has affectation
on model performance. Pending future generalization studies on more use cases, our
work paves the way towards the establishment of a framework for a data-centric AI
approach for virtual screening and CADD.

Method

Machine Learning Models

We tested the performance of five machine learning methods representing different strategies. These include, k-nearest neighbours (kNN), Naïve Bayes (NBayes), gradient-boosted decision tree (GBDT), random forest (RF) and support vector machine (SVM) (python ver. 9.1.2 / sklearn ver.1.0.2), using the BRAF dataset described below.

For each of the 55 molecular representations that we tested, we used 5 training datasets on the above machine learning methods. We did not perform any feature scaling or selection. Each training set underwent 10-fold cross-validation to optimize the hyperparameters for the SVM, kNN and NBayes models and to estimate the accuracy of the models. Grid search was used to determine the optimal values of the hyperparameters. For the RF and GBDT models, the default parameters were used with no additional tuning.

Accuracy, precision, and recall were used as performance metrics.

Dataset

Instead of using a readily available benchmark dataset (such as the BACE1 inhibitors dataset by Subramanian et al.[28]), we manually curated and built a dataset of BRAF actives and inactives to ensure that we would have a high quality dataset for our study. Actives were defined as validated BRAF ligands with an IC50 of less than 10 μM, while inactives were carefully selected based on the fact that they have no known pharmacological activity against BRAF. In total, we identified 4100 BRAF actives and around 24,000 compounds that we deemed to be inactive against BRAF. From this initial set of compounds, we randomly selected 3600 BRAF actives to be part of the training dataset with the remaining 500 actives becoming a part of the hold-out test set. To avoid training bias from any single curated dataset, we created 5 balanced training datasets, each containing the 3600 BRAF actives with an equal number of inactives and where each training dataset contained a unique set of inactives that was not shared, partially or wholly, with the other 4 training datasets. Unless there were some hidden biases in one or more of the training datasets, we expected the performances of the 5 trained models for each molecular representation to be similar. We also created a single balanced test set with 1000 BRAF actives and inactives that would be used to give a fair and objective comparison of the predictive models. (Please refer to Supplementary data (Part 1) for these training and test datasets)

We chose four top predictive models employing a single molecular fingerprint that had
been trained with the third training dataset for the experiments investigating data size,
data composition and data quality. The models chosen were: [i] SVM+ECFP6, [ii]
SVM+Daylight-like, [iii] RF+ECFP6, and [iv] RF+Extended. The performance of these
four original ML models formed the baseline for our comparative analyses and
represented the optimal performance achievable for the respective model. Additionally,
we generated new predictive models where [i] SVM+ECFP6, [ii] SVM+Daylight-like, [iii]
RF+ECFP6, and [iv] RF+Extended were trained on smaller datasets to compare their
performance against the baseline performance. The original training dataset was a
balanced dataset of 7200 BRAF actives and inactives but the smaller training datasets
composed of the following numbers of BRAF actives to inactives: (i) 3000:3600; (ii)
2500:3600; (iii) 2000:3600, (iv) 1500: 3600; (v) 1000:3600; (vi) 500:3600; (vii)
3000:3000; (viii) 2500:2500; (xi) 2000:2000, (x) 1500:1500; (xi) 1000:1000; (xii)
500:500. The actives and inactives in these smaller datasets were randomly selected to
avoid any unintentional bias.

For this study, we generated 10 new balanced hold-out test datasets of 1000 BRAF
actives and inactives to give us an unbiased gauge of the accuracy that our models can
achieve. We define a compound as "inactive" if there are no known pharmacological
assays for the said compound on our target, BRAF.

We found 510 BRAF ligands that have an IC50 of more than 10 µM in the ChEMBL
database which we labelled as "less active" [34]. These "less active" ligands were used for
spike-in experiments where we replaced either 180 (5%), 360 (10%) or 510 (14%)
inactives in our original training dataset with a similar number of "less active" ligands.

The DUD-E database contains 9,950 decoys for BRAF[42]. We randomly selected 3600
decoys to create a training dataset of 7200 BRAF actives and decoys. In addition, we
also created a balanced hold-out test set of 1000 BRAF actives and decoys. As with the
"less actives" spike-in experiments, we also created 3 separate training datasets that
had either 180 (5%), 360 (10%) or 510 (14%) decoys replacing a similar number of
inactives in our original training dataset of 3600 actives and 3600 inactives.

Please refer to Supplementary data (Part 2) for training and test datasets used in these
studies.

Fingerprint Generation

RDKit and the Chemistry Development Kit (CDK) were used to compute the fingerprints
for the molecules in this study[60,61]. The ten standalone molecular fingerprints, namely,

1. Estate fingerprints (CDK)[29,30]

2. PubChem fingerprints (CDK)[11,62]

3. Klekota-Roth fingerprints (CDK)[63]

4. Extended-Connectivity fingerprints 6 (ECFP6) (CDK)[64,65]

5. Functional-Class fingerprints 6 (FCFP6) (CDK)[64,65]

6. Extended fingerprints (CDK)[66]

7. Topological Torsion fingerprints (topo_torsion) (RDKit)[67]

8. Atom Pairs fingerprints (RDKit)[68]

9. Daylight-like RDKit fingerprints (RDKit)[60]

10. CATS2D fingerprints (RDKit)[69]

and 45 paired combinations of these were used in this study.

Acknowledgement

The authors wish to thank Dr. Cameron Osborne for taking time to read our manuscript
and offer valuable comments and suggestions to improve its readability.

Financial & competing interests disclosure

A. Chong, W.W.B. Goh , and H.Y. Li receive funding support from Nanyang Biologics.
The authors have no other relevant affiliations or financial involvement with any
organisation or entity with a financial interest in or financial conflict with the subject
matter or materials discussed in the manuscript apart from those disclosed.

References

1. Huang, R. & Xia, M. Editorial: Tox21 Challenge to Build Predictive Models of
Nuclear Receptor and Stress Response Pathways As Mediated by Exposure to
Environmental Toxicants and Drugs. *Front. Environ. Sci.* **5**, (2017).

2. Ma, J., Sheridan, R. P., Liaw, A., Dahl, G. E. & Svetnik, V. Deep Neural Nets as a
Method for Quantitative Structure–Activity Relationships. *J. Chem. Inf. Model.* **55**,
263–274 (2015).

3. Dahl, G. E., Jaitly, N. & Salakhutdinov, R. Multi-task Neural Networks for QSAR
Predictions. *arXiv preprint arXiv:1406.1231* (2014).

4. Wouters, O. J., McKee, M. & Luyten, J. Estimated Research and Development
Investment Needed to Bring a New Medicine to Market, 2009-2018. *JAMA* **323**,
844–853 (2020).

5. Sabe, V. T. *et al.* Current trends in computer aided drug design and a highlight of
drugs discovered via computational techniques: A review. *Eur. J. Med. Chem.* **224**,
113705 (2021).

6. Liu, R., Wang, H., Glover, K. P., Feasel, M. G. & Wallqvist, A. Dissecting Machine-
Learning Prediction of Molecular Activity: Is an Applicability Domain Needed for
Quantitative Structure–Activity Relationship Models Based on Deep Neural
Networks? *J. Chem. Inf. Model.* **59**, 117–126 (2019).

7. Ng, A. MLOps: From Model-centric to Data-centric AI.
https://www.youtube.com/watch?v=06-AZXmwHjo (2021).

8. Strickland, E. Andrew Ng: Unbiggen AI - IEEE Spectrum.
https://spectrum.ieee.org/andrew-ng-data-centric-ai (2022).

9. Zha, D., Bhat, Z. P., Lai, K.-H., Yang, F. & Hu, X. Data-centric AI: Perspectives and

Challenges. in *Proceedings of the 2023 SIAM International Conference on Data*

Mining (SDM) 945–948 (Society for Industrial and Applied Mathematics, 2023).

doi:10.1137/1.9781611977653.ch106.

10. Whang, S. E., Roh, Y., Song, H. & Lee, J.-G. Data collection and quality challenges

in deep learning: a data-centric AI perspective. *VLDB J.* **32**, 791–813 (2023).

11. Kim, S. *et al.* PubChem 2023 update. *Nucleic Acids Res.* **51**, D1373–D1380 (2023).

12. Aldoseri, A., Al-Khalifa, K. N. & Hamouda, A. M. Re-Thinking Data Strategy and

Integration for Artificial Intelligence: Concepts, Opportunities, and Challenges. *Appl.*

Sci. **13**, 7082 (2023).

13. Yoon, A., Kim, J. & Donaldson, D. R. Big data curation framework: Curation actions

and   challenges.   *J.   Inf.   Sci.*   01655515221133528   (2022)

doi:10.1177/01655515221133528.

14. Kalpathy-Cramer, K. C., Mishka Gidwani ,. Jay B. Patel ,. Matthew D. Li ,.

Jayashree. Data Curation Challenges for Artificial Intelligence. in *Auto-Segmentation*

for Radiation Oncology 201–216 (CRC Press, 2021).

15. Northcutt, C. G., Athalye, A. & Mueller, J. Pervasive Label Errors in Test Sets

Destabilize   Machine   Learning   Benchmarks.   Preprint   at

https://doi.org/10.48550/arXiv.2103.14749 (2021).

16. Xie, X.-Q. Exploiting PubChem for Virtual Screening. *Expert Opin. Drug Discov.* **5**,

1205–1220 (2010).

17. Kim, S. *et al.* PubChem in 2021: new data content and improved web interfaces.

Nucleic Acids Res. **49**, D1388–D1395 (2021).

18. Barras, D. *et al.* BRAF V600E Mutant Colorectal Cancer Subtypes Based on Gene

Expression. *Clin. Cancer Res.* **23**, 104–115 (2017).

19. Paik, P. K. *et al.* Clinical Characteristics of Patients With Lung Adenocarcinomas

Harboring BRAF Mutations. *J. Clin. Oncol.* **29**, 2046–2051 (2011).

20. Dain Md Opo, F. A. *et al.* Identification of novel natural drug candidates against

BRAF mutated carcinoma; An integrative in-silico structure-based pharmacophore

modeling and virtual screening process. *Front. Chem.* **10**, (2022).

21. Żołek, T., Mazurek, A. & Grudzinski, I. P. In Silico Studies of Novel Vemurafenib

Derivatives as BRAF Kinase Inhibitors. *Molecules* **28**, 5273 (2023).

22. Kim, H., Lee, J., Ahn, S. & Lee, J. R. A merged molecular representation learning for

molecular properties prediction with a web-based service. *Sci. Rep.* **11**, 11028

(2021).

23. Tang, Q., Nie, F., Zhao, Q. & Chen, W. A merged molecular representation deep

learning method for blood–brain barrier permeability prediction. *Brief. Bioinform.* **23**,

bbac357 (2022).

24. Mendolia, I., Contino, S., De Simone, G., Perricone, U. & Pirrone, R. EMBER—

Embedding Multiple Molecular Fingerprints for Virtual Screening. *Int. J. Mol. Sci.* **23**,

2156 (2022).

25. Zhao, J., Xie, X., Xu, X. & Sun, S. Multi-view learning overview: Recent progress

and new challenges. *Inf. Fusion* **38**, 43–54 (2017).

26. Jiang, D. *et al.* Could graph neural networks learn better molecular representation

for drug discovery? A comparison study of descriptor-based and graph-based

models. *J. Cheminformatics* **13**, 12 (2021).

27. Wu, Z. *et al.* MoleculeNet: a benchmark for molecular machine learning. *Chem. Sci.*

9, 513–530 (2018).

28. Subramanian, G., Ramsundar, B., Pande, V. & Denny, R. A. Computational

Modeling of β-Secretase 1 (BACE-1) Inhibitors Using Ligand Based Approaches. *J.*

Chem. Inf. Model. **56**, 1936–1949 (2016).

29. Hall, L. H. & Kier, L. B. Electrotopological State Indices for Atom Types: A Novel

Combination of Electronic, Topological, and Valence State Information. *J. Chem. Inf.*

Comput. Sci. **35**, 1039–1045 (1995).

30. Roy, K. & Mitra, I. Electrotopological State Atom (E-State) Index in Drug Design,

QSAR, Property Prediction and Toxicity Assessment. *Curr. Comput. Aided Drug*

Des. **8**, 135–158 (2012).

31. Barta, G. Identifying Biological Pathway Interrupting Toxins Using Multi-Tree

Ensembles. *Front. Environ. Sci.* **4**, (2016).

32. Uesawa, Y. Rigorous Selection of Random Forest Models for Identifying

Compounds that Activate Toxicity-Related Pathways. *Front. Environ. Sci.* **4**, (2016).

33. Adadi, A. A survey on data-efficient algorithms in big data era. *J. Big Data* **8**, 24

(2021).

34. Mendez, D. *et al.* ChEMBL: towards direct deposition of bioassay data. *Nucleic*

Acids Res. **47**, D930–D940 (2019).

35. Rodríguez-Pérez, R., Vogt, M. & Bajorath, J. Influence of Varying Training Set

Composition and Size on Support Vector Machine-Based Prediction of Active

Compounds. *J. Chem. Inf. Model.* **57**, 710–716 (2017).

36. Srinivas, R., Klimovich, P. V. & Larson, E. C. Implicit-descriptor ligand-based virtual

screening by means of collaborative filtering. *J. Cheminformatics* **10**, 56 (2018).

37. Mayr, A. *et al.* Large-scale comparison of machine learning methods for drug target

prediction on ChEMBL. *Chem. Sci.* **9**, 5441–5451 (2018).

38. Lee, J., Kumar, S., Lee, S.-Y., Park, S. J. & Kim, M. Development of Predictive

Models for Identifying Potential S100A9 Inhibitors Based on Machine Learning

Methods. *Front. Chem.* **7**, (2019).

39. Lee, A. A. *et al.* Ligand biological activity predicted by cleaning positive and negative

chemical correlations. *Proc. Natl. Acad. Sci.* **116**, 3373–3378 (2019).

40. Yin, Y. *et al.* AFSE: towards improving model generalization of deep graph learning

of ligand bioactivities targeting GPCR proteins. *Brief. Bioinform.* **23**, bbac077 (2022).

41. Siemers, F. M., Feldmann, C. & Bajorath, J. Minimal data requirements for accurate

compound activity prediction using machine learning methods of different

complexity. *Cell Rep. Phys. Sci.* **3**, 101113 (2022).

42. Mysinger, M. M., Carchia, M., Irwin, John. J. & Shoichet, B. K. Directory of Useful

Decoys, Enhanced (DUD-E): Better Ligands and Decoys for Better Benchmarking.

J. Med. Chem. **55**, 6582–6594 (2012).

43. Riniker, S. & Landrum, G. A. Open-source platform to benchmark fingerprints for

ligand-based virtual screening. *J. Cheminformatics* **5**, 26 (2013).

44. Lee, J., Kumar, S., Lee, S.-Y., Park, S. J. & Kim, M. Development of Predictive

Models for Identifying Potential S100A9 Inhibitors Based on Machine Learning

Methods. *Front. Chem.* **7**, (2019).

45. Khan, M. I. *et al.* Development of machine learning models for the screening of
potential HSP90 inhibitors. *Front. Mol. Biosci.* **9**, (2022).

46. Guzelj, S., Tomašič, T. & Jakopin, Ž. Novel Scaffolds for Modulation of NOD2
Identified by Pharmacophore-Based Virtual Screening. *Biomolecules* **12**, 1054
(2022).

47. Islam, M. A. *et al.* Identification of Potential Cytochrome P450 3A5 Inhibitors: An
Extensive Virtual Screening through Molecular Docking, Negative Image-Based
Screening, Machine Learning and Molecular Dynamics Simulation Studies. *Int. J.*
Mol. Sci. **23**, 9374 (2022).

48. Patil, S. P. *et al.* Machine-Learning Guided Discovery of Bioactive Inhibitors of PD1-
PDL1 Interaction. *Pharmaceuticals* **15**, 613 (2022).

49. Chen, L. *et al.* Hidden bias in the DUD-E dataset leads to misleading performance of
deep learning in structure-based virtual screening. *PLOS ONE* **14**, e0220113
(2019).

50. Polyzotis, N. & Zaharia, M. What can Data-Centric AI Learn from Data and ML
Engineering? Preprint at http://arxiv.org/abs/2112.06439 (2021).

51. Jarrahi, M. H., Memariani, A. & Guha, S. The Principles of Data-Centric AI (DCAI).
Preprint at https://doi.org/10.48550/arXiv.2211.14611 (2022).

52. Tripathi, M. K., Nath, A., Singh, T. P., Ethayathulla, A. S. & Kaur, P. Evolving
scenario of big data and Artificial Intelligence (AI) in drug discovery. *Mol. Divers.* **25**,
1439–1460 (2021).

777 53. Zhao, L., Ciallella, H. L., Aleksunes, L. M. & Zhu, H. Advancing computer-aided drug

778   discovery (CADD) by big data and data-driven machine learning modeling. *Drug*

779   *Discov. Today* **25**, 1624–1638 (2020).

780 54. Zhu, H. Big Data and Artificial Intelligence Modeling for Drug Discovery. *Annu. Rev.*

781   *Pharmacol. Toxicol.* **60**, 573–589 (2020).

782 55. Gómez-Bombarelli, R. *et al.* Automatic Chemical Design Using a Data-Driven

783   Continuous Representation of Molecules. *ACS Cent. Sci.* **4**, 268–276 (2018).

784 56. Lin, X., Quan, Z., Wang, Z.-J., Huang, H. & Zeng, X. A novel molecular

785   representation with BiGRU neural networks for learning atom. *Brief. Bioinform.* **21**,

786   2099–2111 (2020).

787 57. Li, J. & Jiang, X. Mol-BERT: An Effective Molecular Representation with BERT for

788   Molecular Property Prediction. *Wirel. Commun. Mob. Comput.* **2021**, e7181815

789   (2021).

790 58. Mucllari, E., Zadorozhnyy, V., Ye, Q. & Nguyen, D. D. Novel Molecular

791   Representations Using Neumann-Cayley Orthogonal Gated Recurrent Unit. *J.*

792   *Chem. Inf. Model.* **63**, 2656–2666 (2023).

793 59. Mayr, A., Klambauer, G., Unterthiner, T. & Hochreiter, S. DeepTox: Toxicity

794   Prediction using Deep Learning. *Front. Environ. Sci.* **3**, (2016).

795 60. Landrum, G. RDKit: Open-source cheminformatics. Available from: https://rdkit.org/.

796   Zenodo https://doi.org/10.5281/zenodo.10398 (2014).

797 61. Willighagen, E. L. *et al.* The Chemistry Development Kit (CDK) v2.0: atom typing,

798   depiction, molecular formulas, and substructure searching. *J. Cheminformatics* **9**, 33

799   (2017).

62. PubChem. PubChem Substructure Fingerprint. (2/20/2021). Available at

https://ftp.ncbi.nlm.nih.gov/pubchem/specifications/pubchem_fingerprints.pdf.

https://ftp.ncbi.nlm.nih.gov/pubchem/specifications/pubchem_fingerprints.pdf (2009).

63. Klekota, J. & Roth, F. P. Chemical substructures that enrich for biological activity.

Bioinformatics **24**, 2518–2525 (2008).

64. Rogers, D., Brown, R. D. & Hahn, M. Using Extended-Connectivity Fingerprints with

Laplacian-Modified Bayesian Analysis in High-Throughput Screening Follow-Up.

SLAS Discov. **10**, 682–686 (2005).

65. Rogers, D. & Hahn, M. Extended-Connectivity Fingerprints. *J. Chem. Inf. Model.* **50**,

742–754 (2010).

66. The Chemistry Development Kit (CDK): Extended Fingerprint

https://github.com/egonw/cdk/blob/daba2d410cf4fd8462d55a3a4dd6f168db207af3/d

escriptor/fingerprint/src/main/java/org/openscience/cdk/fingerprint/ExtendedFingerpri

nter.java. (2020).

67. Nilakantan, R., Bauman, N., Dixon, J. S. & Venkataraghavan, R. Topological torsion:

a new molecular descriptor for SAR applications. Comparison with other descriptors.

J. Chem. Inf. Comput. Sci. **27**, 82–85 (1987).

68. Carhart, R. E., Smith, D. H. & Venkataraghavan, R. Atom pairs as molecular

features in structure-activity studies: definition and applications. *J. Chem. Inf.*

Comput. Sci. **25**, 64–73 (1985).

69. Reutlinger, M. *et al.* Chemically Advanced Template Search (CATS) for Scaffold-

Hopping and Prospective Target Prediction for 'Orphan' Molecules. *Mol. Inform.* **32**,

133–138 (2013).

Assessment of the impact of molecular representations on predictive
performance

Table 1a: The top performing standalone fingerprints for each of the 5 ML algorithms

Top 3 standalone fingerprints for each ML algorithm (% accuracy)					
Rank	GBDT	NBayes	kNN	RF	SVM
1.	AtomPair (97.06)	ECFP6 (98.17)	FCFP6 (97.64)	ECFP6 (98.48)	FCFP6 (98.54)
2.	Daylight-like (96.6)	FCFP6 (98.06)	Extended (97.36)	FCFP6 (98.24)	ECFP6 (98.5)
3.	ECFP6 (96.46)	PubChem (96.06)	ECFP6 (97.24)	Extended (98.2)	Daylight-like (98.44)

829 Table 1b: The best and worst performing models using a merged fingerprint for all 5 ML
830 algorithms

		GBDT	NBayes	kNN	RF	SVM
Molecular representations (% Accuracy)	Worst Performing Models	Estate (88.19)	Estate (59.44)	Estate (85.13)	Estate (92.13)	Estate (85.67)
	Best Performing Models	AtomPair + Daylight (97.36)	[i] PubChem + FCFP6; [ii] Extended + FCFP6 [iii] ECFP6 +FCFP6 (97.90)	FCFP6 + ECFP6 (98.22)	ECFP6 (98.48)	Extended + ECFP6 (99.05)

833   Table 2a Accuracy (%) of models trained with an imbalanced training dataset where the
834   number of BRAF actives is decreased but the number of BRAF inactives is maintained
835   at a fixed number (3600)

Accuracy (%) of models trained with decreasing number of BRAF actives				
Actives:Inactive	SVM+ECFP6	SVM+Daylight-like	RF+ECFP6	RF+Extended
3600:3600	98.60	98.30	98.40	97.90
3000:3600	98.11	98.11	98.60	98.30
2500:3600	98.11	97.91	98.30	97.90
2000:3600	98.41	97.81	97.90	97.80
1500:3600	97.91	97.42	98.10	97.40
1000:3600	97.22	96.92	97.60	96.60
500:3600	96.32	95.73	94.71	93.91
Performance difference between biggest and smallest datasets	2.28	2.57	3.69	3.99

837   Table 2b Accuracy (%) of models trained with a balanced training dataset where the
838   numbers of BRAF actives and BRAF inactives are both similarly decreased

Accuracy (%) of models trained with decreasing number of BRAF actives and inactives				
Actives:Inactive	SVM+ECFP6	SVM+Daylight-like	RF+ECFP6	RF+Extended
3600:3600	98.60	98.30	98.40	97.90
3000:3000	98.31	98.01	98.40	98.10
2500:2500	98.21	97.91	98.20	97.30
2000:2000	98.11	97.81	98.00	97.50
1500:1500	98.01	97.62	98.20	97.30
1000:1000	97.62	97.12	97.60	96.00
500:500	97.22	96.42	97.20	96.10
Performance difference between biggest and smallest datasets	1.38	1.88	1.20	1.80

841 Table 2c Recall and precision (%) of models trained with an imbalanced training dataset
842 where the number of BRAF actives is decreased but the number of BRAF inactives is
843 maintained at a fixed number (3600)

Model	Performance Metrics (%)	Imbalanced Training Dataset (actives:inactives)						
		3600:3600	3000:3600	2500:3600	2000:3600	1500:3600	1000:3600	500:3600
(i)	Recall	98.20	98	97.80	97.80	96.81	95.41	93.81
	Precision	98.98	98.79	98.99	99.59	99.59	99.58	99.37
(ii)	Recall	98.40	98.40	98	97.60	96.81	95.41	92.61
	Precision	98.21	98.40	98.40	98.59	98.58	98.96	99.36
(iii)	Recall	98	98	97.41	96.61	96.41	95.41	89.42
	Precision	98.79	99.19	99.19	99.18	99.79	99.79	100
(iv)	Recall	97.60	97.80	97.21	96.61	95.21	93.41	87.82
	Precision	98.19	98.79	98.58	98.98	99.58	99.79	100

Key: (i) SVM+ECFP6, (ii) SVM+Daylight-like, (iii) RF+ECFP6, and (iv) RF+Extended.

846 Table 2d Recall and precision (%) of models trained with a balanced training dataset
847 where the numbers of BRAF actives and BRAF inactives are both similarly decreased

Model	Performance Metrics (%)	Balanced Training Dataset (actives:inactives)						
		3600:3600	3000:3000	2500:2500	2000:2000	1500:1500	1000:1000	500:500
(i)	Recall	98.20	98.40	98	97.80	97.80	97.80	97.21
	Precision	98.98	98.80	98.99	98.99	98.79	98	97.79
(ii)	Recall	98.40	98.20	98	97.80	97.60	97.01	96.61
	Precision	98.21	98.40	98.40	98.39	98.19	97.79	96.80
(iii)	Recall	98	98	97.80	97.60	97.41	96.81	95.81
	Precision	98.79	98.79	98.59	98.39	98.99	98.38	98.56
(iv)	Recall	97.60	98	97	97.80	96.81	95.81	96.21
	Precision	98.19	98.2	97.59	97.22	97.78	96.19	96.02

Key: (i) SVM+ECFP6, (ii) SVM+Daylight-like, (iii) RF+ECFP6 and (iv) RF+Extended.

850 Table 3

851 Average accuracy for the 'spiked-in' "less active"-trained models based on testing with
852 10 balanced BRAF actives and inactives hold-out test sets

ML+Fingerprint	Average Accuracy(%)			
	Training sets			
	3600 actives / 3600 inactives	3600 actives / 3420 inactives / 180 less actives	3600 actives / 3240 inactives / 360 less actives	3600 actives / 3060 inactives / 510 less actives
SVM+ECFP6	97.16	96.83	95.86	95.66
SVM+Daylight-like	97.17	96.40	95.83	94.91
RF+ECFP6	97.74	96.24	95.81	95.34
RF+Extended	96.85	95.54	94.99	94.76

859 Table 4A

860 Average accuracy for the 'spiked-in' decoy-trained models based on testing with 10
861 balanced BRAF actives and inactives hold-out test sets

ML+Fingerprint	**Average Accuracy(%)**				
	Training sets				
	3600 actives / 3600 inactives	3600 actives / 3420 inactives / 180 decoys	3600 actives / 3240 inactives / 360 decoys	3600 actives / 3060 inactives / 510 decoys	3600 actives / 3600 decoys
SVM+ECFP6	97.16	96.95	96.85	96.80	93.85
SVM+Daylight-like	97.17	97.34	97.33	97.29	94.59
RF+ECFP6	97.74	97.65	97.66	97.65	94.98
RF+Extended	96.85	96.49	96.69	96.79	94.09

865 Table 4B

866 Accuracy for the 'spiked-in' decoy-trained models based on testing with a balanced
867 BRAF actives and decoys hold-out test set

ML+Fingerprint	Accuracy(%)				
	Training sets				
	3600 actives / 3600 inactives	3600 actives / 3420 inactives / 180 decoys	3600 actives / 3240 inactives / 360 decoys	3600 actives / 3060 inactives / 510 decoys	3600 actives / 3600 decoys
SVM+ECFP6	99.00	98.80	98.80	98.80	99.30
SVM+Daylight-like	99.20	98.80	98.80	98.80	99.10
RF+ECFP6	99.00	99.00	99.10	98.90	99.20
RF+Extended	98.90	98.50	98.80	98.70	99.10

871　Figure 1a Accuracy of models generated with various single and paired molecular representations using support vector

872　machine (SVM) during cross-validation (purple heatmap) and testing (blue heatmap)

Figure 1b Accuracy of models generated with various single and paired molecular representations using random forest (RF) during cross-validation (purple heatmap) and testing (blue heatmap)

Figure 1c Accuracy of models generated with various single and paired molecular representations using naïve bayes
(NBayes) during cross-validation (purple heatmap) and testing (blue heatmap)

Figure 1d Accuracy of models generated with various single and paired molecular representations using k-nearest
neighbour (kNN) during cross-validation (purple heatmap) and testing (blue heatmap)

Figure 1e Accuracy of models generated with various single and paired molecular representations using gradient-boosting

decision tree (GBDT) during cross-validation (purple heatmap) and testing (blue heatmap)

895