1 **Unveiling the Core Functional Networks of Cognition: An Ontology-Guided Machine**
2 **Learning Approach**
3

4 Guowei Wu[1,2], Cui Zaixu[3], Xiuyi Wang[1*], Yi Du[1,2,3*]
5
6 1. *CAS Key Laboratory of Behavioral Science, Institute of Psychology, Chinese Academy of*
7 *Sciences, 16 Lincui Road, Chaoyang, Beijing 100101, China*
8 2. *Department of Psychology, University of Chinese Academy of Sciences, Beijing 100049, China*
9 3. *Chinese Institute for Brain Research, Beijing 102206, China*
10
* Correspondence:
Yi Du, MD, CAS Key Laboratory of Behavioral Science, Institute of Psychology, Chinese
Academy of Sciences, 16 Lincui Road, Chaoyang, Beijing 100101, China (e-mail:
duyi@psych.ac.cn);
Xiuyi Wang, PhD, CAS Key Laboratory of Behavioral Science, Institute of Psychology, Chinese
Academy of Sciences, 16 Lincui Road, Chaoyang, Beijing 100101, China (e-mail: e-mail:
wangxiuyi@psych.ac.cn).
18

Abstract

Deciphering the functional architecture that underpins diverse cognitive functions is fundamental
quest in neuroscience. In this study, we employed an innovative machine learning framework that
integrated cognitive ontology with functional connectivity analysis to identify brain networks
essential for cognition. We identified a core assembly of functional connectomes, primarily
located within the association cortex, which showed superior predictive performance compared to
two conventional methods widely employed in previous research across various cognitive
domains. Our approach achieved a mean prediction accuracy of 0.13 across 16 cognitive tasks,
including working memory, reading comprehension, and sustained attention, outperforming the
traditional methods' accuracy of 0.08. In contrast, our method showed limited predictive power for
sensory, motor, and emotional functions, with a mean prediction accuracy of 0.03 across 9 relevant
tasks, slightly lower than the traditional methods' accuracy of 0.04. These cognitive connectomes
were further characterized by distinctive patterns of resting-state functional connectivity, structural
connectivity via white matter tracts, and gene expression, highlighting their neurogenetic
underpinnings. Our findings reveal a domain-general functional network fingerprint that pivotal to
cognition, offering a novel computational approach to explore the neural foundations of cognitive
abilities.
36
37 **Keywords:** cognitive ontology, functional networks, machine learning

38
39
40
41

Introduction

Unraveling the complexity of the human mind necessitates an in-depth examination of its cognitive functions such as attention, memory, executive functions, language, social cognition, all intertwined and foundational to our understanding of neuroscience [1–3]. The advent of cognitive ontology has paved the way for a structured exploration of these mental capacities, mapping their intricate interrelations with a data-driven approach [4–8]. Despite advancements in the construction of cognitive ontology, revealing its neural underpinnings remains a significant challenge.

Recent studies have leveraged functional connectivity (FC)—the correlation between the BOLD time series of different brain regions—to predict cognitive abilities with notable success, offering insights into the brain's organizational principles [9–12]. However, inconsistencies in methodology across studies have obscured a unified neural basis for cognitive ontology entity. For instance, Dubois et al. [10] utilized exploratory factor analysis (EFA) to establish a classical cognitive ontology entity, namely the g-factor, and demonstrated its predictability through distributed FC networks. In contrast, Kong et al. [11] applied factor analysis to develop a different cognitive ontology entity, the cognitive factor, without examining its predictability through FC networks. This disparity highlights the need for a coherent understanding of FC networks' role in cognition prediction.

Emerging research have underscored specific brain networks' pivotal role in supporting cognition. Bolt et al. [13] identified a general factor indicative of a "focused awareness" process or "attentional episode" through exploratory bifactor analysis, symbolizing a domain-general psychological process across cognition, perception, action, and emotion domains, manifest in core regions of the task-positive network. In parellel, Kristanto et al. [14] investigated the alignment between brain-derived (neurometric) and cognitive performance-derived (psychometric) ontologies, revealing that regions associated with cognitive abilities form an extensively interconnected structural network. These findings underscore the significance of selected brain regions for cognitive functions, laying the groundwork for our hypothesis that certain FC networks are crucial in supporting cognition.

Further bolstering this hypothesis, studies have demonstrated the cognitive factor's predictive power across multiple cognitive domains and its correlation with individual differences in ideological preferences [1,3,5,6]. He et al.'s [15] meta-matching framework, applying predictive models from large-scale datasets (the UK Biobank, N = 36,848) to new, smaller-scale (the Human Connectome Project, HCP, N = 1,019) non-brain-imaging phenotypes, has further exemplified the predictive capacity of FC data. Motived by these findings, we aimed to explore FC networks' capacity to encapsulate the cognitive factor and predict diverse cognitive functions beyond initial study groups.

Given the cognitive factor's stronger link to cognitive functions over sensory, motor, or emotional functions [7,16] we posited that distinct FC networks would preferentially represent cognitive abilities like executive function and language, but not those less cognitively related, such as motor

function and emotion. Furthermore, we hypothesize that the FC networks crucial for representing
the cognitive factor may primarily consist of connections within the association cortex. The
association cortex, encompassing regions such as the prefrontal cortex, parietal cortex, and
temporal cortex, has been implicated in higher-order cognitive processes, including attention,
working memory, decision-making, and language. These regions exhibit high levels of functional
connectivity, forming a densely interconnected network that supports the integration and
processing of information [17–20]. Moreover, the cognitive factor, as a latent variable derived
from diverse cognitive tasks, likely reflects a domain-general cognitive ability that underlies
performance across multiple domains [1,3,5,6,15]. As such, the FC networks that effectively
represent the cognitive factor should be able to predict individual differences in various cognitive
functions, including attention, working memory, executive control, and language processing. This
hypothesis aligns with recent findings demonstrating the predictive power of FC data across
different cognitive domains and datasets [10,11,16].
98
Utilizing behavioral and resting-state fMRI data from the HCP Young Adult (HCP-YA) [21] and
HCP Development Study (HCP-D) [22], we sought to validate if specific functional networks
could consistently predict the cognitive factor constructed by different methods, and subsequently,
cognitive behaviors. This approach not only tested the predictive stability of these networks but
also delved into the biological basis of FC networks associated with the cognitive factor,
examining FC strength variability, white matter connectivity, and gene association patterns. Our
comprehensive approach endeavors to elucidate the complex interplay between functional and
structural connectivity, gene expression, and cognition, ultimately enriching our understanding of
the neural foundations of human intelligence and behavior.
108

Method

(a) Participant information

We used two datasets: the WU-Minn HCP-YA S1200 release [21] and HCP-D [22]. The HCP-YA
dataset was used to test the main hypothesis: whether a unique group of network FC edges
underlying the cognitive factor can effectively predict various cognitive related behaviors rather
than cognitive less-related behaviors. The HCP-D dataset was employed to evaluate the capacity
of this unique network configuration to predict cognitive behaviors across datasets with
comparable efficacy. Please visit HCP project's website (https://www.humanconnectome.org/) for
detailed information about data acquisition protocols. This project was approved by the Washington
University local ethics committee.
119
We utilized the publicly accessible data from the HCP-YA S1200 release, encompassing multiple
magnetic resonance imaging (MRI) modalities such as resting-state functional MRI, diffusion MRI,
and structural MRI. The imaging data were obtained using a Siemens 3T Skyra scanner with a
multiband sequence. Each participant underwent 2 separate fMRI sessions on different days, with
each session comprising 2 phase-encoding runs (left-right and right-left, LR/RL). T1-weighted

structural data involved a single 0.7 mm isotropic scan per participant. The dMRI data encompassed

six 1.25 mm isotropic runs for each participant. Further information about the dataset and MRI

acquisition parameters can be found in the prior study by [21]

In addition to imaging data, the HCP database furnishes demographic data and performance metrics

for numerous cognitive tasks. From the available 1,206 datasets within the HCP database at the time

of the study, we excluded those with incomplete information, insufficient fMRI images, motion

unqualified data, and left-handed individuals. Consequently, a final sample of 601 individuals (329

females; aged between 22 and 36 years), was included.

This study incorporated a total of 633 subjects (294 males, aged 8-21 years) from the Lifespan 2.0

Release of the HCP-D. All imaging data were collected utilizing a multiband EPI sequence on a 3T

Siemens Prisma scanner. Each participant took part in 2 separate rs-fMRI sessions on different days..

The study employed a total of 4 runs, accounting for 26 minutes of rs-fMRI. T1-weighted structural

data involved a single 0.8 mm isotropic scan per participant. For further information about the

dataset and MRI acquisition parameters, please refer to [22].

Participants were excluded including those with incomplete information, insufficient fMRI images,

motion unqualified data, and left-handed individuals. The final sample thus comprised 374

individuals (197 females; age: 8 - 22).

(b) The pre-processing of fMRI data and functional connectivity estimation

In this study, we employed minimally preprocessed T1w and fMRI images from both HCP-D and

HCP-YA. The T1w images were initially corrected for intensity non-uniformity and subsequently

used as T1w-reference throughout the workflow. Following skull-stripping and brain surface

reconstruction, the volume-based brain-extracted T1w images were segmented into cerebrospinal

fluid (CSF), white matter (WM), and gray matter (GM), and spatially normalized to MNI space. The

rs-fMRI images underwent preprocessing steps such as motion correction, distortion correction,

co-registration to the T1w-reference image, and normalization to MNI space [23]. The BOLD

timeseries were resampled to the fsaverage space, generating grayordinates files containing 91k

samples.

Subsequently, the preprocessed fMRI images underwent further post-processing using the

extensible Connectivity Pipelines (XCP-D) [24]. Prior to nuisance regression, volumes with

framewise-displacement (FD) exceeding 0.3 were flagged as outliers and excluded. A total of 36

nuisance regressors were regressed out from the BOLD data, including motion parameters, global

signal, mean white matter, and mean CSF signal with their temporal derivatives, as well as the

quadratic expansion of motion parameters and tissue signals with their derivatives. The residual

timeseries were then band-pass filtered (0.01-0.08 Hz) and spatially smoothed (FWHM = 6 mm)

[25,26].

To mitigate the potential impact of head motion, subjects were further excluded based on two

criteria [27,28]. First, we excluded fMRI data with more than 25% of FDs exceeding 0.2 mm.

Second, we excluded fMRI data if the mean FD surpassed the 1.5*interquartile range (IQR) in the
adverse direction when estimating the distribution of mean FD across the same run for each dataset.
We retained subjects with all fMRI runs in HCP-YA (4 rs-fMRI runs) and HCP-D (4 rs-fMRI runs).
A total of 601 subjects (329 females, age 22-36) in HCP-YA and 374 subjects (197 males, age 8-22)
in HCP-D were utilized in the subsequent analyses.

We employed the Schaefer parcellation [29] to extract regional Blood Oxygen Level Dependent
(BOLD) timeseries data. This parcellation divides the whole brain into 400 parcels and has been
extensively utilized [30–32]. Previous studies showed commendable performance when using this
parcellation in the context of FC network analysis to predict cognitive functions[11,33,34]. We
evaluated FC by calculating the Pearson correlation coefficient between the timeseries of parcels.
As a result, we obtained a symmetric 400 * 400 functional connectivity matrix for each participant.
This matrix was transformed using the Fisher transformation, and the upper triangle was vectorized,
generating 79800 connectivity features.

(c) Cognitive factor computation

To derive a psychometric ontological entity, we conducted a confirmatory factor analysis (CFA)
model using the behavioral data from 13 tasks of the HCP-YA dataset. CFA can robustly construct
ontological entities [3,10,14].   We selected 13 behavioral metrics adopted from the task-evoked
fMRI measurement (in-scanner test), NIH Toolbox, and Penny Cognitive Battery based on previous
studies [3,10,14]. These behavioral metrics cover 5 distinct cognitive domains, including: (1)
executive functions related to processing speed: the NIH unadjusted scale score for Dimensional
Change Card Sort, Flanker test and Pattern completion Processing Speed, (2) executive functions
associated with working memory: Reaction time of 2-back condition in the working memory test,
the NIH unadjusted scale score for List Sorting task and Picture Sequence Memory, (3) fluid
intelligence: Number of Correct Responses (PMAT24 A CR), Total Skipped Items (PMAT24 A SI),
and Median Reaction Time for Correct Responses (PMAT24 A RTCR) in Penn Progressive
Matrices test, (4) relation ability: Reaction time of Relation task of match condition, Reaction time
of Relation task of relevance condition and (5) language ability: the NIH unadjusted scale score for
Picture Vocabulary test, and Reading Recognition test. A summary of these tasks is provided in
Table 1.

There are several methods to derive a cognitive ontological factor from scores on a set of cognitive
tasks, and a consensus comprehensive framework is yet to be established to define cognitive
ontology entity [7,8,16]. However, previous research indicated that cognitive domains, such as
executive functions, fluid intelligence, and language abilities, are not independent but rather exhibit
a hierarchical cognitive organization [3]. Accordingly, we proposed a second-order CFA model to
construct a domain-general cognitive ontological entity. To achieve this, we utilized the *lavaan*
package (https://lavaan.ugent.be) within the R Software (https://www.r-project.org/).

We hypothesized that all 13 task scores can be organized into the five first-order factors: executive
function related to process speed, executive function related to working memory, relation ability,

fluid intelligence, and language ability [3,10,14]. Additionally, we proposed a second order latent
variable called 'cognitive factor' to capture the interrelationships among these five first-order factors
according to EFA model result from previous study [3]. We fitted this model to the data of HCP-YA
which included a total of 601 subjects. To facilitate the model identification, all behavior scores
were standardized using z-scores, allowing for free estimation of all factor loadings. The CFA
model was tested using Maximum Likelihood (ML) estimator, and the model fit was assessed using
the chi-square goodness-of-fit index ($\chi 2$), the comparative Fit Index (CFI), the Root-Mean-Squared
Error of Approximation (RMSEA), and the Standardized Root-Mean-Squared residual (SRMR).
We evaluated the model fit based on established thresholds, considering CFI equal to or greater than
0.95 and both RMSEA and SRMR values less than 0.08, as recommended by [35] After model
fitting, we calculated the individual-level cognitive factor score with a regression method using
lavPredict function [36].

(d) Prediction of the cognitive factor score using FC

To identify the FC edges that have a significant influence on predicting cognitive factor score, we
employed ridge regression to examine the relationship between all FC edges and cognitive factor
score obtained from the CFA model [11,17,20,37]. We set the second-order cognitive factor score as
the dependent variable, enabling us to calculate the regression coefficient (β value) for each edge
corresponding to the cognitive factor score. The L2-norm regularization of ridge regression
archived a balance between penalties for training error and model complexity. The magnitude of the
β coefficient for each edge indicates its significance in predicting the cognitive factor score. We
sorted all the absolute weights of the β coefficient and selected the top 10% ranked edges. In this
way, we identified a subset of FC edges vital for predicting the cognitive factor score. To train the
ridge regression model, we employed a nested 2-fold cross-validation strategy. For each iteration,
we divided the dataset into two parts for training and validation [17]. Specifically, we measured
prediction accuracy using the Pearson correlation and Mean Squared Error (MSE) between actual
and predicted values. For each iteration, roles of training and testing sets were switched,
producing two Pearson R values and MSE values. We averaged these values across 100 iterations
to determine the model's overall performance. The term "prediction accuracy," when not
specifically defined, refers to the Pearson correlation coefficient 'R' between predicted and actual
values.
239
To assess if FC edges significantly predict cognitive factor score, we established a null distribution
using a permutation test. This involved randomly shuffling cognitive factor scores within the
training dataset across participants 200 times, creating 200 samples of prediction accuracy under
the assumption of no relationship between FC and cognitive ontology score. We then compared
the 100 actual correlation coefficients (R values) from the above 100 iterations with this null
distribution using the nonparametric Wilcoxon signed-rank test [12,20].
246

(e) Behaviors used in cross task prediction paradigm

To assess whether the key FC edges used to predict cognitive factor score accurately represent

cognitive functions, we chose 25 behavioral metrics from the HCP-YA dataset in a cross-task
prediction paradigm. These target behaviors encompass a variety cognitive related behavior, such as
working memory, fluid intelligence, language ability, spatial attention, and sustained attention. We
also included several cognitive less-related behaviors, such as motor tasks, sophisticated emotional
processing tasks, and measures assessing life satisfaction. These behaviors allow us to evaluate if
the pivotal FC edges for predicting cognitive factor score can better forecast cognitive functions
compared to motor or emotion functions.
256
The 25 selected behavioral measures span 10 domains, including:
(1) one metric for Working Memory: Median Reaction Time of 2-back condition of Working
Memory Task in fMRI scanner (WM Task 2bk Median RT);
(2) three metrics for Language ability: Accuracy of Language Task in Story condition (Language
Task Story Acc), Average Difficulty in Language Task in Story condition (Story Avg Difficulty)
and Median Reaction Time of Language Task in Story condition (Language Task Story Median
RT);
(3) three metrics for Sustained Attention: Learning Rate in Short Penn Continuous Performance
Test (SCPT LRNR), Sensitivity in Short Penn Continuous Performance Test (SCPT SPEC),
Specificity in Short Penn Continuous Performance Test (SCPT SEN) and Median Response Time
for True in Short Penn Continuous Performance Test (SCPT TPRT);
(4) three metrics for Spatial Orientation: Correct Reaction Time in Penn Line Orientation Test
(VSPLOT CRTE), Offset in Penn Line Orientation Test (VSPLOT OFF) and Total completion in
Penn Line Orientation Test (VSPLOT TC);
(5) one metric for Self-Regulation: Delay Discounting: Area Under the Curve for Discounting of
$40,000 (DDisc AUC 40K);
(6) one for Verbal Episodic Memory: Median Reaction Time for Correct Responses in Penn Word
Memory Test (IWRD RTC);
(7) one metric for Psychological Well-being: Subjective well-being and contentment with life (Life
Satisfy);
(8) four metrics for Social Relationship: Perceived interpersonal rejection (Rejection), Subjective
feelings of loneliness and social isolation (Loneliness), Perceived helpful behaviors from others
(Instru Supp) and Perceived stress level (PercStress);
(9) three metrics for Emotion: Intensity of Anger emotions (Anger Affect), Intensity of Sadness
emotions (Sadness) and Intensity of Fear emotions (Fear Affect);
(10) four metrics for Motor: Endurance, Grip Strength (Strength), Walking Speed (Gait Speed
Component) and Dexterity.
284
Detailed descriptions of each measure are available in Table 3. All task scores were standardized
using z-scores before being included in the prediction model. To measure what the extent that
cognitive factor related to these 25 target behaviors, we calculated the Spearman correlation
between cognitive factor score and their raw scores, which we refer to as 'cognitive loading'.
Behaviors that showed a significant correlation with cognitive factor are considered
cognitive-related behaviors, while others are categorized as cognitive less-related behaviors.

(f) Framework of FC based behavioral prediction

We hypothesized that the edges that contributed significantly to predicting cognitive factor score

could better represent cognitive functions compared to motor or emotion functions. To test this, we

built three comparable models and then used these models to predict the behavior performance.

Finally, we compared the prediction accuracy between these three models.

We built three models using identical cross-validation strategies, differing only in feature selection.

The first named Cognitive Ontology based Prediction Model (COPM), selected FC features based

on their importance in predicting cognitive factor score, using the top 10% of FC edges (7980)

identified by their absolute β coefficients. This model, like the others, was applied to predict

various behaviors, with each model's prediction accuracy averaging over 100 iterations for

stability. As baseline, we also included 2 additional models. The Full-FC (F-F) model, utilized all

FC edges to predict behavioral score. To control feature number differences between COPM and

F-F, our second baseline model, the Ridge-regression based Connectome Predictive Model (rCPM)

also used 7980 edges. Unlike the COPM, which identifies edges based on the training dataset's

absolute β coefficients after 100 iterations of cognitive factor prediction modeling, the rCPM selects

edges by ranking the absolute magnitude of each edge's regression coefficients within the training

set for specific behavioral prediction. For each model and each iteration, we used the split-half

validation method, dividing the dataset into two parts for training and validation [17]. Specifically,

we measured prediction accuracy using the Pearson correlation and MSE between actual and

predicted values. For each iteration, roles of training and testing sets were switched, producing

two Pearson R values and MSEs. We averaged these values across iterations to determine the

model's overall performance.

Finally, we assessed whether the COPM could better represent cognitive functions compared to

motor or emotion functions, a distinction not observed in the F-F and rCPM. Specifically, we

selected 25 behavioral tasks across 10 domains from the HCP-YA dataset. For each task, we first

calculated the 'cognitive loading', which is the correlation between raw performance and cognitive

factor score. Next, we calculated the average prediction accuracy for each model and calculated the

Spearman correlations between the prediction accuracy and cognitive loading, labeling them as

COPM-R, F-F Model-R, and rCPM-R, respectively. To determine if COPM more accurately

predicts behaviors associated with cognitive factor score, we compared these correlations, using the

cocor function in R [38,39]. A higher COPM-R value compared to both F-F Model-R and rCPM-R

indicates that the COPM model offers more accurate predictions for behaviors closely associated

with cognition. Furthermore, to demonstrate that COPM's benefits are primarily for

cognitive-related behaviors, we compared the mean prediction accuracy between tasks that are

cognitive-related and those less so. This comparison was done using the non-parametric Wilcoxon

signed-rank test, with all p-values adjusted using false discovery rate (FDR) correction.

For hyperparameter tuning, we employed a nested 20-fold cross-validation [20], specifically

designed for ridge regression using MATLAB's fitlinear.m function. In each inner training

iteration, a grid search was performed on 100 logarithmically spaced α values ranging from

10^-5/N to 10^5/N, where N represents the number of subjects in the inner training fold. The
optimization process combined Average Stochastic Gradient Descent (ASGD) with the
limited-memory BFGS quasi-Newton algorithm (LBFGS), terminating after 1000 iterations or
when the change in coefficients and intercept fell below 10^-4 per iteration. The optimal α value,
yielding the minimum error across inner test folds, was used to calculate beta coefficients for the
outer training set, while accounting for age, sex, and motion as covariates [11,20]. The resulting
regression parameters were then applied to the testing set to control for covariate effects on
behavioral variables.
341

(g) Cross-dataset predictive efficiency of the COPM

We evaluated the COPM model's ability to predict cognitive functions using the HCP-D dataset.
This dataset includes similar behavioral tasks as HCP-YA, except that it focuses on children aged
between 8 and 22. We hypothesized that if the COPM outperforms the F-F model and rCPM in
predicting cognitive functions in the HCP-D dataset, while showing similar performance in motor
and emotion functions, it would suggest a stable set of FC edges representing human cognition. For
this test, we selected eight behavioral measures covering a broad range of domains. From our
HCP-YA dataset analysis, 6 of these tasks assess cognitive related functions, such as executive
control and language skills, while 2 measure cognitive less-related functions, including motor
ability and emotional processing. The tasks include (1) 4 tasks for measuring executive function:
Dimensional Card Sorting, Flanker test and List Sorting Working Memory and Picture Sequence
Memory; (2) 2 tasks for measuring language ability, including Oral Reading Recognition test and
Picture Vocabulary; (3) 1 task for motor: Grip Strength and (4) 1 task for emotion: Fear Affect, with
detailed descriptions in S2 Table. We applied the COPM, F-F model, and rCPM to predict each
behavior using the same procedures as before. We then used the non-parametric Wilcoxon
signed-rank test to compare the prediction accuracy across the 2 types of behaviors and the 3 models.
The COPM employed the top 10% of FC edges identified as significant in predicting cognitive
factor score within the HCP-YA dataset. We did not reassess cognitive factor within the HCP-D
dataset, thus directly assessing the cross-dataset predictive stability of these influential edges.
361

(h) Exploring the FC variability, white matter structural basis, and genetic basis of FC edges

in COPM

To explore the biological underpinnings of the 7980 FC edges used in the COPM, we analyzed
their FC variability, white matter structural connectivity, and genetic expression similarity patterns,
following the methodology outlined by [40]. To ascertain the significance of each edge in
predicting cognitive factor, we calculated their linear contribution weights, called the 'contribution
weight matrix', based on the cognitive factor prediction model. We obtained four 400x400
matrices, corresponding to contribution weight, FC strength variability, white matter structural
connectivity, and genetic expression similarity, respectively.
371

The 400 parcels in the Schaefer 400 atlas can be classified into 17 functional networks [29,41]. We calculated intra- and inter-network connectivity averages within the Yeo 17 network [29,41] for each of the 400x400 matrices, yielding four distinct 17x17 matrices. Since we were only interested in the edges that make great contributions when predicting cognitive factor, we only considered these edges and calculated the intra- and inter-network average connectivity. After that, we computed the Spearman correlation between the contribution weight matrix and the other three matrices. To evaluate the statistical significance of these correlations, we generated a null distribution using permutation by randomly selecting 7980 edges 10000 times from the 400x400 matrix. We then computed intra- and inter-network connectivity averages within the Yeo 17 network, resulting in a new 17x17 matrix for each index. We subsequently correlated this matrix with the 17x17 contribution weight matrix. The p-value was determined using the proportion of real correlations that exceeded the permuted correlations, with a threshold for significance set at $p < 0.05/3$.

(i) **Validation analysis across varied edge selection percentiles and parcellation scheme**

To assess the stability of our findings, we analyzed the most influential edges in predicting cognitive score using varying thresholds: 20%, 30%. For each threshold, we identified the edges with the greatest contribution and replicated the initial procedure. This process included predicting the performance of specific tasks at each threshold and then evaluating the correlation between cognitive loading and the prediction accuracy of both the COPM and rCPM models. Finally, we compared these correlation results across the 2 models for each threshold.

We further assessed our results' robustness with Glasser's atlas [42], constructing 360x360 individual functional connectomes to predict cognitive factor using COPM and F-F models. The F-F model alone served as the baseline for comparison, given its similar prediction accuracy to the rCPM model with the Schaefer atlas [29], and the time-consuming nature of replicating this analysis with rCPM.

Code availability

All code used to perform the analyses in this study can be found at https://github.com/guoweiwuorgin/FC_COPM_framework.

Data availability

The HCP-YA and HCP-D datasets, including T1-weight MRI, functional MRI and diffusion-weighted MRI are available at https://db.humanconnectome.org/. Gene expression data can be downloaded from the AHBA (http://human.brain-map.org) and processed using the abagen toolbox (https://github.com/rmarkello/abagen).

Results

We first examined whether specific FC edges between networks could reliably represent the cognitive factor. This factor was constructed using CFA based on multiple behavior tasks from the HCP-YA dataset. We then calculated parcel-based FC matrices for each participant using resting-state fMRI data from the HCP-YA dataset, employing the Schaefer atlas which divides the cerebral cortex into 400 parcels [29]. Subsequently, we built a ridge regression model to identify FC edges crucial for predicting the cognitive factor. Next, we assessed whether a model incorporating these edges, the COPM outperformed two baseline models in predicting cognitive related behaviors whose performance showed significant correlations with the cognitive factor score, but not in predicting those cognitive less-related behaviors which showed no significant correlation with the cognitive factor score. The first baseline model, the F-F model, incorporated all edges, while the second used a connectome predictive model (CPM) method (termed as rCPM) to select the same number of edges as COPM but relevant to target behavior, not cognitive factor. We further validated the predictive reliability of these edges for cognitive functions using the HCP-D dataset, which includes 8 tasks identical to those in the HCP-YA. To probe the biological underpinnings of these key edges, we analyzed their relationships with FC variability, white matter structure, and gene expression similarity. Moreover, to ensure the robustness of our findings, we replicated the main results using varying thresholds for edge selection within the COPM, alongside using different brain parcellations to delineate functional areas. The whole analysis framework outlined in Figure 1.

Figure 1. Framework of method. A – We calculated cognitive factor score at the individual level using a second-order confirmatory factor analysis (CFA), analyzing 13 behaviors across multiple domains from the HCP-YA dataset. B – We calculated functional connectivity (FC) for each participant using Schaefer 400 atlas [29]. C – We used ridge regression to predict the cognitive

factor score using all FC edges. D. We then included the top 10% of edges that significantly contributed to predicting cognitive factor in the Cognitive Ontology based Prediction Model (COPM). The selected edges were then used to predict the behavior performance of 25 new behaviors from the HCP-YA dataset. To further examine whether the representation of cognitive closely related functions is distinctly tied to the above edges that play a substantial role in predicting cognitive factor score, we performed similar analyses using two alternative models. The first model, named the Full-FC (F-F) model, utilizes the entire FC matrix. The second, referred to as the Ridge-regression based Connectome Predictive Model (rCPM), used an equivalent number of edges as the COPM, but selected via multiple linear regression within the CPM framework based on their close relation to the target behavior rather than the cognitive factor. E- We calculated the correlation between each task's raw performance and cognitive factor score across all subjects, which we refer to as 'cognitive loading'. Tasks with higher cognitive loading indicate they measure cognitive related functions, whereas those with lower cognitive loading suggest cognitive less-related functions. Each dot presents one subject. F– We calculated the correlations between prediction accuracy calculated in D and the cognitive loading calculated in E to examine whether tasks with greater cognitive loading (i.e., those behaviors closely related with cognitive factor) have higher prediction accuracy. G – We directly compared the correlations between cognitive loading and prediction accuracy across these models. H – To examine whether the same edges identified in HCP-YA dataset also show specificity in predicting cognitive functions in a new dataset, we repeated the analysis using 8 new behaviors from the HCP-D dataset. I– To explore the biological underpinnings of the top FC edges included in the COPM, we analyzed their relationships with three key biological factors: FC variability, white matter structure, and gene expression similarity. Specifically, we extracted the contribution weights of these edges in predicting the cognitive factor score. These weights indicate each edge's relative importance in the prediction process, with higher weights suggesting a more significant role in forecasting the cognitive factor score. We then calculate the correlations between these contribution weights and three key biological factors. J – To ensure the robustness of our findings, we replicated the main results with varying thresholds for edge selection in the COPM and employed a different brain parcellation to delineate functional areas, such as Glasser parcellation.

The cognitive factor can be derived from a second-order CFA model and predicted by the whole brain FC

To test our hypothesis that FC edges can predict cognitive factor, we first created a cognitive factor using the behavior data and calculated FC using the resting-state fMRI data from the HCP-YA dataset. To create a cognitive factor that captures the individual variability across various cognitive domains, we employed a second-order CFA model which can more accurately capture cognitive ontology on 13 behavior tasks from the HCP-YA dataset (see Table 1). These 13 tasks span 5 domains, including: (I) 4 tasks measure executive functions related to processing speed, (II) 3 tasks measure executive functions associated with working memory, (III) 4 tasks measure fluid intelligence, (IV) 2 tasks measure relation ability, and (V) 2 tasks measure language ability. These tasks were often used to calculate the cognitive factor [2,3,10,14].

Our results showed that the five first-order factors exhibited substantial loadings in the following
domains: executive function related to processing speed (β=0.47), executive function related to
working memory (β=2.12), fluid intelligence (β=0.73), relational ability (β=-0.20), and language
(β=0.88). Each primary factor significantly contributes to the second-order cognitive factor termed
as *cognition*, encapsulating a refined representation of cognitive functions (Figure. 2A and Table.
2). The second-order CFA model can capture a second-order factor (i.e., cognitive factor) with a
commendable model fit (CFI=0.95, TLI=0.93, RMSEA=0.07, 90% CI [0.06, 0.08], SRMR=0.074,
χ^2/df=4.16). After calculating the regression-based weights, each participant had one cognitive
factor score.

Further, using the Schaefer 400 atlas, we constructed a parcel-based resting-state FC matrix for
each participant and applied ridge regression to test whether the FC features can significantly
predict the cognitive factor compared to the chance level (computed by permutation approach, see
method '*(d) Prediction of the cognitive factor score using FC*' section). We found that the whole
FC matrix predicted the cognitive factor score with greater accuracy than chance (Figure 2B; p <
0.001 by nonparametric paired Wilcoxon test, with a Wilcoxon effect size of r = 0.82; the median
accuracy = 0.39, interquartile range = 0.04, the median accuracy of chance level = 0.001,
interquartile range of chance level = 0.067, the median MAE = 0.62, the median MAE of chance
level = 0.67).

To address potential model bias, we replicated our analysis using a bifactor CFA model to derive
the cognitive factor score. The bi-factor CFA model can capture a second-order factor (i.e.,
cognitive factor) with a perfect model fit (CFI=0.97, TLI=0.95, RMSEA=0.048, 90% CI [0.35,
0.61], SRMR=0.006, χ^2/df=2.38). We observed a similar pattern that the whole FC matrix
predicted the cognitive factor score with greater accuracy than chance (median accuracy = 0.41,
interquartile range = 0.04, the median accuracy of chance level = 0.001, interquartile range of
chance level = 0.069, the median MAE = 0.60, the median MAE of chance level = 0.67, see
Figure S1 and Table S1 in Supplementary). Then we selected the top 10% edges that made
significant contribution to predicting the cognitive factor for each model (i.e., second-order CFA
model and bifactor CFA). We examined the consistency of the edges among the 2 models and
found a strong consistency (Dice coefficient = 0.83), suggesting that FC can predict the cognitive
factor, regardless of the specific CFA model used.

Additionally, to evaluate the influence of behavior selection, we adapted a G-factor model using
10 behaviors identified by Dubois et al. [10]. Among them, 7 tasks were included in the second
order CFA model and 3 were new (see Table S2 for detailed information). This model also showed
moderate predictive accuracy with FC (Median accuracy = 0.38, interquartile range = 0.04,
median accuracy of chance level = 0.001, interquartile range of chance level = 0.071, the median
MAE = 0.63, the median MAE of chance level = 0.67), and the key predictive edges largely
overlapped with those from our original second-order CFA model (Dice coefficient = 0.58). These
findings collectively highlight FC's robustness in predicting cognitive factor, regardless of the
CFA model or behaviors analyzed.

Table 1 13 behaviors used in CFA model.

Test Name	Test Content
NIH toolbox: DCCS	Dimensional Change Card Sort is a measure of cognitive flexibility. Score is based on a combination of accuracy and reaction time, and the test takes approximately 4 minutes to administer
NIH toolbox: Flanker	The Flanker task measures both a participant's attention and inhibitory control. Scoring is based on a combination of accuracy and reaction time, and the test takes approximately 3 minutes to administer
NIH toolbox: Process Speed	Pattern Completion Processing Speed measures speed of processing. Asking participants to discern whether 2 side-by-side pictures are the same or not. Participants' raw score is the number of items correct in a 90-second period.
fMRI Scanner: WM ACC	Working memory test 2-back overall accuracy in fMRI task.
NIH toolbox: List Sorting	List Sorting assesses working memory and requires the participant to sequence different visually- and orally-presented stimuli.
NIH toolbox: Picture Sequence	Picture Sequence Memory involves recalling increasingly lengthy series of illustrated objects and activities that are presented in a particular order on the computer screen.
PMAT24 A CR	Penn Progressive Matrices: Number of Correct Responses
PMAT24 A SI	Penn Progressive Matrices: Total Skipped Items
PMAT24 A RTCR	Penn Progressive Matrices: Median Reaction Time for Correct Responses
fMRI Scanner: RL RT M	Reaction time of Relation task of match condition.
fMRI Scanner: RL RT R	Reaction time of Relation task of relevance condition.
NIH toolbox: Picture Vocabulary	The respondent is presented with an audio recording of a word and 4 photographic images on the computer screen and is asked to select the picture that most closely matches the meaning of the word.
NIH toolbox: Reading Recognition	The participant is asked to read and pronounce letters and words as accurately as possible.

519 *Note:* Scores of all task from NIH toolbox is normed to those in the entire NIH Toolbox Normative
520 Sample (18 and older), regardless of age or any other variable, where a score of 100 indicates
521 performance that was at the national average and a score of 115 or 85, indicates performance 1 SD
522 above or below the national average.

Figure 2. The cognitive factor can be derived from a second-order CFA model and predicted

by the whole brain FC. A – The five first-order factors exhibited substantial loadings in the

following domains: executive functions related to processing speed (EF: speed), executive

functions associated with working memory (EF: WM), fluid intelligence (FI), relational ability

(RL), and language (LAN). Each primary factor significantly contributes to the second-order

cognitive factor, captured by the second-order CFA model. B – The cognitive factor score can be

predicted by the whole brain FC with greater accuracy than chance. The scatter plot shows

significant positive correlations between the actual and predicted cognitive factor scores from one

iteration (the data used here was the one whose prediction accuracy most closely matched the

median accuracy.). Each dot represents the data of one participant. The gray in the left corner

represents the distribution of prediction accuracy from 200 permutations, while the purple

represents the distribution prediction accuracy from 100 iterations of the prediction model.

Table 2 Fitting results of second order CFA model.

	Estimate (S.E.)	z	*p*	LCI	UCI
Latent Variables:					
EF: Speed =~ Card Sorting	0.76 (0.05)	13.9	<.001 ***	0.67	0.86
EF: Speed =~ Flanker	0.67 (0.04)	13.18	<.001 ***	0.58	0.76
EF: Speed =~ Process Speed	0.46 (0.04)	9.66	<.001 ***	0.38	0.54
EF: WM =~ WM Task 2bk Acc	0.68 (0.08)	3.62	<.001 ***	0.52	0.83
EF: WM =~ List Sorting	0.53 (0.06)	3.69	<.001 ***	0.41	0.64
EF: WM =~ Picture Sequence	0.42 (0.05)	3.59	<.001 ***	0.32	0.51
FI =~ PMAT24 A CR	1.01 (0.03)	25.81	<.001 ***	0.95	1.07
FI =~ PMAT24 A SI	-0.95 (0.03)	-24.91	<.001 ***	-1.01	-0.89
FI =~ PMAT24 A RTCR	0.70 (0.03)	17.87	<.001 ***	0.64	0.77
Relation =~ Match Median RT	1.57 (0.43)	3.59	<.001 ***	0.74	2.41
Relation =~ Rel Median RT	0.41 (0.11)	3.71	<.001 ***	0.20	0.62
LAN =~ Pic Vocabulary	0.80 (0.04)	13.86	<.001 ***	0.73	0.89

LAN =~ Read English	0.79 (0.04)	13.94	<.001 ***	0.71	0.87
Cognition =~ EF: Speed	0.42 (0.07)	6.61	<.001 ***	0.28	0.56
Cognition =~ EF: WM	0.90 (0.65)	3.25	.001 **	0.84	0.99
Cognition =~ Relation	-0.19 (0.07)	-2.64	.008 **	-0.33	-0.04
Cognition =~ LAN	0.66 (0.10)	8.6	<.001 ***	0.46	0.86
Cognition =~ FI	0.59 (0.07)	9.92	<.001 ***	0.45	0.74

539 Note: A * indicates *p*<0.05, two * indicates *p*<0.01 and three indicates *p*<0.001, LCI means lower

540 bound of confidence interval and UCI means upper bound of confidence interval

541 The top edges that significantly contribute to the prediction of the cognitive factor represent

542 cognitive functions more than motor and emotion functions

After identifying the top 10% of edges that contributed significantly to predicting cognitive factor

score, we examined whether they could better represent cognitive functions compared to motor

and emotion functions. For this purpose, we specifically selected 25 new behavioral tasks from the

HCP-YA dataset to cover a spectrum of cognitive functions: some tasks, such as those measuring

executive control, represented cognitive closely related functions while others, like those assessing

motor skills and emotions, indicated cognitive less-related functions. This diverse range of tasks

allowed us to test whether the identified edges could more accurately predict cognitive related as

opposed to cognitive less-related cognitive functions. The selected tasks encompassed a broad array

of cognitive and behavioral areas, including executive control, sustained attention, language, verbal

episodic memory, self-regulation, spatial orientation, motor skills, emotion processing, social

relationships, and psychological well-being. Detailed descriptions and comprehensive information

about these tasks are provided in Table 3.

First, we calculated the correlation between each task's raw performance and cognitive factor

score across subjects (as shown in Figure 3A), which we refer to as 'cognitive loading'. Tasks with

higher cognitive loading indicate they measure cognitive related functions, whereas those with

lower cognitive loading suggest they measure cognitive-less related functions. Following this, we

adapted our methodology by constructing a ridge regression model to predict task performance. In

this model, we deviated from our previous approach by incorporating only the top 10% of

identified edges, instead of the entire FC matrix, into the COPM. After model construction, we

computed the prediction accuracy for each task. Subsequently, we explored the relationship

between cognitive loading and prediction accuracy by calculating their correlation. Our analysis

revealed a significant positive correlation (r = 0.64, p < 0.001, Figure 3B). This finding suggests

that tasks with a stronger correlation to the cognitive factor tend to have higher prediction

accuracy compared to those with a weaker correlation. Consequently, these results imply that the

selected edges are more representative of cognitive related functions than those less-related ones.

To further examine whether the representation of cognitive function is distinctly tied to the edges

that play a substantial role in predicting cognitive factor score, we performed similar analyses

using 2 alternative models. The first model, named the F-F model, utilizes the entire FC matrix.

The second, referred to as the rCPM, incorporates a number of edges equivalent to those in the

COPM, but these edges are selected via multiple linear regression within the CPM framework.
This selection is based on their close relation to the target behavior rather than the cognitive factor
score (refer to the Method section for detailed information). Cognitive loading was not
significantly correlated with the prediction accuracy in either the F-F model (r = 0.35, p = 0.09,
Figure 3B) or the rCPM (r = 0.40, p = 0.05, Figure 3B). To further assess these findings, we
directly compared the correlations between cognitive loading and prediction accuracy across these
models. Cognitive loading exhibited a stronger correlation with the prediction accuracy in the
COPM than in both the F-F model (z = 3.4216, $p = 0.0006$) and the rCPM (z = 3.1577, $p = 0.0016$).
These results suggest that the specific edges identified as significant in predicting cognitive factor
score have a unique association with cognitive functions.

Figure 3. The top edges that significantly contributed to predicting cognitive factor score can
better represent cognitive-related functions compared to less-related ones. A – The bar shows
the correlations between each task's raw performance and cognitive factor score across all subjects,
termed 'cognitive loading'. Tasks with higher cognitive loading indicate they measure cognitive
related functions, whereas those with lower cognitive loading suggest they measure cognitive
less-related functions. Orange bars represent tasks with significant correlations (p < 0.05,
FDR-corrected) and Bule bars denote those with unsignificant correlations (p > 0.05,
FDR-corrected). B – The scatter plot shows the correlation between cognitive loading and the
prediction accuracy of each model for each task. Dark purple filled circle represents COPM, light
purple filled triangle represents F-F model, and light purple empty square represents rCPM.
Table 3 Detailed descriptions of 25 tasks from HCP-YA used in prediction analysis.

Abbreviation	Full name	Content
ACC of Story Task	Accuracy of Language Task in Story condition	Evaluates language comprehension and accuracy
Anger	Anger Affect	Evaluates intensity of anger emotions
DDisc AUC 40K	Delay Discounting: Area Under the Curve for Discounting of $40,000	Measures preference for smaller immediate rewards over delayed rewards
Dexterity	Dexterity	Evaluates fine motor skills
Difficulty of Story Task	Average Difficulty in Language Task in Story condition	Measures cognitive load in language task
Endurance	Endurance	Assesses physical stamina
Fear	Fear Affect	Evaluates intensity of fear emotions
Gait Speed	composite Gait Speed	Assesses walking speed
IWRD RTC	Median Reaction Time for Correct Responses in Penn Word Memory Test	Evaluates memory and cognitive speed
Life Satisfaction	Life Satisfaction	Assesses subjective well-being and contentment with life
Loneliness	Loneliness	Measures subjective feelings of loneliness and social isolation
Median RT of 2-back task	Median Reaction Time of 2-back condition of Working Memory Task in fMRI scanner	Evaluates working memory and cognitive speed
Rejection	Perceived Rejection	Assesses perceived interpersonal rejection
RT of Language Task	Median Reaction Time of Language Task in Story condition	Evaluates cognitive speed in language task
Sadness	Sadness	Evaluates intensity of sadness emotions
SCPT LRNR	Learning Rate in Short Penn Continuous Performance Test	Evaluates cognitive adaptability and learning speed
SCPT SEN	Sensitivity in Short Penn Continuous Performance Test	Measures cognitive accuracy and attention to detail
SCPT SPEC	Specificity in Short Penn Continuous Performance Test	Assesses cognitive discriminative capacity
SCPT TPRT	Median Response Time for True in Short Penn Continuous Performance Test	Evaluates cognitive speed in attention task
Perceived Stress	Perceived Stress	Measures perceived stress level
Strength	Strength	Assesses physical strength, particularly grip strength
Supportive	Instrumental Support	Measures perceived helpful behaviors from others
VSPLOT CRTE	Correct Reaction Time in Penn Line Orientation Test	Evaluates visual-spatial cognitive speed
VSPLOT OFF	Offset in Penn Line Orientation Test	Measures precision in visual-spatial task
VSPLOT TC	Total completion in Penn Line Orientation Test	Assesses completion rate in visual-spatial task

To further substantiate the afore mentioned results, we categorized behaviors according to their
correlation between the raw performance and the cognitive factor score. This categorization aimed
to assess if the COPM could predict highly correlated behaviors more accurately than the other 2
models and if it demonstrated a similar or opposite pattern for behaviors with weaker correlations.
Our findings indicated that 16 out of 25 behaviors showed significant correlations with the
cognitive factor score (p < 0.05, FDR-corrected), whereas 9 did not. The COPM predicted the
performance of the 16 significantly correlated behaviors more accurately than the 9 with weaker
correlations (p < 0.001, Wilcoxon effect size r = 0.868). Within the group of behaviors
demonstrating significant correlations with cognitive factor, the COPM outperformed both the F-F
Model and the rCPM in predicting the performance of 13 behaviors (p<0.05, FDR corrected, see
details in table 4). These behaviors included tasks measuring executive function and language
abilities, such as the reaction time (RT) of 2-back working memory and the accuracy of the story
comprehension task. In contrast, for 2 behaviors in this subset, the COPM yielded greater
prediction accuracies than either the F-F Model or rCPM, including tasks like the RT of the story
comprehension task. Besides, the prediction accuracy of strength task of COPM lower than rCPM.
However, for the subset of behaviors that did not show significant correlations, the predictive
accuracy of the COPM was exceeded by either the F-F Model or the rCPM except the median RT for
true response in Short Penn Continuous Performance Test, which evaluates cognitive speed in
attention task (p > 0.05, FDR-corrected).

Figure 4. The prediction accuracy of the COPM, F-F Model and rCPM for each task in the
HCP-YA dataset. Tasks whose raw performance exhibited significant correlations with the
cognitive factor score are highlighted in orange. In contrast, tasks that did not show a significant
correlation are highlighted in blue. The COPM demonstrates a notable ability to more accurately
predict behaviors that are highly correlated with the cognitive factor score compared to the F-F
and/or rCPM models. However, for behaviors with weaker correlations, the COPM exhibits a
similar or even opposite prediction pattern. A * indicates that COPM has greater prediction accuracy
than F-F/ rCPM. A + indicates the opposite trend. *<0.05, **<0.01, ***<0.001; +< 0.05; ++<0.01;
+++<0.001; NS = not significant. All the p values are FDR-corrected. See full name of each task in
Table 3.

Table 4 The prediction accuracy of all behaviors for all three models.

Domains	Behavior	Full FC (SD)	rCPM (SD)	COPM (SD)
Executive function	WM Task 2bk Median RT	0.084 (0.044)	0.102 (0.033)	0.137 (0.043)
Emotion	Anger Affect	0.044 (0.044)	0.049 (0.030)	0.028 (0.037)
Emotion	Sadness	0.038(0.043)	0.064 (0.030)	0.024 (0.038)
Emotion	Fear Affect	0.031(0. 038)	0.043 (0. 030)	0.008 (0. 041)
Language	Language Task Story Avg Difficulty	0.189 (0.031)	0.194 (0.029)	0.346 (0.030)
Language	Language Task Story Acc	0.048 (0.046)	0.094 (0.037)	0.136 (0.042)
Language	Language Task Story Median RT	0.095 (0.037)	0.060 (0.034)	0.107 (0.037)
Psychological Well-being	Life Satisfy	0.072 (0.039)	0.060 (0.032)	0.113 (0.034)
Motor	Endurance	0.107 (0.043)	0.130 (0.034)	0.147 (0.043)
Motor	Strength	0.053 (0.041)	0.130 (0.034)	0.055 (0.036)
Motor	Gait Speed COPM	0.046 (0.046)	0.049 (0.034)	0.036 (0.043)
Motor	Dexterity	-0.038 (0.043)	0.009 (0.030)	0.026 (0.041)
Sustained Attention	SCPT TPRT	-0.007 (0.038)	0.071 (0.044)	0.116 (0.040)
Sustained Attention	SCPT SPEC	-0.002 (0.038)	0.019 (0.032)	0.070 (0.038)
Sustained Attention	SCPT SEN	0.020 (0.039)	0.048 (0.028)	0.050 (0.039)
Sustained Attention	SCPT LRNR	-0.005 (0.033)	-0.016 (0.025)	-0.017 (0.030)
Spatial Orientation	VSPLOT OFF	0.221 (0.035)	0.122 (0.035)	0.326 (0.032)
Spatial Orientation	VSPLOT TC	0.194 (0.039)	0.195 (0.031)	0.285 (0.033)
Spatial Orientation	VSPLOT CRTE	0.074 (0.033)	0.090 (0.032)	0.071 (0.041)
Self-Regulation	DDisc AUC 40K	0.217 (0.039)	0.172 (0.033)	0.223 (0.036)
Social Relationship	Rejection	0.023 (0.039)	-0.006 (0.030)	0.019 (0.042)
Social Relationship	Loneliness	-0.005 (0.043)	0.049 (0.033)	-0.009 (0.043)
Social Relationship	Supportive	0.003 (0.041)	-0.005 (0.030)	-0.016 (0.040)
Social Relationship	Perceived Stress	0.036 (0.042)	0.019 (0.032)	0.069 (0.040)
Verbal Episodic Memory	IWRD RTC	-0.048(0.040)	-0.051 (0.031)	0.002 (0.042)

The same edges identified in the HCP-YA dataset also show specificity in predicting cognitive

related functions in the HCP-D dataset

We then validated our findings using the HCP-D dataset. We selected 6 tasks designed to assess

cognitive functions, including executive functions and language abilities, along with 2 tasks aimed

at evaluating motor and emotion function (see Table 1 and Table 2 for detailed descriptions). We

then compared the prediction accuracies across the 2 types of behaviors and the three models. We

found that COPM predicted the performance of cognitive related function tasks with significantly

greater accuracy than those for cognitive less-related functions ($p < 0.001$, Wilcoxon effect size r =

0.868). Within the cognitive related function tasks, the COPM outperformed both the F-F Model

and the rCPM in 5 out of 6 tasks ($p < 0.05$, FDR corrected; see Figure 5 and Table 5). However, for

2 tasks assessing cognitive less-related functions, the prediction accuracies of the COPM, the F-F

Model, and the rCPM were comparable ($p > 0.05$, FDR-corrected; Figure 5 and Table 5).

Figure 5. The prediction accuracy of the COPM, F-F Model and rCPM for each task in the

HCPD dataset. Tasks whose raw performance exhibited significant correlations with the cognitive

factor score in HCP-YA are highlighted in orange. In contrast, tasks that did not show a significant

correlation are highlighted in blue. The COPM demonstrates a notable ability to more accurately

predict behaviors that are highly correlated with the cognitive factor score compared to the F-F

and/or rCPM models. However, for behaviors with weaker correlations, the COPM exhibits a

similar or even opposite prediction pattern. A * indicates that COPM has greater prediction accuracy

than F-F/ rCPM. *<0.05, **<0.01, ***<0.001; +< 0.05; NS = not significant. All the p values are
FDR-corrected.

Tabel 5 The prediction accuracy of all 8 behaviors was assessed using a cross-dataset
prediction paradigm for the three models.

Domains	Behavior	Full FC (SD)	rCPM (SD)	COPM (SD)
Executive function	DCCS	0.036 (0.052)	0.037 (0.052)	0.046 (0.050)
Executive function	Flanker	-0.045 (0.058)	-0.056 (0.057)	0.005 (0.057)
Executive function	Picture sequence memory	0.002(0.054)	0.005 (0.052)	0.024 (0.045)
Executive function	List sorting working memory	0.071(0. 051)	0.065 (0. 053)	0.111 (0. 050)
Language	Picture vocabulary	0.236 (0.040)	0.220 (0.041)	0.267 (0.041)
Language	Oral reading recognition	0.169 (0.051)	0.151 (0.050)	0.186 (0.050)
Emotion	Fear	-0.127 (0.050)	-0.118 (0.050)	-0.123 (0.050)
Motor	Strength	0.025 (0.058)	0.029 (0.056)	0.013 (0.054)

Edges with higher predictive contributions to ontology scores show greater FC variability,

stronger SC, and more similar gene expression profiles.

Subsequently, we explored the biological underpinnings of the top 10% FC edges included in the
COPM. Specifically, we extracted the contribution weights of these edges in predicting the
cognitive factor. These weights indicate each edge's relative importance in the prediction process,
with higher weights suggesting a more significant role in forecasting the cognitive factor score.
We then investigated the relationship between these contribution weights and three key biological
factors: individual variability in FC strength, structural connectivity (SC) strength, and gene
expression similarity profiles. Previous research found the SC-FC coupling across distinct brain
regions supports the cognitive process, and SC–FC coupling is heritable[43], thus, we
hypothesized the edges that made greater contribution when predicting the cognitive factor would
show greater individual variability in FC strength, stronger SC, and more similar gene expression
profiles.

To assess the individual variability of each FC edge, we calculated the ratio of inter-individual
variability to intra-individual variability for each edge. This method helps offset the influence of
FC magnitude on variability assessments, as connectivity strength tends to affect both inter- and
intra-individual variability similarly (i.e., edges with stronger FC typically exhibit greater
variability on both counts). As a result, we generated a symmetrical 400x400 matrix, with each
edge representing inter-individual variability across a cohort of 601 subjects from HCP-YA dataset.
In parallel with FC analysis, we also measured SC strength using diffusion MRI data from the
HCP-YA dataset to create a white matter structural connectivity matrix. We constructed a 400x400
SC matrix for each participant and then computed the average across all participants. Furthermore,
we measured the gene expression similarity profiles using the Allen Human Brain Atlas which is a
transcriptional atlas [44]. This atlas includes gene expression levels measured with DNA
microarray probes and sampled from hundreds of neuroanatomical structures in the left

hemisphere across 4 normal postmortem human brains and bilateral hemisphere across 2

additional human brains (Sunkin et al., 2013; Burt et al., 2018). From these data, we calculated

group-averaged gene expression profiles across 400 cortical areas using Schaefer parcellation

[29].

In our analysis, we focused solely on the edges included in the COPM. For each measurement, we

averaged the estimates both within and between networks to create a network-by-network matrix,

as outlined in the methodologies by Schaefer et al. (2018). We then computed Spearman

correlations to explore the relationship between the contribution weights of these edges and their

corresponding metrics in the three matrices: FC variability, SC strength, and gene expression

profiles. We found that the contribution weights were significantly correlated with the FC

variability (r = 0.96, p < 0.001, FDR corrected), SC strength (r = 0.59, p < 0.001, FDR corrected),

and gene expression profiles (r = 0.54, p = 0.002, FDR corrected). These results indicate that the

edges that made greater contribution when predicting the cognitive factor score also showed

greater variability in FC, stronger SC, and more similar gene expression profiles. As shown in

Figure 6, edges making greater contributions to predicting cognitive factor are mainly located

within the association networks, particularly within the intra- and inter-connections of the Default

mode network (DMN) and Frontal-parietal control network (FPCN).

Figure 6. Edges that made greater contribution when predicting the cognitive factor score

showed greater variability in FC, stronger SC, and more similar gene expression profiles. A,

B, and C show the significant Spearman correlations between the contribution weights of the

edges in predicting the cognitive factor score and their corresponding metrics in the three matrices:

FC variability, structural connectivity strength, and gene expression profiles (p < 0.05,

FDR-corrected).

Our findings are robust when using varied thresholds for edge selection and Glasser atlas

To evaluate the robustness of our results, we experimented with varying thresholds for edge selection within the COPM, alongside using different brain parcellations to delineate functional areas. While our primary analysis focused on the top 10% of edges, we expanded this to include thresholds of 20%, 30%. For each threshold, we predicted task-specific behavioral performance and analyzed the correlation between cognitive loading and prediction accuracy. We consistently observed significant correlations at these extended thresholds (20%: $r = 0.57$, $p = 0.002$; 30%: $r = 0.51$, $p = 0.005$). These results reinforce our initial findings, indicating that tasks with a high correlation to cognitive factor consistently demonstrate enhanced prediction accuracy. This trend persists across various thresholds, suggesting a reliable and accurate representation of cognitive related functions.

Furthermore, we conducted parallel analyses using the rCPM, which selects an equivalent number of edges as the COPM but specifically targets edges associated with each behavior rather than cognitive factor score using multiple linear regression within the CPM framework. Cognitive loading also showed significant correlations with prediction accuracy in the rCPM across the varied thresholds (20%: $r = 0.46$, $p = 0.02$, 30%: $r = 0.46$, $p = 0.02$). However, when directly comparing the 2 models, the correlation between cognitive loading and prediction accuracy was stronger in the COPM than in the rCPM at the 20% and 30% thresholds (20%: $z = 2.50$, $p = 0.01$, 30%: $z = 2.27$, $p = 0.02$). This pattern suggests that the edges selected by the COPM, particularly at lower thresholds, are distinctively associated with the representation of cognitive related functions. Overall, these findings highlight the COPM's effectiveness in utilizing a reduced set of FC edges for more precise predictions related to cognitive factor.

After confirming that our results were not influenced by the threshold used, we replicated our analysis using Glasser atlas (Glasser et al., 2016), applying a 10% threshold. Given the comparable predictive efficiency of the rCPM and the F-F model, and due to computational and time constraints, we limited our analysis to the F-F and COPM when using the Glasser 360 atlas. The FC network built with the Glasser 360 atlas showed moderate predictive accuracy for the cognitive factor factor (R median = 0.29, interquartile range = 0.05).

We observed a significant correlation between cognitive loading and prediction accuracy in the COPM ($r = 0.63$, $p = 0.002$). This finding reinforces our earlier observation: tasks with a closer relationship to the cognitive factor tend to have higher prediction accuracy than those with weaker correlations. Such a correlation was not evident in the F-F model ($r = 0.40$, $p = 0.10$). The stronger correlation in the COPM compared to the F-F model ($z = 2.8814$, $p = 0.004$) further substantiates the notion that specific predictive edges in the COPM are uniquely linked to cognitive related functions, a linkage that remains consistent across different brain atlases. Owing to the limitations in computational resources and time, we did not extend this replication to other thresholds or atlases.

Discussion

This study identified a set of core FC connectomes, predominantly located within the association cortex of the human brain, that represent cognition. Leveraging a novel machine learning framework, the COPM, these core FC connectomes not only predict the cognitive factor score with high accuracy but also efficiently forecast a spectrum of cognitive functions, affirming their applicability across datasets. The core FC connectome edges are characterized by substantial inter-individual variability in FC strength, strong SC, and comparable gene expression patterns. Our findings remained robust across various edge selection thresholds and the application of the Glasser atlas.

Our research not only replicated previous findings on the predictive capacity of FC edges for the cognitive factor [10–12,20] but also expanded them by pinpointing a specific set of FC edges within association cortex networks like the DMN, FPCN, and attention network. This discovery aligns with existing findings on the necessity of coordinated activities across distributed brain regions, primarily within the association cortex, for numerous cognitive functions [6,9,45,46]. Moreover, our findings support the massive redeployment hypothesis [47] suggesting a universal brain region framework underpinning diverse cognitive functions.

We also extended previous findings by exploring the biological foundations of these key edges, encompassing aspects like FC variability, white matter integrity, and gene expression similarity. We observed that these edges exhibit not only a high degree of variability in FC but also strong SC and closely matched gene expression profiles. This increased FC variability suggests a potential for enhanced neural adaptability, providing the neural flexibility needed for various cognitive tasks [40,48]. Such findings highlight the brain's dynamic nature and its capacity for plasticity – the ability to modify connections based on experiences, information, or acquired skills. In line with this, the strength of FC within the executive control network have been shown to be positively correlated with performance in sustained cognitive performance [19,49]. This correlation underscores the importance of these connections in learning and cognitive adaptation. Additionally, the association cortex, known for integrating information across diverse brain areas, plays a vital role in complex cognitive functions like decision-making and problem-solving. This integrative capability may underlie the remarkable cognitive flexibility humans demonstrate, allowing us to respond innovatively and adaptively to a constantly changing environment [46]. The observation that certain FC edges exhibited stronger SC and similar gene expression patterns hints at a genetic foundation for these neural connections. This suggests that genetic factors may influence the formation and maintenance of brain networks, affecting how regions connect and interact, and how they are shaped by experiences [50,51].

A key novelty of our study is the COPM, a cognitive ontology-based machine learning framework. Distinct from traditional approaches that utilize all edges in predicting the cognitive factor, the COPM identifies critical edges that are predictive of the cognitive factor. These selected edges can predict a wide range of cognitive functions, such as executive function, language ability, self-regulation, sustained attention, verbal episodic memory, and spatial orientation, but not motor and emotion functions. This approach holds promise for uncovering robust biomarkers specific to

794 cognitive tasks or impairments, offering potential for refined diagnostic and intervention strategies
795 in clinical contexts [9,33,52,53].
796

Despite its contributions, our study has methodological limitations. Firstly, our analysis of FC
edges' importance relied on linear model's coefficient weights, a technique paralleled in prior
research [17,54–56]. However, this method may not fully capture the significance of FC edges.
Future investigation could explore alternative techniques, such as feature dropout [10]or edge
permutation importance [20], to more accurately evaluate the edges' impact on model performance.
Secondly, while we have established correlations among core FC networks, gene expression
patterns, and cognitive factors, a direct exploration of causality between structural networks, gene
expression and cognitive processes could yield deeper insights into the brain's cognitive
architecture. For example, machine learning algorithms could be applied to multimodal brain
imaging and genetics data to predict cognition scores. Structural equation modeling may also
clarify the directionality of these relationships.

Conclusion

This study identifies and validates a set of functional connectomes within the association cortex that
precisely represents cognition, as evidenced by the COPM. These core connectomes demonstrate
superior predictive accuracy for various cognitive functions, such as working memory, reading
comprehension, and sustained attention, and characterized by significant individual variability in
FC strength, interconnected via white matter tracts, and gene expression similarities.
814

Acknowledgments

The authors thank Hu Chuan Peng for helping with advisement. Funding: STI 2030—Major
Projects 2021ZD0201500 (YD); National Natural Science Foundation of China 31822024 (YD)
and 32300881 (XYW); Strategic Priority Research Program of Chinese Academy of Sciences
XDB32010300 (YD); Scientific Foundation of Institute of Psychology, Chinese Academy of
Sciences E2CX3625CX (Y.D.) and E1CX4725CX (XYW). Data were provided by the Human
Connectome Project, WU-Minn Consortium (Principal Investigators: David Van Essen and Kamil
Ugurbil; 1U54MH091657) funded by the 16 NIH Institutes and Centers that support the NIH
Blueprint for Neuroscience Research; and by the McDonnell Center for Systems Neuroscience at
Washington University. The HCP-Development 2.0 Release data used in this report came from
DOI: 10.15154/1520708. Research reported in this publication was supported by the National
Institute of Mental Health of the National Institutes of Health under Award Number
U01MH109589 and by funds provided by the McDonnell Center for Systems Neuroscience at
Washington University in St. Louis.

Reference

1. Cosmides L, Tooby J. 2013 Evolutionary Psychology: New Perspectives on Cognition and Motivation. *https://doi.org/10.1146/annurev.psych.121208.131628* **64**, 201–229. (doi:10.1146/ANNUREV.PSYCH.121208.131628)

2. Harvey PD. 2019 Domains of cognition and their assessment. *Dialogues Clin Neurosci* **21**, 227–237. (doi:10.31887/DCNS.2019.21.3/PHARVEY)

3. Schöttner M, Bolton TAW, Patel J, Nahálka AT, Vieira S, Hagmann P. 2023 Exploring the latent structure of behavior using the Human Connectome Project's data. *Scientific Reports 2023 13:1* **13**, 1–13. (doi:10.1038/s41598-022-27101-1)

4. Burkart JM, Schubiger MN, Van Schaik CP. 2017 The evolution of general intelligence. (doi:10.1017/S0140525X16000959)

5. McGrew KS. 2009 CHC theory and the human cognitive abilities project: Standing on the shoulders of the giants of psychometric intelligence research. *Intelligence* **37**, 1–10. (doi:10.1016/J.INTELL.2008.08.004)

6. Burgoyne AP, Mashburn CA, Tsukahara JS, Engle RW. 2022 Attention control and process overlap theory: Searching for cognitive processes underpinning the positive manifold. *Intelligence* **91**. (doi:10.1016/j.intell.2022.101629)

7. Murtazina MS, Avdeenko T V. 2021 The constructing of cognitive functions ontology. In *Procedia Computer Science*, pp. 595–602. Elsevier B.V. (doi:10.1016/j.procs.2021.04.181)

8. Poldrack RA, Yarkoni T. 2016 From brain maps to cognitive ontologies: Informatics and the search for mental structure. *Annu Rev Psychol* **67**, 587–612. (doi:10.1146/annurev-psych-122414-033729)

9. Chen J *et al.* 2022 Shared and unique brain network features predict cognitive, personality, and mental health scores in the ABCD study. *Nat Commun* **13**. (doi:10.1038/s41467-022-29766-8)

10. Dubois J, Galdi P, Paul LK, Adolphs R. 2018 A distributed brain network predicts general intelligence from resting-state human neuroimaging data. *Philosophical Transactions of the Royal Society B: Biological Sciences* **373**. (doi:10.1098/RSTB.2017.0284)

11. Kong R *et al.* 2023 Comparison between gradients and parcellations for functional connectivity prediction of behavior. *Neuroimage* **273**. (doi:10.1016/j.neuroimage.2023.120044)

12. Tian Y, Margulies DS, Breakspear M, Zalesky A. 2020 Topographic organization of the human subcortex unveiled with functional connectivity gradients. *Nat Neurosci* **23**, 1421–1432. (doi:10.1038/s41593-020-00711-6)

13. Bolt T, Nomi JS, Thomas Yeo XBT, Lucina X, Uddin Q. 2017 Behavioral/Cognitive Data-Driven Extraction of a Nested Model of Human Brain Function. (doi:10.1523/JNEUROSCI.0323-17.2017)

14. Kristanto D, Liu X, Sommer W, Hildebrandt A, Zhou C. 2022 What do neuroanatomical networks reveal about the ontology of human cognitive abilities? *iScience* **25**. (doi:10.1016/J.ISCI.2022.104706)

15. He T, An L, Chen P, Chen J, Feng J, Bzdok D, Holmes AJ, Eickhoff SB, Yeo BTT. 2022 Meta-matching as a simple framework to translate phenotypic predictive models from big to small data. *Nat Neurosci* **25**, 795–804. (doi:10.1038/s41593-022-01059-9)

16.   Francken JC, Slors M, Craver CF. 2022 Cognitive ontology and the search for neural
mechanisms: three foundational problems. *Synthese* **200**.
(doi:10.1007/s11229-022-03701-2)

17.   Cui Z *et al.* 2020 Individual Variation in Functional Topography of Association Networks in
Youth. *Neuron* **106**, 340-353.e8. (doi:10.1016/j.neuron.2020.01.029)

18.   Gordon EM *et al.* 2020 Default-mode network streams for coupling to language and control
systems. *Proc Natl Acad Sci U S A* **117**, 17308–17319. (doi:10.1073/pnas.2005238117)

19.   He L, Liu W, Zhuang K, Meng J, Qiu J. 2021 Executive function-related functional
connectomes predict intellectual abilities. (doi:10.1016/j.intell.2021.101527)

20.   Tian Y, Zalesky A. 2021 Machine learning prediction of cognition from functional
connectivity: Are feature weights reliable? *Neuroimage* **245**, 118648.
(doi:10.1016/j.neuroimage.2021.118648)

21.   Van Essen DC, Smith SM, Barch DM, Behrens TEJ, Yacoub E, Ugurbil K. 2013 The
WU-Minn Human Connectome Project: An overview. *Neuroimage* **80**, 62–79.
(doi:10.1016/j.neuroimage.2013.05.041)

22.   Somerville LH *et al.* 2018 The Lifespan Human Connectome Project in Development: A
large-scale study of brain connectivity development in 5–21 year olds. *Neuroimage* **183**, 456.
(doi:10.1016/J.NEUROIMAGE.2018.08.050)

23.   Glasser MF *et al.* 2013 The minimal preprocessing pipelines for the Human Connectome
Project. *Neuroimage* **80**, 105–124. (doi:10.1016/j.neuroimage.2013.04.127)

24.   Ciric R *et al.* 2018 Mitigating head motion artifact in functional connectivity MRI. *Nat*
Protoc **13**, 2801–2826. (doi:10.1038/s41596-018-0065-y)

25.   Ciric R *et al.* 2017 Benchmarking of participant-level confound regression strategies for the
control of motion artifact in studies of functional connectivity. *Neuroimage*
(doi:10.1016/j.neuroimage.2017.03.020)

26.   Satterthwaite TD *et al.* 2013 An improved framework for confound regression and filtering
for control of motion artifact in the preprocessing of resting-state functional connectivity
data. *Neuroimage* **64**, 240–256. (doi:10.1016/J.NEUROIMAGE.2012.08.052)

27.   Faskowitz J, Esfahlani FZ, Jo Y, Sporns O, Betzel RF. 2020 Edge-centric functional network
representations of human cerebral cortex reveal overlapping system-level architecture.
Nature Neuroscience 2020 23:12 **23**, 1644–1654. (doi:10.1038/s41593-020-00719-y)

28.   Rosenthal G, Váša F, Griffa A, Hagmann P, Amico E, Goñi J, Avidan G, Sporns O. 2018
Mapping higher-order relations between brain structure and function with embedded vector
representations of connectomes. *Nat Commun* **9**. (doi:10.1038/s41467-018-04614-w)

29.   Schaefer A, Kong R, Gordon EM, Laumann TO, Zuo X-N, Holmes AJ, Eickhoff SB, Yeo
BTT. 2018 Local-Global Parcellation of the Human Cerebral Cortex from Intrinsic
Functional Connectivity MRI. *Cerebral Cortex* **28**, 3095–3114.
(doi:10.1093/CERCOR/BHX179)

30.   Rajamanickam K. 2020 A Mini Review on Different Methods of Functional-MRI Data
Analysis. *Archives of Internal Medicine Research* **03**, 44–60. (doi:10.26502/aimr.0022)

31.   Yoo K, Rosenberg MD, Hsu WT, Zhang S, Li CSR, Scheinost D, Constable RT, Chun MM.
2018 Connectome-based predictive modeling of attention: Comparing different functional
connectivity features and prediction methods across datasets. *Neuroimage* **167**, 11–22.
(doi:10.1016/j.neuroimage.2017.11.010)

32. Finn ES, Shen X, Scheinost D, Rosenberg MD, Huang J, Chun MM, Papademetris X,
Constable RT. 2015 Functional connectome fingerprinting: Identifying individuals using
patterns of brain connectivity. *Nat Neurosci* **18**, 1664–1671. (doi:10.1038/NN.4135)

33. Gholipour T, You X, Stufflebeam SM, Loew M, Koubeissi MZ, Morgan VL, Gaillard WD.
2022 Common functional connectivity alterations in focal epilepsies identified by machine
learning. *Epilepsia* **63**, 629–640. (doi:10.1111/EPI.17160)

34. Kong R *et al.* 2021 Individual-Specific Areal-Level Parcellations Improve Functional
Connectivity Prediction of Behavior. *Cerebral Cortex* **31**, 4477–4500.
(doi:10.1093/cercor/bhab101)

35. Hu L, Bentler PM. 1999 Cutoff criteria for fit indexes in covariance structure analysis:
Conventional criteria versus new alternatives. *Structural Equation Modeling, 6(1), 1–55.*

36. Rosseel Y. 2012 lavaan: An R Package for Structural Equation Modeling. *Journal of*
Statistical Software

37. Cui Z, Gong G. 2018 The effect of machine learning regression algorithms and sample size
on individualized behavioral prediction with functional connectivity features. *Neuroimage*
178, 622–637. (doi:10.1016/J.NEUROIMAGE.2018.06.001)

38. Diedenhofen B, Musch J. 2015 cocor: A Comprehensive Solution for the Statistical
Comparison of Correlations. *PLoS One* **10**, e0121945.
(doi:10.1371/JOURNAL.PONE.0121945)

39. Silver NC, Hittner JB, May K. 2004 Testing Dependent Correlations With Nonoverlapping
Variables: A Monte Carlo Simulation. *The Journal of Experimental Education* **73**, 53–69.
(doi:10.3200/JEXE.71.1.53-70)

40. Yang H *et al.* 2023 Connectional Hierarchy in Human Brain Revealed by Individual
Variability of Functional Network Edges. *bioRxiv* , 2003–2023.

41. Thomas Yeo BT *et al.* 2011 The organization of the human cerebral cortex estimated by
intrinsic functional connectivity. *J Neurophysiol* **106**, 1125–1165.
(doi:10.1152/JN.00338.2011)

42. Glasser MF *et al.* 2017 A multi-modal parcellation of human cerebral cortex Matthew.
Nature **536**, 171–178. (doi:10.1038/nature18933.A)

43. Gu Z, Jamison KW, Sabuncu MR, Kuceyeski A. 2021 Heritability and interindividual
variability of regional structure-function coupling. *Nat Commun* **12**.
(doi:10.1038/s41467-021-25184-4)

44. Sunkin SM, Ng L, Lau C, Dolbeare T, Gilbert TL, Thompson CL, Hawrylycz M, Dang C.
2013 Allen Brain Atlas: An integrated spatio-temporal portal for exploring the central
nervous system. *Nucleic Acids Res* **41**. (doi:10.1093/nar/gks1042)

45. Seeley WW, Menon V, Schatzberg AF, Keller J, Glover GH, Kenna H, Reiss AL, Greicius
MD. 2007 Dissociable intrinsic connectivity networks for salience processing and executive
control. *Journal of Neuroscience* **27**, 2349–2356.
(doi:10.1523/JNEUROSCI.5587-06.2007)

46. Houdé O, Rossi S, Lubin A, Joliot M. 2010 Mapping numerical processing, reading, and
executive functions in the developing brain: an fMRI meta-analysis of 52 studies including
842 children. *Dev Sci* **13**, 876–885. (doi:10.1111/j.1467-7687.2009.00938.x)

47. Anderson ML. 2010 Neural reuse: A fundamental organizational principle of the brain.
Behavioral and Brain Sciences. **33**, 245–266. (doi:10.1017/S0140525X10000853)

48. Mueller S, Wang D, Fox MD, Yeo BTT, Sepulcre J, Sabuncu MR, Shafee R, Lu J, Liu H.
2013 Individual Variability in Functional Connectivity Architecture of the Human Brain.
Neuron **77**, 586–595. (doi:10.1016/j.neuron.2012.12.028)

49. Evers EAT, Klaassen EB, Rombouts SA, Backes WH, Jolles J. 2012 The Effects of
Sustained Cognitive Task Performance on Subsequent Resting State Functional
Connectivity in Healthy Young and Middle-Aged Male Schoolteachers. *Brain Connect* **2**,
102–112. (doi:10.1089/brain.2011.0060)

50. Buckner RL, Krienen FM. 2013 The evolution of distributed association networks in the
human brain. *Trends Cogn Sci* **17**, 648–665. (doi:10.1016/J.TICS.2013.09.017)

51. Wei Y *et al.* 2019 Genetic mapping and evolutionary analysis of human-expanded cognitive
networks. *Nat Commun* **10**. (doi:10.1038/S41467-019-12764-8)

52. Jiang Y, Duan M, Chen X, Chang X, He H, Li YJ, Luo C, Yao D. 2017 Common and distinct
dysfunctional patterns contribute to triple network model in schizophrenia and depression:
A   preliminary   study.   *Prog   Neuropsychopharmacol   Biol   Psychiatry*
(doi:10.1016/j.pnpbp.2017.07.007)

53. Xie C *et al.* 2023 A shared neural basis underlying psychiatric comorbidity. *Nat Med* **29**,
1232–1242. (doi:10.1038/s41591-023-02317-4)

54. Yip SW, Scheinost D, Potenza MN, Carroll KM. 2019 Connectome-based prediction of
cocaine   abstinence.   *American   Journal   of   Psychiatry*   **176**,   156–164.
(doi:10.1176/appi.ajp.2018.17101147)

55. Cui Z, Su M, Li L, Shu H, Gong G. 2018 Individualized Prediction of Reading
Comprehension Ability Using Gray Matter Volume. *Cerebral Cortex* **28**, 1656–1672.
(doi:10.1093/CERCOR/BHX061)

56. Gong Q, Li L, Du M, Pettersson-Yeo W, Crossley N, Yang X, Li J, Huang X, Mechelli A.
2014 Quantitative prediction of individual psychopathology in trauma survivors using
resting-state fMRI. *Neuropsychopharmacology* **39**, 681–687. (doi:10.1038/NPP.2013.251)

986