Gossamer: Scaling Image Processing and Reconstruction to Whole Brains

Karl Marrett*†, Keivan Moradi*, Chris Sin Park, Ming Yan, Chris Choi, Muye Zhu, Masood Akram, Sumit Nanda, Qing Xue, Hyun-Seung Mun, Adriana Gutierez, Mitchell Rudd, Brian Zingg, Gabrielle Magat, Kathleen Wijaya, Hongwei Dong‡, X. William Yang and Jason Cong
Department of Computer Science, School of Medicine, University of California Los Angeles
Email: †kdmarrett@cs.ucla.edu, ‡HongWeiD@mednet.ucla.edu

Abstract—Neuronal reconstruction–a process that transforms image volumes into 3D geometries and skeletons of cells–bottlenecks the study of brain function, connectomics and pathology. Unlike artistic domains with similar challenges (e.g., hair modeling), scientists need *exact* and *complete* segmentations to study subtle topological differences. Existing methods are disk-bound, dense-access, coupled, single-threaded, algorithmically unscalable and require manual cropping of small windows and proofreading of skeletons due to low topological accuracy. Designing a data-intensive parallel solution suited to a neurons' shape, topology and far-ranging connectivity is particularly challenging due to I/O and load-balance, yet by abstracting vision tasks such as segmentation and skeletonization into strategically ordered specializations of search, we progressively lower memory by 4 orders of magnitude. This enables 1 mouse brain to be fully processed in-memory on a single server, at $67\times$ the scale with $870\times$ less memory while having 78% higher automated yield than the highest performing alternative methods.

I. INTRODUCTION

Lightsheet microscopy [34] has reached a maturity that it can digitize whole mouse brains in 1 day and produce terabytes of data that require image processing and reconstruction (Figure 1). Unfortunately, these new datasets, at baseline, have marginal value since they lack quality and semantics. How do we future-proof software design against the increasing scale of unstructured data to derive meaningful 3D assets? We offer an application that can efficiently transform large-scale volumes into relatively accurate models for analysis.

Intelligent systems (e.g., biological brains, computer microprocessors) have inherent long-range context that benefits from reconstructing as a complete whole. However, existing methodologies can not scale to modern data sizes; we test up to 30 TB raw inputs for this study. Unstructured data has a larger memory footprint and necessitates further computation to extract a useful representation, yet data bandwidth is a bottleneck across all parts of the modern computing infrastructure stack. This makes distributed or cloud strategies impractical, suggesting instead an edge computing approach. Therefore, our design proposes a single system composed of 1 microscope and 1 workstation processing a single brain at a time. This is feasible because a single modern server can have terabytes of memory and multiple CPUs and GPUs with hundreds of cores. Our system can efficiently process or reconstruct a whole brain

in a similar time that it takes to image or transfer to the cloud (about 4 days each).

Lack of large labeled datasets of 3D geometries is also an issue in the broader graphics community but this need is more acute in science. For researchers to take advantage of recent data-driven and supervised methods they need highly specific, often novel, training labels tailored to new scientific queries. A further complication is that, unlike artistic workflows, accuracy is paramount. Neuroscientists will go to great lengths to ensure that acquired data reflects ground truth exactly before using it for scientific analysis since experimental differences can be incredibly subtle. Transforming automated but inaccurate labels into fully correct ones, which we refer to as *proofreading*, is a time-consuming interactive human-led process. Understandably, this creates a bottleneck where acquiring the numerous proofread samples required for statistical significance prolongs project iteration time.

Neuroscience has a long-standing problem in reconstruction which involves (1) image processing and encoding (2) segmenting cell bodies (seeds) (3) segmenting long-range branches and (4) transforming into *curve skeletons* [15]. Morphology, the 3D shape of semantic objects like neurons, and topology, the arrangement, coverage and connectivity, may be a contributing facet in the study of function, pathology and cell type [43]. *Reconstruction*, a common method of studying neuronal morphology, is a process in which fluorescently labeled cells in 3D images are segmented and compacted into ball and stick models (skeletons) [12]. Skeletons are uniquely useful in shape analysis as they imply both topological and morphological features. Recent reviews in neuroscience identified that a scalable [3], comprehensive application [25] for single-cell reconstruction is the greatest need of the community.

Gossamer is an end-to-end pipeline for image processing and reconstruction of lightsheet images with several unique advancements.

1) We introduce several novel 3D and adaptive methods and accomplish enhancement, artifact removal, segmentation and reconstruction of high-scale images.

2) We achieve state-of-the-art (SOTA) performance in space and time even when compared to the equivalent 2D SOTA via linear complexity algorithms, which is critical for rhizomatic structures (neurons) that are power-law in size.

---

*These authors contributed equally to this work

Fig. 1. Whole-brain lightsheet data. (a) Data acquisition and processing pipeline. (b) A sample mouse brain before and after tissue clearing. (c) Since the field of view of the microscope is limited and cannot cover the entire brain in one scan lightsheet data is in the form of a 2D image series that form 3D tiles. (d) Image stitching is needed to make a whole-brain image. (e) A 3D rendering of the image (black and white) and some of the reconstructed neurons (colored part) that shows the scale of the problem.

3) We advance spatially sparse methodologies to enable the long-range contexts inherent in neuroscience to be computed entirely in-memory on a single workstation.

4) Across many of our workloads, we have the first hardware-accelerated and parallel implementations for multi-GPU or multi-core environments.

5) We enable efficient scaling to whole brain volumes ($13000 \times 13000 \times 16000$ voxels), a $67\times$ end-to-end size increase over comparative algorithms.

II. BACKGROUND AND RELATED WORK

Alternative methods fall short in these critical areas which leads to severe losses in automation, yield, performance and accuracy.

A. Lightsheet imaging data

Raw lightsheet data consists of 3D tiles that must be preprocessed to remove camera artifacts, stitched together to form a whole volume, and post-processed to normalize pixel intensity (brightness) and refine the resolution. There are three major sources of non-uniformity in image brightness [31]: (1) some CMOS cameras have midline artifacts that produce a vertical artifact in the center of each tile. On the horizontal axis, there are also horizontal non-uniformities in brightness; (2) some objects in the tissue can partially block the passage of laser light creating horizontal shadows, i.e. *stripes*; (3) repeated imaging of areas desaturates the brightness unevenly referred to as *image bleaching*.

It is better to address CMOS artifacts, shadows and inherent image noise before stitching the image tiles to form a whole volume since these issues are confined to each tile, the computational cost is higher after stitching, and correcting them can improve automated alignment of tiles. However, correcting image bleaching after stitching is preferred since it benefits from a wider view of the whole brain image. Lightsheet, like other light microscopy forms, suffers from a lower resolution and a blur of signal on the z-axis. Deconvolution not only mitigates this issue but also increases foreground signal brightness. By addressing global image normalization and enhancing the foreground signal, a simple thresholding algorithm can segment the image (Figure 3a). Although there is existing software that can function at smaller scales [35][9][8], we are not aware of a complete software pipeline that can operate at the same scale as modern lightsheet microscopy.

B. Seed segmentation

Segmentation paints pixels of an image that belong to classes with a known meaning, for example, cell bodies. These filled regions can also be broken into instances, separated by occurrence in the volume. Neural network models that leverage convolution like U-net [32] are adept at these tasks at small scales. They also are linear time complexity but have poor runtime and high resource usage due to their space complexity which is on the order of the whole working set (W).

C. Cell segmentation

Voxel grid techniques are particularly effective on thin or intricate filament-like signals whereas existing neural methods have poor topological accuracy. Due to limitations in existing tools for proofreading, an automated segmentation technique is discarded if the frequency or severity of several iconic errors is high. We refer to the rate of adequately accurate outputs as the *automated yield*.

We categorize relevant issues into semantics, morphology and topology. *Semantics* relates to errors in the detection or classification of domain-specific structures. *Morphology*

Fig. 2.

level such as artifacts, thresholding, normalization, pixel-level noise and anisotropic blurring. Neural network approaches tend to have a low-frequency bias and regularization techniques tend to increase dimensional blur instead of correcting for it as demonstrated in NeAT [33]. Neural functions also tend to lack continuity on thin signals as mitigated by Lipschitz regularization [23]. Additionally, CNNs can be prone to oversegmentation and path collisions since there is not an adequate loss for the topological effects of detection. For example, though less fine than neurons, the thin struts of chairs in ShapeNet [13] often create collisions and breaks.

Our work expands upon the design philosophy of OpenVDB [28] which provides methods and data structure for voxel grids. The OpenVDB library takes problem domains from dense volumes (W) into sparse working sets (W_s), generally represented as level set surfaces known as VDB grids. Much of the advantages of voxel grids–an almost infinite domain size and lower computation and memory–stems from their innate concept of an active foreground set. However, its major drawback is that the provided sparse methods generally operate on the *entire* sparse working set (W_s) unnecessarily. For medical imaging volumes such as brains, these methods would consume an estimated 40 TB of peak RAM which is currently beyond what is feasible on a single workstation.

D. Skeletonization

We abstract segmentations into ball (with radii) and stick (connections) models see Figure 1. This is useful for (1) efficient proofreading and interaction with labels and (2) analysis of morphological and topological features and errors. Neuroscientists primarily model cells and their topological branching patterns with these skeletal graphs. More specifically, they use *trees*: each node in the graph has a single unidirectional edge which traces a path back to the tree's seed (the cell body) [12].

This process is bottlenecked by scalability because of entrenched domain-specific methods. Scan and select patterns offer a neuron reconstruction method that is fully parallel, hardware-aware and entirely in-memory. We intentionally implement it for a single workstation, as that could allow for the application to be deployed on the same microscope computer that acquires raw images. For massively compressive pipelines such as this, we advocate for computation on the *edge* as opposed to *distributed* due to the prohibitive network cost of the latter.

There are hundreds of semi-automated (requiring human correction) implementations specialized for neuronal reconstruction [1, 25]. However, these methods lack *scalability*– the ability to handle large image regions. This limits their usage to (1) neuron types that are highly localized, (2) small hand-cropped volume sizes, and (3) neurons with little or no collisions. To our knowledge, there is no other method for reconstruction that does not either manually or automatically crop the neurons arbitrarily for performance reasons. If these alternative methods did not do so, neurons with collisions would be lost due to timeout or excessive reconstruction

refers to errors in surface reconstruction such as breaks, collisions or other unfaithful aspects of the segmented region. *Topology* describes errors in the automatically reconstructed tree graphs when compared to their ground truth skeletons. Curve skeletons reveal both morphological and topological details of objects.

In this work, there are only 2 semantic categories: cell bodies (shown in green) and branches (blue) as illustrated in Figure 2. Cell bodies, also known as *somas*, are the root of a neuron's branching projections. Due to their importance in neuronal reconstruction, it is clear that somas are natural *seeds* (the starting set) in the search for all connected branches. Semantic classification and morphological segmentation can be evaluated with established metrics such as recall and precision which report rates of false negatives and false positives respectively.

Tree topological errors are more nebulous and usually have an upstream cause from the segmentation input to skeletonization. *Path breaks* are false discontinuities in the segmented branches of cells. In contrast, over-segmentation leads to *path collisions*–the incorrect joining of disconnected branches or neuronal paths, which are biologically infeasible. Collisions can either be *intra* (within) or *inter* (between) neurons; both manifest as topological errors. Collisions between neurons are particularly harmful because they can create connected segmentations, erroneously including dozens or hundreds of other nearby cells. Lowering the chemical labeling to prevent such clusters would lower the reconstructable neuron yield per animal, thus methods must be scalable to handle this inevitable power-law distribution (see Results sections).

Poor accuracy can also arise from problems at the image

time. The majority of other algorithms also operate in 2D due to runtime concerns and maintain both a heavy object-oriented view of the data while also consulting the dense representations of the image volume. This coupling results in extremely high memory footprints and low arithmetic intensity as we demonstrate in Section V. Enabling full concurrency and exploiting the cache hierarchy through causal and spatial sparsity nullifies these issues, but only if every working set can fit entirely in memory (see Section V-A for the specifics of our system).

Based on benchmarks comparing numerous neuron reconstruction methods [42][26], APP2 has the lowest runtime and resource usage and the best algorithmic complexity. APP2 also placed in the top 5 highest accuracies, with Neutube [17] placing first in [42]. Neutube [17] as well as many high-performing reconstruction methods [4] employ a fastmarching algorithm similar to APP2. Such methods are all of $O(nlogn)$ complexity. As mentioned because of excessive runtimes, a common practice is to manually crop around a neuron which can create cutoffs, artifacts, and intensive human intervention. For example, a recent prepublication [24] with similar pipeline goals only allows a maximum crop size of $512 \times 512 \times 256$ and applies APP2 on these crops due to performance constraints. Such small sizes are only suitable for a subset of neuron types. APP2, like other available iterative reconstruction methods, is only single-threaded. This is why large-scale applications must start multiple APP2 programs for each seed to enable some concurrency [21]. We compare to APP2 for performance and accuracy metrics.

E. Application Pipeline

Neuroscience data sizes tend to increase at the rate of $1000 \times$ every 4 years. This explosion in the acquisition of unstructured data creates problems which we explore below.

As shown in Table 1, Mouselight [40] is an interactive visualizer of large volumes. Its respective memory footprint reflects the dense volumes size of the images we tested. It relies on a human-guided tracing of neurons which takes several hours per neuron. APP2 [41] reflects the max sizes we could complete on a 4 TB system with our application (in single threaded mode) to auto-crop the region to its bounding box. The commercial software Imaris has an alternate cropping feature but the process is manual per neuron and also fails on images this size. Our method, APP2 and an APP2 based pipeline [24] all trace neuron branches automatically, though they need subsequent proofreading.

Applications in this space offer features in the categories of *creation*, *mastery* and *distribution*[19].

Creation. This involves tools for generating, editing or authoring assets. Much like the autonomous driving space, in microscopy, large-scale noisy 3D volumes are plentiful yet instance-level models (neurons), especially those that are corrected and labeled by type are limited. The diversity and uniqueness of scientific queries similar to artistic endeavors

TABLE I
WE COMPARE THE MAXIMUM SCALE ALLOWED FOR A SINGLE NEURON AND THE MEMORY COST ASSOCIATED (RAM) TO 3 MAJOR RELATED WORKS. OUR METHOD IS $67\times$ LARGER IN SCALE WITH $870\times$ LESS MEMORY THAN APP2 WHICH IS THE MOST EFFICIENT ALTERNATIVE AUTOMATED APPROACH.

Work	Max. neuron	Auto	Mem. GB
SEU pipeline [24]	$512 \times 512 \times 256$	✓	11
APP2 [41]	$3788 \times 5380 \times 1995$	✓	2609
Mouselight [40]	$13000 \times 13000 \times 16000$		2704
Ours	$13000 \times 13000 \times 16000$	✓	3

makes creating specific data even more valuable. We contribute an application that creates a variety of 3D representations. From raw images, we improve image quality, segment cells and output volumes, 3D models (meshes), skeletons and training labels (image window crops). We also provide the test suite *TreeBench* to establish the accuracy of these 3D assets. We rely on the existing tools Neutube[17], Fast Neurite Tracer (FNT)[18], and TeraFly[11]. All of these are volume-rendering GUI tools for either (1) proofreading our automated outputs or (2) creating neuron skeletons or seed labels from scratch (in the case of inadequate skeletal accuracy).

Mastery. This relates to utilities that facilitate discovery, search, reuse and understanding of data. Solving issues in scale brings new problems in the management of numerous outputs. Due to operating on whole brains, we generate hundreds of automated reconstructions per brain. As a result of their multiplicity, these reconstructions have diminishing marginal value unless they are automatically sorted according to their quality which has become untenable to do manually. We filter and tag outputs automatically based on quality.

In the creation of neurons, we use low-bias unsupervised techniques. Our aims are minimal: we seek that paths are continuous, do not collide and do not have unfaithful mutations. Generic transformations are more adaptable because the scientific study of morphological differences is subtle and can be corrupted by the influence of out-of-distribution training data. This allows the outputs to be generic and therefore more likely to be candidates for reuse in future scientific queries. Finally, a semantic understanding of cell bodies and their branches allows automatic tagging and labeling of images. This automation can help bootstrap future methods and more specialized experiments on unforeseen data types.

Distribution. Contributions in this category aid the dissemination and sharing of assets between groups. Mouse brain volumes are on the scale of several terabytes, thus sharing and storage are problematic. Since our end-to-end application is essentially domain-specific compression, whole brains have extremely low memory footprint representations (¡2 GBs) which can be output at various stages, resumed and shared across computers or teams easily. We apply strict final passes of the skeletons to adhere to the community standards established in StdSwc[5]. This allows interoperability with outside or legacy tools and is a requirement before it can be added to the community database NeuroMorpho.org[2].

III. Method

Computer vision tasks involving 3D geometry or volumetric data should leverage not only *spatial* but also *causal* sparsity. *Spatial sparsity* reduces computational demands by exploiting local structures in data. Segmented regions and their values, for example, tend to be spatially coherent within various scales. Languages [20], libraries [28] or applications [27] that leverage patterns in spatial distribution are an increasing necessity on simulations at scale.

Causal sparsity further decreases resource usage by dynamically growing a smaller working set as needed from key salient structures or regions. We term the set of these key features or elements *seeds* and refer to them as $\{S\}$. This approach separates a large-scene into *object-level* tasks where instance-level computation can exploit more temporal locality. Spatial and causal sparsity complement each other. Not only can they share data representations, but their locally restricted access and search patterns can offer best-in-class performance.

The core of our method can be broken down into 3 specializations of search:

1) W_s *scan:* traverse a dense working set W such as an image volume and choose a semantic subset W_s.
2) $\{S\}$ *scan:* find key elements termed seeds $\{S\}$ within W_s.
3) W_c *select:* iteratively apply a recurrence relation from $\{S\}$ to select a causally sparse working set W_c as needed.

These patterns are particularly effective on data-intensive parallel applications. For example, this combination of spatial and causal sparsity dramatically increases the image scale that can be processed on a single workstation. In the context of this manuscript, the dense 3D cube (the whole image) is the original working set W. The labeled region in white is the spatial sparse working set W_s. The colored regions are the cell segmentations that specify a causally sparse working set W_c. Refer to Table IV for the element count reductions. W, W_s and W_c are three views of the same data. Their successively smaller element counts lead to empirical performance gains. Problems, especially those arising from natural data, often start with a dense working set W that can be compacted to a spatially sparse working set W_s. W_s represents a set of relevant elements narrowed *spatially*, whereas W_c is the often much smaller dynamic set of values derived from *causal* selection. W_s scan can also minimize the representation or place it in a specialized data structure to suit later computation. Selective search allows algorithms to terminate early, thereby preventing unnecessary accesses and computation (i.e., $O(W_c)$ as opposed to $O(W_s)$). For example, if regions of an image are not reachable from a seed and thus not *causally* linked then they are ignored (see the connectivity of the diagram in Figure 1).

In this work, our example scan and select functions are of linear complexity which is essential for problem sizes with power-law distribution in scale. Scans are trivially paralleliz-

TABLE II
SINCE EACH STAGE PROGRESSIVELY SHRINKS THE WORKING SET, W, W_s AND W_c TAKE ON DIFFERENT MEANINGS AT EACH STAGE. THE DERIVED OUTPUTS OF ONE STAGE ARE OFTEN THE INPUTS TO A LATER STAGE.

	W	W_s	W_c
Encoding	image	foreground	-
Seed	foreground	surface	{S} surface
Cell	-	{S} surf. & foreground	reach. surf.
Skeleton	reach. surf	coarse mesh	local separator

able and are generally decomposed spatially, whereas selection is iterative but parallelizable across seeds.

Narrowing the working set is effective across varied graphics methods because data is often relevant mainly in contextual relation to seeds. This relevance can often be decomposed into a chain of computations leading back to a seed. Therefore, exploiting causality involves identifying seeds and allocating or weighting resources and computation according to their seed relation.

IV. Implementation

We abstract an emerging design pattern and apply it individually, on 4 example computer vision workloads, and in combination with a challenging application. Each example workload described below can be broken into scans and selections. At a more abstract level, each workload itself is analogous to one of these patterns, especially when viewed in a feedforward pipeline. Encoding is analogous to a W scan, seed segmentation to a $\{S\}$ scan, cell segmentation, a W_c selection and skeletonization, a W_s scan.

A. Encoding

Image processing enhances the image. This allows continuing with a far more minimal view of the image while still retaining the structures of interest.

1) *W scan:* Destriping applies a 2D Gaussian and custom filters to remove camera artifacts and fine non-uniformities in the image tiles.
2) *W scan:* Debleaching removes coarse non-uniformities in the stitched image.
3) *W scan:* Deconvolving improves the axial resolution and improve the brightness of the foreground signal.
4) W_s *scan:* Conversion traverses the image volume, placing voxels above a value in a spatially sparse data structure (VDB). W_s is the segmented mask of the image which holds all foreground voxels.

Destriping: Using 2D wavelet decomposition, the image is decomposed into horizontal, vertical and diagonal coefficients. The horizontal and optionally vertical coefficients are decomposed with 1D Fourier transform on the appropriate axes. The Fourier transforms are multiplied to a Gaussian notch filer with a desired sigma. Finally, using inverse Fourier transform and 2D wavelet recomposition the image is reconstructed.

Debleaching: First, the stitched image is destriped bidirectionally to correct regions that are directly bleached by the

Fig. 3. Detailed data processing pipeline towards the reconstruction: (a) We suggest a specific order in which the data needs to be processed to improve the quality of reconstructions. (b) Gossamer pipeline produces a wide variety of outputs for different needs. (c) A sample reconstructed cell that is visualized in neuTube software and is ready for human validation.

laser beam. Finally, a low-pass filter is applied to the image in order to capture the gradual change in the brightness of the background from the surface of the brain to its center that happens because of poor penetration of laser light. The image is divided by the filter to reverse the bleaching.

Deconvolution: In lightsheet microscopy, the image of a sphere appears convolved by an ellipsoid kernel. By knowing the kernel shape, the original shape of the object can be restored via inverse convolution operation.

Conversion: Due to the substantial increase in signal to noise ratio from the previous steps the image can be segmented by keeping pixels with sufficiently high intensity (brightness). To make conversion more robust across different brains, we use a default desired foreground percent and compute a hard threshold value that most closely matches the foreground percent. We do so with quicksort, the only place in the pipeline outside of the skeleton standardization passes that is not of linear algorithmic complexity.

1) Parallel Implementation and Software Pipeline: Scan steps are embarrassingly parallel in nature. All stages at the encoding level must operate on the extreme size of the dense

W volume (see Tables II and IV). Therefore, we parallelized all W scan steps across multiple GPUs and CPU cores and in so doing developed several programs with significant advancements in scalability.

1) We implemented a multi-GPU accelerated version of Pystripe [35] that has a novel bidirectional destriping and Gaussian denoising algorithm as well as a faster parallel processing model.
2) Our software offers a multi-GPU accelerated version of TeraStitcher [9] image stitching software.
3) We developed a multi-GPU and parallel version of LsDeconvolve [8] – an open-source program for the deconvolution of lightsheet microscope images.
4) `process_images.py` is a script that automates the stitching process.
5) `conver.py`, is a high-scale parallel file conversion tool for the various formats shown in Figure 3b.
6) The FNT cube processor program can apply the destriping algorithm on the z-axis of FNT files.

Our conversion tool can read Imaris files, 2D TIF series, or XML output of Terastitcher to convert them to processed

2D TIF series, Imaris, TeraFly, FNT or MP4 video while applying the above-mentioned filters (destriping, bleach correction, baseline and background subtraction, 16-bit to 8-bit conversion), or resizing or downsampling images to a desired isotropic voxel size. Our stitching implementation can also optionally apply a destriping algorithm, a low-pass filter to the stitched image to remove coarse bleaching artifacts and can downsample the data. Finally, all the above-mentioned image processing tools are in-memory to reduce IO overhead and also have resume support and advanced error-handling mechanisms to reduce day-to-day operational challenges. See supplementary notes 1 to 8 for more information.

B. Seed segmentation

It is critical to first detect cell bodies (*seeds*, shown in green below) from brain images (black and white grid) to further segment each neuron's connected branches. We do so with the following steps:

1) $\{S\}$ *scan:* convert the segmented mask VDB from the previous thresholding step into a VDB which stores voxels only at the surface of the foreground W_s. $\{S\}$ is then the surface voxels of W_s.
2) W_c *select:* seeds are segmented by successive region growing steps outwards and inwards from $\{S\}$. W_c is the resulting segmented cell body surfaces.

Cell bodies are large and spherical and can therefore be segmented with the morphological operations of closing and opening. The images are chemically labeled only on the cell surface resulting from the usage of a novel genetic technique specially designed to improve reconstruction on thin, fine-grained structures, thereby improving long-range neuronal reconstruction. Since the signal inherently describes *shells* [38], it lends itself naturally to the sparse level set methods provided in [28] which our application exploits effectively. To fill hollow cell bodies we perform morphological dilation. Since dilation expands the sizes of signals we apply equal and opposite erosion. Together this is known as morphological *closing*. To remove the cell branches which are thin and tubular we employ erosion followed by an equal amount of dilation, which is referred to as *opening*. This recovers seed regions whose geometries are relatively unchanged. Refer to the grid diagrams of Figure 1. The output of seed segmentation is the green regions. We use a single-threaded implementation of connected component analysis provided by the OpenVDB library to separate all somas into a set of instances.

C. Cell segmentation

We can segment entire cells by computing reachability (blue regions below) from the known cell bodies (green) detected in the previous step (i.e., $\{S\}$) with:

1) W_c *select:* from cell body surfaces, apply region growing outwards by consulting W_s–the segmented image mask to calculate distance to a cell surface. This yields a reachability segmentation W_c.

ALGORITHM 1: Seed segmentation

```
1  Function seed_segment(Ws)
      Input: Mask VDB Ws
      Output: Mask VDB Ws with located and filled somas
2      // Convert mask to surface (level set)
3      Ws = convert_to_ls(Ws)
4      // closes hollow cell bodies
          morphologically
5      Ws = close(Ws)
6      // removes branches by opening
7      {S} = open(Ws)
8      // only cell surfaces remain
9      return {S}
```

---

2) W_s *scan:* traverse the grid to prune voxels whose values indicate unreachability. The kept voxels with a valid reachable distance compose a new W_s.
3) W_c *select:* from the new W_s, separate disjoint cells in a connected component analysis. This yields all instance segmentation surfaces separated into individual neurons.

We apply the fastsweeping implementation in [29], but rather than use it globally we start it from the key semantic areas of interest: the cell bodies from the previous step. Fastsweeping is generally applied on dense 2D or 3D regions (i.e., W). The VDB library improves on this with a sophisticated sparse implementation. This is a key advantage to VDB's sparse methods, although one can have an almost infinite domain size, performance costs only reflect the sparse voxel count W_s. However, when W_s is still too high, as in our case, application on all of W_s is a drawback. Instead, we start the selective search only from known cell bodies. This further improves performance and reduces peak memory usage since only the reachable voxels (e.g., W_c) are accessed during the W_c select. Table IV lists the difference between W_s and W_c which indicates the reduction in computation and memory of our approach. In addition to an implied contiguity (reachability), fastsweeping also computes a maximum distance from any cell body surface. This is employed to finally prune the voxels that have a default (maximum distance) value. Although this approach still entails a final prune over all of W_s, pruning is a scan which, unlike fastsweeping's selective search, has perfect parallellizabilty and minimal computation and memory requirements.

During segmentation, we also optionally employ morphological closing of the branches. Whereas the foreground percent parameter merely keeps or rejects different values in the image, closing is a rather biased mutation of the morphology. In theory, it mitigates path breaks at the cost of path collisions, a relationship we explore in the results. A higher foreground percentage may be preferable for faithful surface reconstructions however closing is tested as an alternative method to keep the global W_s low.

D. Skeletonization

Skeletonization of the segmented cells creates a compact ball and stick representation–a spatially embedded graph with

ALGORITHM 2: Cell segmentation

```
1 Function cell_segment(W_s, {S})
        Input: Mask VDB W_s and the set of cell body surfaces
               {S}
        Output: The set of connected components {C} of
               neuron cluster surfaces
2      // morphologically close the branch
         topology
3      W_s = close(W_s)
4      // find all reachable voxels from cell
         surfaces
5      W_c = fastsweeping(W_s, {S})
6      // separate into contiguous components
7      {C} = connected_components(W_c)
8      // yield set of neuron (cluster)
         surfaces
9      return {C}
```

radii information. Reference [15] gives a formal definition of *curve skeletons*. This allows neuroscientists to effectively study topological features. We do so via:

1) W_s *scan:* traverse the set of surface voxels and create W_s–the spatially sparse mesh that retains topology.
2) $\{S\}$ *scan:* choose a set of seeds randomly from W_s.
3) W_c *select:* from each seed, iteratively search for a separator by expanding a sphere and adding encompassed vertices.

We follow the local separators (LS) skeletonization technique [6][7] but add an initial W_s scan to prevent high runtime at high resolutions. Due to multi-level coarsening of the surface mesh and projection as explained in [7], skeletonization achieves $O(n)$ complexity. LS is particularly scalable on tubular signals especially with mesh (surface) representation–a volumetric representation would have less favorable performance.

LS can recover all, even small and highly fine-grained, protuberances which is either a benefit or a negative for brain research. In switching to a 3D surface representation, we find that neurons have small spines and projections on the surface. These details are often not visible in existing volume rendering tools unless the volume is binarized and projected in 2D. Since neuroscientists historically are only interested in the broader topology of branches and not surface features we remove these before skeletonization via, an optional, surface smoothing of the mesh. Since this mesh pre-coarsening step has the added benefit of a net gain in speed (about 44×), it follows that we use the simple and fast *light-edge matching* approach which is also employed in the LS work. This method guarantees not to introduce new path breaks or path collisions (constant number of connected components), but can produce artifacts related to smoothing. It operates by a user-specified number (coarsen steps) of successive linear scans.

Mesh coarsening allows us to reconstruct only the desired topology of neurons while remaining accurate and performant regardless of the resolution of the image. Higher resolutions benefit further, therefore coarsening steps is a runtime parame-

ter determined by default by the image's voxel size. APP2 does not use a mesh intermediate representation which makes its performance and resource usage highly sensitive to resolution.

ALGORITHM 3: Skeletonization

```
1 Function cell_segment(W_s, {S})
        Input: The set of connected components {C} of neuron
               cluster surfaces
        Output: The set of tree skeletons {T} rooted at each
               seed S
2      parallel for C ∈{C}
3          // convert voxel-based surface into
             tri-mesh
4          W_s = surface_to_mesh(C)
5          // smooth surface of mesh by
             lowering resolution
6          W_s = light_edge_match(W_s)
7          // search for local separators
8          parallel for LS_i in {LS}
9              LS_i = select_local_separator(W_s)
10         // choose a subset via weighted set
             packing
11         {LS} = weighted_set_packing({LS})
12         // trees set rooted at each seed via
             BFS
13         {T} = breadth_first_search({LS})
14         // transform tree to adhere to
             quality standards
15         {T} = standardize({T})
16     // yield the set of skeleton trees
17     return {T}
```

V. EXPERIMENTS AND RESULTS

A. Data, Setup and Code Availability

For these workloads, we recommend a single workstation with 2× AMD EPYC 7763 (128 cores/ 256 threads) CPUs, 4 TB RAM and 8× A100 GPUs. The large memory capacity allows data sizes of 1 whole mouse brain at 1um^3 resolution to be processed entirely in-memory for all tasks. We also test an equivalently sized volume at the higher .4um^3 resolution to test accuracy effects. The 1um^3 brain has 374 gold-standard neurons of a variety of neuron types with which to compare. Some with far-reaching branches that span a large portion of the volume. In contrast, the 181 labeled neurons used for the .4um^3 dataset are local and bush-like which allows us to compare to APP2. Both image volume dimensions are approximately 13000×13000×16000 voxels, thus the higher resolution image only captures approximately half of a brain.

We manually proofread all our automated outputs twice using Neutube [17] or Fast Neurite Tracer (FNT) [18] to establish our ground truth skeletons for comparison. We embed an APP2 implementation into our codebase to lend it automated seed segmentation and windowing around the neuron for a fair comparison. We also supply APP2 with our foreground percent algorithm since its native segmentation method, a raw background threshold value, fails completely.

We tested various foreground percentages with TreeBench and found metrics tend to peak around .8%. Unfortunately

APP2 can only complete a single neuron (the smallest one) at this density, therefore all APP2 runs are all at .4%. These parameter choices illustrate how entangled performance and accuracy is for poor scalability algorithms. Code for the reconstruction and image preprocessing pipeline is available at https://github.com/UCLA-VAST/recut and https://github.com/ucla-brain/image-preprocessing-pipeline respectively.

B. Encoding

1) Empirical scalability and performance: For our images, destriping and debleaching take about a half a day to complete. Deconvolution's runtime is also about a half day. As illustrated in Figure 5, conversion of the dense image W to the spatially sparse VDB representation W_s takes 15.5 hours on a single core and 21 minutes on 128 cores, which is about a 44× increase in speed. Before the VDB conversion the working set was over 3 orders of magnitude larger than the spatially sparse working set W_s used for the remainder of seed segmentation (Table IV).

On a Windows workstation equipped with 2x Quadro RTX A6000 GPUs and 2x Xeon Platinum 8260 CPUs, GPU acceleration improved the destriping speed from 10 image/s to 73 images/s in our testing.

2) Accuracy: We test the efficacy of preprocessing steps in 3 ways. We confirm qualitatively that known artifacts are removed after each stage (top row in Figure 1). Compressibility is a proxy for signal-to-noise ratio. Figure 2 shows that each stage other than deconvolution improves the compaction ratio of the image. Deconvolution sharpens the image which can exacerbate high frequency noise or surface details hence the slight increase in size. Finally, we test each stage with respect to reconstruction accuracy as discussed in Table 8 and the ablations section.

C. Seed segmentation

1) Empirical scalability and performance: When fully parallelized, seed segmentation lasts roughly 35 minutes per brain. This is longer than the other workloads VDB conversion, cell segmentation and skeletonization combined (32 minutes) due to the single-threaded connected component analysis at the end of seed segmentation. The other two portions, morphological closing and opening, only take 48 and 5 seconds respectively.

TABLE III
SEED SEGMENTATION COORDINATE ACCURACY WITH 1 RADIUS WIDTH TOLERANCE FOR 1 WHOLE MOUSE BRAIN IMAGED AT 6X 1UM^3 RESOLUTION. RECALL IS THE FRACTION OF TRUE POSITIVES (TP). PRECISION IS THE FRACTION OF FALSE POSITIVES (FP) TO TP. THE SUM OF TP AND FP REPRESENTS THE TOTAL AUTOMATED SEED AND CELL OUTPUT COUNT.

Type	Recall	Precision	F1	Count
Auto	.94	.06	.12	8953

2) Accuracy: Automated seed detection has high recall as seen in Figure III; it can recover .94 of true positive (TP) seeds.

Fig. 4. The effect of each image processing on image size both in memory and disk. Image processing steps and unstructured data (for example, TIF format) do not have any impact on memory usage but they can improve the data compressibility on disk. VDB format on the other hand can dramatically reduce both memory and disk usage. (a) Unprocessed TIF format occupies 100 percent of the disk and memory. The same data after thresholding and sparsification occupies less than 10 percent of memory and about 1 percent of the disk using a disk-assisted compression method. Interestingly, different stages of image processing increase the data compressibility not only for VDB files but also for compressed TIF files by removing noise and fluctuation in the signal. Using mask-VDB, the memory footprint will be a mere 1.3 percent for reconstruction in our pipeline.

Fig. 5. Aggregate runtime (left) and throughput (right) of the example tasks. Though scaling is sub-linear, added cores still yield significant speedup. More importantly, additional cores allow each task a higher peak memory ceiling which is critical at these scales.

However it produces a high proportion of false positives (FP); only .06 of predicted seeds were true positives. We explain subsequent work to mitigate this behavior in the discussion.

D. Cell segmentation

1) Empirical scalability and performance: Fastsweeping completes in under 9 minutes and cellular connected component segregation requires 23 seconds. Computing reachability from known seeds narrows the working set by almost 6× (Table IV).

	Gigavoxels	Factor	Meaning
W	1790	10,400×	Dense image
W_s	1.01	5.87×	Foreground VDB
W_c	.172	1×	Reachable from seeds

2) Accuracy: Fastsweeping is a simple heuristic that we use indirectly to find regions contiguous to a seed. Its utility depends on the continuity of the image after thresholding and conversion to the VDB representation ($W \rightarrow W_s$). In other words, it still suffers from path breaks or collisions if they remain in the converted image. Below, we examine the downstream effects on topology to best assess its efficacy.

E. Skeletonization

Stage	APP2	Ours
Fastsweeping	$\mathcal{O}(n \log n)$	$\mathcal{O}(n)$
Pruning	$\mathcal{O}(nr^3)$	$\mathcal{O}(n)$
3D		✓
Parallel		✓

Fig. 6. Crosses (APP2) and circles (ours) compare the memory allocated during of skeletonization of individual connected components (ideally 1 neuron). APP2 takes roughly 1000× more memory per neuron which is problematic with large clusters with intersections.

1) Empirical scalability and performance: Skeletonization of 374 seeds takes under 2 minutes fully parallelized and under 43.5 minutes for 1 core (see Figure 5).

Table IV reports that each APP2 single neuron run can incur roughly 4 orders of magnitude more memory overhead than its W_c count. In contrast, our method is on the order of W_c both in time and space at the time of skeletonization. In addition

to reading and retaining the dense 3D bounding box (crop window) of a neuron, APP2 also densely allocates several scratch pads, also on the order of W. On our system with 4 TB of memory, the largest neuron that APP2 could reconstruct (right most red cross) was of size 3788×5380×1995. This largest cluster took about 2609 GB of peak RAM. Our method can operate on a neuron or many neurons that span the whole brain (67× larger than APP2) while also using 870× less memory.

Although APP2 is the fastest and most scalable alternative method for single cell reconstruction, our method can skeletonize even the largest clusters in seconds where APP2 takes over a 100 minutes. Surface coarsening is largely responsible for this speedup since it allows reconstruction at a user-specified resolutions. We use 2 or 4 steps of coarsening since its more suitable for recovering topology (as opposed to surface structure). Note that APP2 pruning must approximate only in 2D due to performance, whereas our methods are all natively 3D. We summarize the differences in Table 5.

	Ours		APP2
Voxel Res.	1um^3	.4um^3	.4um^3
Topology	**.74**	**.74**	.30
Recall	.52	.56	.06
Branch	.60	.58	.06
Direction	.97	.92	.24
Leaf	.28	.39	.03
Precision	**.88**	.76	.44
Yield	.86	.92	.14
Count	374	181	181

2) Accuracy: DIADEM [36] is the gold standard comparison tool for neuron reconstructions largely because it has substantial correlation with both 1) proofread times and 2) expert subjective opinion on automated quality. DIADEM is a strict tree topological similarity score which yields 1 for a perfect match. For each ground truth skeletal node DIADEM checks 3 criteria:

1) Is there a *matching* node in the test skeleton within a Euclidean distance?
2) Do the potential node matches from step 1 have a corresponding *matching* ancestor node?
3) Is the path distance between node and ancestor and potential match node and its ancestor roughly similar?

Step 1 reports the basic recall or completeness of the skeleton. Step 2 prevents nodes on different or incorrectly

directed branches from counting as a match. Step 3 further lowers the chance that nodes with a correct ancestor but a different path back to a seed get counted as a match. The distance threshold is dataset specific and is determined by the diameter of the largest branch point of all gold standard skeletons. For both datasets tested this value is set to 8um.

DIADEM is a good starting point for understanding the tree accuracy, however its largest drawback is a lack of transparency. To compensate, we isolate basic properties that correspond to known error types deduced during proofreading. Each of these topological qualities (see Table VI) helps explain DIADEM's aggregated score. We term this suite, along with DIADEM, TreeBench. Its implementation is available along with the rest of the example benchmarks.

In tables 6, 7 and 8, topology indicates the DIADEM score which is an aggregate tree similarity metric. Recall is the fraction of ground truth skeletal nodes that have a matching node in the test. Branch and leaf also report the proportion of branches and leaf node matches respectively. Direction indicates the proportion of only the *matching* branch nodes that are also oriented in the correct direction which is why the score is often higher than the branch score. Precision is the fraction of test nodes that correspond to a node in the ground truth. Yield gives the proportion of automated neurons that had a topological accuracy within 2 standard deviations of the mean. Count illustrates the number of input seeds (cell bodies) used. The topology score reflects only the successful reconstructions, whereas all other scores aggregate errors across both successful and failed reconstructions.

When we adjust our mesh resolutions such that our runtimes roughly match those of APP2 per neuron, our yield is 78% higher (Table VI). We lend APP2 our foreground percenting algorithm (at the same .8%) for this comparison since it most closely matches the thresholding used by [24] another recent pipeline. APP2 accuracy and yield are far lower due to lack of the image processing steps of destriping, debleaching and deconvolution.

Higher resolution can achieve better overall yield and less path breaks at the cost of more collisions and artifacts. Path breaks are the biggest loss in accuracy since a substantial fraction of ground truth skeleton nodes do not have a match in our automated outputs. Branch nodes tend to be more proximal to a seed and as expected have higher accuracy whereas leaf nodes which are the terminal points of branches have low recall. Of course, the global recall is in between both branch and leaf node recall, since it is an aggregate for all of a neuron's nodes.

More complete neurons is often a priority when reconstructing neuron types that contain longer projections (axons). Reconstructing these neuron types is a key advantage since other pipelines can not capture them automatically at all due to performance. However, 1 collision or path direction error is much more time consuming to correct since it can involve deletion of a substantial proportion of the tree. In contrast, current proofreading tools are optimized to interactively fix path breaks.

F. Application Pipeline Ablations

TABLE VII
TREEBENCH SCORES WITH SEVERAL KEY PARAMETERS CHANGED. WE COMPARE EACH ABLATION TO THE SECOND COLUMN OF TABLE VI (OURS AT .4UM^3) WHICH HAS THE DEFAULT SETTINGS OF 2 STEPS OF SURFACE COARSENING, FOREGROUND PERCENT OF .8 AND 4 STEPS OF MORPHOLOGICAL CLOSING. EACH OF THESE COLUMNS CHANGES ONE OF THESE PARAMETERS.

	Coarsen 4	**Foreground (%)** .4	**Close** 1
Topology	.67 (-△ .07)	.69 (-△ .05)	.72 (-△ .02)
Recall	.53 (-△ .03)	.50 (-△ .06)	**.60 (+△ .04)**
Branch	.46 (-△ .12)	.58	**.63 (+△ .05)**
Direction	.93 (+△ .01)	**.98 (+△ .06)**	.97 (+△ .05)
Leaf	.32 (-△ .07)	.32 (-△ .07)	.40 (+△ .01)
Precision	.78 (+△ .02)	.85 (+△ .09)	.83 (+△ .07)
Yield	.92	.93 (+△ .01)	.65 (-△ .27)

TABLE VIII
TREEBENCH SCORES FOR VARIOUS ABLATIONS IN IMAGE PREPROCESSING. AGAIN, WE COMPARE EACH ABLATION TO THE SECOND COLUMN OF TABLE VI (OURS AT .4UM^3) WHICH APPLIES ALL PREPROCESSING STAGES. EACH COLUMN IS CUMULATIVE USING THE IMAGE PROCESSING STEP TO ITS LEFT. ANISOTROPIC INCLUDES DECONVOLUTION (OMITTED WITH A DOUBLE VERTICAL LINE DUE TO ALREADY BEING LISTED AS THE DEFAULT IN TABLE VI) BUT ADDS A FINAL STEP OF DOWNSAMPLING THE Z-DIMENSION BY A FACTOR OF 3 TO PROBE THE EXTENT TO WHICH ADDED INFORMATION CONTRIBUTES TO RECONSTRUCTION ACCURACY.

	Raw	**Destripe**	**Debleach**	**Anisotropic**
Topology	.71 (-△ .03)	.69 (-△ .05)	.71 (-△ .03)	.72 (-△ .02)
Recall	.57 (+△ .01)	.53 (-△ .03)	.56	.57 (+△ .01)
Branch	.55 (-△ .03)	.45 (-△ .13)	.52 (-△ .06)	.58
Direction	.93 (+△ .01)	.92	.90 (-△ .02)	.91 (-△ .01)
Leaf	**.43 (+△ .04)**	.37 (-△ .02)	.41 (+△ .02)	**.43 (+△ .04)**
Precision	.84 (+△ .08)	.82 (+△ .06)	.81 (+△ .05)	.81 (+△ .05)
Yield	.67 (-△ .25)	.91 (-△ .01)	.90 (-△ .02)	**.94 (+△ .02)**

Surface coarsening lowers the granularity (vertex count) of the mesh surface, which also decreases the TreeBench scores as illustrated in Table 7. Although light-edge matching can not introduce new path breaks or collisions, the resulting lower resolution meshes do have the morphological artifact of shortened branches. The sock-like termini at the distal-end of cell branches have high curvature and tend to erode proximally (towards the seed) at 4 steps of coarsening. Very thin branches are more prone to this shortening, which causes losses in leaf and branch completeness, as well as overall recall, though to a smaller extent.

A lower foreground percent reduces the overall completeness and termini (leaf) recall due to breaks. However, it is less prone to losing small or thin branches since very short branches are eroded entirely.

Closing boosts the automated yield by a similar amount to the combined image preprocessing stages, however it only has these benefits when combined with these enhancements. However, decreasing the morphological closing (1 step instead of 4) improves individual scores of TreeBench which follows our observation that it is the most biased transformation we apply. For example, closing can move skeletal nodes to such an

extent as to lower the matches. Branch points are particularly affected by closing, presumably due to erroneously joining the morphology of branch points further distally.

The highest yield occurs when applying all developed image processing techniques and additionally downsampling the z-dimension by a factor corresponding to the inherent point spread function of lightsheet microscopy. This smear in z is rather dramatic (about $2.5\times$) and deconvolution does not effectively remove it. It also limits the smallest resolution that skeletonization can place nodes and higher sampling leads to more accurate and natively smooth graphs.

VI. DISCUSSION AND FUTURE WORK

Seed segmentation is effective at localizing and segmenting *potential* seeds, but performs poorly at distinguishing them from the background. This is likely because cell bodies are generic simple spheres that are difficult to discriminate from background noise after morphological closing. Adding a lightweight second pass classifier such as a multi-layer perceptron to cull false positives seeds could enable competitive accuracy. As it stands, humans must filter the seeds manually. Though these false positives can usually be batch deleted quickly with existing tools because they are clustered in unintentionally high saturation areas of the image.

It takes a similar time to compute reachability on a whole brain scale as it does similar methods like APP2 to complete fastmarching on moderate sized neurons. Cell segmentation is particularly fast because 1) it applies sparse fastsweeping 2) it starts with a large broadly distributed set of seeds which enables high concurrency with little ramp up and 3) unreachable regions are not accessed until the final prune step. Since the sparse working set W_s of cell segmentation is about 2 GB, it can stay in memory after conversion, and there are no disk read penalties of long-range connections. Other methods couple their algorithms with dense images, thus incurring reads from disk.

The local separators method [6][7] we used has linear time complexity. This is a major improvement over APP2 and Neutube's $O(nlogn)$ complexity which has compounding performance penalties when combined with the power law distribution of components. Although the number of seeds is generally larger than the thread count, some components are orders of magnitude larger. This leads to poor load balance, with some neurons taking much longer to complete regardless of thread count.

A. Conclusion

Our results suggest that even higher resolution would improve accuracy but scales much larger than $13k^3$, consume more than 4TB peak memory and are thus not possible to process with our method and reference system at this time. Still, we show that computational techniques can improve yield and accuracy with available resolutions. It is rather surprising that generalizations of search, when ordered effectively, can alter the scale in which neuroscience is performed. Competing methods employ highly integrated domain-specific heuristics that are coupled with dense image representations making them infeasible to parallelize. Our modular approach is more efficient and can be specialized for a particular representation and on growing datasets which allows it to gain in light of future data driven and supervised techniques.

B. Contributions

We would like to thank the following authors and acknowledgments for their contributions to this work. We thank Tony Nowatski for his suggestions on an early paper draft. Muye Zhu provided the foreground percent algorithm and inspired the pipeline with the original MCP3D pipeline. Muye Zhu, Masood Akram, Chris Choi, Hongwei Dong, Chris Sin Park, X. William Yang, Zhe Chen, and Jason Cong advised on application and pipeline design and provided helpful discussions and feedback. Masood Akram helped evaluate reconstructions on gold standard datasets. Yuze Chi implemented an accelerated version of graph partitioning and fastmarching on FPGA. Chris Sin Park, Chris Choi and X. William Yang provided the mouse imaging data for the .4um lightsheet volume. Keivan Moradi and HongWei Dong provided the mouse imaging data for the 1um lightsheet volume. Chris Choi and Ming Yan led proofreading efforts related to the project and provided proofread soma locations for the .4um image. Ming Yan analyzed soma detection accuracy, provided scripts for overcoming manual steps in the pipeline including neuron filtering methods and designed a soma proofreading protocol. Brian Zingg and Chris Sin Park performed the surgeries needed to generate genetically labeled brains. Mitchell Rudd and Chris Sin Park performed tissue clearing and lightsheet imaging. Adriana Gutierez, Hyun-Seung Mun, and Qing Xue human-validated all reconstructions used in the manuscript. Sumit Nanda and Keivan Moradi, programmatically post-processed SWC files to prepare them for analysis. Sumit Nanda carried out preliminary testing of reconstruction output comparison with manual reconstructions using DIADEM metric Keivan Moradi designed and implemented image processing stages (encoding), wrote the corresponding portions of the manuscript and also second-pass proofread all 555 neuron reconstructions used in the manuscript. Karl Marrett designed and implemented VDB, reconstruction, and TreeBench, performed analysis and wrote the associated sections of the manuscript. This research is funded under NIH Grant No.: (U01MH117079-01).

REFERENCES

[1] Ludovica Acciai, Paolo Soda, and Giulio Iannello. 2016. Automated Neuron Tracing Methods: An Updated Account. *Neuroinformatics* (2016). https://doi.org/10.1007/s12021-016-9310-0

[2] Nanda S. Maraver P. et al. Akram, M. 2018. An open repository for single-cell reconstructions of the brain forest. *Sci. Data* 5, Article 18006 (2018). https://doi.org/10.1038/sdata.2018.6

[3] Katrin Amunts and Thomas Lippert. 2021. Brain research challenges supercomputing. *Science* 374, 6571 (2021), 1054–

1055. https://doi.org/10.1126/science.abl8519 arXiv:https://www.science.org/doi/pdf/10.1126/science.abl8519

[4] Cameron Arshadi, Ulrik Günther, Mark Eddison, Kyle I. S. Harrington, and Tiago A. Ferreira. 2021. SNT: a unifying toolbox for quantification of neuronal anatomy. *Nature Methods* 18, 4 (apr 2021), 374–377. https://doi.org/10.1038/s41592-021-01105-7

[5] Giorgio A. Ascoli, Duncan E. Donohue, and Maryam Halavi. 2007. NeuroMorpho.Org: A Central Resource for Neuronal Morphologies. *Journal of Neuroscience* 27, 35 (2007), 9247–9251. https://doi.org/10.1523/JNEUROSCI.2055-07.2007 arXiv:https://www.jneurosci.org/content/27/35/9247.full.pdf

[6] Andreas Bærentzen and Eva Rotenberg. 2021. Skeletonization via Local Separators. *ACM Trans. Graph.* 40, 5, Article 187 (sep 2021), 18 pages. https://doi.org/10.1145/3459233

[7] J Andreas Bærentzen, Rasmus Emil Christensen, Emil Toftegaard Gæde, and Eva Rotenberg. 2023. Multilevel Skeletonization Using Local Separators. *arXiv preprint arXiv:2303.07210* (2023).

[8] Klaus Becker, Saiedeh Saghafi, Marko Pende, Inna Sabdyusheva-Litschauer, Christian M Hahn, Massih Foroughipour, Nina Jährling, and Hans-Ulrich Dodt. 2019. Deconvolution of light sheet microscopy recordings. *Scientific reports* 9, 1 (2019), 17625.

[9] Alessandro Bria and Giulio Iannello. 2012. TeraStitcher-a tool for fast automatic 3D-stitching of teravoxel-sized microscopy images. *BMC bioinformatics* 13, 1 (2012), 1–15.

[10] Alessandro Bria, Giulio Iannello, Leonardo Onofri, and Hanchuan Peng. 2016. TeraFly: real-time three-dimensional visualization and annotation of terabytes of multidimensional volumetric images. *Nature methods* 13, 3 (2016), 192–194.

[11] Alessandro Bria, Giulio Iannello, Leonardo Onofri, and Hanchuan Peng. 2022. TeraFly: real-time three-dimensional visualization and annotation of terabytes of multidimensional volumetric images. 13 (2022). Issue 3. https://doi.org/10.1038/nmeth.3767

[12] Robert C. Cannon, Dennis A. Turner, G.K. Pyapali, and H.V. Wheal. 1998. An on-line archive of reconstructed hippocampal neurons. *Journal of Neuroscience Methods* 84, 1-2 (1998), 49–54. https://doi.org/10.1016/S0165-0270(98)00091-0

[13] Angel X. Chang, Thomas A. Funkhouser, Leonidas J. Guibas, Pat Hanrahan, Qi-Xing Huang, Zimo Li, Silvio Savarese, Manolis Savva, Shuran Song, Hao Su, Jianxiong Xiao, Li Yi, and Fisher Yu. 2015. ShapeNet: An Information-Rich 3D Model Repository. *CoRR* abs/1512.03012 (2015). arXiv:1512.03012 http://arxiv.org/abs/1512.03012

[14] D Cooke, T Hochberg, F Alted, I Vilata, M Wiebe, G de Menten, A Valentino, and RA McLeod. 2009. NumExpr: Fast numerical expression evaluator for NumPy.

[15] Nicu D Cornea, Deborah Silver, and Patrick Min. 2005. Curve-skeleton applications. In *VIS 05. IEEE Visualization, 2005*. IEEE, 95–102.

[16] Georgios D Evangelidis and Emmanouil Z Psarakis. 2008. Parametric image alignment using enhanced correlation coefficient maximization. *IEEE transactions on pattern analysis and machine intelligence* 30, 10 (2008), 1858–1865.

[17] Linqing Feng, Ting Zhao, and Jinhyun Kim. 2015. neuTube 1.0: A New Design for Efficient Neuron Reconstruction Software Based on the SWC Format. *eNeuro* 2, 1 (January 2015), ENEURO.0049–14.2014. https://doi.org/10.1523/eneuro.0049-14.2014

[18] Le Gao, Sang Liu, Lingfeng Gou, and Yachuang Hu et al. 2022. Single-neuron projectome of mouse prefrontal cortex. 25 (2022), 515–529. Issue 4. https://doi.org/10.1038/s41593-022-01041-5

[19] Patric Hellermann. 2023. *Neural radiance fields and billion-dollar opportunities they create in the 3D tool stack.* https://foundamental.com/aecvc/nerfs-in-3d

[20] Yuanming Hu, Tzu-Mao Li, Luke Anderson, Jonathan Ragan-Kelley, and Frédo Durand. 2019. Taichi: a language for high-performance computation on spatially sparse data structures. *ACM Transactions on Graphics (TOG)* 38, 6 (2019), 201.

[21] Shengdian Jiang, Yimin Wang, Lijuan Liu, Sujun Zhao, Mengya Chen, Xuan Zhao, Peng Xie, Liya Ding, Zongcai Ruan, Hong-Wei Dong, Giorgio A. Ascoli, Michael Hawrylycz, Hongkui Zeng, and Hanchuan Peng. 2021. MorphoHub: A Platform for Petabyte-Scale Multi-Morphometry Generation. *bioRxiv* (2021). https://doi.org/10.1101/2021.01.09.426010

[22] Siu Kwan Lam, Antoine Pitrou, and Stanley Seibert. 2015. Numba: A llvm-based python jit compiler. In *Proceedings of the Second Workshop on the LLVM Compiler Infrastructure in HPC*. 1–6.

[23] Hsueh-Ti Derek Liu, Francis Williams, Alec Jacobson, Sanja Fidler, and Or Litany. 2022. Learning Smooth Neural Functions via Lipschitz Regularization. https://doi.org/10.48550/ARXIV.2202.08345

[24] Yufeng Liu, Shengdian Jiang, Yingxin Li, Sujun Zhao, Zhixi Yun, Lijuan Liu, Hanchuan Peng, et al. 2023. Full-Spectrum Neuronal Diversity and Stereotypy through Whole Brain Morphometry. *Research Square* (2023).

[25] Chiara Magliaro, Alejandro L. Callara, Nicola Vanello, and Arti Ahluwalia. 2019. Gotta trace 'em all: A mini-review on tools and procedures for segmenting single neurons toward deciphering the structural connectome. *Frontiers in Bioengineering and Biotechnology* 7, AUG (2019), 1–8. https://doi.org/10.3389/fbioe.2019.00202

[26] Linus Manubens-Gil, Zhi Zhou, Hanbo Chen, Arvind Ramanathan, Xiaoxiao Liu, Yufeng Liu, Alessandro Bria, Todd Gillette, Zongcai Ruan, Jian Yang, Miroslav Radojević, Ting Zhao, Li Cheng, Lei Qu, Siqi Liu, Kristofer E. Bouchard, Lin Gu, Weidong Cai, Shuiwang Ji, Badrinath Roysam, Ching-Wei Wang, Hongchuan Yu, Amos Sironi, Daniel Maxim Iascone, Jie Zhou, Erhan Bas,

Eduardo Conde-Sousa, Paulo Aguiar, Xiang Li, Yujie Li, Sumit Nanda, Yuan Wang, Leila Muresan, Pascal Fua, Bing Ye, Hai yan He, Jochen F. Staiger, Manuel Peter, Daniel N. Cox, Michel Simonneau, Marcel Oberlaender, Gregory Jefferis, Kei Ito, Paloma Gonzalez-Bellido, Jinhyun Kim, Edwin Rubel, Hollis T. Cline, Hongkui Zeng, Aljoscha Nern, Ann-Shyn Chiang, Jianhua Yao, Jane Roskams, Rick Livesey, Janine Stevens, Tianming Liu, Chinh Dang, Yike Guo, Ning Zhong, Georgia Tourassi, Sean Hill, Michael Hawrylycz, Christof Koch, Erik Meijering, Giorgio A. Ascoli, and Hanchuan Peng. 2022. BigNeuron: A resource to benchmark and predict best-performing algorithms for automated reconstruction of neuronal morphology. *bioRxiv* (2022). https://doi.org/10.1101/2022.05.10.491406

[27] Thomas Müller, Alex Evans, Christoph Schied, and Alexander Keller. 2022. Instant Neural Graphics Primitives with a Multiresolution Hash Encoding. *ACM Trans. Graph.* 41, 4, Article 102 (July 2022), 15 pages. https://doi.org/10.1145/3528223.3530127

[28] Ken Museth. 2013. VDB: High-Resolution Sparse Volumes with Dynamic Topology. *ACM Trans. Graph.* 32, 3, Article 27 (July 2013), 22 pages. https://doi.org/10.1145/2487228.2487235

[29] Ken Museth. 2017. Novel Algorithm for Sparse and Parallel Fast Sweeping: Efficient Computation of Sparse Signed Distance Fields. In *ACM SIGGRAPH 2017 Talks* (Los Angeles, California) *(SIGGRAPH '17)*. Association for Computing Machinery, New York, NY, USA, Article 74, 2 pages. https://doi.org/10.1145/3084363.3085093

[30] Ashwin Pajankar and Ashwin Pajankar. 2017. Signal processing with SciPy. *Raspberry Pi Supercomputing and Scientific Programming: MPI4PY, NumPy, and SciPy for Enthusiasts* (2017), 139–147.

[31] Pietro Ricci, Vladislav Gavryusev, Caroline Müllenbroich, Lapo Turrini, Giuseppe de Vito, Ludovico Silvestri, Giuseppe Sancataldo, and Francesco Saverio Pavone. 2022. Removing striping artifacts in light-sheet fluorescence microscopy: a review. *Progress in Biophysics and Molecular Biology* 168 (2022), 52–65. https://doi.org/10.1016/j.pbiomolbio.2021.07.003 The Resolution Revolution: Fluorescence Microscopy of Biological Samples from Micro to Meso.

[32] Olaf Ronneberger, Philipp Fischer, and Thomas Brox. 2015. U-Net: Convolutional Networks for Biomedical Image Segmentation. *CoRR* abs/1505.04597 (2015). arXiv:1505.04597 http://arxiv.org/abs/1505.04597

[33] Darius Rückert, Yuanhao Wang, Rui Li, Ramzi Idoughi, and Wolfgang Heidrich. 2022. NeAT: Neural Adaptive Tomography. *ACM Trans. Graph.* 41, 4, Article 55 (jul 2022), 13 pages. https://doi.org/10.1145/3528223.3530121

[34] Ernst HK Stelzer, Frederic Strobl, Bo-Jui Chang, Friedrich Preusser, Stephan Preibisch, Katie McDole, and Reto Fiolka. 2021. Light sheet fluorescence microscopy. *Nature Reviews Methods Primers* 1, 1 (2021), 73.

[35] Justin Swaney, Lee Kamentsky, Nicholas B Evans, Katherine Xie, Young-Gyun Park, Gabrielle Drummond, Dae Hee Yun, and Kwanghun Chung. 2019. Scalable image processing techniques for quantitative analysis of volumetric biological images from light-sheet microscopy. *BioRxiv* (2019), 576595.

[36] & G.A. Ascoli T.A. Gillette, K.M. Brown. 2011. The DIADEM Metric: Comparing Multiple Reconstructions of the Same Neuron. *Neuroinformatics* 9 (2011), 233–245. https://doi.org/10.1007/s12021-011-9117-y

[37] Stefan Van der Walt, Johannes L Schönberger, Juan Nunez-Iglesias, François Boulogne, Joshua D Warner, Neil Yager, Emmanuelle Gouillart, and Tony Yu. 2014. scikit-image: image processing in Python. *PeerJ* 2 (2014), e453.

[38] Matthew B. Veldman, Chang Sin Park, Charles M. Eyermann, Jason Y. Zhang, Elizabeth Zuniga-Sanchez, Arlene A. Hirano, Tanya L. Daigle, Nicholas N. Foster, Muye Zhu, Peter Langfelder, Ivan A. Lopez, Nicholas C. Brecha, S. Lawrence Zipursky, Hongkui Zeng, Hong-Wei Dong, and X. William Yang. 2020. Brain-wide Genetic Sparse Cell Labeling to Illuminate the Morphology of Neurons and Glia with Cre-Dependent MORF Mice. *Neuron* 108, 1 (2020), 111–127.e6. https://doi.org/10.1016/j.neuron.2020.07.019

[39] Yimin Wang, Qi Li, Lijuan Liu, Zhi Zhou, Zongcai Ruan, Lingsheng Kong, Yaoyao Li, Yun Wang, Ning Zhong, Renjie Chai, et al. 2019. TeraVR empowers precise reconstruction of complete 3-D neuronal morphology in the whole brain. *Nature communications* 10, 1 (2019), 3474.

[40] Johan Winnubst, Erhan Bas, Tiago A. Ferreira, Nelson Spruston, Karel Svoboda, and Jayaram Chandrashekar. 2019. Reconstruction of 1,000 Projection Neurons Reveals New Cell Types and Organization of Long-Range Connectivity in the Mouse Brain. *Cell* 179, 1 (2019), 268–281.e13. https://doi.org/10.1016/j.cell.2019.07.042

[41] Hang Xiao and Hanchuan Peng. 2013. APP2: Automatic tracing of 3D neuron morphology based on hierarchical pruning of a gray-weighted image distance-tree. *Bioinformatics* 29, 11 (2013), 1448–1454. https://doi.org/10.1093/bioinformatics/btt170

[42] Jian Yang, Ming Hao, Xiaoyang Liu, Zhijiang Wan, Ning Zhong, and Hanchuan Peng. 2019. FMST: an Automatic Neuron Tracing Method Based on Fast Marching and Minimum Spanning Tree. *Neuroinformatics* 17, 2 (2019), 185–196. https://doi.org/10.1007/s12021-018-9392-y

[43] Hongkui Zeng and Joshua R Sanes. 2017. Neuronal cell-type classification: challenges, opportunities and the path forward. *Nature Publishing Group* 18 (2017). https://doi.org/10.1038/nrn.2017.85

VII. SUPPLEMENTARY MATERIAL

Supplementary Note 1 *PyStripe:* To better eliminate CMOS camera artifacts, we modified the PyStripe program to apply a small 5x5 Gaussian kernel with a sigma of 1 to raw

images before applying the destripe algorithm. Empirically, the db9 wavelet and a sigma of 250 for 15x images and 100 for 4x images for foreground and background produced better results. Since the original PyStripe algorithm was adding artifacts to the edges of the image, we temporarily padded the images with the wrap method before destriping. The pad size is automatically calculated based on the destriping sigma.

pad size = half-height width of the Gaussian notch filter

We implemented a more efficient queue-based parallel processing model for pystripe and added PNG reading and damaged-image-detection-and-replacement functionality. Queue-based parallel processing model in contrast to map-function-based is more efficient since there is no need to spawn a new worker for each image. Instead, each worker runs only one time and processes a queue of images. The queue-based model is specifically more beneficial on Windows, which has more overhead to spawn workers compared with Linux which forks them most of the time.

Using Numba[22] and NumExpr [14], we optimized the pipeline by the just-in-time complication of some of the functions where beneficial. Also, we implemented a fast blank image detection algorithm to skip the processing of such images to further speed up the process.

Supplementary Note 2 *Parastitcher:* We implemented a multi-GPU accelerated and NAS-friendly version of Parastitcher[9] on Linux to find the alignment of tiles. We patched TeraStitcher to repeat the read request up to 40 times to fix an issue with some NAS storage in which the reading request fails sometimes.

Supplementary Note 3 *TSV:* We also employed a queue-based parallel processing model for the TeraStitcher volume program[35] that is more resilient to missing tiles. We increased the resiliency of TSV in case of missing tiles; TSV can now detect missing tiles and replace them with blank images. We also made TSV compatible with newer versions of Python (v3.11 at the time of publication).

Supplementary Note 4 *16-bit to 8-bit conversion with variable bit shifting:* lightsheet fluorescent data has an unsigned 16-bit int type and brightness values have a gamma distribution. Traditional 8-bit conversion will shift the bits to the right for 8 bits, which assigns any value between 0 to 255 to zero while over-representing the tail of the gamma distribution. It is possible to clip the tail of the data so that the 16-bit image can be shifted to the right with a smaller number of bits, which leads to the assignment of a narrower range to zero. For example, with 1 right bitshift only 0 to 1 will be assigned to zero in 8-bit. We used a multi-class Otsu thresholding function from the scikit-image package[37] with 4 classes that are applied to the log1p transform of the image. Then we found 99.9 percentile of values larger than the upper threshold to find the upper bound clipping value. For the lower bound of the data, we made sure any value larger than one that could be set to zero by bit-shifting was assigned to 1 instead.

Supplementary Note 4 *Non-blocking Paraconverter:* We used Paraconverter to convert stitched images to TeraFly format[10]. Since Paraconverter did not scale well on our cluster computer, we implemented a parallel processing algorithm that runs Paraconverter without blocking the progress of stitching for the remaining channels. We used TeraFly files for seed detection, visualization of the images in virtual reality (TeraVR)[39], and vetting of neuronal reconstruction.

Supplementary Note 5 *Multi-channel images:* we developed an algorithm that finds the translation of the stitched images for a reference channel (usually the nuclear staining channel that is used for image registration to 3D brain atlases) at the middle z-frame of the volumes using the OpenCV version of enhanced correlation coefficient maximization algorithm[16] before converting the images to RGB format. Finally, the 2D RGB tif series are converted to a single Imaris volume with a custom code in Python.

Supplementary Note 6 *Automation:* We minimized human interaction by automatically calculating the number of processes based on the required RAM and the available resources. Also, we made sure the RAM usage was optimal by avoiding declaring unnecessary temporary variables since the size of each z-step of the stitched images can be in the order of several GBs in RAM.

Supplementary Note 7 *DeBleach:* `coif15` wavelet is used for initial bidirectional destriping. We used sosfiltfilt function from SciPy Signal package[30] with a frequency of (1/tile size) for generating the low-pass filter because it has no phase shift. The foreground of the image was clipped to the max of the background in advance.

Supplementary Note 8 *Deconvolution:* We optimized the deconvolution algorithm to minimize copying data back and forth between system RAM and video RAM (vRAM), which enhanced the performance significantly. We also optimized block size calculation to ensure the maximum block size on vRAM so that larger chunks of the image volume can be processed at any given time. Image blocks now load asynchronously in the background to maximize GPU utilization time. We also fixed a bug in the program, which was adding artifacts on the z-axis, by padding image blocks using the data from the image volume instead of an artificial pad on the z-axis.

For an unknown reason, some of the lightsheet images could show a duplication effect on the z-axis, or neurites could look like halo tubes, which cause problems for reconstruction. Empirically, we found that a 3D Gaussian filter with sigmas of [0.5, 0.5, 1.0] and a kernel size of [3, 3, 9] on x, y, and z axes respectively, can mitigate the issue post hoc. Deconvolution algorithms are sensitive to noise. 3D Gaussian filter can also further denoise the images to improve deconvolution.