BAITSAO: Building A Foundation Model for Drug Synergy Analysis Powered by Language Models

Tianyu Liu[1,2], Tinyi Chu[2], Xiao Luo[3], Hongyu Zhao[1,2*]

[1]Interdepartmental Program in Computational Biology & Bioinformatics, Yale University, New Haven, 06511, CT, USA.
[2]Department of Biostatistics, Yale University, New Haven, 06511, CT, USA.
[3]Department of Computer Science, University of California, Los Angeles, Los Angeles, 90095, CA, USA.

*Corresponding author(s). E-mail(s): hongyu.zhao@yale.edu;
Contributing authors: tianyu.liu@yale.edu; tinyi.chu@yale.edu;
xiaoluo@cs.ucla.edu;

Abstract

Drug synergy prediction is a challenging and important task in the treatment of complex diseases including cancer. In this manuscript, we present a novel Foundation Model, known as BAITSAO, for tasks related to drug synergy prediction with a unified pipeline to handle different datasets. We construct the training datasets for BAITSAO based on the context-enriched embeddings from Large Language Models for the initial representation of drugs and cell lines. After demonstrating the relevance of these embeddings, we pre-train BAITSAO with a large-scale drug synergy database under a multi-task learning framework with rigorous selections of tasks. We demonstrate the superiority of the model architecture and the pre-trained strategies of BAITSAO over other methods through comprehensive benchmark analysis. Moreover, we investigate the sensitivity of BAITSAO and illustrate its unique functions including new drug discoveries, drug combinations-gene interaction, and multi-drug synergy predictions.

Keywords: Foundation Model, Large Language Model, Multi-Task Learning, Transfer Learning, Drug Synergy Prediction

1 Introduction

Treating patients with a combination of drugs has become common for various diseases, including HIV [1] and cancers [2, 3]. One key aspect of drug combinations is the synergistic effect, which means that the joint effect of multiple drugs is larger than the sum of individual drug effects [4]. Other definitions have also been used to define synergistic effects, such as [5]. Effective drug combination can reduce drug resistance of monotherapy [6] with relatively lower doses of individual drugs [7]. Since drugs can change gene expressions when applied to different systems, e.g., cell lines, their effects can be studied through the genomics lens [8, 9]. Currently, researchers use high-throughput combinatorial screening to identify drug combinations with synergistic effects for specific cell lines [10]. However, such experimental screening is laborious and time-consuming due to the very number of potential drug combinations, and it is even more challenging to assess the synergistic effect of combinations with three or more drugs [11]. Therefore, it is important to develop computational methods based on extensive experimental datasets in the public domain as well as diverse types of prior biological knowledge to predict the presence and strength of synergistic effects for candidate drug combinations. Accurate prediction methods can facilitate drug discovery [12] and clinical development [13].

Given its importance, it is no surprise that many machine learning methods, especially deep learning methods, have been proposed to predict drug synergy. These methods differ in model architecture, training strategies, and datasets used to build the models. DeepSynergy [14] is among the earliest tools by building a neural network for both regression and classification, with follow-up work such as TreeComb [15] and MatchMarker [16]. Existing drug synergy prediction methods can be broadly classified into two groups. The first group of methods, such as MARSY [17], focus on predicting specific synergy scores, whereas the second group of methods, such as DeepDDs [18], transfer the continuous synergy score into a binary one via thresholding to infer drug combination synergy. However, most existing methods do not incorporate the extensive synergy information from public databases [19] in their predictions. [20] utilized a transfer learning approach and pre-trained the model based on large-scale databases while incorporating different types of features (e.g., gene expression, molecular structure). However, it did not consider datasets [14] with only partial information and treated drugs with the same molecular formula but different names as distinct ones. Therefore, the generalization ability of this model is limited by its input data format. Moreover, since public databases are updated constantly, it is important to track the versions of training datasets.

Foundation Models (FMs) [21] have greatly improved the performance of deep learning on various tasks in diverse areas, especially in Natural Language Processing (NLP) [22]. Such models, known as Large Language Models (LLMs), have received broad attention from both industry and academia [23]. Researchers have proposed to use FMs to predict drug synergy via LLMs by transferring the drug synergy prediction problem into a Question-Answer problem [24, 25]. By incorporating prior information of single drug and single cell line from LLMs, it has become possible to predict drug synergy of unknown drug combinations in unknown cell lines. Text information may be less noisy than the features (e.g. gene expression levels) that have been used

in this task. However, such QA setting limits the task to a classification problem. Moreover, there is a lack of exploration on the utilization of the information in LLMs for more difficult drug synergy prediction problems, e.g., the effects of multiple drug combinations or model explainability.

Here we present a scalable Foundation Model for drug synergy prediction called BAITSAO[1]. BAITSAO utilizes the information from LLMs as input and was pre-trained based on large-scale known synergistic effect information of paired drug combinations and cell lines. The information of drug combinations and cell lines is necessary to predict synergy scores. We show that the embeddings of these features from LLMs can be effective input for drug synergy prediction as well as the effects of drugs on gene expressions. We further demonstrate the capability of building an effective predictor for synergy prediction under both the classification and regression settings through multi-task learning (MTL) [26]. Finally, we pre-train BAITSAO to predict synergistic effects for unseen drug combinations based on the zero-shot learning framework and the fine-tuning framework. The scalability of BAITSAO allows us to consider multiple drugs and incorporate extra meta information.

2 Results

Overview of BAITSAO. We highlight two major contributions of BAITSAO as a foundation model. We first provide a new unified pipeline for pre-processing the information from both drugs and cell lines for machine learning in a tabular format, and generate training datasets from these embeddings for multiple tasks. We show that these embeddings contain functional information for prediction. We then utilize the unified training datasets to design a foundation model for different synergistic effect prediction tasks under the multi-task learning framework. We demonstrate the superiority of the model architecture and the contribution of pre-training through comprehensive experiments. BAITSAO can be easily transferred to perform novel downstream tasks related to drug synergy analysis. We illustrate the landscape of BAITSAO in Figures 1 (a) and (b) and summarize the differences between BAIT-SAO and other synergy prediction methods in Figure 1 (c). The major functions of BAITSAO are shown in Figure 1 (d).

Drug embeddings from LLMs reflect functional similarity and responses at the cell level. In this section, we discuss the information offered by drug embeddings and cell-line embeddings. We generate the description for the drugs and cell lines from our training datasets based on designed prompts from LLMs, and then use the embedding module from GPT 3.5 [27] to generate the embeddings of such descriptions, where the embeddings become the features of drugs or cell lines. We utilized GPT 3.5 rather than GPT 4 [28] because the layer for generating embeddings is from GPT 3 [27] series and the querying time from GPT 4 with similar quality required much more time [29]. We visualize the drug embeddings and the cell-line embeddings based on Uniform Manifold Approximation and Projection (UMAP) [30] shown in Extended Data Figures 1 (a) and (b). We investigated the quality of the embeddings by considering both the quality of the description and the quality of the functions of

---

[1]BAITSAO means collections of herbs and drugs in Chinese culture.

Fig. 1 An overview of BAITSAO as a FM under the pre-training and fine-tuning/zero-shot learning pipeline. (a) The pre-processing steps we used to transfer the meta information into embeddings to construct training datasets. (b) The model architecture of BAITSAO under a multi-task learning framework. (c) Comparisons of different methods for drug synergy analysis. (d) Different functions of BAITSAO.

embeddings. For the first aspect, we recorded the outputs as descriptions from GPT 3.5 based on our prompts and compared the content with information from Drug-Bank [31] and NCBI [32]. Here we used drugs and cell lines from DeepSynergy, which contains 39 drugs and 38 cell lines. The descriptions summarized the functional information of drugs and cell lines. Based on our experiments, only one drug (MK-8669) has a mismatched generated description and all descriptions are included in Supplementary file 1. We plot the cosine similarity for all drugs' embeddings in Figure 2 (a). We also randomly selected 10 drugs from this dataset and plot the cosine similarity for the embeddings of the same drug under 10 different descriptions by running GPT 3.5 multiple times in Extended Data Figure 2. These two figures show that the cosine similarity from different drugs is generally lower than that from the same drug, suggesting that we can get informative embeddings from LLMs. In Figure 2 (b), we used drug MK-4541 as one example and there is no clinical information for this drug in the DrugBank. By excluding the drug MK-8669 due to mismatched information, drug MK-2206 and drug MK-4827 have the highest similarity with MK-4541. Since MK-2206 and MK-4827 have similar functions (e.g., treating Breast-cancer-related

and Prostate-cancer-related diseases), we may infer that MK-4541 may have a similar effect. Among these drugs, EPTOPOSIDE has the lowest similarity and it also has different clinical trial information, suggesting that correlation between embedding similarity and function similarity. Therefore, our drug embeddings may help the inference of clinical functions of drugs based on embeddings' similarity.

To investigate whether the embeddings can be used to predict drug response for the cell-level task, we utilized CPA [9] and single-cell RNA sequencing (scRNA-seq) [33] datasets with different perturbations (defined by different drugs or drug combinations) to evaluate whether our drug embeddings can facilitate the gene expression prediction task. With drug embeddings, we can use CPA to predict gene expression response to unseen drugs. Cells with unknown perturbation results are also known as out-of-distribution (OOD) samples. The original implementation of CPA utilized the drug embeddings from Rdkit [34, 35] to encode the molecular structure of the selected drug into the embedding space. However, such methods could not handle drugs not in the Simplified Molecular-input Line-entry System (SMILES) [36], which limits the generalization of CPA. Here we considered replacing the original embeddings in CPA with the embeddings from GPT 3.5, enlarging the accessibility for drug embeddings. We compared three different embedding settings for two datasets, with results shown in Extended Data Figures 3 (a)-(d), where stacking the embeddings from SMILES and GPT 3.5 achieved the best performance. For the Openproblems dataset, the contribution of such embeddings stacking for prediction is especially significant (p-values<0.05 based on Wilcoxon rank-sum test). Therefore, the embeddings from LLMs can improve the gene expression prediction for perturbed scRNA-seq data.

Since our experiments demonstrate that drug embeddings and cell embeddings can summarize the functional information and drug embeddings can also interact with cell-level gene expressions, we believe that these embeddings allow us to construct the training dataset to predict drug synergy effect in different cell lines.

Selection of model structure by evaluation without pre-training. In this section, we consider the choice of network structure for model pre-training for two different drug synergy prediction tasks: classification and regression. For each task, we selected two datasets and two metrics for evaluation. For regression, we included the Pearson Correlation Coefficient (PCC) and Mean Squared Error (MSE) for model evaluation based on datasets D1 [14] and D2 [17]. For classification, we included ROC-AUC (ROCAUC) and Accuracy (ACC) for model evaluation based on datasets D1 and D3 [18]. These metrics and datasets were widely used in the related work [14, 17, 18, 37, 38]. We selected seven other methods (DeepSynergy, MARSY, TreeComb, SVM [39, 40], TabNet [41], BERT [42] and Lasso [40, 43]) for benchmarking the regression task and seven methods (DeepSynergy, DeepDDs, TreeComb, SVC, TabNet, BERT and Lasso) for benchmarking the classification task. We utilized the best hyper-parameters for these methods for different datasets, with details of hyper-parameter tuning summarized in the Methods section. Our results based on five-fold cross-validation [14] are summarized in Figure 3. This figure shows that BAITSAO ranked the best in three out of four metrics. Moreover, BAITSAO was also the most stable among the top deep-learning-based methods (including MARSY, DeepSynergy, DeepDDs, and TabNet). The performance of BERT was worse than BAITSAO in three

Fig. 2 Investigation of drug embeddings. (a) The heatmap for the similarity of embeddings across all the drugs. (b) Exploration of drug similarity related to MK-4541. The drugs above the red line represent the two most similar drugs, while the drugs below the red line represent the most different drug. We list five types of clinical trial information ranked by the phases.

out of four metrics, thus using embeddings as input is better than using text in general. For the evaluation based on MSE, BAITSAO performed well on the D1 dataset. Our experiments showed that embeddings from LLMs with a suitable model architecture can formalize a better training-testing framework compared with data from the classical feature space. The details of our dataset information, model construction, and training process are summarized in the Methods section.

Explainability of BAITSAO for drug-gene interaction and drug-cell line interaction. We interpret contributions of different features for the prediction task with the help of SHAP [44]. Here we integrated known gene expression profiles of different cell lines in D3 to our input datasets and performed the same training process for the drug synergy prediction task. We then utilized SHAP to study the importance of different genes and the results could be treated as the relevance between the gene expression levels and the possibility to produce synergistic effect for drug combinations. We followed the default setting of SHAP to fix the number of genes for explainability at 20. We also performed statistical analysis based on the outputs of BAITSAO to discover the drug combination with the largest range of synergistic targets. The details of our approach are provided in the Methods section.

By collecting gene expression profiles of cell lines [45], we studied the explainability of BAITSAO for DEXAMETHASONE (drug)-DINACICLIB (drug) across different cell lines. In Figure 3 (b), we visualize the importance of different genes. The gene VIM was top-ranked by the average importance, and VIM is known as important for various cancers from pan-cancer analysis [46]. Moreover, we note that the genes with

high importance did not match the targeted genes of these two drugs according to DGIdb [47]. Therefore, the genes associated with drug synergistic effect may not be the same as the target genes of individual drugs. We conducted three experiments to further investigate the contributions of the selected genes.

We first separated the samples into two groups based on the existence of the synergistic effect and performed DEG analysis using DESeq2 [48, 49] between two groups of cell lines. We present the adjusted p-values using Benjamini-Hochberg for the selected genes in Figure 3 (b). Genes SPON2, HMCN1, and BMP4 listed in this figure were significant DEGs. Our selected genes had significant overlap with DEGs (Fisher's exact test p-value=0.0062). Moreover, these genes had relatively lower expression levels with synergistic effect, which matched the distribution of their SHAP values (enriched in the negative values).

We list the ranks of the selected genes based on their variances in Figure 3 (b). The top five ranked genes had relatively greater variances, suggesting that the genes we selected characterize the heterogeneity from both cell lines and the drug synergistic effect. We further performed enrichment analysis based on Gene Ontology (GO) [50] for biological pathways and Molecular Signature Database (MsigDB) [51] for cancer-specific signals based on this set of genes, with results shown in Extended Data Figures 4 (a) and (c). These enriched pathways represent important biological processes and cancer-specific signals. These results suggest that our method may uncover the heterogeneity in the drug synergy prediction process. We summarize our results for the single cell line with the same drug combination in Appendix A. The plots for important genes across different cell lines can be found in Extended Data Figure 13. The test statistics used in this section are given in Supplementary file 2.

We further investigated the drug combination that showed synergistic effects on the largest number of cell lines. We first plot the probabilities of all drug-cell line combinations to be classified as samples with synergistic effects in Figure 3 (c). This figure shows that the distribution of such probability is different under different synergistic labels. We performed the Rank-sum test [52] for these two sets of probabilities and their difference is significant (p-value¡2.22e-308). Therefore, our model can uncover the relationship between input features and the synergistic effect. Moreover, we ranked the drug combinations based on the number of cell lines predicted to have synergistic effects in descending order. We computed the Pearson correlation coefficient [52] between the count value based on predicted labels and observed labels, summarized in Figure 3 (d). Based on this figure, the count values based on the predicted labels had a strong positive correlation with those based on the real labels, thus our model can also be used to identify the drug combinations with the most synergistic targets given a set of cell lines and cancer types used in our experiments. We also highlight the drug combination L778123 and MK-8669 that has the largest number of targeted cell lines with synergistic effect in Figure 3 (d). Therefore, BAITSAO can capture the variance of different drug combinations across cell lines, offering a novel option for selecting effective drug combinations.

Statistics of pre-training datasets. Here we summarize the statistics and properties of our pre-training datasets for BAITSAO. We collected information from DrugComb [19], which is known as the largest database containing synergistic effect

Fig. 3 Results of evaluations for model structure and explainability. (a) Evaluations for BAITSAO and other methods. Each panel represents one metric with two datasets. The ranks of methods are averaged by datasets. The explanations of datasets D1-D3 are summarized in the Methods section. (b) The explainability of BAITSAO for the combination DEXAMETHASONE (drug)-DINACICLIB (drug) for different cell lines. We also list the ranks based on variance (HVG rank) and the adjusted p-value based on DESeq2 analysis results for each gene. The genes with adjusted p-value smaller or close to 0.05 are boldfaced. (c) The violin plot for the outputs of BAITSAO (Probability) across the synergistic labels. We also present the p-value in this figure. (d) The rank-based plot between the number of drugs-cell line combinations with synergy (Count) and the index of drug combination (Index of drug combination). The index is ranked by the value of Count. We present the Pearson correlation (corr) and p-value in this figure.

information for drug pairs with different cell lines. We downloaded the updated version of DrugComb and removed the missing value or single-drug information. The major statistics of DrugComb are summarized in Figure 4, whose (a) represents the total number of *drug-cell line* combinations by tissue types and Figure 4 (b) represents the total number of *cell lines* by the type of tissues from DrugComb. Most of the drugs presented here were analyzed using cells from skin, lymphoid, and/or lung. These tissues are important for maintaining normal physiological activity in the human body. In total, DrugComb collects more than 700,000 available combinations. As shown in Figure 4 (c), the distribution of the synergy scores is not balanced, with a large number of combinations having low synergy scores. We further plot the Half Maximal Inhibitory Concentration (IC_50) for all drugs in Figure 4 (d) with a similar distribution to the synergy score. We illustrate the non-linear relationship between single drug IC_50 and synergy score in Figure 4 (e). Therefore, fitting non-linear models like neural networks may help the synergy prediction task. Finally, Figure 4 (f) shows the overlap of combinations by tissues, where most tissues have low overlap, and thus the pre-training dataset has information from diverse tissues. We plot the embeddings for drugs and cell lines in the pre-training dataset colored by clusters from Leiden [53] in Extended Data Figures 5 (a) and (b). The items in the same Leiden cluster can be treated in similar context of embeddings with functional information, so we can visualize the functional similarity of different drugs and cell lines through embeddings. Since our pre-training dataset was published in June 2021 and GPT 3.5 collected data for pre-training until Sep 2021, considering the time needed for pre-training a LLM, we believe that the data from DrugComb were precluded in GPT 3.5.

Pre-trained BAITSAO contributes to drug synergistic effect prediction under the multi-task condition. Here we investigated and pre-trained BAITSAO based on the optimal model structure. Specifically, we extended the model structure with a multi-task learning framework. By pre-training BAITSAO with large-scale synergy datasets, BAITSAO is able to predict both single drug inhibition and drug synergistic effect. For drug pairs, we expect to predict both drugs' inhibition, thus we have a total of four tasks inspired by the pre-training datasets, including the regression task for synergy prediction, the classification task for synergy prediction, and regression tasks for single-drug inhibition of each drug in the drug pairs. For the regression task of synergy prediction, we only considered predicting the synergy score under the Loewe setting because we show that the synergy scores computed based on other methods are positively correlated with the Loewe score [54] in Extended Data Figure 6, and literature [14, 24] suggests using the threshold for generating a classification task from the Loewe score. For other synergy scores including Zip score [55], HSA score [56], and Bliss score [57], we pre-trained specific models and restored the pre-training weights. Instead of using the simple average of loss functions from different tasks during the training process, we introduced the Uncertainty Weighting (UW) method [58] advocated by the performance evaluations of different multi-task learning strategies from [59] and improved the numerical stability and the validation strategy of this method.

We first determined the tasks that can help each other in the multi-task learning framework by constructing the Help-Harm matrix. We sampled 1% of the pre-training

Fig. 4 Statistics of the pre-training dataset from DrugComb. (a) The barplot for the number of *drug-cell lines* combinations by different tissues. (b) The barplot for the number of *cell lines* by different tissues. (c) The histogram for the distribution of synergy score computed based on Loewe [54]. The x-axis is transferred into log scale. (d) The histogram for the distribution of single-drug IC_50 levels. The x-axis is transferred into log scale. (e) 3D plot for the relation between single-drug IC_50 levels and synergy score. (f) The heatmap for the overlap of combinations across different tissues.

dataset and trained task-specific models as well as multi-task models with paired tasks, and constructed the Help-Harm matrix shown in Figure 5 (a). According to this figure, joint training always boosts the classification task, while joint training with the classification task can help predict the synergy scores as well as inhibition levels for a single drug. Moreover, the relative inhibition (RI) information from one of the drugs in drug pairs did not show a significant contribution to other tasks, and incorporating this information reduced performance for the classification task. Since we had RI levels for both drug pairs, we removed the information of RI_col in the training process, and collected three tasks in the pre-training stage. After finishing pre-training based on the sampled and full datasets, we plot the metrics for comparing the performance between BAITSAO under the STL framework and our final MTL framework in Figure 5 (b). MTL can improve the performance of BAITSAO for solving all regression-based tasks. We show the outputs from the hidden layers of BAITSAO by ground truth synergistic labels and predicted synergistic labels in Extended Data Figures 7 (a) and (b). According to these two figures, the learned drug embeddings for drugs with no synergistic effect tended to be co-embedded. Therefore, BAITSAO with the MTL framework is reasonable and superior in drug synergy analysis. Finally, we consider the generalization ability of BAITSAO with pre-trained weights. We conducted experiments based on three datasets we used in the subsection *Selection of the model structure by evaluation without pre-training* and visualize the results in Figure 5 (c). We report the metrics based on five-fold cross-validation results. According to this figure, BAITSAO with the pre-training design after fine-tuning (BAITSAO-FT) is comparable or better for the regression and classification tasks, compared with BAIT-SAO without pre-training (BAITSAO-ZS). Moreover, our fine-tuning stage used fewer epochs and we froze the shared layers during the fine-tuning process, thus our fine-tuning approach was more efficient. We note the potentials of BAITSAO under the zero-shot learning framework for solving this task. For example, BAITSAO-ZS showed a high ACC score in the evaluation based on D1. Moreover, for the metrics related to classification, BAITSAO-ZS had results higher than 0.5, and thus BAITSAO under the zero-shot learning framework was better than random guessing. We also performed Rank-sum tests [52] between the pre-training dataset and fine-tuning datasets and the results are shown in Extended Data Figure 8, which demonstrated that samples in the fine-tuning datasets satisfied the OOD cases. In summary, the combination of MTL and the pre-training process can improve the performance of BAITSAO on tasks related to drug synergy analysis.

We then predicted the synergistic effect for the combination of three drugs (tri-drugs) and one cell line, with two examples shown in Figures 5 (d) and (e). The drug names and cell line names were extracted from DrugCombDB [61], which did not provide the observed synergistic information for the existing combinations. To enhance the reliability of our prediction results, we relied on Monte Carlo Dropout (MC Dropout) [62, 63] and ran inference 100 times to generate the prediction interval of different drug combinations. According to [64], MC Dropout was the only method considered in this benchmarking paper to estimate the mean and variance without extra hyper-parameters. Our full prediction results are summarized in Supplementary file 3. Here we compared the difference between the two combinations by changing the

Fig. 5 Results under the multi-task learning framework. (a) The Help-Harm matrix for different combinations of tasks. The values indicate the percentage (unit: %) of improvement using multi-task learning compared to single-task learning (STL) defined by the tasks in rows. The columns represent the paired tasks. We boldfaced blocks with increments larger than 0.5%, which is a threshold reported in [60] as acceptable improvement and half of the natural threshold 1%. (b) Comparisons for the results under MTL and STL. The metric for regression tasks, including Loewe and RI_row, is PCC. The metric for the classification task, including Classification, is ROCAUC. (c) Comparisons for the results under different training settings. Here *BAITSAO-FT* represents that we fine-tuned the pre-trained model, *BAITSAO-ZS* represents that we applied the pre-trained model for these tasks under zero-shot learning framework, and *BAITSAO-FS* represents that we did not use the pre-trained weights for these tasks. Here FT means fine-tuning, ZS means zero-shot learning and FS means from scratch. We included four metrics across three datasets for comparisons. (d) The first example of tri-drug cases for drug synergy prediction with BAITSAO. (e) The second example of tri-drug cases for drug synergy prediction with BAITSAO.

third drug. We found that the combination with I-BET151 was predicted to have a positive sign in the synergy score under Loewe, while the combination with I-BET was predicted to have a negative synergistic effect. As an explanation, although these two drugs can both combine with bromodomain and extra terminal domain (BET) with the same major targeted proteins [65, 66], I-BET151 was reported as an optimized version with excellent BET target potency and selectivity [66]. Therefore, we expected I-BET151 to have better efficacy and thus a higher synergy score. Another example from Figure 5 (e) presents the difference between PF562271 [67] and Saracatinib [68] as a third drug under the cell line MZ7-mel. The combination with PF562271 had a higher predicted synergy score compared with Saracatinib, which was supported by the experimental results from [69] as PF562271 generated higher growth inhibition. Therefore, the results from BAITSAO can help researchers to optimize drugs with higher synergistic effect and better clinical outcomes.

Sensitivity analysis. Here we investigated the sensitivity of model training based on the statistics we collected. Figure 6 (a) displays the ablation results by considering different types of embeddings as well as different types of combination rules for embeddings as model input. *BAITSAO* denotes our final choice for pre-training and fine-tuning. *BAITSAO-v3* denotes that we utilized the updated embeddings from OpenAI in 2024 [70]. *Mean* denotes that we took the mean of drug embeddings and cell embeddings as input for training. *Sum* denotes that we took the sum of drug embeddings and cell embeddings as input for training. *SentStack* denotes that we stacked the descriptions of different drugs and used the modified description to generate drug embeddings, and then stacked such drug embeddings with cell-line embeddings. *Stack* represents that we stacked the drug embeddings and cell embeddings by rows. *Rdkit* [34, 35] represents that we generated embeddings from Rdikt with SMILES and stacked the embeddings with cell embeddings from LLMs. This figure shows that averaging the drug embeddings and stacking them with cell embeddings by rows generated the best performance for all tasks. These results suggest the most effective way to incorporate embeddings from different sources to construct the datasets for training and testing. Moreover, our approach strikes a good balance between efficiency and performance. According to Figure 6 (b), the running time of BAITSAO without pre-training was significantly lower than the classical methods DeepSynergy and SVM for drug synergistic effect prediction. Moreover, the pre-trained BAITSAO with the fine-tuning framework converges at a much faster rate, thus pre-trained BAITSAO achieved an even faster running speed by comparing with MARSY and DeepDDs. Therefore, our training framework strikes a good balance between runtime and model performance. Both pre-training and fine-tuning stages can be finished with only one GPU, presenting no hardware barrier to deploy BAITSAO.

We performed ablation tests for the MTL strategy, shown in Extended Data Figure 9 for ablation of methods and Extended Data Figure 10 for ablation of task-specific layers. We compared the gradient matching-based approaches including PCGrad [71], GradVac [72], CAGrad [73], Nash-MTL [74] and the linear MTL framework LinearMTL [75, 76] with our revised UW approach and found that our choice generally had comparable or better results, especially for the classification task. Moreover, LinearMTL performed much worse than deep learning based methods on the regression

type tasks. Therefore, we chose the revised UW as the method for the pre-training stage. Moreover, our final choice with one task-specific layer for each task had the best overall performance, and increasing the number of layers required more computing resources, thus we chose our design shown in Figure 1 (c).

We also analyzed the relation between the size of the training dataset and model performance. We adjust the proportion we used for model training and visualize the relation between proportion and metrics in Figures 6 (c) for regression and (d) for classification. From these figures, a larger proportion tended to increase the model performance, with its limit for proportion ≥ 0.9 for these two tasks. Moreover, using only 0.1% training dataset to train a model for a classification task can still generate relatively high ROCAUC, thus the classification task may not be difficult for BAITSAO.

In Figures 6 (e) and (f), we examined the scaling law [77, 78] of BAITSAO as a foundation model. We adjusted the layer width of our model and plotted the relation between the layer width in the hidden layer and model performance for the regression task and the classification task. These figures show that we can model the relation between model parameters and model performance to predict performance, where more parameters lead to better performance. Therefore, the performance improvement of our model with scaling can be explained by the scaling law, and our model has good scalability. Our findings can help us understand the model training process in a better approach and determine the optimized source allocation of a fixed compute budget. For example, for machines that cannot support the version of BAITSAO with layer width as 10240, the version of BAITSAO with layer width as 4096 can also have acceptable performances and can be considered to deploy.

Fig. 6 Statistics of model training. (a) Ablation test results for BAITSAO with different input formats. (b) The comparison of running time for different methods. We highlight the running time of BAITSAO and use the regression task as an example. (c) Plot for the proportion of training dataset and PCC for BAITSAO under the regression task. We reported $(\mu - \sigma, \mu + \sigma)$ for each proportion, where μ represents the mean and σ represents the standard deviation. (d) Plot for the proportion of training dataset and ROCAUC for BAITSAO under the classification task. We reported $(\mu - \sigma, \mu + \sigma)$ for each proportion. (e) Plot for layer width and PCC for BAITSAO under the regression task. We reported $(\mu - \sigma, \mu + \sigma)$ for each proportion. (f) Plot for layer width and ROCAUC for BAITSAO under the classification task. We reported $(\mu - \sigma, \mu + \sigma)$ for each proportion.

3 Discussion

Predicting drug synergistic effect is important for drug development and patient treatment. In the past, limited by available experimental data, information on drugs/cell

lines, and pipelines to predict drug synergistic effect, there are few approaches to predicting drug synergistic effect for general use. With the help of large-scale drug synergy information databases, LLMs, and an MTL framework, we introduced BAITSAO as a FM with a general pipeline for drug synergistic effect prediction as well as single-drug inhibition prediction. BAITSAO optimized the network architecture through comprehensive benchmarking analysis and was pre-trained based on the latest large-scale databases. It achieved top-tier performance in both regression tasks and classification tasks for drug synergistic effect prediction.

There are two major contributions of our work. Firstly, we presented a unified pipeline to construct datasets for synergistic effect analysis for both drugs and cell lines based on the embeddings from LLMs, thus we mitigated the difference caused by aliases for drugs and cell lines of different datasets. We demonstrated that the embeddings contained functional information for drugs and cell lines. We proposed a new design to construct training datasets, thus we only need to utilize the overlapped information across datasets for drug synergy analysis. Secondly, we pre-trained a FM with a MTL framework for drug synergy analysis and single-drug inhibition analysis supported by rigorous task-selection steps. We demonstrated that BAITSAO benefited from the pre-training process and had good generalization ability with fine-tuning in fewer steps compared with the training process from scratch. Moreover, pre-trained BAITSAO showed its potential as a good zero-shot reasoner for drug synergy prediction under the classification settings. Therefore, we overcame the generalization issue in previous work based on transfer learning [20] and proposed a new avenue for the construction of FM for drug synergy analysis.

We conducted a sensitivity analysis to offer guidance for future model deployment. We showed that our current hyper-parameter settings and data construction methods are the optimal choices by hyper-parameter tuning and ablation tests. We also analyzed the relation between the proportions of data we used for training and model performance. While increasing training data proportions tended to improve prediction, BAITSAO performed well for the classification task for small data scales. Finally, we investigated the scaling law of BAITSAO as a FM and showed that the model performance is predictable and we could increase the model performance by scaling up BAITSAO for drug synergy prediction.

In conclusion, we have developed BAITSAO, explainable FM for drug synergy prediction, and demonstrated the superiority of BAITSAO over other methods by comprehensive benchmarking analysis and rigorous sensitivity analysis. We hope that BAITSAO can help researchers to better understand the process of drug synergistic effect prediction and further help in optimizing drug structures for drug design and discovering novel drug combinations with synergistic effects for clinical usage. In the future, we plan to incorporate more updated drug synergy databases to keep this model updated, and we also plan to combine this model with information from genomics including single-cell data [79] and genome-wide association studies (GWAS) [80].

4 Methods

Problem definition. In this manuscript, we intend to construct a dataset $\mathcal{D} = (X, Y)$ and pre-train a model known as $\mathcal{M}$ for the prediction of values in $Y^{n \times t}$, where n represents the number of combinations between drug pairs and the cell line, and t represents the number of tasks. Here $X^{n \times p}$ represents the feature space with n samples and p features. We then split the dataset $\mathcal{D}$ into $\mathcal{D}_{train} = (X, Y)_{i=1}^{n_0}$ for training and $\mathcal{D}_{val} = (X, Y)_{i=1}^{n_1}$ for validation. Our target is to train a model $\mathcal{M}^*$ based on $\mathcal{D}_{train}$ and then select the optimal model based on $\mathcal{D}_{val}$. That is,

$$\theta^* = argmin_\theta \mathcal{L}_m(\mathcal{M}(X_{val}, \theta), Y_{val}),$$

where $\mathcal{M}(, \theta)$ represents the pre-trained model with parameter θ, and θ^* represents the optimal model parameters. $\mathcal{L}_m$ represents multi-task learning loss. After obtaining the optimal model, we apply the model $\mathcal{M}^*(, \theta^*)$ for a new dataset containing out-of-distribution (OOD) data, known as $\mathcal{D}_{test}$.

Construction of pre-training datasets and testing datasets. One major contribution of our work is to unify the features we need to predict the drug-related information for both the synergistic effect and inhibition effect. We at least need the names of drugs and cell lines. Considering we have a drug pair (d_1, d_2) and a cell line (c_1), our idea is to generate the description of both drugs as $W(d_1), W(d_2)$ and the cell line as $W(c_1)$ based on LLMs such as GPT 3.5, and then utilize the embeddings tool of GPT 3.5 to transfer the text description into embeddings with e dimensions. Therefore, our final sample $x \in X$ is defined as:

$$x = AVG(emb(W(d_1)), emb(W(d_2))) || emb(W(c_1)) || \# d,$$

where $AVG()$ represents the functions to compute the mean of the given variables, and $emb()$ is the function to obtain the embeddings of the input. $\# d$ represents the number of drugs we used, which can be encoded as embeddings [81]. We take the unbiased estimation of the drug combination in the feature levels by computing the average value of embeddings, and we show that this approach works better than other types of feature integration in the sensitivity analysis section of the manuscript. Notably, this approach also scales for more drug combinations. Considering the case of k drugs with the cell line c_i, we define one sample $x \in X$ as:

$$x = AVG(emb(W(d_1)), ..., emb(W(d_k))) || emb(W(c_i)) || k.$$

Therefore, for an arbitrary input dataset with feature space X containing drug information and cell-line information, we can transfer the samples in the given dataset from the text space to the numerical space, thus we unify the input data format for this task. Furthermore, to predict the drug synergistic effect, we consider both regression and classification. In the case of regression, we intend to predict the specific synergy score of samples. To compute the synergistic effect based on IC_50 information, under different rules, we can have different scores. Here we consider four methods to model the synergy scores, known as HSA, Bliss, Loewe and ZIP. If we consider N drugs with

multi-drug combination effect as $E_{A,B,...,N}$ and we intend to compute the synergy scores $S_{HSA}, S_{Bliss}, S_{Loewe}$, and S_{ZIP}, according to [5], we have:

$$S_{HSA} = E_{A,B,...,N} - \max\left(E_A, E_B, \ldots, E_N\right).$$

$$S_{Bliss} = E_{A,B,...,N} - \left(E_A + E_B + \ldots + E_N - E_A E_B \right.$$
$$\left. - E_A E_N - E_B E_N - \ldots - E_A E_B \ldots E_N\right).$$

$$S_{Loewe} = \frac{a}{E_A} + \frac{b}{E_B} + \ldots + \frac{n}{E_N}.$$

$$S_{ZIP} = E_{A,B,...,N} - \left(\frac{\left(\frac{x_A}{m_A}\right)^{\lambda_A}}{1 + \left(\frac{x_A}{m_A}\right)^{\lambda_A}} + \frac{\left(\frac{x_B}{m_B}\right)^{\lambda_B}}{1 + \left(\frac{x_B}{m_B}\right)^{\lambda_B}} + \ldots \right.$$
$$+ \frac{\left(\frac{x_N}{m_N}\right)^{\lambda_N}}{1 + \left(\frac{x_N}{m_N}\right)^{\lambda_N}} - \frac{\left(\frac{x_A}{m_A}\right)^{\lambda_A}}{1 + \left(\frac{x_A}{m_A}\right)^{\lambda_A}} \frac{\left(\frac{x_B}{m_B}\right)^{\lambda_B}}{1 + \left(\frac{x_B}{m_B}\right)^{\lambda_B}}$$
$$- \frac{\left(\frac{x_A}{m_A}\right)^{\lambda_A}}{1 + \left(\frac{x_A}{m_A}\right)^{\lambda_A}} \frac{\left(\frac{x_N}{m_N}\right)^{\lambda_N}}{1 + \left(\frac{x_N}{m_N}\right)^{\lambda_N}}$$
$$- \frac{\left(\frac{x_B}{m_B}\right)^{\lambda_B}}{1 + \left(\frac{x_B}{m_B}\right)^{\lambda_B}} \frac{\left(\frac{x_N}{m_N}\right)^{\lambda_N}}{1 + \left(\frac{x_N}{m_N}\right)^{\lambda_N}} - \ldots$$
$$\left. - \frac{\left(\frac{x_A}{m_A}\right)^{\lambda_A}}{1 + \left(\frac{x_A}{m_A}\right)^{\lambda_A}} \frac{\left(\frac{x_B}{m_B}\right)^{\lambda_B}}{1 + \left(\frac{x_B}{m_B}\right)^{\lambda_B}} \cdots \frac{\left(\frac{x_N}{m_N}\right)^{\lambda_N}}{1 + \left(\frac{x_N}{m_N}\right)^{\lambda_N}} \right).$$

Here we have $E_A, E_B, ..., E_N$ as measured responses of different drugs, and $a, b, ..., n$ represent the doses of the single drugs we need to produce the combination effect. Moreover, to compute S_{ZIP}, we have x_N as the dose of drug N fitted with the four-parameter log-logistic model, and m_N represents the dose we need to produce the half-maximum effect (IC_50). We also have λ_N as the shape parameter to indicate the slope of the dose-response curve. In the MTL case, we consider S_{Loewe} for the targets of regression. We also pre-train models to predict the other three scores. All of the synergy scores are extracted from the database of DrugComb.

In order to characterize the inhibitory effects of individual drugs, we introduce the RI score in the prediction task. RI score is the normalized area under the $log_{10}-$transformed dose-response curves. RI scores of all drugs are also extracted from the database of DrugComb.

In the case of classification, we intend to predict whether the given drug pair has a synergistic effect under a specific cell line, which is a binary classification problem. To construct the dataset for this task, we set the threshold of S_{Loewe} to binarize the synergistic effect of different drug combinations. Since not all of the testing datasets

in the real world contain data for both regression and classification, thus introducing a classification task is meaningful.

Investigation of embeddings. We set up different methods to ensure that embeddings from LLMs contain the necessary information to describe the properties of drugs and cell lines. Here we generate text descriptions and embeddings for drugs and cell lines from the dataset used by Deepsynergy (D1). We check the correctness of the all descriptions and the similarity of 10 sampled embeddings across different drugs to evaluate the correctness. Moreover, we change the random seed to generate different descriptions as well as embeddings to check the variance of drug embeddings from the same drug. We also record the description of cell lines in Supplementary file 1. Furthermore, we modify CPA to predict gene expression under different perturbations enhanced by drug embeddings from LLMs. In this step, we replace the original drug embeddings used in the CPA with our new embeddings. This approach allows us to check the correctness of embeddings from the application perspective. We use R^2 scores to evaluate the performances. To compute the R^2 score, we have the ground truth synergy score y and predicted synergy score $\hat{y}$ and follow its definition:

$$R^2 = 1 - \frac{\sum_i (y_i - \hat{y}_i)^2}{\sum_i (y_i - \bar{y})^2},$$

where $\bar{y}$ means that we compute the average value of the input variable y. R^2 represents the explanation of independent variables for the dependent variable. Higher R^2 means better model performance.

Therefore, our assessment of the quality of embeddings takes into account meanings, variance, and applications.

Hyper-parameter searching. We summarize the search space for hyper-parameters of each method in Table 1. The best hyper-parameter setting is determined by the performance of models based on the testing dataset.

Table 1 Hyper-parameter search space for each method ranked in alphabetical order.

Methods	Searching space
BAITSAO	lr:[1e-5,1e-4]; Dropout:[0.1,0.3]
BERT	epochs:[5,10]; lr: [1e-5,1e-4]
DeepDDs	Optimal hyper-parameters from [18]
DeepSynergy	Optimal hyper-parameters from [14]
Lasso	alpha:[1,10]
MARSY	Optimal hyper-parameters from [17]
SVM	C:[1,5]
TabNet	n_steps:[1,5]; n_a:[8,64]; n_d:[8,64]; gamma:[1.1,1.5]
TreeComb	max_depth:[10, 100]; n_estimators:[10,50]; min_child_weight:[1, 3]

Here lr means learning rate, Dropout means dropout rate (the ratio of neurons we intend to close during the training process), max_depth means the maximal depth for tree-based models, n_estimators means the number of estimators for tree-based models, min_child_weight means the minimal weights of child nodes in tree-based models,

C means the regularization weight for SVM, n_steps means the number of decision steps in the model architecture, n_a means the width of the attention embedding for each masked choice, n_d means the width of the prediction layer, gamma means the coefficient for the feature re-usage in the masking process, epochs mean the number of epochs we used to train the model, alpha represents the regularization coefficient for Lasso. We present the results under different hyper-parameters for BAITSAO in Extended Data Figures 11 (a) and (b). We find that lr plays a more important role in the training process while adjusting the dropout rate does not affect the model performance much.

Selection of model architecture. After setting up the pre-training dataset, we seek a suitable model architecture. Since deep neural networks (DNNs) related methods have shown impressive performance as a base model for large-scale FMs [82, 83], we construct the pre-training architecture of BAITSAO based on DeepSynergy. To assess the strength of our model architecture, we remove the pre-training step and compare BAITSAO with other methods for both the regression task and classification task with three different datasets. We also determine the hyper-parameters of model training in this stage. The superiority of BAITSAO is shown in the Results section, and we expect to see its similar performance at both the pre-training and fine-tuning stages.

In the model architecture selection stage, we utilize Adam [84] as the optimizer and ReduceLROnPlateau [81] as the learning rate scheduler. The starting learning rate for D1 and D3 is 1e-5, while it is 1e-4 for D2. The dropout rate is 0.2, and the patience for the scheduler is 10. Our patience for early-stopping step is 100, and the maximum number of epochs is 1000.

Explainability. The design of BAITSAO allows us to characterize the relevance between the specific gene and drug combinations across different cell lines. To perform this analysis, the input format of one combination becomes:

$$x' = AVG(emb(W(d_1)), ..., emb(W(d_k)))||exp(c_i)||emb(W(c_i))||k,$$

where $exp(c_i)$ represents the gene expression profile for the cell line i. After the training process, we can extract the importance of different genes based on SHAP. For gene j, its importance for the synergistic effect of drug combinations $(d_1, ..., d_k)$ for cell line c_i can be calculated as:

$$I_j = ShapValue(\mathcal{M}, x'),$$

where I_j represents the importance and x' was defined above. $ShapValue()$ is a function to compute the importance with model $\mathcal{M}$ and input x'. Here larger I_j represents more importance in the prediction process.

We select 1000 highly-variable genes for the analysis of explainability. This number is determined by adjusting the number of genes to achieve the best model performance. Our tuning results are shown in Extended Data Figure 12.

For the bulk RNA-seq datasets of different cell lines, we use DESeq2 to identify DEGs by comparing groups with and without predicted drug synergistic effects.

For the two scRNA-seq datasets used for validating our selected genes, we follow the pre-processing pipeline of Scanpy [85] and run the Wilcoxon Rank-sum test to access the list of DEGs.

Pre-training BAITSAO under the multi-task learning framework. Here we explain our settings for the multi-task learning framework. After filtering tasks based on the constructed help-harm matrix, we consider three tasks: 1. Prediction of S_{Loewe} as a regression task. 2. Prediction of RI for one drug as a regression task. 3. Prediction of drug synergistic effect as a binary classification task. Therefore, we have two regression tasks and one classification task, and their loss functions are represented as $\mathcal{L}_1, \mathcal{L}_2,$ and $\mathcal{L}_3$. Traditionally, we construct the final loss function as a linear combination:

$$\mathcal{L}_m = \sum_{i=1}^{n_t} w_i \mathcal{L}_i,$$

where w_i represents the pre-defined weights for the loss function $\mathcal{L}_i$ and $n_t = 3$. However, determining the values of the weights is difficult. Moreover, it is a strong assumption that the weights do not change during training is also a very strong assumption. Therefore, we introduce the uncertainty of loss function in this process and make the weights learnable. Typically, by choosing mean squared error (MSE) as the loss function in the training process for the regression task, we have the equivalent maximum likelihood framework of a Gaussian distribution for prediction output y and model $\mathcal{M}$. Therefore, the log-likelihood of the regression task can be represented as:

$$log(p(y|\mathcal{M}(x,\theta))) \propto -\frac{1}{2\sigma^2}||y - \mathcal{M}(x,\theta)||^2 - log\sigma,$$

where the uncertainty is defined as σ, and x represents model input. Similarly, for a classification problem, we can represent the log-likelihood based on a Softmax function, that is:

$$log(p(y|\mathcal{M}(x,\theta))) = log(Softmax(\frac{1}{\sigma^2}\mathcal{M}(x,\theta))),$$

where $Softmax(x)_i = \frac{exp(x_i)}{\sum_j^p exp(x_j)}$, and p represents the length of x.

Therefore, the final loss function can be represented as maximizing the joint distribution of three tasks. In the validation stage, we minimize the maximal term in the loss function group rather than the original weighted loss function design from UW. We also add a constant term ϵ to ensure the numerical stability, so our final loss function is:

$$\mathcal{L}_m = -log(p(y_1, y_2, y_3|M(x,\theta)))$$
$$\approx \frac{1}{2\sigma_1^2 + \epsilon}\mathcal{L}_1(y_1, M(x,\theta)) + \frac{1}{2\sigma_2^2 + \epsilon}\mathcal{L}_2(y_2, M(x,\theta))$$
$$+ \frac{1}{\sigma_3^2 + \epsilon}\mathcal{L}_3(y_3, M(x,\theta)) + log(\sigma_1\sigma_2\sigma_3).$$

In the pre-training stage, we utilize Adam [84] as optimizer and ReduceLROn-Plateau [81] as the learning rate scheduler. The starting learning rate is 1e-4, the dropout rate is 0.2, and the patience for the scheduler is 100. Our patience of early-stopping step is 500, and the maximum number of epochs is 1000. The number of combinations we used for pre-training is 739,652, including 4268 unique drugs and 288 unique cell lines.

After finishing the pre-training step, we test the model performance on the testing datasets under both the zero-shot learning case and the fine-tuning case with a parameter-freezing design. We also extend the prediction of the synergistic effect to the case of n ($n \geq 3$) drug combinations. Finally, we include a tutorial in our code repository for both the fine-tuning approach and the zero-shot inference approach.

Zero-shot query and multi-drug prediction. Our model is capable of zero-shot synergy effect prediction. By transferring the knowledge and information of drugs and cell lines into embeddings through GPT 3.5 and the embedding layer, users can generate embeddings of arbitrary combinations as input for querying the synergy effects with a pre-trained BAITSAO.

For the combinations with three or more drugs, we directly generate the synergy score under the pre-trained model with the zero-shot learning framework. The three-drug case we used in the main text is from a known database, while it is possible to explore combinations with a larger number of drugs as long as the combinations are practical and meaningful. To access the determined predicted value, we do not use the dropout layers in the testing process. To access the predicted value with uncertainty, we keep the dropout layers in the testing process and repeat the prediction process for 100 times to access the estimation of mean and standard deviation for each combination. Such approach is known as MC Dropout.

We summarize the details of zero-shot query as a tutorial in our code repository.

Model evaluation. We consider four different metrics to evaluate the performance of different models for the drug synergistic effect prediction task, with two metrics for regression and two metrics for classification.

For the regression task, we consider two metrics: Pearson correlation coefficient (PCC) and Mean Squared Error (MSE).

1. PCC: Since we know the ground truth synergy score y and predicted synergy score $\hat{y}$, we can directly compute the PCC as:

$$PCC(y, \hat{y}) = \frac{COV(y, \hat{y})}{\sigma(y)\sigma(\hat{y})},$$

where $COV()$ is the function to compute the covariance of two variables, and $\sigma()$ is the function to compute the standard deviation of the input variable. Higher PCC means better model performance.

2. MSE: To compute the mean squared error, we have the ground truth synergy score y and predicted synergy score $\hat{y}$ and follow its definition:

$$MSE = \frac{1}{n} \sum_{i=1}^{n} (y_i - \hat{y}_i)^2,$$

where i represents the index of samples, and lower MSE means better model performance.

For the classification task, we consider two metrics: Area under the ROC Curve (ROCAUC) and Accuracy (ACC).

1. ROCAUC: To compute this metric, we construct the relation between the true-positive rate and the false-positive rate with 0.5 as the probability threshold. Such relation can be reflected in the ROC curve. We then compute the area under the ROC curve, and this area represents ROCAUC. Higher ROCAUC means better model performance.

2. ACC: To compute this metric, we have the ground truth synergistic effect condition $y^{n \times 1}$ and predicted binary value $\hat{y}$, we then compute the ACC as:

$$ACC = \frac{\sum_{i=1}^{n} \mathbb{1}_{y_i = \hat{y}_i}}{n},$$

where $\mathbb{1}_{y_i = \hat{y}_i}$ is a indicator function and only takes 1 when $y_i = \hat{y}_i$. Higher ACC means better model performance.

We report the mean and standard deviation of these metrics by using five-fold cross-validation for each dataset.

Overview of other methods. In this section, we summarize the benchmarking methods used in our work. These methods (ranked in alphabetical order) include:

- BERT: BERT is a pre-trained bi-directional transformer for language understanding. For this model, we construct the training datasets and testing datasets directly from drug descriptions and cell-line descriptions. The problem is then formalized as Question-answering case for both classification and regression tasks.
- DeepDDs [18]: DeepDDs is a Graph Neural Network (GNN)-based method for drug synergistic effect prediction. This method can only handle the classification task. The training dataset of DeepDDs is constructed base on features of drugs as graphs from chemical information and gene expression levels from cell lines.
- DeepSynergy [14]: DeepSynergy is a DNN-based method for drug synergistic effect prediction. This method can handle both the regression task and the classification task, by changing the loss function and the activation function of the last network layer. The training dataset of DeepSynergy follows its default mode, including features of drugs from chemical information and cell-line features from gene expression levels.
- Lasso [40, 43]: Lasso is a regularized regression method for drug synergistic effect prediction. This method can handle both the regression task and the classification task, by using the default mode or logistic regression mode with L1 penalty. The training dataset of Lasso is constructed based on the drug embeddings and cell-line embeddings from LLMs.
- MARSY [17]: MARSY is a DNN-based method with multi-task learning framework for drug synergistic effect prediction. This method can only handle the regression task. The training dataset of MARSY is constructed based on features of drugs from chemical information, gene expression levels from cell lines and tissue information.
- SVM [39, 40]: SVM is a machine learning method based on constructing decision-making boundaries for drug synergistic effect prediction. This method can handle both the regression task and the classification task, by using SVR or SVC. The training dataset of SVM is constructed based on the drug embeddings and cell-line embeddings from LLMs.

- TabNet [41]: TabNet is a DNN-based method with transformer architecture for drug synergistic effect prediction. TabNet combines the ideas from both neural network design and tree-model design. This method can handle both the regression task and the classification task, by changing the loss function and the activation function of the last network layer. The training dataset of TabNet is constructed based on the drug embeddings and cell-line embeddings from LLMs.
- TreeComb [15]: TreeComb is an explainable machine learning method based on XGBoost for drug synergistic effect prediction. This method can handle both the regression task and the classification task, by using XGBREGRESSOR or XGB-CLASSIFIER. The training dataset of TreeComb is constructed based on the drug embeddings and cell-line embeddings from LLMs.

Datasets preparation. We utilize public datasets from DrugComb v1.5 for pre-training. For the regression task, we have one dataset from DeepSynergy (as D1, which is processed in the original paper) using Loewe as the synergy score computation method. We also have one dataset from MARSY (as D2, which is processed in the original paper) using ZIP as the synergy score computation method. For the classification task, we have one dataset from DeepSynergy (as D1) using the Loewe synergy score with a threshold. We also have one dataset from DeepDDs with a known binary synergistic effect condition (as D3 [86]). For multi-drug synergistic effect inference, we utilize one dataset from DrugCombDB. Every dataset at least contains the names of drugs and cell lines.

5 Data availability

We do not generate new data in this research. We collect the information of downloading training dataset in Supplementary file 4.

6 Reproductivity and codes availability

We used the resources from the Yale High Performance Center (Yale HPC) and UCLA Computing Servers to conduct all of the experiments. Our maximum running time for each dataset was 24 hours and maximum RAM was 100 GB. The version of GPU we used is NVIDIA A5000 (24 GB) for fine-tuning and single task learning, and NVIDIA A100 (40GB) for pre-training. The codes of BAITSAO can be found in https://github.com/HelloWorldLTY/BAITSAO with MIT license. We will release the pre-training weights upon the publication of this work.

7 Acknowledgements

We thank Yijia Xiao for fruitful discussion about training the foundation model. We thank Wangjie Zheng, and Tianqi Chen for helpful discussion about designing drug embeddings. We thank Ning Sun, Xinyi Chen, Gefei Wang and Yingxin Lin for the suggestions about approaches to improve the experimental design.

8 Author contributions

T.L. proposed this study. T.L., T.C., and X.L. designed the model. T.L. ran all the experiments. T.L., X.L. and H.Z. wrote the manuscript. H.Z. supervised this study.

9 Ethics and Inclusion

Although BAITSAO is not biased on gender, races, and other factors, the users are solely responsible for the content they generate with models in BAITSAO, and there are no mechanisms in place for addressing harmful, unfaithful, biased, and toxic content disclosure. Any modifications of the models should be released under different version numbers to keep track of the original models related to this manuscript. The users must comply with the laws of the country in which they are located.

The target of current BAITSAO only serves for academic research. The users cannot use it for other purposes. Finally, we are not responsible for any effects produced by other users.

References

[1] Clercq, E.D.: The design of drugs for hiv and hcv. Nature reviews Drug discovery **6**(12), 1001–1018 (2007)

[2] Mokhtari, R.B., Homayouni, T.S., Baluch, N., Morgatskaya, E., Kumar, S., Das, B., Yeger, H.: Combination therapy in combating cancer. Oncotarget **8**(23), 38022 (2017)

[3] Al-Lazikani, B., Banerji, U., Workman, P.: Combinatorial drug therapy for cancer in the post-genomic era. Nature biotechnology **30**(7), 679–692 (2012)

[4] Holbeck, S.L., Camalier, R., Crowell, J.A., Govindharajulu, J.P., Hollingshead, M., Anderson, L.W., Polley, E., Rubinstein, L., Srivastava, A., Wilsker, D., *et al.*: The national cancer institute almanac: a comprehensive screening resource for the detection of anticancer drug pairs with enhanced therapeutic activity. Cancer research **77**(13), 3564–3576 (2017)

[5] Ianevski, A., Giri, A.K., Aittokallio, T.: Synergyfinder 2.0: visual analytics of multi-drug combination synergies. Nucleic acids research **48**(W1), 488–493 (2020)

[6] Law, M., Wald, N., Morris, J., Jordan, R.: Value of low dose combination treatment with blood pressure lowering drugs: analysis of 354 randomised trials. Bmj **326**(7404), 1427 (2003)

[7] Wood, K.B., Wood, K.C., Nishida, S., Cluzel, P.: Uncovering scaling laws to infer multidrug response of resistant microbes and cancer cells. Cell reports **6**(6), 1073–1084 (2014)

[8] Hetzel, L., Boehm, S., Kilbertus, N., Günnemann, S., Theis, F., *et al.*: Predicting cellular responses to novel drug perturbations at a single-cell resolution. Advances in Neural Information Processing Systems **35**, 26711–26722 (2022)

[9] Lotfollahi, M., Klimovskaia Susmelj, A., De Donno, C., Hetzel, L., Ji, Y., Ibarra, I.L., Srivatsan, S.R., Naghipourfar, M., Daza, R.M., Martin, B., et al.: Predicting cellular responses to complex perturbations in high-throughput screens. Molecular Systems Biology, 11517 (2023)

[10] Wilding, J.L., Bodmer, W.F.: Cancer cell lines for drug discovery and development. Cancer research **74**(9), 2377–2384 (2014)

[11] Ianevski, A., Giri, A.K., Aittokallio, T.: Synergyfinder 3.0: an interactive analysis and consensus interpretation of multi-drug synergies across multiple samples. Nucleic Acids Research **50**(W1), 739–743 (2022)

[12] Roemer, T., Boone, C.: Systems-level antimicrobial drug and drug synergy discovery. Nature chemical biology **9**(4), 222–231 (2013)

[13] Sun, W., Sanderson, P.E., Zheng, W.: Drug combination therapy increases successful drug repositioning. Drug discovery today **21**(7), 1189–1195 (2016)

[14] Preuer, K., Lewis, R.P., Hochreiter, S., Bender, A., Bulusu, K.C., Klambauer, G.: Deepsynergy: predicting anti-cancer drug synergy with deep learning. Bioinformatics **34**(9), 1538–1546 (2018)

[15] Janizek, J.D., Celik, S., Lee, S.-I.: Explainable machine learning prediction of synergistic drug combinations for precision cancer medicine. BioRxiv, 331769 (2018)

[16] Kuru, H.I., Tastan, O., Cicek, A.E.: Matchmaker: a deep learning framework for drug synergy prediction. IEEE/ACM transactions on computational biology and bioinformatics **19**(4), 2334–2344 (2021)

[17] El Khili, M.R., Memon, S.A., Emad, A.: Marsy: a multitask deep-learning framework for prediction of drug combination synergy scores. Bioinformatics **39**(4), 177 (2023)

[18] Wang, J., Liu, X., Shen, S., Deng, L., Liu, H.: Deepdds: deep graph neural network with attention mechanism to predict synergistic drug combinations. Briefings in Bioinformatics **23**(1), 390 (2022)

[19] Zheng, S., Aldahdooh, J., Shadbahr, T., Wang, Y., Aldahdooh, D., Bao, J., Wang, W., Tang, J.: Drugcomb update: a more comprehensive drug sensitivity data repository and analysis portal. Nucleic acids research **49**(W1), 174–184 (2021)

[20] Kim, Y., Zheng, S., Tang, J., Jim Zheng, W., Li, Z., Jiang, X.: Anticancer drug

synergy prediction in understudied tissues using transfer learning. Journal of the American Medical Informatics Association **28**(1), 42–51 (2021)

[21] Bommasani, R., Hudson, D.A., Adeli, E., Altman, R., Arora, S., Arx, S., Bernstein, M.S., Bohg, J., Bosselut, A., Brunskill, E., et al.: On the opportunities and risks of foundation models. arXiv preprint arXiv:2108.07258 (2021)

[22] Min, B., Ross, H., Sulem, E., Veyseh, A.P.B., Nguyen, T.H., Sainz, O., Agirre, E., Heintz, I., Roth, D.: Recent advances in natural language processing via large pre-trained language models: A survey. ACM Computing Surveys **56**(2), 1–40 (2023)

[23] Zhao, W.X., Zhou, K., Li, J., Tang, T., Wang, X., Hou, Y., Min, Y., Zhang, B., Zhang, J., Dong, Z., et al.: A survey of large language models. arXiv preprint arXiv:2303.18223 (2023)

[24] Edwards, C.N., Naik, A., Khot, T., Burke, M.D., Ji, H., Hope, T.: Synergpt: In-context learning for personalized drug synergy prediction and drug design. bioRxiv, 2023–07 (2023)

[25] Li, T., Shetty, S., Kamath, A., Jaiswal, A., Jiang, X., Ding, Y., Kim, Y.: Cancergpt: Few-shot drug pair synergy prediction using large pre-trained language models. ArXiv (2023)

[26] Zhang, Y., Yang, Q.: A survey on multi-task learning. IEEE Transactions on Knowledge and Data Engineering **34**(12), 5586–5609 (2021)

[27] Brown, T., Mann, B., Ryder, N., Subbiah, M., Kaplan, J.D., Dhariwal, P., Neelakantan, A., Shyam, P., Sastry, G., Askell, A., *et al.*: Language models are few-shot learners. Advances in neural information processing systems **33**, 1877–1901 (2020)

[28] Achiam, J., Adler, S., Agarwal, S., Ahmad, L., Akkaya, I., Aleman, F.L., Almeida, D., Altenschmidt, J., Altman, S., Anadkat, S., et al.: Gpt-4 technical report. arXiv preprint arXiv:2303.08774 (2023)

[29] Liu, T., Chen, T., Zheng, W., Luo, X., Zhao, H.: scelmo: Embeddings from language models are good learners for single-cell data analysis. bioRxiv, 2023–12 (2023)

[30] McInnes, L., Healy, J., Melville, J.: Umap: Uniform manifold approximation and projection for dimension reduction. arXiv preprint arXiv:1802.03426 (2018)

[31] Knox, C., Wilson, M., Klinger, C.M., Franklin, M., Oler, E., Wilson, A., Pon, A., Cox, J., Chin, N.E., Strawbridge, S.A., et al.: Drugbank 6.0: the drugbank knowledgebase for 2024. Nucleic Acids Research, 976 (2023)

[32] Schoch, C.L., Ciufo, S., Domrachev, M., Hotton, C.L., Kannan, S., Khovanskaya, R., Leipe, D., Mcveigh, R., O'Neill, K., Robbertse, B., *et al.*: Ncbi taxonomy: a comprehensive update on curation, resources and tools. Database **2020**, 062 (2020)

[33] Luecken, M.D., Theis, F.J.: Current best practices in single-cell rna-seq analysis: a tutorial. Molecular systems biology **15**(6), 8746 (2019)

[34] Landrum, G.: Rdkit documentation. Release **1**(1-79), 4 (2013)

[35] Landrum, G.: RDKit: Open-source Cheminformatics. http://www.rdkit.org

[36] Weininger, D.: Smiles, a chemical language and information system. 1. introduction to methodology and encoding rules. Journal of chemical information and computer sciences **28**(1), 31–36 (1988)

[37] Malyutina, A., Majumder, M.M., Wang, W., Pessia, A., Heckman, C.A., Tang, J.: Drug combination sensitivity scoring facilitates the discovery of synergistic and efficacious drug combinations in cancer. PLoS computational biology **15**(5), 1006752 (2019)

[38] Baptista, D., Ferreira, P.G., Rocha, M.: A systematic evaluation of deep learning methods for the prediction of drug synergy in cancer. PLOS Computational Biology **19**(3), 1010200 (2023)

[39] Cortes, C., Vapnik, V.: Support-vector networks. Machine learning **20**, 273–297 (1995)

[40] Pedregosa, F., Varoquaux, G., Gramfort, A., Michel, V., Thirion, B., Grisel, O., Blondel, M., Prettenhofer, P., Weiss, R., Dubourg, V., *et al.*: Scikit-learn: Machine learning in python. the Journal of machine Learning research **12**, 2825–2830 (2011)

[41] Arik, S.Ö., Pfister, T.: Tabnet: Attentive interpretable tabular learning. In: Proceedings of the AAAI Conference on Artificial Intelligence, vol. 35, pp. 6679–6687 (2021)

[42] Devlin, J., Chang, M.-W., Lee, K., Toutanova, K.: BERT: Pre-training of deep bidirectional transformers for language understanding. In: Burstein, J., Doran, C., Solorio, T. (eds.) Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers), pp. 4171–4186. Association for Computational Linguistics, Minneapolis, Minnesota (2019). https://doi.org/10.18653/v1/N19-1423 . https://aclanthology.org/N19-1423

[43] Tibshirani, R.: Regression shrinkage and selection via the lasso. Journal of the Royal Statistical Society Series B: Statistical Methodology **58**(1), 267–288 (1996)

[44] Lundberg, S.M., Lee, S.-I.: A unified approach to interpreting model predictions. Advances in neural information processing systems **30** (2017)

[45] Barretina, J., Caponigro, G., Stransky, N., Venkatesan, K., Margolin, A.A., Kim, S., Wilson, C.J., Lehár, J., Kryukov, G.V., Sonkin, D., *et al.*: The cancer cell line encyclopedia enables predictive modelling of anticancer drug sensitivity. Nature **483**(7391), 603–607 (2012)

[46] Blatkiewicz, M., Białas, P., Taryma-Leśniak, O., Hukowska-Szematowicz, B.: Pan-cancer analysis of vim expression in human cancer tissues (2021)

[47] Cotto, K.C., Wagner, A.H., Feng, Y.-Y., Kiwala, S., Coffman, A.C., Spies, G., Wollam, A., Spies, N.C., Griffith, O.L., Griffith, M.: Dgidb 3.0: a redesign and expansion of the drug–gene interaction database. Nucleic acids research **46**(D1), 1068–1073 (2018)

[48] Muzellec, B., Teleńczuk, M., Cabeli, V., Andreux, M.: Pydeseq2: a python package for bulk rna-seq differential expression analysis. Bioinformatics **39**(9), 547 (2023)

[49] Love, M.I., Huber, W., Anders, S.: Moderated estimation of fold change and dispersion for rna-seq data with deseq2. Genome biology **15**(12), 1–21 (2014)

[50] Thomas, P.D., Ebert, D., Muruganujan, A., Mushayahama, T., Albou, L.-P., Mi, H.: Panther: Making genome-scale phylogenetics accessible to all. Protein Science **31**(1), 8–22 (2022)

[51] Liberzon, A., Birger, C., Thorvaldsdóttir, H., Ghandi, M., Mesirov, J.P., Tamayo, P.: The molecular signatures database hallmark gene set collection. Cell systems **1**(6), 417–425 (2015)

[52] Virtanen, P., Gommers, R., Oliphant, T.E., Haberland, M., Reddy, T., Cournapeau, D., Burovski, E., Peterson, P., Weckesser, W., Bright, J., *et al.*: Scipy 1.0: fundamental algorithms for scientific computing in python. Nature methods **17**(3), 261–272 (2020)

[53] Traag, V.A., Waltman, L., Van Eck, N.J.: From louvain to leiden: guaranteeing well-connected communities. Scientific reports **9**(1), 5233 (2019)

[54] Loewe, S.: The problem of synergism and antagonism of combined drugs. Arzneimittel-forschung **3**(6), 285–290 (1953)

[55] Yadav, B., Wennerberg, K., Aittokallio, T., Tang, J.: Searching for drug synergy in complex dose–response landscapes using an interaction potency model. Computational and structural biotechnology journal **13**, 504–513 (2015)

[56] Me, B.: What is synergy. Pharmacol Rev **41**, 93–141 (1989)

[57] Bliss, C.I.: The toxicity of poisons applied jointly 1. Annals of applied biology

$\qquad$ **26**(3), 585–615 (1939)

[58] Kendall, A., Gal, Y., Cipolla, R.: Multi-task learning using uncertainty to weigh losses for scene geometry and semantics. In: Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition, pp. 7482–7491 (2018)

[59] Lin, B., Zhang, Y.: Libmtl: A python library for deep multi-task learning. Journal of Machine Learning Research **24**(1-7), 18 (2023)

[60] Zhao, Y., He, L.: Deep learning in the eeg diagnosis of alzheimer's disease. In: Computer Vision-ACCV 2014 Workshops: Singapore, Singapore, November 1-2, 2014, Revised Selected Papers, Part I 12, pp. 340–353 (2015). Springer

[61] Liu, H., Zhang, W., Zou, B., Wang, J., Deng, Y., Deng, L.: Drugcombdb: a comprehensive database of drug combinations toward the discovery of combinatorial therapy. Nucleic acids research **48**(D1), 871–881 (2020)

[62] Gal, Y., Ghahramani, Z.: Dropout as a bayesian approximation: Representing model uncertainty in deep learning. In: Balcan, M.F., Weinberger, K.Q. (eds.) Proceedings of The 33rd International Conference on Machine Learning. Proceedings of Machine Learning Research, vol. 48, pp. 1050–1059. PMLR, New York, New York, USA (2016). https://proceedings.mlr.press/v48/gal16.html

[63] Lemay, A., Hoebel, K., Bridge, C.P., Befano, B., De Sanjosé, S., Egemen, D., Rodriguez, A.C., Schiffman, M., Campbell, J.P., Kalpathy-Cramer, J.: Improving the repeatability of deep learning models with monte carlo dropout. npj Digital Medicine **5**(1), 174 (2022)

[64] Kirchhof, M., Mucsányi, B., Oh, S.J., Kasneci, D.E.: Url: A representation learning benchmark for transferable uncertainty estimates. Advances in Neural Information Processing Systems **36** (2024)

[65] Sigma-Aldrich's I-BET. https://www.emdmillipore.com/US/en/product/I-BET-CAS-1260907-17-2-Calbiochem,EMD_BIO-401010. Accessed: 2024-01-17

[66] Selleck's I-BET151 (GSK1210151A). https://www.selleckchem.com/products/i-bet151-gsk1210151a.html. Accessed: 2024-01-17

[67] Selleck's PF-562271. https://www.selleckchem.com/products/pf-562271.html. Accessed: 2024-01-29

[68] Selleck's Saracatinib. https://www.selleckchem.com/products/AZD0530.html. Accessed: 2024-01-29

[69] Saatci, O., Kaymak, A., Raza, U., Ersan, P.G., Akbulut, O., Banister, C.E., Sikirzhytski, V., Tokat, U.M., Aykut, G., Ansari, S.A., *et al.*: Targeting lysyl oxidase (lox) overcomes chemotherapy resistance in triple negative breast cancer.

842   Nature communications **11**(1), 2416 (2020)

[70] New embedding models and API updates. https://openai.com/blog/new-embedding-models-and-api-updates. Accessed: 2024-01-27

[71] Yu, T., Kumar, S., Gupta, A., Levine, S., Hausman, K., Finn, C.: Gradient surgery for multi-task learning. In: Larochelle, H., Ranzato, M., Hadsell, R., Balcan, M.F., Lin, H. (eds.) Advances in Neural Information Processing Systems, vol. 33, pp. 5824–5836. Curran Associates, Inc., ??? (2020). https://proceedings.neurips.cc/paper_files/paper/2020/file/3fe78a8acf5fda99de95303940a2420c-Paper.pdf

[72] Wang, Z., Tsvetkov, Y., Firat, O., Cao, Y.: Gradient vaccine: Investigating and improving multi-task optimization in massively multilingual models. In: International Conference on Learning Representations (2021). https://openreview.net/forum?id=F1vEjWK-lH_

[73] Liu, B., Liu, X., Jin, X., Stone, P., Liu, Q.: Conflict-averse gradient descent for multi-task learning. Advances in Neural Information Processing Systems **34**, 18878–18890 (2021)

[74] Navon, A., Shamsian, A., Achituve, I., Maron, H., Kawaguchi, K., Chechik, G., Fetaya, E.: Multi-task learning as a bargaining game. In: International Conference on Machine Learning, pp. 16428–16446 (2022). PMLR

[75] LinearMTL. GitHub (2018)

[76] Kim, S., Xing, E.P.: Tree-guided group lasso for multi-response regression with structured sparsity, with an application to eqtl mapping (2012)

[77] Frantar, E., Ruiz, C.R., Houlsby, N., Alistarh, D., Evci, U.: Scaling laws for sparsely-connected foundation models. In: The Twelfth International Conference on Learning Representations (2024). https://openreview.net/forum?id=i9K2ZWkYIP

[78] Kaplan, J., McCandlish, S., Henighan, T., Brown, T.B., Chess, B., Child, R., Gray, S., Radford, A., Wu, J., Amodei, D.: Scaling laws for neural language models. arXiv preprint arXiv:2001.08361 (2020)

[79] Heumos, L., Schaar, A.C., Lance, C., Litinetskaya, A., Drost, F., Zappia, L., Lücken, M.D., Strobl, D.C., Henao, J., Curion, F., et al.: Best practices for single-cell analysis across modalities. Nature Reviews Genetics, 1–23 (2023)

[80] Sun, N., Zhao, H.: Statistical methods in genome-wide association studies. Annual Review of Biomedical Data Science **3**, 265–288 (2020)

[81] Paszke, A., Gross, S., Massa, F., Lerer, A., Bradbury, J., Chanan, G., Killeen,

876 T., Lin, Z., Gimelshein, N., Antiga, L., et al.: Pytorch: An imperative style, high-
877 performance deep learning library. Advances in neural information processing
878 systems **32** (2019)

[82] Awais, M., Naseer, M., Khan, S., Anwer, R.M., Cholakkal, H., Shah, M., Yang,
M.-H., Khan, F.S.: Foundational models defining a new era in vision: A survey
and outlook. arXiv preprint arXiv:2307.13721 (2023)

[83] Campos Zabala, F.J.: Neural networks, deep learning, foundational models. In:
Grow Your Business with AI: A First Principles Approach for Scaling Artificial
Intelligence in the Enterprise, pp. 245–275. Springer, ??? (2023)

[84] Kingma, D.P., Ba, J.: Adam: A method for stochastic optimization. In: Bengio,
Y., LeCun, Y. (eds.) 3rd International Conference on Learning Representations,
ICLR 2015, San Diego, CA, USA, May 7-9, 2015, Conference Track Proceedings
(2015). http://arxiv.org/abs/1412.6980

[85] Wolf, F.A., Angerer, P., Theis, F.J.: Scanpy: large-scale single-cell gene expression
data analysis. Genome biology **19**, 1–5 (2018)

[86] O'Neil, J., Benita, Y., Feldman, I., Chenard, M., Roberts, B., Liu, Y., Li, J.,
Kral, A., Lejnine, S., Loboda, A., *et al.*: An unbiased oncology compound screen
to identify novel combination strategies. Molecular cancer therapeutics **15**(6),
1155–1162 (2016)

[87] Sounni, N.E., Baramova, E.N., Munaut, C., Maquoi, E., Frankenne, F., Foidart,
J.-M., Noël, A.: Expression of membrane type 1 matrix metalloproteinase (mt1-
mmp) in a2058 melanoma cells is associated with mmp-2 activation and increased
tumor growth and vascularization. International journal of cancer **98**(1), 23–28
(2002)

[88] Vizuete, A.F.K., Hansen, F., Negri, E., Leite, M.C., Oliveira, D.L., Gonçalves, C.-
A.: Effects of dexamethasone on the li-pilocarpine model of epilepsy: protection
against hippocampal inflammation and astrogliosis. Journal of Neuroinflamma-
tion **15**, 1–14 (2018)

[89] Kohlmeyer, J.L., Kaemmer, C.A., Pulliam, C., Maharjan, C.K., Samayoa, A.M.,
Major, H.J., Cornick, K.E., Knepper-Adrian, V., Khanna, R., Sieren, J.C., *et al.*:
Rabl6a is an essential driver of mpnsts that negatively regulates the rb1 pathway
and sensitizes tumor cells to cdk4/6 inhibitors. Clinical cancer research **26**(12),
2997–3011 (2020)

[90] Moon, H., Donahue, L.R., Choi, E., Scumpia, P.O., Lowry, W.E., Grenier, J.K.,
Zhu, J., White, A.C.: Melanocyte stem cell activation and translocation initiate
cutaneous melanoma in response to uv exposure. Cell stem cell **21**(5), 665–678
(2017)

[91] Bono, A., La Monica, G., Alamia, F., Mingoia, F., Gentile, C., Peri, D., Lauria, A., Martorana, A.: In silico mixed ligand/structure-based design of new cdk-1/parp-1 dual inhibitors as anti-breast cancer agents. International Journal of Molecular Sciences **24**(18), 13769 (2023)

[92] Ramon, J., Engelen, Y., De Keersmaecker, H., Goemaere, I., Punj, D., Morales, J.M., Bonte, C., Berx, G., Hoste, E., Stremersch, S., *et al.*: Laser-induced vapor nanobubbles for b16-f10 melanoma cell killing and intracellular delivery of chemotherapeutics. Journal of Controlled Release **365**, 1019–1036 (2024)

[93] Tirosh, I., Izar, B., Prakadan, S.M., Wadsworth, M.H., Treacy, D., Trombetta, J.J., Rotem, A., Rodman, C., Lian, C., Murphy, G., *et al.*: Dissecting the multicellular ecosystem of metastatic melanoma by single-cell rna-seq. Science **352**(6282), 189–196 (2016)

[94] Jerby-Arnon, L., Shah, P., Cuoco, M.S., Rodman, C., Su, M.-J., Melms, J.C., Leeson, R., Kanodia, A., Mei, S., Lin, J.-R., *et al.*: A cancer cell program promotes t cell exclusion and resistance to checkpoint blockade. Cell **175**(4), 984–997 (2018)

[95] Zhang, C., Shen, H., Yang, T., Li, T., Liu, X., Wang, J., Liao, Z., Wei, J., Lu, J., Liu, H., *et al.*: A single-cell analysis reveals tumor heterogeneity and immune environment of acral melanoma. Nature Communications **13**(1), 7250 (2022)