1 **Evaluating the timecourses of morpho-orthographic, lexical, and grammatical processing**
2 **following rapid parallel visual presentation: an EEG investigation in English.**
3
4 **Abstract**
5

Theories of language processing – and typical experimental methodologies – emphasize

the word-by-word processing of sentences. This paradigm is good for approximating speech or

careful text reading, but arguably, not for the common, cursory glances used while reading short

sentences (e.g., cellphone notifications, social media posts). How can we interpret a sentence in a

single glance? In an electroencephalography (EEG) study, brain responses to grammatical

sentences (*the dogs chase a ball*) presented for 200ms diverged from non-lexical consonant

strings (*thj rjxb zkhtb w lhct*) ~160ms post-sentence onset and from scrambled constructions (*a*

dogs chase ball the) ~250ms post-sentence onset, demonstrating – at different time points – rapid

recognition and cursory analysis of linguistic stimuli. In the grammatical sentences, unigram

probability correlated with EEG data ~150–300ms post-sentence onset, and probability of the

word given its context estimated by BERT correlated with EEG data after ~700–800ms. EEG

responses did not diverge between grammatical sentences and their counterparts with

ungrammatical agreement (*the dogs chases a ball*), although EEG responses did diverge for

plural vs. singular morphology at ~200ms. These results suggest that 'at-a-glance' reading is

possible, based on coactivation of individual lexical items, morphological structures, and

constituent structure at ~200-300ms, but that words are not integrated into a coherent

syntactic/semantic analysis, as evidenced by the substantially later responses to BERT

probability and the absence of sensitivity to agreement errors.

Keywords. Sentence processing, syntax, agreement, reading, EEG, psycholinguistics
26
27

1.

Introduction

Most theories of language processing assume incremental word-by-word processing (e.g., Brasoveanu & Dotlačil, 2020; Frazier, 1987; Frazier & Fodor, 1978; Hale, 2001; Lewis & Vasishth, 2005). In the cognitive neuroscience of language, standard methodology follows this general framework – sentences are presented serially, word-by-word, with evoked brain responses measured at each word. This is motivated by the fact that speech, sign, and careful reading of longer texts are serial. However, seriality is a poor model for an increasingly common mode of reading: casual glances at short sentences (e.g., TikTok video captions, text notifications). The psycholinguistic mechanisms deployed in comprehending sentences read 'at-a-glance' are still poorly understood. With electroencephalography (EEG) and rapid parallel (~200ms) visual presentation, we seek to: (1) establish when comprehenders distinguish grammatical sentences (*the dogs chase a ball*) from scrambled, ungrammatical counterparts (*a dogs chase ball the*) and non-linguistic consonant strings (*thj rjxb zkhtb w lhct*), i.e., isolate the 'sentence superiority effect' (SSE); and (2) establish the relative timecourse of this response to the interpretation of the lexical items in the grammatical sentences. We also sought to establish whether comprehenders build an integrated syntactic/semantic analysis of the sentence, in or subsequent to the SSE time period, by contrasting grammatical sentences with agreement violation counterparts (*the dogs chases a ball*). Our results suggest that the SSE depends on a mechanism that enables rapid detection of words and basic constituent structure. It is not the case that the analysis is detailed enough to reject agreement errors or to interpret words relative to their context until much later than the SSE.

Significant progress has been made in understanding the timecourse of word-by-word

processing by associating event-related potentials (ERPs) with distinct stages of language

processing (e.g., Friederici, 2011; Friederici & Kotz, 2003; Kaan, 2007). The early left anterior

negativity (eLAN; generally observed over left anterior electrodes at 100–200ms) is associated

with automatic local structure building, and can be found for word category violations (see

Friederici & Weissenborn, 2007). The N170 and N250 (negative-going components observed

over parietal and posterior sensors ~200–300ms) are associated with initial visual processing and

sub-word, morpho-orthographic processing (Grainger & Holcomb, 2009; Holcomb & Grainger,

2006, 2007; Morris & Stockall, 2012; Morris et al., 2008). A later left anterior negativity (LAN;

at 300–500ms) is associated with case marking and morphosyntactic agreement (e.g., subject-

verb number disagreement; see Molinaro et al., 2011). The N400 (a negative-going centro-

parietal component ~400ms) is associated with the access of lexical-semantic information

(Friederici, 2011; Lau et al., 2008) and is highly correlated with surprisal (e.g., Frank et al.,

2015; Lowder et al., 2018). Lastly, The P600 (a positive-going centro-parietal component

between 500–900ms) is associated with the integration and retrieval of sentence-level syntactic

and semantic information (Friederici, 2011). These ERPs – and their interpretations –

importantly, are contextualized by word-by-word language comprehension; that is, the

processing and integration of lexical items in a given parsing state. It is unclear to what degree

these commonly-observed responses from serial reading and listening paradigms should be

evoked in the reading of parallel input.

Several threads of research demonstrate that the visual system is capable of extracting

information from more than a single word in one fixation. For example, skilled English readers

are capable of detecting several letters to the right of a fixation (Rayner, 1998) and access some

features of words in the parafovea (Antúnez et al., 2022; Rayner et al., 2003; Schotter et al.,

2012). Therefore, it is possible that readers use parallel processing strategies, integrating

information from across the visual field (Snell & Grainger, 2019). Similarly, findings from

single-word processing studies also suggest rapid and parallel processing. A number of results

suggest rapid, form-based processing of morphologically complex forms into their constituent

parts (Rastle et al., 2000; see Taft & Forster, 1975). Magnetoencephalography (MEG) recordings

show that morphologically complex forms (*re-made*; *sing-er*) exhibit increased activity in

occipito-temporal regions ~170ms (the 'M170' event-related field; Zweig & Pylkkänen, 2009),

and that this activity correlates with the relative probability of the whole word vs. the stem

(Gwilliams & Marantz, 2018; Lewis et al., 2010; Solomyak & Marantz, 2011; see also Grainger

& Holcomb, 2009; Holcomb & Grainger, 2006; Morris et al., 2013). This M170 response

temporally precedes neural responses reflecting lexico-semantic interpretation of the word

(Fruchter & Marantz, 2015; Pylkkänen & Marantz, 2003). This suggests that early stages of

reading assess features of the form of multiple morphemes in a single fixation in single-word

reading, which could in principle extend to short phrasal stimuli as well.

Nonetheless, it remains controversial how much linguistic information can be extracted

from a single fixation, and how parallel these processes might be (Snell & Grainger, 2019; White

et al., 2019). Recent work has explored the visual system's capacity to extract grammatical and

semantic information from short sentences read in a single fixation, presented rapidly, only

visible for ~200ms. Asano and Yokosawa (2011) found that Japanese readers were more

accurate at recalling words in rapidly-presented sentences in which target words were

contextually appropriate vs. sentences that had a semantic anomaly. To account for this, they

propose that features of the sentence can be processed in parallel, and that a 'gist' can be rapidly

extracted. In a similar vein, in a series of studies in French sentences with 200ms presentation

times, Snell, Grainger, and colleagues found an increase in word recall accuracy for grammatical

and semantically plausible sentences vs. scrambled or implausible sentences (Massol et al., 2021;

Snell & Grainger, 2017; Wen et al., 2019), which they refer to as the 'sentence superiority effect'

(SSE). In an (EEG) study, Wen et al. (2019) found that, compared to their scrambled

counterparts, grammatical sentences presented in this fashion resulted in a reduction in amplitude

of the N400, a component which is inversely correlated with the accessibility of lexical

semantics in a context (Bornkessel-Schlesewksy & Schlesewsky, 2019; Kutas & Hilyard, 1984;

Lau et al., 2008). Similar to Asano and Yokosawa (2011), Wen et al. (2019) propose that

grammatical information is extracted in parallel from the fleeting stimulus, and that this

information then interactively facilitates lexical access, resulting in a reduction in the N400

component.

With MEG, Dufau et al. (2024) – using the same stimuli and scrambled vs. grammatical

comparison as Snell and Grainger (2017) and Wen et al. (2019) – localize a series of left-

lateralized cortical regions that display an SSE. The first sensitive region is the inferior frontal

gyrus (321–406ms), followed by the anterior temporal lobe (466–531ms), and then the inferior

frontal (549–602ms) and posterior superior temporal gyri (553–622ms). Further MEG work

elaborating on this paradigm reliably finds responses to grammatical manipulation even faster

than 300ms. In English, Fallon and Pylkkänen (2024) found that grammatical sentences elicited

greater activation than length-matched noun lists in left middle temporal cortex ~125ms post-

sentence onset. Similarly, Flower and Pylkkänen (2024) found sensitivity to grammatical

sentences vs. reversed sentences starting at ~210ms post-sentence onset, localized to a broad left

fronto-temporal and temporo-parietal language network. These two MEG studies further

demonstrate that the syntactic information gleaned from a single fixation may not be fully

detailed. Fallon and Pylkkänen (2024) showed that the SSE is insensitive to agreement errors

(*nurses cleans wounds*) and implausible thematic role reversals (*wounds clean nurses*),

suggesting an analysis that is insensitive to word-to-word relations like subject-verb number

agreement and thematic role likelihood. Their results demonstrate rapid detection of basic

constituent structure ~150ms, which we take to be distinct from the interactive lexical processes

hypothesized by Wen et al. (2019). Similarly, Flower and Pylkkänen (2024) found that brain

activity did not distinguish between grammatical sentences and sentences with two-word

transpositions until ~320ms, significantly after the earliest stages of neural SSEs. Finally, in an

MEG study in Danish, Krogh and Pylkkänen (2024) replicated a neural SSE at ~230ms, with

activity localized to left inferior frontal and anterior temporal regions. Moreover, they observed

that different features of well-formed grammatical sentences elicited neural effects at different

times, with argument structure features impacting activity starting at ~250ms, and yes/no

questions involving a displacement diverging from declarative sentences at ~500–720ms. These

findings further support the claim that the SSE is dependent on early, top-down deployment of

grammatical knowledge to identify basic constituent structure.

Here, we consider three distinct hypotheses about the timecourse of the SSE relative to

other linguistic computations. We first seek to establish the SSE using EEG by contrasting

Grammatical sentences (*the dogs chase a ball*) with their ungrammatical Scrambled counterparts

(*a dogs chase ball the*). Having established the relative timecourse of the SSE, we then sought to

determine where in the EEG topography and when in time this effect occurred relative to other

ERP responses. We further contrast grammatical sentences to non-linguistic, character-matched

Consonant Strings (*thj rjxb zkhtb w lhct*) trials and agreement violations (*the dogs chases a ball*).

Then, to query the relation between the SSE and lexical processes, we correlate the EEG

responses recorded for the Grammatical trials with unigram probability (p('dogs')) and

probability of the word given its context (p('dogs' | 'the __ chase a ball')). Contextual

probability is estimated using BERT (Devlin et al., 2019), a bidirectional Transformer encoder

(Vaswani et al., 2017) trained on the masked language modeling objective. Given one or more

masked input tokens, the model learns to predict the corresponding vocabulary item(s), given the

surrounding context. A trained BERT model assigns a probability for a word, given a

bidirectional context. While BERT probability is context-dependent, unigram frequency is

context-independent.

We consider the **morpho-orthographic processing** hypothesis, by which structure is

identified by rapid visual detection of its visual correlates, such as short functional elements, like

the aligned with the left edge of the visual field, or morphosyntactic markers such as nominal

plural *-s* or verbal singular *-s*. This hypothesis predicts that the SSE should co-occur with earlier

stages of orthographic processing, i.e., concurrent with the N170+N250 complex (Grainger &

Holcomb, 2009; Holcomb & Grainger, 2006, 2007; Morris & Stockall, 2012; Morris et al.,

2008), and analogizes the SSE with rapid 'blind' identification of morphosyntactic structure in

vision (Rastle et al., 2008, Zweig & Pylkkänen, 2009; Solomyak & Marantz, 2010). To test this

hypothesis, we contrast the grammatical sentences with non-linguistic, consonant string

counterparts (*thj rjxb zkhtb w lhct*) to first identify the earliest stage of morpho-orthographic

processing. The morpho-orthographic hypothesis predicts that the SSE should precede EEG

responses correlated with unigram and contextual word probability as the mechanisms are

proposed to operate on the visual form of the stimuli, prior to lexical access. Lastly, the morpho-

orthographic hypothesis predicts that readers should be able to rapidly detect number agreement

errors, since these are transparently reflected in the orthographic representation of English (i.e.,

the dogs chases).

Secondly, we consider the **constituent structure** hypothesis in which shortly after (or

concurrent to) access of lexical items, comprehenders detect basic constituency, i.e., whether

there is a subject noun phrase or verb phrase, without necessarily integrating the word meanings

into a single interpretation, or checking formal relations such as agreement. We take this

hypothesis to be compatible with Fallon & Pylkkänen's (2024) findings of early detection of

short sentences, regardless of the plausibility of their thematic role or agreement errors. This

hypothesis predicts that the SSE is likely to occur after the N170+N250 complex, i.e. after the

divergence between Grammatical and Consonant String conditions, and may be concurrent to or

subsequent to activation of lexical items, i.e. unigram probability. However, this hypothesis also

predicts that the SSE should be insensitive to agreement, i.e., there should be no point during the

SSE in which the ungrammatical agreement and grammatical agreement trials diverge, especially

if readers deploy top-down knowledge that enables 'correction' of minor errors (Flower &

Pylkkänen 2024). Importantly, this hypothesis does not predict that there is insensitivity to

morphology like the nominal plural marker -*s* or the verbal singular marker -*s*, but rather

insensitivity to the ungrammaticality of illicit combinations. Finally, this hypothesis predicts that

contextual integration of the lexical items should follow the SSE, i.e., the contextual probability

correlations should occur substantially later than the SSE.

Finally, we consider the **coactivation hypothesis**, following Asano & Yosokawa (2011),

Snell & Grainger (2017), and Wen et al. (2019). This hypothesis predicts that the SSE is

coextensive with lexical access, i.e., grammatical structure facilitates lexical access in a parallel,

interactive, cascaded fashion. Crucially, this predicts that the SSE should temporally co-occur

with measures of lexical probability. Since this hypothesis links identification of the syntactic

structure of the sentence with the lexical items, this hypothesis also proposes that effects of

unigram probability should temporally co-occur or overlap with effects of conditional

probability. It is unclear whether this hypothesis makes predictions about sensitivity to

agreement, given that agreement is a formal relation that may not necessarily be activated by

lexical processing. We also propose that this model predicts that lexical activation should be

parallel, i.e., there should not be distinct 'phases' of processing each lexeme in the neural signal,

but rather lexical probability of words should modulate the neural response at the same time.

Figure 1. Experiment structure and behavioral results. (A) Example stimulus items for each
condition. (B) Trial structure. (C) Accuracy by trial condition on the match/mismatch task. Stars
signify a significant pairwise difference, as indicated by the logistic regression presented in §3.1.
Each comparison is significant ($p < 0.001$), except for the comparison between Grammatical and
Ungrammatical. (D) Proportion of trials by presentation time. 77% of trials were at the ceiling
presentation time of 200ms.

2.

Methods

2.1.

Participants

Thirty-five self-identified English speakers were recruited from the ANONYMOUS
CITY community. Thirty-three participants were right handed, as assessed by the Edinburgh
Handedness inventory (Oldfield, 1971). All participants had normal or corrected-to-normal
vision, and reported no history of language impairment. Participants gave written informed
consent, and were compensated $10 per 30 minutes of participation time. The study was
approved by ANONYMOUS UNIVERSITY (#ANONYMOUS NUMBER) and was performed
in compliance with relevant laws and institutional guidelines.

2.2.

Materials

We prepared 50 sets of sentences in four conditions: Grammatical, Scrambled,
Ungrammatical, and Consonant String (Fig. 1A). All Grammatical trials (*the dogs chase a ball*)
were simple transitive sentences consisting of five words: a determiner, an animate noun subject,
a transitive verb, a different determiner, and an inanimate noun object. Half of the grammatical
trials consisted of a plural subject noun ending in -*s* and a plural verb; the other half had a
singular subject noun and a singular verb ending in -*s*. All words were monosyllabic and
monomorphemic, with the exception of the plural morphemes -*s*. Scrambled sentences (*a dogs
chase ball the*) were constructed by randomly permuting the words of the Grammatical trials,
with manual verification that the new string did not form a new grammatical sentence. We did
not exclude scrambled phrases that could create locally coherent sub-strings (e.g., the relative

clause interpretation of *a ball the dogs chase*). Length-matched, unpronounceable consonant

strings (*thj rjxb zkhtb w lhct*) were also generated. Ungrammatical trials were created from the

Grammatical trials by either removing the required singular verb agreement morpheme *-s* from

the verb (*the dog chase a ball*), or by adding an unlicensed singular verb agreement morpheme *-s*

to the verb (*the dogs chases a ball*). Because number was counterbalanced across item sets,

length was matched between the Grammatical and Ungrammatical conditions.

Mismatch trials were constructed by replacing either the subject noun, the verb, or the

object noun with a semantically similar length-matched foil (*the dogs chase a ball ~ the cats*

chase a ball). The probes in the match/mismatch task maintained all other features, i.e.,

scrambled word order, ungrammatical agreement, or consonant strings. In the Consonant String

condition, the consonant string at either the subject noun position, the verb position, or the object

noun position was replaced with another random consonant string of equal length.

Half of the stimuli were paired with a match trial, and the other half were paired with a

mismatch trial. This was counterbalanced within-stimulus set, so participants could not leverage

the identity of specific lexical items to guess whether a trial would be a match/mismatch. Instead,

participants had to attend to the two nouns and verbs, i.e., the three content words.

2.3.

Procedure

We used an adapted version of a match/mismatch task which has previously been

employed in studies on behavioral and neural sentence superiority effects (Fallon & Pylkkänen,

2024; Flower & Pylkkänen, 2024, Krogh & Pylkkänen, 2024; Pegado & Grainger, 2020; Pegado

et al., 2021). In this task, participants determine whether an untimed, second sentence is the same

as, or different from, the rapidly displayed sentence.

All sentences were displayed centered on a screen, printed in a white monospace font

against a dark gray background. Target sentences were displayed for a variable length, followed

by a dark gray blank screen of variable length, which was adjusted such that the total time of the

target sentence and the blank screen summed to 800ms. After the blank screen, participants saw

another short sentence, which remained visible until participants pressed a button to indicate

whether it matched. Participants entered their response using a keyboard, with the 'f' key

corresponding to 'match' and the 'j' key corresponding to 'mismatch.' On-screen reminders

('same?', 'different?') were presented at each memory probe, to ensure participants remembered

the mapping between key presses and responses. Participants were kept at a uniform distance

from the screen, approximately 70cm from nasion to center of the screen. The visual angle

subtended of the stimuli was approximately 15 degrees. The trial structure is shown in Fig. 1B.

Half of the trials were 'Mismatch' trials, and the other half were 'Match.' Unlike in prior

RPVP studies using a match task (Fallon & Pylkkänen, 2024; Flower & Pylkkänen, 2024; Krogh

& Pylkkänen, 2024; Pegado & Grainger, 2020; Pegado et al., 2021), sentence and blank screen

display time were dynamically adjusted based on participant's performance. This variable display

time mechanic was implemented, in part, to conduct parallel experiments in other languages with

different writing systems. We did not know *a priori* whether the minimum feasible stimulus

length would be the same across writing systems and languages, and we expected by-participant

variance, as well. Thus, we wanted the trial length to be adjusted dynamically to identify the

ideal trial length for each subject. Sentence display time was constrained to vary between 200

and 600ms, initialized at 200ms. Sentence display time increased by 50ms after incorrect

responses, and decreased by 50ms after correct responses. Participants received feedback on

incorrect trials, with a 1000ms delay before the next trial. Faster presentation times were

necessary to ensure that participants could not saccade during the critical time window, and thus

read the stimuli serially. For our experiment, responses were remarkably accurate across trials

(see § 3 and Fig. 1C). Thus, the average stimulus length was 216ms (SE = 0.43ms), and 77.0%

of trials were at the minimum speed of 200ms (Fig. 1D), suggesting that variable display time

should not be a substantial influence on performance or EEG responses.

Stimuli were presented in 4 separate blocks. Participants saw one trial per item set per

block, with conditions and items evenly distributed between the 4 blocks. After each block,

participants were instructed to take a break, which ranged from 2-5 minutes, and were provided

with jokes to encourage them to not progress immediately into the next block. An experimenter

was present with the participant during the recording and was available to answer questions or

assist the participant if needed.

EEG signals were recorded using a 64 channel Ag/Cl BrainVision actiChamp+ system

(Gilching, Germany). Impedance of the EEG sensors was reduced by the application of

SuperVisc gel and lowered to <25kΩ. On-line EEG recording was referenced to FCz according

to manufacturer standards, and then re-referenced to average sensors offline. Participants

engaged in an unrelated task that is not reported here. The order of the two tasks was

counterbalanced. Participants also engaged in a series of localizer tasks at the beginning of each

recording session, but we do not report them here.

2.4.

Data Availability

We make our data and analysis code publicly available via an Open Science Framework

repository, the link to which has been removed for the sake of anonymity during the peer review

process.

3.

Results

3.1.

Behavioral Results

Average accuracy was 81.42% (SE = 0.005). All participants except for one scored 70%

or above. The data from all participants were analyzed. We used the lme4 package (v1.1-35.1,

Bates et al., 2015) in R (v4.3.28, R Core Team, 2023) to fit a mixed effects logistic regression

model to the accuracy data. The correct response was fit as the dependent variable, with

condition as a 4-level factor, and with by-participant and by-item random intercepts. The model

formula was Correct ~ Condition + (1|Subject) + (1|Item). More complex random effect

structures failed to converge. We fit the factor Condition with Grammatical as the intercept,

since the research question at hand is how each sentence type diverges from the Grammatical

condition. The data from all participants were analyzed. The results of the model are presented in

Table 1. Afterwards, pairwise comparisons were conducted to assess which conditions diverged.

Pairwise comparisons were conducted on the logistic regression model, with Tukey HSD

correction, using the *emmeans* package (v1.10.5, Lenth, 2016). All conditions diverged from

each other (z-ratios > 6, ps < 0.001), except for the pairwise comparison between Grammatical

and Ungrammatical ($\beta = 0.156$, SE $= 0.12$, z-ratio $= 1.35$, $p = 0.53$), strongly suggesting that

there is no detectable difference between sentences with grammatical agreement vs. sentences

with agreement errors. The behavioral results are shown in Fig. 1C.

	β	SE	z	p
(Intercept)	2.48	0.15	16.38	**<0.001**
Condition: Ungrammatical	–0.18	0.11	–1.56	0.12
Condition: Scrambled	–0.83	0.10	–7.93	**<0.001**
Condition: Cons. String	–1.73	0.10	–17.37	**<0.001**

Table 1. Results of the mixed effects logistic regression fit to the behavioral responses. The

model formula was Correct ~ Condition + (1|Subject) + (1|Item). Bolded *p*-values are significant

at alpha < 0.05.

3.2.

EEG Processing

All EEG preprocessing was conducted in MNE-Python (v1.4, Gramfort et al., 2013), and

statistical analyses were conducted using Eelbrain (v0.39.5, Brodbeck et al., 2023). Raw EEG

data was filtered off-line between 0.1–40Hz, using an IIR bandpass filter. We removed flat or

noisy sensors (mean $= 1.4$, SE $= 0.17$ channels), and interpolated them using spherical spline

interpolation (Perrin et al., 1989).

EEG data were re-referenced to an average reference off-line. Afterwards, epochs were

extracted from –100ms to 800ms post-stimulus onset, i.e., the time of the rapid sentence

presentation and the subsequent blank screen. The 100ms pre-onset period was used for baseline

correction. Independent component analysis (ICA) was used to identify semi-regular endogenous

electromagnetic noise sources, including eyeblinks, eye movements, and heartbeats. These

components were removed. Following ICA, we automatically rejected all epochs that exceeded a

100μV peak-to-peak threshold. Afterwards, we visually inspected and removed other

problematic epochs.

For each participant, we equalize the number of trials for each condition. Thus, each

participant ends up with an equal number of good epochs for each trial condition. We then

created condition averages for each participant for factorial analyses. After exclusion of the

18.4% of incorrect trials, exclusion of the unusable epochs, and trial condition normalization,

38.8% of trials were excluded. The data from all participants were analyzed.

3.3.

Factorial Analysis

Our research question consists of two parts: What is the timing of structure sensitivity,

relative to the timing of sensitivity to lexical content or agreement? What role does lexical

processing play with respect to the SSE? For these reasons, we conduct two sets of analyses. The

first analysis contrasts the Grammatical, Consonant String, Scrambled, and Ungrammatical

conditions. The second pair of analyses then only includes the Grammatical trials to determine

when we observe correlations between EEG signal and lexical variables.

Both sets of analyses use a two-stage regression analysis. At the first level, within each

subject, a linear model is fit to each time point and sensor. For the factorial analysis, this model

includes an intercept, and three β coefficients corresponding to the difference between

Grammatical trials and Consonant String, Scrambled and Ungrammatical trials for each sensor

and time point.

At the second stage, we conduct an across-participants analysis in which, for each effect

separately, the β values are entered into a two-tailed one-sample t-test to determine, at each time

point and each sensor, whether their values are significantly different from a population mean of

0 across participants. This produces t-values at each time point and sensor,. For estimating

significance at the group level, we perform spatio-temporal cluster-based permutation testing

over the resulting t-values (Maris & Oostenveld, 2007). This is a non-parametric method for first

identifying clusters of significant responses that are contiguous in space and time, and then

bootstrapping a null distribution from the data to estimate the statistics of the cluster. This allows

for correcting for multiple comparisons, while acknowledging the non-independence of adjacent

sensors or time points in an EEG recording. Adjacent time points and sensors (of the same

polarity) were clustered together if their (uncorrected) p-value was $p < 0.01$. Cluster-forming p is

a parameter which controls cluster size in space and time, rather than determining statistical

significance. T-values were summed to calculate a cluster-level statistic. A null cluster

distribution was estimated by repeating this procedure for 10,000 permutations in which the β

value of each participant was randomly shuffled with 0. Cluster p-value was equated with

position in the null distribution with the bottom 2.5% and top 2.5% being considered statistically

significant. For the clustering procedure, we used a stricter cluster forming p-value threshold

than may be typical (i.e., $p < 0.05$), because lower p-values favor smaller clusters, which may be

more useful for estimating the temporal onset of effects. Additional *post-hoc* analyses with

different cluster forming *p*-value thresholds ($p < 0.05$, $p < 0.10$) did not significantly change the

pattern of results, and are thus not reported here.

Strictly speaking, spatio-temporal cluster-based permutation tests are only null hypothesis

significance testing procedures for the size of a cluster in space-time, not for the temporal and

spatial dimensions of the cluster (Rousselet, 2019; Sassenhagen & Deschkow, 2019). For this

reason, we report the largest cluster (i.e., the smallest *p*-value). Afterwards, for each factorial

comparison, we average the raw signal from the spatio-temporal coordinates of the cluster and

conduct pairwise *t*-tests between Grammatical, Scrambled, Ungrammatical, and Consonant

String. We also calculate and plot the correlation of the unigram and contextual probability of

content words (words 2, 3, and 5; see § 3.4) in the Grammatical trials with the single-trial EEG

data. This analysis also follows Fallon & Pylkkänen's (2024) and Flower & Pylkkänen's (2024)

strategy of using the SSE as a spatio-temporal localizer followed by secondary analyses on what

other effects are observable in the SSE cluster.

For the Consonant String comparison (Grammatical as reference), the largest cluster was

positive-going and consisted of 32 centro-parietal sensors, 167–800ms, $p < 0.001$ (Fig. 2A). This

cluster suggests a relatively uniform sustained difference in evoked response between

Grammatical and Consonant String stimuli; the latter are immediately detectable as non-lexical,

and thus none of the subsequent linguistic processes are likely to be engaged, unlike the other

three conditions. The onset of this cluster falls within the N170+N250 complex, and the centro-

parietal distribution is consistent with the topography of this ERP. Post-hoc analyses in this time

window showed more positive activity for Consonant Strings compared to Grammatical,

Scrambled, and Ungrammatical trials. There was a correlation of word 3 (main verb) contextual

probability within the grammatical trials during this cluster (Pearson's $r = 0.29$, $p = 0.05$), but no

significant correlations between the contextual probability of the other lexical items nor unigram

probability of any words.

The Scrambled condition (Grammatical as reference) was associated with one significant

cluster, which was negative-going and consisted of 8 right lateral sensors, 253–399ms, $p = 0.036$

(Fig. 2D). This cluster showed a sustained negative response for the Scrambled condition. The

topography of this cluster is centered on anterior and right lateral sensors, although normally

N400 effects are observed over centro-parietal and posterior sensors (cf. Wen et al., 2019).

However, this time window is approximately the same as Wen et al.'s (2019) N400 finding.

Pairwise comparisons between conditions revealed a significant difference between

Grammatical and Consonant String trials ($p < 0.05$), but not between Grammatical and

Ungrammatical trials. Within the grammatical trials, there were marginal correlations of word 3

(main verb) and word 5 (object noun) contextual probability during this cluster (Pearson's $r = $

0.25, $p = 0.08$; Pearon's $r = 0.25$, $p = 0.09$), but no significant correlations between the contextual

probability of the word 2, nor the unigram probability of any words.

The Ungrammatical condition (Grammatical as reference) was not associated with any

significant clusters (the largest having $p = 0.331$) and is not presented here. This was the case

with clustering thresholds of $p < 0.01$, $p < 0.05$, $p < 0.10$, or $p < 0.30$. Thus, the failure to identify

a significant cluster is not likely to be due to the stringentness of our clustering parameters.

Figure 2. Clusters, pairwise activation comparisons, and correlations from the two-stage EEG analyses. (A, B, D) Topographic plots show the distribution of *t*-values and sensors included in each cluster. Time series show the average β coefficient value in these sensors over time, with the temporal extent of the cluster shaded. Bar plots show the average activity by condition in the spatial and temporal extent of the cluster (Grammatical vs. Scrambled vs. Consonant String vs. Ungrammatical for A and D; Singular vs. Plural Subject noun phrase (NP) in B). Error bars show one standard error above and below the mean; starred pairwise comparisons are significant at *p* < 0.05 with Hochberg correction for multiple comparisons. Scatterplots in A and D show the correlation of unigram probability (top) and contextual probability (bottom) for the Grammatical trials in the spatial and temporal extent of the cluster for word 2 (blue), word 3 (orange), and word 5 (green). (C, E) Topographic plots show the sensors included in each (overlapping) cluster for word 2 (blue), word 3 (orange), and word 5 (green) unigram probability (C) and contextual

444   probability (E). Time series show the overlapping average β coefficient value in these clusters
445   over time, with the temporal extent of the cluster shaded.
446
447
To determine whether the lack of a difference between the Grammatical and

Ungrammatical conditions indexes a failure to notice the singular vs. plural morphology (i.e., *-s,*

vs. *-Ø* on the subject noun and the verb), we conducted a *post hoc* two-stage regression analysis

with the same parameters comparing *singular* Grammatical trials (*the dogØ chases a ball*) and

plural Grammatical trials (*the dogs chaseØ a ball*). Before a participant can realize that a

stimulus is ungrammatical, they must first evaluate the number specification on both the subject

noun phrase (NP) and verb, and then 'check' whether these values are appropriate given the

syntactic structure of the sentence.

A significant cluster was observed consisting of 7 central right electrodes, 117–226ms, *p*

= 0.03, (Fig 2B). Afterwards, we conducted *post hoc* Grammatical vs. Ungrammatical analyses

nested within the singular trials and the plural trials. We did this because some behavioral

findings demonstrate asymmetrical sensitivity to number errors in subject-verb agreement for

plural controllers vs. singular controllers (Wagers et al., 2009). We failed to find any significant

clusters distinguishing Grammatical vs. Ungrammatical, nested within singular or plural trials.

Thus, while the EEG data indicate that participants distinguish trials with singular vs. plural

subject NPs, neural responses are not sensitive to mismatch between subject NP and verb

number specification.

3.4.

Single-Trial Analyses

To determine the relative timing and topography of the SSE relative to activation of

lexical items, we conducted two-stage linear regression analyses over unigram probability and

contextual probability of the content words (*dogs*, *chase*, *ball*) in the Grammatical trials.

This also permits us to determine whether individual lexical items are processed in parallel

during parallel presentation of sentences. We conducted two separate single-trial analyses with

two different measures of word likelihood: unigram frequency and BERT masked language

modeling probability.

The analyses for the unigram and contextual probability analyses used the same two-

stage regression procedure described in § 3.3. Both analyses included the continuous probability

estimates for words 2 (subject noun), 3 (main verb), and 5 (object noun) in the same regression.

The first and fourth words were not analyzed, (1) because they are contentless determiners (*the*,

a); and (2) because, depending on which trials were excluded for a given participant, it was

commonly the case that the only remaining trials available for analysis had a constant value for

the first or fourth word position, i.e., all *the*'s in the first position or all *a*'s in the fourth position.

Constant-valued regressors cannot be included in a linear model. Predictors were standardized

before model estimation (i.e., shifted to mean zero and scaled to unit variance).

Unigram probability was calculated as the base 10 logarithm of the case insensitive

frequency in the Google Books Ngram Dataset (v3, Michel et al., 2011). Contextual probability

was estimated using BERT large, uncased, with whole word masking (Devlin et al., 2019), as

accessed through Hugging Face (Wolf et al., 2020). The model had 336M parameters, with 24

layers, 16 attention heads, and with hidden dimensionality 1,024. Differing slightly from vanilla

BERT, this BERT used whole word masking, in which rather than masking (potentially) sub-

word units, all of the tokens corresponding to a word would be masked. We do not perform any

comparisons, but we hypothesized that training to predict all of the sub-word tokens which make

up a word would lead to more cognitively realistic whole-word prediction probabilities than the

standard masked language modeling objective. Given an input with a mask (*the [MASK] chase a*

ball), BERT produces a probability distribution over the tokens of its vocabulary. Thus, by

masking words 2, 3, and 5 of each Grammatical stimulus item, we extract the model probability

of each word in its bidirectional context.

For the unigram frequency analyses, we observed a significant cluster for the unigram

probability of word 5 (the object noun), centered over 9 centro-parietal sensors, 161–223ms, $p =$

0.04. We also observed a marginally significant cluster for the unigram probability of word 3

(the main verb), centered over 6 left posterior sensors, 213–272ms, $p = 0.08$. These clusters are

spatially adjacent, overlap temporally, and have a typical time and topographic location of an

(early) N400 response. They are also positive-going, consistent with a reduction in the N400 for

more probable words. We also report on the largest cluster observed for the unigram probability

of word 2 (the subject noun), centered over 3 posterior sensors, 218–262ms, $p = 0.17$. This

cluster shares the same wave morphology, topographic distribution, and temporal structure as the

other unigram probability clusters. Taken together, this suggests that in rapid parallel reading,

participants can coactivate multiple lexical items, each affecting the N400 independently. These

three clusters are plotted together in Fig. 2C.

For the contextual probability analysis, we observed a cluster for word 3 (the main verb)

centered over 7 left lateral sensors, 562–705ms, $p < 0.01$. We also observed a non-significant

cluster for word 2 (the subject noun) centered over 8 left parietal and posterior sensors, 586–

618ms, $p = 0.13$. As before, these clusters both overlap in space and time, and both show an

increase in positive activity for more contextually probable words, shown in Fig. 2E. These

clusters overlap in time with typical 'P600' effects. We did not observe any clusters for word 5

(the object noun).

4.

Discussion

Despite the overwhelming emphasis on serial, word-by-word reading in sentence

processing research, fluent readers are capable of extracting abstract grammatical information

from a single glance. How is this possible? Here, we contribute to the growing literature

examining brain responses to grammatical properties of written sentences displayed rapidly in

parallel (Asano & Yokosawa, 2011; Dufau et al., 2024; Fallon & Pylkkänen, 2024; Flower &

Pylkkänen, 2024; Krogh & Pylkkänen, 2024; Massol et al., 2021; Snell & Grainger, 2017; Wen

et al., 2019). We found that EEG responses in fluent English readers showed evidence of

detecting linguistic vs. non-linguistic orthographic representations at ~160ms post-sentence

onset, and whether the arrangement of the words maps onto a syntactic representation by

~300ms post-sentence onset. Moreover, we demonstrated that EEG signals correlated with

unigram probability for content words ~200–300ms, slightly earlier than the SSE. We also failed

to find evidence that readers detected subject-verb agreement errors in English, either in the

whole epoch or during the SSE space-time. Interestingly, we demonstrated distinct neural

signatures for singular vs. plural subject NPs in the pre-SSE time period. Thus, although readers

appear to 'detect' number morphology, they may not 'check' whether subject-verb agreement is

grammatical in rapid parallel reading. Finally, we showed that the SSE likely precedes

integration of the words into a larger syntactic/semantic representation, as benchmarked by the

later, 'P600' effect of contextual lexical probability.

Taken together, we suggest that these findings support (our interpretation of) **the**

constituent structure hypothesis. When reading a short sentence displayed rapidly, readers

initially map the visual stimulus onto a letter-form or morpho-orthographic representation,

during the M170/N170/N250 (Zweig & Pylkkänen, 2009; Grainger & Holcomb, 2009). In our

study, this is reflected as the rapid distinction between the Consonant String stimuli and the

Grammatical stimuli, and the rapid detection of subject NP number. Shortly thereafter, readers

activate the lexical representations of the words. This is reflected in the N400(-style) effect

reported in our unigram frequency analysis, with a reduction in negative activity from ~200–

300ms for more probable words (Bornkessel-Schlesewksy & Schlesewsky, 2019; Kutas &

Hilyard, 1984; Lau et al., 2008). Interestingly, we observed spatially and temporally overlapping

clusters for each of the three content words in our target stimuli, which may suggest a parallel

reading strategy. Following this, we observe the SSE, the detection of Grammatical trials vs.

Scrambled counterparts, ~300ms. This ERP effect is temporally overlapping with the N400, but

spatially distinct, centered over right anterior and lateral sensors. Within-cluster analyses failed

to identify a difference between Grammatical trials and Ungrammatical trials, reflecting an

insensitivity to subject-verb agreement processing (Fallon & Pylkkänen, 2024). Finally, we

observe a pattern of ERP responses to the contextual probability of the content words, much later

than the SSE, 500–800ms. Although the topographic distribution and wave morphology are not

typical of a P600, the finding that contextual properties do not correlate with EEG responses

until this late are consistent with models of the P600 as an index of integration difficulty (e.g.,

Kuperberg, 2007; Friederici, 2011). Crucially, the finding that the ERP corresponding to the SSE

does not index either contextual integration nor subject-verb agreement are compatible with **the**

constituent structure hypothesis (c.f., Fallon & Pylkkänen, 2024).

4.1.

Lexical Access in RPVP

In our study, we observed one significant cluster corresponding to the unigram frequency

of the main verb, a marginally significant cluster for the subject noun, and a non-significant

cluster for the object noun. This pattern is suggestive of parallel reading of multiple words in a

single fixation. Flower & Pylkkänen (2024) report temporally overlapping responses for *bigrams*

in 4-word grammatical sentences (*all cats are nice*) at ~250ms, contemporaneous with the early-

stage SSE in their study. This may demonstrate an intermediate 'chunking' of words into units,

which may be compatible with either coactivation of lexical and syntactic representations (Asano

and Yokosawa, 2011; Snell and Grainger, 2017), or rapid identification of constituents.

Both our results and Flower & Pylkkänen's (2024) results depend on a two-stage

regression analysis. As discussed in § 3, the first stage of regression collapses across individual

trials, and the second stage of regression collapses across participants at the group level. It is still

feasible that, trial-to-trial, participants coactivate only one or two lexical items, if this is the

maximum that is possible in a single (foveal) fixation (Brothers et al. 2017; White et al. 2019).

Additionally, we mention that our two-stage regression analysis only revealed one significant

cluster post-correction. We therefore remain agnostic about the degree to which parallel reading

is a component of comprehending sentences in 'at-a-glance' reading generally.

4.2.

The SSE ERP

One concern about research on the SSE is that participants may be able to use their top-

down knowledge of syntax while performing the task (match/mismatch or post-cued word recall)

to make an informed guess for grammatical, but not ungrammatical trials, thus producing the

behavioral sentence superiority effect (Staub, 2023). This account, however, is unable to explain

observed EEG (e.g., here and in Wen et al., 2019) and MEG (e.g., Fallon & Pylkkänen, 2024;

Flower & Pylkkänen, 2024; Krogh & Pylkkänen, 2024) SSEs in RPVP.

Another point is that the EEG SSE observed here could potentially be explained by

selective fixation and differences in bigram frequency or transition probability between the

conditions. Given the Grammatical stimulus *the dogs chase a ball* and the Scrambled stimulus *a*

dogs chase ball the, if the participant were to fixate on a single word position for each trial e.g.,

the fourth, with the following word available parafoveally, they would process *a ball* for the

Grammatical condition and *ball the* for the Scrambled condition. On average, the Grammatical

items are likely to have 2-word substrings with higher bigram frequency or transition probability

than the corresponding Scrambled items. The behavioral data, however, disprove a strong

fixation account.

If participants used this strategy, then participant accuracy should be close to 40%, given

that the position in which a 'mismatch' might occur is counterbalanced. Even if they focused on

a single position and parafoveally processed the next word as well as the previous word, i.e.,

attended to three words in parallel without engaging in linguistic processing, then accuracy

would be closer to 60%. Observed accuracy, however, is 90% for the Grammatical condition and

81% for the Scrambled condition. Further, if participants used this strategy, then we would

predict that accuracy should be similar across conditions. But, we observe that accuracy is

significantly higher for the Grammatical, Ungrammatical, and Scrambled conditions compared to

the Consonant String conditions. Accuracy on the Consonant String conditions was

approximately around this 60% benchmark, suggesting that participants may have used this kind

of reading strategy in these non-linguistic cases. Lastly, this explanation seems unlikely given

the lack of sensitivity to agreement errors, since it would be expected that the bigram and

transition probabilities for agreement violations (*dogs chases*) would be lower than for

grammatical relations (*dog chases*).

Secondly, we note some differences between the SSE ERP we elicited in our study vs.

that of Wen et al (2019). Like their study, we observe an ERP for Grammatical trials compared

to their Scrambled counterparts ~250–400ms, in a typical N400 time window. Like them, we

also observe a positive (= reduction in negative) response. However, our topographic distribution

is over right anterior sensors, whereas theirs has a larger centro-parietal scalp distribution, more

typical of the N400. The SSE response observed here is comparable to the MEG findings by

Dufau et al. (2024), which show the neural SSE emerging in anterior portions of traditional

language cortex at ~320ms. By contrast, Fallon & Pylkkänen (2024) observe much earlier SSEs,

around ~125ms and ~200–250ms. One consideration is that our stimuli had 5 words (3 content

words, 2 functional words), Dufau et al.'s (2024) study used 4, and Fallon & Pylkkänen's (2024)

used 3 (all content words). It is possible that length may affect the latency of the SSE, especially

if readers rely on a parallel reading mechanism; i.e., 3 short words may be more likely to be read

foveally compared to 4 or 5 words. It could also suggest a degree of serialism such that the SSE

is delayed as a function of how many words make up the syntactic tree.

4.3.

Agreement and Contextual Integration in the SSE

The failure to detect agreement violations supports an interpretation in which the SSE

reflects a rapid sketch of a syntactic representation rather than a detailed analysis. In ERP

research, subject-verb agreement errors elicit a strong, early response (a LAN followed by a

P600) in serial reading experiments, which suggests both detection of the ungrammaticality

followed by a repair attempt (Angrilli et al., 2002; Coulson et al., 1998, Osterhout & Mobley,

1995; see Molinaro et al., 2011, for a review). Furthermore, if we accept that readers may

process (some of) a short sentence in a single glance, why were they unable to notice the

mismatch in number specification of two adjacent words in our study?

We suspect that there are two possible explanations for this. The first is that readers may

deploy top-down grammatical knowledge to constrain or 'correct' the percept. Flower &

Pylkkänen (2024) demonstrate that while the earliest phase of the neural SSE is sensitive to local

transpositions ~250–300ms (*all cats are nice*, *all are cats nice*), the later phase is not ~300–

400ms. They interpret this finding as demonstrating an initial bottom-up detection of the error

followed by top-down correction. The second possible explanation is that the mechanisms

subserving the SSE do not permit integration of lexical items into a detailed analysis, in which

relations between words are evaluated and interpreted. In either case, it is unclear why the later

components of our ERP did not reveal sensitivity to the ungrammatical agreement relation,

particularly during the 500–800ms stage in which we argue lexical items are integrated into the

larger analysis.

Another possibility, however, is that comprehenders may simply ignore morphosyntactic

information that is not conducive to identifying the semantic 'gist' of a sentence (Asano &

Yokosawa, 2011), which may be consistent with 'good enough' parsing models (Ferreira &

Patson, 2007). Subject-verb agreement in English is a formal grammatical dependency, which

serves as an indirect cue to the interpretation of the sentence, which is arguably more important

in 'at-a-glance' reading. Investigating whether the SSE is sensitive to selectional restrictions

(*they will bring a book* vs. *they will bringing a book*; *they depend on him* vs. *they depend in him*)

may further clarify why readers ignore agreement. We also observe that psycholinguistic

research has long observed that agreement violations are particularly 'fallible', compared to

other kinds of long-distance dependencies, such as anaphora (Wagers et al., 2009; Phillips et al.,

2011; Dillon et al., 2013).

Lastly, the source of insensitivity to agreement may be due to the relatively weak visual

salience of the number affixes in English (-*s*, -Ø). This could be further tested by contrasting

more visually salient agreement errors, such as *child **is*** vs. *child-**ren are*** or leveraging agreement

morphology in other languages with more complex and visually salient agreement morphemes

(*asa-**vara*** 'I love him'; *asa-**vassi*** 'we love you,' Kalaallisut/West Greenlandic; ⬛⬛ *kôr-**i*** 'I do';

⬛⬛⬛ *kôr-en* 'you do,' Bangla/Bengali).

Importantly, we found that readers do exhibit distinct ERPs for singular vs. plural subject

NPs in grammatical trials, which suggests that comprehenders do not always fail to notice small

suffixes like -*s*. This is to be expected if readers attend to morphological cues ('interpretable

features') that are semantically relevant, such as number on subject NPs, but ignore

morphological features ('uninterpretable features') that are semantically irrelevant. Investigating

whether the neural SSE is sensitive to plurality in contexts that are semantically inert (i.e.,

pluralia tantum nouns like *scissors*), or agreement phenomena in languages that may be more

semantically informative (i.e., number features in a null subject language) may be instructive.

Our study suggested distinct phases of lexical processing in the RPVP task – unigram

probability corresponding to neural activity ~200–300ms, and contextual probability ~500–

800ms. As before, we acknowledge that, of the reported clusters, two are significant and one is

only marginal.

While myriad work has related word-by-word information-theoretical complexity metrics

from causal (left-to-right) language models (see Hale, 2016 for a review) to observed human data

(e.g., self-paced reading time, EEG, fMRI) during language processing, we believe the use of

probability from a *bidirectional* language model to be a novel application made possible by the

use of RPVP. Future work remains to further investigate how predictors derived from

bidirectional models can be related to language processing.

5.

Conclusion

Our theories of language comprehension must be as flexible as the range of forms that

language can take. In the visual domain, language can be understood slowly or from a quick

glance – when editing a journal article vs. checking a text notification. Here, we demonstrate that

there are several distinct stages involved during the processing of sentence-length written stimuli

viewed only momentarily. After the rapid detection of linguistic content ~160ms and initial

activation of lexical items at ~200ms, a 'sketch' of a grammatical analysis occurs at ~300ms.

These findings are compatible with the hypothesis that the initial sketch involves identification

of basic constituent structure (cf., Fallon & Pylkkänen, 2024). This initial sketch is insensitive to

formal grammatical errors, such as subject-verb agreement errors, and precedes deeper

interpretative processes, occurring after ~500ms. We also demonstrate that several language-

related ERPs are observed in the processing of sentences 'at-a-glance', and that coactivation of

lexical items may be observable in a typical 'N400' response, just prior to the SSE.

References

Angrilli, A., Penolazzi, B., Vespignani, F., De Vincenzi, M., Job, R., Ciccarelli, L., ... &
Stegagno, L. (2002). Cortical brain responses to semantic incongruity and syntactic violation in
Italian language: an event-related potential study. *Neuroscience Letters*, *322*(1), 5-8.
https://doi.org/10.1016/S0304-3940(01)02528-9

Antúnez, M., Milligan, S., Hernández-Cabrera, J.A., Barber, H.A., & Schotter, E.R. (2022).
Semantic parafoveal processing in natural reading: Insight from fixation-related potentials & eye
movements. *Psychophysiology* 59(4), e13986. https://doi.org/10.1111/psyp.13986

Asano, M., & Yokosawa, K. (2011). Rapid extraction of gist from visual text and its influence on
word recognition. *The Journal of General Psychology* 138, 127–154.
https://doi.org/10.1080/00221309.2010.542510

Baayen, R. H., Piepenbrock, R., & Gulikers, L. (1996). Celex2. *Linguistic Data Consortium,
Philadelphia*. https://doi.org/10.35111/gs6s-gm48

Bates, D., Mächler, M., Bolker, B., & Walker, S. (2015). Fitting linear mixed-effects models
using lme4. *Journal of Statistical Software*, *67*(1), 1–48. https://doi.org/10.18637/jss.v067.i01

Bojanowski, P., Grave, E., Joulin, A., & Mikolov, T. (2017). Enriching word vectors with
subword information. *Transactions of the Association for Computational Linguistics*, *5*, 135-146.
https://doi.org/10.1162/tacl_a_00051

Bornkessel-Schlesewsky, I., & Schlesewsky, M. (2019). Towards a neurobiologically plausible
model of language-related, negative event-related potentials. *Frontiers in Psychology* 10, 298.
https://doi.org/10.3389/fpsyg.2019.00298

Brasoveanu, A., & Dotlačil, J. (2020). *Computational cognitive modeling and linguistic theory*.
Springer Nature. https://library.oapen.org/handle/20.500.12657/39529

Brodbeck, C., Das, P., Gillis, M., Kulasingham, J. P., Bhattasali, S., Gaston, P., Resnik, P., &
Simon, J. Z. (2023). Eelbrain, a Python toolkit for time-continuous analysis with temporal
response functions. *eLife 12*, e85012. https://doi.org/10.7554/eLife.85012

Brothers, T., Hoversten, L.J., Traxler, M.J. (2017). Looking back on reading ahead: No evidence
for lexical parafoveal-on-foveal effects. *Journal of Memory and Language* 96, 9–22.
https://doi.org/10.1016/j.jml.2017.04.001

Coulson, S., King, J. W., & Kutas, M. (1998). Expect the unexpected: Event-related brain response to morphosyntactic violations. *Language and Cognitive Processes*, *13*(1), 21-58. https://doi.org/10.1080/016909698386582

Devlin, J., Chang, M-W., Lee, K., & Toutanova, K. (2019). BERT: Pre-training of deep bidirectional transformers for language understanding. in *Proceedings of the North American Chapter of the Association for Computational Linguistics: Human language technologies (volume 1: Long and Short papers)* (pp. 4171–4186). Association for Computational Linguistics. https://doi.org/10.18653/v1/N19-1423

Dillon, B., Mishler, A., Sloggett, S., Phillips, C. (2013). Contrasting intrusion profiles for agreement and anaphora: Experimental and modeling evidence. *Journal of Memory and Language* 69, 85–103. https://doi.org/10.1016/j.jml.2013.04.003

Dufau, S., Yeaton, J., Badier, J. M., Chen, S., Holcomb, P. J., & Grainger, J. (2024). Sentence superiority in the reading brain. *Neuropsychologia*, *198*, 108885. https://doi.org/10.1016/j.neuropsychologia.2024.108885

Fallon, J., & Pylkkänen, L. (2024). Language at a glance: How our brains grasp linguistic structure from parallel visual input. *Science Advances*, *10*(43), eadr9951. https://doi.org/10.1126/sciadv.adr9951

Ferreira, F., & Patson, N. (2007). The 'good enough' approach to language comprehension. *Language and Linguistics Compass* 1(1–2), 71–83. https://doi.org/10.1111/j.1749-818X.2007.00007.x

Flower, N. & Pylkkänen, L. (2024). The spatiotemporal dynamics of bottom-up and top-down processing during at-a-glance reading. *Journal of Neuroscience*, e0374242024. https://doi.org/10.1523/JNEUROSCI.0374-24.2024

Frank, S. L., Otten, L. J., Galli, G., & Vigliocco, G. (2015). The ERP response to the amount of information conveyed by words in sentences. *Brain and Language* 140, 1–11. https://doi.org/10.1016/j.bandl.2014.10.006

Frazier, L. (1987). Syntactic processing: Evidence from Dutch. *Natural Language and Linguistic Theory* 5(4), 519–559. https://doi.org/10.1007/BF00138988

Frazier, L., & Fodor, J. D. (1978). The sausage machine: A new two-stage parsing model. *Cognition* 6(4), 291–325. https://doi.org/10.1016/0010-0277(78)90002-1

Friederici, A. D., & Kotz, S. A. (2003). The brain basis of syntactic processes: Functional imaging and lesion studies. *Neuroimage*, *20*, S8-S17. https://doi.org/10.1016/j.neuroimage.2003.09.003

Friederici, A. D., & Weissenborn, J. (2007). Mapping sentence form onto meaning: The syntax–semantic interface. *Brain research*, *1146*, 50-58. https://doi.org/10.1016/j.brainres.2006.08.038

Friederici, A. D. (2011). The brain basis of language processing: From structure to function. *Physiological reviews*, *91*(4), 1357-1392. https://doi.org/10.1152/physrev.00006.2011

Fruchter, J., & Marantz, A. (2015). Decomposition, lookup, and recombination: MEG evidence for the Full Decomposition model of complex visual word recognition. *Brain and Language* 143, 81–96. https://doi.org/10.1016/j.bandl.2015.03.001

Grainger, J., & Holcomb, P.J. (2009). An ERP investigation of orthographic priming with relative-position and absolute-position primes. *Brain Research* 1270; 45–53. https://doi.org/10.1016/j.brainres.2009.02.080

Gramfort, A., Luessi, M., Larson, E., Engemann, D. A., Strohmeier, D., Brodbeck, C., Goj, R., Jas, M., Brooks, T., Parkkonen, L., & Hämäläinen, M. (2013). MEG and EEG data analysis with MNE-Python. *Frontiers in Neuroscience*, 267. https://doi.org/10.3389/fnins.2013.00267

Gwilliams, L., & Marantz, A. (2018). Morphological representations are extrapolated from morpho-syntactic rules. *Neuropsychologia* 114, 77–87. https://doi.org/10.1016/j.neuropsychologia.2018.04.015

Hale, J. (2001). A probabilistic Earley parser as a psycholinguistic model. *Proceedings of the North American Chapter of the Association for Computational Linguistics* 2, 1–8. https://doi.org/10.3115/1073336.1073357

Hale, J. (2016). Information theoretical complexity metrics. *Language and Linguistics Compass*, *10*(9), 397-412. https://doi.org/10.1111/lnc3.12196

Hao, Y., Mendelsohn, S., Sterneck, R., Martinez, R., & Frank, R. (2020). Probabilistic predictions of people perusing: Evaluating metrics of language model performance for psycholinguistic modeling. *Proceedings of the Workshop on Cognitive Modeling and Computational Linguistics,* 75–86. https://doi.org/10.18653/v1/2020.cmcl-1.10

Holcomb, P. J., & Grainger, J. (2006). On the time course of visual word recognition: An event-
related potential investigation using masked repetition priming. *Journal of Cognitive*
Neuroscience 18(10), 1631–1643. https://doi.org/10.1162/jocn.2006.18.10.1631

Holcomb, P. J., & Grainger, J. (2007). Exploring the temporal dynamics of visual word
recognition in the masked repetition priming paradigm using event-related potentials. *Brain*
research, *1180*, 39-58. https://doi.org/10.1016/j.brainres.2007.06.110

Kaan, E. (2007). Event☐related potentials and language processing: A brief overview. *Language*
and Linguistics Compass, *1*(6), 571-591. https://doi.org/10.1111/j.1749-818X.2007.00037.x

Krogh, S. & Pylkkanen, L. (2024). Manipulating syntax without taxing working memory: MEG
correlates of syntactic dependencies in a Verb-Second language. *bioRxiv*.
https://doi.org/10.1101/2024.02.20.581245

Kuperberg, G.R. (2007). Neural mechanisms of language comprehension: Challenges to syntax.
Brain Research, 1146, 23–49. https://doi.org/10.1016/j.brainres.2006.12.06

Kutas, M., & Hillyard, S. (1984). Brain potentials during reading reflect word expectancy
and semantic association. *Nature* 307, 161–163. https://doi.org/10.1038/307161a0

Lau, E., Phillips, C., & Poeppel, D. (2008). A cortical network for semantics: (de)constructing
the N400. *Nature Reviews: Neuroscience* 9(12), 920–933. https://doi.org/10.1038/nrn2532

Lenth R. V. (2016). "Least-Squares Means: The R Package lsmeans." *Journal of Statistical*
Software, 69(1), 1–33. https://doi.org/10.18637/jss.v069.i01

Levy, R. (2008). Expectation-based syntactic comprehension. *Cognition*, *106*(3), 1126-1177.
https://doi.org/10.1016/j.cognition.2007.05.006

Lewis, G., Solomyak, O., & Marantz, A. (2011). The neural basis of obligatory decomposition of
suffixed words. *Brain & Language* 118(3), 118–127. https://doi.org/10.1016/j.bandl.2011.04.004

Lewis, R., & Vasishth, S. (2005). An activation-based model of sentence processing as skilled
memory retrieval. *Cognitive Science* 29(3), 375–419.
https://doi.org/10.1207/s15516709cog0000_25

Lowder, M. W., Choi, W., Ferreira, F., & Henderson, J. M. (2018). Lexical predictability during
natural reading: Effects of surprisal and entropy reduction. *Cognitive Science* 42(S4), 1166–
1183. https://doi.org/10.1111/cogs.12597

Maris, E., & Oostenveld, R. (2007). Nonparametric statistical testing of EEG- and MEG-data. *Journal of Neuroscience Methods* 164(1), 177–190. https://doi.org/10.1016/j.jneumeth.2007.03.024

Massol, S., Mirault, J., & Grainger, J. (2021). The contribution of semantics to the sentence superiority effect. *Scientific Reports* 11, 20148. https://doi.org/10.1038/s41598-021-99565-6

Michel, J. B., Shen, Y. K., Aiden, A. P., Veres, A., Gray, M. K., Google Books Team, ... & Aiden, E. L. (2011). Quantitative analysis of culture using millions of digitized books. *Science*, *331*(6014), 176-182. https://doi.org/10.1126/science.1199644

Molinaro, N., Barber, H. A., & Carreiras, M. (2011). Grammatical agreement processing in reading: ERP findings and future directions. *Cortex*, *47*(8), 908-930. https://doi.org/10.1016/j.cortex.2011.02.019

Morris, J., Grainger, J., & Holcomb, P. J. (2008). An electrophysiological investigation of early effects of masked morphological priming. *Language and Cognitive Processes*, *23*(7-8), 1021-1056. https://doi.org/10.1080/01690960802299386

Morris, J., Grainger, J., & Holcomb, P. J. (2013). Tracking the consequences of morpho-orthographic decomposition of words using ERPs. *Brain Research* 1529, 92–104. https://doi.org/10.1016/j.brainres.2013.07.016

Morris, J., & Stockall, L. (2012). Early, equivalent ERP masked priming effects for regular and irregular morphology. *Brain and Language*, *123*(2), 81-93. https://doi.org/10.1016/j.bandl.2012.07.001

Noureddine, S. (2024). GPT-2 for Psycholinguistic Applications. GitHub repository. https://github.com/samer-noureddine/GPT-2-for-Psycholinguistic-Applications

Oldfield, R. C. (1971). The assessment and analysis of handedness: the Edinburgh inventory. *Neuropsychologia*, *9*(1), 97-113. https://doi.org/10.1016/0028-3932(71)90067-4

Osterhout, L., & Mobley, L. A. (1995). Event-related brain potentials elicited by failure to agree. *Journal of Memory and Language*, *34*(6), 739-773. https://doi.org/10.1006/jmla.1995.1033

Pegado, F., & Grainger, J. (2020). A transposed-word effect in same-different judgments to sequences of words. *Journal of Experimental Psychology: Learning, Memory, and Cognition*, *46*(7), 1364. https://doi.org/10.1037/xlm0000776

919 Pegado, F., Wen, Y., Mirault, J., Dufau, S., & Grainger, J. (2021). An ERP investigation of
920 transposed-word effects in same-different matching. *Neuropsychologia*, *153*, 107753.
921 https://doi.org/10.1016/j.neuropsychologia.2021.107753
922

923 Perrin, F., Pernier, J., Bertrand, O., & Echallier, J. F. (1989). Spherical splines for scalp potential
924 and current density mapping. *Electroencephalography and clinical neurophysiology*, *72*(2), 184-
925 187. https://doi.org/10.1016/0013-4694(89)90180-6
926

927 Phillips, C., Wagers, M.W., Lau, E.F. (2011). Grammatical illusions and selective fallibility in
928 real-time language comprehension. In J.T. Runner (ed.), *Syntax and Semantics vol. 37:*
929 *Experiments at the Interfaces*. https://doi.org/10.1163/9781780523750_006
930

931 Pylkkänen, L., & Marantz, A. (2003). Tracking the time course of word recognition with MEG.
932 *Trends in Cognitive Sciences* 7(5), 187–189. https://doi.org/10.1016/S1364-6613(03)00092-5
933

934 R Core Team (2023). R: A language and environment for statistical computing. R Foundation for
935 Statistical Computing, Vienna, Austria. http://www.R-project.org/
936

937 Rastle, K., Davis, M. H., & Marslen-Wilson W. D. (2000). Morphological and semantic effects
938 in visual word form recognition: A time-course study. *Language and Cognitive Processes*
939 15(4/5), 507–537. https://doi.org/10.1080/01690960050119689
940

941 Rayner, K. (1998). Eye movements in reading and information processing: 20 years of research.
942 *Psychological Bulletin*, *124*(3), 372. https://doi.org/10.1037/0033-2909.124.3.372.
943

944 Sassenhagen, J., & Dreschkow, D. (2019). Cluster-based permutation tests of MEG/EEG data do
945 not establish significance of effect latency or location. *Psychophysiology* 56(6), e13335.
946 https://doi.org/10.1111/psyp.13335
947

948 Schotter, E. R., Angele, B., & Rayner, K. (2012). Parafoveal processing in reading. *Attention,*
949 *Perception, & Psychophysics*, *74*, 5-35. https://doi.org/10.3758/s13414-011-0219-2
950

951 Snell, J., & Grainger, J. (2017). The sentence superiority effect revisited. *Cognition* 168, 217–
952 221. https://doi.org/10.1016/j.cognition.2017.07.003
953

954 Snell, J., & Grainger, J. (2019). Readers are parallel processors. *Trends in Cognitive Sciences*,
955 *23*(7), 537-546. https://doi.org/10.1016/j.tics.2019.04.006
956

Solomyak, O., & Marantz, A. (2011). Evidence for early morphological decomposition in visual
word recognition: A single-trial correlational study. *Journal of Cognitive Neuroscience* 22(9),
2042–2057. https://doi.org/10.1162/jocn.2009.21296

Staub, A. (2023). A commentary on the 'sentence superiority effect': Almost certainly guessing,
not parallel interactive activation. *PsyArXiv*. https://doi.org/10.31234/osf.io/hzaqr

Taft, M., & Forster, K. I. (1975). Lexical storage and retrieval of prefixed words. *Journal of
Verbal Learning and Verbal Behavior* 14, 638–647. https://doi.org/10.1016/S0022-
5371(75)80051-X

Vaswani, A., Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A. N., Kaiser, L., &
Polosukhin, I. (2017). Attention is all you need. *Advances in Neural Information Processing
Systems*, 30.
https://proceedings.neurips.cc/paper_files/paper/2017/file/3f5ee243547dee91fbd053c1c4a845aa-
Paper.pdf

Wagers, M. W., Lau, E. F., & Phillips, C. (2009). Agreement attraction in comprehension:
Representations and processes. *Journal of Memory and Language*, *61*(2), 206-237.
https://doi.org/10.1016/j.jml.2009.04.002

Wen, Y., Snell, J., & Grainger, J. (2019). Parallel, cascaded, interacting processing of words
during sentence reading. *Cognition* 189, 221–226.
https://doi.org/10.1016/j.cognition.2019.04.013

White, A., Boynton, G. M., & Yeatman, J. D. (2019). You can't recognize two words
simultaneously. *Trends in Cognitive Science*s 23(10), 812–814.
https://doi.org/10.1016/j.tics.2019.07.001

Wolf, T., Debut, L., Sanh, V., Chaumond, J., Delangue, C., Moi, A., ... & Rush, A. M. (2020).
Transformers: State-of-the-art natural language processing. In *Proceedings of the 2020
Conference on Empirical Methods in Natural Language Processing: System Demonstrations* (pp.
38-45). https://doi.org/10.18653/v1/2020.emnlp-demos.6

Zweig, E., & Pylkkänen, L. (2009). A visual M170 effect of morphological complexity.
Language and Cognitive Processes 24(3), 412–439. https://doi.org/10.1080/01690960802180420