Automated detection of Bornean white-bearded gibbon (*Hylobates albibarbis*) vocalisations using an open-source framework for deep learning

A. F. Owens[1], Kimberley Hockings[2], Muhammed Ali Imron[3], Shyam Madhusudhana[4,5], Mariaty Ayudia Niun[6], Tatang Mitra Setia[7], Manmohan Sharma[1], Siti Maimunah Soebagio[6,8], F. J. F. Van Veen[1]* & Wendy M. Erb[5]

[1]Faculty of Environment, Science and Economy, Department of Earth and Environmental Science, Centre for Geography and Environmental Science, University of Exeter, Penryn, TR10 9FE, UK

[2]Centre for Ecology and Conservation, University of Exeter, Penryn, TR10 9FE, UK

[3]Faculty of Forestry, Universitas Gadjah Mada, Yogyakarta, 55281, Indonesia

[4]Centre for Marine Science and Technology, Curtin University, Perth, WA, 6102, Australia

[5]K. Lisa Yang Centre for Conservation Bioacoustics, Cornell Lab of Ornithology, Cornell University, Ithaca, NY 14850, USA

[6]Fakultas Kehutanan dan Pertanian, Universitas Muhammadiyah Palangka Raya, Palangka Raya, 73111, Indonesia

[7]Department of Biology, Faculty of Biology and Agriculture, Universitas Nasional, Jakarta, 12520, Indonesia

[8]Fakultas Kehutanan, Instiper Yogyakarta, Yogyakarta, 55281, Indonesia

*Email: f.j.f.van-veen@exeter.ac.uk

ABSTRACT

Passive acoustic monitoring is a promising tool for monitoring at-risk populations of vocal

species, yet extracting relevant information from large acoustic datasets can be time-

consuming, creating a bottleneck at the point of analysis. We adapted an open-source

framework for deep learning in bioacoustics to automatically detect Bornean white-bearded

gibbon (*Hylobates albibarbis)* "great call" vocalisations in a long-term acoustic dataset from a

rainforest location in Borneo. We describe the steps involved in developing this solution, such

as collecting audio recordings, developing training and testing datasets, training neural-network

models, and evaluating model performance. Our best model performed at a satisfactory level (F

score = 0.87), identifying 98% of the highest-quality calls from 90 hours of manually-annotated

audio recordings. We also found no significant difference in the distribution of great call

detections over time between the manual annotations and the model's output, and greatly

reduced analysis times when compared to a human observer. Future work should seek to apply

our model to long-term acoustic datasets to understand spatiotemporal variations in *H.*

albibarbis' calling activity. With additional information, such as detection probability over

distance, we demonstrate how our model could be used to monitor gibbon population density

and spatial distribution on an unprecedented scale.

I.   INTRODUCTION

Ever-increasing anthropogenic pressures on the environment, such as habitat loss, have

led to widespread population declines in many animal species (Bender et al. 1998). However,

for many species, data in population trends is often sparse and lacking in standardised

methodology (Jetz et al. 2019), leading to a demand for a greater quantity and scale of wildlife

population monitoring programmes to inform conservation responses (Verma et al. 2016). To

meet this demand, conservation scientists and ecologists have turned to developing

technologies to automate data collection, enabling the rapid accumulation of large volumes of

data (Piel and Wich 2021). While this has allowed for unprecedented insight, it can also make

practical aspects of ecological inference challenging (Borowiec et al. 2022).

Manual extraction of relevant information from large datasets can be time consuming,

resulting in a bottleneck at the point of analysis (Norouzzadeh et al. 2018). This bottleneck is

evident in data generated as part of passive acoustic monitoring (PAM) programmes, which

involve the use of acoustic sensors to autonomously collect sound recordings in the field

(Acevedo and Villanueva-rivera 2010). Advancements in recording device design, greater

availability of lower-cost equipment, and improved data storage options have made the task of

capturing many hours of acoustic data relatively straightforward (Morgan and Braasch 2021).

Data must then be browsed to identify relevant signals of interest, such as species-specific

vocalisations, often by manually listening to each recording in full or visually inspecting the data

in spectrogram form (a time-frequency pictorial representation of an audio signal), or both.

PAM can provide a step-change in standardised population monitoring of vocal species at high

temporal resolution and simultaneous large spatial scales, that would be impossible to achieve

with 'traditional' methods relying on manual data collection (Sugai et al. 2019). However, such

PAM programmes often capture datasets so large that they cannot be studied manually in full

in a reasonable timeframe, so automating this limiting data-processing step is critical (Morgan

and Braasch 2021; Clink et al. 2023).

Machine learning has proven to be an effective solution for fast and accurate analysis of

acoustic data, including the automated detection of signals of interest (Stowell 2022; Miller et

al. 2023). There are many options available for this task, including artificial neural networks

(ANNs) (Mielke and Zuberbühler 2013), Gaussian mixture models (GMMs) (Heinicke et al. 2015)

and support vector machines (SVMs) (Noda et al. 2016), among others. These each have

associated advantages, and due to the diversity of potential signal types and acoustic

environments, no single method has been shown to be optimal in all situations (Clink et al.

2023). However, it is worth noting that ANNs demonstrate comparatively strong adaptability

and proficiency in understanding complex patterns in data (Haykin 2009; Bengio et al. 2016).

Early work applying ANNs to animal sound made use of the multi-layer perception (MLP)

architecture, with manually selected summary features such as syllable duration, peak

frequency, etc., used to inform the network's predictions (Stowell 2022). While MLPs have been

effective in classifying a wide variety of terrestrial and marine animal calls, the structure of non-

speech acoustic events can be highly variable (Kong et al. 2017), and reducing the data to a

series of manually assigned summary features can restrict the wealth of information available

to train a network, potentially limiting its effectiveness (Stowell 2022).

An alternative is to use convolutional neural networks (CNNs) which, like other deep-

learning ANN architectures, rely on feature sets that are not manually selected, but instead

learned during the training process (Morgan and Braasch 2021). CNNs can be applied to visual

representations of audio, such as spectrograms, leveraging their ability to learn patterns that

occur both spatially and temporally in data. This allows CNNs to learn local features regardless

of their spatial position within an image (Knight et al. 2017). CNNs are therefore ideal

candidates for the automated detection of signals within bioacoustic data, where instances of

relevant features within a spectrogram are not predefined or readily identifiable.

The suitability of CNNs is making them a highly popular choice of model to process

acoustic data (Stowell 2022). They have been used to analyse vocalisations from a variety of

taxa, including insects (Hibino et al. 2021), fish (Guyot et al. 2021), anurans (Colonna et al.

2016), birds (Narasimhan et al. 2017), bats (Mac Aodha et al. 2018), marine mammals (Miller et

al. 2023) and terrestrial mammals (Bjorck et al. 2019), including primates (Dufourq et al. 2021).

Their potential is far from fully realised however (Rammer and Seidl 2019), and there are

relatively few examples of CNNs being used to answer well-defined research questions in

ecology, as is so with other deep learning approaches (Dufourq et al. 2021). Additionally, there

are few guidelines on how to approach key steps such as model tuning and performance

assessments (Josh Patterson and Adam Gibson 2017; Knight et al. 2017; Stowell 2022). Further

case studies reporting successful applications will advance the development of best practices

for overcoming these challenges (Dufourq et al. 2021).

Gibbons (family Hylobatidae) are ideal candidates for the automated detection of

species-specific vocalisations. As they reside exclusively in tropical forests, which are often

visually challenging and inaccessible, studying their populations using visual methods, such as

line transect and camera trap surveys, is typically very difficult (Vu and Tran 2019). Gibbons

engage in loud, highly stereotyped song bouts which are largely confined to a specific daily

temporal period (Cheyne et al. 2008). During a particular calling bout, they usually emit

multiple calls, allowing for ample training data (Clink et al. 2023). Here, we apply a variation of a

pre-defined CNN architecture, DenseNet (Huang et al. 2016), to identify female great call

vocalisations of the endangered Bornean white-bearded gibbon (*Hylobates albibarbis*) from a

long-term acoustic dataset. Since the great call is performed largely by mated females, it is

often used as an indicator of a gibbon family group, allowing for group density and spatial

distribution estimates to be derived from great call densities (Cheyne et al. 2016). We train a

detector with high precision that minimises false-positive rates (i.e., the rate of detections

incorrectly labelled as the positive class) for application to large acoustic datasets recorded by

PAM arrays. This can then be used to facilitate accurate population monitoring of wild gibbons

on an ever-greater spatiotemporal scale and applied as a case study for developing PAM

frameworks for other endangered loud-call species.

II.   METHODS

A. Data collection

The long-term acoustic dataset used in this study derives from the Mungku Baru

Education Forest (MBEF), a ~50 km^2 area of tropical rainforest in Central Kalimantan, Indonesia.

The MBEF lies in the centre of the wider Rungan Forest Landscape, which covers 1,500 km^2

between the Kahayan and Rungan rivers north of the provincial capital of Palangka Raya. This

represents the largest area of unprotected lowland rainforest remaining on the island of

Borneo (Purnama and Afitah 2021). There is an estimated population of 4,000 white bearded

gibbons in the Rungan Landscape and an estimated density of 2.79 groups per km^2 in the MBEF,

making it of significant importance for the conservation of the species (Buckley et al. 2018).

Eight autonomous recording units (ARUs) (Song Meter SM4, Wildlife Acoustics,

Maynard, Massachusetts) were deployed here by WME in July 2018. These were placed on

trees, 5 meters high, in a dispersed grid with approximately 1,200 meters between each device.

The MBEF contains a mosaic of different forest types, and the location of the ARUs was

intended to reflect this heterogeneity, with three situated in 'kerangas' heath forest, three in

'low pole' peat swamp forest, and two in 'mixed swamp forest', with the latter representing a

transition habitat between the former two (Buckley et al. 2018).

The ARUs were set to record continuously from 4 am to 6 pm local time (WIB/UTC +7)

daily between 18th July 2018 to 5th January 2020. These were set to default settings (see

Appendix [i]) and recorded on two channels with a sampling rate of 24 kHz. Audio was captured

in 16-bit Waveform Audio File Format (WAV) and saved as one-hour files. Memory cards and

batteries were changed every two weeks.

B. Manual annotation

Separate manually-annotated training and testing datasets were required to develop

the automated detector. To create these samples, recordings between 4-10am were selected

from a single day every four weeks from a randomly selected device for each habitat. This

covers the temporal period in which most *H. albibarbis* great calls occur (Cheyne et al. 2008)

and ensured that a variety of potential sound environments were included as training inputs to

the model, improving its ability to generalise over a wider range of applications. The resultant

subset contained 300 hours of recording, covering 50 days spanning from October 2018 to

December 2019.

The selected sound files were then loaded into the sound analysis software Raven Pro

1.6, (K. Lisa Yang Center for Conservation Bioacoustics, Ithaca, NY, USA) and visualised as

spectrograms (see Appendix [ii]). With assistance from a team of undergraduate interns, each

recording was listened to in full and visually scanned to identify great call events. A selection

was created for each event by drawing a box around the call in the spectrogram, providing

information about its time-frequency boundaries (see Figure 1).

FIG. 1. A spectrogram image of a female H. albibarbis great call, created using Raven Pro 1.6.

This vocalisation comprises of introductory (a), climax (b) and descending (c) notes. The red box

represents the time and frequency boundaries of a manually-annotated selection. The time

boundaries span from the start of the first introductory note to the end of the last descending

note. The frequency boundaries span from the lowest frequency descending note up to the

highest frequency climax note.

Each selection was annotated for its completeness and quality. A selection was marked

as "clear" when the entirety of the call could be heard and was visually clear in the

spectrogram, "faint" when the whole call could be heard but was not fully shown in the

spectrogram (and vice versa), and very faint when the call was only partially seen and heard

(i.e., part of the great call was not captured in the recording). Each annotation was confirmed

by AFO to reduce the influence of inter-observer variability. In total, 1611 great calls were

annotated.

The manually-annotated data was then randomly split, with 70% allocated for training

(210 hours, 1089 calls) and 30% allocated for testing (90 hours, 522 calls). Due to the

ambiguous nature of "very faint" calls, they were removed from the training process and used

solely for testing thereafter. This prevented misleading information, i.e., non-target events,

being fed into the positive class weightings. Models were trained using "clear" and "faint"

instances (729 calls), as well as only "clear" instances (522 calls).

C. Automated detection

The development and testing of the automated detector utilised Koogu (version 0.7.2)

(Madhusudhana 2023), an open-source framework for deep learning from bioacoustic data.

Koogu offers a variety of functions for deep learning, including preparing audio for use as inputs

to machine learning models, training models, assessing their performance, and using trained

models for the automated analysis of large datasets. For a full workflow describing how the

following steps were implemented within Koogu, see Supplementary Material A.

1. Data preparation

All audio files were first down sampled to 4,500 Hz to reduce the overall file size and

improve the efficiency of downstream computations (Miller et al. 2023). The resulting Nyquist

frequency (2,250 Hz) is above the highest manually-annotated great call frequency (2,077 Hz),

and so no relevant information was lost in this process. The recordings were then split into

consecutive 28 second (s) segments (longer than the longest manually-annotated great call at

27.7s) with a hop size of 1s, leaving an overlap of 27s between clips. The waveform of each

segment was normalised by scaling the amplitudes to occur in the range -1.0 to 1.0.

The resulting start and end times of each segment were then compared to those from

manual annotations. Segments that fully contained the temporal extents of an annotated great

call were considered as positive inputs while segments without temporal overlap were

considered as negative inputs. Segments with partial overlap were excluded from training as

these could resemble non great call events and so lead to uncertainties during the training

process.

Spectrograms for both the positive and negative class were then computed (see

Appendix [iii]), resulting in input spectrograms with a shape of 384 x 580 (height x width) pixels.

To address the imbalance between positive and negative classes, the maximum number of

training inputs for each class was reduced to 10,000. This utilised all the positive class inputs

while randomly subsampling inputs from the negative class. Following this, there were 5,763

"clear" and 1,253 "faint" positive class spectrograms as well as 10,000 negative class

spectrograms.

2. Data augmentation

Despite the manually-annotated calls showing a high level of variance in background

noise, call duration and note length, for example, data augmentation was applied to further

improve input variance. To do this, several pre-defined augmentations supported by Koogu

were applied both on waveforms before conversion into spectrograms, and on the

spectrograms themselves. These were performed at each epoch, i.e., each time the model

passed through the entire training dataset, during the feeding of inputs into the model. This

meant that the same original sample could have different levels of augmentations between

epochs.

Firstly, Gaussian noise (Schlüter and Grill 2015) was added to 25% of the training input's

waveforms at each epoch to simulate varying levels of background noise. The amount of noise

added randomly varied from -20dB to -30dB below the peak dB of the input signal.

The spectrogram was then smeared and squished along the time axis (Madhusudhana

2023). These augmentations were independently added to 20% of the input spectrograms each

epoch, at a magnitude of -1,1 (smearing backwards and forwards by one frame of the

spectrogram) and -2,2 (stretching and squishing over up to 2 frames of the spectrogram). This

process essentially blurred inputs along the time axis, as while the target calls were contained

within a standard frequency range, the duration of the signals was highly variable.

205   Finally, Koogu's "AlterDistance" augmentation was applied on 25% of the spectrogram

206 inputs. This aimed to mimic the effect of increasing or reducing the distance between the

207 calling gibbon and the receiver, by attenuating or amplifying higher frequencies while keeping

208 lower frequencies relatively unchanged. This was applied by a random factor between -5dB

209 (attenuation) and 5dB (amplification).

210   **_3. Network parameters and training_**

211 The DenseNet architecture (Huang et al. 2016) was chosen as the base CNN architecture for this

212 study. Early variations of the model suffered from overfitting, occurring when the model learns

213 noise or random fluctuations in the training data rather than the underlying pattern itself. This

214 is a symptom of when the model is too complex relative to its intended task. Bearing this in

215 mind, the standard DenseNet architecture was adapted to a "quasi-DenseNet" architecture

216 (Madhusudhana et al. 2021). This reduces the number of connections within each dense block,

217 limiting model size and complexity. To limit the model's complexity further and improve

218 computational efficiency, bottleneck layers were also added (Huang et al. 2016). Finally, batch

219 normalisation was enabled to improve model convergence. For the final model architecture,

220 see Figure 2.

FIG. 2. Flowchart showing the final model architecture. The final model had a growth rate of 12,

began with a 16-filter pre-convolutional layer, contained 3 quasi-dense blocks with 4, 6 and 6

layers respectively and finished on a 32-node dense layer. Average pooling layers downscaled

the inputs by a factor of 3x3 (height x width) in the transition blocks between quasi-dense

blocks. Global Average pooling was used to reduce the spatial dimensions of outputs of the

final block to the 32-node feature vectors.

Training inputs were then divided further, with 15% randomly selected as a validation

set to evaluate the model's performance throughout the training process. Dropout layers were

added (Srivastava et al. 2014) at a rate of 5% to further reduce overfitting and improve

generalisation. The models were then trained over 80 epochs using the Adam optimizer

(Kingma and Ba 2014) with a minibatch size of 24. The learning rate was initially set at 0.01 and

then reduced successively by a factor of 10 at epochs 20, and 40.

4. Testing

Trained models were then applied to the test dataset to provide a preliminary

assessment of model performance and establish a desirable detector threshold value. To do

this, each test segment was assigned a confidence score by the model between 0 and 1

indicating how likely it was to contain a great call. For thresholds 0 to 1, with an interval of 0.01,

performance scores were outputted containing the number of true positives (TP), false

positives (FP) and false negatives (FN). If there was a 100% overlap between an input and an

annotated great call, and the confidence score was above the threshold it was marked as a TP.

If there was no- or partial overlap and the score was above the threshold it was marked as an

FP. If there was full overlap but the confidence score was below the threshold, then it would be

marked as a FN.

These quantities were used to compute recall, precision, and F score at each threshold.

Recall was defined as: *TP/(TP+FN)*, precision as: *TP/(TP+FP)*, and F score as: *2(PxR)/(P+R)* (where

P = precision and R = recall). The optimal threshold was then selected using maximum F score,

as it has been shown to be a good indicator of overall model performance (Clink et al., 2023).

Once a threshold had been decided, the model was re-run on the test dataset audio files

to produce detections and analyse the models' output. Neighbouring segments for which

scores were above the identified threshold were grouped together to form a single detection.

The score of each detection was then set as the maximum of its component segment scores,

and its start and end times were set to the start time of the first segment and the end time of

the last segment respectively. This considered every segment generated, regardless of the

amount of overlap with any annotation. These detections were then outputted in the format of

Raven Pro selection tables.

D. Post-processing

Initial inspection of the models' outputs showed that they produced clusters of

detections for each great call, overestimating the number of calls within the data. To minimise

the number of repeat detections for each target event, these were grouped together further

(see Supplementary Material B). If any detections overlapped with the first model detection,

then they were assigned to the same group. This process iterated across all the models'

detections, forming groups based off the first detection in each cluster of detections. These

groups were then filtered to retain only the highest scoring detection(s) within each group.

Where the start times of remaining selections were the same, only one detection was retained.

There was no further judication between remaining detections where their scores were tied, as

this could indicate that two great calls overlapped or occurred close in time.

III.   RESULTS

A. Preliminary assessment

The preliminary assessment of the best performing model, trained on only "clear" calls,

showed precision ranging from 0.19 to 0.97 and recall ranging from 0.93 to 0.23 at thresholds

from 0.01 to 0.99 (Fig. 3). This gave a maximum F score of 0.75 at a threshold of 0.36 (precision:

0.80, recall: 0.70).

As the aim was to optimise the model for "clear" and "faint" calls, the testing was re-run

excluding "very faint" calls. In this case, precision ranged from 0.12 to 0.94 and recall ranged

from 0.99 to 0.33 at thresholds from 0.01 to 0.99 (Fig. 3). The maximum F score was improved

to 0.78 at a threshold of 0.78 (precision: 0.80, recall: 0.76). To maximise performance for

"clear" and "faint" calls while minimising false positives, a threshold of 0.78 was therefore

chosen.

FIG. 3. Precision-recall curves of the best performing model tested against all calls (left) and

both "clear" and "faint" calls (right).

B. Comparison with manual annotations

After re-running the chosen model on the test dataset at the desired threshold and

processing the output, it produced 535 detections. These were then visually analysed in Raven

Pro and compared to the manually-annotated dataset to discern the true number of TPs, FPs,

and FNs. In this case, a TP instance was defined as any model detection that overlapped with a

great call. The model was found to have produced 511 TPs and 24 FPs, missing a further 133

calls (FNs). This gives a precision of 0.96, a recall of 0.79, and an F score of 0.87.

Upon closer inspection of the post-processed model output, 86 of the TP detections

were the result of repeated detections for singular great call events. Additionally, 22 FNs were

classed as TPs before the post-processing stage. These were created as a result of grouping

together detections where two great calls overlapped in time or were adjacent to one another,

despite them being within the bounds of the model's detections prior to processing the output.

Overall, the non-post-processed model identified 409 (78%) of the 522 manually-

annotated calls. This included 98% of all "clear" calls, 73% of "faint" calls, and 44% of "very

faint" calls. Out of the FN instances before post-processing, 77% were "very faint" calls with

only 0.05% representing 6 missed "clear" annotations. A further 38 great calls were identified

which had been missed in the manual annotation stage, including 6 "clear", 8 "faint" and 24

"very faint" calls.

The frequency of great call detections over time for both the non-post-processed and

post-processed model outputs were compared against the manually-annotated dataset. A

Kolmogorov–Smirnov test indicated no significant difference (D = 0.036, $p > 0.05$ and D = 0.045,

$p > 0.05$ respectively). Also, we found no significant difference between pre-processed and

post-processed data (D = 0.020, $p > 0.05$).

FIG. 4. Histogram showing the number of great calls detected every 5 minutes between 04:00

and 10:00 for the manual annotations, the non-post-processed model output, and the post-

processed model output.

IV.   DISCUSSION

The results show how our best performing model was effective at detecting high-quality

H. albibarbis great calls with a low rate of false positive instances. The best performing model (F

score: 0.87) exceeded previously reported SVM models for detecting gibbon vocalisations e.g.,

Hylobates funereus detector, F score: 0.78 (Clink et al. 2023). It also performed comparatively

to other CNN models, e.g., *Nomascus hainanus* detector, F score: 0.91 (Dufourq et al. 2021),

Nomascus concolor detector, F score: 0.92 (Zhou et al. 2023).

We found that the best performing model detected 38 great calls that had been missed

during the manual annotation stage, amounting to 0.07% of the total number of target events.

Human listening is subject to error (Brauer et al. 2016; Knight et al. 2017), and this study relied

on multiple human observers with differing levels of training to construct the manually-

annotated dataset. While it has been shown that human observers with less experience may

perform worse than some automated detectors (Jennings et al. 2008), the consensus from

multiple observers may have actually reduced the level of human error (Drake et al. 2016).

Furthermore, signals with low signal to noise ratio (SNR) are difficult to detect for both humans

and automated detectors (Knight et al. 2017). Precision and recall are often measured relative

to manually-annotated datasets, but these are not always perfect. With this in mind, it has

been recommended to view the manually-annotated dataset as the output from an alternative

detector rather than a ground truth set (Knight et al. 2017).

Due to the apparent inevitability for great calls to be missed by manual annotation, it is

unrealistic to presume that all target calls were identified in the 210-hour training dataset. This

could pose a problem when training the model if any of the randomly selected unannotated

time periods for the negative class contained target events, potentially increasing the rate of

false negatives. Dufourq et al. (2021) found that better results were obtained by specifically

including negative class segments with typical ambient noise, such as other species'

vocalisations, which could potentially confuse the classifier. This method of 'hand picking' the

negative class could reduce the false negative rate while also reducing the false positive rate by

negatively labelling potentially confusing information. The low false positive rate reported in

this study, as well as the low false negative rate for "clear" calls, suggests that our method of

randomly selecting the negative class was sufficient for our aims. Where reducing the false

negative rate has greater importance, such as identifying infrequent vocalisations, a more

thorough approach could be preferable. Either way, it is important to recognise the trade-off

between ensuring that the negative class contains as little erroneous information as possible

and the time required to construct an adequate training dataset.

345   It is important to acknowledge that the distinction of great calls into "clear", "faint" and

"very faint" categories was not based on exact measurements. These categories cannot be

translated directly to distance; however, in most cases, it is likely that "clear" calls were

recorded from gibbons singing closer to the ARUs. Overall, our best performing model

identified 98% of all "clear" calls, missing only 6 from the manually-annotated dataset. This was

comparable to the human observers, who also missed 6 "clear" calls. The model performed

worse than the human detector at detecting "faint" and "very faint" calls, however, picking up

73% and 44% of the manually-annotated instances respectively. With this in mind, the results

suggest that detection likelihood is affected by the caller-ARU distance (Spillmann et al. 2015).

This supports the suggestion by Jahn et al. (2017) that the difference in recall between an

automated detector and a human listener is caused by the former having a smaller detection

radius. Future studies should aim to apply relationships between signal strength and the

distance of the source from the receiver to estimate call detection probability over distance.

This will help to determine the effective area being sampled by PAM studies.

359   Although the model did not have perfect recall, the importance of detecting all great

calls within a recording will depend on the research question. With regards to calling activity

over time, the distribution of calling frequency detected by the model was not significantly

different to that of the manual annotations. Therefore, our model can be used to estimate

spatiotemporal variations in *H. albibarbis* calling activity. Through analysing recordings from

multiple habitats, our model could be applied to understand the relative importance of forest

subtypes for the species, as singing behaviour is density dependent (Cheyne et al. 2008), with

less singing activity at lower group densities. This could operate on a continuous long-term time

frame which would be hard to achieve when relying on human observers in the field.

For an in-depth understanding of gibbon group abundance and density, further

information is necessary. One method is to use individuals as the sampling unit (Buckland 2006)

by analysing their call structure (Clink et al. 2023), or by localising vocalisations using estimates

of direction to the source from multiple ARUs (Stevenson et al. 2015). This may prove highly

effective at estimating gibbon abundance and density over the short term yet could prove too

complex over the course of hundreds, or thousands of hours of audio. An alternative method is

to estimate vocalisation density per unit time, apply an estimation of vocalisation rate, and

then convert vocalisation density into group density (Marques et al. 2013). This does require a

knowledge of the area covered by each ARU, yet, for this task, Marques et al. (2013) notes that

automated detectors need not perform extraordinarily well so long as true positive and false

positive rates are characterised accurately. This method does not require for the effective area

of ARUs to overlap, so in theory could monitor a larger area with the same resources.

While post-processing greatly reduced the number of repeated detections for single

great call events, these would still account for many false positives if only one true positive per

great call is allowed. The post-processing protocol did not seek to judicate between detections

if there was a tie in the highest scoring instances within a group, as in some cases this

represented two great call events close in time. In fact, 22 false negatives derived from

instances when the grouping of detections failed to take this into account, and limiting the

number of detections per group to one would have increased the false negative rate further. An

alternative approach would be an improved post-processing stage to better interpret the

output of the model. In audio classification, CNNs inspect audio recordings as image-like

segments and so are unable to use broader-scale contextual information, such as whether the

current point in a recording is preceded by a target call (Wang et al. 2022). It has therefore

been proposed to combine CNNs with other machine learning techniques, such as Hidden

Markov Models (HMMs) or deep learning techniques, such as Recurrent Neural Networks

(RNNs). Postprocessing the output of a CNN with a HMM or an RNN has been shown to improve

F score (Madhusudhana et al. 2021; Wang et al. 2022). For instance, Wang et al. (2022) showed

that the application of a combined Convolutional Recurrent Neural Network (CRNN) reduced

error rates arising from overestimation of gibbon calls (49-54%) to 0.5%. It was noted, however,

that while post-processing the model output with a HMM performed second best, it required

much less computational power. Future work should therefore consider both of these options

when attempting to improve on our post-processing method.

A key aim of this study was to help address the analysis bottleneck evident in PAM data

by improving on the time taken to manually analyse recordings. During the batch processing

stage, it took 19 seconds for our trained model to process each hour of test recordings. This

greatly improved on a human processing speed of minimum 1 hour per hour of audio for this

study, varying depending on the level of observer experience. One caveat is the significant

amount of time required to construct a manually-annotated dataset to train and test a CNN

when compared to other machine learning approaches (Stowell 2022). Despite our study

showing how data augmentation can be effective where training data is limited, careful

consideration should be taken when under time-pressure if no training datasets are already

available. In some cases, it may be better to adopt an approach that requires less data to

develop, such as an SVM or a GMM (Clink et al. 2023).

Stowell (2022) noted that it was increasingly common to evaluate deep learning models

on test sets specifically designed to differ in some respects from the training data, such as

location, signal to noise ratio, or by season. In this case, the model was designed with

application to the MBEF bioacoustic dataset in mind, and so it is appropriate that the test data

came from the same location as the training data. Test inputs spanned across all times of the

year and were recorded from three different habitats. This ensured a variety of potential sound

environments were included in the testing stage. However, for applications in other locations,

especially outside the Rungan Forest Landscape, it would be advantageous to first test the

model on recordings captured elsewhere within *H. albibarbis'* range.

V.   CONCLUSION

Our study demonstrates how an open-source deep-learning framework can be adapted

to produce a CNN capable of detecting *H. albibarbis* great calls, performing at a comparative

level to similar CNN approaches (see Table 1). Our model performed best on the highest-quality

calls and yielded a low false-positive rate, meeting the objectives of this study. There was a

much lower likelihood of successful detection for the lowest-quality calls, however, and future

studies should aim to estimate call detection probability over distance to determine the

effective area being sampled.

Further development of the post-processing stage could help to reduce the number of

repeat detections for each call. However, the current output can be used to estimate calling

rate over time. Further work should seek to apply this model to long-term acoustic datasets

over a variety of habitats to study spatial and temporal variation in gibbon calling activity.

Furthermore, in combination with future studies on sound propagation of gibbon vocalisations,

this represents an opportunity to monitor *H. albibarbis'* populations on an ever-greater

spatiotemporal scale. Our work presents some key considerations to inform decision-making

for such projects, and a full workflow script to visualise how these can be implemented in

developing an automated detector.

SUPPLEMENTARY MATERIAL

For the full Koogu workflow, see Supplementary Material A (SuppPub1.txt). For the post-

processing script, see Supplementary Material B (SuppPub2.txt).

ACKNOWLEDGEMENTS

We thank Universitas Muhammadiyah Palangkaraya and the Borneo Nature Foundation for

access and support at the Mungku Baru Education Forest. We thank the Indonesian

government for permission to carry out this research (RISTEK foreign research permits:

189/SIP/FRP/E5/Dit.KI/VI/2018 and 43/E5/E5.4/SIP.EXT/2019 [Wendy M. Erb], BRIN foreign

research permits: 223/SIP/IV/FR/5/2023 [F. J. F. van Veen] and 225/SIP/IV/FR/5/2023 [A. F.

Owens]). We thank Erik Estrada and Rido for their invaluable support in deploying and

maintaining the ARUs and data in the field. We also thank Georgia Allen, Amy Barron, Sophie

Carpenter, and Elena Gough for their contributions in creating the manually-annotated dataset.

This project has been a collaboration between international and Indonesian researchers from

the start and this is recognised in joint authorship here. In addition, the Indigenous Dayak Ngaju

community of Mungku Baru have been closely involved in the field research, sharing their

knowledge, and discussing the implications with researchers and with local conservation

practitioners from Yayasan Borneo Nature.

AFO, FJFvV, WME, MAI and KH developed the project and concept; MAN, TMS and SMS

provided permissions and guidance for field study design and execution; AFO, SM and MS

carried out building and analysis of the model; AFO drafted the manuscript to which all other

authors then contributed to produce the final version.

AUTHOUR DECLARATIONS

The authors declare no competing interests.

DATA AVAILABILITY

[Recordings of great calls for both the training and testing datasets will be uploaded to a public

repository that issues datasets with DOIs before publication.]

ETHICS APPROVAL

Ethical approval was provided by the University of Exeter (application ID: 1845574), BRIN

(application number: 22022023000026) and Rutgers University (IACUC ID: PROTO201800073).

APPENDIX

i. Song Meter SM4 default settings: sensitivity of -35 ± 4 dB (0 dB = 1V/pa@1kHz), dynamic

range of 14 to 100 dB SPL at 0 dB gain, microphone gain of 16 dB, and inbuilt preamplifier gain

of 26 dB.

ii. Spectrograms were loaded into Raven Pro 1.6 for manual annotation. These were generated

using a 3462-sample Hann window with a 90% overlap and a 4096-sample Discrete Fourier

Transformation.

iii. Spectrograms were computed to provide inputs to the CNN model. These had an analysis

window of 0.192s and a 75% overlap. The bandwidth was also restricted to between 200 and

2200 Hz to exclude noise outside of the target frequency range.

REFERENCES

Acevedo, M. and Villanueva-rivera, L. 2010. From the Field: Using Automated Digital

Recording Systems as Effective Tools for the Monitoring of Birds and Amphibians. *Wildlife*

Society Bulletin 34(1), pp. 211–214.

Mac Aodha, O. et al. 2018. Bat detective—Deep learning tools for bat acoustic signal

detection. *PLOS Computational Biology* 14(3), p. e1005995. doi: 10.1371/journal.pcbi.1005995.

Bender, D. J., Contreras, T. A. and Fahrig, L. 1998. Habitat loss and population decline:

a meta-analysis of the patch size effect. *Ecology* 79(2), pp. 517–533.

Bengio, Y., Goodfellow, I. and Courville, A. 2016. *Deep Learning*. Cambridge,

Massachusetts: MIT Press.

Bjorck, J., Rappazzo, B.H., Chen, D., Bernstein, R., Wrege, P.H. and Gomes, C.P. 2019.

Automatic Detection and Compression for Passive Acoustic Monitoring of the African Forest

Elephant. *Proceedings of the AAAI Conference on Artificial Intelligence* 33(01), pp. 476–484.

doi: 10.1609/aaai.v33i01.3301476.

Borowiec, M.L., Dikow, R.B., Frandsen, P.B., McKeeken, A., Valentini, G. and White,

A.E. 2022. Deep learning as a tool for ecology and evolution. *Methods in Ecology and Evolution*

13(8), pp. 1640–1660. doi: 10.1111/2041-210X.13901.

Brauer, C.L., Donovan, T.M., Mickey, R.M., Katz, J. and Mitchell, B.R. 2016. A

comparison of acoustic monitoring methods for common anurans of the northeastern United

States. *Wildlife Society Bulletin* 40(1), pp. 140–149. doi: 10.1002/wsb.619.

Buckland, S.T. 2006. Point-Transect Surveys for Songbirds: Robust Methodologies. *The*

Auk 123(2), pp. 345–357. doi: 10.1093/auk/123.2.345.

498  Buckley, B. et al. 2018. Biodiversity, Forest Structure & Conservation Importance of the

499 Mungku Baru Education Forest, Rungan, Central Kalimantan. *Borneo Nature Foundation*.

500  Cheyne, S. et al. 2016. Population mapping of gibbons in Kalimantan, Indonesia:

501 correlates of gibbon density and vegetation across the species' range. *Endangered Species*

502 *Research* 30, pp. 133–143. doi: 10.3354/esr00734.

503  Cheyne, S.M., Thompson, C.J.H., Phillips, A.C., Hill, R.M.C. and Limin, S.H. 2008.

504 Density and population estimate of gibbons (Hylobates albibarbis) in the Sabangau catchment,

505 Central Kalimantan, Indonesia. *Primates* 49(1), pp. 50–56. doi: 10.1007/s10329-007-0063-0.

506  Clink, D.J., Kier, I., Ahmad, A.H. and Klinck, H. 2023. A workflow for the automated

507 detection and classification of female gibbon calls from long-term acoustic recordings. *Frontiers*

508 *in Ecology and Evolution* 11. doi: 10.3389/fevo.2023.1071640.

509  Colonna, J., Peet, T., Ferreira, C.A., Jorge, A.M., Gomes, E.F. and Gama, J. 2016.

510 Automatic Classification of Anuran Sounds Using Convolutional Neural Networks. In:

511 *Proceedings of the Ninth International C* Conference on Computer Science & Software*

512 *Engineering - C3S2E '16*. New York, New York, USA: ACM Press, pp. 73–78. doi:

513 10.1145/2948992.2949016.

514  Drake, K.L., Frey, M., Hogan, D. and Hedley, R. 2016. Using digital recordings and

515 sonogram analysis to obtain counts of yellow rails. *Wildlife Society Bulletin* 40(2), pp. 346–354.

516 doi: 10.1002/wsb.658.

517  Dufourq, E. et al. 2021. Automated detection of Hainan gibbon calls for passive acoustic

518 monitoring. *Remote Sensing in Ecology and Conservation* 7(3), pp. 475–487. doi:

519 10.1002/rse2.201.

Guyot, P., Alix, F., Guerin, T., Lambeaux, E. and Rotureau, A. 2021. Fish migration

monitoring from audio detection with CNNs. In: *Audio Mostly 2021*. New York, NY, USA: ACM,

pp. 244–247. doi: 10.1145/3478384.3478393.

Heinicke, S., Kalan, A.K., Wagner, O.J.J., Mundry, R., Lukashevich, H. and Kühl, H.S.

2015. Assessing the performance of a semi‑automated acoustic monitoring system for primates.

Methods in Ecology and Evolution 6(7), pp. 753–763. doi: 10.1111/2041-210X.12384.

Hibino, S., Suzuki, C. and Nishino, T. 2021. Classification of singing insect sounds with

convolutional neural network. *Acoustical Science and Technology* 42(6), p. E2152. doi:

10.1250/ast.42.354.

Huang, G., Liu, Z., van der Maaten, L. and Weinberger, K.Q. 2016. Densely Connected

Convolutional Networks.

Jahn, O., Ganchev, T.D., Marques, M.I. and Schuchmann, K.-L. 2017. Automated Sound

Recognition Provides Insights into the Behavioral Ecology of a Tropical Bird. *PLOS ONE* 12(1),

p. e0169041. doi: 10.1371/journal.pone.0169041.

Jennings, N., Parsons, S. and Pocock, M.J.O. 2008. Human vs. machine: identification

of bat species from their echolocation calls by humans and by artificial neural networks.

Canadian Journal of Zoology 86(5), pp. 371–377. doi: 10.1139/Z08-009.

Jetz, W. et al. 2019. Essential biodiversity variables for mapping and monitoring species

populations. *Nature Ecology & Evolution* 3(4), pp. 539–551. doi: 10.1038/s41559-019-0826-1.

Josh Patterson and Adam Gibson. 2017. *Deep Learning*. Loukides, M. and McGovern,

T. eds. O'Reilly Media.

Kingma, D.P. and Ba, J. 2014. Adam: A Method for Stochastic Optimization.

Knight, E.C., Hannah, K.C., Foley, G.J., Scott, C.D., Brigham, R.M. and Bayne, E. 2017.

Recommendations for acoustic recognizer performance assessment with application to five

common automated signal recognition programs. *Avian Conservation and Ecology* 12(2), p.

art14. doi: 10.5751/ACE-01114-120214.

Kong, Q., Xu, Y. and Plumbley, M.D. 2017. Joint detection and classification

convolutional neural network on weakly labelled bird audio detection. In: *2017 25th European*

Signal Processing Conference (EUSIPCO). IEEE, pp. 1749–1753. doi:

10.23919/EUSIPCO.2017.8081509.

Madhusudhana. 2023. shyamblast/Koogu: v0.7.2.

Madhusudhana, S. et al. 2021. Improve automatic detection of animal call sequences

with temporal context. *Journal of The Royal Society Interface* 18(180), p. 20210297. doi:

10.1098/rsif.2021.0297.

Marques, T.A. et al. 2013. Estimating animal population density using passive acoustics.

Biological Reviews 88(2), pp. 287–309. doi: 10.1111/brv.12001.

Mielke, A. and Zuberbühler, K. 2013. A method for automated individual, species and

call type recognition in free-ranging animals. *Animal Behaviour* 86(2), pp. 475–482. doi:

10.1016/j.anbehav.2013.04.017.

Miller, B.S., Madhusudhana, S., Aulich, M.G. and Kelly, N. 2023. Deep learning

algorithm outperforms experienced human observer at detection of blue whale D-calls: a

double-observer analysis. *Remote Sensing in Ecology and Conservation* 9(1), pp. 104–116. doi:

10.1002/rse2.297.

Morgan, M.M. and Braasch, J. 2021. Long-term deep learning-facilitated environmental

acoustic monitoring in the Capital Region of New York State. *Ecological Informatics* 61, p.

101242. doi: 10.1016/j.ecoinf.2021.101242.

Narasimhan, R., Fern, X.Z. and Raich, R. 2017. Simultaneous segmentation and

classification of bird song using CNN. In: *2017 IEEE International Conference on Acoustics,*

Speech and Signal Processing (ICASSP). IEEE, pp. 146–150. doi:

10.1109/ICASSP.2017.7952135.

Noda, J.J., Travieso, C.M., Sanchez-Rodriguez, D., Dutta, M.K. and Singh, A. 2016.

Using bioacoustic signals and Support Vector Machine for automatic classification of insects. In:

2016 3rd International Conference on Signal Processing and Integrated Networks (SPIN). IEEE,

pp. 656–659. doi: 10.1109/SPIN.2016.7566778.

Norouzzadeh, M.S., Nguyen, A., Kosmala, M., Swanson, A., Palmer, M.S., Packer, C.

and Clune, J. 2018. Automatically identifying, counting, and describing wild animals in camera-

trap images with deep learning. *Proceedings of the National Academy of Sciences* 115(25). doi:

10.1073/pnas.1719367115.

Piel, A.K. and Wich, S.A. 2021. *Conservation Technology*. Wich, S. A. and Piel, A. K.

eds. Oxford University PressOxford. doi: 10.1093/oso/9780198850243.001.0001.

Purnama, A. and Afitah, I. 2021. Motivasi Masyarakat Terhadap Pengelolaan Khdtk

Mungku Baru, Palangka Raya. *Anterior Jurnal* 20(2), pp. 43–49. doi:

10.33084/anterior.v20i2.2162.

Rammer, W. and Seidl, R. 2019. Harnessing Deep Learning in Ecology: An Example

Predicting Bark Beetle Outbreaks. *Frontiers in Plant Science* 10. doi: 10.3389/fpls.2019.01327.

Schlüter, J. and Grill, T. 2015. Exploring Data Augmentation for Improved Singing Voice

Detection with Neural Networks. In: *, 16th International Society for Music Information Retrieval*

Conference.

Simon S. Haykin. 2009. *Neural Networks: A Comprehensive Foundation.* 3rd ed.

McMaster University, Canada: Pearson Education.

Spillmann, B., van Noordwijk, M.A., Willems, E.P., Mitra Setia, T., Wipfli, U. and van

Schaik, C.P. 2015. Validation of an acoustic location system to monitor Bornean orangutan (

Pongo pygmaeus wurmbii) long calls. *American Journal of Primatology* 77(7), pp. 767–776. doi:

10.1002/ajp.22398.

Srivastava, N., Hinton, G., Krizhevsky, A., Sutskever, I. and Salakhutdinov, R. 2014.

Dropout: A Simple Way to Prevent Neural Networks from Overfitting. *Journal of Machine*

Learning Research 15, pp. 1929–1958.

Stevenson, B.C., Borchers, D.L., Altwegg, R., Swift, R.J., Gillespie, D.M. and Measey,

G.J. 2015. A general framework for animal density estimation from acoustic detections across a

fixed microphone array. *Methods in Ecology and Evolution* 6(1), pp. 38–48. doi: 10.1111/2041-

210X.12291.

Stowell, D. 2022. Computational bioacoustics with deep learning: a review and roadmap.

PeerJ 10, p. e13152. doi: 10.7717/peerj.13152.

Sugai, L.S.M., Silva, T.S.F., Ribeiro, J.W. and Llusia, D. 2019. Terrestrial Passive

Acoustic Monitoring: Review and Perspectives. *BioScience* 69(1), pp. 15–25. doi:

10.1093/biosci/biy147.

Verma, A., van der Wal, R. and Fischer, A. 2016. Imagining wildlife: New technologies

and animal censuses, maps and museums. *Geoforum* 75, pp. 75–86. doi:

10.1016/j.geoforum.2016.07.002.

Vu, T.T. and Tran, L.M. 2019. An Application of Autonomous Recorders for Gibbon

Monitoring. *International Journal of Primatology* 40(2), pp. 169–186. doi: 10.1007/s10764-018-

0073-3.

Wang, Y., Ye, J. and Borchers, D.L. 2022. Automated call detection for acoustic surveys

with structured calls of varying length. *Methods in Ecology and Evolution* 13(7), pp. 1552–1567.

doi: 10.1111/2041-210X.13873.

Zhou, X. et al. 2023. Methods for processing and analyzing passive acoustic monitoring

data: An example of song recognition in western black-crested gibbons. *Ecological Indicators*

155, p. 110908. doi: 10.1016/j.ecolind.2023.110908.