Spatio-temporal transformers for decoding neural movement control

Benedetta Candelori[1], Giampiero Bardella[1,a,*], Indro Spinelli[b],
Pierpaolo Pani[a], Stefano Ferraina[a,†], Simone Scardapane[c,†,*]

[a] Department of Physiology and Pharmacology, Sapienza University of Rome, Italy
[b] Department of Computer Science, Sapienza University of Rome, Italy
[c] Department of Information Engineering, Electronics and Telecommunications,
Sapienza University of Rome, Italy
1, Equally contributing authors
†, Equally contributing co-senior authors
* corresponding author(s)

E-mail: `simone.scardapane@uniroma1.it`, `giampiero.bardella@uniroma1.it`

Abstract. Deep learning tools applied to high-resolution neurophysiological data have significantly progressed, offering enhanced decoding, real-time processing, and readability for practical applications. However, the design of artificial neural networks to analyze neural activity remains a challenge, requiring a delicate balance between efficiency in low-data regimes and the interpretability of the results. To this end, we introduce a novel specialized transformer architecture to analyze single-neuron spiking activity. We test our model on multi electrodes recordings from the dorsal premotor cortex (PMd) of non-human primates while performing a motor inhibition task. The proposed architecture provides a very early prediction of the correct movement direction - no later than 230ms after the Go signal presentation across animals - and can accurately forecast whether the movement will be generated or withheld before a Stop signal, unattended, is actually presented. We also analyze the internal dynamics of the model by computing the predicted correlations between time steps and between neurons at successive layers of the architecture. We find that their evolution mirrors previous theoretical analyses. Overall, our framework provides a comprehensive use case for the practical implementation of deep learning tools in motor control research.

1. Introduction

Recent innovations in brain recording technologies have enabled simultaneous investigation of vast neuronal populations. On one hand, this is leading to the replacement of conventional methods that rely on analyzing the activity of individual neurons with an ensemble approach, providing insights that could not be inferred solely from the modulation of single units [1–19]. On the other hand, the broad spectrum of recording technologies and the resulting abundance of experimental data have posed

challenges in developing standardized routines of analysis consistent across species and conditions. In such a plethora of information, machine learning algorithms, especially deep learning ones, are emerging as cutting-edge tools for skimming redundancies and selecting the most relevant variables for complex system's dynamics [20–25], opening exciting opportunities for analysis and interpretation of such data [26,27]. In particular, their application in cognitive neuroscience has gained significant attention for their appealing flexibility to link neural representations to behavioral outcomes [28].

In motor control research, decoding neural dynamics to predict motor intentions is of long-standing interest [29]. It is widely recognized that motor control is exerted by an intricate network of cortical, subcortical, cerebellar, and spinal structures [14, 30–41], in which crucial regions are the motor and premotor cortices. These structures play a pivotal role in the encoding of neural signals associated with the planning, execution, and inhibition of voluntary movements. It is also established that single neurons in the motor and premotor cortex codify specific parameters of movement intentions such as direction, speed, and type of intended movements [42–47] before their initiation. Some recently developed deep learning methods have shown potential to achieve remarkable results in decoding behavioral parameters related to movement [2,4,17,48–50] . Beyond the unquestionable scientific knowledge, one of the ultimate goals of these approaches is enhancing technological progress in prosthetic devices for motor-impaired patients. The scope of exploiting neural signals to control robotic devices or computer cursors in brain-machine interface (BCI) systems [51] is aiding individuals in which gestures, speech [13,51–53] or even spinal cord transmissions are compromised [54–57]. Crucially, the efficacy of BCIs heavily depends on their ability to decode and predict the user's intended behavior accurately, as well as on their power to infer the temporal dynamics and spatial functional connectivity patterns of the recorded neural ensembles.

Traditionally, the analysis of neural spiking activity with neural networks has involved the use of 1-dimensional convolutional or recurrent networks [21,58]. In the field of deep learning, transformer-based models, which are built on top of the so-called attention layer [59], have quickly replaced the use of convolutions or recurrences in multiple cases, from natural language processing to cellular automata [22] and computer vision [60]. For the reader less familiar with this terminology, we would like to stress that term "attention" is just a name overlay with the neurophysiological mechanism of attention. In the deep learning context, attention maps are visual representations that highlight the parts of the input data that the model deems most important for making predictions. In natural language processing tasks, for instance, attention maps may highlight specific words or phrases in a sentence. In computer vision tasks, they may pinpoint relevant objects or features in an image. In this paper we will use the term "attention" only in the deep learning sense, without implying any direct parallels to neurophysiological attention mechanisms. When looking at neural data, transformers have a number of interesting features. First, different types of data-formats (time series, images) can be analyzed with a unified architecture by proper pre-processing, e.g., via suitable tokenization or embedding stages [61]. Second, transformers are well-suited to forecasting tasks,

Figure 1. Overall schema of our framework. The experimental single-trial binary data matrix, with dimensions (neurons x time), is pre-processed into a set of vectors (tokens), each representing a small time interval. Having two layers, one temporal and one spatial, a token represent either "one neuron in time" or "all neurons at a given instant" depending on the layer. After adding positional embeddings, we process the tokens via n trainable transformer blocks. Each block is composed of multi-head attention (MHA) over the tokens, optionally masked for causal models, followed by another optional block that performs MHA over the transposed tokens. On the bottom of the figure, we show some examples of the outputs we can obtain by visualizing the internal states of the model at each layer. See 2.5 for details.

such as the prediction of behavioral variables, e.g., movement direction or movement generations vs. movement inhibition, by proper masking of the attention layers, an operation that is highly efficient on modern hardware. Third, attention operates through pairwise comparisons of the input elements. The visualization of the resulting *attention maps* inside their layers provides useful information in terms of which parts of the input are interacting across the architecture [62]. Finally, spatio-temporal variants of the basic transformer [63] have popularized the idea of operating through alternating operations on the spatial and temporal dimension of the data via decomposable layers, making the models perform better on spatio-temporal data with a small number of trainable parameters. Although preliminary investigations have shown promise for the analysis of non-invasive EEG data [21], little has been done for the design of efficient, interpretable transformer-based models for analyzing intraparenchimal recordings of neural populations. To this end, in this paper we propose one of the first transformer-based models to analyze single neuron spiking activity in low-data regimes, which is shown schematically in Fig. 1.

2. Methods

2.1. Subjects

Two male rhesus macaque monkeys (Macaca mulatta, Monkeys P and C), weighing 9 and 9.5 kg, respectively, were employed for a Stop signal task, as shown in Fig. 2. Animal

Figure 2. Stop signal task. The target could appear in one of two directions (D1 or D2). In Go trials, monkeys had to reach and hold the peripheral target to get the reward. In Stop trials, monkeys had to refrain from moving to obtain rewards. Go and Stop trials were randomly intermixed during each session. See Section 2 for further details. RT: reaction time; CT: central target; Go: go signal appearance; M_on: movement onset. SSD, stop signal delay; SSRT, stop signal reaction time. White circles are feedbacks for the touch provided to the animals.

care, housing, surgical procedures and experiments conformed to European (Directive 86/609/ECC and 2010/63/UE) and Italian (D.L. 116/92 and D.L. 26/2014) laws and were approved by the Italian Ministry of Health. Monkeys were pair-housed with cage enrichment. They were fed daily with standard primate chow that was supplemented with nuts and fresh fruits if necessary. During recording days, the monkeys received their daily water supply during the experiments.

2.2. Apparatus and task

The monkeys were seated in front of a black isoluminant background ($< 0.1cd/m2$) of a 17-inch touchscreen monitor (LCD, 800 x 600 resolution) inside a darkened, acoustic-insulated room. A non-commercial software package, CORTEX (http://www.nimh.gov.it), was used to control the presentation of the stimuli and the behavioural responses. Fig. 2 shows the scheme of the task. The appearance of a central target (CT) (red circle with a diameter of 1.9 cm) signalled the start of the trial. Then, after a holding time of variable duration (400–900 ms, 100 ms increments), a peripheral target (PT) (red circle, diameter 1.9 cm) randomly appeared in one of two possible locations on the horizontal plane with respect to the CT (D1/D2) while the CT disappeared (Go signal). Following the Go signal, the subjects had to reach and hold the PT for a variable time (400–800 ms, 100 ms increments) to receive a reward. The time between the presentation of the Go signal and the onset of the hand movement

(**M_on**) is defined as reaction time (**RT**). Stop trials were identical to the Go trials until the Go signal, and then, after a variable delay known as the Stop signal delay (SSD), the CT reappeared, signaling the Stop signal. The monkeys had to hold the CT until the end of the trial, which was between 800-1000 ms, to get rewarded for a correct Stop trial (**CS**). To determine the duration of the SSDs a staircase tracking approach was utilized to obtain a success rate of roughly 50% in Stop trials. The SSD rose by 100 ms in the following Stop trial if the monkey successfully inhibited the movement. It was instead reduced by 100 ms if the monkey failed to cancel the response. A Stop trial was deemed incorrect (wrong Stop trial, **WS**) if the monkey removed its hand after the Stop signal and before the trial ended, and no juice was provided. For both correct Stop and correct Go trials, the same amount of reward was given. Stop trials accounted for approximately 25% of all Monkey P trials and 32% of Monkey C trials. White circles after touching the screen were provided to the animals as feedbacks.

2.3. Behavioral analysis

In the stop-signal task, the efficiency in movement suppression can be calculated through the so-called Stop Signal Reaction Time (**SSRT**). The expected behavior in the Stop trials is described by the *race model* [64], which comprises the competition towards a threshold of two stochastic processes: the GO process, triggered by the Go signal and whose duration is represented by the RT, and the STOP process, whose duration must be computed. When the GO process wins the race versus the STOP process, movement is generated, resulting in wrong Stop trials. Conversely, when the STOP process prevails, the movement is inhibited, resulting in correct Stop trials. SSRT may be estimated by exploiting the race model by considering the duration of the GO process, the probability of response, and the Stop-Signal Delays (**SSDs**). Among various methods to estimate the SSRT, the so-called integration approach has been demonstrated to be the most reliable one [65]. This method considers the existence of a certain probability of response (denoted as P(response)) for a given SSD in stop trials. The longer the SSD, the higher the P(response), indicating a higher probability of a wrong Stop trial. By integrating P(response) over the distribution of Go trials, the nth value Go RT is derived. Subtraction of the SSD from the nth Go RT yields the SSRT. To visualize the procedure, imagine an SSD where P(response) is exactly 0.5. For such an SSD, the Go and Stop processes would have the same probability of winning the race, meaning that they would both reach the threshold at the same time with equal probability. The ending times of the Stop and Go processes are the end of the SSRT and the end of the RT respectively, i.e., the beginning of the movement. Behavioural results for the analyzed sessions (2, one for each animal) are reported in Table 2.

2.4. Extraction and processing of neuronal data

A 96-electrode array (Blackrock Microsystems, Salt Lake City; electrode spacing: 0.4 mm) was surgically implanted in the left dorsal premotor cortex (PMd) taking as

reference the arcuate sulcus and pre-central dimple. The raw signal sampled at 24.4 kHz (Tucker Davis Technologies, Alachua, FL) was acquired. We used the spike sorting toolbox KiloSort3 with the following settings to get single neuron activities from the raw signal, similar to previous work [14,66]. Thresholds for template-matching on spike detection: (9 9); Lambda: 10 (bias factor of the individual spike amplitude towards the cluster mean); Area Under the Curve split: 0.9 (threshold for cluster splitting); Number of blocks: 5 (the number of blocks channels are divided into for estimating probe drift). The output of the sorter was curated manually in Phy (v2.0; 17) to merge clusters erroneously split by the automated sorter. Then, a binary data matrix of dimensions (neuron x time) with a time resolution of 1 ms (1 for a spike, 0 for no spikes) was obtained for each single trial of each monkey.

2.5. Transformer architecture

We use a special transformer architecture [59] arranged in a space-time configuration [63] that is tailored to simultaneously predicting movement direction (D1 vs. D2), movement intentions (movement vs. inhibition), and an estimate of the spatial and temporal correlations between the recorded neurons, using as input only their experimental spiking activity. Fig. 1 provides a visual schema of our model, denoted ST-T, and its outputs. First, a single-trial binary spike data matrix is preprocessed to convert it to a sequence of fixed-dimensional vectors (which we refer to as *tokens*). Then, we process the sequence via alternating attention-based blocks that operate on the time or on the neuron dimension of the input data. The network is trained for each time step to predict a predefined behavioural event, e.g. the movement onset. We show that this design provides at the same time a strong predictive accuracy of the event, as long as a set of explainable maps that describe the dynamics of the interactions between time steps and neurons inside each intermediate layer of the model, which can be visualized and compared to experimental ones and/or to theoretical models to validate the performance. By looking at the accuracy of the predictions and the evolution of the internal states of the network, several insights can be gathered, which are summarized qualitatively here and quantitatively in the experimental section.

1) Nonlinear correlation analysis: It has been shown that temporal and spatial correlations among neurons carry non-trivial features of the dynamics of executed and inhibited movements [14, 19, 41, 66–71]. Even if pairwise correlation can be computed with standard statistical techniques [72], it is not guaranteed that they are indicative in terms of predictive power for movement parameters, i.e., the type and direction. Because (artificial) neural networks are instead trained to evolve their internal representations to maximize performance, looking at the correlations across the internal embeddings of neurons and time intervals, information is extracted in the form of nonlinear, task-dependent correlations. We show below that suitably designed transformer models are a natural fit for this assignment, since representations are updated by pairwise comparisons of the internal tokens. The resulting *attention maps* can be immediately

visualized to understand the evolution of these dynamics (see Section 2.5). In addition,
the same model can be customized to work across different axes (time and/or space),
providing both attention maps as auxiliary outputs (see the bottom plots in Fig. 1 for
examples).

2) Forecasting accuracy: Second, operations inside a transformer can be easily
masked to obtain *causal* variants, in which the output y_t at time t does not depend
on input data $\mathbf{x}_{>t}$ corresponding to subsequent time indexes. By training a separate
predictor on each output $y_1, \ldots, y_T$ and looking at the average accuracy of the
predictions, we can analyze when, after the presentation of the Go signal, we can
accurately predict the trial outcome and the direction of movement, independently of
the specific RT and SSD. We now briefly describe the models that we used in the
analysis. For the D1 vs. D2 prediction, data is extracted for each trial in a fixed
interval of 400 ms, i.e., from 100 to 500 ms after the Go signal presentation, resulting
in a set $\{\mathbf{x}_t\}, \mathbf{x}_t \in \mathbb{R}^N$ corresponding to N neurons and $t = 1, \ldots, T$ time instants
$(T = 400)$. For the movement vs. inhibition prediction, data is extracted for each
trial from 100 to 300 ms after the Go signal presentation, to control for the stop Signal
appearance (T=200ms) (see Section 3). Because transformer models are equivariant
to permutations, sinuisodal embeddings [59] are added to the initial embeddings to
encode information about the distance between temporal instants. As shown in Fig. 1,
embeddings are then processed by a series of n trainable blocks. Each of these blocks
contains up to 2 standard transformer blocks which process data across the two axes.
First, a temporal transformer block is applied:

$$\mathbf{z}_t = \mathrm{LN}\left(\mathrm{MHA}\left(\{\mathbf{x}_i\}_{i=1}^{T}\right) + \mathbf{x}_t\right) \tag{1}$$

$$\mathbf{h}_t = \mathrm{LN}\left(\mathrm{FF}\left(\mathbf{z}_t\right) + \mathbf{z}_t\right) \tag{2}$$

where LN stands for layer normalization, SA for self-attention, and FF is a two-
layer fully-connected network applied to each token independently [59]. Note that the
only operation which combines information from multiple tokens is the SA. Denoting
generically by $\{\mathbf{x}_i\}$ the set of input tokens, MHA proceeds by first linearly projecting
each of them three times with different trainable matrices to obtain query tokens $\mathbf{q}_i$,
value tokens $\mathbf{v}_i$, and key tokens $\mathbf{k}_i$, before combining them as:

$$\mathbf{h}_i = \sum_j \mathrm{softmax}\left(\frac{1}{\sqrt{d}}\mathbf{q}_i^\top \mathbf{k}_j\right)\mathbf{v}_j \tag{3}$$

The outputs of the softmax operation can be combined into a $T \times T$ matrix, that we
call the *temporal attention matrix*. We also consider a causal variant of this layer, in
which all values such that $j > i$ are masked by setting the corresponding dot product to
$-\infty$. In this way, each output token $\mathbf{h}_t$ will only depends on the input tokens $\mathbf{x}_{t'}$ such
that $t' \leq t$, preserving the temporal dynamics of the signal. For the non-causal variant,
we also include a second, symmetrical block working on the channel-wise (spatial) axis.
Denoting by $\mathbf{H} \in \mathbb{R}^{T \times N}$ the matrix collecting the output of the first block, we apply

Table 1. Setting of hyperparameters for different predictions

Hyperparameters	D1 vs. D2			Movement vs. Inhibition	
	CNN	ST-T	Causal ST-T	CNN	ST-T
Heads	-	1	1	-	1
Layers	-	5	2	-	2
Learning Rate	$1e^{-4}$	$1e^{-4}$	$1e^{-4}$	$1e^{-4}$	$1e^{-5}$
Epochs	15	80	150	30	80
Batch size	8	8	8	8	8

a second block by first transposing the matrix, which is equivalent to considering the columns of $\mathbf{H}$ as the input tokens, before transposing again for the next block. We call the corresponding attention map of size $N \times N$ the *spatial attention matrix*. Note that SA can be extended by considering a multi-head variant (with multiple SA blocks running in parallel), but we ignore it here for better interpretability of the resulting attention maps. For training, we apply a prediction head to each output token independently, obtaining a series of predictions $\hat{y}_1, \ldots, \hat{y}_T$. For the non-causal variant, we discard all predictions except the last one, which we train to predict the binary label corresponding to the chosen event (D1 vs. D2 or movement vs. inhibition). For the causal variant (Causal ST-T), we consider a separate classification task for each time interval, and we optimize by minimizing the average loss across intervals. The test accuracies a_t for each interval can be plotted to visualize the moment in which the behavior becomes successfully predictable by the model.

3. Experimental results

We performed single-trial analyses aligning the temporal series of neural activity to the Go signal for each session data of both monkeys. Such alignment was motivated by the evidence that, after the Go signal, PMd neurons express strong modulations associated with movement control. Indeed, it has been shown that the motor planning of actions in the PMd is encoded at the population level through synchronization patterns that significantly peak around 200 ms before movement initiation [14, 19, 30, 34, 40, 41, 67, 68, 70, 71, 73, 73–77]. Considering the RT distributions shown in Table 2, for the D1 vs. D2 prediction we aligned neural activity [+100, +500] ms to the Go signal for both monkeys. This ensured an appropriate epoch comparison across animals, while also controlling not to include the first 100 ms after the Go signal to avoid any bias in the prediction due to purely visual processing of the stimuli. We benchmarked our model's performance against that of a simple CNN architecture. The hyperparameters of both architectures are reported in Table 1.

3.1. Prediction of movement direction

The accuracy of the predictions is reported in Table 3 for both architectures, both monkeys, and both trial types (Go and correct Stop trials). Overall, ST-T performs

Table 2. Behavioral results (mean ± std) for the analysed recording sessions

Subject	RT	SSD	SSRT
Monkey P	595 ± 90 ms	343 ± 70 ms	209 ms
Monkey C	671 ± 111 ms	423 ± 128 ms	207 ms

Table 3. Results for D1 vs. D2 prediction

Subject	CNN		ST-T	
	Go Trials	correct Stop Trials	Go Trials	Stop Trials
Monkey P	99.8%	94%	88%	96%
Monkey C	70.7%	66%	93%	93%

better than the basic CNN model, with an accuracy of over 90% in almost all sessions. The CNN is less consistent, yielding a high accuracy for Monkey P ($> 94\%$) but not for Monkey C ($\leq 70\%$). It is worth noting that our model predicts in advance the correct direction of movement for correct Stop trials as well, where movement is eventually inhibited. This is relevant for two reasons. The first is that it strongly confirms, at the neural level, the assumptions underlying the Stop Signal paradigm and its effectiveness in the study of response inhibition: that the movement is planned and then inhibited in the correct stop trials (see also Section 2.3). The second is that, our model provides an effective method to quantitatively measure how motor planning fully develops even when the movement is not eventually generated. These are two basic premises for being able to address the movement vs. inhibition prediction (see next paragraph). Then, we tested the stability of our prediction exploiting Causal ST-T. In this way we could obtain the time evolution of the prediction accuracy for movement direction in Go trials. Using Causal ST-T, we repeated the analysis first considering all the trials together and successively dividing the trials according to their RTs (four groups, as shown in Table 4). Results are shown in Table 4, Figure 3 and Figure 4. Considering all the trials together we are able to correctly decode movement direction with a 80% accuracy $\sim$ 200 ms after the Go signal for Monkey P and after $\sim$ 130 ms for monkey C. Since trials with slower RT imply later motor planning, we expect the time at which the prediction reaches high levels of accuracy to be progressively further away from the Go signal as the RT increases. As shown in Table 4 and Figure 4, it is evident how an high accuracy is reached earlier after the Go-signal for trials with faster RTs, confirming our assumptions. This is significant because it demonstrates the ability of our architecture in predicting the behavior efficiently for different levels of motor preparation.

Figure 3. Time evolution of the accuracy for D1 vs. D2 prediction for all the Go trials using the causal ST-transformer. Shaded areas are the standard deviations over multiple model runs.

Figure 4. Evolution of the prediction accuracy for movement direction for Go trials with different RTs. Shaded areas are the standard deviations over multiple model runs.

Table 4. Results for D1 vs D2 prediction using Causal ST-T for various gropus of RTs (RTs are reported in ms).

Go trials only	Time after the Go signal to reach >80% of accuracy				
	Overall	$RT < 520$	$520 \leq RT \leq 600$	$600 \leq RT \leq 700$	$RT \geq 700$
Monkey P	204 ms	140 ms	154 ms	233 ms	201 ms
Monkey C	135 ms	113 ms	115 ms	135 ms	135 ms

3.2. Prediction of movement inhibition

Our goal was also to predict the generation or inhibition of a movement. To do so, we chose the Stop trials corresponding to the SSD with the highest number of Stop trials presented, specifically 300 ms for Monkey P and 400 ms for Monkey C. This choice was forced by the smaller number of trials available for the correct Stop condition compared to Go trials and led to the inclusion of 62 Stop trials for monkey P and 27 for monkey C. This also prompted us to employ a simpler architecture, with only 2 layers instead of 5, so that the model could attain better generalization without overfitting. For this prediction, we aligned neural activity [+100, +300] ms after the Go signal,

Table 5. Movement vs. inhibition prediction results.

Subject	CNN		ST-T	
	All Trials	Stop trials	All trials	Stop Trials
Monkey P	83.9%	75%	95.1%	95%
Monkey C	71.4%	77%	92.6%	80%

thus controlling for the possible bias of including the Stop signal presentation in the time window of analysis. We performed two tests: in the first, we compared only the Stop trials (correct vs wrong) while in the second one we used all three trial types (go, correct Stop and wrong stop trials). Correct Stop trials can be compared with Go trials only if an appropriate subset of the latter is considered. Such subset must include all the Go trials that, if a Stop had appeared, would have had a high probability of being inhibited. These trials are called latency matched trials, and are the trials with $RT > SSD + SSRT$ (see also Section 2.3). As before, we compared the CNN and the Transformer performances. Results are shown in Table 5. Consistent with the D1 vs. D2 prediction, ST-T yields a significantly higher accuracy in both tests compared to the CNN. However, the latter also achieves a very good level of accuracy. We attribute the lower performance for Monkey C in the first test to the fewer number of trials available. The results obtained are quite noteworthy, as they demonstrate the efficiency of our model in predicting very early and accurately whether motion will be generated or not, even with very few trials available.

4. Conclusion

We conclude by giving a perspective of how the spatiotemporal attention maps provided by the model can be interpreted in a neurophysiological context. We leave a more extensive formal analysis for future investigations. The temporal attention maps represent how much the temporal correlations among the recorded neurons impact the required prediction. In our case, the magnitude of the matrix elements indicates the importance that the collective state of the neural ensembles at that time instant has in determining the forecast of the behavioral outcome. In Figure 5 panel A we compared the temporal attention matrices for the D1 vs. D2 prediction. The model's ability to identify new correlation patterns becomes evident as its depth grows, especially in correct Stop trials where condition-specific patterns of synchronization appear already from layer 2. This is particularly noticeable in panel B when looking at the distributions of their matrix elements as a function of depth. Interestingly, until about 250 ms after the Go signal, the synchrony patterns inferred by the model are very similar between conditions. This is suggestive of the partitioning of the phase space of neural activity into common and specific subspaces according to behavioral conditions [14,67]. Quantitative and formal study of these maps can facilitate the development of a causal connection between findings obtained with diverse methodologies [66]. This strategy

can also be extended to the spatial component of attention maps. Indeed, synchronized firing between spatially separated pairs of neurons is commonly employed as a measure of functional connectivity. As shown in earlier research [19, 41, 78, 79], differences in the topological organization of spatial synchronizations have a key role in explaining how motor cortices are involved in both movement generation and inhibition. Therefore, spatial attention maps produced by each layer could be compared to the experimental covariance matrices, looking for topological invariants between the two. In this scenario, these matrices could be interpreted as the adjacency matrices of weighted networks, with the spatial attention map that would represent a naive unsupervised inference of the spatial interaction graph of the system. However, with other methods also directed matrices could be obtained [22, 24, 25]. As also addressed by Ha et al. [22], this hints at how our ST-T architecture can be an alternative route for developing new models for so-called relational-inference problem: detect interactions among components of a dynamical system based on samples of the observed time-series [24, 25, 80–83]. In this regard, very recent works are addressing relational prediction from spike data [23] while others are seeking to infer detailed models and interpretable microscopic theories of physical systems [84] directly from data. These works exposed how to use deep learning to physical systems where some detail of microscopic interactions is known but effective theories are needed to explain the emergence of multiscale collective behavior. This is perfectly fitting for almost every experimental setting in a behavioral neurophysiology experiment.

Acknowledgments

The project was partly funded by Sapienza grant RM1221816BD028D6 (DESMOS), European Union's CHIST-ERA programme under grant agreement CHIST-ERA-19-XAI-009 (MUCCA), the PNRR MUR project PE0000013 FAIR, and by a NextGenerationEU grant (ID IR0000011, "EBRAINS-Italy", Stefano Ferraina).

Data availability statement

Data are available from the corresponding author(s) upon reasonable request.

Competing interests

The authors report no declarations of interest.

Figure 5. Qualitative comparison between temporal attention maps of Go and Stop trials for the D1 vs. D2 prediction for Monkey P. **Panel A)** Attention maps of each layer. Ticks are every 100 ms and mark the time after the Go signal presentation **Panel B)** Distribution of their entries.

References

[1] Steinmetz N A, Aydin C, Lebedeva A, Okun M, Pachitariu M, Bauza M, Beau M, Bhagat J, Böhm C, Broux M, Chen S, Colonell J, Gardner R J, Karsh B, Kloosterman F, Kostadinov D, Mora-Lopez C, O'Callaghan J, Park J, Putzeys J, Sauerbrei B, van Daal R J, Vollan A Z, Wang S, Welkenhuysen M, Ye Z, Dudman J T, Dutta B, Hantman A W, Harris K D, Lee A K, Moser E I, O'Keefe J, Renart A, Svoboda K, Häusser M, Haesler S, Carandini M and Harris T D 2021 *Science (New York, N.Y.)* **372** ISSN 10959203 URL /pmc/articles/PMC8244810/ /pmc/articles/PMC8244810/?report=abstract https://www.ncbi.nlm.nih.gov/pmc/articles/PMC8244810/

[2] Pandarinath C, O'Shea D J, Collins J, Jozefowicz R, Stavisky S D, Kao J C, Trautmann E M, Kaufman M T, Ryu S I, Hochberg L R, Henderson J M, Shenoy K V, Abbott L F and Sussillo D 2018 *Nature Methods 2018 15:10* **15** 805–815 ISSN 1548-7105 URL https://www.nature.com/articles/s41592-018-0109-9

[3] Barack D L and Krakauer J W 2021 *Nature Reviews Neuroscience 2021 22:6* **22** 359–371 ISSN 1471-0048 URL https://www.nature.com/articles/s41583-021-00448-6

[4] Stavisky S D, Kao J C, Nuyujukian P, a, Willett F R, Suminski A J, Fagg A H, Sadras N, Pesaran B, Shanechi M M, Ahmadi N, Constandinou T G and Bouganis C S 2021 *Journal of Neural Engineering* **18** 026011 ISSN 1741-2552 URL https://iopscience.iop.org/article/10.1088/1741-2552/abde8a https://iopscience.iop.org/article/10.1088/1741-2552/abde8a/meta

[5] Pang J C, Aquino K M, Oldehinkel M, Robinson P A, Fulcher B D, Breakspear M and Fornito A 2023 *Nature 2023 618:7965* **618** 566–574 ISSN 1476-4687 URL https://www.nature.com/articles/s41586-023-06098-1

[6] Faskowitz J, Moyer D, Handwerker D A, Gonzalez-2 Castillo J, Bandettini P A, Jbabdi S and Betzel R 2023 *bioRxiv* 2023.07.20.549785 URL https://www.biorxiv.org/content/10.1101/2023.07.20.549785v1 https://www.biorxiv.org/content/10.1101/2023.07.20.549785v1.abstract

[7] Gardner R J, Hermansen E, Pachitariu M, Burak Y, Baas N A, Dunn B A, Moser M B and Moser E I 2022 *Nature 2022 602:7895* **602** 123–128 ISSN 1476-4687 URL https://www.nature.com/articles/s41586-021-04268-7

[8] Shi Y L, Zeraati R, Levina A and Engel T A 2023 *Physical Review Research* **5** 013005 ISSN 26431564 URL https://journals.aps.org/prresearch/abstract/10.1103/PhysRevResearch.5.013005

[9] Genkin M, Hughes O and Engel T A 2021 *Nature Communications 2021 12:1* **12** 1–9 ISSN 2041-1723 URL https://www.nature.com/articles/s41467-021-26202-1

[10] Pinotsis D A and Miller E K 2023 *Cerebral Cortex* ISSN 1047-3211 URL https://dx.doi.org/10.1093/cercor/bhad251

[11] Bullard A 2019 Feasibility of Using the Utah Array for Long-Term Fully Implantable Neuroprosthesis Systems Tech. rep.

[12] Wei Z, Lin B J, Chen T W, Daie K, Svoboda K and Druckmann S 2020 *PLoS Computational Biology* **16** ISSN 15537358

[13] Chandrasekaran S, Fifer M, Bickel S, Osborn L, Herrero J, Christie B, Xu J, Murphy R K J, Singh S, Glasser M F, Collinger J L, Gaunt R, Mehta A D, Schwartz A and Bouton C E 2021 *Bioelectronic medicine* **7** ISSN 2332-8886 URL https://pubmed.ncbi.nlm.nih.gov/34548098/

[14] Pani P, Giamundo M, Giarrocco F, Mione V, Fontana R, Brunamonti E, Mattia M and Ferraina S 2022 *Proceedings of the National Academy of Sciences of the United States of America* **119** e2122395119 ISSN 10916490 URL https://www.pnas.org/doi/abs/10.1073/pnas.2122395119

[15] Stringer C, Pachitariu M, Steinmetz N, Reddy C B, Carandini M and Harris K D 2019 *Science (New York, N.Y.)* **364** ISSN 1095-9203 URL https://pubmed.ncbi.nlm.nih.gov/31000656/

[16] Pachitariu M, Stringer C, Dipoppa M, Schröder S, Rossi L F, Dalgleish H, Carandini M and Harris K D 2017 *bioRxiv* 061507 URL https://www.biorxiv.org/content/10.1101/061507v2 https://www.biorxiv.org/content/10.1101/061507v2.abstract

[17] Yu C H, Stirman J N, Yu Y, Hira R and Smith S L 2021 *Nature Communications 2021 12:1* **12** 1–8 ISSN 2041-1723 URL https://www.nature.com/articles/s41467-021-26736-4

[18] Zhang H L, Liu J, Wang B Z, Dai J, Lian J L, Ke A, Zhao Y W, Zhou J and Wang C Y 2022 *Science China Technological Sciences* **65** 2763–2775 ISSN 18691900 URL https://link.springer.com/article/10.1007/s11431-022-2072-9

[19] Bardella G, Giuffrida V, Giarrocco F, Brunamonti E, Pani P and Ferraina S 2024 *Network Neuroscience* 1–48 URL https://dx.doi.org/10.1162/netn$_a$0365

[20] Roy Y, Banville H, Albuquerque I, Gramfort A, Falk T H and Faubert J 2019 *Journal of neural engineering* **16** 051001

[21] Abibullaev B, Keutayeva A and Zollanvari A 2023 *IEEE Access*

[22] Ha S and Jeong H 2021 *Scientific Reports 2021 11:1* **11** 1–13 ISSN 2045-2322 URL https://www.nature.com/articles/s41598-021-91878-w

[23] Lv C, Wang Y, Han D, Zheng X, Huang X and Li D 2024 *arXiv* URL https://arxiv.org/abs/2402.01533v1

[24] Kipf T, Fetaya E, Wang K C, Welling M and Zemel R 2018 *35th International Conference on Machine Learning, ICML 2018* **6** 4209–4225 URL https://arxiv.org/abs/1802.04687v2

[25] Pan L, Shi C and Dokmani´c I D 2023 URL https://arxiv.org/abs/2306.06041v2

[26] Azabou M, Arora V, Ganesh V, Mao X, Nachimuthu S, Mendelson M J, Richards B, Perich M G, Lajoie G, Dyer E L and Tech G 2023 URL https://arxiv.org/abs/2310.16046v1

[27] Zhu F, Grier H A, Tandon R, Cai C, Agarwal A, Giovannucci A, Kaufman M T and Pandarinath C 2022 *Nature Neuroscience 2022 25:12* **25** 1724–1734 ISSN 1546-1726 URL https://www.nature.com/articles/s41593-022-01189-0

[28] Wang S, Falcone R, Richmond B, Averbeck B B and Davidoff L M 2023 *Nature Neuroscience 2023 26:11* **26** 1970–1980 ISSN 1546-1726 URL https://www.nature.com/articles/s41593-023-01445-x

[29] Carmena J M, Lebedev M A, Crist R E, O'Doherty J E, Santucci D M, Dimitrov D F, Patil P G, Henriquez C S and Nicolelis M A 2003 *PLOS Biology* **1** e42 ISSN 1545-7885 URL https://journals.plos.org/plosbiology/article?id=10.1371/journal.pbio.0000042

[30] Caminiti R, Johnson P B, Galli C, Ferraina S and Burnod Y 1991 *Journal of Neuroscience* **11** 1182–1197 ISSN 0270-6474 URL https://www.jneurosci.org/content/11/5/1182 https://www.jneurosci.org/content/11/5/1182.abstract

[31] Johnson P B, Ferraina S, Bianchi L and Caminiti R 1996 *Cerebral Cortex* **6** 102–119 ISSN 1047-3211 URL https://dx.doi.org/10.1093/cercor/6.2.102

[32] Caminiti R, Ferraina S and Mayer A B 1998 *Current Opinion in Neurobiology* **8** 753–761 ISSN 0959-4388

[33] Nambu A, Tokuno H and Takada M 2002 *Neuroscience Research* **43** 111–117 ISSN 01680102 URL https://pubmed.ncbi.nlm.nih.gov/12067746/

[34] Battaglia-Mayer A, Buiatti T, Caminiti R, Ferraina S, Lacquaniti F and Shallice T 2014 Correction and suppression of reaching movements in the cerebral cortex: Physiological and neuropsychological aspects URL https://pubmed.ncbi.nlm.nih.gov/24631852/

[35] Caminiti R, Borra E, Visco-Comandini F, Battaglia-Mayer A, Averbeck B B and Luppino G 2017 *eNeuro* **4** 306–322 ISSN 23732822 URL /pmc/articles/PMC5329620/?report=abstract https://www.ncbi.nlm.nih.gov/pmc/articles/PMC5329620/

[36] Manto M, Bower J M, Conforto A B, Delgado-García J M, Da Guarda S N F, Gerwig M, Habas C, Hagura N, Ivry R B, Marien P, Molinari M, Naito E, Nowak D A, Ben Taib N O, Pelisson D, Tesche C D, Tilikete C and Timmann D 2012 *Cerebellum (London, England)* **11** 457 ISSN 14734222 URL /pmc/articles/PMC4347949/ /pmc/articles/PMC4347949/?report=abstract

https://www.ncbi.nlm.nih.gov/pmc/articles/PMC4347949/

[37] Menz V K, Schaffelhofer S and Scherberger H 2015 *Journal of Neural Engineering* **12** 056016 ISSN 1741-2552 URL https://iopscience.iop.org/article/10.1088/1741-2560/12/5/056016 https://iopscience.iop.org/article/10.1088/1741-2560/12/5/056016/meta

[38] Middleton F A and Strick P L 2001 *The Journal of Neuroscience* **21** 700 ISSN 02706474 URL /pmc/articles/PMC6763818/ /pmc/articles/PMC6763818/?report=abstract https://www.ncbi.nlm.nih.gov/pmc/articles/PMC6763818/

[39] Marconi B, Genovesio A, Battaglia-Mayer A, Ferraina S, Squatrito S, Molinari M, Lacquaniti F and Caminiti R 2001 *Cerebral Cortex* **11** 513–527 ISSN 1047-3211 URL https://dx.doi.org/10.1093/cercor/11.6.513

[40] Mirabella G, Pani P and Ferraina S 2011 *Journal of Neurophysiology* **106** 1454–1466 ISSN 0022-3077 URL https://www.physiology.org/doi/10.1152/jn.00995.2010

[41] Bardella G, Pani P, Brunamonti E, Giarrocco F and Ferraina S 2020 *NeuroImage* **207** ISSN 10959572

[42] Georgopoulos A P, Kalaska J F, Caminiti R and Massey J T 1982 *The Journal of neuroscience : the official journal of the Society for Neuroscience* **2** 1527–1537 ISSN 0270-6474 URL https://pubmed.ncbi.nlm.nih.gov/7143039/

[43] Kurata K 1993 *Journal of neurophysiology* **69** 187–200 ISSN 0022-3077 URL https://pubmed.ncbi.nlm.nih.gov/8433130/

[44] Messier J and Kalaska J F 2000 *Journal of neurophysiology* **84** 152–165 ISSN 0022-3077 URL https://pubmed.ncbi.nlm.nih.gov/10899193/

[45] Hatsopoulos N G, Joshi J and O'Leary J G 2004 *Journal of Neurophysiology* **92** 1165–1174 ISSN 00223077 URL https://journals.physiology.org/doi/10.1152/jn.01245.2003

[46] Lungu I A, Riehle A, Nawrot M P and Schmuker M 2017 *IBM Journal of Research and Development* **61** ISSN 21518556

[47] Abbaspourazad H, Choudhury M, Wong Y T, Pesaran B and Shanechi M M 2021 *Nature Communications 2021 12:1* **12** 1–19 ISSN 2041-1723 URL https://www.nature.com/articles/s41467-020-20197-x

[48] Liu F, Meamardoost S, Gunawan R, Komiyama T, Mewes C, Zhang Y, Hwang E and Wang L 2022 *Journal of Neural Engineering* **19** 056021 ISSN 1741-2552 URL https://iopscience.iop.org/article/10.1088/1741-2552/ac8fb5 https://iopscience.iop.org/article/10.1088/1741-2552/ac8fb5/meta

[49] Antoniades A, Yu Y, Canzano J, Wang W and Smith S L 2023 URL https://arxiv.org/abs/2311.00136v3

[50] Lawhern V J, Solon A J, Waytowich N R, Gordon S M, Hung C P and Lance B J 2018 *Journal of Neural Engineering* **15** 056013 ISSN 1741-2552 URL https://iopscience.iop.org/article/10.1088/1741-2552/aace8c https://iopscience.iop.org/article/10.1088/1741-2552/aace8c/meta

[51] Shanechi M M 2019 *Nature Neuroscience* **22** 1554–1564 ISSN 15461726 URL https://pubmed.ncbi.nlm.nih.gov/31551595/

[52] Shanechi M M, Hu R C, Powers M, Wornell G W, Brown E N and Williams Z M 2012 *Nature neuroscience* **15** 1715–1722 ISSN 1546-1726 URL https://pubmed.ncbi.nlm.nih.gov/23143511/

[53] Wilson G H, Stavisky S D, Willett F R, Avansino D T, Kelemen J N, Hochberg L R, Henderson J M, Druckmann S and Shenoy K V 2020 *Journal of neural engineering* **17** 066007 ISSN 17412552 URL /pmc/articles/PMC8293867/ /pmc/articles/PMC8293867/?report=abstract https://www.ncbi.nlm.nih.gov/pmc/articles/PMC8293867/

[54] Ethier C, Oby E R, Bauman M J and Miller L E 2012 *Nature 2012 485:7398* **485** 368–371 ISSN 1476-4687 URL https://www.nature.com/articles/nature10987

[55] Capogrosso M, Milekovic T, Borton D, Wagner F, Moraud E M, Mignardot J B, Buse N, Gandar J, Barraud Q, Xing D, Rey E, Duis S, Jianzhong Y, Ko W K D, Li Q, Detemple P, Denison T, Micera S, Bezard E, Bloch J and Courtine G 2016 *Nature* **539** 284–288 ISSN 14764687 URL

`http://www.nature.com/authors/editorial`$_p$`olicies/license.htmlterms`

[56] Kiehn O 2016 *Nature Reviews Neuroscience 2016 17:4* **17** 224–238 ISSN 1471-0048 URL `https://www.nature.com/articles/nrn.2016.9`

[57] Lorach H, Galvez A, Spagnolo V, Martel F, Karakas S, Intering N, Vat M, Faivre O, Harte C, Komi S, Ravier J, Collin T, Coquoz L, Sakr I, Baaklini E, Hernandez-Charpak S D, Dumont G, Buschman R, Buse N, Denison T, van Nes I, Asboth L, Watrin A, Struber L, Sauter-Starace F, Langar L, Auboiroux V, Carda S, Chabardes S, Aksenova T, Demesmaeker R, Charvet G, Bloch J and Courtine G 2023 *Nature 2023 618:7963* **618** 126–133 ISSN 1476-4687 URL `https://www.nature.com/articles/s41586-023-06094-5`

[58] Kuzovkin I, Vicente R, Petton M, Lachaux J P, Baciu M, Kahane P, Rheims S, Vidal J R and Aru J 2018 *Communications Biology* **1** 1–12 ISSN 23993642 URL `https://www.nature.com/articles/s42003-018-0110-y`

[59] Vaswani A, Shazeer N, Parmar N, Uszkoreit J, Jones L, Gomez A N, Kaiser Ł and Polosukhin I 2017 *Advances in neural information processing systems* **30**

[60] Han K, Wang Y, Chen H, Chen X, Guo J, Liu Z, Tang Y, Xiao A, Xu C, Xu Y *et al.* 2022 *IEEE transactions on pattern analysis and machine intelligence* **45** 87–110

[61] Xu P, Zhu X and Clifton D A 2023 *IEEE Transactions on Pattern Analysis and Machine Intelligence*

[62] Chefer H, Gur S and Wolf L 2021 Transformer interpretability beyond attention visualization *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition* pp 782–791

[63] Grigsby J, Wang Z, Nguyen N and Qi Y 2021 *arXiv preprint arXiv:2109.12218*

[64] Logan G D and Cowan W B 1984 *Psychological Review* **91** 295–327 ISSN 0033-295X

[65] Band G P, van der Molen M W and Logan G D 2003 *Acta Psychologica* **112** 105–142 ISSN 00016918

[66] Bardella G, Franchini S, Pan L, Balzan R, Ramawat S, Brunamonti E, Pani P and Ferraina S 2024 *arXiv* URL `https://arxiv.org/abs/2310.09178v3`

[67] Churchland M M, Cunningham J P, Kaufman M T, Ryu S I and Shenoy K V 2010 *Neuron* **68** 387–400 ISSN 1097-4199 URL `https://pubmed.ncbi.nlm.nih.gov/21040842/`

[68] Churchland M M, Cunningham J P, Kaufman M T, Foster J D, Nuyujukian P, Ryu S I, Shenoy K V and Shenoy K V 2012 *Nature* **487** 51–56 ISSN 00280836 URL `/pmc/articles/PMC3393826/?report=abstract` `https://www.ncbi.nlm.nih.gov/pmc/articles/PMC3393826/`

[69] Kaufman M T, Churchland M M, Ryu S I and Shenoy K V 2014 *Nature neuroscience* **17** 440 ISSN 10976256 URL `/pmc/articles/PMC3955357/` `/pmc/articles/PMC3955357/?report=abstract` `https://www.ncbi.nlm.nih.gov/pmc/articles/PMC3955357/`

[70] Elsayed G F, Lara A H, Kaufman M T, Churchland M M and Cunningham J P 2016 *Nature Communications 2016 7:1* **7** 1–15 ISSN 2041-1723 URL `https://www.nature.com/articles/ncomms13239`

[71] Kaufman M T, Seely J S, Sussillo D, Ryu S I, Shenoy K V and Churchland M M 2016 *eNeuro* **3** 85–101 ISSN 23732822 URL `http://dx.doi.org/10.1523/ENEURO.0085-16.2016`

[72] Sheskin D J 2003 *Handbook of parametric and nonparametric statistical procedures* (Chapman and hall/CRC)

[73] Weinrich M and Wise S P 1982 *The Journal of neuroscience : the official journal of the Society for Neuroscience* **2** 1329–1345 ISSN 0270-6474 URL `https://pubmed.ncbi.nlm.nih.gov/7119878/`

[74] Ramawat S, Mione V, Di Bello F, Bardella G, Genovesio A, Pani P, Ferraina S and Brunamonti E 2022 *Neuroscience* **485** 147–162 ISSN 0306-4522

[75] Churchland M M, Yu B M, Ryu S I, Santhanam G and Shenoy K V 2006 *The Journal of neuroscience : the official journal of the Society for Neuroscience* **26** 3697–3712 ISSN 1529-2401 URL `https://pubmed.ncbi.nlm.nih.gov/16597724/`

[76] Mattia M, Pani P, Mirabella G, Costa S, Del Giudice P and Ferraina S 2013 *Journal of Neuroscience* **33** 11155–11168 ISSN 02706474

[77] Ames K C, Ryu S I and Shenoy K V 2014 *Neuron* **81** 438 ISSN 08966273 URL /pmc/articles/PMC3936035/ /pmc/articles/PMC3936035/?report=abstract https://www.ncbi.nlm.nih.gov/pmc/articles/PMC3936035/

[78] Dann B, Michaels J A, Schaffelhofer S and Scherberger H 2016 *eLife* **5** ISSN 2050084X

[79] Varley T F, Sporns O, Schaffelhofer S, Scherberger H and Dann B 2023 *Proceedings of the National Academy of Sciences of the United States of America* **120** e2207677120 ISSN 10916490 URL https://www.pnas.org/doi/abs/10.1073/pnas.2207677120

[80] Peng J, Wang P, Zhou N and Zhu J 2009 *Journal of the American Statistical Association* **104** 735 ISSN 01621459 URL /pmc/articles/PMC2770199/ /pmc/articles/PMC2770199/?report=abstract https://www.ncbi.nlm.nih.gov/pmc/articles/PMC2770199/

[81] Schreiber T 2000 *Physical Review Letters* **85** 461–464 ISSN 00319007 URL https://journals.aps.org/prl/abstract/10.1103/PhysRevLett.85.461

[82] Wu T, Breuel T, Skuhersky M and Kautz J 2020 URL https://arxiv.org/abs/2001.01885v1

[83] Quinn C J, Coleman T P, Kiyavash N and Hatsopoulos N G 2011 *Journal of computational neuroscience* **30** 17–44 ISSN 1573-6873 URL https://pubmed.ncbi.nlm.nih.gov/20582566/

[84] Merger C, René A, Fischer K, Bouss P, Nestler S, Dahmen D, Honerkamp C and Helias M 2023 *Physical Review X* **13** 041033 ISSN 21603308 URL https://journals.aps.org/prx/abstract/10.1103/PhysRevX.13.041033