RESEARCH

Knowledge Graph-based Thought: a knowledge graph enhanced LLMs framework for pan-cancer question answering

Yichun Feng[1,2], Lu Zhou[2,*], Yikai Zheng[2], Ruikun He[4,5,*], Chao Ma[3,*] and Yixue Li[1,2,*]

[1]Hangzhou Institute for Advanced Study, University of Chinese Academy of Sciences, 310024 Hangzhou, China and [2]Guangzhou National Laboratory, No. 9 XingDaoHuanBei Road, Guangzhou International Bio Island, 510005 Guangzhou, China and [3]Smartquerier Gene Technology (Shanghai) Co., Ltd., 200100 Shanghai, China and [4]BYHEALTH Institute of Nutrition & Health, 510663 Guangzhou, China and [5]Shanghai Institute of Nutrition and Health, Chinese Academy of Sciences Shanghai, 200030 Shanghai, China

*Correspondence address. Yixue Li, Guangzhou National Laboratory, No. 9 XingDaoHuanBei Road, Guangzhou International Bio Island, 510005 Guangzhou, China. E-mail: yxli@sibs.ac.cn; Lu Zhou, Guangzhou National Laboratory, No. 9 XingDaoHuanBei Road, Guangzhou International Bio Island, 510005 Guangzhou, China. E-mail: zhou_lu@gzlab.ac.cn; Chao Ma, Smartquerier Gene Technology (Shanghai) Co., Ltd., 200100 Shanghai, China. E-mail: machao@smartquerier.com; Ruikun He, BYHEALTH Institute of Nutrition & Health, 510663 Guangzhou, China. E-mail: herk@by-health.com

Abstract

Background. In recent years, Large Language Models (LLMs) have shown promise in various domains, notably in biomedical sciences. However, their real-world application is often limited by issues like erroneous outputs and hallucinatory responses. **Results**. We developed the Knowledge Graph-based Thought (KGT) framework, an innovative solution that integrates LLMs with Knowledge Graphs (KGs) to improve their initial responses by utilizing verifiable information from KGs, thus significantly reducing factual errors in reasoning. The KGT framework demonstrates strong adaptability and performs well across various open-source LLMs. Notably, KGT can facilitate the discovery of new uses for existing drugs through potential drug-cancer associations, and can assist in predicting resistance by analyzing relevant biomarkers and genetic mechanisms. To evaluate the Knowledge Graph Question Answering task within biomedicine, we utilize a pan-cancer knowledge graph to develop a pan-cancer question answering benchmark, named the Pan-cancer Question Answering (PcQA). **Conclusions**. The KGT framework substantially improves the accuracy and utility of LLMs in the biomedical field, demonstrating its exceptional performance in biomedical question answering.

Key words: pan-cancer knowledge graph, large language model, knowledge graph question answering, prompt engineering

Introduction

With the increasing prominence of Large Language Models (LLMs) in the field of artificial intelligence, the advent of influential models such as ChatGPT [1] and Llama [2] consequently catalyze the development of a wide array of applications in biomedicine and healthcare. However, LLMs still face the challenge of factual hallucination, where they generate incorrect statements due to limited inherent knowledge [3]. Factual hallucination presents a significant challenge for the practical use of LLMs, especially in real-world scenarios where factual accuracy is crucial. Consequently, there is a growing focus on addressing factual hallucinations in LLMs within the field of Natural Language Processing (NLP) [4, 5].

LLMs often struggle to capture and access factual knowledge, primarily due to three aspects: the inability to comprehend ques-

---

Key Points

- We introduce a framework combining LLMs with KGs to improve factual accuracy in LLM reasoning.
- Our system is a flexible architecture that seamlessly integrates various LLMs.
- Utilizing a pan-cancer knowledge graph, we have proposed the first KGQA benchmark in the field of biomedicine.
- Case studies reveal our method enhanced LLMs in addressing biomedical challenges such as drug repositioning, resistance research, individualized treatment, and biomarker analysis.
- The method performs favorably in comparison to existing methods.

---

tions due to the lack of contextual information, the insufficient knowledge to generate accurate answers, and the incapacity to recall specific facts [6]. Consequently, researchers consider the fine-tuning technique as a solution to address these issues. For example, MedAlpaca [7] builds upon medical data to fine-tune Stanford Alpaca for applications related to medical question-answering and dialogue. ChatDoctor [8] is designed to simulate a conversation between a doctor and a patient by fine-tuning LLaMA with medical literature. Additionally, Med-PaLM [9] shows promising performance on the MedQA exam based on clinical corpora and human feedback. Meanwhile, aiming at the Chinese medical domain, LLMs such as BenTsao [10], DoctorGLM [11], and HuatuoGPT [12], are developed on the Chinese medical dialogue data. More recently, Zhongjing [13] and ChiMed-GPT [14] adopted full pipeline training from pre-training, SFT, to Reinforcement Learning with Human Feedback (RLHF) [15]. While fine-tuning can reduce hallucinations in large language models (LLMs), it brings about considerable training expenses. Additionally, it poses a critical challenge known as catastrophic forgetting. This issue manifests when a model forgets its previously learned information as a consequence of parameter modifications during the acquisition of new tasks. This forgetfulness results in a deterioration of performance on prior tasks, consequently constraining the model's practical applicability [16, 17].

In addition to fine-tuning, researchers also enhance the output of LLMs through the field of prompt engineering. Prompt engineering focuses on the creation and optimization of prompts to improve the effectiveness of LLMs across various applications and research domains [18]. It can enhance the capabilities of LLMs in a wide range of complex tasks, including question answering, sentiment classification, and common-sense reasoning. Chain-of-thought (CoT) prompts [19] enable complex reasoning capabilities by incorporating intermediate reasoning steps. The Automatic Prompt Engineer (APE) proposes an automatic prompt generation method aimed at enhancing the performance of LLMs [20]. Prompt engineering offers a straightforward approach to harnessing the potential of LLMs without fine-tuning.

On the other hand, Knowledge Graphs (KGs) are repositories of vast quantities of high-quality structured data, offering the potential to effectively mitigate the issue of factual hallucinations when integrated with LLMs. Hence, employing KGs for question-answering can enhance the precision of the responses and furnish a dependable foundation for the factual verification of information produced by LLMs. Knowledge Graph Question Answering (KGQA) has long been a hot research topic. Before the advent of LLMs, certain studies [21, 22, 23] typically begin by retrieving a subgraph related to the question to reduce the search space, then perform multi-hop reasoning on this basis. This retrieval-plus-reasoning paradigm has shown its advantages over direct reasoning across the entire KG [24, 25]. Additionally, Researchers tackle KGQA by parsing the question into a structured query language (e.g., SPARQL) and using a query engine to obtain accurate answers [26, 27]. UniKGQA [28] introduces a unified fine-tuning framework for retrieval and reasoning, more closely linking these two stages. However, traditional KGQA methods usually perform poorly in accurate semantic understanding and high-quality text generation due to the lack of

Figure 1. Illustrative examples contrasting our work with previous efforts. **(A) LLM-only-based inference**, answering questions solely through the inherent knowledge of LLMs. **(B) Subgraph-based inference**, enhancing LLMs by retrieving the knowledge from KGs based on the question. If intermediate entities are not provided in the multi-hop question, no appropriate knowledge can be retrieved. **(C) Graph schema-based inference**, enhancing retrieval capabilities by reasoning intermediary entity types on the schema of the KG, using the knowledge of the KG to enhance LLMs' responses.

LLMs for retrieval and reasoning. Hence, recent research is increasingly utilizing external KGs to enhance LLMs in addressing KGQA challenges. For instance, StructGPT [29] navigates through knowledge graphs by identifying pathways from an initial seed entity to the target answer entity, whereas KG-GPT [30] opts for retrieving an entire subgraph from the knowledge graph and then deduces the answer through inference. Although these methods have achieved gratifying results in general areas, as shown in Figure 1(B), when the intermediate entity in the multi-hop question is unknown, it is impossible to retrieve the appropriate knowledge from the KG.

In this paper, we introduce an innovative framework called Knowledge Graph-based Thought (KGT), which integrates LLMs with KGs through employing LLMs for reasoning on the schema of KGs to mitigate factual hallucinations of LLMs, as shown in Fig. 1(C). Unlike traditional methods, KGT does not retrieve factual information through original queries, but instead utilizes LLMs to generate the optimal subgraph based on key information extracted from the question. Subsequently, the optimal subgraph is used to infer the answer to the question through LLMs. KGT requires no fine-tuning,

Table 1. Comparison of SOKG with SynLethKG and SDKG

	Entity Types	Relational Types	Nodes	Edges	Attributes
SynLethKG	11	24	54,012	2,231,921	0
SDKG	7	12	165,062	727,318	0
SOKG	**24**	**21**	**3,640,259**	**10,656,273**	**98**

offers seamless integration with multiple LLMs, and is plug-and-play, facilitating easy deployment. It demonstrates generalizability, making it adaptable for use with diverse knowledge graphs. This framework is tailored for wide-ranging applications in numerous biomedical challenges, such as: (1) enhancing clinical decision-making for physicians and medical organizations; (2) delivering medical advice to patients and healthcare providers; (3) uncovering crucial biomarkers for early disease detection and tailored therapy; and (4) exploring novel therapeutic applications for existing medications through insights into their mechanisms, side effects, and the biological processes of associated diseases. Furthermore, we utilize the SmartQuerier Oncology Knowledge Graph (SOKG), a pan-cancer knowledge graph developed by SmartQuerier[1], to create a benchmark for the Knowledge Graph Question Answering task within biomedicine, named the Pan-cancer Question Answering (PcQA). This benchmark is currently the sole question answering dataset available in the domain of biomedical knowledge graphs.

Materials and Methods

Knowledge graph introduction

In this work, we tackle the problem of logical reasoning over the KG $\mathcal{K} : E \times R$ that store entities (E) and relations (R). Without loss of generality, KG can be organized as a set of triplets $\{(e_1, r, e_2)\} \subseteq \mathcal{K}$, where each relation $r \in R$ exists between the pair of entities $(e_1, e_2) \in E \times E$. To further enrich the KG, attribute information is included through pairs $(e, attr)$, where $attr$ represents an attribute associated with an entity e, thereby enhancing the KG's semantic richness and precision by incorporating detailed characteristics of each entity.

Within the specialized realm of pan-cancer research, our employed SOKG stands out with its vast repository of oncological information. As depicted in Table 1, SOKG boasts an extensive collection of over 3 million entities, which dwarfs the entity count in the compared knowledge graphs, SynLethKG [31] and SDKG [32], with 540,012 and 165,062 entities respectively. Furthermore, SOKG's nearly 6 million unique concept relations eclipse those of SynLethKG and SDKG, which stand at 2,231,921 and 727,318 relations respectively. Furthermore, SOKG's inclusion of 98 distinct attribute types enriches data comprehension and enhances the efficiency and precision of queries, a capability not matched by either SynLethKG or SDKG due to their absence of comparable attributes.

Tasks description

In order to tackle a diverse array of challenges in the field of biomedicine, we devise four categories of problems: one-hop problems, multi-hop problems, intersection problems and attribute problems as illustrated in Table 2.

One-hop problems

One-hop problems involve single-relation chain reasoning, where the objective is to deduce the tail entity $T_?$ given a head entity H_1 and a relation R_1, or to infer the relation $R_?$ when a head entity H_1

and a tail entity T_1 are known, as depicted in Equ.1 and Equ.2.

$$H_1 + R_1 \rightarrow T_? \tag{1}$$

$$H_1 + T_1 \rightarrow R_? \tag{2}$$

Multi-hop problems

Multi-hop problems involve multiple-relation chain reasoning, that can be broadly categorized into two types. The first category involves deducing potential relationships between entities by navigating through indirect relations. By examining the indirect relations (R_1, R_2) between a head entity H_1 and a tail entity T_1, it is possible to infer an unknown or potential relation $R_?$ linking them directly. This inference process is encapsulated in the following equation:

$$H_1 + T_1 \rightarrow R_1 + R_2 \rightarrow R_? \tag{3}$$

The second category extends the reasoning to include the discovery of entities themselves, by following a path from a head entity through intermediate relations to a final tail entity. Starting with a head entity H_1, coupled with an indirect relation R_1, an intermediary entity M can be inferred. This intermediary entity M is then applied with an indirect relation R_2 to deduce the final tail entity $T_?$. This inference process is summarized in the following equation:

$$H_1 + R_1 \rightarrow M + R_2 \rightarrow T_? \tag{4}$$

Intersection problems

Intersection problems refer to taking the intersection of multiple relational chains. Two head entities (H_1, H_2) lead to the deduction of two types of tail entities (T_1, T_2) based on different relations (R_1, R_2). The final tail entity $T_?$ is determined by intersecting these two types of tail entities (T_1, T_2). This inference process is summarized as following:

$$H_1 + R_1 \rightarrow T_1 \tag{5}$$

$$H_2 + R_2 \rightarrow T_2 \tag{6}$$

$$T_1 \cap T_2 \rightarrow T_? \tag{7}$$

Attribute problems

Attribute problems refer to the attribute information of entity, where the task involves retrieving the attributes of a known head entity H_1 or determining whether the tail entity T_1, identified through a known head entity H_1 and relation R_1, satisfies the attributes specified in the query, as illustrated in Equ.8 and Equ.9.

$$H_1 \rightarrow P_{H_1} \tag{8}$$

$$H_1 + R_1 \rightarrow P_{T_1} \tag{9}$$

Table 2. Four different reasoning types of task.

Reasoning Type	Claim Example	Graph
One-hop	What types of cancer can be treated with diethylstilbestrol?	$H1 \xrightarrow{R_1} T1$
Multi-hop	What are the gene mutations in adenoid cystic carcinoma?	$H1 \xrightarrow{R_1} M \xrightarrow{R_2} T1$
Intersection	Which drugs are sensitivity to ALK in basaloid large cell carcinoma of the lung?	$H_1 \xrightarrow{R_1} T_1$, $H_2 \xrightarrow{R_2} T_2$, $\cap \rightarrow T_?$
Attribute	What is the maximum age for recruitment of clinical trials for patients with meningioma?	$H1 \xrightarrow{R_1} P_{T_1}$

Datasets

In the continuously evolving field of biomedical research, the integration of LLMs with KGs offers a more efficient and effective method for knowledge discovery and utilization, particularly in advancing cancer research. Nonetheless, we note a scarcity of appropriate datasets for evaluating these sophisticated methodologies within this field. To address this, we leverage the SOKG to establish a benchmark for the Knowledge Graph Question Answering task within biomedicine, named the Pan-cancer Question Answering (PcQA). This dataset includes 405 data entries, covering a wide range of applications in the field of pan-cancer research, including genetic predisposition to cancer, medication treatment planning, drug repositioning, identification of potential drug targets, studies on drug resistance, and predictions of cancer progression and metastasis. By deeply exploring cancer-related reasoning and information retrieval challenges, this dataset can inspire researchers and clinicians to gain a deeper understanding of cancer and explore more effective treatment methods.

KGT framework

The overall framework of KGT is laid out in Fig. 2. When users input their question in natural language, the first step is to analyze the question, extracting the main information with the goal of breaking down the question into smaller, more manageable units. This main information is then passed to a LLM, which applies graph reasoning on the schema graph of the knowledge graph, yielding the optimal relational chain. Subsequently, a retrieval statement is generated, and a subgraph is constructed within the KG through search. The relational chains and attributes in the subgraph are then fed back into the LLM to finalize the reasoning and generate an output in natural language.

Question analysis

Key information extraction. The user inputs a question text (Q) in natural language, which is initially deconstructed and parsed. A LLM is applied to analyze the question, resulting in the identification of the head entity name (H_n), the tail entity type (T_t), and the attributes of tail entity (T_a). The prompt for the LLM to extract key information from the question is presented in Fig. 3.

Retrieving key information from KG. Based on H_n, a fixed Cypher format is set to query the head entity type (H_t), facilitating subsequent reasoning.

Graph Schema-based inference

Construction of a graph based on KG schema. Based on the entity types (E_t) and the relations (R) between them in the SOKG, an undirected graph $\mathcal{G}$ is established where E_t serve as nodes $\mathcal{N}$ and R act as edges $\mathcal{P}$.

Candidate Path Search. Breadth-First Search (BFS) is employed to identify the shortest paths connecting H_t and T_t from the constructed graph $\mathcal{G}$. Initiate the search at H_t, creating a queue to hold nodes encountered along the way. Simultaneously, form a set to track nodes that have been visited to avoid revisiting them. Insert H_t into the queue. Continue processing as long as the queue remains non-empty, removing a node from the queue at each step. For each of its unvisited neighbors, enqueue the neighbor, mark it as visited, and log the pathway from H_t to this neighbor. Upon arrival at T_t, use the accumulated path data to compile the set of shortest paths (SPs) from H_t to T_t, with each individual path within the set referred to as an SP.

Optimal path selection. By utilizing embedding technology, textual information is mapped into a low-dimensional space, resulting in N-dimensional real-value vectors. The similarity between each SP and the Q is calculated based on their respective real-value vectors, with the SP exhibiting the highest similarity being selected as the optimal path (OP).

$$\text{Similarity}(Q, SP) = \frac{Q \cdot SP}{\|Q\| \times \|SP\|}$$
$$= \frac{\sum_{i=1}^{n}(Q_i \times SP_i)}{\sqrt{\sum_{i=1}^{n} Q_i^2} \times \sqrt{\sum_{i=1}^{n} SP_i^2}} \quad (10)$$

$$OP = \max_{Q,SP} \text{Similarity}(Q, SP) \quad (11)$$

Subgraph construction

Query statement generation. Input H_t, H_n, T_t, T_a, and OP into an LLM to generate a query statement, such as Cypher. Text2Cypher Prompt is presented in Fig. 4.

Subgraph generation. Enter the query statement in the KG to obtain a reasonable subgraph.

Inference

Subgraph inference. Based on the relational chains and attribute data in the subgraph, determine the relevance to the question text. Prune any erroneous information, retaining only the correct relational chains.

Natural language output. The LLM divides the subgraph into multiple relational chains, each of which outputs a sentence in natural language, and then the LLM generates natural language output. LLMs Inference and Output Prompt is presented in Fig. 5.

Results

Evaluation criteria

We use evaluators based on GPT-4 [33], BERTScore [34], and ROUGE [35] to assess the accuracy of the generated answers. As

Figure 2. Framework of KGT. (A) Question analysis. Decompose the question and extract its key information. (B) Graph Schema-based inference. Input the types of the head and tail entities into the graph schema of the knowledge graph, complete the graph reasoning, and obtain the optimal relational chain pattern. (C) Subgraph construction. Generate a query statement and retrieve the subgraph. (D) Inference. Complete the final reasoning and output the results in natural language.

Key Information Extraction Prompt

You need to follow these three steps based on your biomedical knowledge:
step1:
Extract the name of the head entity and the type of the tail entity in my question, with the head defined as the active voice of the problem and the tail defined as the passive voice of the problem. The entity types include ...
step2:
Based on the entity type from step 1, select an attribute from the attribute list that best fits my question.
step3:
If there is only one head entity name, the output format should be (head entity name, tail entity type, attribute); if there are two head entity names, the output format should be (head entity name 1, tail entity type, attribute), (head entity name 2, tail entity type, attribute).
Examples

Figure 3. Prompt for key information extraction.

Text2Cypher Prompt

Given a knowledge graph, create a Cypher statement to answer the following question.
Examples

Figure 4. Prompt for query statement generation.

a scoring bot, GPT-4 evaluates and assigns scores based on the similarity in meaning between two sentences. GPT-4-based Evaluation Prompt is presented in Fig. 6. BERTScore evaluates semantic similarity using context-sensitive embeddings, offering a comprehensive evaluation of language model outputs. ROUGE, on the other hand, evaluates the longest common subsequence (LCS) between

LLMs Inference and Output Prompt

You are a reasoning robot, and you need to perform the following two steps step by step:
step1: Output a corresponding natural language sentence for each relational chain.
step2: Answer the question using natural language from step1.
Examples

Figure 5. Prompt for LLMs inference and output.

GPT4-based Evaluation Prompt

I have two sentences: my-answer and standard-answer. You need to rate their similarity, and if they express exactly the same meaning, give them 100 points; If the expressed meaning is opposite, give 0 points; If there are any unreasonable aspects, corresponding points will be deducted and specific scores will be given.

Figure 6. Prompt for GPT-4-based evaluation.

the generated text and the reference text, focusing on sequence-based similarity to assess the fluency and the preservation of semantic content.

Baselines

To assess the advantages of our framework, we compare it with several approaches that can be directly applied for KGQA tasks without fine-tuning. We introduce a straightforward baseline approach, named Base, which is similar to KG-GPT [30], currently the leading method in the KGQA field, excluding the sentence segmentation step of KG-GPT. Initially, this involves leveraging a LLM to retrieve relevant information from the KG by generating a query statement. Then, another LLM is used to answer the question with

Table 3. Prompts for Base and CoT&ICL.

	Base	CoT&ICL
Text2Cypher Prompt	Given a knowledge graph, create a Cypher statement to answer the question	Given a knowledge graph, you need to perform the following two steps step by step: step1: Select the optimal path and attributes from the knowledge graph based on the question. step2: Create a Cypher statement to answer the question. Examples
Inference Prompt	Answer my question based on the relational chain.	You need to perform the following two steps step by step: step1: Output a corresponding natural language sentence for each relational chain. step2: Answer my question using natural language from step 1. Examples

Table 4. Comparison of results between KGT and other commonly used methods based on the Code-Llama-13B. Display the best results in bold for each indicator.

Method	GPT-4 Eval (%)	BERTScore (%)	ROUGE (%)		
			Recall	Precision	F1-score
Base	46.6	85.3	25.3	28.5	24.5
CoT&ICL	57.9	88.8	38.9	39.4	37.6
KG-GPT	68.2	93.5	55.2	55.8	53.3
KGT(ours)	**92.4**	**97.7**	**87.4**	**87.7**	**86.8**

the retrieved information. To enhance the baseline, we incorporate Chain-of-Thought (CoT) prompting [19] and In-Context Learning (ICL) techniques [36] , collectively referred to as CoT&ICL. The prompts for these methods are illustrated in Table 3. Additionally, we implement KG-GPT [30] to enhance the retrieval and reasoning capabilities of the LLMs. For a fair comparison, all methods are based on Code-Llama-13B [37].

To further underscore the efficacy of our framework, we conduct a comparative analysis of KGT, which is built upon Code-Llama-13B, against two highly capable large language models that are prominent in the general and biomedical domains: ChatGPT-3.5 [1] and Taiyi [38]. ChatGPT-3.5, a leader in tasks across the general domain, has exhibited competitive performance in a wide range of applications. To compensate for its limited biomedical knowledge, we employed two methodologies previously described, Base and CoT&ICL, as advanced baselines to augment ChatGPT-3.5's capabilities. Taiyi, a cutting-edge LLM in biomedicine, pre-trained on two trillion tokens, leverages its extensive biomedical knowledge base for direct question answering, bypassing the need for knowledge graph retrieval.

Due to the scarcity of KGQA datasets within the biomedical domain, all experiments are conducted on our newly proposed benchmark, named PcQA.

Comparative analysis across different KGQA methods

We evaluated the capabilities of various methods based on Code-Llama-13B, with the experimental results presented in Table 4. The experimental results indicate that the Code-Llama-13B model, enhanced with KGT, consistently surpasses competing methods across all metrics assessed. Notably, KG-GPT improves the F1 score by 15.7% over previous methods CoT&ICL, while our method KGT increases the F1 score by 33% over KG-GPT. Because KG-GPT overlooks the impact of entity types and attributes on answers within the biomedical domain. This achievement positions our approach as a pioneering benchmark in biomedical KGQA, eclipsing previously established best practices.

Comparative analysis across diverse LLMs

We presents a comparative study of KGT applied to Code-Llama-13B against two highly capable LLMs in the general and biomedical domains, with experimental results displayed in Table 5. Code-Llama-13B, enhanced by KGT, significantly outperforms its peers, achieving the highest marks in every assessment metric: a GPT-4 Eval score of 92.4, a BERTScore of 97.7, and a ROUGE F1-score of 86.8. Remarkably, our approach's F1 score surpasses that of ChatGPT-3.5 with the Base method by 52.7%, the CoT&ICL method by 36.3%, and Taiyi's base model by 67.3%. These results highlight KGT's substantial contribution to improving the performance of large language models for the pan-cancer KGQA task. Even when integrated with open-source general models, KGT exhibits remarkable performance, outstripping both the recognized state-of-the-art closed-source large language models and those specifically tailored for the biomedical domain. This showcases KGT's adeptness at parsing and leveraging knowledge graph data, setting a new standard for future research and applications in the field.

Assessing KGT's effectiveness on diverse LLM platforms

To underscore the adaptability and effectiveness of our KGT framework when applied to a range of large language models, we conduct experiments on several LLMs: Zephyr [39], Llama-2 [2], and Code-Llama [37]. The outcomes, illustrated in Fig. 7, reveal that while the CoT&ICL techniques significantly boost performance in terms of F1-score, our KGT methodology delivers even more substantial enhancements across all evaluated models. This demonstrates not only the effectiveness of CoT&ICL as a performance-enhancing strategy but also highlights the superior advancements and impact of KGT, establishing its dominance and efficiency in knowledge graph question-answering tasks.

Ablation study for dissecting the components of KGT

In our effort to illuminate the individual contributions of the components that constitute our KGT framework and their collective impact on enhancing the performance of LLMs, we define four foundational modules: (1) question analysis for the extraction of pivotal information, (2) graph schema-based inference to identify the optimal relational chains in the knowledge graph, (3) the generation of query statements to facilitate subgraph construction, and (4) the inference process coupled with the articulation of results in natural language. This ablation study, grounded on the Code-Llama-13B model, is meticulously designed to evaluate the efficacy of these components. Since graph schema-based inference requires the process of question analysis, the question analysis module can-

Table 5. Comparison of KGT based on Code-Llama-13B with results from other commonly used models. Display the best results in bold for each indicator.

Model	Method	GPT-4 Eval (%)	BERTScore (%)	ROUGE (%)		
				Recall	Precision	F1-score
ChatGPT-3.5	Base	65.4	91.0	42.7	32.3	34.1
	CoT&ICL	70.3	93.3	57.0	50.6	50.5
taiyi	\	40.6	85.3	15.4	39.6	19.5
Code-Llama-13B	**KGT(ours)**	**92.4**	**97.7**	**87.4**	**87.7**	**86.8**

Table 6. Ablation study of the KGT framework under Code-Llama-13B.

Method	GPT-4 Eval (%)	BERTScore (%)	ROUGE (%)		
			Recall	Precision	F1-score
KGT(ours)	92.4	97.7	87.4	87.7	86.8
w/o GSBI	71.8	95.5	68.1	69.8	66.8
w/o QA&GSBI	69.7	94.7	55.0	66.3	58.2
w/o QA&GSBI&SC	24.7	77.4	14.8	12.3	12.2

Figure 7. Performance of various models using different strategies.

not be removed in isolation; simultaneously, subgraph construction is indispensable for knowledge graph retrieval. If the subgraph construction module is independently omitted, the outputs of the initial two modules will not impact the final results, making the isolated exclusion of this component illogical. Therefore, we introduce three specific ablated configurations for examination: (1) excluding graph schema-based inference (*w/o* GSBI), (2) omitting both question analysis and graph schema-based inference (*w/o* QA&GSBI), and (3) removing question analysis, graph schema-based inference, and subgraph construction(*w/o* QA&GSBI&SC), effectively bypassing the structured query of the SOKG and relying solely on the LLM's inherent knowledge for question answering.

The results of the ablation study, as shown in Table 6, demonstrate that when we remove the GSBI, we observe a 20% decrease in the F1 score. Removing both GSBI and QA results in an additional 8.6% decrease in the F1 score compared to removing GSBI alone. Furthermore, removing GSBI, QA, and SC together leads to a 46% decrease in the F1 score compared to removing just GSBI and QA. The experiments reveal that SC is crucial; its absence forces the LLM to rely solely on its inherent knowledge, significantly reducing effectiveness. GSBI is also key, as it aids in navigating complex multi-hop questions by providing necessary intermediate entity information for subgraph construction. QA is equally essential, ensuring accurate identification of entities and properties for correct subgraph construction. All these variants underperform compared to the complete KGT, indicating that each of the three modules is vital for the final performance. Furthermore, such observations confirm that our KGT can indeed leverage knowledge to enhance the final performance of LLMs.

Figure 8. (A), (B), (C) and (D) respectively represent the relational diagrams of drug repositioning, drug resistance research, individualized treatmen and selection and understanding of biomarkers.

Case studies

Drug repositioning

Drug repositioning emerge as a promising strategy to accelerate the process of drug development. This approach involves identifying new therapeutic uses for existing drugs, thereby saving time and resources typically required for bringing a new drug to market [40]. Our system is capable of investigating the potential repositioning of carteolol for the treatment of hemangiomas. The example is shown in Table 7 and relational diagram is shown in Fig. 8(A). Utilizing the system's knowledge graph, a relational chain is delineated, illustrating that propranolol, another inhibitor of ADRB1, is effectively employed in the treatment of hemangiomas. The system harnesses this insight to formulate a hypothesis that carteolol, by virtue of its similar mechanism of inhibition, could be potentially repositioning for treating hemangiomas [41]. This hypothesis would serve as a precursor to clinical trials and research, potentially expediting the availability of an additional therapeutic option for hemangiomas patients.

Table 7. Example of drug repositioning

Question	Is carteolol effective in treating hemangioma?
Reasoning Paths	Drug - [inhibition_to] → Genesymbol ← [inhibition_to] - Drug - [treatment]→ Cancer
Relational Chain	(carteolol) − [inhibition_to] → (ADRB1) ← [inhibition_to] − (propranolol) − [treatment] → (hemangiomas)
Inference	Carteolol inhibits ADRB1.Propranolol also inhibits ADRB1 and is used in the treatment of hemangiomas.This relational chain suggests that by inhibiting ADRB1, propranolol can serve as a treatment method for hemangiomas. carteolol, operating through the same mechanism of inhibition (inhibiting ADRB1), allows us to infer that carteolol may have some efficacy in the treatment of hemangiomas.
Answer	Carteolol may have some efficacy in treating hemangiomas due to its mechanism of inhibiting ADRB1, the same target inhibited by propranolol, which is used for hemangiomas treatment.

Table 8. Example of drug resistance research

Question	Which drugs does cancer carrying ALK-p.L1196M exhibit resistance?
Reasoning Paths	SnvFull ← [has_var] - CancerCell - [resistance_to]→ Drug
Relational Chain	(ALK-p.L1196M) ← [has_var] − (ALK-p.L1196M-lung cancer) − [resistance_to] → (crizotinib)
Inference	ALK-p.L1196M is a gene mutation. The term "has var" indicates that the ALK-p.L1196M mutation is present in the context related to lung cancer. "Resistance to" denotes that this ALK-p.L1196M variant, associated with lung cancer, exhibits resistance to the crizotinib. Therefore, from this chain of relations, it can be concluded that ALK-p.L1196M demonstrates resistance to crizotinib in lung cancer, implying that crizotinib might not be an effective medication for treating cancers caused by this specific gene mutation.
Answer	The cancer carrying ALK-p.L1196M shows resistance to crizotinib.

Drug resistance research

Drug resistance in cancer treatment poses a significant challenge in clinical oncology. Understanding the genetic basis of resistance can lead to more effective treatment strategies and personalized medicine approaches. Research in drug resistance involves determining why certain cancer carrying mutated gene are not responsive to specific drugs and finding ways to overcome this resistance [42]. Our system is capable of exploring drug resistance in cancer. The example is shown in Table 8 and relational diagram is shown in Fig. 8(B). The KG data indicates that the ALK-p.L1196M mutation, which is associated with gastric cancer, has a known resistance to Nalatinib [43, 44]. The LLM processes this information and infers that due to this resistance, Nalatinib might not be an effective medication for treating cancers caused by the ALK-p.L1196M mutation. The case highlights the critical importance of understanding specific gene-drug interactions in drug resistance research. It demonstrates how certain gene mutations could render a drug ineffective, which in turn could guide oncologists in choosing alternative treatments or developing new drugs that can bypass or target the resistance mechanisms. By accelerating the process of understanding drug resistance, these AI-driven systems can contribute to improved patient outcomes and the optimization of cancer treatment protocols.

Individualized treatment

The advancement of personalized medicine is predicated on the ability to tailor treatments to individual patient characteristics [45], particularly their genetic makeup. Individualized treatment is crucial for optimizing therapeutic efficacy and minimizing adverse effects. In oncology, this approach is particularly important as genetic variations can significantly influence how a patient responds to a drug. Our system is capable of providing individualized treatment plans. The example is shown in Table 9 and relational diagram is shown in Fig. 8(C). The KG provides a relational chain that establishes the sensitivity of lung adenocarcinoma cells harboring the ERBB2-p.Y772_A775dup mutation to ado-trastuzumab emtansine [46]. Through reasoning paths, the system identifies that ado-trastuzumab emtansine has efficacy against lung adenocarcinoma characterized by this particular mutation [47]. This case exemplifies the importance of individualized treatment. Our question-answering system can rapidly identify actionable genetic mutations and suitable drug therapies, enabling clinicians to prescribe treatment plans based on the genetic characteristics of a patient's tumor, thereby achieving more precise and potentially more successful cancer treatments.

Selection and understanding of biomarkers

Biomarkers play a crucial role in disease diagnosis, prognosis, and therapeutic interventions [48]. The selection and understanding of biomarkers are essential for tailoring patient-specific treatment strategies. However, the vast amount of biological data presents a significant challenge for clinicians and researchers in identifying relevant biomarkers efficiently. Our system is capable of discerning the impact of the PTEN-p.R173C mutation as a biomarker for intestinal cancer. The example is shown in Table 10 and relational diagram is shown in Fig. 8(D). Using the relational chain from the KG, the system reveals that the PTEN-p.R173C mutation is present in certain cancer cells of intestinal cancer and that these cells originate from intestinal cancer, indicating the mutation's potential role as a driver for this type of cancer [49, 50]. The inference made by the system emphasizes the significance of the PTEN-p.R173C mutation as a biomarker for intestinal cancer. Thus providing valuable insights for clinical decision-making.

Discussion

In this paper, we introduce a novel framework KGT, which employs LLMs for reasoning on the schema of KGs, to enhance the reasoning abilities of LLMs in areas with missing domain data by utilizing domain-specific knowledge graphs, such as oncology knowledge graphs, thereby addressing the issue of factual hallucinations in LLMs. Our method excels in extracting, validating, and refining factual knowledge throughout the LLMs' reasoning process. It seamlessly integrates with various LLMs, including open-source models like Code-Llama, and enhances the capabilities of LLMs solely through prompt engineering and in-context learning, without any fine-tuning. This grants it significant generalizability.

We possess an extensive oncology knowledge graph and establish a benchmark based on it to evaluate the capabilities of various methods. Additionally, case studies indicate that our approach can provide therapeutic plans, generate valuable hypotheses for drug repositioning, effectively identify potential drug targets, and study drug resistance. This highlights its effectiveness in delivering practical insights for developing and optimizing treatment strategies. And the conclusions of each case study are corroborated by evidence from research papers that have been previously published.

In the future, we are considering using an acceleration framework to accelerate the response time of LLMs, ensuring that our system not only provides accurate but also timely answers. Our ultimate goal is to create a robust framework that is applicable to the

Table 9. Example of individualized treatment

Question	Which oncogenic gene mutation can be treated by ado-trastuzumab emtansine?
Attribute	snvfull.oncogenic
Reasoning Paths	Drug ← [sensitivity_to] - CancerCell - [has_var]→ SnvFull
Relational Chain	(ado-trastuzumab emtansine) ← [sensitivity_to] – (ERBB2-p.Y772_A775dup-lung adenocarcinoma) – [has_var] → (ERBB2-p.Y772_A775dup) oncogenic
Inference	Ado-trastuzumab emtansine is sensitive to lung adenocarcinoma cells with the ERBB2-p.Y772_A775dup mutation. This sensitivity suggests that ado-trastuzumab emtansine may be effective in inhibiting or treating the proliferation of lung adenocarcinoma cells with this mutation. Therefore, it can be deduced that ERBB2-p.Y772_A775dup is an oncogenic gene mutation that can be treated with ado-trastuzumab emtansine.
Answer	The oncogenic mutation gene that can be treated with ado-trastuzumab emtansine is ERBB2-p.Y772_A775dup.

Table 10. Example of selection and understanding of biomarkers

Question	What type of cancers can be driven by PTEN-p.R173C?
Reasoning Paths	SnvFull ← [has_var] - CancerCell - [originated_from]→ Cancer
Relational Chain	(PTEN-p.R173C) ← [has_var] – (PTEN-p.R173C-intestinal cancer) – [originated_from] → (intestinal cancer)
Inference	PTEN-p.R173C is a specific genetic mutation that exists in certain cancer cells of intestinal cancer, and these cancer cells originate from intestinal cancer, indicating that this mutated gene can drive this cancer.
Answer	PTEN-p.R173C can drive intestinal cancer.

rapidly evolving domain of medical knowledge and supports healthcare professionals in delivering personalized, precise medication tailored to the individual needs of each patient.

Abbreviations

KG: knowledge graph; LLM: large language model; NLP: natural language processing; SFT: supervised fine-tuning; RLHF: reinforcement learning with human feedback; CF: catastrophic forgetting; CoT: Chain-of-thought; APE: automatic prompt engineer; KGQA: knowledge graph question answering; BFS: breadth-first search; PcQA: Pan-cancer Question Answering; ICL: in-context learning; GPT: generative pre-trained transformer.

Competing Interests

The authors declare that they have no competing interests.

Funding

This work was supported in part by funds from the National Key R&D Program (No. 2022YFF1202101, 2023YFC3041600); the CAS Research Fund (No. XDB38050200); the Self-supporting Program of Guangzhou National Laboratory (No. SRPG22001 and SRPG22007)

Authors' Contributions

Y.F. and L.Z. conceived the project. Y.F. proposed a KGQA benchmark, developed the KGT framework, implemented the code, conducted the experiments, and drafted the manuscript. C.M. contributed the SmartQuerier Oncology Knowledge Graph. Y.L. and L.Z. supervised the study. All authors read and approved the final manuscript.

References

1. OpenAI, Introducing ChatGPT; 2022.
2. Touvron H, Martin L, Stone K, Albert P, Almahairi A, Babaei Y, et al. Llama 2: Open foundation and fine-tuned chat models. arXiv preprint arXiv:230709288 2023;.
3. Ji Z, Lee N, Frieske R, Yu T, Su D, Xu Y, et al. Survey of hallucination in natural language generation. ACM Computing Surveys 2023;55(12):1–38.
4. Liu T, Zheng X, Chang B, Sui Z. Towards faithfulness in open domain table-to-text generation from an entity-centric view. In: Proceedings of the AAAI Conference on Artificial Intelligence, vol. 35; 2021. p. 13415–13423.
5. Kang D, Hashimoto T. Improved natural language generation via loss truncation. arXiv preprint arXiv:200414589 2020;.
6. Pan S, Luo L, Wang Y, Chen C, Wang J, Wu X. Unifying large language models and knowledge graphs: A roadmap. IEEE Transactions on Knowledge and Data Engineering 2024;.
7. Han T, Adams LC, Papaioannou JM, Grundmann P, Oberhauser T, Löser A, et al. MedAlpaca–An Open-Source Collection of Medical Conversational AI Models and Training Data. arXiv preprint arXiv:230408247 2023;.
8. Yunxiang L, Zihan L, Kai Z, Ruilong D, You Z. Chatdoctor: A medical chat model fine-tuned on llama model using medical domain knowledge. arXiv preprint arXiv:230314070 2023;.
9. Singhal K, Azizi S, Tu T, Mahdavi SS, Wei J, Chung HW, et al. Large language models encode clinical knowledge. arXiv preprint arXiv:221213138 2022;.
10. Wang H, Liu C, Xi N, Qiang Z, Zhao S, Qin B, et al. Huatuo: Tuning llama model with chinese medical knowledge. arXiv preprint arXiv:230406975 2023;.
11. Xiong H, Wang S, Zhu Y, Zhao Z, Liu Y, Wang Q, et al. Doctorglm: Fine-tuning your chinese doctor is not a herculean task. arXiv preprint arXiv:230401097 2023;.
12. Zhang H, Chen J, Jiang F, Yu F, Chen Z, Li J, et al. HuatuoGPT, towards Taming Language Model to Be a Doctor. arXiv preprint arXiv:230515075 2023;.
13. Yang S, Zhao H, Zhu S, Zhou G, Xu H, Jia Y, et al. Zhongjing: Enhancing the chinese medical capabilities of large language model through expert feedback and real-world multi-turn dialogue. arXiv preprint arXiv:230803549 2023;.
14. Tian Y, Gan R, Song Y, Zhang J, Zhang Y. ChiMed-GPT: A Chinese Medical Large Language Model with Full Training Regime and Better Alignment to Human Preferences. arXiv preprint arXiv:231106025 2023;.
15. Ouyang L, Wu J, Jiang X, Almeida D, Wainwright C, Mishkin P, et al. Training language models to follow instructions with human feedback. Advances in Neural Information Processing Systems 2022;35:27730–27744.
16. Luo Y, Yang Z, Meng F, Li Y, Zhou J, Zhang Y. An empirical study of catastrophic forgetting in large language models dur-

ing continual fine-tuning. arXiv preprint arXiv:230808747 2023;.

17. Li Z, Hoiem D. Learning without forgetting. IEEE transactions on pattern analysis and machine intelligence 2017;40(12):2935–2947.

18. Liu V, Chilton LB. Design guidelines for prompt engineering text-to-image generative models. In: Proceedings of the 2022 CHI Conference on Human Factors in Computing Systems; 2022. p. 1–23.

19. Wei J, Wang X, Schuurmans D, Bosma M, Xia F, Chi E, et al. Chain-of-thought prompting elicits reasoning in large language models. Advances in Neural Information Processing Systems 2022;35:24824–24837.

20. Zhou Y, Muresanu AI, Han Z, Paster K, Pitis S, Chan H, et al. Large language models are human-level prompt engineers. arXiv preprint arXiv:221101910 2022;.

21. Sun H, Dhingra B, Zaheer M, Mazaitis K, Salakhutdinov R, Cohen WW. Open domain question answering using early fusion of knowledge bases and text. arXiv preprint arXiv:180900782 2018;.

22. Sun H, Bedrax-Weiss T, Cohen WW. Pullnet: Open domain question answering with iterative retrieval on knowledge bases and text. arXiv preprint arXiv:190409537 2019;.

23. Zhang J, Zhang X, Yu J, Tang J, Tang J, Li C, et al. Subgraph retrieval enhanced model for multi-hop knowledge base question answering. arXiv preprint arXiv:220213296 2022;.

24. Chen Y, Wu L, Zaki MJ. Bidirectional attentive memory networks for question answering over knowledge bases. arXiv preprint arXiv:190302188 2019;.

25. Saxena A, Tripathi A, Talukdar P. Improving multi-hop question answering over knowledge graphs using knowledge base embeddings. In: Proceedings of the 58th annual meeting of the association for computational linguistics; 2020. p. 4498–4507.

26. Lan Y, He G, Jiang J, Jiang J, Zhao WX, Wen JR. A survey on complex knowledge base question answering: Methods, challenges and solutions. arXiv preprint arXiv:210511644 2021;.

27. Das R, Zaheer M, Thai D, Godbole A, Perez E, Lee JY, et al. Case-based reasoning for natural language queries over knowledge bases. arXiv preprint arXiv:210408762 2021;.

28. Jiang J, Zhou K, Zhao WX, Wen JR. Unikgqa: Unified retrieval and reasoning for solving multi-hop question answering over knowledge graph. arXiv preprint arXiv:221200959 2022;.

29. Jiang J, Zhou K, Dong Z, Ye K, Zhao WX, Wen JR. Structgpt: A general framework for large language model to reason over structured data. arXiv preprint arXiv:230509645 2023;.

30. Kim J, Kwon Y, Jo Y, Choi E. KG-GPT: A general framework for reasoning on knowledge graphs using large language models. arXiv preprint arXiv:231011220 2023;.

31. Wang J, Wu M, Huang X, Wang L, Zhang S, Liu H, et al. SynLethDB 2.0: a web-based knowledge graph database on synthetic lethality for novel anticancer drug discovery. Database 2022;2022:baac030.

32. Zhu C, Yang Z, Xia X, Li N, Zhong F, Liu L. Multimodal reasoning based on knowledge graph embedding for specific diseases. Bioinformatics 2022;38(8):2235–2245.

33. Lin YT, Chen YN. LLM-Eval: Unified Multi-Dimensional Automatic Evaluation for Open-Domain Conversations with Large Language Models. arXiv preprint arXiv:230513711 2023;.

34. Zhang T, Kishore V, Wu F, Weinberger KQ, Artzi Y. Bertscore: Evaluating text generation with bert. arXiv preprint arXiv:190409675 2019;.

35. Lin CY. Rouge: A package for automatic evaluation of summaries. In: Text summarization branches out; 2004. p. 74–81.

36. Dong Q, Li L, Dai D, Zheng C, Wu Z, Chang B, et al. A survey for in-context learning. arXiv preprint arXiv:230100234 2022;.

37. Roziere B, Gehring J, Gloeckle F, Sootla S, Gat I, Tan XE, et al. Code llama: Open foundation models for code. arXiv preprint arXiv:230812950 2023;.

38. Luo L, Ning J, Zhao Y, Wang Z, Ding Z, Chen P, et al. Taiyi: a bilingual fine-tuned large language model for diverse biomedical tasks. arXiv preprint arXiv:231111608 2023;.

39. Tunstall L, Beeching E, Lambert N, Rajani N, Rasul K, Belkada Y, et al., Zephyr: Direct Distillation of LM Alignment; 2023.

40. He S, Liu X, Ye X, Tetsuya S. Analysis of Drug Repositioning and Prediction Techniques: A Concise Review. Current Topics in Medicinal Chemistry 2022;22(23):1897–1906.

41. Gan Lq, Wang H, Ni Sl, Tan Ch. A prospective study of topical carteolol therapy in Chinese infants with superficial infantile hemangioma. Pediatric Dermatology 2018;35(1):121–125.

42. Gottesman MM. Mechanisms of cancer drug resistance. Annual review of medicine 2002;53(1):615–627.

43. Alshareef A, Zhang HF, Huang YH, Wu C, Zhang JD, Wang P, et al. The use of cellular thermal shift assay (CETSA) to study Crizotinib resistance in ALK-expressing human cancers. Scientific reports 2016;6(1):33710.

44. Simionato F, Frizziero M, Carbone C, Tortora G, Melisi D. Current strategies to overcome resistance to ALK-inhibitor agents. Current drug metabolism 2015;16(7):585–596.

45. Stock G, Sydow S. Personalised medicine: Paradigm shift within drug research and therapy. Bundesgesundheitsblatt-Gesundheitsforschung-Gesundheitsschutz 2013;56:1495–1501.

46. Wang H, He Y, Zhao W, Tong Z. Ado-trastuzumab emtansine in the treatment of lung adenocarcinoma with ERBB2 mutation: a case report and literature review. Anti-cancer drugs 2022;33(8):773–777.

47. Huang X, Jin R, Lou L, Zhao J, Xia L, Zhao J, et al. The efficacy of ado-trastuzumab emtansine in patients with ERBB2-aberrant non-small cell lung cancer: a systematic review. Translational Cancer Research 2020;9(8):4507.

48. Bodaghi A, Fattahi N, Ramazani A. Biomarkers: Promising and valuable tools towards diagnosis, prognosis and treatment of Covid-19 and other diseases. Heliyon 2023;.

49. Davies EJ, Marsh Durban V, Meniel V, Williams GT, Clarke AR. PTEN loss and KRAS activation leads to the formation of serrated adenomas and metastatic carcinoma in the mouse intestine. The Journal of pathology 2014;233(1):27–38.

50. Yang Z, Yuan XG, Chen J, Luo SW, Luo ZJ, Lu NH. Reduced expression of PTEN and increased PTEN phosphorylation at residue Ser380 in gastric cancer tissues: a novel mechanism of PTEN inactivation. Clinics and research in hepatology and gastroenterology 2013;37(1):72–79.