Decipher: A computational pipeline to extract context-specific mechanistic insights from single-cell profiles

Edgar Basto[1,2], Bilal Wajid[1,3,4], James Read[1,5], Jesse Armitage[7,8], Jason Waithman[7,8], Michael Small[2], and Anthony Bosco[1,5,6,†]

[1]INSiGENe Pty Ltd, Perth, WA, Australia
[2]Department of Mathematics and Statistics, University of Western Australia, WA, Australia
[3]Ibn – Sina Research & Development Division, Sabz-Qalam, Lahore 54000, Pakistan
[4]Dhani School of Science and Engineering, Habib University, Karachi, Pakistan
[5]Asthma & Airway Disease Research Center, The BIO5 Institute, The University of Arizona, Tucson, AZ
[6]Department of Immunobiology, The University of Arizona College of Medicine, Tucson, AZ
[7]School of Biomedical Sciences, University of Western Australia, WA, Australia
[8]Telethon Kids Institute, WA, Australia

[†]Corresponding author: anthony.bosco@insigene.com

Competing Interests Statement:
AB is the founder of the start-up company INSiGENe Pty Ltd that funded this work. AB is a co-founder, equity holder, and director of the startup company Respiradigm Pty Ltd that is unrelated to this work. EB received a scholarship from INSiGENe Pty Ltd to conduct this work.

Abstract

The advent of single-cell profiling technologies has revolutionized our understanding of the cellular and molecular states that underpin disease. However, current computational tools struggle to recover both known and novel mechanistic insights at distinct layers of biological regulation. Here, we present *Decipher*, a novel computational pipeline that builds integrated cell signalling networks from single-cell profiles in a context-specific, data-driven manner and identifies the key cellular and molecular events that drive disease. We benchmarked *Decipher* against existing tools and found it could recover known, experimentally determined cytokine signalling pathways, whilst maintaining the flexibility to detect novel pathways and context-specific effects. Notably, *Decipher* produces global cell-to-cell signalling maps that are interpretable. We utilised *Decipher* to unveil the cellular and molecular mechanisms driving a novel population of inflammatory monocytes enriched with interferon stimulated genes that is markedly increased in frequency following secondary immunization with the Pfizer-BioNTech COVID-19 mRNA vaccine. Finally, we employed Decipher to interrogate regulon profiles from covid-19 patients with mild versus severe disease, and we found that progression to severe disease was associated with a loss of interferon signalling transcription factors (Irf7, Irf9, STAT1, STAT2) and a gain of factors that drive inflammation and cellular stress responses (NFkB, HIF-1a, ATF3, ATF4). Taken together, our findings demonstrate that *Decipher* can decode signalling pathways and report on ligand-receptor mediated transcription factor-target gene networks that underlie processes in homeostasis, disease, and cellular responses to therapies. We present *Decipher* as an invaluable new tool for the discovery of novel therapeutic targets and the development of new medicines.

1 Main

Complex multicellular life forms execute a multitude of high-level biological functions, including growth, differentiation, metabolism and homeostasis. These functions are mediated by interactions among multiple cell types through diverse molecules, such as ligands and receptors[1]. The advent of single-cell omics, which profiles biological systems at single-cell resolution[2], along with computational tools that infer

patterns of cell-to-cell communication from such data[3,4], have furthered our understanding of the role of
intercellular interactions in diverse contexts such as the maternal-fetal interface[5], wound healing[4], human
development[6] and cancer[7].

While inferring cell-cell communication patterns is an active area of method development, with
over one-hundred available tools catalogued by Armingol et al.[8], most share two key limitations: they
overlook the downstream transcriptional effects of upstream signalling events[9], and even those that
consider such effects often rely heavily on pre-defined knowledge graphs to connect upstream signalling to
cellular responses.

Accounting for downstream effects is essential, as it reveals how cellular interactions reprogram
gene expression and ultimately drive disease processes[7], insights which are lost when analyses stop at
ligand-receptor pairs alone. Conversely, integrating curated knowledge graphs can improve the reliability
and accuracy of inferred networks[10], but at the same time, they can also bias the results towards well-
studied pathways[11], and obscure novel or context-specific signalling.

We surveyed eleven computational tools that analyse cell-cell communication and explicitly
account for downstream signalling. We found that most methods tend to rely on curated molecular
interaction databases, limiting their findings to well-studied relationships. This is the case for Pathway-
centric methods (SoptSC[12], CommPath[13]), Multilayer knowledge-graph methods (NicheNet[7], LRLoop[14],
Scriabin[15]) and Transcription-factor-centric methods (ScMLNet[16], CellCall[17], scSeqComm[18], SPARTAN[19]). *De*
novo network inference tools (CytoTalk[20], DIALOGUE[21]), in contrast, avoid this reliance on prior knowledge
by reconstructing networks directly from expression data, yet the resulting relationships often lack
mechanistic context. In both cases, the methodology limits the ability to identify novel signalling pathways.

To address these gaps, we developed *Decipher*, a novel computational platform that builds
integrated signalling networks that operate between and within cells, capturing both ligand-receptor
signalling and transcription factor-target gene regulatory activity. *Decipher* utilizes prior-knowledge
approaches when considering these networks separately, and data-driven network inference when
integrating them. Thus, *Decipher* carefully balances the ability to accurately prioritize signalling mechanisms
with the necessity to detect previously unidentified pathways.

2 Results

Decipher requires annotated single-cell RNA-seq profiles from two experimental conditions, a
database of interacting ligand-receptor (LR) pairs and a reference gene regulatory network capturing
relationships between transcription factors (TF) and their downstream target genes. A *Decipher* analysis is
not limited to any specific source of prior knowledge, however, by default we use LR pairs from
connectomeDB2020[22] and a base network from CellOracle[23]. In addition, as gene regulatory network wiring
is context-specific[24], we leverage further functionality from CellOracle[23] to tailor the base network to the
experimental and cellular context of each cell type, retaining only the edges that show evidence of being
active.

To score LR signalling, Decipher relies on reconstructed integrated signalling networks to link
intercellular signalling potential to downstream transcription factor activity. Signalling potential refers to
the capacity of cells to engage in differential signalling and is estimated as the mean-product[22] of ligand and
receptor expression across meta-cells[25] (a strategy we employ to limit dropout effects). Transcription factor
activity reflects the influence TFs exert within the cell and is inferred by applying an overdispersion-based
scoring function from PAGODA2[26,27] to the expression profile of the target gene set for each transcription
factor, as per the tailored gene regulatory networks. To reconstruct integrated signalling networks, the

calculated interaction potentials and TF activities are used as the predictor and target variables in a random
forest regression model, whose feature importance values represent the edge weights connecting LR pairs
to TFs within the network. The sign of the Spearman correlation between each predictor-target pair
designates the mode of influence of that edge. Together, these steps yield a weighted, signed integrated
signalling network that captures how extracellular cues propagate to transcriptional responses.

To quantify the activity of each LR pair i across conditions, *Decipher* integrates the predicted
regulatory weight $w_{i,f}$ between LR pair i and transcription factor f with the observed changes in TF activity
Δ_f, defined as the difference in median TF activity between conditions. The resulting *Decipher* score S is
computed as:

$$S = \sum_{f \in F} w_{i,f} \cdot \Delta_f$$

101 Where F denotes the set of TFs relevant to a given cell type. This formulation prioritizes LR pairs that are
102 both influential (high $w_{i,f}$ indicating a strong regulatory relationship) and associated with responsive TFs
103 (a large Δ_f signals a substantial intracellular change). *Decipher* scores support three core layers of
104 analysis: cell-to-cell LR signalling, LR-to-TF regulatory signalling and TF-target gene regulation (Fig. 1).

Figure 1. Overview of the *Decipher* framework for integrating intercellular and intracellular signalling. *Decipher* connects ligand-receptor (LR) interactions between a sender cell (e.g., antigen-presenting cell, APC) and a receiver cell (e.g., T-cell) to downstream transcription factor (TF) activity and target gene (TG) regulation. The framework consists of three hierarchical layers: (1) ligand-receptor interactions, (2) the interaction between LR pairs and TF activity profiles, (3) TF-target gene regulation. Together, these layers capture key signalling pathways both between and within cells.

Benchmarking Decipher with other cell-cell communication methods

To demonstrate the utility of *Decipher* in extracting insights into the cellular and molecular
responses to a perturbation, we applied *Decipher* to twelve publicly available scRNA-seq datasets
(Methods) focused on immune responses to viral and bacterial infections[28–31], vaccination[32,33], autoimmune
conditions[34,35], genetic disorders[36], chronic disease[37], and cancer[38,39]. We compared *Decipher* with four
other cell-cell communication methods: two that account for intracellular responses (NicheNet[7] and
LIANA+[40]) and two that focus solely on intercellular signalling (Connectome[41] and NATMI[22]).

We first profiled the general characteristics of the LR interaction scores produced by each method,
including the total number of reported LR pairs and the corresponding distribution of their scores. Although
the number of reported interactions by each method is not strictly a measure of performance, it can be
informative about how a method balances sensitivity and specificity.

We observed that *Decipher* reports two orders of magnitude fewer interactions than NicheNet,
NATMI, and Connectome, and one order of magnitude fewer interactions than LIANA+ (Fig. 2a). Methods
further differed in the characteristics of the distributions of their prioritization scores (Fig. 2b). Only
Decipher, LIANA+, and NATMI produced negative and positive scores, which indicate inhibition and
activation of signalling, respectively. The score distributions produced by the five methods formed four
distinct patterns. *Decipher* displayed a sharp peak at zero with long, exponentially decaying tails. NicheNet
had a peak at a moderately positive value and much shorter tails. LIANA+ and NATMI displayed bimodal
distributions, with peaks at moderately negative and moderately positive values, with NATMI exhibiting
especially short tails. Lastly, Connectome exhibited a sharp peak at zero and a long right tail, though the
decay was less steep.

Consensus among methods was limited. Overlap between the top-100 ranked LR pairs per dataset
(Fig. 2c) showed that NicheNet reported the greatest number of unique interactions. In comparison to other
methods, NicheNet displayed few two-way intersections, whereas three-way overlap was most frequent
among *Decipher*, NicheNet, and LIANA+. Four- and five-way overlaps were rare. Agreement in ranking was
assessed on the top-100 ranked consensus LR pairs using Spearman correlation and search depth (Fig. 2d),
defined as the rank position within each method required to retrieve all 100 consensus interactions.
Decipher required the smallest search depth in every pairwise comparison. LIANA+ displayed a similar
profile to *Decipher*, except when compared with NATMI. NATMI and Connectome showed moderate mutual
agreement, while NicheNet required markedly deeper searches to align with NATMI and Connectome.
Spearman correlation further highlighted structural differences among methods. NATMI and Connectome
displayed the highest consensus among all pairs. *Decipher*, NicheNet and LIANA+ were weakly to
moderately correlated with one another. In contrast, NATMI was negatively correlated with this group.

We benchmarked each method against CytoSig[42], which predicts cytokine activity for 62 ligands
based on experimentally determined gene expression signatures. Because NicheNet shares training data
with CytoSig[43], we treated NicheNet as a positive control. In some datasets, CytoSig detected an insufficient
number of active ligands (median z-score $\geq$ 2) to construct reliable ROC curves. *Decipher*, NicheNet and
NATMI achieved the highest upper-range AUC values, although the latter two exhibited a few low-
performing outliers. Connectome showed intermediate performance with modest variance, whereas
LIANA+ displayed limited predictive power in this benchmark.

Figure 2. Comparison of predicted ligand-receptor activity across methods. (a) Box plots summarizing the number of reported interactions for each method across all datasets. (b) Violin plots of the combined distributions of predicted interaction scores for each method across all datasets. (c) Box plot of the overlap between methods for the top 100 interactions in each dataset. The plot displays the number of interactions unique to each method, as well as the number of two-way, three-way, four-way, and five-way overlap. (d) Compound heatmap of the search space (bottom-left of heatmap) required to find 100 overlapping LR pairs that are both highly ranked, as well as Spearman correlations (top-right of heatmap) between the rankings of the top 100 overlapping LR pairs. The search space is displayed using a Viridis scale, where darker colours indicate a smaller search space and brighter colours a larger one. A smaller search space indicates a greater degree of agreement between methods. Spearman correlation utilizes a red to green colour scale, where red indicates negative Spearman correlation, green positive correlation, and white no correlation. (e) Beeswarm plot of AUC scores for eleven datasets benchmarking the performance of Decipher and other frameworks against CytoSig scores as true labels. We omitted the lupus and sepsis datasets from this comparison, as CytoSig did not define enough active ligands to construct reliable ROC curves. (f) Heatmap indicating the consistency of interactions prioritized

by Decipher across 100 runs on the dataset of lupus patient response to interferon-β[44] with distinct random seeds. White indicates that a ligand-receptor pair was not relevant to a particular cell type. (g) System-level signalling for the same dataset. The left sub-plot displays ligand-level statistics for the sender cell type, while the right sub-plot presents receptor-statistics for the receiver cell type. The size of the bubbles indicates the relative expression of the gene in the corresponding cell type, whereas the colour indicates the differential expression of that gene in case vs control. The central sub-plot presents *Decipher* scores for all receiver cell types. Here, blue indicates that a LR pair is predicted to be inhibited, and red activated.

Because *Decipher* includes stochastic steps, we tested its robustness to changes in the initial
random seed. The analysis was repeated 100 times on a dataset of lupus patient response to interferon-
β[44] distributed through the ExperimentHub package from Bioconductor[45]. Across the majority of the 100
runs, the same LR pairs were consistently prioritized (Fig. 2f); for example, IL15-IL2RG dominated B, CD4 T,
and CD8 T cell rankings, whereas LGALS9-CD44 was frequently the leading interaction for CD14⁺ monocytes.

Lastly, we compared the visual outputs of *Decipher*, NicheNet and LIANA+. Each tool conveys two
metrics: the signalling potential of individual ligands and receptors, and an activity score for every LR pair.
To convey the signalling potential, *Decipher* reports on the normalized proportion of transcripts originating
from each cell type, whereas NicheNet relies on the average expression of each ligand and receptor. LIANA+
does not convey this information. Differential signalling, on the other hand, is captured by all three methods
by reporting on the differential expression of the ligand or receptor separately. Because *Decipher*
aggregates all sender cell types into a single mixed cluster, it presents fewer visual outputs than the other
methods. Reformatting NicheNet and LIANA+ outputs for the infant response to Poly-IC comparison to the
same visual output format as *Decipher* highlighted this increase in complexity (Supplementary Fig. SF.1).

Extracting mechanistic insights from predictions made by *Decipher*

To assess the capacity of *Decipher* to extract mechanistic insights and identify candidate
therapeutic targets from single-cell profiles, we focused on two studies related to COVID-19: a study
investigating the immune response to the Pfizer-BioNTech COVID-19 vaccine in humans[33] and a study
profiling PBMCs from patients with mild or severe COVID-19[31]. Both studies included baseline, unvaccinated
or healthy, controls.

In the vaccination study, Arunachalam et al.[33] described the strong activation of the innate immune
system and the emergence of a novel CD14⁺BDCA1⁺PD-L1 (cluster C8) monocyte subpopulation one day
post-secondary vaccination. Moreover, Arunachalam et al. characterized the intracellular activity of this
subpopulation, identifying activation of STAT1, STAT2, STAT3, IRF1 and IRF8 TFs, and associatively linked
the observed response to interferon gamma (IFNG) signalling, hypothesizing that these two factors were a
key component of the programmed immune response after vaccination.

We applied *Decipher* to identify the upstream and downstream signals driving activation of the C8
monocyte subpopulation. The intracellular response of the C8 cluster showed strong upregulation in
subsets of the IRF and STAT family of TFs: IRF2, IRF7, IRF8, STAT1, and STAT2, consistent with observations
reported by Arunachalam et al.[33], (Fig. 3a). *Decipher* also detected IFNG signalling into the C8
subpopulation (Fig. 3b), in further accordance with the reference study[33]. In addition, we observed
autocrine and paracrine signalling into the C8 monocytes through SLAMF7, CCL2, and C1QB pathways, as
well as inhibited signalling via PRG4-TLR2 and HGF-CD44 pathways (Fig. 3b). We further characterized the
downstream TF response to prioritized LR pairs and observed that C1QB, CCL2, and SLAMF7 activation are
strongly related to STAT2, IRF2, IRF7, and IRF8 activity, as well as moderately related to a much broader
transcription factor response (Fig. 3c). IFNG, as well as other activated pathways identified by *Decipher*,
such as SPN and HGF, exhibited a more exclusive response.

Figure 3. Mechanistic insights in the Pfizer–BioNTech COVID-19 vaccine comparison. (a) Volcano plot of changes in transcription factor (TF) activity in the C8 cluster on day one post-secondary vaccination vs baseline. (b) Multi-panel plot of global dynamics from the top 10 identified ligand–receptor (LR) pairs in the C8 cluster. (c) Heatmap of individual LR–TF *Decipher* scores for the LR pairs highlighted in the *Decipher* multi-panel plot. (d) Heatmap of reference log fold-changes from the SLAMF7-high gene signature in synovial fluid (ref_syn_fluid) and PBMCs (ref_pbmc) from sorted CD14+ monocytes (Simmons et al.[46]), shown alongside differential expression profiles from three monocyte populations (C8, CD14+, and CD16+), as well as CD8 T, NK, and pDC cells.

To validate the predicted SLAMF7 signalling, we compared differential expression signatures of C8
monocytes, CD16+ monocytes, CD8 T, NK, and pDC cells with a published signature of SLAMF7[high]
macrophages from synovial fluid and PBMCs in an inflammatory setting[46]. The C8 signature, and to a lesser
extent the CD16+ signature, matched the reference (Fig. 3d). Although pDCs, NK cells and CD8 T cells express
SLAMF7, their differential expression signatures did not match the reference signatures, nor did *Decipher*
identify them as receiving signalling via SLAMF7.

We next compared mild and severe COVID-19 samples. Cell types were annotated with Azymuth[47]
using its PBMC reference annotated dataset. Analysis was restricted to cell types that were sufficiently
abundant and exhibited either changes in differential expression or in proportion across conditions (Fig.
4a). Out of the 29 cell types identified by Azimuth, fourteen represented less than 1% of the total cell pool
and were excluded. Abundance differences were further assessed with scCODA[48], which identified six cell
types that presented significant changes in abundance (FDR < 0.05): B naive cells, CD16+ monocytes, CD4

TCMs, CD8 cells, NK cells, and plasmablasts. To elucidate changes in these populations, we calculated the total number of differentially expressed genes (DEGs), as well as the proportion corresponding to mild versus severe and up- vs down-regulation (Fig. 4c).

Figure 4. Cell-type-specific transcriptional differences in mild and severe COVID-19. (a) Text summarizing the total proportion of each cell type across the three conditions (Healthy, Mild, and Severe). (b) Bar plot of the relative proportion of each cell type for each condition. Guide vertical lines are displayed at the 33% and 66% values. (c) Bar plot of total number of differentially expressed genes and changes in the proportion of upregulated vs downregulated genes. Crosshairs in each bar indicate the 50% mark of the number of differentially expressed genes. (d) Line plot of the first principal component embedding of changes in TF activity by cell type and condition. Cell types across conditions are joined by a dotted line whose colour reflects the distance (Euclidean) between them. (e) Heatmap of differences in changes in TF activity (mild – severe) for top 10 PC1 loadings. (f) Differential TF activity plots for CD16+ Monocytes and CD14+ Monocytes, sorted by absolute value of change in TF activity for that given cell type in either the mild or severe condition.

We then quantified changes in transcription factor (TF) activity in the two comparisons and
projected the change in TF activity scores onto a reduced-dimensional representation via principal
component analysis. Four cell types: CD14$^+$ monocytes, CD16$^+$ monocytes, NK and CDC2 cells, showed
the largest differences in the first principal component embedding between the mild and severe
conditions (Fig. 4d). The loadings corresponding to the first principal component accounted for 36.7%
of the observed variance and included interferon-related transcription factors IRF7, IRF8, IRF9 and
STAT1 (Fig. 4e). Critically, a cell-type- and condition-dependent divergent response to mild and severe
COVID-19 was apparent in the direction of change along the PC1 axis. Heatmaps of the delta in the
change in TF activity between mild and severe, calculated as the subtraction of the mild scores from
the severe scores, further showcased evidence for this divergent response; CD16$^+$ monocytes in severe,
for example, exhibited inhibition in most TFs related to PC1, whereas CD14$^+$ monocytes in severe
exhibited strong activation of those same TFs (Fig. 4e). Together, these observations suggest that these
cell types underwent substantial transcriptional reprogramming, particularly in interferon-related
functions, between the mild and severe states.

To further corroborate this observation, we visualized changes in TF activity sorted by the absolute
values for both mild and severe conditions for CD14$^+$ and CD16$^+$ monocytes (fig. 4f). Here, we observed that
CD16$^+$ monocytes from the mild condition display strong differential activation of interferon-related
transcription factors (STAT1, IRF7, STAT2, JUND, and IRF9), which were not upregulated in CD16$^+$ monocytes
from the severe condition. This difference appears reversed in CD14$^+$ monocytes, albeit the effect does not
speak to a divergent response, but rather to a change in intensity of activation.

To further characterize this divergence in intracellular programs we examined comparative
network representations across the three layers produced by the *Decipher* analysis for both the mild and
severe comparisons of the two monocyte subpopulations (Fig. 5). The LR signalling of these networks
showed that CD14$^+$ monocytes in the severe condition exhibited the strongest activation of intercellular
signalling: via CD63, SIGLEC1, SELL and ITGB2 receptors. In addition, pDCs only played a role in signalling in
the mild condition. We again observed markers of type I interferon signalling via the TFs IRF7, IRF9, STAT1
and STAT2, active in CD14$^+$ monocytes from both mild and severe COVID, and in CD16$^+$ Monocytes from
mild COVID only. In CD16$^+$ monocytes from severe COVID, there is a complete loss of type I interferon
signalling TFs. Moreover, this loss of type I interferon TFs is associated with a gain in TFs that drive
inflammation (NFkB2) and responses to oxidative and cellular stress (HIF-1A, ATF3, ATF4).

Figure 5. Multi-layer visualizations of *Decipher* results for CD14⁺ Monocytes and CD16⁺ monocytes in mild and severe COVID-19. Network graphs displaying sender cell type (blue), ligand (green), receptor (orange) and transcription factors (TFs) for the CD14⁺ and CD16⁺ monocytes in mild and severe COVID-19. Each network is constrained to the top 10 upregulated TFs, coloured by the change in calculated TF activity. Edges between sender cell types and ligands are weighted by the proportion of total ligand expression (normalized by cell count) expressed by each cell type. Additionally, only the top three cell types producing a given ligand are given an edge with that ligand. In addition, only ligands and receptors involved in the top 20 interactions by Decipher score and strongly associated with the top TFs (based on permutation importance) were considered. Lastly, each network is accompanied by a heatmap of downstream target genes (TG) for each TF. We limited these target genes to the top 40 most researched genes (within the set of target genes for the selected TFs), as determined by the number of publications that mention said gene in PubMed[49]. Red colour within the heatmap indicates the existence of a regulatory relationship between a TF and a TG. All four plots share the same scale for the node colours (applicable to TFs) and widths or colours of edges.

3 Discussion

Decoding the cellular and molecular events that drive disease processes and cellular responses to therapies requires the development of new methods that can extract deep mechanistic insights at multiple layers of regulation from single-cell profiles. Cell-cell communication is one of these critical layers, as it mediates many of the functions necessary for multicellular life. However, among the methods that study intercellular communication, most only focus on upstream ligand-receptor interactions and fail to consider downstream effects. Among the subset of methods that do account for multiple regulatory levels, most tend to overly rely on prior knowledge, limiting their findings to well-characterized relationships. Those that do rely primarily on data-driven network reconstruction often lack mechanistic context and may not even possess sufficient predictive power for network inference[50]. In both instances, the methodology limits the ability to identify novel signalling pathways. Toward this goal, we developed *Decipher*, a novel computational pipeline that builds integrated cell-signalling networks from single-cell profiles and unveils key cellular and molecular events that drive biological responses. *Decipher* employs both prior knowledge and data-driven approaches to strike a balance between novelty and accuracy. We found that *Decipher* performed as well as or better than other state-of-the-art cell-cell communication methods, while also generating more interpretable visualizations. To test the ability of *Decipher* to extract mechanistic insights, we analysed two COVID-19 single-cell datasets. In the first study, we identified the upstream signals that drive a previously described monocyte subpopulation critical to the immune response post Pfizer-BioNTech COVID-19 vaccination. In the second study, we characterized the difference in cellular responses of monocytes in mild and severe COVID-19, which aligned with current understanding of the mechanisms of this disease. Taken altogether, our findings suggest that *Decipher* can decode signalling pathways and report on mechanistic relationships captured through ligand-receptor mediated transcription factor – target gene networks.

We benchmarked *Decipher* against four established cell-cell communication methods and found that *Decipher* returns a tightly prioritized set of molecular pathways with scores that capture both the strength and mode of influence across ligands, receptors, transcription factors and target genes. While agreement among methods was generally low, as previously noted for other methods by Dimitrov et al.[11] we did observe that tools limited to exploring only ligand-receptor interactions behaved differently from those that included intracellular signalling as well. When evaluated against ligand activity predictions from CytoSig[42], *Decipher* performed as well as or better than other methods, while maintaining the flexibility to detect novel pathways by reducing its reliance on prior knowledge. Importantly, *Decipher* consistently prioritized top ligand-receptor pairs across runs, suggesting robustness in its analysis. We further observed that, by pooling all sender cell types into a single mixed cluster, *Decipher* produced signalling maps that reduce visual clutter without sacrificing biological insight. Thus, *Decipher* offers a balance between highly prioritized interactions, concise visualisations and competitive predictions.

To evaluate the capacity of *Decipher* to extract mechanistic insights from single-cell profiles, we analysed two COVID-19 scRNA-seq studies profiling PBMCs: the first from individuals one day post-secondary Pfizer-BioNTech COVID-19 vaccination, and the second from patients with mild or severe COVID-19. We employed *Decipher* to recover the underlying mechanism driving a novel subpopulation of CD14+BDCA1+PD-L1+ monocytes identified by Arunachalam et al. to be markedly increased in frequency following secondary vaccination and characterized by Type I interferon response, TLR and inflammation, with elevated activity of interferon and STAT TFs and reduced activity of AP-1 TFs[33]. *Decipher* analysis confirmed the previously reported upregulation of IFN (IRF2, IRF7, IRF8) and STAT (STAT1, STAT2, STAT3) family of TFs, as well as displayed significant crosstalk between innate immune cell types, as well as autocrine signalling in C8 cells, a common phenomenon in cell-cell communication[3]. We confirmed previous data demonstrating that interferon gamma (IFNG) is a driver of the C8 population[33], as well as identified

CD8 T and NK cells as the primary producers of this ligand[51]. IFNG, however, was not the strongest signal
found by *Decipher*, as we also found significant signalling through the SLAMF7, CCL2 and C1QB ligands into
the C8 cluster. Notably, SLAMF7 is a self-ligand receptor from the signalling lymphocytic activation molecule
(SLAM) family and a potent regulator of interferon responses[52] and inflammatory macrophage activation[46].
Importantly, IFNG and SLAMF7 have been previously implicated as a driver of a super-activated
macrophage state present in autoimmune diseases and severe COVID-19[46].

The response to SARS-CoV-2 infection involves an interplay of immune pathways that determine
disease severity. During the early stages of SARS-Cov2 infection, it is crucial to mount a robust type I
interferon response to limit the spread of infection and prime adaptive immune responses that promote
viral clearance. In patients with severe disease, delayed and ineffective interferon responses result in
increased viral loads. SARS-CoV2 proteins inhibit interferon signalling at multiple steps in the pathway and
promote NFkB signalling, resulting in a cytokine storm that drives severe disease[53]. Oxidative stress and
excessive tissue damage activates inflammasomes, further driving the cytokine storm, which in turn
promotes vascular permeability, decreased oxygen levels in the blood, multi-organ damage, and respiratory
failure[53]. *Decipher* analysis of monocyte responses in patients with COVID-19 found that transcription
factors that mediate interferon responses (e.g. IRF7, IRF9, STAT1, STAT2) were strongly activated in CD14$^+$
monocytes from patients with both mild and severe disease. However, in CD16$^+$ monocytes from patients
with severe disease, we observed a loss of interferon transcription factors and a gain of NFkB and other
factors that mediate responses to oxidative and cellular stress (HIF-1a, ATF3, ATF4). Importantly, this was
not observed in patients with mild disease. In this context it is noteworthy that about 10% of blood
monocytes are infected with SARS-CoV2 in patients with covid disease[54]. Given that monocytes do not
express the viral entry receptor ACE2, virus is taking up by monocytes via antibody-mediated opsonisation
through the Fcγ receptor CD16[54]. Once inside monocytes, the viral proteins will inhibit interferon signalling,
promote NFkB signalling and inflammasome activation and drive a system cytokine storm.

Decipher has limitations that should be acknowledged. We observed intracellular activity to be
imbalanced, where some cell types have a greater number of differentially activated TFs. While this is
expected behaviour, it may affect the ability to compare prioritization scores between cell types. To address
this, a potential alternative could be to perform scaling on TF activity and introduce a normalization factor,
in similar manner to scSeqComm[18]. We also observed that TF activity was highly correlated within each cell
type. Although multi-collinearity is a known property of biological networks, in the context of our analysis
it does pose a problem, as LR pairs that are most predictive of the activity of a TF are likely to be selected
for other TFs. Here, we suggest implementing new scoring strategies for TF activity, something that is in
active development by the bioinformatics community. Conceptually, *Decipher* currently does not consider
the fact that signalling occurs within local niches nor account for feedback control or response dynamics.
These issues can be addressed, for example, by extending *Decipher* to spatial transcriptomics data and by
modelling this dynamical systems behaviour. Despite these limitations, our findings demonstrate the utility
of *Decipher* to decode biological processes and, in doing so, unveil novel therapeutic targets for
experimental validation and clinical development. We present *Decipher* as a modular pipeline that
quantifies active ligand-receptor pairs, accounts for downstream intracellular responses and maps cell-cell
communication at a systems level. We believe that *Decipher* will be invaluable as a tool to accelerate the
identification of novel therapeutic targets for human diseases, as well as accelerate the development of
new medicines.

4 Methods

Collection and processing of single-cell transcriptomic data of poly-IC stimulation to human blood mononuclear cells from Read et al.[28] Processed single-cell data was directly obtained from the original authors. We used the original cell type labels, so no further preprocessing was required. Alternatively, the data are available from Gene Expression Omnibus (Accession Number GSE184383).

Collection and processing of mouse single-cell transcriptomic data of lung-tissue response to BCG vaccination from Lee et al.[32] Count data was downloaded from Gene Expression Omnibus (Accession Number: GSE244126). No cell type labels were provided, so we used ScType[55] along with two reference tissue profiles (Immune system and lung) to assign cell type labels to each cluster, retaining the label with the largest score for each cluster.

Collection and processing of human single-cell transcriptomic data of human PBMC response to Pfizer-BioNtech vaccination from Arunachalam et al.[33] Count data and phenotypic data were downloaded from Gene Expression Omnibus (Accession Number: GSE171964). We used the original cell type labels, so no further preprocessing was required.

Collection and processing of single-cell transcriptomic data of PBMCs from subjects with Systemic Lupus (SLE) and healthy control from Perez et al.[34] Count data, including phenotypic data, was downloaded from Gene Expression Omnibus (Accession number: GSE174188). We used the original cell type labels, so no further preprocessing was required. We constrained our analysis to the subset of samples belonging to female individuals of Asian ancestry that were either classified as healthy or as 'managed' SLE cases.

Collection and processing of single-cell transcriptomic data of PBMCS from ICU patients with and without sepsis from Reyes et al.[29] Count data with phenotypic information were downloaded from the Broad Institute Single-cell Portal (Accession Number: SCP548). We used the original cell type labels, so no further preprocessing was required.

Collection and processing of single-cell transcriptomic data of PBMCS from breast cancer patients treated with immune checkpoint blockade from Bassez et al.[38] Processed single-cell data was downloaded directly from Diether Lambrecht's laboratory website, through their Data portal. We used the original cell type labels, so no further preprocessing was required.

Collection and processing of single-cell transcriptomic data of PBMCS from patients with mild or severe COVID-19 from Arunachalam et al.[31] Count data of PBMCs from mild and severe COVID-19 patients was downloaded from GEO (accession number: GSE155673). Only samples corresponding to actual RNA-seq experiments were selected (cov01–cov04, cov07–cov12, cov17–cov18). For each sample, the corresponding barcodes.tsv.gz and matrix.mtx.gz files were retrieved. Separate Seurat objects were created for each sample and merged into a single object, with sample identifiers tracked in metadata. Sample-level metadata (age, sex, disease status, severity, and days since symptom onset) were curated from GEO and merged with cell-level metadata. We followed the preprocessing protocol outlined in the original study to produce cluster-level marker genes distinguishing severe and mild COVID-19 from Healthy controls. We applied the Azimuth pipeline[47] to label cell types (at level-2 resolution).

Collection and processing of single-cell transcriptomic data from the CellxGene collection[56]. Processed single-cell datasets were downloaded as annotated .h5ad objects from the CZ CellxGene portal. For each dataset, we applied consistent preprocessing steps: cells with fewer than 200

detected genes were removed. Datasets were optionally subset based on disease or condition
annotations, depending on the study context. The AnnData objects were parsed in Python, and we
verified that raw count matrices contained integer values. Metadata, gene names, and filtered count
matrices were extracted and saved in standard formats. Where applicable, Ensembl gene IDs were
converted to HGNC symbols. Resulting count matrices and metadata was used to create Seurat
objects in R, with cleaned cluster annotations and standardized condition labels. Original cell type
and disease labels were retained throughout
379
380 This workflow was applied to: PBMCs from healthy individuals and patients with influenza from Lee
381 et al.[30]; Pancreatic islets from healthy donors and individuals with type 1 diabetes from Fasolino et
382 al.[35] ; Head and neck squamous cell carcinoma samples from Jenkins et al.[39]; Kidney samples from
383 healthy individuals and chronic kidney disease patients from Lake et al.[37]; and Bronchial biopsy
384 samples from cystic fibrosis patients and healthy controls from Berg et al.[36].
385
Preprocessing pipeline. If needed, a standard preprocessing pipeline based on Seurat[47] is delineated
in "Supplementary Note 1: Preprocessing pipeline for single-cell profiles". Said pipeline addresses
standard scRNA-seq preprocessing, beginning after the raw data has been read aligned to produce
gene counts D. In brief, this preprocessing pipeline covers the filtering out poor-quality, invalid, or
damaged cells, normalization of gene counts, using these counts to produce clusters $\mathbb{G}_j$ of similar
cells and determining representative genes for each cluster for downstream cell-labelling. To aid
with interpretability of results, we recommend clusters are labelled using expert judgement. If expert
judgement is not available, there are several cell type labelling tools, one of which we used (ScType[55])
to pre-process lung-tissue data from Lee et al[32].
395
Meta-cell generation. To remove noise and account for zero-inflation of gene counts in scRNA-seq
data, we applied the method proposed by Baran et al.[25] with parameters determined from guidelines
by Obradovic et al.[57] Here, randomly-sampled individual single-cell profiles from each condition and
cell type were aggregated into meta cells by adding the counts of each gene across similar cells
(based on Euclidean distance of their gene counts). The number of cells per meta-cell, k, was
determined such that for most cell types, the median gene count per cell was between 7,500 and
10,000[57]. We constrained the number of meta-cells such that each cell type had the same number
of meta-cells, and, on average, no cell appeared in more than one meta-cell. In addition, we include
a parameter to limit the number of meta-cells generated for each cluster-condition pair. This
prevents overrepresentation of large cell groups and ensures computational tractability by capping
the number of meta-cells at 600 per group, which typically exceeds the number of features modelled
in downstream analyses. Lastly, each meta-cell was normalized by its new library size and scaled by
a factor of 10^6 for interpretability.
409
Interaction potential between clusters. As a pre-requisite to determine which ligand-receptor (LR)
pairs are actively modulating a system's response, we first confirmed that these same LR pairs had
the potential to signal. Here, we relied on the reference LR pair database ConnectomeDB2020[22]. LR
interactions in ConnectomeDB2020 were manually curated, based on literature support, and
focused on monomeric interactions, i.e. a single ligand interacts with a single receptor. This aligned
with our current version of the pipeline, as *Decipher* currently does not support multimeric
interactions.
417
We retained any ligand that was expressed in at least 10% of cells in any cell type and condition. We
addressed ligands at a global level because we assumed that ligand-concentration in the
environment is the driver of signalling, as opposed to ligand production by a single cluster. Receptors
were filtered on a cluster-by-cluster basis. For each cell type, a receptor was only retained if it was
expressed in at least 10% of the cells in either condition. Receptors were treated as cluster-specific

because receptor signalling is biologically constrained to individual cells. Together, this yielded a
cluster-specific list of LR pairs.
425
426 The condition-specific interaction potential p of a ligand-receptor pair i in each meta-cell from a
427 receiver cell type was calculated as:
428
429 $$p = \sqrt{\bar{l} \times r}$$
430
Where $\bar{l}$ represents the mean ligand expression of ligand l across all cell types in each condition and
r represents the receptor expression in a meta-cell. We performed the Wilcoxon Rank Sum test as
implemented in the *FindMarkers* function from the *Seurat* package to identify differentially
expressed interactions $\left(p_{adj} < 0.01 \,\&\, \log_2(\cdot) > 0.1\right)$ across conditions. Here, we assumed that the
interaction potential had to exhibit some change across conditions to be relevant for downstream
analysis.
437
A significant portion of selected LR pairs exhibited high correlation with each other and thus could
affect downstream statistical modelling. Highly correlated LR pairs occurred primarily when multiple
ligands shared a single receptor (Supplementary Fig. SF.2). Therefore, we focused on selecting
representative interactions for those interactions whose receptors had multiple complementary
ligands. To identify which interactions behaved similarly across samples, we calculated the distance
between each pair of interactions as:
444
445 $$d(\boldsymbol{p}_a, \boldsymbol{p}_b) = 1 - \rho_S(\boldsymbol{p}_a, \boldsymbol{p}_b)$$
446
Where $\boldsymbol{p}_a$ and $\boldsymbol{p}_b$ represent the vector of interactions potentials for two LR pairs, and $\rho_S(\cdot)$
represents the Spearman correlation function. We performed hierarchical clustering on these
distances to define clusters of similarly behaving interactions. Subsets produced by hierarchical
clustering were defined using a distance metric threshold; we set this parameter so that we
produced approximately the same number of clusters as unique receptors within our features.
Lastly, we randomly selected and retained one representative LR interaction from each subset.
453
Context-specific GRNs for each cluster. We relied on base gene regulatory networks provided by
CellOracle[23], as these were generated using single-cell ATAC-seq data which, unlike computationally
derived gene regulatory networks, ensures there is biological evidence of a relationship between a
transcription factor (TF) and a target gene (TG). We further relied on *CellOracle* to tailor this network
to each cell type. *CellOracle* is implemented as a Python pipeline, which required converting our
Seurat objects to Python objects. Given difficulties with mapping Seurat objects to the required
format, we converted our count matrices to Python-compatible matrices and re-processed these
counts using the Scanpy[58] pipeline. The pipeline consisted of removing genes with no counts,
normalizing cell counts by library size, filtering normalized counts to retain only the top 3,000 most
variable genes, which were re-normalized by their new library size, and taking the natural logarithm
and scaling these counts to unit variance and zero mean. We ran the *get_links()* function from the
cellOracle pipeline on the scaled counts to tailor the base gene regulatory network to each cell type.
466
The tailored gene regulatory networks produced by *CellOracle* proved too dense, so we only retained
the strongest 20,000 edges in the network (based on the absolute values of their weights). This first
pruning was a more global, entire-network based-pruning. We complemented this global pruning
with a more local pruning of edges, such that for each TF present in the network, we restricted its
outdegree to a maximum of 40 edges, retaining the largest edges within each sub-network. We
performed pruning of the network to increase the heterogeneity of regulons (as large regulons
naturally tended to have overlap with smaller regulons.

Scoring TF activity. Using the tailored networks, we proceeded to calculate the activity of individual TFs based upon the expressions of their TGs using elements of PAGODA2[27]. We applied PAGODA2's 'mixture model' to the meta-cell count matrix to derive a matrix of residuals, capturing the over- or under-dispersion of each gene in each meta-cell. We applied PAGODA2's function *testPathwayOverdispersion()* to the residual matrix. This function is an implementation of the implicitly restarted Lanczos bidiagonalization algorithm, which returns the first principal component for a given. For each meta-cell, we projected its residual vector onto that first principal component, obtaining a meta-cell-specific activity score. The collection of these scores across all meta-cells was then standardized to yield a TF activity score.

Relevant TFs for each cell-type were then selected based on statistically significant deviations in their activity across conditions. Specifically, we assessed significance (two-tailed, $p < 0.05$) by comparing TF activity scores to a null distribution of scores generated from randomized gene regulatory networks, in which target genes were shuffled independently for each TF while preserving the number of targets.

Building integrated signalling networks. For each cluster, we began by assuming that LR pairs and TFs formed a directed bipartite network where each ligand-receptor pair had the potential to influence every transcription factor. We then refined this network by inferring both the weights and mode of influence (direction) of each edge. To do so, we modelled the relationship between LR pairs, represented by their interaction potentials, and transcription factors, represented by their TF activity profiles.

For each cell type, we formulated this as n separate regression problems, one for each TF f, represented by its TF activity vector, $\boldsymbol{t}_f$. For each TF f, we modelled its relationship with all LR pairs signalling potential $\boldsymbol{P}$ relevant to that cell type as:

$$\boldsymbol{t}_f \approx R_f(\boldsymbol{P})$$

Where $R_f(\cdot)$ represents the regression function mapping ligand-receptor interaction potentials to the activity of TF f. Here, we used a Random Forest regressor.

For each regression problem, we further calculated each feature's permutation importance metric as:

$$imp(\boldsymbol{p}; R_f(\cdot))$$

Where $imp(\cdot)$ represents the importance function, which randomly shuffles the interaction potential vector $\boldsymbol{p}$ to calculate the impact of permuting a given interaction on model performance. The importance metric was used as the weight of the edge between LR pairs and transcription factors. Furthermore, as LR pairs can either activate or suppress TF activity, we estimated the mode of influence for each edge as the sign of the Spearman correlation between each predictor-target pair in the model.

Repeated across n problems this yields a weighted adjacency matrix $\boldsymbol{A}$ connecting all LR interactions and TFs in each cell type. Naturally, it is possible to extend this network to include target genes, as this information is already encoded in the tailored, cluster-specific gene regulatory networks.

Scoring differential ligand-receptor activity. Having obtained cluster-specific signed, weighted, and directed iSNs comprising ligands, receptors and TFs, we utilized these networks to score LR

interactions for each cell type. Since *Decipher* was designed to compare signalling at the cell type level, we first calculated the changes in intracellular TF activity for each cluster as the difference in median TF activity for each TF f across conditions, Δ_f.

Differential activity is then captured by the *Decipher* score S, which is represented by:

$$S = \sum_{f \in F} w_{i,f} \cdot \Delta_f$$

Where F represents all TFs relevant to a given cell type, and $w_{i,f}$ represents the weight between a ligand-receptor pair i and a TF f.

Taken altogether, with this approach, we achieve our two primary aims of building cluster-specific Integrated Signalling Networks and scoring interaction activity based on such a network.

CytoSig ligand activity. We estimated ligand activity with CytoSig[42]. For each cluster, we only retained genes with non-zero total counts across all cells. Gene counts were normalized by total cell count, scaled by a factor of 100,000, and log-transformed using $\log_2(x + 1)$. We defined a differential expression profile for each case cell by subtracting the mean expression of control cells from the log-transformed expression values. We applied CytoSig to the differential expression profiles of cells in each cluster, producing z-scores for the ligand activity in each cell.

Evaluation of ligand-activity prediction. We evaluated how well ligand-receptor predictions from each method aligned with the CytoSig model. Here, ligands were assumed to be active if they displayed an absolute median z-score > 2. Most methods reported scores for some ligands but not others, so we assumed that no prediction implied no activity, and assigned these ligands zero values. Except *Decipher*, all methods output scores for each sender-receiver cell type pair. Therefore, we reduced these scores to a single score per ligand and receiver cell type by selecting the LR interaction with the highest absolute score involving that ligand.

References

1.   Armingol, E., Officer, A., Harismendy, O. & Lewis, N. E. Deciphering cell–cell interactions and communication from gene expression. *Nat Rev Genet* (2020) doi:10.1038/s41576-020-00292-x.

2.   Baysoy, A., Bai, Z., Satija, R. & Fan, R. The technological landscape and applications of single-cell multi-omics. *Nature Reviews Molecular Cell Biology* vol. 24 695–713 Preprint at https://doi.org/10.1038/s41580-023-00615-w (2023).

3.   Ramilowski, J. A. *et al.* A draft network of ligand–receptor-mediated multicellular signalling in human. *Nat Commun* **6**, 7866 (2015).

4.   Jin, S. *et al.* Inference and analysis of cell-cell communication using CellChat. *Nat Commun* **12**, (2021).

5.   Vento-Tormo, R. *et al.* Single-cell reconstruction of the early maternal–fetal interface in humans. *Nature* **563**, 347–353 (2018).

6.   Garcia-Alonso, L. *et al.* Single-cell roadmap of human gonadal development. *Nature* **607**, 540–547 (2022).

7. Browaeys, R., Saelens, W. & Saeys, Y. NicheNet: modeling intercellular communication
by linking ligands to target genes. *Nat Methods* **17**, 159–162 (2020).

8. Armingol, E., Baghdassarian, H. M. & Lewis, N. E. The diversification of methods for
studying cell–cell interactions and communication. *Nature Reviews Genetics* Preprint at
https://doi.org/10.1038/s41576-023-00685-8 (2024).

9. Almet, A. A., Cang, Z., Jin, S. & Nie, Q. The landscape of cell–cell communication through
single-cell transcriptomics. *Current Opinion in Systems Biology* vol. 26 12–23 Preprint at
https://doi.org/10.1016/j.coisb.2021.03.007 (2021).

10. Stock, M. *et al.* Leveraging prior knowledge to infer gene regulatory networks from
single-cell   RNA-sequencing   data.   *Molecular   Systems   Biology*   Preprint   at
https://doi.org/10.1038/s44320-025-00088-3 (2025).

11. Dimitrov, D. *et al.* Comparison of methods and resources for cell-cell communication
inference from single-cell RNA-Seq data. *Nat Commun* **13**, (2022).

12. Wang, S., Karikomi, M., Maclean, A. L. & Nie, Q. Cell lineage and communication network
inference via optimization for single-cell transcriptomics. *Nucleic Acids Res* **47**, (2019).

13. Lu, H. *et al.* CommPath: An R package for inference and analysis of pathway-mediated
cell-cell communication chain from single-cell transcriptomics. *Comput Struct Biotechnol*
J **20**, 5978–5983 (2022).

14. Xin, Y. *et al.* LRLoop: a method to predict feedback loops in cell–cell communication.
Oxford Bioinformatics **38**, 4117–4126 (2022).

15. Wilk, A. J., Shalek, A. K., Holmes, S. & Blish, C. A. Comparative analysis of cell–cell
communication at single-cell resolution. *Nat Biotechnol* (2023) doi:10.1038/s41587-
023-01782-z.

16. Cheng, J., Zhang, J., Wu, Z. & Sun, X. Inferring microenvironmental regulation of gene
expression from single-cell RNA sequencing data using scMLnet with an application to
COVID-19. *Brief Bioinform* **22**, 988–1005 (2021).

17. Zhang, Y. *et al.* CellCall: Integrating paired ligand-receptor and transcription factor
activities for cell-cell communication. *Nucleic Acids Res* **49**, 8520–8534 (2021).

18. Baruzzo, G., Cesaro, G. & Camillo, B. Di. Identify, quantify and characterize cellular
communication   from   single-cell   RNA   sequencing   data   with   scSeqComm.
BIOINFORMATICS **38**, 1920–1929 (2022).

19. Ma, X. *et al.* SPaRTAN, a computational framework for linking cell-surface receptors to
transcriptional regulators. *Nucleic Acids Res* **49**, 9633–9647 (2021).

20. Hu, Y., Peng, T., Gao, L. & Tan, K. CytoTalk: De novo construction of signal transduction
networks using single-cell transcriptomic data. *Sci. Adv* **7**, (2021).

21. Jerby-Arnon, L. & Regev, A. DIALOGUE maps multicellular programs in tissue from
single-cell or spatial transcriptomics data. *Nat Biotechnol* **40**, 1467–1477 (2022).

22. Hou, R., Denisenko, E., Ong, H. T., Ramilowski, J. A. & Forrest, A. R. R. Predicting cell-to-
cell communication networks using NATMI. *Nat Commun* **11**, (2020).

23. Kamimoto, K. *et al.* Dissecting cell identity via network inference and in silico gene
perturbation. *Nature* **614**, 742–751 (2023).

24. Wang, Y. *et al.* Reprogramming of regulatory network using expression uncovers sex-
specific gene regulation in Drosophila. *Nat Commun* **9**, (2018).

25. Baran, Y. *et al.* MetaCell: Analysis of single-cell RNA-seq data using K-nn graph partitions.
Genome Biol **20**, (2019).

26. Fan, J. *et al.* Characterizing transcriptional heterogeneity through pathway and gene set
overdispersion analysis. *Nat Methods* **13**, 241–244 (2016).

27. Barkas, N., Petukhov, V., Kharchenko, P. & Biederstedt, E. pagoda2: Single Cell Analysis
and Differential Expression. Preprint at https://CRAN.R-project.org/package=pagoda2
(2022).

28. Read, J. F. *et al.* Lipopolysaccharide-induced interferon response networks at birth are
predictive of severe viral lower respiratory infections in the first year of life. *Front*
Immunol **13**, (2022).

29. Reyes, M. *et al.* An immune-cell signature of bacterial sepsis. *Nature Medicine* vol. 26
333–340 Preprint at https://doi.org/10.1038/s41591-020-0752-4 (2020).

30. Seok Lee, J. *et al. Immunophenotyping of COVID-19 and Influenza Highlights the Role of*
Type I Interferons in Development of Severe COVID-19. *Sci. Immunol* vol. 5
https://www.science.org (2020).

31. Arunachalam, P. S. *et al. Systems Biological Assessment of Immunity to Mild versus Severe*
COVID-19 Infection in Humans. https://www.science.org.

32. Lee, A. *et al.* BCG vaccination stimulates integrated organ immunity by feedback of the
adaptive immune response to imprint prolonged innate antiviral resistance. *Nat*
Immunol (2023) doi:10.1038/s41590-023-01700-0.

33. Arunachalam, P. S. *et al.* Systems vaccinology of the BNT162b2 mRNA vaccine in humans.
Nature **596**, 410–416 (2021).

34. Perez, R. K. *et al.* Single-cell RNA-seq reveals cell type-specific molecular and genetic
associations to lupus. *Science (1979)* **376**, (2022).

35. Fasolino, M. *et al.* Single-cell multi-omics analysis of human pancreatic islets reveals
novel cellular states in type 1 diabetes. *Nat Metab* **4**, 284–299 (2022).

36. Berg, M. *et al.* Evidence for altered immune-structural cell crosstalk in cystic fibrosis
revealed by single cell transcriptomics. *Journal of Cystic Fibrosis* (2025)
doi:10.1016/j.jcf.2025.01.016.

37. Lake, B. B. *et al.* An atlas of healthy and injured cell states and niches in the human
kidney. *Nature* **619**, 585–594 (2023).

38. Bassez, A. *et al.* A single-cell map of intratumoral changes during anti-PD1 treatment of
patients with breast cancer. *Nat Med* **27**, 820–832 (2021).

39. Jenkins, B. H. *et al.* Single cell and spatial analysis of immune-hot and immune-cold
tumours identifies fibroblast subtypes associated with distinct immunological niches
and positive immunotherapy response. *Mol Cancer* **24**, (2025).

40. Dimitrov, D. *et al.* LIANA+: an all-in-one cell-cell communication framework. *bioRxiv*
(2023) doi:10.1101/2023.08.19.553863.

41. Raredon, M. S. B. *et al.* Computation and visualization of cell–cell signaling topologies in
single-cell systems data using Connectome. *Sci Rep* **12**, (2022).

42. Jiang, P. *et al.* Systematic investigation of cytokine signaling activity at the tissue and
single-cell levels. *Nat Methods* **18**, 1181–1191 (2021).

43. Browaeys, R. Evaluation of NicheNet's ligand-target predictions.
https://github.com/saeyslab/nichenetr/blob/master/vignettes/model_evaluation.md.

44. Kang, H. M. *et al.* Multiplexed droplet single-cell RNA-sequencing using natural genetic
variation. *Nat Biotechnol* **36**, 89–94 (2018).

45. Huber, W. *et al.* Orchestrating high-throughput genomic analysis with Bioconductor. *Nat*
Methods **12**, 115–121 (2015).

46. Simmons, D. P. *et al.* SLAMF7 engagement superactivates macrophages in acute and
chronic inflammation , Accelerating Medicines Partnership (AMP) RA/SLE Network †,
Deepak A. *Sci. Immunol* **7**, 2846 (2022).

47. Hao, Y. *et al.* Integrated analysis of multimodal single-cell data. *Cell* **184**, 3573-3587.e29
(2021).

48. Büttner, M., Ostner, J., Müller, C. L., Theis, F. J. & Schubert, B. scCODA is a Bayesian model
for compositional single-cell data analysis. *Nat Commun* **12**, (2021).

49. *PubMed*. https://www.ncbi.nlm.nih.gov/pubmed/ (1946).

50. Petri, T., Altmann, S., Geistlinger, L., Zimmer, R. & Küffner, R. Addressing false discoveries
in network inference. *Bioinformatics* **31**, 2836–2843 (2015).

51. Li, C. *et al.* Mechanisms of innate and adaptive immunity to the Pfizer-BioNTech
BNT162b2 vaccine. *Nat Immunol* **23**, 543–555 (2022).

52. O'Connell, P. *et al.* SLAMF7 Is a Critical Negative Regulator of IFN-α–Mediated CXCL10
Production in Chronic HIV Infection. *The Journal of Immunology* **202**, 228–238 (2019).

53. Hiti, L. *et al.* The immunopathogenesis of a cytokine storm: The key mechanisms
underlying severe COVID-19. *Cytokine and Growth Factor Reviews* Preprint at
https://doi.org/10.1016/j.cytogfr.2024.12.003 (2025).

54. Junqueira, C. *et al.* FcγR-mediated SARS-CoV-2 infection of monocytes activates
inflammation. *Nature* **606**, 576–584 (2022).

55. Ianevski, A., Giri, A. K. & Aittokallio, T. Fully-automated and ultra-fast cell-type
identification using specific marker combinations from single-cell transcriptomic data.
Nat Commun **13**, (2022).

56.   Abdulla, S. *et al.* CZ CELLxGENE Discover: a single-cell data platform for scalable
680   exploration, analysis and modeling of aggregated data. *Nucleic Acids Res* **53**, D886–D900
681   (2025).

682   57.   Vlahos, L. *et al.* Systematic, Protein Activity-based Characterization of Single Cell State.
683   doi:10.1101/2021.05.20.445002.

684   58.   Wolf, F. A., Angerer, P. & Theis, F. J. SCANPY: Large-scale single-cell gene expression data
685   analysis. *Genome Biol* **19**, (2018).

Acknowledgements

688   We would like to acknowledge Dr. J Heng from Remotely Consulting for the services provided in
689   English-language editing of the manuscript, as well as for his valuable feedback on *Decipher*.
690