One size does not fit all: a novel approach for determining the Realised Viewshed Size for remote camera traps

Carswell, B.M.[1,2]*, Avgar, T.[3,4], Street, G.M.[5], Boyle, S.P.[1,6] and E. Vander Wal[1]

1. Department of Biology, Memorial University of Newfoundland and Labrador, Arctic Avenue, St. John's, NL, Canada, A1C 5S7
2. Department of Biological Sciences, University of Calgary, Calgary, AB, Canada, T2N 4V8
3. Department of Biology, University of British Columbia, Kelowna, BC, Canada, V1V 1V7
4. Wildlife Science Centre, Biodiversity Pathways Ltd., University of Alberta, Edmonton, AB, Canada, T6G 2E9
5. Department of Wildlife, Fisheries, and Aquaculture, Mississippi State University, Box 9690, Mississippi State, MS 3972, USA
6. School of Science and the Environment, Memorial University of Newfoundland and Labrador Grenfell, University Drive, Corner Brook, NL, Canada, A2H 5G4

* Corresponding author: bmcarswell@mun.ca

Data availability: Data and code used in this analysis will be made available at the link following publication: https://github.com/wildlifeevoeco/RealisedViewshedSize

Abstract

1. Camera traps (CTs) have become cemented as an important tool of wildlife research, yet,

their utility is now extending beyond academics, as CTs can contribute to more inclusive

place-based wildlife management. From advances in analytics and technology, CT-based

density estimates of wildlife is an emerging field of research. Most CT-based density

methods require an estimate of the size of the viewshed monitored by each CT, a

parameter that may be highly variable and difficult to quantify.

2. Here, we developed and tested a standardized field and analytical method allowing us to

predict the probability of photographic capture as it varies within CT viewshed. We

investigated how capture probability changes due to environmental influences, i.e.,

vegetation structure, ambient temperature, speed of subject, time of day, in addition to

internal factors from CTs themselves, i.e., sensitivity settings, number of photos taken,

and CT brand. We then summarize these spatial capture probability kernels into a

Realised Viewshed Size (RVS)—the capture-probability corrected size of a CTs viewshed

3. We found that RVS values are heavily influenced by location-specific environmental

factors, i.e., vegetation structure, technological delays associated with CTs themselves,

i.e., refractory period, and internal CT settings, i.e., sensitivity, number of photographs

taken. We also found that the RVS values computed using our methodology are

substantially smaller than reported values in the literature.

4. Imprecision surrounding CT viewshed areas can create propagating bias when

implementing CT-based density estimators. Our method can change how practitioners

consider photographs for use in CT density estimators thus increasing the reliability of

CT-based density estimation, and contribute to more accessible wildlife management

practices.

Key Words: Camera trap, motion sensor photography, viewshed density estimator, Realised

Viewshed Size, capture probability, REST, TIFC

Introduction

Context

In the last five decades, camera traps (CTs) have become an established method of studying and

monitoring wildlife populations (Fisher, 2023; Sollmann, 2018). CTs are an easy-to-operate,

accessible, relatively affordable, and low-impact method of monitoring wildlife. CTs have

become an integral part of wildlife management allowing researchers to answer location-based

questions of occupancy (e.g., Tobler et al., 2015; Neilson et al., 2018), movement (e.g., Tape and

Gustine, 2014), and behaviour (e.g., Caravaggi et al., 2017). Despite their common use,

ambiguities around CT performance leads to uncertainty and decreasing the quality of inference

made from some CT-based science. Among their limitations (e.g., Burton et al., 2015; Foster &

Harmsen, 2012; Kolowski et al., 2021; Urbanek et al., 2019), empirically estimating the

viewshed area a CT can monitor is an understudied, yet, critical facet when considering many

CT-based analyses.

CT-based density and abundance estimation methods, henceforth referred to as viewshed

density estimators (Moeller et al., 2023), are a novel group of statistical models incorporating

different processes to estimate wildlife density (e.g., Rowcliffe et al., 2008; Moeller et al., 2018;

Nakashima et al., 2020; Becker et al., 2022). Using CTs to estimate wildlife density promises to

lower financial and logistic barriers currently in place for other traditional density estimation

methods, e.g., aerial surveys. Some viewshed density estimators do not require the identification

of individual animals and thus may constrain less, e.g., no need to mark individuals or census a

population, than their traditional counterparts, such as physical mark-recapture methods or aerial

flight surveys. Each viewshed density estimator, however, comes with its own set of assumptions

and require novel parameters that we lack precision in estimating. For example, many viewshed

density estimators require a precise estimate of the sampling area that CT's monitor (Becker et

al., 2022; Moeller et al., 2023; Nakashima et al., 2020; Rowcliffe et al., 2008; Rowcliffe et al.

2011).

Previous research has developed methods to quantify CT viewshed area (Table 1).

Commonly used methods to estimate viewshed area include assuming a viewshed area or shape

(Campos-Candela et al., 2018; Lyet et al., 2024; Figure 1), determining spatial bounds of CT

viewshed (Cusack et al., 2015; Moeller et al., 2018; Figure 1A), and the Effective Detection

Distance (EDD; Hofmeester et al., 2017; Howe et al., 2017; Rowcliffe et al., 2011; Figure 1B)

that is based on distance sampling theory (Buckland, 2004). Each existing method to estimate

viewshed area has its own unique application and set of limiting assumptions (Table 1). EDD for

example, can account for obstructions in the viewshed and variation in study species size,

however, the assumptions of distance sampling, i.e., perfect detection at 0 m (e.g., Figure 1B),

are unrealistic as CTs cannot account for missed captures due to Passive Infrared (PIR) motion

sensors. Additionally, methods to estimate EDD either require additional field apparatuses, i.e.,

marked distance poles, or require substantial *post-hoc* data processing and analysis, which are

impractical in some geography and research programs (Haucke et al., 2022). Other methods,

such determining viewshed bounds (Cusack et al., 2015; Moeller et al., 2018; Figure 1) or

assuming manufacture determined areas (Campos-Candela et al., 2018; Lyet et al., 2024; Figure

1A) may be adequate for some CT studies, i.e., timelapse photography, yet, such methods

assume perfect capture probability within determined bounds—unrealistic for PIR-based CT

studies.

Focus

Imprecise estimates of the viewshed area are problematical because CTs, even when

large number being used together, monitor a relatively small area—often a minute percentage of

a study region. As a result, small errors in the determining the sampling area can propagate to

large biases in abundance estimates when extrapolating fine-scale density estimates (Moeller et

al., 2023). In addition, the theoretical area a CT monitors, as described by the CT's

manufacturer, does not align with the realised area. For example, Reconyx Hyperfire CT, a

popular brand in wildlife research, market a viewshed area extending up to 30 m from the CT

and 40° angle perpendicular to the CT's lens, an area approximating 315 m^2 (Reconyx, 2022;

Figure 1). In reality, environmental factors such as habitat structure, topography, and vegetation

(Moeller et al., 2023; Moll et al., 2020; Sultaire et al., 2023), will dictate a CT's viewshed area

for each unique location where CTs are placed (Apps and McNutt, 2018; Urbanek et al., 2019).

Researchers also need to account for the probability a photo will be taken given an

animal is located within the CT's viewshed, henceforth referred to as capture probability

(Findlay et al., 2020; Moeller et al., 2023). Capture probability is more complicated and depends

on numerous, interacting conditions caused by the environment in which CTs are placed, and CT

settings. Capture probability is influenced by the CT's Passive Infrared (PIR) motion detectors.

PIR motion detectors require recognition of movement within pre-programmed zones (Urbanek

et al., 2019), and a heat signature that contrasts ambient temperature for a photograph capture

(Reconyx, 2022; Welbourne et al., 2016). PIR performance influences capture probability. Yet,

few viewshed size estimation methods can adequately account for capture probability (Table 1).

Internal CT functioning and settings also dictate the viewshed area and how effectively

CTs take photos (Apps & McNutt, 2018; Becker et al., 2022; Lepard et al., 2019; Urbanek et al.,

2019). Even on rapid-fire modes, many CT user manuals report a 1–2 s refractory period from

the time the PIR motion detector is triggered until that photograph can be written to the memory

storage device (Del Bosco, 2021; Paula et al., 2014; Reconyx, 2022). Because a CT must reset

and register another trigger for subsequent photos to be taken, this phenomenon would be

sequential across the entire period an animal is in a CT's viewshed. Thus, the trigger-to-photo

delay can result in missed captures, i.e., when an animal is moving across the viewshed but no

photographs are taken (e.g., Figure 1C1, 1C2). To decrease false triggers, e.g., from vegetation

moving, researchers often lower CT sensitivity settings, influencing CT viewshed size. To aid in

identification of species from photos, it is common practice to set CTs to capture multiple rapid-

fire photos. Researchers often consider a photo series (i.e., all 3, 5, 10 photos) as a single event.

As it takes CTs more time to capture more photographs, however, increasing the number of

photos per trigger will reduce viewshed size. Effects of CT settings have not been empirically

incorporated into CT literature, yet, have compounding influences on how effective CTs are at

photographing wildlife.

Viewshed density estimators are often criticized for estimates that inconsistently align

with traditional density estimation methods (e.g., Palencia et al., 2021; Becker et al., 2022;

Fisher et al., 2023; Koetke et al., 2024). Although there may be many explanations for

inconsistent results from viewshed density estimators, a lack of accuracy in, or entirely absent

incorporation of viewshed area is undoubtedly one reason behind these discrepancies (Moeller et

al., 2023). Here, we tested a standardized field protocol to 1) account for spatial variation and

missed captures within the viewshed, 2) enumerate a kernel-based capture probability and how it

changes with space in front of CTs, and 3) summarize capture probability kernels into a *Realised*

Viewshed Size (RVS)—the capture probability corrected size of a CT's viewshed.

Methods

Overall approach

The workflow we have developed, and detail below, is based on the idea that different locations

in front of a CT will have differential capture probabilities due to factors such as position relative

to the PIR sensor, vegetation, and microterrain between the location and the sensor. In general,

we expect spatially variable capture probabilities to be highest near the PIR's focal point (along

the optical, at a distance of 10 meters), and decay to 0 at prereferral locations. We recognize that

the resulting spatial capture probability surface may be complex, with local valleys and peaks,

and vary substantially from one deployment to another. Our aim was thus to develop a workflow

that enables us to quantify this spatial capture probability surface, such that, we can then

integrate over the capture probability surface to obtain the Realised Viewshed Size (RVS)—the

denominator of the Random Encounter Staying Time (REST)/ Time in Front of Camera (TIFC)

density estimator.

To estimate RVS, we present the CT with PIR triggering events (a person jogging) and

analyse the resulting successful vs failed capture events, i.e., if a photograph was captured, as a

function of the spatial coordinates of an event, resulting in an empirically derived spatial capture

probability surface.

Field methods

To assess capture probability, we tested a standardized field method in two separate case studies.

We applied our methods to each CT to calculate capture probability, unique to each CT in our

study that in Case Study A) accounts for differences due to habitat and other location specific

influences and in Case Study B) incorporates variation resulting from internal CT settings.

Adapting methods from other researchers (Apps & McNutt, 2018; Del Bosco, 2021; Palencia et

al., 2021), we established six 20 m long transects, perpendicular to and centred at the CT's

optical axis at distances of 3, 5, 10, 12, 15, and 20 m from the lens (Figure 1D). These transects

extended past CTs' viewshed and all cameras were deployed at a height of ~1.5 m. We

performed a 'jog-test' where one researcher jogged at a speed of ~2 m/s along each transect, six

times, for a total of 36 jogs per CT. With a timer, another researcher initiated each jog-test by

triggering the CT using a hand motion to take a photo and recorded the time in seconds it took to

jog across the full 20 m. CTs captured PIR motion-triggered photos during jogs, just as they

would when triggered by a moving animals, however, in our tests, we know exactly the location

of the subject across space and time, and can hence confidently identify failed capture events to

be contrasted with successful capture events.

Analytical methods

To calculate capture probability, we determined the time elapsed (s) between the transect start

times and the time when each photograph was taken. Next, we calculated the speed of each jog

as the time taken to cross each transect divided by transect distance (m/s). We calculated spatial

locations where successful capture events or 'used locations' occurred, by multiplying the time

elapsed at each photograph by jog velocity to calculate the distance travelled along the transect,

rounding to nearest meter and second. For trials where more than one photo were taken per

trigger, we filtered photo series down to the first instance when a photograph of the jogger was

taken. We filtered photo series down to one event to represent how many practitioners consider

CT data. By using jog velocities, and transect start and end time, we calculated all possible

spatial locations where photographs could have occurred or 'available locations'. We then

excluded 'used' locations from the set of 'available locations, leaving us with a set of unused

locations, i.e., failed capture events. Combined, the 'used' and 'unused' locations were projected

onto a 1 m grid-system along each transect where each cell had a Bernoulli outcome, whether a

photographic capture occurred or not (Figure 1E).

Statistical models

We fit Bernoulli capture data using Generalized Additive Mixed Models (GAMMs) using the

mgcv package in Program R (Wood, 2017) for each case study, separately. We used GAMMs to

estimate a spatial capture probability surface by fitting a Gaussian Process spline (i.e., Kriging)

to the spatial coordinates of our used/unused data (Wood, 2017).

We used the resulting GAMM models, along with covariate data for each case study, and

the *predict_gamm()* function (Wood, 2023) to predict the probability of photographic capture

occurring across a 1x1 m spatial grid—a discrete approximation of the undelaying capture

probability surface (Figure 1F). We further applied these models to also predict capture

probability at any CTs where data were collected, e.g., vegetation cover, ambient temperature,

but that were not included in the trial tests.

Our primary goal was to determine the size of the theoretical area that a CT monitors

with 100% capture probability: the RVS. To estimate the RVS, we summed the GAMM-based

probability of photographic capture across each 1 m^2 grid cell with a rectangular area 20 m wide

and 40 m long (800 grid cells; see Figure 1G), resulting in an RVS estimator in units of m^2. Our

approach assumes that the capture probability outside of 20 x 40 m rectangle is negligibly small,

which is likely the case for most CT designs. Our approach further assumes equivalency between

predicted probabilities of photographic capture and the percent area monitored in each cell. This

assumption of equivalency is a fundamental assumption underlying other, popular analyses for

CT data such as occupancy modelling (MacKenzie et al., 2002). Capture probabilities represent

the equivalent area within each cell that a photograph would be captured with certainty. For

example, a capture probability of 0.33 in a 1 m^2 cell is equivalent to having 0.33 m^2 of area

where a capture will occur 100% of the time. In addition, we determined the uncertainty

associated with each RVS calculation.

We wanted to ensure sufficient predictive accuracy of our analysis for our Case Study A

field trial. Because a CT's monitoring area is unknown, we employed *k*-folds cross validation on

the probability of photographic capture for spatial locations in front of each CT (Geisser, 1975).

Using unique CT ID as a blocking variable, we withheld entire CTs to assess the predictive

accuracy of each 1x1-m cell across CT and thus the validity of our method at CTs where jog-

tests were not conducted (Fielding & Bell, 1997). We generated Receiver Operating

Characteristics (ROC) Area Under Curve (AUC) scores for each of these validations.

Case Study A

In Case Study A, we tested 45 CTs actively deployed as a part of a long-term monitoring

program located on Treaty 2 territory, the traditional lands of the Anishinabewaki, Očhéthi

Šakówiŋ, Cree, Oji-Cree, and the Homeland of the Métis peoples (Riding Mountain National

Park, Canada; RMNP; 50.658524, -99.970601). We conducted jog-tests on two different CT

brands deployed at our research sites: Reconyx Ultrafire (*n* = 9; Reconyx, Holmen, USA) and

Cuddeback H-1453 (*n* = 36; Cuddeback, Green Bay, USA). We did not vary any internal settings

between trials in Case Study A—all CTs were set to a high sensitivity setting and a single

photograph taken for each trigger. Instead, we measured external factors known to affect capture

probability. Factors included: vegetation cover in front of CTs (Moeller et al., 2023; Moll et al.,

2020), ambient temperature (°C) at time of survey (Urbanek et al., 2019), speed (m/s) of jog for

each transect (McIntyre et al., 2020), and CT model (Apps and McNutt, 2018). In addition, to

account for a refractory period after a photographic capture (Del Bosco, 2021; Paula et al., 2014;

Reconyx, 2022), we recorded whether CTs captured a photo in the previous two seconds—we

expected a negative effect of a recent capture on the probability of a current capture. To measure

vegetation cover, we conducted two surveys: (1) a shrub cover survey counting multi-stemmed

woody species 10 m in front of each CT by using the Daubenmire method on a 4 m radius plot

(Daubenmire, 1959); and, (2) horizontal cover via a cover pole, placed 10 m in front of CTs to

quantify vegetation height. For Case Study A, we created a single, saturated model including

covariates measured in the field, i.e., parallel and perpendicular distances from CT, percent

shrub, and vegetation cover in front of CT, ambient temperature (°C), velocity (m/s) of each jog,

CT model (categorical), and whether a photograph had occurred in the previous 2 seconds

(binary). Additionally, to allow different CTs to differ in their RVS above and beyond the effect

of covariates, we implemented unique CT ID as a random factor smoother (Wood, 2017, 2023).

Case Study B

For Case Study B, we conducted a series of jog-tests in an open, non-vegetated, flat field in a

local park located on traditional unceded territories of the Beothuk and Mi'kma'ki peoples (St.

John's, Canada; 47.595254, -52.745665). The trial used a controlled habitat to isolate the effect

of internal CT settings on capture probability. In total, we surveyed 27 Reconyx Hyperfire 2

(Reconyx, Holem, USA) CTs across 3 trials: two during daylight (~14:00 h; during partially

cloudy conditions) and one after sunset (~23:00 h). These trials were conducted to measure the

influences of the internal CT sensitivity settings (Heiniger & Gillespie, 2018), the number of

photos taken per motion trigger and refractory period following a photograph capture (Paula et

al., 2014). In addition, we wanted to measure the deterioration of CT performance during the

nighttime. We held CT settings constant across trials using specific combinations of settings (see

Table 2 for all combinations). Due to the lack of visual obstructions during the daytime trials in

the open field, we observed a higher-than-expected capture probability on the 20 m transect.

Thus, for the two daytime trials we jogged an additional two transects at 30 and 40 m parallel to

CTs to fully enumerate the decay of capture probability with distance. For CTs assessed in Case

Study B, in addition to the smoothed parallel and perpendicular locations (McIntyre et al., 2020),

we included categorical covariates for each of the variables of interest: CT sensitivity setting,

number of photos taken per motion trigger, time of day, and whether a capture had been taken in

the previous two seconds (Table 3).

To determine how strongly numeric covariates in Case Study A influence a CT's RVS,

we calculated a *post-hoc* effect size through prediction. We ran separate predictions for each

numeric covariate of interest—percent shrub cover, percent horizontal cover, velocity of jog, and

ambient temperature—and generated RVS values across the observed range of each covariate

while holding all other variables at their mean values. For example, horizontal cover ranged from

42–99%, thus we ran an RVS prediction for each unit (percent) value in that range. Next, we

calculated the mean of all unit-change differences in RVS predictions. The resulting values

represent the mean influence of a 1-unit change by a covariate on a CT's RVS. For Case Study

B, we ran similar predictions, but for each level in the categories of interest, i.e., sensitivity

setting and number of photos per trigger, while holding all other variables at constant values.

Results

Case Study A

We determined the predicted probability of a successful photographic capture occurring within a

CT viewshed at a 1 x 1 m resolution (Figure 2). For all CTs where we collected local site data,

we calculated unique capture probability distributions and scaled them to a RVS. For example,

Figure 2 represents a Reconyx Ultrafire CT within our Riding Mountain National Park field site,

with an average 62% shrub cover, 79% horizontal cover, and an ambient air temperature of

1.5°C during survey time. Assuming a subject moving at a velocity of 2 m/s in the CTs viewshed

area, we scaled these probabilities to a RVS of 15 m^2 and a standard error ranging from 8–27 m^2

(Figure 2). Ambient temperature at time of jog-test surveys ranged from -2–10°C, velocity of

each jog from 0.76–2.86 m/s, percent shrub cover from 0–176%, and percent horizontal cover

from 42–98%.

Covariates in the model showed varying levels of significance (Table 3). The effect of

spatial location in front of the CT, fitted as a Kriged surface using a Gaussian process spline, was

highly significant ($F = 42.655$, $p < 0.001$). In addition, the binary refractory period variable

showed a significant negative relationship with photographic capture ($\beta = -0.955$, $p < 0.001$).

Other covariates showed varying effects on the resulting RVS value (see Table 3). Percent unit

changes in shrub ($\bar{x} = 0.14$ m^2) and horizontal cover ($\bar{x} = 0.62$ m^2) had a relatively small

influence on RVS. Maximal effects between the largest and smallest RVS predictions, however,

were larger. The difference between the largest and smallest RVS was 24.48 m^2 for shrub cover

and 35.60 m^2 for horizontal cover (Figure 3). A unit change in temperature (°C) had a larger

influence on RVS, with a mean of 3.11 m^2, and a maximum of 37.32 m^2 difference between the

maximum and minimum RVS predictions (Figure 3). Finally, unit changes in velocity (m/s) of

each jog had the largest influence on RVS prediction, with a mean of 6.97 m^2 and a maximum of

13.95 m^2 between the largest and smallest predictions (Figure 3). The cross validated predictive

accuracy of the model, assessed at each 1x1 m cell between CTs, was good (AUC=0.76; Boyce

et al., 2002).

Case Study B

Our controlled, open field trials suggested that predetermined sensitivity settings have a large,

significant influence on the probability of photographic capture and thus RVS (Table 3). Our

model estimated a maximum difference of approximately 250 m^2 in RVS between the lowest and

highest sensitivity settings on the Reconyx Hyperfire 2 CTs (Figure 4). The number of photos

taken per trigger had a significant negative influence on RVS, where 3 and 5 photographs per

capture produced significantly lower RVS than 1 photo (but were not different from each other;

Table 3, Figure 4). Jog-tests conducted in the daytime produced significantly higher RVS ($\bar{x}$ =

151 m^2, SE =122–191 m^2) than the post-sunset jog-tests ($\bar{x}$ = 73 m^2, SE = 51–101 m^2, Table 3,

Figure 5).

Discussion

To determine CT viewshed size that is scaled by capture probability and specifically for use in

the Random Encounter Staying Time (REST) and Time in Front of Camera (TIFC) density

estimation models, we enumerated the Realised Viewshed Size (RVS). The RVS is the

theoretical area a CT monitors with 100% capture probability. Here, we showed how the RVS is

influenced by local environmental variables and internal CT settings. We determined the RVS

through a spatially predictive kernel-based photographic capture probability analysis, providing

new insight into how capture probability varies within a CT's viewshed. Our analysis suggested

that capture probabilities and the associated RVS are sensitive metrics and can vary substantially

depending on both environmental influences and user-defined settings. Understanding and

accurately estimating the RVS is crucial when implementing viewshed-based density estimators

and may also contribute how researchers interpret CT-based occupancy.

Utility for viewshed density estimators

The RVS provides multiple novel considerations for use in some viewshed density

estimators. In literature that uses Effective Detection Distance (EDD) with viewshed density

estimators (e.g., Becker et al., 2022; Fisher et al., 2023; Palencia et al., 2021), researchers

consider periods of time animals were never photographed, but likely present in the viewshed.

For example, it is common practice to assume an animal was in a viewshed for all the time in

between the first and last photographs of an event. Though this assumption is likely true, it can

undoubtedly lead to an overinflation in density estimates (e.g., as seen in Becker et al., 2022;

Fisher et al., 2023). Furthermore, it presupposes the animal did not leave then return to the

viewshed area. By considering the probability of missed captures our method to estimate RVS

removes the need to assume where animals are or are not in the viewshed in the absence of data.

Thus, we think the RVS would improve density estimation specifically when used with the

REST or TIFC models or derivations (Hogg, 2021; Nakashima et al., 2018; Warbington &

Boyce, 2020) that can consider single photographs and their temporal footprint.

Case Study A

RVS values generated from our Case Study A model are substantially smaller than other

published literature. For example, an average Reconyx Ultrafire CT in our study was estimated

to monitor an area of 16m^2 (ranging from 12–22m^2) with a perfect capture probability. Our

average Reconyx RVS, in the Case Study A field trial, was less than 10% of the total possible

area the CT advertises (Reconyx, 2022) and still smaller than other published monitoring areas

(Becker et al., 2022; Garland et al., 2020). Thus, if implementing the previous detection areas,

i.e., 16 m^2 vs 315 m^2, on viewshed density estimators, density estimates would differ by an order

of magnitude. Although CT capture probability area cannot be unilaterally applied across

different studies in varying geography and with different external influences, our work highlights

the importance of conducting a standardized test on all CT of a study when attempting to

estimate monitoring areas.

344   In Case Study A, our goal was to develop an accurate metric to estimate the physical

space CTs monitor, specifically for use with viewshed density estimators. Though not

statistically significant, our environmental covariates, i.e., shrub cover, horizontal cover,

temperature, and jog velocity, still contributed considerable variability in RVS. For example,

when holding other covariates at mean values, average per-unit changes in vegetation structure,

shrub cover and horizontal cover can influence RVS by ~0.2 m^2. Although changes are small

over single percentage changes, if we consider CTs with 50% differences in either shrub or

horizontal cover, RVS could be influenced by over 10 m^2. Vegetation influences are likely even

greater in affecting RVS, considering shrub and horizontal cover are additive, resulting in a

compounded effect on RVS.

354   We detected a relatively small influence of unit changes of temperature on RVS, with a

mean of ~2 m^2 per °C. The small influence of temperature is intuitive given the short duration

when we conducted jog-tests. For example, we conducted our Case Study A jog-tests on the

edges of winter (April and November 2023). The time of year allowed us to safely access remote

field sites, in addition to providing conditions consistent with when traditional density estimation

surveys take place, e.g., aerial flight surveys in late winter, for future applications of our work.

As a result, many of our covariates show little range. Ambient air temperatures at time of survey

only ranged from -2–10°C, and total shrub was measured after leaf senescence in the fall,

limiting observed variability. Although we would not expect CTs to decrease performance until -

20°C or below (Reconyx, 2022), it is worth noting that other research has observed CTs

performing best around 0°C, where higher false-negatives occur in positive temperature ranges

(Jacobs & Ausband, 2018), and negative temperature ranges and associated weather can

contribute to decreased performance (Maile et al., 2023). Conducting jog-tests during other

seasons and within a greater range of forest types and habitat will likely contribute to detecting

statistical differences in environmental covariates and help determine if a CT's RVS varies more

substantially across space and time (e.g., as in McIntyre et al., 2020; Moeller et al., 2023; Moll et

al., 2020; Sultaire et al., 2023; Urbanek et al., 2019).

Though our jog-tests were conducted at relatively consistent velocities, we detected a

large difference in RVS between unit (m/s) changes in jog velocity, with a mean of ~35 m^2.

Further, our predictions show that slower jog speeds lead to higher RVSs. Our jog velocity

results stand in contrast to previous findings (e.g., Del Bosco, 2021) who found that faster jog

velocities generally lead to higher capture rates at CTs. The velocity discrepancy may be

explained by the habitat in which jog-tests were conducted. Specifically, our tests took place in

primary and secondary conifer and mixed forests where as Del Bosco's (2021) work occurred in

more open, sagebrush-mountain habitat. We suggest researchers consider both habitat

composition and effective movement speed of the species of interest when implementing the jog-

test method.

Cross-validation of the probability of photographic capture occurring in each 1x1-m cell

assessed during jog-tests highlighted that our RVS modelling framework had useful predictive

accuracy (ROC score of 0.76). In addition, environmental covariates explained substantial

variation in our model, as determined through average unit-changes. The variation explained by

covariates, along with our cross-validation results, suggest that, in our geography, we can predict

RVS well at CTs where we did not conduct jog-tests, but did collect vegetation data.

Case Study B

Overall, sensitivity settings on Reconyx Hyperfire II CTs greatly influenced the predicted RVS.

Differences between lower sensitivity settings were smaller but bme more pronounced as the

sensitivity settings became higher. These results show how drastically a CT monitoring zone can

change with sensitivity settings, e.g., from ~75m^2 to ~350m^2 in open conditions, reinforcing the

importance of consistency and assessing CTs in each location they are placed. Our results

highlight the balance researchers need to consider when altering sensitivity settings to decrease

false negative photographic captures, while risking tremendous loss of area in photographable

space.

Predicted RVS for trials set to take 3 or 5 photos per trigger were significantly smaller

than trials with 1 photo per trigger, but not different from each other. As we take more

photographs per event, the CT will be less able to capture future photographs. Failure to capture

future events is because, even on rapid fire modes, it takes longer for to capture and write 3 or 5

photographs than a single photograph. When considering refractory period, setting CTs to take

more photos will greatly reduce the available time a CT has to take a photo and thus, the RVS.

Though additional photos per trigger can be very useful in the identification of species,

additional photos have an overall negative influence on a CTs viewshed area. Intuitively, trials

conducted in the daytime had significantly higher RVSs compared to post-sunset trials. A lower

nighttime RVS is likely because the visible range of the CT will be reduced during nighttime, in

addition to a reduced contrast from the subject to the background. Nighttime RVSs will be

particularly important on CT studies for species that are predominately nocturnal, as viewshed

area may be lower than anticipated.

Camera refractory period

Our two case studies observed opposite effects of the refractory period variable. In Case

Study A, we observed a significant negative relationship between capture probability within a

1x1-m cell and whether a photo was captured in the previous two seconds. The refractory period

result met our null expectations that, due to delay, our CTs deployed in the field were less able to

capture photos immediately after a previous photo had been taken. Our Case Study B model,

however, exhibited the opposite trend and the refractory period variable was significantly

positively correlated with capture probability, i.e., photos were more likely to be taken

immediately following a previous capture. These contrasting results were likely due to the way

we structured the Case Study B trials, where many trials took more than one photo per trigger.

For example, in trials where CTs took 3 or 5 images per trigger, by artifact of CT shutter speed,

the time it takes to capture 3 or 5 images is longer than 1 image. Thus, the refractory period of a

CT would be longer if the CT is set to capture more images per trigger, e.g., potentially 3–6

seconds after the first photo in the series is captured.

The elongated refractory period caused by trials with more than 1 photograph taken per

trigger is also likely responsible for the divergence in capture probability observed in our

graphical representation of RVS in Case Study B (Figure 5). During trials where CTs were set to

take multiple photos, if captures were registered at the start and end of transects, where a

refractory period occurred near the midpoint of the trial, the pattern we observe of decreased

capture probability directly perpendicular to CTs past ~14m could be explained (Figure 5). The

gap in photograph captures would not be observed at closer distances to CTs because of CT lens

angle—there is physically less space within a CT's viewshed, explaining the gap in detection

probability for trials with multiple photos per activation (Figure 5).

Limitations and future directions

The functioning and performance of CTs remains an understudied facet of the field that

certainly influences CT analyses and thus interpretation of CT-based research. In our work, how

PIR sensors perform across temperature and seasonal gradients is particularly important. PIR

detectors in CTs function by sensing a difference in temperature of a subject from ambient

temperature, in addition to movement, to capture a photograph (Reconyx, 2022; Welbourne et

al., 2016). The interacting effects of ambient temperature and seasonality will influence the

amount of heat wildlife subjects will emit. For example, in winter, ungulates have thick winter

coats that allow them to retain heat and survive harsh conditions and as such, less heat may be

escaping the coat (Parker and Robbins 2018). A lack of heat emission has been previously

observed in thermal imaging studies, where thermal CTs have a difficult time picking up certain

species during certain temperature ranges (Kuhn & Meyer, 2009; Zabel et al., 2023). In addition,

the effects of snow cover in northern geography and how it may contribute to capture of animals,

through heat recognition or increased exposure merits further research. As a result, capture

probability may be even lower during mid-winter months for some wildlife species.

CTs are influenced, to some degree, by the size of the subject they are capturing (DeWitt

& Cocksedge, 2023). Other viewshed size estimators (e.g., Effective Detection Distance; EDD)

have found substantial variation in the EDDs between different sized animals (Hofmeester et al.,

2017; Becker et al., 2022). Because EDD measures the minimum distance where at least one

photograph of a species is captured, we think size may be more influential than the RVS—where

we measure the probability a photograph will be captured given a subject is in a discrete space.

For example, Urbanek et al. (2019) observed that raw number of photographs at CTs were

similar for species groups that were generally the same size. The pattern in Urbanek et al. (2019)

data suggests a potential trigger threshold where above certain body sizes, the number of

photographs taken (and thus RVS) may increase. Thus, we think that our approach will work

well for some species, particularly ungulates, based on height, however, we would not

recommend our methods when applied to species with large size discrepancies, particularly

smaller, to humans.

Our jog-test trials used linear transects at an angle perpendicular to CTs optical axis.

Such linear transects may influence RVS values. In realistic settings, wildlife may move

simultaneously along both perpendicular and parallel angles relative to a CT's optical axis. In

addition, a subject's body orientation, and thus size, may change as the subject moves throughout

a CT's viewshed. Effects on capture probability and RVS would be non-linear and dependent on

each specific capture event being photographed. Despite our linear transects, we investigated the

probability of photographic capture given a subject was in a delineated location and fit those

probabilities as a kriged surface using a Gaussian process spline. Thus, because of our statistical

approach we think the influence of other angles of approach within a CT viewshed on the RVS

would be negligible.

Our GAMM model was developed to incorporate important predictor variables

specifically at our field site in Riding Mountain National Park (MB, Canada). We hypothesized

the largest influencing factor to CTs would be vegetation, specifically shrub cover. Although

vegetation cover in our study had a relatively lower influence on RVS (Table 3, Figure 3), the

importance of different predictor variables, will likely depend on the geography and habitat

conditions of the study. For example, topography (Sultaire et al., 2023) and weather (Madsen et

al., 2020) have been found to influence CT capture probabilities in some geographies. Thus, if

implementing our method, researchers should consider all potential important predictor variables

that may influence capture probability at their study sites.

Conclusion

We use a standardized, *a priori* field and analytical protocol to predict the variable probability of

photographic capture at CTs while incorporating internal and environmental influences on CT

performance. We use our predictions of capture probability to estimate the Realised Viewshed

S1ize (RVS), a novel estimator that is the scaled area in front of CTs that represents a 100%

capture probability. Our results highlight how variable CT performance can be and provide a

framework for researchers and other CT users to account for variable viewshed areas and capture

probabilities for some taxa of wildlife. RVS may contribute to increasing the reliability and

precision of CT-based density estimators and thus forward the growing branch of CT research.

Literature cited

Apps, P., & McNutt, J. W. (2018). Are camera traps fit for purpose? A rigorous, reproducible and realistic test of camera trap performance. *African Journal of Ecology*, *56*(4), 710–720. https://doi.org/10.1111/aje.12573

Becker, M., Huggard, D. J., Dickie, M., Warbington, C., Schieck, J., Herdman, E., Serrouya, R., & Boutin, S. (2022a). Applying and testing a novel method to estimate animal density from motion-triggered cameras. *Ecosphere*, *13*(4). https://doi.org/10.1002/ecs2.4005

Boyce, M. S., Vernier, P. R., Nielsen, S. E., & Schmiegelow, F. K. A. (2002). Evaluating resource selection functions. *Ecological Modelling*, *157*, 281–300. https://doi.org/10.1016/S0304-3800(02)00200-4

Buckland, S. T. (2004). *Advanced distance sampling: Estimating abundance of biological populations* (D. R. Anderson, K. P. Burnham, J. L. Laake, D. L. Borchers, & L. Thomas, Eds.). Oxford University Press.

Burton, A. C., Neilson, E., Moreira, D., Ladle, A., Steenweg, R., Fisher, J. T., Bayne, E., & Boutin, S. (2015). Wildlife camera trapping: A review and recommendations for linking surveys to ecological processes. *Journal of Applied Ecology*, *52*(3), 675–685. https://doi.org/10.1111/1365-2664.12432

Campos-Candela, A., Palmer, M., Balle, S., & Alós, J. (2018). A camera-based method for estimating absolute density in animals displaying home range behaviour. *Journal of Animal Ecology*, *87*(3), 825–837. https://doi.org/10.1111/1365-2656.12787

Caravaggi, A., Banks, P. B., Burton, A. C., Finlay, C. M. V., Haswell, P. M., Hayward, M. W., Rowcliffe, M. J., & Wood, M. D. (2017). A review of camera trapping for conservation behaviour research. *Remote Sensing in Ecology and Conservation*, *3*(3), 109–122. https://doi.org/10.1002/rse2.48

Cusack, J. J., Swanson, A., Coulson, T., Packer, C., Carbone, C., Dickman, A. J., Kosmala, M.,

Lintott, C., & Rowcliffe, J. M. (2015). Applying a random encounter model to estimate

lion density from camera traps in Serengeti National Park, Tanzania: Density Estimation

of Serengeti Lions. *The Journal of Wildlife Management*, *79*(6), 1014–1021.

https://doi.org/10.1002/jwmg.902

Daubenmire, R. (1959). A canopy-coverage method of vegetational analysis. *Northwest Science*,

33, 43–64.

Del Bosco, T. (2021). *An eulerian perspective on spring migration in mule deer* [MSc. thesis].

Utah State University.

DeWitt, P. D., & Cocksedge, A. G. (2023). A simple framework for maximizing camera trap

detections using experimental trials. *Environmental Monitoring and Assessment*, *195*(11),

1381. https://doi.org/10.1007/s10661-023-11945-9

Fielding, A. H., & Bell, J. F. (1997). A review of methods for the assessment of prediction errors

in conservation presence/absence models. *Environmental Conservation*, *24*(1), 38–49.

https://doi.org/10.1017/S0376892997000088

Findlay, M. A., Briers, R. A., & White, P. J. C. (2020). Component processes of detection

probability in camera-trap studies: Understanding the occurrence of false-negatives.

Mammal Research, *65*(2), 167–180. https://doi.org/10.1007/s13364-020-00478-y

Fisher, J. T. (2023). Camera trapping in ecology: A new section for wildlife research. *Ecology*

and Evolution, *13*(3), e9925. https://doi.org/10.1002/ece3.9925

Fisher, J. T., Dickie, M., Burgar, J. M., Burton, A. C., & Serrouya, R. (2023). Density estimates

of unmarked mammals: Comparing two models and assumptions across multiple species

and years. *Canadian Journal of Zoology*, cjz-2023-0055. https://doi.org/10.1139/cjz-

2023-0055

Foster, R. J., & Harmsen, B. J. (2012). A critique of density estimation from camera-trap data.

The Journal of Wildlife Management, *76*(2), 224–236. https://doi.org/10.1002/jwmg.275

Garland, L., Neilson, E., Avgar, T., Bayne, E., & Boutin, S. (2020). Random Encounter and

Staying Time Model Testing with Human Volunteers. *The Journal of Wildlife*

Management, *84*(6), 1179–1184. https://doi.org/10.1002/jwmg.21879

Haucke, T., Kühl, H. S., Hoyer, J., & Steinhage, V. (2022). Overcoming the distance estimation

bottleneck in estimating animal abundance with camera traps. *Ecological Informatics*, *68*,

101536. https://doi.org/10.1016/j.ecoinf.2021.101536

Heiniger, J., & Gillespie, G. (2018). High variation in camera trap-model sensitivity for

surveying mammal species in northern Australia. *Wildlife Research*, *45*(7), 578.

https://doi.org/10.1071/WR18078

Hofmeester, T. R., Rowcliffe, J. M., & Jansen, P. A. (2017). A simple method for estimating the

effective detection distance of camera traps. *Remote Sensing in Ecology and*

Conservation, *3*(2), 81–89. https://doi.org/10.1002/rse2.25

Hogg, J. (2021). *The precision and accuracy of the Random Encounter Staying Time model's*

estimation of species population density [MSc. thesis]. Memorial University of

Newfoundland and Labrador.

Howe, E. J., Buckland, S. T., Després-Einspenner, M., & Kühl, H. S. (2017). Distance sampling

with camera traps. *Methods in Ecology and Evolution*, *8*(11), 1558–1565.

https://doi.org/10.1111/2041-210X.12790

Jacobs, C. E., & Ausband, D. E. (2018). An evaluation of camera trap performance – What are

we missing and does deployment height matter? *Remote Sensing in Ecology and*

Conservation, *4*(4), 352–360. https://doi.org/10.1002/rse2.81

Kolowski, J. M., Oley, J., & McShea, W. J. (2021). High-density camera trap grid reveals lack of

consistency in detection and capture rates across space and time. *Ecosphere*, *12*(2).

https://doi.org/10.1002/ecs2.3350

Kuhn, R., & Meyer, W. (2009). Infrared thermography of the body surface in the Eurasian otter

Lutra lutra and the giant otter Pteronura brasiliensis. *Aquatic Biology*, *6*, 143–152.

https://doi.org/10.3354/ab00176

Lepard, C. C., Moll, R. J., Cepek, J. D., Lorch, P. D., Dennis, P. M., Robison, T., &

Montgomery, R. A. (2019). The influence of the delay-period setting on camera-trap data

storage, wildlife detections and occupancy models. *Wildlife Research*, *46*(1), 37.

https://doi.org/10.1071/WR17181

Lyet, A., Waller, S., Chambert, T., Acevedo, P., Howe, E., Kühl, H. S., Naidoo, R., O'Brien, T.,

Palencia, P., Soutyrina, S. V., Vicente, J., Wearn, O. R., & Gray, T. N. E. (2024).

Estimating animal density using the Space-to-Event model and bootstrap resampling with

motion-triggered camera-trap data. *Remote Sensing in Ecology and Conservation*, *10*(2),

141–155. https://doi.org/10.1002/rse2.361

MacKenzie, D. I., Nichols, J. D., Lachman, G. B., Droege, S., Andrew Royle, J., & Langtimm,

C. A. (2002). Estimating site occupancy rates when detection probabilities are less than

one. *Ecology*, *83*(8), 2248–2255. https://doi.org/10.1890/0012-

9658(2002)083[2248:ESORWD]2.0.CO;2

Madsen, A. E., Corral, L., & Fontaine, J. J. (2020). Weather and exposure period affect coyote

detection at camera traps. *Wildlife Society Bulletin*, *44*(2), 342–350.

https://doi.org/10.1002/wsb.1080

Maile, R. E., Duggan, M. T., & Mousseau, T. A. (2023). The successes and pitfalls: Deep-

learning effectiveness in a Chernobyl field camera trap application. *Ecology and*

Evolution, *13*(9), e10454. https://doi.org/10.1002/ece3.10454

McIntyre, T., Majelantle, T. L., Slip, D. J., & Harcourt, R. G. (2020). Quantifying imperfect

camera-trap detection probabilities: Implications for density modelling. *Wildlife*

Research, *47*(2), 177. https://doi.org/10.1071/WR19040

Moeller, A. K., Lukacs, P. M., & Horne, J. S. (2018). Three novel methods to estimate

abundance of unmarked animals using remote cameras. *Ecosphere*, *9*(8), e02331.

https://doi.org/10.1002/ecs2.2331

Moeller, A. K., Waller, S. J., DeCesare, N. J., Chitwood, M. C., & Lukacs, P. M. (2023). Best

practices to account for capture probability and viewable area in camera-based abundance

estimation. *Remote Sensing in Ecology and Conservation*, *9*(1), 152–164.

https://doi.org/10.1002/rse2.300

Moll, R. J., Ortiz-Calo, W., Cepek, J. D., Lorch, P. D., Dennis, P. M., Robison, T., &

Montgomery, R. A. (2020). The effect of camera-trap viewshed obstruction on wildlife

detection: Implications for inference. *Wildlife Research*, *47*(2), 158.

https://doi.org/10.1071/WR19004

Nakashima, Y., Fukasawa, K., & Samejima, H. (2018). Estimating animal density without

individual recognition using information derivable exclusively from camera traps.

Journal of Applied Ecology, *55*(2), 735–744. https://doi.org/10.1111/1365-2664.13059

Nakashima, Y., Hongo, S., & Akomo-Okoue, E. F. (2020). Landscape-scale estimation of forest

ungulate density and biomass using camera traps: Applying the REST model. *Biological*

Conservation, *241*, 108381. https://doi.org/10.1016/j.biocon.2019.108381

Neilson, E. W., Avgar, T., Burton, A. C., Broadley, K., & Boutin, S. (2018). Animal movement

affects interpretation of occupancy models from camera-trap surveys of unmarked

animals. *Ecosphere*, *9*(1). https://doi.org/10.1002/ecs2.2092

Palencia, P., Rowcliffe, J. M., Vicente, J., & Acevedo, P. (2021). Assessing the camera trap

methodologies used to estimate density of unmarked populations. *Journal of Applied*

Ecology, *58*(8), 1583–1592. https://doi.org/10.1111/1365-2664.13913

Parker, K. L., & Robbins, C. T. (2018). Thermoregulation in ungulates. In *Bioenergetics of wild*

herbivores (pp. 161–182). CRC press.

Paula, J. J. S., Bispo, R. M. B., Leite, A. H., Pereira, P. G. S., Costa, H. M. R. G., Fonseca, C. M.

M. S., Mascarenhas, M. R. T., & Bernardino, J. L. V. (2014). Camera-trapping as a

methodology to assess the persistence of wildlife carcasses resulting from collisions with

human-made structures. *Wildlife Research*, *41*(8), 717. https://doi.org/10.1071/WR14063

Reconyx. (2022). *Reconyx Hyperfire 2 high performance camera instruction manual*.

https://www.reconyx.com/img/file/HyperFire_2_User_Guide_2018_07_05_v5.pdf

Rowcliffe, J. M., Carbone, C., Jansen, P. A., Kays, R., & Kranstauber, B. (2011). Quantifying

the sensitivity of camera traps: An adapted distance sampling approach. *Methods in*

Ecology and Evolution, *2*(5), 464–476. https://doi.org/10.1111/j.2041-

210X.2011.00094.x

Rowcliffe, J. M., Field, J., Turvey, S. T., & Carbone, C. (2008). Estimating animal density using

camera traps without the need for individual recognition. *Journal of Applied Ecology*,

45(4), 1228–1236. https://doi.org/10.1111/j.1365-2664.2008.01473.x

Sollmann, R. (2018). A gentle introduction to camera-trap data analysis. *African Journal of*

Ecology, *56*(4), 740–749. https://doi.org/10.1111/aje.12557

Sultaire, S. M., Millspaugh, J. J., Jackson, P. J., & Montgomery, R. A. (2023). The influence of

fine-scale topography on detection of a mammal assemblage at camera traps in a

mountainous landscape. *Wildlife Biology*, *2023*(2). https://doi.org/10.1002/wlb3.01026

Tape, K. D., & Gustine, D. D. (2014). Capturing Migration Phenology of Terrestrial Wildlife

Using Camera Traps. *BioScience*, *64*(2), 117–124. https://doi.org/10.1093/biosci/bit018

Tobler, M. W., Zúñiga Hartley, A., Carrillo-Percastegui, S. E., & Powell, G. V. N. (2015).

Spatiotemporal hierarchical modelling of species richness and occupancy using camera

trap data. *Journal of Applied Ecology*, *52*(2), 413–421. https://doi.org/10.1111/1365-

2664.12399

Urbanek, R. E., Ferreira, H. J., Olfenbuttel, C., Dukes, C. G., & Albers, G. (2019). See what

you've been missing: An assessment of Reconyx® PC900 Hyperfire cameras. *Wildlife*

Society Bulletin, *43*(4), 630–638. https://doi.org/10.1002/wsb.1015

Warbington, C. H., & Boyce, M. S. (2020). Population density of sitatunga in riverine wetland

habitats. *Global Ecology and Conservation*, *24*, e01212.

https://doi.org/10.1016/j.gecco.2020.e01212

Welbourne, D. J., Claridge, A. W., Paull, D. J., & Lambert, A. (2016). How do passive infrared

triggered camera traps operate and why does it matter? Breaking down common

644   misconceptions. *Remote Sensing in Ecology and Conservation*, *2*(2), 77–83.

645   https://doi.org/10.1002/rse2.20

646   Wood, S. (2017). *Generalized Additive Mixed Models: An introduction with R*. CRC press.

647   Wood, S. (2023). mgcv: Mixed GAM computation vehicle with automatic smoothness

648   estimation. *R Package: Version 1.9-0*. https://cran.r-

649   project.org/web/packages/mgcv/index.html

650   Zabel, F., Findlay, M. A., & White, P. J. C. (2023). Assessment of the accuracy of counting large

651   ungulate species (red deer *Cervus elaphus*) with UAV-mounted thermal infrared cameras

652   during night flights. *Wildlife Biology*, *2023*(3), e01071.

653   https://doi.org/10.1002/wlb3.01071

655 **Table 1.** Commonly used methods to estimate viewshed area in camera trap literature, including which viewshed density model (i.e.,
656 Random Encounter Model [REM], Random Encounter Staying Time [REST], Time in Front of Camera [TIFC], Distance Sampling,
657 Space-to-Event [STE], Time-to-Event [TTE]), and camera trap mode was used (i.e., Passive Infrared [PIR] motion sensor or timelapse
658 photography), and various assumptions made about the viewshed area.

Method to estimate viewshed area	Viewshed Density estimator used	Citation	Camera trap mode	Additional field surveys	Considers physical obstructions	Considers species size variation	Considers spatial variation	Accounts for missed captures	Determines viewshed shape
Distance Sampling, *post-hoc* angle analysis	Distance Sampling	Howe et al. 2017	PIR motion sensor			X	X*		
	REST	Nakashima et al. 2018				X	X*		
	REM	Palencia et al. 2022				X	X*		
	STE	Lyet et al. 2024				X	X*		
Distance Sampling, in-field distance markers	TIFC	Becker et al. 2022	PIR motion sensor	X	X	X	X*		
	REM	Hofmeester et al. 2017		X	X	X	X*		
Viewshed bounds estimation	REM	Cusack et al. 2015	PIR motion sensor	X					X
	TTE	Moeller et al. 2018		X					X
	STE	Moeller et al. 2018	Timelapse	X	X				X
Assumed viewshed area	Association Modelling	Campos-Candela et al. 2016	PIR motion sensor						
	STE	Lyet et al. 2024							

Realized Viewshed Size	—	—	PIR motion sensor	X	X		X	X	X

659   * Papers only considers spatial variation along a single linear transect, not across the entire viewshed

660 **Table 2.** The combinations of camera sensitivity settings, number of photos taken for each
661 passive infrared motion trigger, and time of day we implemented on to Reconyx Hyperfire 2 ($n =$
662 26) camera traps during Case Study B, in a controlled, open field setting, in St. John's Canada.

Trial type	Number of cameras	Sensitivity setting	Number of photos per trigger	Time of day
Sensitivity	3	Low	1	Day
	3	Medium	1	Day
	3	Very high	1	Day
Number of photos	3	High	1	Day
	3	High	3	Day
	3	High	5	Day
Night	9	High	1	Night

665   **Table 3.** Binary Generalized Additive Mixed Models (GAMMs) used in determining the Effective Capture Areas of (a) camera traps
666   ($n = 46$) in Riding Mountain National Park, Canada and (b) camera traps ($n = 27$) in a non-vegetated local park near St. John's,
667   Canada. Showing different predictor variables used in each model, with their respective explanations, coefficient values, and
668   probability values. Both models contain the parallel and perpendicular locations in front of each camera trap with splines
669   implemented, in addition to unique camera identification implemented as a random intercept.

Riding Mountain National Park field data (Case Study A) model:				Controlled setting data (Case Study B) model:			
Covariate	Explanation	Coefficient (χ^2 for smoothed terms)	p-value	Covariate	Explanation	Coefficient (χ^2 for smoothed terms)	p-value
s(parallel distance, perpendicular distance)	Gaussian process spline of the parallel (locations in front) and perpendicular (locations to the side) of camera traps	**829.978**	**<0.001**	**s(parallel distance, perpendicular distance)**	Gaussian process spline on parallel (in front) and perpendicular locations (to the side) of camera traps	**1009.3**	**<0.001**
te(shrub cover, horizontal cover)	Tensor product spline of percent shrub cover (determined by Daubenmire plots) and horizontal cover (determined from cover pole)	1.435	0.707	Low camera sensitivity	Categorical variable for the sensitivity setting chosen on each camera trap for a specific trial	Set as intercept	
				Medium camera sensitivity		**1.076**	**<0.001**
				High camera sensitivity		**1.837**	**<0.001**
				Very high camera sensitivity		**3.479**	**<0.001**
Photo taken in previous 2 seconds	Binary variable of whether the camera took a photo in the previous two seconds	**-1.064**	**<0.001**	1 photo per trigger	Categorical variable for the number of photos taken per trigger setting chosen on each camera trap for a specific trial	Set as intercept	
				3 photos per trigger		**-1.266**	**<0.001**
				5 photos per trigger		**-1.186**	**<0.001**
Jog velocity		0.211	0.126	Nighttime trial		Set as intercept	

	Velocity of each transect jog during the field surveys			Day-time trial	Whether or not trials occurred during daylight or night hours	**1.072**	**<0.001**
Ambient temperature	Ambient temperature (°C) measured from camera traps at time of survey	0.082	0.428	**Photo taken in previous 2 seconds**	Binary variable of whether the camera took a photo in the previous two seconds	**0.173**	**0.047**
Camera model	Categorical variable for the brand of camera trap (Reconyx or cuddeback) used in the field trials	-0.370	0.527				
s(unique camera ID)	Random factor smooth implemented on each unique camera trap	**358.793**	**<0.001**	**s(unique camera ID)**	Random factor smooth implemented on each unique camera trap	**24.7**	**<0.001**

Figure 1: Various depictions of capture probability within camera trap (CT) viewshed; an assumed viewshed area based on manufacturer settings (gray cone; e.g., Campos-Candela et al., 2018; Lyet et al., 2024). **A.** Viewshed bound estimation based on physical obstructions—which assumes perfect capture probability within bounds (e.g., Cusack et al., 2015). **B.** Effective Detection Distance, based on in-field measuring poles, which considers the decay of capture probability with linear distance from the CT's focal axis (e.g., Becker et al., 2022; Hofmeester et al., 2017; Rowcliffe et al., 2011). **(C1)** When an animal crosses the CT viewshed the number of photographs and thus capture probability spatially varies. The CT typically does not capture photos across all viewshed space for the time an animal is in the viewshed (green squares in **C2**). Our proposed method, which estimates the Realised Viewshed Size (RVS), uses jog-tests at fixed locations across the viewshed (**D**) to determine precisely where a subject was when photographs were taken or not taken (**E**). Using kernel-based analytics, we estimate capture probability accounting for missed captures and as it varies spatially across camera viewshed (**E**). We integrate spatially variable capture probabilities to represent the RVS—CT viewshed size

687   corrected for perfect capture probability. The RVS is a theoretical value relevant for some
688   viewshed density estimators (e.g., Random Encounter Staying Time, Time in Front of Camera
689   models). Animal detections will occur outside of the theoretical RVS, but their probabilities are
690   integrated into a minimum size with 100% capture probability.
691

692
693 **Figure 2.** Predicted probabilities of photographic capture, determined by Generalized Additive
694 Mixed Models, on a 1x1 m grid for an average Reconyx Ultrafire camera in Case Study A, with
695 62 % shrub cover, a subject moving at a 2 m/s velocity, and an ambient air temperature of 1.5°C.
696 The predicted Realised Viewshed Size ($\pm$ 1 SE) for this camera was determined to be 15 m^2 (8–
697 27m^2). The camera traps is located at position [0,0] on the grid.
698

699
700
701 **Figure 3.** The predicted influence of unit changes of numerical covariates across their measured
702 range in Case Study A, i.e., percent shrub cover, percent horizontal cover of vegetation, ambient
703 air temperate (°C) at time of survey, and velocity (m/s) of each jog, on the Realised Viewshed Size
704 at a given camera trap. For each numerical covariate of interest, all other covariates are held at
705 their mean value for all predictions.
706

Figure 4. Effects of different sensitivity settings (low, medium, high, very high) and number of photos taken per each Passive Infrared Motion trigger (one, three, five) on the predicted Realised Viewshed Size ($m^2 \pm$ SE) of Reconyx Hyperfire 2 camera traps ($n = 26$) predicted from Generalized Additive Mixed Models during our controlled setting trials for Case Study B.

713
Figure 5. Predicted probabilities of photographic capture, predicted with Generalized Additive
Mixed Models, on a 1x1 m grid for Reconyx Hyperfire 2 cameras, assuming a "medium"
sensitivity setting, and a single photo taken for each Passive Infrared motion detector trigger
during **A**. daytime trials and **B.** nighttime trials. Cameras are located at position [0,0] on each
figure. The Realised Viewshed Size (± SE) were determined to be 151 m^2 (122–191 m^2) for
daytime (**A**) and 73 m^2 (53–101 m^2) for nighttime (**B**).
720