A linear perception-action mapping accounts for response range-dependent biases in heading estimation from optic flow

Qi Sun[1,2,3*†], Ling-Hao Xu[4†], Alan A Stocker[5*]

[1] School of Psychology, Zhejiang Normal University, Jinhua, China, PRC

[2] Intelligent Laboratory of Zhejiang Province in Mental Health and Crisis Intervention for Children and Adolescents, Jinhua, P. R. China

[3] Key Laboratory of Intelligent Education Technology and Application of Zhejiang Province, Zhejiang Normal University, Jinhua, P. R. China

[4] Dominick P. Purpura Department of Neuroscience, Albert Einstein College of Medicine, Bronx, New York, USA

[5] Department of Psychology, University of Pennsylvania, Philadelphia, Pennsylvania, USA.

[†] **Co-first authors**

* Correspondence:

SQ: sunqi_psy@zjnu.edu.cn; https://orcid.org/0000-0001-9382-3249

AS: astocker@psych.upenn.edu, https://orcid.org/0000-0002-2041-1515

Abstract

Accurate estimation of heading direction from optic flow is a crucial aspect of human spatial perception. Previous psychophysical studies have shown that humans are typically biased in their estimates of heading directions, but the reported results are inconsistent. While some studies found that humans generally underestimate heading direction (central bias), others find the opposite, an overestimation of heading direction (peripheral bias). We conducted three psychophysical experiments showing that these conflicting findings do not reflect inherent differences in heading perception but are caused by the different sizes of the response range that participants were allowed to utilize when reporting their estimates. Notably, we show that participants' heading estimates monotonically scale with the size of the response range, leading to underestimation for small and overestimation for large response ranges. Additionally, neither the speed profile of the optic flow pattern nor the response method (mouse vs. keyboard) significantly affected participants' estimates.

Furthermore, we introduce a Bayesian heading estimation model that can quantitatively account for participants' heading reports. The model assumes an efficient sensory encoding of heading direction according to a prior inferred from human heading discrimination data. In addition, the model assumes a response mapping that linearly scales the perceptual estimate with a scaling factor that monotonically depends on the size of the response range. This simple perception-action model accurately predicts participants' estimates both in terms of mean and variance across all experimental conditions. Our findings underscore that human heading perception follows efficient Bayesian inference; differences in participants reported estimates can be parsimoniously explained as differences in mapping percept to probe response.

Author summary

Humans can estimate the direction of their self-motion (heading) from the associated visual motion pattern (optic flow) on their retinae. While these heading estimates are typically biased, previous studies have found quite conflicting bias patterns despite using very similar optic flow stimuli. Our findings demonstrate that these differences in participants' reported estimates can be attributed to differences in the response range within which participants were able to move their cursor to report their estimates. We introduce an efficient Bayesian observer model to quantitatively analyze these conflicting bias patterns. The model assumes that perceived heading directions are identical for identical optical flow patterns, yet the reported heading directions are the result of an additional response mapping that linearly maps the percept to the reported estimate. This model fits the data well and demonstrate that participants reported perceptual estimates can be substantially modulated by post-perceptual response transformations, in particular under conditions where they do not receive feedback. Our study is a reminder that psychophysical measurements necessarily provide only an indirect account of perception. Full explanations of such data require the inclusion of appropriate post-perceptual transformations that describe the mapping from perception to action.

Introduction

An accurate and precise estimation of stimulus features based on visual information is important for a successful interaction with our environment. However, humans are often biased in their estimates of stimulus features. For instance, orientations are often inaccurately perceived, a phenomenon referred to as the oblique effect [1], while color estimates exhibit systematic compressions towards the center of individual color categories [2]. Most of these biases are robust and have been successfully replicated across multiple studies performed by different labs. For example, the effect that perceived visual orientations are typically biased away from cardinal orientations (the aforementioned oblique illusion), is robust and has been repeatedly reported with little quantitative difference [3-5]. However, that is not true for biases in perceived heading direction (i.e., self-motion direction) based on optic flow (Fig. 1a, S1 and S2 for Movies). Some studies found that participants consistently overestimated their heading direction, thus exhibiting a peripheral bias [6-8]. Whereas in other studies, participants consistently underestimated their heading direction, producing a consistent center bias towards the straight-ahead direction [9-15]. What contributes to these seemingly contradictory results remains unclear, in particular since all these studies used very similar optic flow stimuli in overall very similar experiments. A careful examination of the differences in experimental design between these studies, however, reveals two potential factors that may have caused the contrasting behavioral results. The first factor concerns the **speed profiles** of the used optic flow stimuli. Studies that found central biases (underestimation) generally utilized optic flow patterns that simulate observers moving in 3D space at constant speed [10-12, 15]. In contrast, studies that reported a peripheral bias (overestimation) typically employed optic flow patterns that simulate observer moving at variable speeds [6-8, 16]. Note that variable speed in this these studies refers to a predetermined

pattern of acceleration and deceleration during stimulus presentation. The second factor is the

response method. Specifically, in studies that reported central bias, participants expressed their

perceived headings by adjusting the position of a probe along a horizontal line using the mouse

(see right panel in Fig. 1b; [10-12, 15]), whereas in the studies that reported peripheral bias,

participants adjusted the position of a probe on a circle using key presses (see middle panel in

Fig. 1b; [6, 7]). It is unclear in what way these two factors are responsible for the different type

of bias and why.

Fig. 1. Heading estimation based on optic flow. (a) Illustration of an optic flow pattern [17] that simulates

an observer moving straight-forward (i.e., a heading direction of 0°). The dots indicate the positions of

dots in the first frame. The white lines (invisible in the experiment) indicate the motion trajectory of dots

in the subsequent frames. Previous heading perception studies have used very similar optic flow stimuli.

(b) Response methods used in our three experiments. In Experiment 1, participants either used a mouse-

controlled probe on a horizontal line with a range of 80° (left panel) or moved a key-controlled dot on a

circle with a range of 360° (middle panel) to indicate their perceived heading direction. In Experiment 2,

all participants reported their perceived heading direction by moving a mouse-controlled probe on a line

(block 1), circle (block 2), or an arc with a range of 80° (block 3, right panel). In Experiment 3,

participants reported their estimates for three different arc ranges: 80°, 160°, or 240° (right panel). The

range of tested heading directions in all experiments was [-33, +33] deg. Note, the white lines and the

numbers denoting the range were not shown to participants during the experiment, and the mouse and

keyboard labels in b are from https://openclipart.org/.

Supporting information S1 and S2 Movies provide examples of the optic flow stimuli used in the

experiments, demonstrating constant and variable speed profiles, respectively.

In the current study, we undertook three experiments and aimed at determining how

stimulus speed profiles and response methods may affect heading estimates based on optic flow.

Our findings reveal that the response range played a pivotal role in causing distinct estimation

biases, causing a gradual transition from underestimation to overestimation biases with

increasing response range. Building on these empirical results, we introduce a model that extends

the efficient Bayesian observer model of Wei & Stocker [18-20]. The extended observer model

assumes that perceived heading direction is linearly mapped to participants' reported estimates

with a scaling factor that grows monotonically with the size of the response range. We found that

our model accurately predicts both biases and variances in participants' heading estimates across

different response ranges, suggesting that divergent heading estimates can be attributed

exclusively to variations in response ranges. This novel extension of the efficient Bayesian

observer model provides a comprehensive explanation for the observed biases in heading

estimation and highlights the importance of considering sensorimotor transformations when

interpreting behavioral reports in perceptual decision-making tasks.

Experimental Results

Impact of navigation speed on reported heading direction (Experiment 1)

Thirty-six participants were exposed to two types of optic flow stimuli generated by simulated

movement of observers in a 3D dot-cloud environment: movement was either at constant speed

or at variable speed (S1 and S1 for Movies 1 and 2). Throughout all experiments, participants

were exposed to heading directions within the range [-33°, 33°] with uniform sampling at 6°

steps. Negative and positive values denote the headings left (-) or right (+) of straight-ahead

direction (0°). Consistent with previous studies, one group of participants (N=18) reproduced

their perceived heading directions by moving a mouse-controlled probe on a horizontal line with

a limited response range (80°, left panel in Fig. 1b), while another group adjusted a key-

controlled dot on a circle (response range is 360°, middle panel in Fig. 1b; see Methods for more

details). No feedback was given to participants.

Fig. 2 illustrates the bias (difference between the average heading estimate and the actual

heading direction) and the standard deviation of subjects' estimates for the two different speed

and response conditions. The bias patterns are similar for the two speed profiles but exhibit

significant differences under the two response conditions. Specifically, participants

overestimated heading direction (peripheral bias) when reporting their estimates on the circle

(red line), whereas they underestimated heading direction (central bias) when reporting on the

line (black line). These results suggest that the speed pattern by which participants navigate does

not affect perceived heading directions. The specific response condition, however, can

substantially affect the reported heading estimates.

Fig. 2. Bias and standard deviation in perceived heading direction (Experiment 1, N=18) (a) Average bias across participants as function of actual heading angle (0° corresponds to straight-ahead). To capture the general tendency towards over- or under-estimation, we applied a linear fit to the measured bias data points (solid lines). Positive slope values indicate overestimation (peripheral bias), while a negative slope indicates underestimation (central bias). (b) Average standard deviation (SD) of reported heading estimates across participants as a function of actual heading direction. Red dots correspond to estimates

reported on the circle, and black dots correspond to estimates reported on the line. Error bars in all plots

indicate the standard error across participants.

Likewise, variability in participants' estimates is also different for the two response

conditions but again does not depend on the speed profile. Standard deviations were significantly

larger in the circle response condition compared to the line response condition, although the

overall pattern was similar (Fig. 2b).

Impact of response method (mouse vs. keys) on reported heading direction (Experiment 2)

Experiment 2 was identical to Experiment 1, with the exceptions that i) the optic flow displays

corresponded to an observer moving at a constant speed, and ii) participants reported their

perceived heading direction by adjusting a cursor with a computer mouse. In addition to the line-

and circle-response conditions (left and middle panels in Fig. 1b), we also included an arc-

response condition where participants reported their heading direction on an 80° response arc ([-

40°, +40°] range; right panel in Fig. 1b). Note that the tested heading directions never exceeded a

range of [-33°, 33°]. The three response conditions were randomly interleaved in the experiment

(see Methods for details).

Fig. 3a shows the average biases across all 18 participants in Experiment 2. Participants

clearly underestimate heading direction when reporting their estimates both on the 80° line and

the 80° arc. Note, the biases are not significantly different between the two conditions. In

contrast, participants clearly overestimated heading directions in trials where they reported their

estimates on the circle. Consistent with the data from Experiment 1, the standard deviation of

participants' reported estimates was significantly larger in the circle response conditions

compared to the line and arc response conditions (Fig. 3c); again, there was no significant

difference between the latter two conditions. Results of Experiment 2 indicate that the divergent

bias patterns are solely due to a difference in response range (80° arc vs. full circle). The

difference in response method had no effect on participants' reported heading direction.

Fig. 3. Bias and standard deviation in perceived heading direction (Experiments 2 and 3, N=18) (a, b)

Average bias of participants (N=18) as a function of heading direction (0° corresponds to straight-ahead).

Solid lines represent linear fits to the average bias curves. A positive slope indicates overestimation

(peripheral bias), while a negative slope indicates underestimation (central bias). (c-d) Average standard

deviation of reported heading estimates as a function of heading direction. In (a, c), the red, blue and

black dots represent the circle, 80° arc, and line response conditions, respectively. In (b, d), the red, blue

and black dots represent the 240°, 160°, and 80° arc response conditions, respectively. In all panels, error

bars indicate the standard errors across participants.

Impact of response range on reported heading direction (Experiment 3)

Results of Experiment 2 indicate that heading estimates may progressively increase when

participants are provided with an increasingly larger response range. We recruited another 18

participants to conduct Experiment 3. The experimental design was similar to that of Experiment

2 except that participants only provide their estimates on a response arc with progressively

increased response range (i.e., arcs of 80°, 160°, and 240°; see Methods for more details).

Importantly, trials of the different range conditions were randomly interleaved. Fig. 3b shows

that participants' central bias (underestimation) is progressively reduced with increasing

response range, eventually turning into a peripheral bias (overestimation) when the response

range is 240° or more. Standard deviations of participants' reported estimates as a function of

actual heading direction are similar in shape across all response conditions but progressively

increase with increasing response range (Fig. 3d). The results of Experiment 3 further confirm

that the response range is the main factor leading to different estimation biases and standard

deviations.

To further validate the influence of response range on reported heading estimates, we

conducted an additional experiment in which participants reported their perceive heading by

adjusting the mouse-controlled probe on a line of different lengths (e.g., 80°, 111°, and 142°).

The results (Supplementary Fig. 1.) show that shorter lines led to underestimation while longer

lines caused more overestimation, mirroring our findings with the arc responses. This highlights

the generalization of the range effect in heading perception.

In summary, the results from the three experiments demonstrate that participants' heading

estimates were neither significantly different between different speed profiles (constant vs.

variable) nor did they depend on the response method (mouse vs keyboard). However, estimates

were strongly dependent on the response range, showing progressively increasing biases from

underestimation to overestimation with increasing size of the response range. The difference in

response range is the main explanation for the previously reported, contrasting biases in reported

heading estimates.

Bayesian Observer Model

Bayesian observer models express how knowledge about the distribution of a stimulus feature

(i.e., the prior) needs to be combined with current sensory information (i.e., the likelihood) in

order to optimally estimate the value of the feature [23-25]. Measured heading direction

distributions by freely behaving human observers show a characteristic peak for straight-ahead

heading [26]. With such a prior, however, standard Bayesian observer models consistently

predict a bias toward the prior peak, thus a central bias toward straight-ahead direction [10-12,

15]. As a result, these models cannot account for peripheral biases. More importantly, previous

Bayesian observer model did not consider potential transformations between participants'

heading percepts and their reported estimates, and thus are generally not equipped to explain the

dependency on the response range we found in our experiments.

Here, we present a Bayesian observer model that can account for these range effects. The

model extends the Bayesian observer model constrained by efficient coding proposed by Wei

and Stocker [18-20]. The original model's innovation was to integrate efficient coding theory

[21, 22] with a Bayesian observer model, resulting in a unified framework known as the efficient

Bayesian observer model. The model assumes that the neural system efficiently encodes the

stimulus by maximizing the mutual information between the stimulus and its sensory

representation. Subsequently, guided by the observer's prior belief $p(\theta)$, the efficient sensory

representation is optimally decoded to yield the observer's estimate (Fig. 3).

230   Originally, the model considers the Bayesian estimate as a direct reflection of participants'

231 reported estimate (Fig. 4a). With the extended model, however, we assume that participants'

232 perceptual estimate of heading $\hat{\theta}(m)$ is mapped to their reported estimate $\hat{\theta}_r(m)$ via a linear

233 response mapping, thus $\hat{\theta}_r(m)=\alpha_i\hat{\theta}(m)$ (Fig. 4b), with a scaling factor α_i that monotonically

234 depends on the response range (see Methods).

235   We jointly fit this extended model to the data from individual participants in Experiment 3

across all three response conditions. We constrained the prior $p(\theta)$ on heading direction based

on the assumption that heading direction is efficiently represented in the brain. This assumption

predicts that the prior is inversely proportional to the discrimination threshold [20]. Specifically,

we used a smooth approximation of previously measured heading direction discrimination data

[8] to determine the prior on heading direction (see also [27]). The prior shows characteristic

peaks for straight-ahead and straight-back directions (Fig 4c), in agreement with measured

behavioral statistics [26]. Importantly, in the interest of simplicity, we used this fixed prior for all

model fits of individual participants' data. Furthermore, given the deterministic generation of the

optic flow stimuli, we assume no external noise. This leaves us with only two free model

parameters per participant: the overall sensory noise magnitude κ fixed across all response

conditions, and the scaling factor α that is free for each response condition.

Fig. 4. Extended efficient Bayesian observer model. (a) The efficient Bayesian observer model [19] assumes that the stimulus feature θ (e.g., heading direction) is first efficiently encoded in a sensory signal m before a Bayesian inference process computes an optimal estimate of the feature value $\hat{\theta}(m)$. (b) We extended the efficient Bayesian observer model by assuming a response mapping that maps the perceptual estimate $\hat{\theta}(m)$ to the participants reports $\hat{\theta}_r(m)$ in the experiment. We assume that this mapping is linear, thus $\hat{\theta}_r(m)=\alpha_i\hat{\theta}(m)$ where α_i is a positive and monotonically depends on the size of the response range. (c) Prior distribution for heading direction, $p(\theta)$. We estimate a single prior for all participants based on previously measured heading discrimination thresholds $D(\theta)$ [8]. Under the efficient coding assumption, the prior is inversely proportional to $D(\theta)$ [20, 28, 29, 36]. We smoothly approximate the experimentally determined prior with a two-peak von-Mises distribution, providing an indirect estimate of the underlying natural distribution of heading directions. Supplementary Fig. S2 shows an alternative method of obtaining a similar estimate of the heading prior based on neural response characteristics

Note that the encoding precision, and thus the likelihood function, changes with heading

direction but is precisely determined by the prior distribution (Fig. 4c) according to efficient

coding. Because we assume the same approximation of the prior distribution for all participants,

the likelihood functions of each participant are self-similar and only scaled by the individual

sensory noise magnitude (see Methods).

Fig. 5 presents the results of our model fits. Fig. 5a shows the fit scaling factor α (group

level, individual subjects, and average), which exhibits a positive correlation with the expansion

of the response range. Fig. 5b shows the fit overall sensory noise level κ. Based on these two free

parameters, our model generates detailed predictions for the bias and standard deviation of

heading estimates, both at the group level (left panel of Fig. 5c) and individual level (right panel

of Fig. 5c). These predictions demonstrate the model's ability to accurately represent the key

characteristics of participants' data, both at the level of the average subject (Fig. 5d) as well as at

the level of individual subjects (Fig. 6). The model effectively anticipates central biases

(underestimation) when the response range is narrowest (80°). These biases transition to

peripheral biases (overestimation) for broader response ranges (160° and 240°), with a

discernible increase in bias corresponding to the enlargement of the response range. Similarly,

the model adeptly mirrors the overall characteristic of the standard deviation as a function of

heading direction, showcasing a gradual magnitude increase with increasing response range

while its pattern remains the same (Fig. 5e). This matches the observed self-similar pattern in

participants' standard deviation (Fig. 5f and Fig. 6).

In conclusion, our results demonstrate that an extended efficient Bayesian observer model

based on a prior inferred from heading discrimination data can well account for nonlinear

patterns of participants' heading estimation behavior (bias and standard deviation). Furthermore,

the model assumes that participants' perceived heading direction is mapped to their reported

heading direction with a scaling factor that monotonically depends on the specific response range

available to the participants in the experiment.

It is important to note that for the standard efficient Bayesian observer model [19] the

experimentally imposed response range is irrelevant; it would predict identical perceptual biases

regardless of how responses are collected. Our extended model builds on this well-proven

theoretical framework and thus assumes that the underlying perceptual (Bayesian) processing

remains constant across conditions. With the proposed linear mapping between participants'

percepts and their responses, it provides a parsimonious explanation for the observed systematic

dependencies of participants' heading reports on response range without the need for unrealistic

assumptions of how the (invisible) response range could possibly directly affect the percept. As

such, our results provide an intuitive, non-perceptual explanation for the apparently contrasting

findings of both central (underestimation) and peripheral (overestimation) biases in heading

estimation from optic flow.

Fig. 5. Fit of the extended efficient Bayesian observer model to the data from Experiment 3. (a) Values of the scaling factor α from the group-level fit (left panel; combined data from all participants) and individual-level fits (right panel; fits to each participant's data). The right panel also shows the mean *α* values across participants for each response range condition. A repeated-measures ANOVA with Bonferroni-corrected post-hoc tests revealed that α significantly increases with the response range (***$p<0.001$). (b) Fit values of the sensory noise parameter *κ* (group-level and individual-level fits). (c, e) Model predictions for bias and standard deviation of heading estimates, respectively, based on the group-level (left panel) and individual-level (right panel) fits. Shaded areas represent the standard error across

307 participants. (d, f) Mean bias and standard deviation of heading estimates across the 18 participants in

308 Experiment 3. Error bars indicate the standard error of the mean across participants.

310 **Fig. 6.** Behavioral data and model fits for individual participants in Experiment 3, demonstrating the

311 model's ability to capture individual-level patterns in heading estimation biases and variability.

Discussion

Our study demonstrates that the seemingly conflicting reports about biases in human heading

estimates can be attributed to the influence of the response range in the psychophysical

experiments. Specifically, participants' reported heading directions transitioned progressively

from underestimation to overestimation with increasing response range. The fact that both bias

and standard deviation in participants' reported heading estimates systematically vary with

response range, despite identical visual stimuli, suggests that the transformation between

perception and response plays a crucial role in shaping participants' reported estimates. We

demonstrate that this systematic dependency is parsimoniously explained by with extending the

efficient Bayesian observer model [19] with a linear response mapping between perceived and

reported estimates that scales with the response range (Fig. 5a). We quantitatively validated this

extended model and show that it provides a rational explanation for human heading perception,

thereby reconciling the many, seemingly conflicting, previous findings about the nature of

heading estimation biases. Our results emphasize the significant role that perception-action

mapping can have in shaping the reported estimates of stimulus features in psychophysical

experiments, which has been frequently neglected in the past.

With only a few free parameters, our observer model is able to accurately express the large

range of individual differences in subjects heading estimates, both in terms of bias and variance

(Fig. 6). For our model, we assumed a fixed prior for heading direction based on the smooth

approximation of previously recorded heading discrimination data [8]. According to the efficient

coding assumption of the model, the prior is defined as being proportional to the inverse of the

discrimination threshold function [20]. Although this is an indirect way of determining the prior,

previous studies have shown that it faithfully captures the statistical prior in the visual

environment for other stimulus variables such as local orientation [28] and visual motion [29].

Furthermore, preliminary data on the actual heading direction statistics of freely behaving human

observers seem to support the predominance of straight-ahead heading [26]. We also considered

an alternative derivation of the prior based on neural responses. Specifically, we analyzed single

cell recorded, neural activity in area MSTd of non-human primates in response to optical flow

stimuli indicating heading direction [8]. Following a previous approach [19], we extracted Fisher

information from the neural population responses in order to derive the prior distribution (see

Supplementary Fig. 2). This neurally derived prior for heading direction is similar to the prior

from the psychophysical discrimination data and, importantly, leads to model predictions that are

qualitatively well aligned with the current results [37]. This alternative derivation of the prior

further validated the assumptions of our model and our general conclusions. Future studies,

however, are necessary to determine in more detail the exact shape of the prior distribution by

actual measurements of the natural statistics of human heading behavior.

Such statistical measurements of the natural prior of human heading directions will also

help to explain another interesting characteristic of our data. Although our observer model

overall well explains the data, there are slight but systematic deviations between data and model

predictions, especially with regard to the bias pattern around straight-ahead heading (0 degrees).

Under all response conditions, participants' bias curves are non-monotonic (i.e., they show a

"wiggle") in the range of 0-15 degree heading direction, which is not accounted for by the model

using the current prior. However, a prior with non-monotonic fall-off (i.e. with some side peaks

close to straight-ahead heading) likely would capture this behavior. An alternative explanation is

that these non-monotonic bias patterns are not due to a non-monotonic prior distribution, but

may be the signature of a categorical influence in participants heading estimates [30].

Our model makes clear predictions with regard to stimulus (external) and sensory (internal)

noise (Fig. 4a). Due to the efficient coding assumption, the two noise sources differentially affect

the perceptual estimate [19]. In our experiments, the optic flow pattern was fully coherent with

each simulated heading direction and thus the stimulus noise was zero. Furthermore, dot

densities and contrasts, as well as stimulus presentation times were fixed, thus sensory noise was

assumed to be constant. Our model predicts that adding stimulus noise (e.g., by reducing the

fraction of dots with coherent optic flow motion) would lead to an increase in central bias (i.e., a

decrease in peripheral bias, respectively), while an increase in sensory noise (e.g., by reducing

the presentation time of the flow pattern) would decrease central bias (i.e., increase peripheral

bias, respectively). Note, our model provides these quantitative predictions at the level of both,

bias and variance across the entire heading direction range. Future studies employing targeted

psychophysical experiments will help to more specifically test those predictions.

It is important to note that in our experiments, participants did not receive visual feedback

about the correct heading direction after reporting their estimates. This was a deliberate choice in

order to be consistent with the experimental designs of previous studies. Without feedback, it

seems reasonable to assume that participants used their experience of the response range to

calibrate their responses. This would explain the monotonic scaling of the estimates with the size

of the response range that we found in our study. Several studies have shown that real-time

feedback can improve our visual perception [5, 31-33]. Thus, it is an interesting open question to

ask to what degree feedback will reduce or even eliminate the effects of the response range on

heading estimation. Based on our model, we predict that with feedback, participants will be able

to quickly recalibrate and substantially reduce the observed bias because the biases are mostly

attributed to the linear response mapping. We expect that the remaining biases will then mainly

reflect only the inductive biases that are intrinsic to the Bayesian inference process due to the

prior and the non-homogeneous, efficient encoding.

Another important aspect of our experimental design is that we manipulated the response

range while keeping the stimulus range constant. Future studies are necessary to more

systematically explore how our results generalize to larger ranges of heading directions. This will

also reveal whether the linear response mapping of our model extends uniformly across all

heading directions or shows deviations at ecologically significant angles (such as straight ahead,

sideways, or backward motion). This consideration of broader heading ranges also constrains our

current version of the model. While we considered the scaling factor α a free model parameter,

we note that for cases where both stimulus and response ranges span 360°, α must be constrained

to equal 1 to avoid impossible predictions at extreme angles. Interestingly, with our

unconstrained model fit, α is indeed approximately 1 for the largest response range. Thus,

imposing such a constraint would not significantly affect our results.

Similarly, although our current experiments focused on forward heading directions only,

our model's predictions for backward heading perception are well-supported by existing

literature [6, 7, 35]. This suggests that our efficient Bayesian observer model and the assumed

heading prior likely generalizes across the full range of heading directions. However, future

research is needed to further validate our model for backward heading perception using similar

experimental paradigms as those employed in our current study.

Finally, while our results well supports the idea of a linear mapping between perceived and

reported heading estimates, we acknowledge that this process likely involves working memory

and other downstream processes. Thus, our results do not make any specific predictions about

the underlying neural mechanisms involved in this perception-to-response mapping.

In conclusion, our study successfully demonstrates that the previously reported, contrasting

findings of underestimation [9-15] and overestimation of heading direction [6-8] can be

coherently accounted for by the different sizes of response range used in these different studies.

We show that participants' reported estimates under different response range conditions are

quantitatively accounted for by an extended efficient Bayesian observer model that incorporates

a linear mapping between perceived and reported estimates. This suggests that human heading

perception follows efficient Bayesian inference and is not dependent on the specific response

characteristics of a psychophysical experiment; the observed differences in participants' reported

estimates originates from differences in mapping from percept to probe response. As such, our

model provides a unifying account of a wide range of heading estimation datasets. It offers a

simple yet parsimonious explanation for a seemingly complex phenomenon. Our findings

contribute to a more comprehensive understanding of human perception and have implications

for the design of navigational aids and virtual reality systems.

Materials and Methods

Experimental methods

Participants

All participants were enrolled in Zhejiang Normal University. All were naive to the experimental

purpose with normal or corrected-to-normal vision. The experiment was approved by the

Scientific and Ethical Review Committee in the School of Psychology of Zhejiang Normal

University. Thirty-six participants took part in Experiment 1 and were randomly divided into two

groups (Group 1: 11 females, 7 males, 19-28 years; Group 2: 11 females, 7 males, 20-25 years).

Eighteen participants took part in Experiment 2 (10 females, 8 males; 19-27 years). Another

eighteen participants took part in Experiment 3 (9 females, 9 males; 17-23 years). We obtained

the consent forms of all participants before they conducted the experiments.

Apparatus

The experiment was programmed in MATLAB using the Psychophysics Toolbox 3 and

presented on a 27-inch Dell monitor (resolution: 2560 H$\times$ 1440 V pixels; refresh rate: 60 Hz)

with NVIDIA GeForce GTX 1660Ti graphics card.

Stimuli

The optic flow stimuli (80° H × 80° V visual angle, Fig. 1a) simulated observers translating in a

3D dot-cloud (depth range: 0.20 – 5 m; eye-height: 0.17 m) consisting of 126 dots (diameter:

0.2°). The simulated self-motion speed was either constant (i.e., 1.5 m/s, used in Experiments 1-

3; see Supplementary materials: Movie 1), or first accelerating (0 m/s to 3 m/s) and then

decelerating to 0 m/s (used in Experiment 1; see Supplementary materials: Movie 2).

Acceleration and deceleration were identical in magnitude (12 m/s^2). Two types of speed profiles

generated the same moving distances (0.75 m) during the stimulus presentation. The simulated

self-motion direction (i.e., heading) was selected from ±3°, ±9°, ±15°, ±21°, ±27°, and ±33°.

Negative and positive values denote the headings left (-) or right (+) to the straight-ahead

direction (0°).

Procedure

Participants sat in a dark room with their heads stabilized with a chin-rest. They viewed the

display binocularly with a 20-cm viewing distance. During the experiment, participants were

asked to fixate on the display center without head and body movements during the entire

experiment duration. Straight-ahead direction was aligned with the display center.

The trial procedures were the same across all three experiments. Each trial started with a

heading display for 500 ms, followed by participants' responses (self-timed). The next trial

started right after a participant's response. Heading direction in each trial was randomly selected

from ±3°, ±9°, ±15°, ±21°, ±27°, and ±33°.

Experiment 1 used a mixed experimental design. Response methods (line vs. circle

responses) were the between-subject variable, while speed profiles (constant vs. variable speeds)

were the within-subject variable. Thus, the current experiment included four conditions. Note

that, in the line-response condition, the left and right end-points of the line were shifted from the

display center (0°) by 40°, resulting in a response range of 80° (left panel in Fig. 1a). Participants

used the mouse to adjust the probe position on the line to indicate their heading estimates. In

contrast, in the circle-response condition, participants could freely adjust the probe position on a

circle, resulting in a response range of 360° (middle panel in Fig. 1a). Participants reported their

heading estimates by pressing the arrow keys to adjust the probe dot position on the circle. The

two speed profiles were tested in two separate blocks. That is, in the line- or circle-response

conditions, participants completed two blocks. Each block corresponded to one speed profile. In

each block of the line- and circle-response conditions, every heading direction was repeated 40

and 15 times, leading to a total of 480 and 180 trials, respectively. There were fewer trials in the

circle-response condition than in the line-response condition because participants typically took

more time to respond in the circle condition. The sequence of the two blocks in the line- and

circle-response conditions was counterbalanced among participants. For example, one participant

would first finish the block with the constant speed, followed by the block with the variable

speed; another participant would first finish the block with the variable speed, followed by the

constant speed.

Experiment 2 was similar to Experiment 1, except that **i)** the motion speed was always

constant, **ii)** the probe on the line or circle was controlled only by the mouse, and **iii)** each

participant in the current experiment finished three blocks of trials. Each block corresponded to

one response method (e.g., line, arc, or circle) and consisted of 240 trials (20 trials × 12

headings). The response range for the arc condition was 80° (right panel in Fig. 1a). The

conducting sequence of the three blocks was counterbalanced among participants.

Experiment 3 was similar to Experiment 2, except that only one block was conducted. The

block contained 12 heading directions and three response range conditions: 80°, 160°, and 240°.

There was a total of 36 combinations. Each combination was repeated 15 times, resulting in 720

trials. All trials were randomly interleaved.

Before starting the experiment, participants were given 20 practice trials in which the speed

profile was constant. The practice trials helped participants to familiarize the stimuli and

response methods. After the practice part, the experiment started.

Modeling methods

Our model consists of two parts: the efficient Bayesian observer model as originally proposed

(Fig. 3a, [19, 20]) and a linear perception-action mapping stage (Fig. 4b).

Part 1: the efficient Bayesian observer model

The efficient Bayesian observer model was built based on the following three assumptions:

(1) The neural system encodes stimulus features (e.g., heading direction from optic flow)

efficiently, following the efficient coding hypothesis [21, 22];

(2) The sensory noise follows a von-Mises distribution in sensory space. Because the noise is

homogeneous in this space, the likelihood function $p(m/\theta)$ for a stimulus θ_0 also follows a

von-Mises distribution, where μ is the distribution mean equal to $F(\theta_0)$, and κ is the

concentration parameter that represents the sensory noise magnitude;

(3) Following assumption (1) and [20], the prior distribution $p(\theta)$ is inversely proportional to

the discrimination threshold $D(\theta)$, thus

$p(\theta) \propto \dfrac{1}{D(\theta)}$ (1)

In the current study, we used the visual discrimination data from [8] and fitted a bimodal

Von-Mises distribution to obtain a smooth approximation of the prior distribution (Fig. 4c).

Alternatively, we extracted the prior distribution for neural data based on single-cell recordings

in area MSTd of macaque monkeys [8]; the resulting estimate of the prior distribution is similar

(see Supplementary Fig. 2).

With the above assumptions, we provide the following step-by-step formulation of the

extended efficient Bayesian observer model:

1.1 Encoding and Mapping Function $F(\theta)$

To encode the heading direction, we employed a one-to-one mapping to transform the heading

direction θ from stimulus space into sensory space according to efficient coding, given by

$F(\theta) = \int_{-\pi}^{\theta} p(\vartheta)d\vartheta$ (2)

which represents the cumulative prior distribution $p(\theta)$ with θ in $[-\pi, \pi)$. The cumulative prior

distribution serves as a mapping function that transforms the physical stimulus space into a

perceptual space. In this transformed space, the Fisher information becomes uniform, which,

under the specific assumptions of the model, provides an efficient coding of sensory information.

This approach has been widely adopted in perceptual modeling studies (e.g., [5, 18-20, 28, 30,

34]).

1.2 Sensory measurement m

For each heading direction θ_0, the corresponding measurement on the sensory space m is given by,

$$m=F(\theta_0)+\eta \tag{3}$$

where η represents the internal sensory noise.

1.3 Likelihood Function $p(m|\theta)$

We assume the sensory noise η follows a von-Mises distribution in the sensory space:

$$p(m|\theta)=\frac{1}{2\pi I_0(\kappa)} e^{(\kappa cos(m-F(\theta)))} \tag{4}$$

where $I_0(\cdot)$ is the modified Bessel function of order 0, and κ is the concentration parameter that controls the noise magnitude. The likelihood function $p(m|\theta)$ captures the bottom-up sensory information for a specific measurement m.

1.4 Prior Distribution $p(\theta)$

The prior distribution $p(\theta)$ represents the observer's belief about the probability of each heading direction θ before any sensory observation. As stated in assumption (3), we assume it to be inversely proportional to the heading discrimination threshold $D(\theta)$ measured in the experiment [8]. We keep this prior distribution fixed for all model fits and predictions of our model analysis.

1.5 Posterior Distribution $p(\theta|m)$

With the likelihood function $p(m|\theta)$ and the prior distribution $p(\theta)$ defined above, the posterior distribution $p(\theta|m)$ can be computed using Bayes' rule:

$$p(\theta|m)\propto p(m|\theta)p(\theta) \tag{5}$$

1.6 Bayesian Estimate $\hat{\theta}(m)$

To obtain the Bayesian estimate $\hat{\theta}(m)$ for a given measurement m, we minimize the expected loss based on a specific loss function $L(\hat{\theta},\theta)$:

$\hat{\theta}(m)=\underset{\hat{\theta}}{argmin}\int L(\hat{\theta},\theta)p(\theta|m)d\theta$ (6)

For the squared error loss function (L_2 norm: $L(\hat{\theta},\theta)=\|\hat{\theta}-\theta\|_2$, the Bayesian estimate is the mean

of the posterior distribution:

$\hat{\theta}(m)=\int \theta p(\theta|m)d\theta$ (7)

1.7 Estimation Bias $b(\theta_0)$ and Standard Deviation $\sigma(\theta_0)$

The expected bias $b(\theta_0)$ for a given stimulus value θ_0 can be computed by marginalizing the

estimate $\hat{\theta}(m)$ over the measurement distribution $p(m|\theta_0)$:

$b(\theta_0)=\int \hat{\theta}(m)\,p(m|\theta_0)dm-\theta_0$ (8)

To compute the standard deviation of the circular variable $\hat{\theta}$, we first calculate the average

cosine and sine of the estimate:

$$\begin{aligned} C(\theta_0) &=\int cos(\hat{\theta}(m))p(m|\theta_0)dm \\ S(\theta_0) &=\int sin(\hat{\theta}(m))p(m|\theta_0)dm \end{aligned}$$ (9)

Then, the circular standard deviation $\sigma(\theta_0)$ of the estimate for a given stimulus value θ_0 can be

computed as:

$\sigma(\theta_0)=\sqrt{2(1-\sqrt{C(\theta_0)^2+S(\theta_0)^2})}$ (10)

Part 2: Linear Perception-Action Mapping

To account for the effect of the response range on the reported heading estimates, we extend the

efficient Bayesian observer model by introducing a linear mapping between the perceived

heading direction $\hat{\theta}(m)$ and the reported heading estimate $\hat{\theta}_r(m)$:

$\hat{\theta}_r(m)=\alpha_i\hat{\theta}(m)$ (11)

where α_i ($i=1, 2, 3$) is a scaling factor that depends on the response range condition (Fig. 5a).

Part 3: Model Fitting

Our extended model has four free parameters: the sensory noise magnitude κ (assumed to be

constant across response range conditions) and the three scaling factors $\{\alpha_1, \alpha_2, \alpha_3\}$ (one for each

response range condition). We jointly fit these parameters to the data from all participants in

Experiment 3 using maximum likelihood estimation:

$$\{\kappa^*, \alpha_1^*, \alpha_2^*, \alpha_3^*\} = \underset{\kappa, \alpha_1, \alpha_2, \alpha_3}{argmax} \, p(X|\kappa, \alpha_1, \alpha_2, \alpha_3) \tag{12}$$

where X represents the observed heading estimates across all participants and conditions.

Data and code

568 All data and modeling codes have been deposited on OSF:

569 https://osf.io/t47v6/?view_only=659d4bac8e4344f996eb8a51eb236d55

Funding

571 This study was supported by National Natural Science Foundation of China (NSFC), China (No.

572 32200842) to Qi Sun and in part by the University of Pennsylvania (to AAS). No author received

573 a salary from any of our funders. The funders had no role in study design, data collection and

574 analysis, decision to publish, or preparation of the manuscript.

Acknowledgement

576 We thank Bao-Yin Zhang and Lin-Zhe Zhan for collecting the data and doing the pilot data

577 analysis.

References

1. Appelle, S. Perception and discrimination as function of stimulus orientation. Psychol Bull.

1972; 78, 266–278. https://doi.org/10.1037/ h0033117

2. Olkkonen M, McCarthy PF, Allred SR. The central tendency bias in color perception: Effects

of internal and external noise. J Vis. 2014; 14(11):5.

http://www.journalofvision.org/content/14/11/5

3. De Gardelle V, Kouider S, Sackur J. An oblique illusion modulated by visibility: Non-

monotonic sensory integration in orientation processing. 2010; J Vis. 10(10):6.

http://www.journalofvision.org/content/10/10/6

4. Taylor R, Bays PM. Efficient coding in visual working memory accounts for stimulus-specific

variations in recall. Neurosci J. 2018; 38(32):7132–7142.

https://doi.org/10.1523/JNEUROSCI.1018-18.2018

5. Noel JP, Zhang LQ, Stocker AA, Angelaki DE. Individuals with autism spectrum disorder

have altered visual encoding capacity. PLoS Biol. 2021; 19(5):e3001215.

https://doi.org/10.1371/journal.pbio.3001215

6. Crane BT. Direction specific biases in human visual and vestibular heading perception. PloS

One. 2012; 7(12):e51383. https://doi.org/10.1371/journal.pone.0051383

7. Cuturi LF, MacNeilage, PR. Systematic biases in human heading estimation. PloS One. 2013;

8(2):e56862. https://doi.org/10.1371/annotation/38466452-ba14-4357-b640-5582550bb3dd

8. Gu Y, Fetsch CR, Adeyemo B, DeAngelis GC, Angelaki DE. Decoding of MSTd population

activity accounts for variations in the precision of heading perception. Neuron. 2010;

66(4):596-609. doi: 10.1016/j.neuron.2010.04.026.

9. D'Avossa G, Kersten D. Evidence in human subjects for independent coding of azimuth and

elevation for direction of heading from optic flow. Vis Res. 1996; 36(18):2915-2924.

https://doi.org/10.1016/0042-6989(96)00010-7

10. Sun Q, Zhan LZ, You FH, Dong XF. Attention affects the perception of self-motion

direction from optic flow. iScience. 2024; 27:109373.

https://doi.org/10.1016/j.isci.2024.109373

11. Sun Q, Zhan LZ, Zhang BY, Jia S, Gong XM. Heading perception from optic flow occurs at

both perceptual representation and working memory stages with EEG evidence. Vis Res.

2023; 208:108235. https://doi.org/10.1016/j.visres.2023.108235

12. Wang XY, Gong XM, Sun Q, Li X. Attractive effects of previous form information on

heading estimation from optic flow occur at perceptual stage. J Vis. 2022; 22(12):18.

https://doi.org/10.1167/jov.22.12.18

13. Warren WH, Kurtz KJ. The role of central and peripheral vision in perceiving the direction

of self-motion. Percept Psychophys. 1992; 51(5), 443-454.

14. Warren Jr WH, Saunders JA. Perceiving heading in the presence of moving objects.

Perception, 1995; 24(3):315-331. https://doi.org/10.1068/p24031

15. Xu LH, Sun Q, Zhang B, Li X. Attractive serial dependence in heading perception from

optic flow occurs at the perceptual and postperceptual stages. J Vis. 2022; 22(12):11.

https://doi.org/10.1167/jov.22.12.11

16. Crane BT. Human visual and vestibular heading perception in the vertical planes. JARO.

2014; 15:87-102. doi: 10.1007/s10162-013-0423-y

17. Gibson JJ. The perception of the visual world. Boston, MA: Houghton Mifflin; 1950.

18. Wei XX., Stocker AA. Efficient coding provides a direct link between prior and likelihood

in perceptual Bayesian inference. Adv Neural Inf Process Syst. 2012; 25:1-9.

624 19. Wei XX, Stocker, AA. A Bayesian observer model constrained by efficient coding can

625 explain 'anti-Bayesian' percepts. 2015; Nat Neurosci. 18(10):1509-1517.

626 https://doi.org/10.1038/nn.4105

627 20. Wei XX, Stocker AA. Lawful relation between perceptual bias and discriminability. PNAS.

628 2017; 114(38):10244-10249. https://doi.org/10.1073/pnas.1619153114

629 21. Attneave F. Some informational aspects of visual perception. Psychol Rev. 1954; 61(3):183-

630 193. https://doi.org/10.1037/h0054663

631 22. Barlow HB. Possible principles underlying the transformation of sensory messages. Sensory

632 Communication. 1961; 1(01):217-233

633 23. Geisler WS, Kersten D. Illusions, perception and Bayes. Nat Neurosci. 2002; 5(6):508-510.

634 https://doi.org/10.1038/nn0602-508

635 24. Knill DC, Richards W. Perception as Bayesian inference. Cambridge University Press; 1996.

636 25. Weiss Y, Simoncelli E P, Adelson EH. Motion illusions as optimal percepts. Nat Neurosci.

637 2022; 5(6):598-604. https://doi.org/10.1038/nn0602-858

638 26. Sinnott C, MacNeilage P. Statistical characterization of heading stimuli in natural

639 environments using SLAM. J Vis. 2019; 19(8):53. https://doi.org/10.1167/19.8.53

640 27. Crowell JA., Banks, MS. Perceiving heading with different retinal regions and types of optic

641 flow. Percept Psychophys. 1993; 53(3):325-337. https://doi.org/10.3758/BF03205187

642 28. Ganguli D, Simoncelli EP. (2014). Efficient sensory encoding and Bayesian inference with

643 heterogeneous neural populations. Neural Comput. 2014; 26(10), 2103-2134. DOI:

644 10.1162/NECO_a_00638

29. Zhang LQ, Stocker AA. Prior expectations in visual speed perception predict encoding

characteristics of neurons in area MT. J Neurosci. 2022; 42(14), 2951-2962.

https://doi.org/10.1523/JNEUROSCI.1920-21.2022

30. Mao J, Stocker AA. Sensory perception is a holistic inference process. Psychol Rev. 2024;

Advance online first. https://dx.doi.org/10.1037/rev0000457

31. Alenezi HM, Bindemann M. The effect of feedback on face☐matching accuracy. Appl Cogn

Psychol. 2013; 27(6):735-753. https://doi.org/10.1002/acp.2968

32. Attar N, Wu CC, & Pomplun M. The effect of immediate accuracy feedback in a multiple-

target visual search task. In Proceedings of the Annual Meeting of the Cognitive Science

Society. 2014; 36(36):1868-1873.

33. Bjasch D, Bockisch CJ, Straumann D, Tarnutzer AA. Differential effects of visual feedback

on subjective visual vertical accuracy and precision. PLoS One. 2021; 7(11):e49311.

https://doi.org/10.1371/journal.pone.0049311

34. Polanía R, Woodford M, Ruff CC. Efficient coding of subjective value. Nat Neurosc. 2019;

22(1), 134-142. https://doi.org/10.1038/s41593-018-0292-0

35. Crane BT. Coordinates of Human Visual and Inertial Heading Perception. PLoS One. 2015;

10(8): e0135539. https://doi.org/10.1371/journal.pone.0135539

36. Wei XX, Stocker AA. Mutual Information, Fisher Information, and Efficient Coding. Neural

Comput. 2016; 28 (2): 305–326. https://doi.org/10.1162/NECO_a_00804

37. Xu LH, Sun Q, Stocker AA. Heading estimation from optic flow is Bayesian but strongly

modulated by the size of the experimental response range. J Vis. 2023; 23(9):5374.

https://doi.org/10.1167/jov.23.9.5374

Supporting Information

S1   Movie. Optic flow with constant speed.

S2   Movie. Optic flow with variable speed.

S3   Supplementary Fig. 1. Experiment in which participants report their perceive

headings on a line with limited ranges.

Supplementary Fig. 1. Bias and standard deviation in perceived heading direction with line-responses (N=18). The lengths of the response line are randomly selected from 80°, 111°, and 142°. The stimulus and apparatus parameter, as well as the experimental procedures are similar to those in Experiment 3. (a) Average bias of participants as function of actual heading angle (0° corresponds to straight-ahead). To capture the general tendency towards over- estimation or under-estimation, we fit a linear function to the measured bias data points (solid lines). Positive slope values indicate overestimation (peripheral bias), while a negative slope indicates underestimation (central bias). (b) Average standard deviation (SD) of heading estimates across participants as a function of actual heading direction. Red dots represent estimates reported on the circle, and black dots represent estimates reported on the line. Error bars in all plots indicate the standard error across participants. The raw data can be also downloaded from the OSF link:
https://osf.io/t47v6/?view_only=659d4bac8e4344f996eb8a51eb236d55

688 **S4   Supplementary Fig. 2. Comparison between the psychophysical prior and the neurally**

689 **extracted prior.**

690
Supplementary Fig. 2. Comparison between the psychophysical prior distribution derived from human
heading discrimination data (blue) and the neurally extracted prior from primates MSTd recording data (red).
The psychophysical prior (blue) is identical to that shown in Figure 4(c). The neurally extracted prior (red) is
constrained by the Fisher information $J(\theta)$ from previously measured neural population responses in macaque
MSTd area [8], following the approach described in [19]. Under the efficient coding assumption, the prior is
proportional to the square root of the Fisher information $\sqrt{J(\theta)}$.
697