Flawed machine-learning confounds coding sequence annotation

DJ Champion[1], Ting-Hsuan Chen[2], Susan Thomson[2], Michael A. Black[1], Paul P. Gardner[1]*

Abstract

Background: Detecting protein coding genes in genomic sequences is a significant challenge for understanding genome functionality, yet the reliability of bioinformatic tools for this task remains largely unverified. This is despite some of these tools having been available for several decades, and being widely used for genome and transcriptome annotation.

Results: We perform an assessment of nucleotide sequence and alignment-based *de novo* protein-coding detection tools. The controls we use exclude any previous training dataset and include coding exons as a positive set and length-matched intergenic and shuffled sequences as negative sets.

Our work demonstrates that several widely used tools are neither accurate nor computationally efficient for the protein-coding sequence detection problem. In fact, just three of nine tools significantly outperformed a naive scoring scheme. Furthermore, we note a high discrepancy between self-reported accuracies and the accuracy achieved in our study. Our results show that the extra dimension from conserved and variable nucleotides in alignments have a significant advantage over single sequence approaches.

Conclusions: These results highlight significant limitations in existing protein-coding annotation tools that are widely used for lncRNA annotation. This shows a need for more robust and efficient approaches to training and assessing the performance of tools for identifying protein-coding sequences. Our study paves the way for future advancements in comparative genomic approaches and we hope will popularise more robust approaches to genome and transcriptome annotation.

Keywords

Genome annotation, transcriptome, protein coding, open reading frame, ORF, benchmark

[1] *Department of Biochemistry, University of Otago, Dunedin, New Zealand.*

[2] *The New Zealand Institute for Plant and Food Research Limited, Lincoln, New Zealand.*

***Corresponding author**: paul.gardner@otago.ac.nz

Background

Annotating protein-coding regions within genomes and transcripts remains a crucial bioinformatic challenge [1, 2, 3], particularly in the context of differentiating between protein-coding and non-coding transcripts for analyzing nucleotide sequences [4, 5]. However, assessing how well preferred tools handle realistic datasets, which include truncations, sequencing, and processing errors, remains unclear [3].

In model species like *Homo sapiens*, *Mus musculus*, *Drosophila melanogaster*, and *Saccharomyces cerevisiae*, rigorous manual biocuration has significantly refined genome annotations [6, 7, 8]. For example, *H. sapiens* genome annotations have evolved from an initial estimate of 30,000 protein-coding genes to about 20,000 through decades of meticulous review, which highlights the importance of cautious interpretation of predicted annotations [9]. These annotations have been enhanced by experimental methods that detect active gene expression in specific tissues and conditions, though such methods are limited by experimental parameters and can include noisy non-functional transcription and translation signals [9, 3, 10, 11, 12].

As genome sequencing becomes more accessible, manual annotation, once considered the gold standard, has given way to automated techniques for annotating both genomes and transcriptomes [13, 3, 14, 15]. Despite extensive literature on genome annotation [16, 5, 17, 18, 2], there are few systematic evaluations of tools that differentiate coding from non-coding sequences [1, 13, 17, 19, 20]. Therefore, we think it is timely for further evaluations of genome annotation tools.

The field of genome annotation could greatly benefit from unbiased benchmarking protocols similar to those used in protein structure prediction, such as those in the Critical Assessment of Protein Structure Prediction (CASP) initiative [21]. CASP has driven advancements by promoting rigorous data collection and innovation, leading to high-accuracy tools like AlphaFold2 and RosettaFold [22, 23]. Adopting a similar framework could significantly enhance the accuracy and reliability of genome annotation tools, improving our understanding of genome function.

Software benchmarks are subject to many caveats that are the result of inevitable limitations. In spite of these caveats benchmarks serve a valuable purpose in providing an assessment of how tools perform on given datasets at a particular point in time. They can also identify performance limitations and directions where further improvements may be made. In brief, we: 1. use default parameters in each case in order to avoid inflating individual tool performance [24], 2. we may apply some tools in a manner in which they were not designed (e.g. a transcriptome tool can be applied to genomic sequences), and 3. some of the control data may be mislabelled, leading to conflicted outcomes. These caveats have been documented in detail elsewhere [25].

In this study, we evaluate the effectiveness of *de novo* coding annotation tools for eukaryotic nucleotide sequences that do not need specific training. These tools differentiate between nucleotide sequences or alignments that are either constrained by genetic codes or are non-coding. Given the distinct statistical signatures that coding sequences typically exhibit compared to non-coding ones, this task should be feasible using bioinformatic methods. The findings of this research have significant implications for the long non-coding RNA (lncRNA) research community, which heavily relies on these tools to identify non-coding transcripts [26].

Results

Tool accuracy: Some clear trends have emerged from our analysis of coding sequence detection of reference datasets. The alignment-based tools RNAcode and PhyloCSF show a clear accuracy advantage over the single sequence approaches (Figure 1A-C). This ranking holds across each accuracy measure (Area Under ROC Curve (AUC), Sensitivity, Specificity and the Matthews Correlation Coefficient (MCC)) with RNAcode consistently outperforming PhyloCSF. The tcode tool, which is an implementation of a method proposed in 1982 is not only faster, but also significantly more accurate than modern sequence-based tools.

We were particularly surprised to find that a naive tool, stopFree, that simply reports the length of the longest stop-codon-free region for a sequence, outperforms the widely used tools CPC2, PLEK, LGC and CPPred. This was a consistent finding across the performance metrics and datasets. To assess this further, we performed a permutation-based test to compare the ROC curves for each tool against the baseline stopFree tool (Figure 1B) [27]. Three tools performed significantly better than the baseline stopFree tool: RNAcode (z score= 33.2, $p = 4.3x10^{-241}$), PhyloCSF (z score= 23.1 $p = 1.3x10^{-117}$), and 1982 sequence-based tool tcode (z score= 6.1, $p = 1.01x10^{-9}$). The performances of bioseq2seq and CPC2 were not significantly better or worse than the stopFree tool. Whereas RNAsamba, CPPred, PLEK and LGC produced ROC curves that indicated a significantly worse performance than the stopFree baseline ($p < 0.05$ for each).

Self-assessment disparities: For most tools we note that there were large differences between the self-reported accuracies and the ones we calculated. While this trend has been reported previously [28], we were surprised by the degree of discrepancy (black arrows, Figure 1B & Supplementary Figure S1). The RNAcode publication reports the lowest self-reported accuracy statistics of all included tools, and yet is the most consistent with our independent accuracy measurements (Figure 1A, Supplementary Figure S1, Supplementary Table S4). All self-reported accuracy statistics for the other tools have a much larger discrepancy with our results, which are ranked by degree of disparity in Supplementary Figure S1B. The possible causes of

these discrepancies are discussed further in the conclusions.

Computational efficiency of selected tools: In terms of computational efficiency, we found that the linear, composition and sequence-based tools tcode, stopFree, LGC and PLEK shared roughly equivalent runtimes of $0.01 - 0.03$ seconds per sequence. CPPred, CPC2 and RNAcode had similar runtimes of $0.1 - 0.4$ seconds per sequence, and bioseq2seq, RNAsamba and PhyloCSF are slower tools, needing $2.0 - 50$ seconds per sequence (See Figure 1D, Supplementary Table S4). As can be seen in Supplementary Figure S2, most tools are relatively insensitive to sequence length at these length scales, with only the alignment-based methods showing a clear dependency between runtime and sequence length.

Integrity of the control data sets: For most of the tools we tested, the coding potential scores for the two negative control sets (intergenic and shuffled sequences) of each clade (Animalia, Fungi, and Plantae) are generally very consistent (Figures S4-S6), indicating that both shuffled and random intergenic regions can serve as valid negative controls for coding annotation tools, except two tools, RNAsamba and LGC.

The RNAsamba scores show a large differences between animal intergenic and shuffled sequences, with the shuffled scores being high and similar to the values for coding sequences. This suggests that RNAsamba identifies intergenic sequences rather than coding sequences when run on animal and plant derived sequences Figure S6.

The LGC scores for plant genomes have a large discrepancies between the intergenic and shuffled negative controls, which may be due to the low C+G content in plant intergenic regions. These regions received higher scores than coding sequences, as shown in Supplementary Figure S5. This suggests a flaw in the LGC model's ability to differentiate between non-coding and coding sequences with low C+G content [29].

Relationship between citations and accuracy and speed: As observed in previous studies, citations rates do not reflect the accuracy or computational efficiency of bioinformatic tools [30]. This lack of a relation can be confirmed here by comparing tool rankings from Figure 3B and Figure 1B In particular, RNAcode citations are approximately the same as two of the tools that performed barely better than a random number generator. In our hands RNAcode consistently outperforms competing tools. Meanwhile, the most highly cited, and presumably most widely used tool CPC2, performed no better than the baseline stopFree scores while being one of the least computationally efficient sequence based tools (Figures 3B & 1D).

Conclusions

Evolutionary vs single sequence tools: Our evaluation shows that tools using evolutionary conservation patterns, like RNAcode and PhyloCSF, are more accurate than those based on single sequences alone. As we continue to expand the genomic tree of life [31, 32] , the usefulness of deploying such tools across different clades will increase significantly. These tools benefit from incorporating variations in nucleotide sequences that preserve protein functions, such as synonymous changes, conservative amino acid substitutions and frame-preserving insertions and deletions. This approach not only enhances accuracy but also supports the 'selected effect' definition of functional elements [33].

The only sequence based tool, tcode, to outperform the naive stopFree score is faster and more accurate that modern sequence-based tools. These three tools (RNAcode, PhyloCSF and tcode), published in 2011, 2011, and 1982 respectively, highlight how little genuine progress in the field has been made in recent years.

Challenges and recommendations for future development: This study adhered to key principles that should guide future tool development and evaluation. This is in contrast with some current tools that overlook essential aspects of mathematical modeling such as understanding the data and its applications. We highlight three main areas for consideration:

1. Sampling controls: We used well-annotated reference eukaryotic genomes outside any training dataset for our positive controls, questioning the need for species-specific tools. Given the conservation of the genetic code and translation machinery [34, 35], more generalized coding detection tools are feasible. Moreover, coding detection tools must be robust to biological and technical deviations from standard results, including truncated sequences, splicing errors, frame-shifting elements, recoding, non-AUG starts and non-standard genetic codes [36, 37, 38, 39, 40, 35]. *2. Dataset construction:* Both positive and negative datasets must be challenging and well-matched to control confounding factors such as sequence length and C+G content. This ensures that coding sequence scores will be robust and distinct from genomic background. Using short and long ncRNAs as negative controls is insufficient (see below). *3. Dataset representation:* Evaluation datasets should mirror the typical genomic composition, which for many species includes a predominance of junk and functional non-coding sequences. Evaluation metrics must be robust against imbalanced datasets [41].

In this study, several widely used tools performed poorly in distinguishing coding from non-coding sequences, illustrating once more that software popularity does not equate to accuracy or efficiency [30]. Despite high self-reported accuracy, our independent evaluations revealed large discrepancy with measurements, suggesting the need for more rigorous validation measures (See Figures 1A and S1) [28].

Stop using highly curated datasets for training and testing: The meticulously curated mRNA sequences from RefSeq and GENCODE [42, 43] are, in our view, unsuitable as positive controls for training or testing coding annotation tools. These datasets have undergone extensive refinement over decades by many curators, and have incorporated additional experimental

Figure 1. Coding potential tools, accuracy and speeds. A: A jitter plot showing the mean Area Under ROC Curve (AUC), Sensitivity, Specificity and Matthews Correlation Coefficient (MCC) values for each software tool and clade. Tools are ordered by the median AUC (mean performance values are indicated with a tick mark for each metric and tool). The black crosses and arrows indicate the accuracy metrics reported by the authors of each tool on their own test datasets. **B:** Bar plot showing Z-score differences of each tools ROC curves from our naive stopFree tool, with notated p-values. **C:** ROC curves showing the ability of each tool to discriminate between positive coding sequences and negative unannotated, length matched genome regions, and shuffled controls. The x-axis displays 1-Specificity (false-positive rate) and the y-axis displays the Sensitivity (true-positive rate). Each tool maps a trajectory from $(0.0, 0.0)$ to $(1.0, 1.0)$ through this plane as thresholds are lowered from the maximal to minimal value values for the tool on the test data. Ideal tools pass through the point $(0.0, 1.0)$. **D:** A jitter plot showing the runtimes for each tool, measured in seconds. Runtimes were recorded by running each tool on sequences of varying lengths on an isolated computer.

data such as Ribo-seq and mass-spec to further support annotations [44, 45]. However, typical real-world datasets contain errors such as truncations, sequencing and assembly problems that can cause frame-shifts and mis-spliced transcripts (to list just a few discrepancy sources). Consequently, highly curated datasets are a trivial problem set that exaggerate the significance of inherent sequence features, such as the longest canonical ORFs. This is likely the cause of the many misclassifications by many tools in our practical assessment scenarios.

The problematic selection of negative training data sets is a further issue. We noted that either short or long ncRNAs have been used as negative datasets for training some of the above tools (see tools descriptions in the Supplementary Materials). Rfam-derived datasets are an inadequate negative control for this problem as these short non-coding RNAs have profoundly different lengths and sequence compositions compared to coding and typical genomic sequences. Furthermore, the majority of lncRNAs have been labelled lncRNAs because they have (a) some evidence of transcription, and (b) lack an obvious open reading frame [4]. Therefore, lncRNAs have shorter ORFs than random sequences and therefore are a trivial and inadequate negative control for training or testing a coding-potential prediction tool. Finally, lncRNAs have a very different length distribution relative to mRNAs, therefore trivial tools could distinguish between these transcripts using measures as simple as sequence length.

In short, the tools that underperform here excel at solving a non-existent problem in genomics: distinguishing error-free, curated coding sequences from shorter non-coding RNA sequences in model organisms with up to 99.85% accuracy.

Class balance: We noted that many tools trained and evaluated their performance on relative balanced classes of negative and positive datasets. In reality the ratio of coding to non-coding is likely to be low in eukaryotes (approximately 1 to 100 the human genome for example). In order to evaluate performance under realistic conditions we recommend that realistic positive to negative class ratios are maintained. Assessments should use metrics that are robust to class imbalance, rather than artificially attempt to balance positive and negative classes [41, 46].

Limit sequence similarity between test and training: a standard practice for applying machine learning techniques in computational biology is to ensure test and validation sets are freed of homologous or similar sequences found in the training set [47, 48, 49]. Some of the tools assessed here did not report controlling for evolutionary relationships between their training and test sets (See "tool descriptions" in the Supplementary Information), as a consequence may have artificially inflated the performance measures for their tool.

Study limitations: Firstly, this study is very eukaryote-specific, we have not assessed tools on more diverse genomic data from organelles, protists, archaeal, bacterial or viral sequences. Species that utilise novel genetic codes may prove to be a particularly challenging cohort for assessments [35].

Secondly, we have used a relatively balanced positive and negative datasets (ratios of approximately 1:3). On more representative datasets the negative datasets vastly outnumber the positive (e.g. approximately 98.5% of the genome is non-coding in human). So, ideally aim for approximately 30-50 times more negative sequences as positive to reflect realistic coding:non-coding ratios [41].

Thirdly, we have "abused" some tools by not applying them to the scenarios for which they were developed. For example, transcriptome tools that expect positive stranded and full-length ORFs in sequences free of introns. Also, our intergenic negative control regions are likely to be less well conserved than coding sequence. However, the alignment depths and percent-identity are not terribly dissimilar (Table S3), whereas the shuffled alignments have identical depth and identity. We found there was little difference in score distributions between intergenic and shuffled for the alignment-based tool results, as a consequence believe the alignments for intergenic sequence to be valid negative controls.

Finally, we have not generated more complex sequence sets for evaluation. We did not attempt to assemble full length transcripts or simulate sequencing and assembly errors found in typical genome and transcriptome datasets.

Future efforts: We have highlighted the scope for further development of tools to address the coding sequence annotation challenge. We note that the existing tools have not employed some of the latest machine-learning methods, nor do they include more complex information for conserved peptide predictions, for example the increased covariation in coding sequence alignments has been observed in recent analyses [50, 51]. We also note there has not been much work in identifying the strengths of the statistical features that contribute to predictions.

From a biocuration perspective, there has been relatively little development of the "conservome" for coding sequences, i.e. large-scale screens of conserved sequence elements with characteristic signatures of evolutionarily conserved coding sequences [52]. These screens may prove very useful for classifying alternative splicing, alternate start or stop codons, short open reading frames and other conserved non-canonical protein coding sequences.

Finally, the results presented here further highlight the need for well maintained, robust, up-to-date and accurate software. To be achieved this will require further support for long-term software maintenance and career incentives that encourage these activities [53].

Methods

Our methodology is divided into these key sections: (1) Dataset preparation, where we describe the acquisition and preparation of coding and non-coding sequences used as controls; (2) Performance measures, where we explain the methods used to analyze the results and verify the significance of our findings. (3) Tool inclusion, detailing the criteria for selecting the annotation tools evaluated in this study; and (4) Benchmarking Strategy, outlining the protocols for tool performance assessment, including accuracy, efficiency, and computational demand; These ensure a comprehensive evaluation of each tools' capabilities in distinguishing between coding from non-coding genomic sequences.

Data selection: positive & negative control sequences

To improve the assessment of software predictions for protein-coding nucleotide sequences and mitigate biases, we avoid commonly used reference genomes such as *Homo sapiens* and *Mus musculus*. We selected representative species from three eukaryotic clades (mammals, plants, and fungi) that have not previously been used in software training. These are *Felis catus* (house cat), *Cucumis melo* (melon), and *Aspergillus puulaauensis*. Further details are available in Supplementary Tables S2 and S3 and Figure 2.

Figure 2. Controls for benchmarking protein coding detection tools. A: Annotated exons of 80 to 1,200 nucleotides (nts) are selected from reference genomes, flanking 75 nts are also included with these positive control sequences. These are length-matched with genomically nearby intergenic sequences which serve as one source of negative controls. Shuffled coding sequences are used as a further source of negative control. **B-D:** Exemplar multiple sequence alignments, these include a partial exon (**B**), with corresponding negative controls from a shuffled alignment (**C**) and a neighbouring intergenic region (**D**). For alignment **B** the corresponding amino-acid(s) of each codon is shown along the top line. **E-G:** Phylogenetic trees for genomic reference and selected related genomes for producing alignments, these are the (**E**) animalia (reference: *Felis catus*), (**F**) fungi (reference: *Aspergillus puulaauensis*), and (**G**) plants (reference: *Cucumis melo*).

Up to ten further genomes that span a range of phylogenetic distances are selected for each group, these are used to construct multiple sequence alignments for the comparative tools (Table 1). Each selected genome assembly has a high BUSCO completeness score [54, 55] (Supplementary Table S3), and have numbers of annotated coding genes that is consistent with related genomes.

The positive control coding sequences are derived from GenBank annotations. We collapsed overlapping annotations and randomly sampling 1,200 coding exons from each reference genome. Further realism is introduced into the test dataset by including 75 nucleotides of intron or UTR from both sides of each exons (refer to Figure 2A). Negative control intergenic sequences of the same lengths are selected from adjacent upstream and downstream intergenic regions that exceed one kilobase (kb) in length (for summary statistics see Supplementary Table S3). The intergenic sequences are compared with protein in the UniProt database and possible coding sequences (e-value $< 10^{-10}$, bitscore > 31) were removed using translated searches with MMseqs2 (v15.6f452) [56].

Alignments for comparative tools were made for intergenic and coding sequences (Figure 2). Reference sequences are queried with MMseqs2, and top-scoring matches for each genome selected for multiple sequence alignment with Clustal Omega (1.2.4) [57]. A further negative control set is produced by shuffling coding alignments with `esl-shuffle` (Easel 0.48 (Nov 2020)).

Each of the selected prediction tools were run on both the coding and non-coding sequences or alignments. Subsequently, the optimal coding potential scores for each input for each tool were used as a basis for computing performance statistics, as defined in the below 'Performance metrics' section. For the tools that only scan the forward strand, the reverse complement of each input sequence was also screened. In instances where multiple scores are returned for a sequence (in any of the six-frames), the best score is selected (highest or lowest, depending on which is a better indicator for a coding sequence).

Performance metrics and output management

Sequences are ranked by prediction score, and a sliding threshold is used. The coding sequences that score at or above a threshold are labelled "true positives" (TP), negative control sequences at or above the threshold are "false positives" (FP), coding sequences below a threshold are "false negatives" (FN), and negative control sequences below a threshold are "true negatives" (TN). An optimal score threshold is selected for each tool based on the minimal distance to the [0.0,1.0] coordinate on the ROC plot (i.e. "closest.topleft" in the `R pROC` package). This best balances the sensitivity and specificity for each tool [58].

For each possible score threshold the *sensitivity*, *specificity* and *Matthews correlation coefficient (MCC)* are computed, these are defined below. Furthermore, a "receiver-operator characteristic" (ROC) plot is also generated for each tool (Figure 1A) using the pROC package (version 1.18.5) [58]. The "AUC" or Area Under the ROC curve is computed for each tool as a further performance measure, which we note has a theoretical range $[0.5, 1.0]$, and is robust to potential issues of class imbalance [46].

$$Sensitivity = \frac{TP}{TP+FN}, \ Specificity = \frac{TN}{TN+FP}, \ MCC = \frac{TP*TN-FP*FN}{\sqrt{(TP+FP)(TP+FN)(TN+FP)(TN+FN)}}.$$

The runtimes for each tool were collected on a standard, isolated desktop computer (Intel 12-core processor i9-8950HK, 32GB RAM) running a Linux operating system (Ubuntu 22.04.2 LTS, Linux kernel 6.2.0-36). We recorded times for predictions on 240 sequences with lengths ranging from 232 to 1114 nts. The three-frame, top-strand only tools were run on both the forward, and reverse complement sequences. The average runtimes for each tool can be viewed in Figure 1D, the dependency between sequence length and runtime can be seen in Supplementary Figure S2, average values can be viewed in Supplementary Table S4, column O.

Name	Input	Frames	Installation	Ease of Use	Outputs	Version	Reference
Single-sequence tools							
Bioseq2seq	Sequence	3	☺	😐	☹	2024-02-08	[59]
CPC2	Sequence	6	☹	😐	☺	2.0Beta	[60]
CPPred	Sequence	3	😐	☹	☹	2018-05-17	[61]
LGC	Sequence	3	😐	☹	☹	1.0	[29]
PLEK	Sequence	3	☺	☺	☹	1.2	[62]
RNAsamba	Sequence	3	☺	☺	😐	0.2.4	[63]
tcode	Sequence	6	😐	☺	😐	EMBOSS:6.6	[64, 65]
Comparative tools							
PhyloCSF	Alignment	6	☹	😐	😐	1.0.1	[66]
RNAcode	Alignment	6	☹	☺	☺	0.3	[67]

Table 1. Summary of assessed tools. We have annotated the type of input each tool requires, the number of frames they scan (frames 1-3 [fwd], or frames 1-6 [fwd+rev]), the version and references. In addition, tools have been assessed for their ease of installation on a modern *nix environment, and for their ease of use, and whether the outputs included useful information like ORF coordinates as well as scores. The categories for each were: Excellent: ☺, Acceptable: 😐, Unsatisfactory: ☹. Further details on these assessments can be found in **Supplementary Text**.

Tool inclusion criteria: In order to select tools for inclusion in the benchmark we iteratively searched the published literature (GoogleScholar, PubMed), examining previous benchmarks, software tool papers and reviews of the topic [1, 5, 19, 20]. We extracted candidate tools from the text and from the reference sections, these have been assessed against the following inclusion criteria: 1. The primary purpose of the tool is to predict protein-coding potential from nucleotide sequences or alignments, 2. The tool is publicly accessible, 3. The tool is able to be installed and is executed, 4. The tool is generalised, and not restricted to a single species or phylogenetic group, 5. The tool is unique, i.e. is not a clone or a slight modification of an existing tool, 6. The tool is **not** based on homology to known proteins, 7. The tool has been recently used, and there is evidence that it is or may be popular.

The tools that we assessed against these criteria are listed in Supplementary Table S1. A total of 36 tools were assessed and **75% (27)** did not meet at least one of the above criteria. The most common reasons for excluding a tool was the installation was unnecessarily complex or failed on a modern linux computing environment (criterion #3, 41% failed, 11/27), the tool was not generalised (criterion #4, 33%, 9/27) or was not publicly accessible (criterion #2, 26%, 9/27) (Figure 3A, Supplementary Table S1).

Brief tool descriptions

In the following section we briefly describe each of the software tools that met the above inclusion criteria for this study. See Supplementary Information for detailed information on sources of training and test data, the number of sequences used as positive and negative controls for each, whether summary statistics for each (e.g. mean length and C+G content) are reported and whether similarity between training and test datasets were accounted for.

Figure 3. Software inclusion, exclusion and popularity. A: The proportions and counts of candidate software tools (total of 36), and the reasons some tools were excluded. See text and Supplementary Table S1 for further details. **B:** The average number of citations per year for each of the included tools (citation counts were collected in March 2024 from Google Scholar).

Base-line tools

The authors of this manuscript added a naive coding potential finder "`stopFree`", and employed a random number generator "`randScore`". Both tools serve as base-line scores for a minimal and lowest expected performance in our evaluation that are free of any machine-learning based training. The simplest coding potential measure we have identified is the length of the longest in-frame stop-free region for any input sequence (i.e. the longest run of `UAA`, `UAG`, and `UGA` free sequences over each of the six possible reading frames). This value conforms with the most general definition of an ORF [68].

We expect the stopFree measure to be robust to common sequence errors and non-canonical features such as truncations, non-AUG start codons [39], mis-splicing, and many forms of sequence error [36, 40]. We anticipate that stopFree as a minimal, single-metric tool will serve as a lower bound on tool accuracy for more sophisticated tools.

Meanwhile, randScore uses a random number generator that generates integers in the range [1, 100] for any input sequence, and is expected to be the worst possible prediction tool (also known as "monkey with a pencil").

Protein coding potential tools

Various approaches were employed by the tools that were benchmarked. We briefly describe them here, while more detailed tool descriptions, discussion of their training and test datasets, sequence/alignment features, command-line parameters, installation, user experience and output notes can be found in the Supplementary Information.

For the sequence-based tools, `Bioseq2seq` [59] and `RNAsamba` [63] use neural network models. `CPC2` "Coding Potential Calculator 2" [60], `CPPred` "Coding Potential PREDiction" [61] and `PLEK` [62] utilise support vector machines. `LGC` "ORF Length and GC content" [29] employs a maximum likelihood method. `tcode` [64, 65] uses an implementation of the Fickett TESTCODE statistic which is a probabilistic method.

For the alignment-based tools, `PhyloCSF` "Phylogenetic Codon Substitution Frequencies" [66] is a maximum likelihood method, while `RNAcode` [67] is a comparative analysis tool.

Author engagement

In order to ensure methods are used correctly, a preprint of these results and methods was shared with corresponding authors for each tool. We have elected to do this in order to minimise disagreements between benchmark and method authors, and ensure that we have adequately described, and not misrepresented any tools.

Declarations

Ethics approval and consent to participate: Not applicable
Consent for publication: Not applicable
Availability of data and materials: A slim github repository for researchers who wish to use just the tool prediction scores, control sequences and alignment is available here:
`https://github.com/Gardner-BinfLab/PCPBSlim/`
The full github repository required to replicate the genome sequence sampling, shuffling and multiple sequence alignment, the scripts to run each tool, and calculate summary accuracy statistics is here:

`https://github.com/Gardner-BinfLab/PCPBFull/`

Funding: This research was supported by an MBIE smart idea PROP-61726-ENDSI-PFR (DJC, THC, ST, PPG), the MBIE data science platform "Beyond Prediction: explanatory and transparent data science" (DJC, MAB, PPG), Genomics Aotearoa (MAB, PPG), and Marsden Grants 19-UOO-040 and 20-UOA-282 (PPG).

Authors' contributions: this work was conceived by DJC, THC, ST & PPG, designed by DJC & PPG, the analysis was carried out by DJC, PPG & MAB, interpretation of the results was by DJC & PPG, the manuscript was drafted by DJC & PPG. All authors revised and edited the final manuscript. All authors approve the submitted version.

Acknowledgements: We have received valuable feedback from the Genomics Aotearoa research community. Professor Mercelo Carazzolle and Dr. Antonio Camargo for feedback on their tool, `RNAsamba`.

References

[1] James W Fickett and Chang-Shung Tung. Assessment of protein coding measures. *Nucleic acids research*, 20(24):6441–6450, 1992.

[2] Paulo Amaral, Silvia Carbonell-Sala, Francisco M De La Vega, Tiago Faial, Adam Frankish, Thomas Gingeras, Roderic Guigo, Jennifer L Harrow, Artemis G Hatzigeorgiou, Rory Johnson, et al. The status of the human gene catalogue. *Nature*, 622(7981):41–47, 2023.

[3] Daniel R Zerbino, Adam Frankish, and Paul Flicek. Progress, challenges, and surprises in annotating the human genome. *Annual review of genomics and human genetics*, 21:55–79, 2020.

[4] Jinyuan Xu, Jing Bai, Xinxin Zhang, Yanling Lv, Yonghui Gong, Ling Liu, Hongying Zhao, Fulong Yu, Yanyan Ping, Guanxiong Zhang, et al. A comprehensive overview of lncRNA annotation resources. *Briefings in bioinformatics*, 18(2):236–249, 2017.

[5] Jing Li, Xuan Zhang, and Changning Liu. The computational approaches of lncRNA identification based on coding potential: status quo and challenges. *Computational and Structural Biotechnology Journal*, 18:3666–3677, 2020.

[6] Adam Frankish, Sílvia Carbonell-Sala, Mark Diekhans, Irwin Jungreis, Jane E Loveland, Jonathan M Mudge, Cristina Sisu, James C Wright, Carme Arnan, If Barnes, et al. GENCODE: reference annotation for the human and mouse genomes in 2023. *Nucleic acids research*, 51(D1):D942–D949, 2023.

[7] Aoife Larkin, Steven J Marygold, Giulia Antonazzo, Helen Attrill, Gilberto Dos Santos, Phani V Garapati, Joshua L Goodman, L Sian Gramates, Gillian Millburn, Victor B Strelets, et al. FlyBase: updates to the Drosophila melanogaster knowledge base. *Nucleic acids research*, 49(D1):D899–D907, 2021.

[8] Stacia R Engel, Edith D Wong, Robert S Nash, Suzi Aleksander, Micheal Alexander, Eric Douglass, Kalpana Karra, Stuart R Miyasato, Matt Simison, Marek S Skrzypek, et al. New data and collaborations at the Saccharomyces Genome Database: updated reference genome, alleles, and the Alliance of Genome Resources. *Genetics*, 220(4):iyab224, 2022.

[9] Klas Hatje, Stefanie Mühlhausen, Dominic Simm, and Martin Kollmar. The protein-coding human genome: Annotating high-hanging fruits. *BioEssays*, 41(11):1900066, 2019.

[10] Alexander F Palazzo and Eliza S Lee. Non-coding RNA: what is functional and what is junk? *Frontiers in genetics*, 6:2, 2015.

[11] Jonathan M Mudge, Jorge Ruiz-Orera, John R Prensner, Marie A Brunet, Ferriol Calvet, Irwin Jungreis, Jose Manuel Gonzalez, Michele Magrane, Thomas F Martinez, Jana Felicitas Schulz, et al. Standardized annotation of translated open reading frames. *Nature biotechnology*, 40(7):994–999, 2022.

[12] Yi Qiu Alexander F. Palazzo and Yoon Mo Kang. mRNA nuclear export: how mRNA identity features distinguish functional RNAs from junk transcripts. *RNA Biology*, 21(1):1–12, 2024. PMID: 38091265.

[13] Roderic Guigó, Paul Flicek, Josep F Abril, Alexandre Reymond, Julien Lagarde, France Denoeud, Stylianos Antonarakis, Michael Ashburner, Vladimir B Bajic, Ewan Birney, et al. EGASP: the human ENCODE genome annotation assessment project. *Genome biology*, 7:1–31, 2006.

[14] Lincoln Stein. Genome annotation: from sequence to biology. *Nature reviews genetics*, 2(7):493–503, 2001.

[15] Y Amy Tang, Klemens Pichler, Anja Füllgrabe, Jane Lomax, James Malone, Monica C Munoz-Torres, Drashtti V Vasant, Eleanor Williams, and Melissa Haendel. Ten quick tips for biocuration. *PLoS computational biology*, 15(5):e1006906, 2019.

[16] Holly R Pinkney, Brandon M Wright, and Sarah D Diermeier. The lncRNA toolkit: databases and in silico tools for lncRNA analysis. *Non-coding RNA*, 6(4):49, 2020.

[17] Christopher Klapproth, Rituparno Sen, Peter F Stadler, Sven Findeiß, and Jörg Fallmann. Common features in lncRNA annotation and classification: a survey. *Non-coding RNA*, 7(4):77, 2021.

[18] Kiran Dindhoria, Isha Monga, and Amarinder Singh Thind. Computational approaches and challenges for identification and annotation of non-coding RNAs using RNA-Seq. *Functional & Integrative Genomics*, 22(6):1105–1112, 2022.

[19] Hansi Zheng, Amlan Talukder, Xiaoman Li, and Haiyan Hu. A systematic evaluation of the computational tools for lncRNA identification. *Briefings in Bioinformatics*, 22(6):bbab285, 2021.

[20] Dalwinder Singh and Joy Roy. A large-scale benchmark study of tools for the classification of protein-coding and non-coding RNAs. *Nucleic Acids Research*, 50(21):12094–12111, 2022.

[21] Andriy Kryshtafovych, Torsten Schwede, Maya Topf, Krzysztof Fidelis, and John Moult. Critical assessment of methods of protein structure prediction (CASP)—Round XIV. *Proteins: Structure, Function, and Bioinformatics*, 89(12):1607–1617, 2021.

[22] John Jumper, Richard Evans, Alexander Pritzel, Tim Green, Michael Figurnov, Olaf Ronneberger, Kathryn Tunyasuvunakool, Russ Bates, Augustin Žídek, Anna Potapenko, et al. Highly accurate protein structure prediction with AlphaFold. *Nature*, 596(7873):583–589, 2021.

[23] Minkyung Baek, Frank DiMaio, Ivan Anishchenko, Justas Dauparas, Sergey Ovchinnikov, Gyu Rie Lee, Jue Wang, Qian Cong, Lisa N Kinch, R Dustin Schaeffer, et al. Accurate prediction of protein structures and interactions using a three-track neural network. *Science*, 373(6557):871–876, 2021.

[24] Christina Nießl, Moritz Herrmann, Chiara Wiedemann, Giuseppe Casalicchio, and Anne-Laure Boulesteix. Over-optimism in benchmark studies and the multiplicity of design and analysis options when interpreting their results. *Wiley Interdisciplinary Reviews: Data Mining and Knowledge Discovery*, 12(2):e1441, 2022.

[25] Lukas M Weber, Wouter Saelens, Robrecht Cannoodt, Charlotte Soneson, Alexander Hapfelmeier, Paul P Gardner, Anne-Laure Boulesteix, Yvan Saeys, and Mark D Robinson. Essential guidelines for computational method benchmarking. *Genome biology*, 20:1–12, 2019.

[26] Chris P Ponting and Wilfried Haerty. Genome-wide analysis of human long noncoding RNAs: a provocative review. *Annual review of genomics and human genetics*, 23:153–172, 2022.

[27] ES Venkatraman. A permutation test to compare receiver operating characteristic curves. *Biometrics*, 56(4):1134–1138, 2000.

[28] Stefan Buchka, Alexander Hapfelmeier, Paul P Gardner, Rory Wilson, and Anne-Laure Boulesteix. On the optimistic performance evaluation of newly introduced bioinformatic methods. *Genome biology*, 22(1):152, 2021.

[29] Guangyu Wang, Hongyan Yin, Boyang Li, Chunlei Yu, Fan Wang, Xingjian Xu, Jiabao Cao, Yiming Bao, Liguo Wang, Amir A Abbasi, et al. Characterization and identification of long non-coding RNAs based on feature relationship. *Bioinformatics*, 35(17):2949–2956, 2019.

[30] P P Gardner, J M Paterson, S McGimpsey, F Ashari-Ghomi, S U Umu, A Pawlik, A Gavryushkin, and M A Black. Sustained software development, not number of citations or journal choice, is indicative of accurate bioinformatic software. *Genome Biol*, 23(1):56, Feb 2022.

[31] Matthew J Christmas, Irene M Kaplow, Diane P Genereux, Michael X Dong, Graham M Hughes, Xue Li, Patrick F Sullivan, Allyson G Hindle, Gregory Andrews, Joel C Armstrong, et al. Evolutionary constraint and innovation across hundreds of placental mammals. *Science*, 380(6643):eabn3943, 2023.

[32] Lukas FK Kuderna, Jacob C Ulirsch, Sabrina Rashid, Mohamed Ameen, Laksshman Sundaram, Glenn Hickey, Anthony J Cox, Hong Gao, Arvind Kumar, Francois Aguet, et al. Identification of constrained sequence elements across 239 primate genomes. *Nature*, pages 1–8, 2023.

[33] Stefan Linquist, W Ford Doolittle, and Alexander F Palazzo. Getting clear about the f-word in genomics. *PLoS genetics*, 16(4):e1008702, 2020.

[34] Anton S Petrov, Burak Gulen, Ashlyn M Norris, Nicholas A Kovacs, Chad R Bernier, Kathryn A Lanier, George E Fox, Stephen C Harvey, Roger M Wartell, Nicholas V Hud, et al. History of the ribosome and the origin of translation. *Proceedings of the National Academy of Sciences*, 112(50):15396–15401, 2015.

[35] Yekaterina Shulgina and Sean R Eddy. A computational screen for alternative genetic codes in over 250,000 genomes. *Elife*, 10:e71402, 2021.

[36] Tamara Steijger, Josep F Abril, Pär G Engström, Felix Kokocinski, Tim J Hubbard, Roderic Guigó, Jennifer Harrow, and Paul Bertone. Assessment of transcript reconstruction methods for RNA-seq. *Nature methods*, 10(12):1177–1184, 2013.

[37] Joseph K Pickrell, Athma A Pai, Yoav Gilad, and Jonathan K Pritchard. Noisy splicing drives mRNA isoform diversity in human cells. *PLoS genetics*, 6(12):e1001236, 2010.

[38] Heidi Dvinge and Robert K Bradley. Widespread intron retention diversifies most cancer transcriptomes. *Genome medicine*, 7:1–13, 2015.

[39] Dmitry E Andreev, Gary Loughran, Alla D Fedorova, Maria S Mikhaylova, Ivan N Shatsky, and Pavel V Baranov. Non-AUG translation initiation in mammals. *Genome Biology*, 23(1):111, 2022.

[40] Marina V Rodnina, Natalia Korniy, Mariia Klimova, Prajwal Karki, Bee-Zen Peng, Tamara Senyushkina, Riccardo Belardinelli, Cristina Maracci, Ingo Wohlgemuth, Ekaterina Samatova, et al. Translational recoding: canonical translation mechanisms reinterpreted. *Nucleic acids research*, 48(3):1056–1067, 2020.

[41] Sean Whalen, Jacob Schreiber, William S Noble, and Katherine S Pollard. Navigating the pitfalls of applying machine learning in genomics. *Nature Reviews Genetics*, 23(3):169–181, 2022.

[42] Adam Frankish, Mark Diekhans, Irwin Jungreis, Julien Lagarde, Jane E Loveland, Jonathan M Mudge, Cristina Sisu, James C Wright, Joel Armstrong, If Barnes, et al. GENCODE 2021. *Nucleic acids research*, 49(D1):D916–923, 2021.

[43] Bhanu Rajput, Kim D Pruitt, and Terence D Murphy. RefSeq curation and annotation of stop codon recoding in vertebrates. *Nucleic acids research*, 47(2):594–606, 2019.

[44] Nuala A O'Leary, Mathew W Wright, J Rodney Brister, Stacy Ciufo, Diana Haddad, Rich McVeigh, Bhanu Rajput, Barbara Robbertse, Brian Smith-White, Danso Ako-Adjei, et al. Reference sequence (RefSeq) database at NCBI: current status, taxonomic expansion, and functional annotation. *Nucleic acids research*, 44(D1):D733–D745, 2016.

[45] Eric W Sayers, Mark Cavanaugh, Karen Clark, Kim D Pruitt, Stephen T Sherry, Linda Yankie, and Ilene Karsch-Mizrachi. GenBank 2024 update. *Nucleic Acids Research*, 52(D1):D134–D137, 2024.

[46] Matthew McDermott, Lasse Hyldig Hansen, Haoran Zhang, Giovanni Angelotti, and Jack Gallifant. A Closer Look at AUROC and AUPRC under Class Imbalance. *arXiv preprint arXiv:2401.06091*, 2024.

[47] Johannes Söding and Michael Remmert. Protein sequence comparison and fold recognition: progress and good-practice benchmarking. *Current opinion in structural biology*, 21(3):404–411, 2011.

[48] Ian Walsh, Gianluca Pollastri, and Silvio CE Tosatto. Correct machine learning on protein sequences: a peer-reviewing perspective. *Briefings in bioinformatics*, 17(5):831–840, 2016.

[49] Samantha Petti and Sean R Eddy. Constructing benchmark test sets for biological sequence analysis using independent set algorithms. *PLOS Computational Biology*, 18(3):e1009492, 2022.

[50] Helena B Cooper and Paul P Gardner. Features of functional human genes. *bioRxiv*, pages 2020–10, 2020.

[51] William Gao, Ann Yang, and Elena Rivas. Thirteen dubious ways to detect conserved structural RNAs. *IUBMB life*, 75(6):471–492, 2023.

[52] Jonathan M Mudge, Irwin Jungreis, Toby Hunt, Jose Manuel Gonzalez, James C Wright, Mike Kay, Claire Davidson, Stephen Fitzgerald, Ruth Seal, Susan Tweedie, et al. Discovery of high-confidence human protein-coding genes and exons by whole-genome PhyloCSF helps elucidate 118 GWAS loci. *Genome Research*, 29(12):2073–2087, 2019.

[53] Adam Siepel. Challenges in funding and developing genomic software: roots and remedies. *Genome biology*, 20(1):147, 2019.

[54] Felipe A Simão, Robert M Waterhouse, Panagiotis Ioannidis, Evgenia V Kriventseva, and Evgeny M Zdobnov. BUSCO: assessing genome assembly and annotation completeness with single-copy orthologs. *Bioinformatics*, 31(19):3210–3212, 2015.

[55] Mosè Manni, Matthew R Berkeley, Mathieu Seppey, Felipe A Simão, and Evgeny M Zdobnov. BUSCO update: novel and streamlined workflows along with broader and deeper phylogenetic coverage for scoring of eukaryotic, prokaryotic, and viral genomes. *Molecular biology and evolution*, 38(10):4647–4654, 2021.

[56] Martin Steinegger and Johannes Söding. MMseqs2 enables sensitive protein sequence searching for the analysis of massive data sets. *Nature biotechnology*, 35(11):1026–1028, 2017.

[57] Fabian Sievers, Andreas Wilm, David Dineen, Toby J Gibson, Kevin Karplus, Weizhong Li, Rodrigo Lopez, Hamish McWilliam, Michael Remmert, Johannes Söding, et al. Fast, scalable generation of high-quality protein multiple sequence alignments using Clustal Omega. *Molecular systems biology*, 7(1):539, 2011.

[58] Xavier Robin, Natacha Turck, Alexandre Hainard, Natalia Tiberti, Frédérique Lisacek, Jean-Charles Sanchez, and Markus Müller. pROC: an open-source package for R and S+ to analyze and compare ROC curves. *BMC bioinformatics*, 12:1–8, 2011.

[59] Joseph D Valencia and David A Hendrix. Improving deep models of protein-coding potential with a Fourier-transform architecture and machine translation task. *bioRxiv*, pages 2023–04, 2023.

[60] Yu-Jian Kang, De-Chang Yang, Lei Kong, Mei Hou, Yu-Qi Meng, Liping Wei, and Ge Gao. CPC2: a fast and accurate coding potential calculator based on sequence intrinsic features. *Nucleic acids research*, 45(W1):W12–W16, 2017.

[61] Xiaoxue Tong and Shiyong Liu. CPPred: coding potential prediction based on the global description of RNA sequence. *Nucleic acids research*, 47(8):e43–e43, 2019.

[62] Aimin Li, Junying Zhang, and Zhongyin Zhou. PLEK: a tool for predicting long non-coding RNAs and messenger RNAs based on an improved k-mer scheme. *BMC bioinformatics*, 15:1–10, 2014.

[63] Antonio P Camargo, Vsevolod Sourkov, Gonçalo A G Pereira, and Marcelo F Carazzolle. RNAsamba: neural network-based assessment of the protein-coding potential of RNA sequences. *NAR genomics and bioinformatics*, 2(1):lqz024, 2020.

[64] James W Fickett. Recognition of protein coding regions in DNA sequences. *Nucleic acids research*, 10(17):5303–5318, 1982.

[65] Peter Rice, Ian Longden, and Alan Bleasby. EMBOSS: the European molecular biology open software suite. *Trends in genetics*, 16(6):276–277, 2000.

[66] Michael F Lin, Irwin Jungreis, and Manolis Kellis. PhyloCSF: a comparative genomics method to distinguish protein coding and non-coding regions. *Bioinformatics*, 27(13):i275–i282, 2011.

[67] Stefan Washietl, Sven Findeiß, Stephan A Müller, Stefan Kalkhof, Martin Von Bergen, Ivo L Hofacker, Peter F Stadler, and Nick Goldman. RNAcode: robust discrimination of coding and noncoding regions in comparative sequence data. *Rna*, 17(4):578–594, 2011.

[68] Patricia Sieber, Matthias Platzer, and Stefan Schuster. The definition of open reading frame revisited. *Trends in Genetics*, 34(3):167–170, 2018.

A   Tool performance

C   ROC curves across all clades

Sensitivity — 1 − Specificity

- RNAcode
- PhyloCSF
- tcode
- bioseq2seq
- stopFree
- CPC2
- RNAsamba
- PLEK
- CPPred
- LGC
- randScore

D   Execution time

A Intergenic, negative control   Coding exons 80–1,200 nts   Intergenic, negative control

75 nts non-coding flank   75 nts non-coding flank

B Positive set: coding sequence

Coding seq V   P   P   +C/H/R H/R I/V G   V   F   L

Felis   GTC CCT CCC --- CAT ATT GGG GTT TTC CTA
Mustela   GTT CCT CCC TGT CGT ATT GGG GTT TTC CTT
Equus   GTT CCT CCC CAT CGT GTT GGG GTT TTC CTA
Tursiops GTG CCC CCC TCG CCG AAT TGG GGG TGT CTT TA

C Negative set: shuffled alignment

Felis   -G-TAGCTACATTGCCCCGCGATTCTTC-T
Mustela   TGGTAGTTACTTTGCCCCGCGGTTCTTCTT
Equus   CGATGGTTACATTGCCCCGCGGTTCTTCTT
Tursiops CGGCAGGTACATTGCCCTGCGGAGCTTTCT

D Negative set: intergenic alignment

Felis   CTTATTCTATTTATAGGTCTGATT----CT
Mustela   CTTGTTCTCTGTATGTATAGGTCTGATTCT
Equus   TTTGTTCTCTGTATCTATGAGTCTGTTTCT
Tursiops TTTGTTCTCTGTATCTATGAGTCTGTTTCT

E
Felis catus
Prionailurus bengalensis
Felis chaus
Panthera tigris
Mustela erminea
Tursiops truncatus
Equus caballus
Epinephelus fuscoguttatus
Anopheles funestus
Kluyveromyces lactis

F
Aspergillus puulaauensis
Aspergillus sydowii
Aspergillus versicolor
Aspergillus nidulans
Aspergillus mulundensis
Aspergillus luchuensis
Aspergillus niger
Aspergillus campestris
Fusarium culmorum
Ustilago bromivora
Kluyveromyces lactis

G
Cucumis melo
Cucumis sativus
Benincasa hispida
Curcurbita pepo
Prunus persica
Cicer arietinum
Solanum pennellii
Nicotiana attenuata
Nymphaea colorata
Oryza sativa
Brachypodium distachyon

A Number of included tools & exclusion reasons

B Average citations per year
(Google Scholar, 2024)