Connection Building Method: High-Accuracy MicroRNA Target Prediction Using Disease Semantic Strings

Baiming CHEN[*1,2] and Hsi-Yuan Huang[†3]

[1]School of Medicine, The Chinese University of Hong Kong, Shenzhen, Longgang District, Shenzhen, Guangdong Province 518172, China
[2]Shenzhen X-Institute, Shenzhen, China

May 17, 2024

Abstract

MicroRNAs (miRNAs) are non-coding RNAs approximately 22 nucleotides in length. miRNAs regulate gene expression by binding to target mRNAs, inhibiting translation, or promoting mRNA degradation. miRNAs are of great importance in the development of disease. So far, a variety of miRNA prediction tools have been available, which are able to identify and predict miRNA sequences and their target genes, providing key support for studying miRNA regulatory networks, resolving disease mechanisms and developing potential therapeutic strategies. In this paper, we propose a unique prediction approach that predicts miRNA-gene relationships based on the disease semantic strings of miRNAs and their potential target genes, named MicroRNA-Gene Connection Building Method. The method was trained on more than 1,900 pairs of experimental and predictive data consisting of 10 cancer-related genes and evaluated using stratified cross-validation (StratifiedKFold) with a model accuracy of more than 90%. Subsequently, we used this model to classify 10 genes related to immunity and inflammation with a classification accuracy of over 85%.

1 Introduction

In 1993, miRNA (Lin-4) was first discovered in humans and found to be critical for the timing of embryonic development in C. elegans [1]. Since then, a large number of miRNAs have been discovered with the development of high-throughput sequencing, bioinformatics, and other technologies [2]. microRNAs (miRNAs) belong to small ncRNAs, and miRNAs play a key role in regulating many physiological processes, such as cell cycle [3], cell growth, development, differentiation, and apoptosis [4], as well as pathological processes such as those associated with various

---

[*]Corresponding author: `baimingchen@link.cuhk.edu.cn`
[†]First corresponding author: `huanghsiyuan@cuhk.edu.cn`

cancers [5]. In addition, miRNAs may be promising biomarker candidates for early detection or prognosis of various diseases [6].

Sentence-BERT (SBERT) fine-tunes BERT using siamese and triple network structures and is an extension of the BERT (Bidirectional Encoder Representations from Transformers) model. SBERT achieves good results in semantic similarity tasks [7]. The SBERT has faster speed compared to BERT [8] and RoBERTa [9] while maintaining accuracy.

There are many existing miRNA prediction tools, such as miRDB [10], relies on machine learning and predicts human miRNA targets based on experimental data, TargetScan [11], predicts based on seed match and conservativeness analysis, and miRanda [12], predicts based on the free energy of sequence matching. In this paper, we propose a prediction method based on the Sentence-BERT model to predict miRNA-gene relationships by miRNA and gene disease semantic similarity. We selected 10 genes(TP53, PTEN, KRAS, BCL2, FOXO3, KIF2C, PLK1, CENPA, MYC, STAT3) to test the model, which are strongly linked to cancer [13–22]. The miRNAs corresponding to functional interaction with experiment verify for each gene, and the miRNAs predicted from the miRDB were input into the model, 1932 scores were obtained by model. The distribution of scores is shown in the box plot below, and the model has excellent performance.

Figure 1: Score distribution for 10 cancer-related genes

2 Method

2.1 Fine tuning model

We downloaded the MeSH descriptors(https://www.nlm.nih.gov/mesh) from the National Library of Medicine and selected category C (diseases). In order to calculate the similarity between different disease codes, after trying many methods, we designed and implemented a method that yields a distribution of values that is similar to the distribution of semantic similarity values output by the sentiment-transformers/multi-qa-MiniLM-L6-cos-v1 [23] model without fine-tuning. Both distribution types are log normal. The specific methods are as follows:

- Determine the depth of the lowest common ancestor (LCA):

$$D_{\text{LCA}} = \text{find\_lca\_depth}(\text{code1}, \text{code2}) \tag{1}$$

- Calculate the depth of each disease code:

$$D_1 = \text{len}(\text{code1.split('.')}) \tag{2}$$

$$D_2 = \text{len}(\text{code2.split('.')}) \tag{3}$$

- Calculate the maximum depth and total depth:

$$D_{\text{max}} = \max(D_1, D_2) \tag{4}$$

$$D_{\text{total}} = D_1 + D_2 - D_{\text{LCA}} \tag{5}$$

- Calculate the base similarity:

$$\text{similarity} = \frac{D_{\text{LCA}}}{D_{\text{total}}} \tag{6}$$

- Calculate the weighted similarity:

$$\text{weighted\_similarity} = \text{similarity}^{1+\left(\frac{D_{\text{LCA}}^{\text{DecayFactor}}}{D_{\text{total}}}\right)} \tag{7}$$

Here we have chosen the decay factor to be 0.8. Based on the formula, we can calculate the similarity between C18.452.648.398.500.440 Hypobetalipoproteinemias and C18.452.648.398.500.440 Abetalipoproteinemia as 0.781542212457061. The distribution of similarity was transformed so that the distribution type matches the distribution type of the same disease string entered into the model 'multi-qa-MiniLM-L6-cos-v1'. Fine-tune the 'multi-qa-MiniLM-L6-cos-v1' model with this dataset. We then tested the fine-tuned model using the BIOSSES dataset, a dataset for evaluating biomedical text similarity measures. BIOSSES contains 100 pairs of biomedical statements, each with human-annotated similarity scores [24]. On this dataset, the 'Connection Building Method' model achieves good performance, demonstrating that after fine-tuning with MeSH disease data, the model retains the original pattern while learning new data.

The model has been uploaded to hugging face and named 'Connection Building Method', after the article is accepted by bioXriV, the model will be switched from private to public mode.

2.2 Model Design

We propose an algorithm to compare the similarity of two lists of functions. The algorithm combines string clustering and semantic string similarity calculation to evaluate the overall similarity between disease lists by calculating the average similarity between list elements or the similarity of clustered elements.

2.2.1 Semantic Coding and Similarity Calculation

First, each string in the list is encoded using the Sentence-BERT model. The similarity between two semantic vectors is obtained by calculating the cosine similarity:

$$\text{Cosine Similarity} = \frac{\vec{A} \cdot \vec{B}}{\|\vec{A}\|\|\vec{B}\|}$$

Figure 2: Scores from Connection Building Method vs. Human Scores on BIOSSES Dataset

2.2.2 Clustering

For each element in list 1, the similarity to all elements in list 2 is calculated using the previously trained model. If the similarity is greater than a threshold, the two elements are considered to be of the same class; otherwise, the element is considered as a new class. After the traversal is completed, the elements in each class are traversed to find the element with the highest similarity sum as the center of the class.

$$c^* = \arg \max_{c \in C} \sum_{e \in C, e \neq c} \text{Cosine Similarity}(\vec{v_c}, \vec{v_e})$$

where $\vec{v_c}$ and $\vec{v_e}$ represent the semantic vectors of elements c and e respectively, and Cosine Similarity$(\vec{v_c}, \vec{v_e})$ is the cosine similarity between these vectors.

2.2.3 Evaluation of Clustering Results

For the result after clustering, if the number of successfully clustered(successful clustering is defined that the elements within the cluster are not a subset of list 1 or list 2) clusters is greater than n(in this paper, we chose n=5), accumulate the average similarity within each cluster and divide by the number of successful clusters:

$$\text{Average Similarity}_{\text{cluster}} = \frac{1}{|C|} \sum_{(i, j) \text{ in } C} \text{Cosine Similarity}(\vec{v_i}, \vec{v_j})$$

where C denotes all pairwise elements within a cluster, and $\vec{v_i}$ and $\vec{v_j}$ represent the semantic vectors of the i-th and j-th elements, respectively.

If the number of successfully clustered clusters is less than n, the average similarity between all elements is calculated:

$$\text{Average Similarity}_{\text{overall}} = \frac{1}{|\text{Pairs}|} \sum_{(i, j) \text{ in Pairs}} \text{Cosine Similarity}(\vec{v_i}, \vec{v_j})$$

where Pairs represents all pairwise elements.

2.2.4 Overall similarity measure

Ultimately, the value obtained from the above calculation is used as a measure of overall similarity between the two lists.With these steps, we are able to efficiently assess the semantic similarity between two function lists and thus the relevance between miRNAs and diseases.

2.3 Data Process

In the data preprocessing step, we used four databases, miRTarbase [25], miRWalk [26], HMDD [27] and DisGeNet [28]. miRTarbase provides experimentally validated miRNA-gene pairs. miRWalk provides predicted miRNA-gene pairs. HMDD provides microRNA-related disease data. DisGeNet provides gene-related disease data. Here, we processed the miRTarbase data by merging the -3p and -5p of the same miRNA, which are considered as the same microRNA, in order to match with the HMDD database.

We downloaded disease data related to 10 genes (TP53, PTEN, KRAS, BCL2, FOXO3, KIF2C, PLK1, CENPA, MYC, STAT3) from DisGeNET and chose the top 40 diseases with the highest scores for each gene to make up the gene's associated disease semantic string list.

Next, we searched for the miRNAs corresponding to these 10 genes in miRTarBase and miRWalk, respectively, and obtained the list of related disease semantic strings for the miRNAs in the HMDD database. To filter the data from miRWalk, we set the following conditions: the prediction score is greater than 0.5, and the binding region is limited to the 3'UTR, in order to provide predictive data that is as inaccurate as possible, treating as Non-functional MTI data. In addition, to ensure the reasonableness of the data, we restricted the number of miRNAs from miRWalk to be at most twice as many as those from miRTarBase. This is because if both were of the same size (i.e., 1:1 ratio), we would have difficulty in accurately distinguishing the difference between the predicted data and the experimental data (we assumed that the accuracy of the prediction database was any value between 0 and 1). Since the prediction database may contain both Functional MTIs and Non-Functional MTIs, by increasing the size of the prediction data we are able to more clearly distinguish the difference between the scores of Functional MTIs and Non-Functional MTIs.

3 Result

Based on these 10 genes, the model outputs a total of 1932 data, of which 250 are labelled with 'Functional MTI', 394 are labelled with 'Functional MTI (Weak)' and 1288 are labelled with 'miRWalk'. Our classification using SVM on datasets with different levels of outlier removal shows impressive accuracy. The specific results are as follows:

1. **After removing the top and bottom 5% outliers for each gene**, the model achieved an accuracy of 82%.

2. **After removing the top and bottom 10% outliers for each gene**, the model's accuracy further increased to 90%.

3. **After removing the top and bottom 20% outliers for each gene**, the model achieved an accuracy of 98%.

To assess the performance of the model, we used the `StratifiedKFold` method for cross-validation with data after removing the top and bottom 10% outliers for each gene with the fold value set to 5. On each fold, we calculated the AUC (area under the curve) value of the ROC curve. The AUC values for each fold are as follows:

- Fold 1: 0.84

- Fold 2: 0.94

- Fold 3: 0.90

- Fold 4: 0.91

- Fold 5: 0.90

The average AUC value is 0.90 with a standard deviation of 0.03. This indicates that the model performs consistently well across different data subsets with high stability and reliability. (The decision boundary for SVM classifier is 0.48705359.)

Figure 3: ROC Curve of Model

Figure 4: Each Gene Score Distribution

In, addition, we plotted each of the 10 genes individually and the images are as follows, we found that there are miRNA-gene pairings with strong experimental validation (validated by Reporter Assay or Western blot or qPCR), and weak experimental validation (validated by Microarray, NGS and other methods) and pure

predictive database (miRWalk) miRNA-gene pairings, the score intervals of these three types of data are from high to low. The resulting distribution of the 10 genes basically matches biological evidence.

4 Discussion

In this paper, we propose a Connection Building Method for predicting miRNA-gene relationships. the method is based on semantic list similarity computation of miRNAs and gene-related diseases to obtain miRNA-gene relationship scores. The results of this experiment and the testing of the model on the BIOSSES dataset show that the Natural Language Processing (NLP) method performs excellently in the biomedical domain, demonstrating that the semantic similarity algorithm is still highly accurate when dealing with specific biomedical vocabularies.

But here, we also have a question whether only cancer-related genes have such a pattern. So we additionally selected 10 genes related to immune and inflammatory pathways, namely TNF, IL6, TGFB1, IL1B, IL10, IL17A, MMP9, CRP, TLR4, NLRP3 [29–38]. 342 miRNA gene pairwise scores were found using the Connection Building Method. The SVM classification model for cancer-related genes was used to classify these 342 sets of data, and after removing 10% outliers above and below each gene, the model achieved 86% accuracy. This suggests a high likelihood that the pattern is generalizable.

Figure 5: Confusion Matrix of Immunity- and Inflammation-related miRNA-gene Pairing Classification Result

The most important point is that we think that the actual accuracy of the model must exceed what we have gotten so far because we consider all the low threshold

data from the prediction database to be Non-Functional MTI. In fact, according to the box plot, it is clear that there are some data distributions from miRWalk that are in the Functional MTI interval. This also coincides with the fact that the predicted data has some accuracy. So we think these miRNA gene relationships may have Functional MTI. But further confirmation can only be done by experimental methods.

In addition, we think that the results show that there may be a very strong correlation between miRNAs and diseases, so that such a high level of accuracy can be achieved simply by calculating the semantic string similarity of diseases. However, there are still some limitations. Although the method shows a consistent scoring trend in more than 2000 samples, more validation is still needed to turn the present phenomenon into a general rule, including validation of more genetic data.

5 Perspective

The Connetion Building Method has promising scalability and can also be used to calculate the disease semantic similarity between other biomolecules as a way to explore the interactions between biomolecules. For example, except for the physical and chemical property prediction tools, the Connection Building Method can also provide data based on the disease semantic similarity dimension to optimise the prediction model. In addition, this method can also be used to calculate the functional semantic similarity between biomolecules. Prospectively, we propose an application prospect whereby a large amount of miRNA-related disease data can be obtained by performing miRNA profiling on diseased tissue samples from clinical patients. A similar approach can also be used to obtain gene expression data. Using this method, it may be possible to build a prediction network with high accuracy, which is expected to provide strong support for future diagnosis and treatment.

Declarations

Funding

This research was partially funded by the Shenzhen X-institute ESRT Scholarship.

Conflicts of interest

The authors declare that they have no conflicts of interest.

Availability of data and materials

The datasets generated during and/or analyzed during the current study are available from the corresponding author on reasonable request. The scores for the 20 genes have been uploaded to the attachment. All the source code will be made publicly available after the paper is accepted by the journal.

Acknowledgements

I would like to thank Dr.Xiang for his valuable discussions and insights. My conversation with him inspired me to continue this project, which I had almost

given up on. Thanks Dr.Huang for letting me get to know about miRNA Target prediction, which is really fascinating. Thank you X-institute for changing my life. Last but not least, I want to thank the people around me, my family and friends who have always supported me. My work wouldn't go so well without your guys.

Patent

A patent application related to the work presented in this paper has been filed Patent Application No.202410559682.3 Title: 基于文本的MicroRNA和基因关系挖掘方法、装置、设备及介质

References

[1] Rosalind C Lee, Rhonda L Feinbaum, and Victor Ambros. The c. elegans heterochronic gene lin-4 encodes small rnas with antisense complementarity to lin-14. *cell*, 75(5):843–854, 1993.

[2] Marieke Van Kouwenhove, Martijn Kedde, and Reuven Agami. Microrna regulation by rna-binding proteins and its implications for cancer. *Nature Reviews Cancer*, 11(9):644–656, 2011.

[3] Michael Carleton, Michele A Cleary, and Peter S Linsley. Micrornas and cell cycle regulation. *Cell cycle*, 6(17):2127–2132, 2007.

[4] Angie M Cheng, Mike W Byrom, Jeffrey Shelton, and Lance P Ford. Antisense inhibition of human mirnas and indications for an involvement of mirna in cell growth and apoptosis. *Nucleic acids research*, 33(4):1290–1297, 2005.

[5] Meredith Hill and Nham Tran. mirna interplay: mechanisms and consequences in cancer. *Disease models & mechanisms*, 14(4):dmm047662, 2021.

[6] Colin C Pritchard, Heather H Cheng, and Muneesh Tewari. Microrna profiling: approaches and considerations. *Nature Reviews Genetics*, 13(5):358–369, 2012.

[7] Nils Reimers and Iryna Gurevych. Sentence-bert: Sentence embeddings using siamese bert-networks. *arXiv preprint arXiv:1908.10084*, 2019.

[8] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.

[9] Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. Roberta: A robustly optimized bert pretraining approach. *arXiv preprint arXiv:1907.11692*, 2019.

[10] Yuhao Chen and Xiaowei Wang. mirdb: an online database for prediction of functional microrna targets. *Nucleic acids research*, 48(D1):D127–D131, 2020.

[11] Vikram Agarwal, George W Bell, Jin-Wu Nam, and David P Bartel. Predicting effective microrna target sites in mammalian mrnas. *elife*, 4:e05005, 2015.

[12] Anton Enright, Bino John, Ulrike Gaul, Thomas Tuschl, Chris Sander, and Debora Marks. Microrna targets in drosophila. *Genome biology*, 4:1–27, 2003.

[13] A Petitjean, MIW Achatz, AL Borresen-Dale, P Hainaut, and M Olivier. Tp53 mutations in human cancers: functional selection and impact on cancer prognosis and outcomes. *Oncogene*, 26(15):2157–2165, 2007.

[14] Nader Chalhoub and Suzanne J Baker. Pten and the pi3-kinase pathway in cancer. *Annual Review of Pathology: Mechanisms of Disease*, 4:127–150, 2009.

[15] Hua Yu, Drew Pardoll, and Richard Jove. Stats in cancer inflammation and immunity: a leading role for stat3. *Nature reviews cancer*, 9(11):798–809, 2009.

[16] Niki Karachaliou, Clara Mayo, Carlota Costa, Ignacio Magrí, Ana Gimenez-Capitan, Miguel Angel Molina-Vila, and Rafael Rosell. Kras mutations in lung cancer. *Clinical lung cancer*, 14(3):205–214, 2013.

[17] Anna Frenzel, Francesca Grespi, Waldemar Chmelewskij, and Andreas Villunger. Bcl2 family proteins in carcinogenesis and the treatment of cancer. *Apoptosis*, 14:584–596, 2009.

[18] Shang Yao, Lavender Yuen-Nam Fan, and Eric Wing-Fai Lam. The foxo3-foxm1 axis: A key cancer drug target and a modulator of cancer drug resistance. In *Seminars in cancer biology*, volume 50, pages 77–89. Elsevier, 2018.

[19] Shanshan Liu, Ziwei Ye, Vivian Weiwen Xue, Qi Sun, Huan Li, and Desheng Lu. Kif2c is a prognostic biomarker associated with immune cell infiltration in breast cancer. *BMC cancer*, 23(1):307, 2023.

[20] Zhixian Liu, Qingrong Sun, and Xiaosheng Wang. Plk1, a potential target for cancer therapy. *Translational oncology*, 10(1):22–32, 2017.

[21] Jing Han, Rongkai Xie, Ying Yang, Diangang Chen, Li Liu, Jiayang Wu, and Sufen Li. Cenpa is one of the potential key genes associated with the proliferation and prognosis of ovarian cancer based on integrated bioinformatics analysis and regulated by mybl2. *Translational cancer research*, 10(9):4076, 2021.

[22] Chi V Dang. Myc on the path to cancer. *Cell*, 149(1):22–35, 2012.

[23] sentence-transformers/multi-qa-minilm-l6-cos-v1 · hugging face.

[24] Gizem Soğancıoğlu, Hakime Öztürk, and Arzucan Özgür. Biosses: a semantic sentence similarity estimation system for the biomedical domain. *Bioinformatics*, 33(14):i49–i58, 2017.

[25] Hsi-Yuan Huang, Yang-Chi-Dung Lin, Jing Li, Kai-Yao Huang, Sirjana Shrestha, Hsiao-Chin Hong, Yun Tang, Yi-Gang Chen, Chen-Nan Jin, Yuan Yu, et al. mirtarbase 2020: updates to the experimentally validated microrna–target interaction database. *Nucleic acids research*, 48(D1):D148–D154, 2020.

[26] Carsten Sticht, Carolina De La Torre, Alisha Parveen, and Norbert Gretz. mirwalk: an online resource for prediction of microrna binding sites. *PloS one*, 13(10):e0206239, 2018.

[27] Zhou Huang, Jiangcheng Shi, Yuanxu Gao, Chunmei Cui, Shan Zhang, Jianwei Li, Yuan Zhou, and Qinghua Cui. Hmdd v3. 0: a database for experimentally supported human microrna–disease associations. *Nucleic acids research*, 47(D1):D1013–D1017, 2019.

[28] Janet Piñero, Àlex Bravo, Núria Queralt-Rosinach, Alba Gutiérrez-Sacristán, Jordi Deu-Pons, Emilio Centeno, Javier García-García, Ferran Sanz, and Laura I Furlong. Disgenet: a comprehensive platform integrating information on human disease-associated genes and variants. *Nucleic acids research*, page gkw943, 2016.

[29] Daniela N Mannel and Bernd Echtenacher. Tnf in the inflammatory response. *Chem Immunol*, 74(74):141–161, 2000.

[30] Toshio Tanaka, Masashi Narazaki, and Tadamitsu Kishimoto. Il-6 in inflammation, immunity, and disease. *Cold Spring Harbor perspectives in biology*, 6(10):a016295, 2014.

[31] John J Letterio and Anita B Roberts. Regulation of immune responses by tgf-β. *Annual review of immunology*, 16(1):137–161, 1998.

[32] Yuki Nakamura, Riho Aihara, Hisataka Iwata, Takehito Kuwayama, and Koumei Shirasuna. Il1b triggers inflammatory cytokine production in bovine oviduct epithelial cells and induces neutrophil accumulation via ccl2. *American Journal of Reproductive Immunology*, 85(5):e13365, 2021.

[33] Margarida Saraiva and Anne O'garra. The regulation of il-10 production by immune cells. *Nature reviews immunology*, 10(3):170–181, 2010.

[34] Yoichiro Iwakura, Susumu Nakae, Shinobu Saijo, and Harumichi Ishigame. The roles of il-17a in inflammatory immune responses and host defense against pathogens. *Immunological reviews*, 226(1):57–79, 2008.

[35] Xiaodong Wang, Yan Yiu Yu, Shirley Lieu, Frank Yang, Jeffrey Lang, Chuanyong Lu, Zena Werb, Diane Hu, Theodore Miclau, Ralph Marcucio, et al. Mmp9 regulates the cellular response to inflammation after skeletal injury. *Bone*, 52(1):111–119, 2013.

[36] Marco Del Giudice and Steven W Gangestad. Rethinking il-6 and crp: Why they are more than inflammatory biomarkers, and why it matters. *Brain, behavior, and immunity*, 70:61–75, 2018.

[37] Suprabhat Mukherjee, Subhajit Karmakar, and Santi Prasad Sinha Babu. Tlr2 and tlr4 mediated host immune responses in major infectious diseases: a review. *Brazilian Journal of Infectious Diseases*, 20:193–204, 2016.

[38] Fayyaz S Sutterwala, Stefanie Haasken, and Suzanne L Cassel. Mechanism of nlrp3 inflammasome activation. *Annals of the New York Academy of Sciences*, 1319(1):82–95, 2014.