A Data-Intelligence-Intensive Bioinformatics Copilot System for Large-scale Omics Researches and Scientific Insights

Yang Liu[1,2,8], Rongbo Shen[1,2,8], Lu Zhou[1,2,8], Qingyu Xiao[1,2], Jiao Yuan[1,2*], Yixue Li[1,2,3,4,5,6,7*]

1, Guangzhou National Laboratory, Guangzhou 510005, China.

2, GMU-GIBH Joint School of Life Sciences, The Guangdong-Hong Kong-Macau Joint Laboratory for Cell Fate Regulation and Diseases, Guangzhou Medical University, Guangzhou 511436, China.

3, Shanghai Institute of Nutrition and Health, Chinese Academy of Sciences, Shanghai 200030, China.

4, Key Laboratory of Systems Health Science of Zhejiang Province, School of Life Science, Hangzhou Institute for Advanced Study, University of Chinese Academy of Sciences, Hangzhou 310024, China.

5, School of Life Sciences and Biotechnology, Shanghai Jiao Tong University, Shanghai 200240, China.

6, Collaborative Innovation Center for Genetics and Development, Fudan University, Shanghai 200433, China.

7, Shanghai Institute for Biomedical and Pharmaceutical Technologies, Shanghai 200032, China.

8, These authors contributed to the work equally and should be regarded as co-first authors.

*Corresponding authors: Jiao Yuan (yuan_jiao@gzlab.ac.cn), Yixue Li (li_yixue@gzlab.ac.cn).

Abstract

Advancements in high-throughput sequencing technologies and artificial intelligence offer unprecedented opportunities for groundbreaking discoveries in bioinformatics research. However, the challenges of exponential growth of omics data and the rapid development of artificial intelligence technologies require automated big biological data analysis capability and interdisciplinary knowledge-driven scientific insight. Here we propose a data-intelligence-intensive bioinformatics copilot (Bio-Copilot) system that synergizes AI capabilities with human expertise to facilitate hypothesis-free exploratory research and inspire novel scientific insights in large-scale omics studies. Bio-Copilot forms high-quality intensive intelligence through close collaboration between multiple agents, driven by large language models (LLMs), and human experts. To augment the capabilities of Bio-Copilot, this study devises an agent group management strategy, an effective human-agent interaction mechanism, a shared interdisciplinary knowledge database, and continuous learning strategies for the agents. We comprehensively compare Bio-Copilot against GPT-4o and several leading AI agents across diverse bioinformatics tasks, using a broad range of evaluation metrics. Bio-Copilot achieves the overall state-of-the-art performance across all tasks, while showcases exceptional task completeness. Furthermore, in the application of constructing a large-scale human lung cell atlas, Bio-Copilot not only reproduces the intricate data integration process detailed in a seminal study but also introduces a hierarchical annotation strategy to capture the continuous nature of cellular states and uncovers the characteristics of rare cell types, highlighting its potential to unravel hidden complexities in biological systems. Beyond the technical achievements, this study also underscores the profound implications of integrating AI capabilities with expert knowledge in accelerating impactful biological discoveries and exploring uncharted territories in life sciences.

I. Introduction

A. Background and Significance

Bioinformatics, as an interdisciplinary field that marries biology, computer science, mathematics, and statistics, has experienced unprecedented growth over the past few decades[1,2], driven primarily by advancements in high-throughput sequencing technologies[3,4] such as genomics[5,6,7,8], transcriptomics[9,10], proteomics[11,12,13] and metabolomics[14,15]. With the plummeting costs and the accelerated proliferation of these technologies, the amount of biological data being generated has exploded exponentially, presenting a wealth of opportunities for groundbreaking discoveries[16,17]. This torrential influx of data has fundamentally revolutionized our understanding of life sciences, ranging from fundamental molecular biology[18] to practical clinical applications and the burgeoning domain of personalized medicine[19,20].

In recent years, the scientific research landscape in bioinformatics has been undergoing a profound shift[21,22], propelled by the confluence of two major factors: the exponential growth of complex and interconnected biological data and the rapid advancement of artificial intelligence (AI) technologies. Despite the significant strides achieved in merging bioinformatics with AI technologies, current bioinformatics research still faces several critical challenges[23,24]. Firstly, integrating the strengths of AI with big biological data to propel advancements in bioinformatics research constitutes an ongoing and arduous pursuit[25,26]. Many researchers in the field are limited by a single area of expertise, but lack interdisciplinary knowledge and the ability to conduct cross-disciplinary scientific research. The effective application of AI in bioinformatics often requires a deep understanding of both the biological domain knowledge and advanced computational techniques, therefore there is a need for enhanced interdisciplinary collaboration to bridge the domain gap and unlock the AI-driven

analytical capabilities for life science research[27]. Secondly, the rapid accumulation of high-dimensional and multimodal biological data, characterized by large-scale, complexity, diversity, noise, and contextual dependencies, necessitates the development and application of advanced AI technologies. AI must not only enable scalable, adaptable, and interpretable processing of big biological data, but also promote synergistic integration with expert knowledge, thereby enhancing overall intelligent capacity.

B. Research Statement

In light of the revolutionary progress in AI technology and the exponential growth of biological data, this study delineates a data-intelligence-intensive research paradigm, as illustrated in Figure 1a. This paradigm integrates AI capabilities with human expertise in a cohesive collaboration to form intensive intelligence[28], that leverages big biological data to propel hypothesis-free exploratory research driven by a data-intelligence-intensive methodology. This novel research paradigm aligns with the future trend of bioinformatics research, characterized by data-intensive and computation-intensive[29] in big biological data processing, and knowledge-intensive and intelligence-intensive[30,31] in the convergence of interdisciplinary. Within this paradigm, human expertise continually enhances and refines AI agents, while AI agents driven by large language models (LLMs), in turn, leverages multidisciplinary knowledge fusion and big biological data mining to generate novel insights, thereby improving our understanding of life sciences. By leveraging their complementary strengths, bioinformatics research gains the ability to traverse uncharted territories of knowledge, generating testable hypotheses, delineating novel research directions, and refining experimental designs to accelerate discoveries, thereby revealing previously unexplored associations and emergent characteristics within complex biological systems.

The data-intelligence-intensive research paradigm presents a promising perspective for addressing contemporary challenges in current bioinformatics. It embeds knowledge from diverse scientific disciplines into AI agents, who, as integral members of intensive intelligence, actively participate in bioinformatics researches, facilitating interdisciplinary collaboration and overcoming long-standing knowledge barriers. Moreover, this novel research paradigm, leveraging the complementary integration of expert knowledge with AI capabilities[32,33], accelerates bioinformatics workflows by feature extraction from big biological data, proposing innovative scientific hypotheses, optimizing research designs, orchestrating computational resources for high-performance computing, and instituting fair and objective evaluation metrics.

In the data-intelligence-intensive research paradigm, both human experts and AI agents are core participants in scientific investigations. Here, we propose a data-intelligence-intensive bioinformatics copilot (Bio-Copilot) system that synergizes AI capabilities with human expertise to facilitate hypothesis-free exploratory research and inspire novel scientific insights in large-scale omics. Bio-Copilot utilizes the potent natural language processing capabilities of LLMs[34,35,36] and their broad perspective on scientific issues to enable interdisciplinary knowledge embedding, interaction with human experts, inter-agent communication, and agent self-reflective learning, thereby forming high-quality intensive intelligence through close collaboration between multiple agents and human experts. Initiated by scientific insights from LLMs, Bio-Copilot first decomposes a bioinformatics task into modular, hierarchical steps, then configures agent groups and specifies the roles of agents within each group according to step characteristics, alongside formulating rules for task allocation and scheduling. Thereafter, researchers collaborate with the planning agent groups to generate more explicit execution plans for the respective steps. Finally, according to the generated execution plans, the action

execution agent groups proceed gather necessary resources from the environment and sequentially accomplish each execution plan.

In the context of data-intelligence-intensive research paradigm, this study uses Bio-Copilot to substantiate the following scientific hypothesis: Firstly, the workflows planned by high-quality intensive intelligence, involving collaboration between researchers and multiple agents in Bio-Copilot, can enable bioinformatics researches to achieve superior results, significantly improving research efficiency and overcoming the limitations[37] inherent to standalone LLM applications. Secondly, the interactions between researchers and Bio-Copilot can inspire novel scientific insights, mitigate comprehension biases in LLMs pertaining to prompts, context, and both long-term and short-term memory, and address the problems of incomplete information during action execution, thereby enabling adaptability to complex bioinformatics research. Thirdly, strengthened by multidisciplinary knowledge empowerment and continuous learning of its agents, Bio-Copilot can make better decisions, plan better workflows and select optimal tools for bioinformatics research.

C. Main Contributions

The main contributions of this study are enumerated as follows:
- This study proposes a data-intelligence-intensive Bio-Copilot system, which forms high-quality intensive intelligence through close collaboration between multiple agents and human experts to facilitate hypothesis-free exploratory research and inspire novel scientific insights in large-scale omics.
- To augment the capabilities of Bio-Copilot, this study devises an agent group management strategy, an effective human-agent interaction mechanism, a shared interdisciplinary knowledge database, and continuous learning strategies for agents.

- This study systematically compares Bio-Copilot against GPT-4o and several
AI agents in diverse bioinformatics tasks using a broad range of evaluation
metrics, and demonstrates the advancement of Bio-Copilot.
- Through the application of Bio-Copilot in constructing a large-scale human
lung cell atlas, this study demonstrates that Bio-Copilot can not only reproduce
existing workflow, but also carry out exploratory research tasks.
176

II. Literature Review

A. The development trend of bioinformatics

The evolution of bioinformatics, tracing back to the mid-20th century, has lately entered into a phase of accelerated development, catalyzed by the successful completion of the Human Genome Project[38,39,40,41] and the groundbreaking advancements in high-throughput sequencing technologies[3,4,42,43]. The explosive growth of high-throughput sequencing data, exemplified by genomics[5,6,7,8], transcriptomics[9,10,44], proteomics[11,12,13], and metabolomics[14,15], has provided unprecedented data resources for life sciences research. Driven by the data-intensive research paradigm, researchers developed more efficient methods for processing and analyzing large-scale biological datasets to elucidate the structures and functions of biomolecules, cells, tissues, organs, and entire organisms, encompassing gene regulatory networks[45,46], epigenetic modifications[47,48], cellular heterogeneity[49,50], evolutionary relationships[51,52], and disease mechanisms[53,54,55]. In precision medicine[19,20,56], the integration of genomic, cellular phenotype, and clinical data enabled multi-modal data analyses[57,58], advancing applications in disease prevention, diagnosis, personalized treatment planning, and drug response prediction. Recently, with the breakthroughs in AI technology, machine learning and deep learning methods have become paramount tools in large-scale biological data analysis,

excelling in handling complex nonlinear relationships and demonstrating

substantial potential in microscopy image analysis[59,60], protein structure

prediction[61,62,63,64], deciphering gene regulatory networks[45,46,65,66], biomarker

detection for diseases[67], diagnostic and prognostic assessments[68], and drug

discovery and design[69,70,71].

To address the mounting volume of biological data and comprehensively

unravel complex life systems, the progression of bioinformatics evolved

advancements in technology, computational methodology innovation, and

interdisciplinary collaboration, propelling the development of life sciences

through deeper analysis and understanding of biological data. For instance,

with the maturation and cost reduction of single-cell sequencing technologies,

single-cell multi-omics[72,73] studies integrated multi-omics data in spatiotemporal

dimensions, elucidating the fundamental laws governing life systems across

different molecular levels (i.e., genetic, transcriptional, proteomic, and

metabolic), thereby enabling a finer dissection of cellular heterogeneity,

intercellular interactions, and dynamic cellular processes, which fostered novel

discoveries in precision medicine, tumor biology, and developmental biology.

Third-generation sequencing technologies[74], with their high sensitivity, long

reads, and real-time sequencing capabilities, generated full-length transcript

sequencing data, facilitating rapid epigenetic modification identification, and

contributing to the study of alternative splicing[75] and non-coding RNA

structures[76,77,78], thereby enhancing our understanding of gene transcription

regulation, non-coding RNA biology, and the mechanisms underlying disease

development. AI technologies are becoming increasingly embedded in

bioinformatics research, capable of handling complex pattern recognition, big

data analytics, and predictive modeling, enhancing accuracy and efficiency

from omics data analysis to protein structure prediction, to disease diagnostics

and drug development. To enhance the efficiency and reproducibility of

bioinformatics research, automated workflows provided standardized data

processing, elastic resource allocation with distributed computing, and workflow

management and monitoring, thereby reinforcing the rigor and objectivity of

scientific investigations.

B. Large Language Models

Large language models (LLMs) are deep learning architectures based on the

Transformer[79], featuring stacked multi-layered structures and positional

encoding, which leverage self-attention mechanisms to process input text

sequences in parallel, thereby efficiently capturing long-range dependencies

and learning linguistic structures and patterns. LLMs typically undergo pre-

training on vast amounts of unlabeled text data, acquiring general linguistic

patterns and structures. Following the pre-training phase, LLMs can be fine-

tuned to specific tasks such as question answering, text classification, or text

generation, tailored to the precise requirements of the given application. LLMs,

with their massive parameters and deep network architectures, excel at

understanding complex contextual relationships and generating coherent, high-

quality text[80]. With technological progress, some LLMs incorporate multimodal

learning capabilities, enabling comprehension of data such as images and

audio in addition to text, and thereby achieving cross-modal information

processing and synthesis.

The proposal of Transformer[79] architecture in 2017 marked the dawn of the era

of LLMs. In 2018, the unveiling of BERT[81] by Google and GPT-1[82] by OpenAI

introduced pre-training techniques, which substantially improved the

performance capacities of LLMs. The successive releases of the GPT

series[83,84] propelled the rapid advancement of LLMs, with model parameters

swiftly surging into trillions. Particularly, ChatGPT[83] and GPT-4[84] demonstrated

unprecedented capabilities in language generation and comprehension,

achieving remarkable performance across diverse applications such as question answering, text composition, code generation, and conversational system[85,86,87]. Subsequently, LLMs integrated multimodal processing capabilities, enabling joint modeling of diverse data types such as images and text, and thereby offering enhanced visual generation abilities (e.g., Sora[88]).

While LLMs have demonstrated remarkable capabilities, they also come with inherent limitations[37]. The output of LLMs is highly contingent upon training data, thereby inheriting biases, factual inaccuracies, and illusion issues from biased, erroneous, or incomplete training datasets. While capable of handling and generating sophisticated language structures, LLMs, as statistical prediction engines, lack the comprehension, common sense, autonomous planning, and self-learning capabilities inherent to humans, rendering them potentially inadequate in tasks requiring profound understanding or logical reasoning. Owing to the complexity of LLMs, the decision-making processes of LLMs tend to be opaque, rendering explanations for specific predictions or generations elusive.

C. AI Agent

The origins of AI agent development can be traced back to the emergence of expert systems, which leveraged rule-based knowledge databases to mimic human experts in solving domain-specific problems. Subsequently, reinforcement learning[89,90] emerged as a vital machine learning paradigm integrated into AI agents, offering a pathway for AI agents to learn through iterative interactions with their environments. In recent years, the revolutionary advancements in deep learning technologies, highlighted by the introduction of LLMs such as the GPT series, empowered LLM-based agents with formidable natural language processing capabilities. Agents[91,92,93,94], capable of

autonomously perceiving their environment, cognitive reasoning, decision-
making, and executing actions through tool invocation, emerged as a highly
promising direction in the pursuit of general artificial intelligence. Specifically,
an AI agent comprises four modules: the perception module for gathering
environmental information, the cognition and decision-making module to
analyze inputs and devise action strategies, the memory module to archive
knowledge and past behaviors, and the action module to implement decisions
by manipulating tools to impact the environment. AI Agents execute tasks
through a perceptual-decisional-action loop, subsequently engaging in
reflective evaluation of the results, which informs learning to acquire knowledge,
stored in the memory module, thereby optimizing future decision-making and
actions. Agents demonstrate human-like intelligence behavior[95] through
autonomous environmental perception, decision-making process, and an
aptitude for learning and adapting via dynamic environmental engagements.

Prominent existing single-agent frameworks such as AutoGPT[96], BabyAGI, and
HuggingGPT[97] facilitated task planning and tool invocation, thereby
accomplishing user-defined objectives effectively. For instance, the
Coscientist[98] system, powered by GPT-4, autonomously conducted chemical
research, involving automated experiment planning and execution, along with
predicting and refining reaction pathways through sophisticated modeling
capabilities. Researchers interacted with the Coscientist system to accomplish
six pivotal tasks: planning synthesis routes of known compounds using public
data, efficiently retrieving and navigating hardware documentation, executing
advanced directives in cloud labs, precisely controlling liquid handling
equipment, multitasking across multiple hardware modules for complex
operations, integrating diverse datasets and analyzing past experimental data
for optimization problem-solving. For another example, the ChemCrow[99]
system, driven by LLMs，autonomously planned and executed tasks including
the synthesis of organic compounds, drug discovery, and material design. By

incorporating tools such as web searches, literature exploration, and interactive

coding interfaces, the ChemCrow system augmented its capability to acquire

and comprehend external information, thereby showcasing the potential for

enhanced scientific task management. In the field of computational pathology,

PathChat[100], a multimodal generative AI Copilot system, demonstrated the

ability to combine histological images, clinical data, and subsequent

immunohistochemical (IHC) results for interactive differential diagnosis in

unknown primary cancer cases, aiming to assist pathologists improving the

accuracy and efficiency in diagnosis and understanding complex cases.

PathChat was designed to handle pathology-related queries in multiple-choice

diagnostic questions, demonstrating its potential in pathology diagnostic

support. While LLMs have propelled the evolution of AI agent technologies,

single-agent systems still grapple with inherent limitations. Firstly, the

capabilities of AI agents are confined by the prowess of their underlying LLMs，

which can lead to biased, hallucinatory, erroneous, or outdated action decisions

during complex tasks, often due to the quality of training data. When dealing

with extensive texts, iterative conversations, or complex contexts, AI agents

may misconstrue user intentions and offer partially relevant responses,

hampered by the finite memory retention of LLMs and limitations in

comprehending prompt cues and contextual associations. Secondly, while

individual agents can adopt multiple roles, they often rapidly converge onto a

specific viewpoint influenced by prompts or earlier conversation turns, thereby

missing out multiperspective and holistic abilities for problem analysis. Lastly,

single-agent systems typically decompose tasks into linear workflows, resulting

in inefficient execution and inadequate responsiveness to dynamically

changing environments.

LLM-based single-agent systems focus on internal reasoning and decision-

making processes as well as interactions with the external environment.

Inspired by human collaboration in tackling complex tasks, LLM-based multi-

agent systems emphasize diverse agent groups, inter-agent interactions, and

collective decision-making protocols. Compared to single-agent systems, multi-

agent systems orchestrate a consortium of diverse agents with distinct

capabilities and roles, simulating intricate real-world scenarios via inter-agent

cooperation, harnessing the collective intelligence born of their individual

strengths to tackle more dynamic and intricate tasks such as software

development, scientific experiment, and embodied AI.

Recently, the open-source community witnessed the rise of several prominent

multi-agent frameworks[101,102,103], such as MetaGPT[104], CAMEL[105], and

AutoGen[106]. MetaGPT embedded human workflow procedures into the actions

of LLM-based agents, employing structured outputs and a publish-subscribe

mechanism, effectively resolving information redundancy in multi-agent

conversations and mitigating the prevalence of illusions in complex tasks.

CAMEL leveraged prompt engineering techniques to delineate the roles of

agents, facilitating autonomous collaboration between them, and directing

agent conversations to progress in alignment with mission objectives. AutoGen

emerged as a highly customizable multi-agent framework, enabling

researchers to customize the LLMs of agents, communication protocols and

workflow management, thereby tackling intricate tasks. However, multi-agent

systems also face some challenges. Fundamentally, the design and

implementation of multi-agent systems entail heightened complexity, requiring

meticulous attention to issues of inter-agent communication, collaboration, and

conflict resolution mechanisms. Additionally, multi-agent systems encounter

sophisticated interaction patterns in the dynamic contexts, which can lead to

information overlaps and non-productive discourse, ultimately hindering the

effectiveness of task execution. Furthermore, multi-agent systems are

characterized by significant computational resource consumption and a

heightened cost associated with customization.

III. Results

A. Architecture and advancements of Bio-Copilot

Architecture

The architecture of Bio-Copilot comprises multiple agents with diverse roles, a coordination layer, and an environment, as illustrated in Figure 1b. Agents, the core components of Bio-Copilot, employ LLMs as their controlling nucleus and exhibit a high degree of autonomous capability. They are capable of perceiving environmental information, deciphering complex natural language instructions (such as the prompts from experts in the environment), conducting cognitive reasoning, and executing actions through tool invocations. Agents can act various roles with specific responsibilities, such as information acquisition, task planning, code generation, task execution, and etc. The coordination layer serves as a bridge for agents to perceive environmental information and feedback to influence the environmental state, while harmonizing the behaviors of agents such as task planning and allocation, resource scheduling, conflict resolution, and collaborative strategies. Within the coordination layer, we devise an agent group management strategy, an effective human-agent interaction mechanism, a shared interdisciplinary knowledge database, and continuous learning strategies for agents, thereby augmenting the capabilities of Bio-Copilot. The environment, as an external context of Bio-Copilot, influences the behavior of agents, while the actions of these agents in turn modify the state of the environment. Specifically, the environment comprises elements from both the real world, such as experts, instruments, devices and tools, and the virtual world, including datasets, documents, knowledge databases, and software.

Advancements

Bio-Copilot employs an innovative design approach that emphasizes interdisciplinary collaboration, shared knowledge resources, and continuous interactive feedback, devising novel strategies in efficient human-agent interaction, agent group management, interdisciplinary knowledge empowerment, and continuous learning. Firstly, to address the complexity of bioinformatics problems, we devise user-friendly, highly real-time human-agent interaction mechanism, aimed to alleviate the misunderstandings of agents related to prompts, context, and both long-term and short-term memory, alongside issues of incomplete information during action execution. This human-agent interaction mechanism also supports natural language interactions and immediate feedback between human experts and Bio-Copilot, thereby inspiring new scientific insights. As a result, human experts can direct the activities of Bio-Copilot in real time and promptly assimilate analytical insights from Bio-Copilot. Secondly, to enhance collaboration efficiency, we devise agent group management strategies which can reduce redundant information exchange and inconsequential interactions to ensure efficient and accurate information flow. Thirdly, acknowledging the interdisciplinary nature of bioinformatics, we establish a shared knowledge database which encodes domain-specific expertise from diverse fields into a format intelligible within Bio-Copilot. Empowered by interdisciplinary knowledge, agents can dynamically retrieve relevant information from the shared knowledge database to formulate rational plans for task-specific requirements, thereby mitigating biases and illusions prevalent in LLMs during reasoning and decision-making. Lastly, to swiftly accommodate emerging and challenging bioinformatics research tasks, we devise continuous learning strategies for agents. Specifically, the multiple agents engage in both self-reflective learning[107] from their own behaviors and competitive knowledge acquisition with fellow agents, progressively refining their decision-making and execution capabilities over time to enhance intensive

intelligence. The aforementioned innovative design enhances Bio-Copilot in terms of language intelligence, social intelligence, knowledge empowerment, and learning intelligence.

B. Benchmarking Bio-Copilot for the construction of a large-scale human lung cell atlas

Workflow description

In recent years, a series of single-cell sequencing studies dissected molecular profiles of cells in both normal and diseased tissues, and the rapidly advancing single-cell sequencing technology made it feasible to establish human cellular atlas (HCA) [108], which was listed among the seven notable technologies in 2024 by the scientific journal Nature[109]. A comprehensive cellular atlas of human lung tissue systematically unveiled molecular distinctions among various pulmonary cell populations, poised to revolutionize our understanding of cells in healthy and diseased lungs, thereby offering crucial insights for elucidating respiratory disease pathogenesis, vaccine development, immunotherapy, and tissue regeneration. Several independent studies embarked on constructing a cellular atlas for lung tissue. However, limitations in experimental techniques, sequencing methodologies, sample selection and cell quantity constrained comprehensive and unbiased capture of the diversity and heterogeneity inherent to lung tissues. Consequently, integrating datasets from these independent studies in an unbiased manner to construct a comprehensive cellular atlas of lung tissue would address these limitations and further facilitate the identification of variability patterns across different demographics, such as age, gender, BMI, smoking status, and etc.

In this study, we employ Bio-Copilot to construct a large-scale human lung cell

atlas, thereby evaluating the capability of Bio-Copilot in handling data-

intelligence-intensive bioinformatics research tasks. Referencing the HLCA[110]

study, the workflow is collaboratively generated by researchers and Bio-Copilot,

which mainly comprises four tasks: dataset integration task, hierarchical

clustering task, cell type annotation task, and downstream analysis task. Bio-

Copilot adopts a consistent procedure for each task, comprising coarse-level

planning, fine-level planning, and action execution, the example procedure for

hierarchical clustering task is illustrated in Figure 2. Specifically, for each task

objective, Bio-Copilot employs coarse-level planning group to formulate an

initial plan, which then iteratively refined by fine-level planning group for each

step. During the action execution of plan, researchers can intervene via human-

agent interaction to set parameters and correct any erroneous actions and

behaviors, as illustrated in Figure 2. Comprehensive workflow and

implementation details for constructing the large-scale human lung cell atlas

are in the Experimental setup section of Methodology.

Performance evaluation

To fully evaluate the performance of Bio-Copilot, we systematically compare

Bio-Copilot against the control group and the ablation group in all bioinformatics

tasks in the workflow of constructing the large-scale human lung cell atlas,

using a broad range of evaluation metrics. The control group comprises GPT-

4o, AutoBA and AutoGen, where GPT-4o is a state-of-the-art LLM, AutoBA is

an influential single AI agent for bioinformatics, and AutoGen is an influential

multiple agent system. The ablation group comprises the exclusion of

knowledge empowerment, self-reflective learning and document retrieval for

Bio-Copilot, respectively. The evaluation of Bio-Copilot focuses on the following

three aspects: task planning, code quality, and execution efficiency. We use an

overall evaluation formula to synthesize all the evaluation aspects. Obviously, Bio-Copilot achieves the overall state-of-the-art performance in all tasks (Figure 3a), while showcases highest task completeness, as illustrated in Supplementary Figure 3a.

The task planning evaluation assesses the capabilities of Bio-Copilot in decomposing bioinformatics tasks and formulating execution plans. The evaluation metrics includes clarity, technical feasibility, structurality, comprehensiveness, rationality of method selection, risk management, data management, scientific rigor, resource allocation, and scalability. To ensure objectivity in this comparison, we employ GPT-4 to score the execution plans generated by each method, where the prompt of GPT-4 is illustrated in Supplementary Figure 1a. Obviously, Bio-Copilot achieves the overall state-of-the-art task planning performance in all tasks, as illustrated in Figure 3b. The execution plans generated by Bio-Copilot exhibit higher implementability in bioinformatics research tasks, compared to GPT-4o, AutoBA and AutoGen in the control group. It is further substantiated that intensive intelligence through close collaboration between multiple agents and experts facilitates the design of excellent scientific research programs. In addition, the comparison with the ablation group also demonstrates that knowledge empowerment, self-reflective learning and document retrieval can improve the task planning performance of Bio-Copilot. More scores of evaluation metrics for task planning are illustrated in Supplementary Figure 2a-b.

The code quality evaluation assesses the ability of Bio-Copilot to understand the execution plans. The evaluation metrics includes accuracy, efficiency, completeness, readability, logicality, portability, maintainability, usability, reusability, robustness, security, and scalability. This comparison also employs GPT-4 to score the quality of code generated by each method, where the prompt of GPT-4 is illustrated in Supplementary Figure 1b. Similarly, Bio-

Copilot achieves the overall state-of-the-art code quality performance in all
tasks, evidencing a more comprehensive understanding of execution plans, as
illustrated in Figure 3b. The comparison with the control group demonstrates
that Bio-Copilot can generate higher quality code for the execution plans. The
comparison with the ablation group also demonstrates that knowledge
empowerment, self-reflective learning and document retrieval are beneficial for
Bio-Copilot in code generation. More scores of evaluation metrics for code
quality are illustrated in Supplementary Figure 2c-d.

The execution efficiency evaluation assesses Bio-Copilot in task completeness,
user interventions, runtime, computing resource cost, as illustrated in
Supplementary Figure 3a-d. Obviously, Bio-Copilot can complete all tasks
according to the generated codes, whereas methods in the control group fail to
complete most of the tasks. More features of methods in the control group are
illustrated in Supplementary Figure 3e. The user interventions represent the
frequency with which the user directs the model. Bio-Copilot accomplishes all
tasks with few user interventions, highlighting a high level of automation.
Notably, AutoBA has no user intervention during execution, but it has a low task
completeness, suggesting that proper user interventions during the execution
of complex tasks can prevent task interruptions or failures due to
misunderstanding or inadequate information. GPT-4o and AutoGen have about
the same number of user interventions as Bio-Copilot across all tasks, but their
tasks are not completed. This also substantiates the efficacy of our designed
human-agent interaction mechanism, enabling Bio-Copilot to tackle complex
bioinformatics tasks. The comparison with the ablation group demonstrates that
knowledge empowerment, self-reflective learning and document retrieval can
effectively reduce the user interventions. Across all tasks, Bio-Copilot has less
overall rumtine than GPT-4o and AutoGen, while achieving a higher task
completeness. Although AutoBA has less overall runtime, it has the lowest task
completeness. In terms of resource consumption, the computing resource

consumption of each method is within an affordable range, where 128 CPU
cores, 32GB memory, and a GPU with 24GB memory can meet the usage
requirements of Bio-Copilot.

Details on the evaluation metrics and the GPT-4 assessment approach
(Supplementary Figure 1a-b) are provided in the Evaluation Metrics section of
Methodology. The prompts of Bio-Copilot with self-reflective learning,
knowledge empowerment and document retrieval are illustrated in
Supplementary Figure 4a, 5a and 6a, respectively. In contrast, the prompts of
the exclusion of self-reflective learning, knowledge empowerment and
document retrieval in the ablation group are illustrated in Supplementary Figure
4b, 5b and 6b, respectively.

C. Result analysis of the human lung cell atlas

Data integration and hierarchical clustering

Conforming to the workflow of constructing the large-scale human cell atlas, all
tasks are performed by Bio-Copilot with expert collaboration. Bio-Copilot first
performs the data integration task on multiple independent datasets. Utilizing
the scANVI[111] algorithm, Bio-Copilot accomplishes dimensionality reduction to
embed cells from these datasets into a unified feature space. The scANVI
algorithm mitigates batch effects arising from variations in sampling techniques
and sequencing technologies across datasets, enabling cells of the same type
to cluster in the feature space, thereby facilitating downstream analyses and
visualizations.

Subsequently, Bio-Copilot conducts the hierarchical clustering task on the
embeddings of the integrated dataset to identify distinct cell populations. By

clustering cells in a hierarchical manner from coarse to fine resolutions, this

approach enables researchers to identify cell populations at various levels and

decipher the intricate relationships between them. Specifically, Bio-Copilot

performs a four-level hierarchical clustering to categorize all cells within the

dataset into distinct clusters at each level. The UMAP visualizations of the

hierarchical clustering results from level 1 to level 4 are illustrated in

Supplementary Figure 7a. These visualizations reveal that Bio-Copilot

successfully reproduces the data integration task and hierarchical clustering

task as reported in the original study. Furthermore, the batch effects between

originally independent datasets are effectively mitigated after integration, in

which most cells are grouped into a few of cell populations, and very few cells

are isolated.

More details of Bio-Copilot performing the data integration task and hierarchical

clustering task refer to the Experimental Setup section in Methodology.

Cell type annotation

In the original hierarchical annotations of these datasets, a considerable

number of cells show unfilled categories (prefixed with numbers and inherited

from upper levels during preprocessing) from level 2 to level 4, evidencing

incomplete cell annotations under the original cell type nomenclature.

Therefore, to refine the cell atlas and harmonize the cell type nomenclature,

Bio-Copilot performs the cell type annotation task to re-annotate all clusters

from level 2 to level 4. Specifically, Bio-Copilot ingests a database of human

cell marker genes, and subsequently invokes the Decoupler[112] tool to identify

cell types for each cluster based on that database. This method of invoking

tools is more stable and reproducible than directly leveraging LLMs for

annotations[113]. The re-annotated cell types from level 2 to level 4 exhibit a

stable hierarchical structure and favorable lineage characteristics, as illustrated

in Figure 4a. This also underscores the continuity in cellular states within cell

atlases, rendering a hierarchical annotation strategy for cell atlas construction

facilitates lineage tracing and the discovery of novel subpopulations[114],

whereas single-cluster definitions inadequate for fully capturing the complexity

of cell types. Due to the limited capabilities of the Decoupler tool and the

database of human cell marker genes, a few cell clusters (a total of 4,579 cells,

about 0.8% of the integrated dataset) cannot be identified as reliable cell types,

so they are classified as unknown cell types. Subsequently, Bio-Copilot

calculated the distribution of cells within each well-annotated cell type at level

4 across the original independent datasets, alongside entropy values, as

illustrated in Figure 4b. From these computations, it is evident that the majority

of cell types comprise cells from multiple datasets, whereas a few cell types

originate predominantly from individual datasets. This again demonstrates that

the batch effects between originally independent datasets are effectively

mitigated in previous data integration task. Bio-Copilot further performs

differential expression analysis and correlation analysis for the re-annotated

integrated dataset at level 4, as illustrated in Supplementary Figure 8a. These

analyses further elucidate the differences between cell types, where similarity

is higher among cell types with homologous lineages, as illustrated in

Supplementary Figure 8b.

Furthermore, we further compare the differences between the cell types re-

annotated by Bio-Copilot and the original cell types, as illustrated in

Supplementary Figure 9a-c. It can be found that there is a consistent granularity

between the re-annotated cell types and the original cell types in level 2

(Supplementary Figure 9a) and level 3 (Supplementary Figure 9b). Although

the cell type nomenclature is different, the two cell type labels of most cells are

from homologous lineages and can be well aligned. The re-annotated cell types

in level 4 (Supplementary Figure 9c) have lower granularity resolution than the

original cell types, which is limited by the cell type nomenclature of the database

of human cell marker genes used by Bio-Copilot. Besides, we further analyzed

unknown cell types at each level. As the level of clustering increases, more

subclusters are classified as unknown cell types, as illustrated in

Supplementary Figure 7b and Figure 4c. Finally, a total of 4,579 cells are

classified as unknown cell types at level 4, as illustrated in Figure 4c. They are

all isolated from major cell populations, and are used for exploratory research

of rare cell types in downstream analysis task.

More details of Bio-Copilot performing the cell type annotation task refer to the

Experimental Setup section in Methodology.

Downstream analysis

Following the cell type annotation task, Bio-Copilot performs downstream

analysis task to explore new scientific discoveries, including rare cell type

analysis and variance between individuals explained by covariates.

Bio-Copilot first analyzes the unknown cell types with a total of 4,579 cells. By

analyzing the relationship between the unknown cell types from level 2 to level

4, there are three unknown cell types in the level 2 (i.e., '0_5', '1_5' and '3_3'),

and their subtypes can be traced to these three unknown cell types, as

illustrated in Supplementary Figure 10a-b. The other unknown cell types in level

3 and level 4 can be traced to well-annotated cell types. Therefore, we merge

the unknown cell subtypes upward and keep the unknown cell types in the

upper levels, as illustrated in Figure 5a. Subsequently, Bio-Copilot calculated

the distribution of cells within each unknown cell type across the original

independent datasets, alongside entropy values, as illustrated in Figure 5b.

Obviously, most unknown cell types comprise cells from individual dataset and

the number of cells is relatively small. Therefore, these unknown cell types can

be classified as rare cell types. Bio-Copilot further analyzes the three rare cell

types derived from level 2, i.e., '0_5', '1_5' and '3_3'. The original cell type

distributions for these rare cell types are illustrated in Figure 5c and

Supplementary Figure 10 c-d. Obviously, the rare cell types '1_5' and '3_3' were

annotated as macrophage and alveolar type II in original dataset, respectively.

The outlier characteristics of rare cell types '1_5' and '3_3' indicate that they

may be cell subtypes of macrophage and alveolar type II, with specific gene

expression and cell functions. The rare cell type '0_5' has more original cell

types, that can be traced back to epithelial cells, as illustrated in Figure 5c.

However, this rare cell type has a significant difference from the epithelial cell,

as illustrated in Figure 5a. Therefore, Bio-Copilot performs differential

expression analysis at level 2 to obtain specifically expressed genes for these

three rare cell types. Then, Bio-Copilot calls Enrichr[115,116] enrichment analysis

tool to parse the biological processes of each rare cell type, as illustrated in

Figure 5d. The results of enrichment analysis suggest biological processes that

are significantly activated or inhibited, and can guide the design of further

biological experiments, such as validating the function of key genes, probing

regulatory networks, or developing new therapeutic strategies.

While the data integration task effectively mitigates batch effects, residual batch

effects persist. Bio-Copilot employs the embeddings of scANVI to conduct

variance analysis across different cell types and covariates, with results

illustrated in Figure 5e. The variance analyses can reveal that technical

covariates, such as tissue dissociation protocol, tissue sampling method, and

single cell platform, still demonstrate noticeable variation contributions across

many cell types. Specifically, tissue sampling methods such as 'brush', 'biopsy',

'donor_lung', 'scraping', and 'surgical_resection' show varied contributions to

differential expression across cell types, as illustrated in Figure 5e. Notably, cell

types that incorporate a greater variety of tissue sampling methods display

more significant variation, with a positive correlation coefficient of 0.71, as illustrated in Figure 5f. Biological covariates, in contrast, exhibit lower contributions to variation across different cell types. Some cell types belonging to epithelial cells have relatively higher biological differences, such as secretory cell, goblet cell, basal cell and ciliated cell, as illustrated in Supplementary Figure 10e. It shows that they are less affected by technical covariates. For cell types sampled in fewer than 40 samples, the mean variance explained across all covariates showed a high negative correlation with the number of samples, as illustrated in Supplementary Figure 10f. This also underscores that adopting uniform technical protocols can significantly alleviate batch effects. Variance analyses conducted by Bio-Copilot yields conclusions consistent with those presented in the original study.

IV. Discussion

A. Summary

In the future trend of data-intensive and computation-intensive in big biological data processing and knowledge-intensive and intelligence-intensive in the convergence of interdisciplinary, this study proposes a data-intelligence-intensive Bio-Copilot system to facilitate hypothesis-free exploratory research and inspire novel scientific insights in large-scale omics. Bio-Copilot forms high-quality intensive intelligence through close collaboration between multiple agents, driven by LLMs, and human experts. We devise an agent group management strategy, an effective human-agent interaction mechanism, a shared interdisciplinary knowledge database, and continuous learning strategies to augment the capabilities of Bio-Copilot. In the benchmark test, Bio-Copilot achieves the overall state-of-the-art performance in all tasks against GPT-4o, AutoBA and AutoGen, while showcases high execution efficiency.

Furthermore, in the application of constructing a large-scale human lung cell
atlas, Bio-Copilot not only reproduces the processes detailed in the original
study but also employs a hierarchical annotation strategy to illustrate the
continuous nature of cellular states and explore the characteristics of rare cell
types. These experiments demonstrate the capabilities of Bio-Copilot to
perform data-intelligence-intensive complex bioinformatics research. This study
also reveals the potential of integrating AI capabilities with expert knowledge to
accelerate impactful biological discoveries and explore uncharted territories in
life sciences.

B. Limitations

Although Bio-Copilot exhibits enormous promise in tackling data-intelligence-
intensive research tasks, there remain limitations and areas requiring further
development. Competition among agents is conducive to the enhancement of
Bio-Copilot capabilities. Multiple agents can gain new knowledge through
competition with other agents, serving as a strategy to continuous learning. For
example, multiple agents perform the same task at the same time, use the
evaluation function to evaluate the results of each agent, and then compare the
results of each agent to obtain knowledge, and screen excellent solutions.
Multiple agents usually require a large amount of computing resource overhead,
especially when dealing with complex tasks and large-scale data, how to use
these resources efficiently remains a critical challenge. Promising solutions
include dynamic resource allocation, elastic computing, containerization, and
microservice architectures that dynamically increase or decrease compute
resources based on demand to improve resource utilization efficiency.
Furthermore, complex tasks usually need to be decomposed into sub-tasks
parallel or data parallel, and how to maintain load balance and control energy
consumption and cost is also a key problem. Task prioritization scheduling

algorithms and load balancing mechanisms are promising strategies to address

these complexities. Additionally, incorporating energy-efficient management

strategies, designing more efficient algorithms, leveraging heterogeneous

computing resources, and employing model compression techniques can

significantly reduce the cost of computation and energy consumption. Efficiently

collecting, transmitting, processing, storing, and managing data to accurately

monitor task progress and resource utilization poses another critical challenge.

Current promising solutions entail lightweight data acquisition, data

compression, streaming data processing, distributed data storage, and

dashboard visualizations for real-time insights.

Designing effective prompts[117] for user interaction with multiple agents,

ensuring clear communication and efficient task delegation, presents a critical

challenge. Vague, inconsistent, overly complex prompts, or those lacking

coherent context, can lead to misdirected agent decisions and erroneous

outputs, highlighting the importance of precise and contextually appropriate

prompting strategies. Current prompt engineering approaches include: utilizing

concise, clear, and neutral prompts; adopting stepwise guidance, incremental

processing, and conversational prompts for complex tasks; reusing context,

implementing positive feedback loops, and incorporating knowledge retrieval

mechanisms to mitigate comprehension deviations. Furthermore, enhancing

the diversity and adaptability of interactions to varying user needs and contexts

poses a critical challenge. This includes supporting multifaceted interaction

modes such as voice, vision, and text, alongside adaptive learning algorithms

and feedback mechanisms to meet personalized interaction requirements.

Potential solutions include multimodal fusion, cross-modal learning, online

learning, user profiling.

C. Potential future improvements

With the rapid advancement of AI technologies, AI agents have demonstrated substantial potential across various domains and ushered in new development opportunities. The integration of AI agent technology with cutting-edge technologies such as embodied intelligence[118,119,120], world models[121], and digital twins[122] continues to drive innovation and advancements in various fields.

Embodied intelligence serves as a physical extension of AI agents into the real world, which can manipulate the senses and act of robots to interact with physical environment, and combine physical experience with cognitive processes. AI agents focus on autonomous learning, decision-making, and task execution based on data and algorithms, while embodied intelligence emphasizes physical interaction capabilities. When AI agents integrate embodied intelligence, they gain enhanced capacity to manipulate the physical environment, which requires the agent to have strong cognitive processing and physical interaction capabilities. For example, medical robots use the cognitive abilities of AI to diagnose patients and then perform specific physical therapies, embodying the synergy of intelligence and physical interaction. Embodied intelligence also has broad prospects in life science research, which can bring revolutionary changes to precision medicine, automated analysis of omics data, cell and molecular experiments, and ecological environment research.

The world model is the cognition and abstraction of AI agent's environment, which can enhance the agent's ability to perceive and understand changes in environmental states, and improve decision-making and action capabilities. Integrating AI agents with world models enables them to better understand and adapt to complex, dynamic environments. For example, in robotic navigation and autonomous driving, world models representing roads, traffic, and pedestrians enable agents to make decisions and navigate, avoiding obstacles

and identifying optimal routes. In life sciences, world models apply to simulating disease spread, drug discovery, studies in biological evolution and genetics, integrating diverse data from organisms, compounds, and physical environments, thereby empowering agents with heightened environmental perception, informed decision-making, and precise actions.

Digital twins serve as virtual replicas of physical entities or environments, facilitating bidirectional communication between the physical realm and its digital counterpart. The convergence of AI agents with digital twins amplifies their capabilities and adaptability, encompassing real-time data analytics, simulation-based optimization, fusion of multi-source data, and environmental simulations. In smart cities, digital twins supplying real-time traffic data empower AI agents to optimize signal timing through refined decision-making, effectively alleviating congestion. In life sciences, digital twins integrate multi-source biological data and furnish virtual environments that enable AI agents to perform numerous simulations, thereby diminishing risks associated with physical experiments and expediting the research process.

In the future, AI agents will transcend their roles as mere human assistants to become collaborative partners, augmenting human capabilities across diverse tasks and delivering more intelligent decision-making support. AI agents will facilitate broader and more convenient applications in domains such as autonomous driving, smart factories, precision medicine, drug discovery, and scientific research, seamlessly integrating into daily life and work routines.

V. Methodology

A. Technical specifications of Bio-Copilot

Overall framework

The overall architecture of Bio-Copilot comprises multiple agents, a coordination layer, and an environment, as illustrated in Figure 1b. Agents, as the core components of Bio-Copilot, utilize LLMs as their central control nucleus. Based on task allocation, agents with different roles undertake distinct responsibilities. The coordination layer is responsible for mediating interactions between agents and the environment, as well as orchestrating the behaviors of agents. The environment, as an external context of Bio-Copilot, influences the behavior of agents, while the actions of these agents in turn modify the state of the environment.

Bio-Copilot employs AutoGen as its underlying framework that enables developers to customize task-specific agents from the predefined agent modules, and incorporates natural language conversation protocols to facilitate interactions between users and agents. In the coordination layer of Bio-Copilot, we design an agent group management strategy in the form of community structure to administer agents in various roles and coordinate inter-group communications. This strategy is optimized for addressing large-scale bioinformatics research tasks involving the engagement of numerous agents. Specifically, the task of constructing a large-scale human lung cell atlas employs three agent groups: coarse-level planning, fine-level planning, and action execution. Additionally, we devise three effective strategies within the coordination layer: A user-friendly and efficient human-agent interaction mechanism supports close collaboration between human experts and multiple agents; A shared interdisciplinary knowledge database enhances the cognitive capabilities of agents through knowledge empowerment, and supports task-driven extraction of relevant information; Continuous learning strategies, such

as self-reflective learning, enhance the decision-making and execution capabilities of agents, thereby rapidly accommodating emerging and challenging bioinformatics research tasks.

Agent group management strategy

We illustrate the agent group management strategy using the case of agent groups engaged in the task of constructing a large-scale human lung cell atlas. Each group comprises multiple agents fulfilling distinct roles, and those agents sharing the same role across different groups exhibiting slightly different variations in responsibilities.

Coarse-level planning group. As the name suggests, the coarse-level planning group aims to formulate a coarse-grained task execution plan based on user inputs that typically comprise task specifications and data descriptions. This group has three agents: 'Planner', 'User Proxy' and 'Reviewer'. 'Planner' initially receives user inputs and generate an overall plan. Subsequently, 'Reviewer' meticulously reviews the overall plan and propose s suggestions for revisions. Afterwards, 'Planner' revises the overall plan based on suggestions, and relays the revised overall plan to 'User Proxy'. 'User Proxy' provides a static human-agent interaction interface, enabling users to verify whether the overall plan requires any further adjustments.

Fine-level planning group. The fine-level planning group has similar agent roles and internal communication protocols to the coarse-level planning group, consisting of 'Refined Planner', 'User Proxy', and 'Reviewer'. The difference is that the fine-level planning group receives a single step from the overall plan devised by the coarse-level planning group as input, to generate and refine a more detail plan for that step.

Action execution group. Action execution refers to code generation, execution and debugging, involving data loading and writing, information

retrieval, and tool invocation. This group consists of four agents including
'Coder', 'Executor', 'User Proxy' and 'Checker'. Specifically, 'Coder' receives the
detail plan for the current step from the fine-level planning group and generates
the corresponding code. 'Executor', equipped with a Python kernel and a code
execution environment, is responsible for receiving and executing the code
generated by 'Coder'. Following code execution, 'Checker' receives outcomes
returned by 'Executor', undertakes code debugging, identifies issues within the
current code, suggests remedial modifications, and returns these to 'Coder' as
feedback. 'User Proxy' is responsible for the termination. Moreover, within the
action execution group, 'User Proxy' offers two types of human-agent
interaction interfaces (i.e., static and dynamic). The static interface is exposed
following the initial receipt of code by 'Coder', so that users can inspect the code
for any potential issues before execution. The timing of the dynamic interface
exposure is determined by 'Checker'. 'Checker' will instruct 'User Proxy' to
expose the dynamic human-agent interface in three specific situations. Firstly,
'Checker' receives a repeated execution error, indicating 'Coder' inability to
correct the error. Secondly, 'Checker' receives more than five error messages
pertaining to code anomalies. Thirdly, 'Checker' identifies instances
necessitating manual specification of names within errors, such as actual gene
names present in the dataset. Additionally, the code generation capability of
'Coder' is enhanced through continuous learning by feeding its output from the
previous step into the current one, ensuring the continuity and consistency of
generated code. When the code is executed successfully, 'User Proxy' will
terminate the group conversation.
Communications between agent groups. With in each agent group, we have
introduced how agents interact. In this section, we will comprehensively
elaborate the communication mechanisms between agent groups. The three
agent groups communicate approximately linearly. As illustrated in Figure 2,
the coarse-level planning group decomposes user-assigned task into a multi-
step overall plan following predefined rules, with subsequent refinements. Then,

the fine-level planning group iteratively conducts further detailed planning on
each step of the overall plan in a loop manner, subsequently refining the
detailed execution plans for each step. The action execution group is
responsible for executing the detailed execution plan of each step, involving
code generation, running, and debugging. Upon completion of a step, the
process iterates to the next one until the entire overall plan is accomplished.
915

Human-agent interaction mechanism

Although Bio-Copilot can autonomously carry out many routine bioinformatics
analysis tasks, human-agent collaboration remains the most effective approach
in tackling complex and dynamic tasks. There are three primary reasons: Firstly,
bioinformatics analysis tasks often entail personalized data processing stages,
where agents relying on their inherent knowledge may struggle to
accommodate personalized requirements. Secondly, when agents cannot
autonomously resolve encountering errors, they risk being locked in infinite
loops, hindering progression to subsequent steps. Lastly, insufficient user input
can lead to misinterpretations by agents due to information gaps, resulting in
erroneous decisions or failed executions.
927

In the data-intelligence-intensive research paradigm, both human experts and
AI agents serve as core participants in the scientific investigation. To support
the tightly coupled human-agent collaborative workflow, we design a user-
friendly and efficient human-agent interaction mechanism for Bio-Copilot.
Departing from conventional static human-agent interaction models, where the
timing of human interaction with Bio-Copilot is fixed, we devise a dynamic
human-agent interaction mechanism that enables agents to determine the
timing of exposing the human-agent interaction interfaces based on the
fulfillment of predetermined conditions, thereby ensuring high real-time

interaction capabilities. This dynamic human-agent interaction mechanism is
extensively employed within the action execution group, that can enhance the
capabilities of agents to tackle complex and dynamic tasks. Bio-Copilot
integrates both dynamic (appears in action execution group) and static
(appears in all agent groups) human-agent interaction mechanisms, optimizing
autonomous task execution while minimizing unnecessary human intervention.
943

Shared interdisciplinary knowledge database

We establish a shared interdisciplinary knowledge database within Bio-Copilot,
thereby augmenting the cognitive capacities of agents with diverse roles
through knowledge empowerment. By collecting and encoding knowledge from
multidisciplinary research articles into a form comprehensible to agents, the
shared interdisciplinary knowledge database enables agents to retrieve
relevant information. For instance, during coarse-level planning, 'Planner'
initiates its process by retrieving relevant information from the knowledge
database, which is then strategically integrated as supplementary cues into its
planning workflow. Knowledge-driven insights augment the input of 'Planner',
thereby the planning quality of 'Planner' is enhanced by enriching the decision-
making process with informed perspectives. In Bio-Copilot, knowledge
empowerment is crucial for achieving high autonomy and efficiency in handling
complex biological data and tasks, which can alleviate biases and illusions
inherent in reasoning and decision-making processes.
959

Continuous learning.

In order to rapidly accommodate emerging and challenging bioinformatics
research tasks, we devise continuous learning strategies for Bio-Copilot,
incorporating self-reflective learning. In Bio-Copilot, agents engage in self-

reflective learning by reviewing their own behaviors, progressively refining
autonomous decision-making and execution capabilities over time, thereby
enhancing task efficiency in subsequent missions through process streamlining,
selecting optimal tools, and minimizing manual intervention. For example, the
self-reflective learning mechanism is embodied in two kinds of agents, i.e,
'Reviewer' and 'Checker', that are responsible for examining the plans
formulated by 'Planner' (or 'Refined Planner') and the code produced by 'Coder'.
Through iterative interactions and self-reflective learning, they have refined
their capabilities to autonomously suggest modifications, thereby improving the
quality of feedback.

B. Experimental Setup

Datasets

Data for constructing the core HLCA (human lung cell atlas) is derived from 11
independent studies[123,124,125,126,127,128,129,130,131,132], integrating 14 datasets
comprising 168 health lung tissue samples from a total of 107 individual donors,
with diversity in age, sex, ethnicity, BMI and smoking status. The HLCA project
has preprocessed these datasets, involving harmonization of cell type
nomenclature, alignment of gene nomenclature, data quality control, and data
normalization. Specifically, the HLCA project established a five-level
hierarchical cell type nomenclature to harmonize cell types across datasets,
aligned gene nomenclature to the GRCh38[133] human genome reference with
Ensembl[134] standardization, applied quality control to exclude cells with fewer
than 200 genes and genes expressed in less than 10 cells, and performed
SCRAN[135] normalization on raw counts for uniformizing UMI counts per cell.

The workflow of constructing a large-scale lung cell atlas

The workflow of constructing a large-scale human lung cell atlas is accomplished through a collaborative effort between researchers and Bio-Copilot, which mainly comprises four tasks: dataset integration task, hierarchical clustering task, cell type annotation task, and downstream analysis task. For each task, researchers specify the task objectives, prompting Bio-Copilot to generate an initial execution plan, which then iteratively refined via extensive human-machine interactions, guided by researcher feedback informed by insights and experience. Additionally, during the task execution phase of Bio-Copilot, researchers can actively engage in human-machine interactions to identify and rectify incorrect actions of the system.

Data integration. To integrate disparate single-cell datasets of lung tissue, data integration algorithms are employed to yield an integrated embedding that aligns cells of the same type across independent datasets within a feature expression space. This unified embedding facilitates the construction of a comprehensive and unbiased cell atlas, enabling insightful analyses into the biological diversity and heterogeneity within lung tissue. Bio-Copilot queries single-cell data integration methods to get current existing numerous approaches, such as BBKNN[136], fastMNN[137], Harmony[138], Scanorama[139], scGEN[140], scANVI[111], scVI[141], and Seurat[142]. Through further document retrieval, Bio-Copilot gained knowledge from the research study of scIB[143] benchmarking, that evidences the capability of scANVI in achieving the optimal comprehensive performance. Hence, Bio-Copilot employs scANVI to perform single-cell dataset integration, and retrieves its code example for automatic code generation. Next, we describe the key parameter settings in the order of code, all of which are set by Bio-Copilot and can be adjusted according to the feedback of experts. To prepare the input of the top 2,000 highly variable genes (HVGs) for scANVI, the scanpy.pp.highly_variable_genes function provided by

the scanpy[144] toolkit is employed to process raw count data, configured with

parameters: batch_key='dataset',   min_mean=0.6,   flavor='cell_ranger',

n_top_genes=2000, leaving default settings for all other parameters.

Furthermore, scANVI can use cell labels to improve performance, thus the

curated original cell types are employed. Guided by user prompts, Bio-Copilot

utilizes the names of the independent study datasets as batch-covariates, sets

the number of hidden features to 30 for scANVI, while other parameters are

automatically configured to their defaults: n_layers=2, encode_covariates=True,

deeply_inject_covariates=False, gene_likelihood='nb', with GPU acceleration

enabled via use_cuda=True. Employing GPUs significantly accelerates the

training process of the scANVI method. The trained scANVI model outputs the

hidden embeddings of the integrated datasets, which have undergone batch-

effect correction and are utilized for subsequent clustering analyses and

visualization tasks.

1033

Hierarchical clustering. Following data integration, the integrated dataset

comprises 587,218 cells. To gain deeper insights into cellular diversity and

heterogeneity, Bio-Copilot performs a hierarchical clustering with 4 levels to

delineate cell populations by iterating from coarse to finer resolutions. Firstly,

the K-nearest neighbor graph of the hidden embeddings is constructed using

the scanpy.pp.neighbors function, with the parameter for the number of

neighbors set to n_neighbors=30. At the first level of clustering (i.e., the

coarsest level), a leiden clustering function scanpy.tl.leiden is employed to

generate the first level cell population clusters, with the clustering resolution

parameter of resolution=0.01. Subsequently, new K-nearest neighbor graphs

for each cluster from the first level cell populations are constructed using the

hidden   embeddings   and   the   scanpy.pp.neighbors   function   with

n_neighbors=30 again. Reapplying leiden clustering to each cluster from the

first level, with a clustering resolution parameter of resolution=0.1, produces the

second level cell populations. Next, sequentially proceeding the third and fourth

level analysis like second level ultimately generates a hierarchical, four-level

structure of cell populations. In order to track relationships among cell

populations effectively, hierarchical clusters are labeled according to their

parental lineage and ordinal position among sisters, such that Cluster 1_2

denotes the third sub-cluster (counting from 0) of Cluster 1. Besides, Bio-

Copilot employs scanpy.tl.rank_genes_groups function with default parameters

in scanpy toolkit to perform differential expression analysis for clusters at each

level. Furthermore, for visualizing cell clusters at each level, the K-nearest

neighbor graph of the hidden embeddings is fed to the scanpy.tl.umap function

for dimensionality reduction followed by scanpy.pl.umap function to plot 2D

UMAPs, where the color parameter in scanpy.pl.umap is set to the level key of

hierarchical clustering and the palette parameter defines the colors for cell

clusters.

1062

Cell type annotation. Bio-Copilot performs cell type annotation for cell clusters

in the hierarchical structure. Considering the coarse granularity of first level

clusters renders their annotation less informative, thus the cell type annotation

is performed from level 2 to level 4. Bio-Copilot ingests a database of human

cell marker genes from CellMarker[145], and subsequently invokes the Decoupler

tool to identify cell types for each cluster based on that database. Decoupler

uses the over representation analysis (ORA) function to process a table for

screening lung tissue associated cell types from the database and the

integrated dataset with 2,000 HVGs, leaving default settings for all other

parameters. Then, Decoupler employs statistical test function

dc.rank_sources_groups to identify which are the top predicted cell types for

each cluster, with parameters of groupby='cluster_level_2', reference='rest',

method='t-test_overestim_var' for level 2 cell clusters. Based on the results of

the statistical test, Bio-Copilot considers the rank of significance score and

mean foldchange value to calculate a comprehensive ranking, annotating the

top 1 cell type for each cluster. If a cluster has a top 1 significance score of less

than 30, the cluster is classified as unknown cell type. This same strategy is then replicated for the annotation of level 3 and level 4 cell clusters, with parameters groupby='cluster_level_3' and groupby='cluster_level_4' in statistical tests, respectively. After completing the cell type annotation, Bio-Copilot perform some basic statistical analysis for each well-annotated cell type at level 4, including the number of cells, original dataset distribution, and information entropy. Furthermore, Bio-Copilot performs differential expression analysis for these well-annotated cell types at level 4 to uncover marker genes. The scanpy.tl.rank_genes_groups function in scanpy toolkit is utilized for differential expression analysis, with the groupby parameter set to the group of level 4 cell types, n_genes=2 specifying the top 2 differentially expressed genes to retrieve, and the parameter of statistical test method='wilcoxon'. To refine the selection for more significant differentially expressed genes, the scanpy.tl.filter_rank_genes_groups function is applied for additional filtering with default parameters: min_in_group_fraction=0.7, max_out_group_fraction=0.2, min_fold_change=2. After filtering, the differentially expressed genes are ranked based on significance and inter-group variation, enabling the selection of a subset of top 2 genes as marker genes for each cell type.

Downstream analysis. Following the cell type annotation, Bio-Copilot performs rare cell type analysis and variance between individuals explained by covariates in downstream analysis to explore new scientific discoveries. For the rare cell type analysis, Bio-Copilot merge the unknown cell subtypes upward to keep the unknown cell types in the higher granularity, enabling top-down analysis. Bio-Copilot first performs basic statistical analysis for unknown cell types, including the number of cells, original dataset distribution, and information entropy. Based on these results, their rare properties are inferred. Bio-Copilot further analyzes the three significant rare cell types derived from level 2, including the original cell type distributions, and differential expression

analysis with all cell types at level 2. The scanpy.tl.rank_genes_groups function

in scanpy toolkit is utilized for differential expression analysis, with the groupby

parameter set to the group of level 2 cell types, and the parameter of statistical

test method='wilcoxon'. The specifically expressed gene set for each rare cell

type is obtained with significance P-value<0.05. Based on the specifically

expressed gene set, Bio-Copilot calls Enrichr enrichment analysis tool to parse

the biological processes using the GO_Biological_Process_2023 database. For

variance between individuals explained by covariates, Bio-Copilot performs

statistical analysis to elucidate the correlations between covariates in technical

methods and biological characteristics. A quantitative assessment of the

variance in gene expression profiles attributable to each covariate within every

cell type is performed. To ensure robust statistical analysis, the cell types

represented by fewer than two samples or those with a total cell count below

50 are excluded, while any sample within a cell type containing less than ten

cells is also excluded. Initially, the covariate statuses and 30 scANVI latent

embeddings per sample for every cell type are statistically summarized to

generate matrices. Statistical summaries for scANVI latent embeddings, UMI

counts, and mitochondrial ratios involve averaging across all cells within a

sample, whereas other covariates are sampled from any cell within the sample,

as they remain invariant among cells from the same sample. Within matrices

derived for each cell type, linear regressions between each covariate and each

scANVI latent embedding are conducted to predict the embedding feature

explained by each covariate, subsequently calculating variances. Finally, the

variances across all scANVI latent embeddings are summed to quantify the

differential impact of covariates across individual samples. Bio-Copilot further

calculates the correlations between variance explained and various covariates,

including the correlation between the diversity in tissue sampling methods for a

cell type and the fraction of variance explained by sampling method for that cell

type, the correlation between the ratio of variance explained by biological

covariates versus technical covariates for a cell type and the number of

samples in that cell type, and the correlation between the mean variance
explained by covariates in a cell type and the number of samples in that cell
type.

1142

Implementation Details

Computing resource. All analyses presented in the study run on Bio-OS[146]
with elastic resources, at least 128Gb RAM memory, 128 cores of 2.5GHz CPU,
and a GPU with 32Gb memory. And the following python (v3.11) packages
support for Bio-Copilot and lung cell atlas workflow are required:
python==3.11.7, chainlit==1.0.100, autogen==1.0.16, pyautogen==0.2.19,
openai==1.14.0, jupyter==1.0.0, httpx==0.23.0, jupyterlab==4.0.12,
notebook==7.0.8, torch=1.7.1+cu110, scanpy==1.10.0, scarches[147]==0.3.5,
decoupler==1.6.0, numpy==1.26.4, pandas=2.2.2, scikit-learn==1.4.2

1152

Details of the system. The preliminary input from the user includes the task
and dataset descriptions, separated by a line break. Upon receipt of this
preliminary input, Bio-Copilot is initiated into operation. Specifically, the user's
task requirements are subjected to the coarse-level planning group to obtain a
high-level plan that is used to extract steps with a step extractor. Then, each
step is sent to the fine-level planning group for a detailed plan. Moreover, at the
end stage of the coarse-level planning and the fine-level planning groups, Bio-
Copilot will automatically provide an interactive interface for users to determine
whether the plan completed by the agents still needs to be modified. The action
execution group receives information from the fine-level planning group and is
responsible for generating, debugging, and executing code. During the code
debugging process, if a code error arises that the group cannot resolve
independently, the group will provide an interactive interface for users to
participate in solving the error. Once the code for the current step runs

successfully, the action execution is terminated. Bio-Copilot cyclically executes

fine-level planning and action execution groups according to the steps division

until all are completed. When Bio-Copilot completes the user's task, it exits the

operational mode, and returns to a waiting state.

1171

Details in the construction of the lung cell atlas.

Data integration. Firstly, user provides the task and dataset descriptions as the

initial input, that is, "Perform single-cell data integration. xxx.h5ad: all single-

cell data need to be integrated and analysis for constructing the human lung

cell atlas. The adata column of "integration_label" contains the label information

for integration.". The main steps of coarse-level planning include: (i) Load and

preprocess the data; (ii) Integrate the data using scANVI; (iii) Generate

integrated embeddings; (iv) Save the integrated data. Next, when performing

the data preprocessing step, the agent is prompted to omit the visualization

step, "do not need to do any visualizations", to improve the running efficiency.

When executing the scANVI model training step, the 'Coder' agent will call

existing documents to assist in code writing, which uses the default parameter

values in documents. The user can let the agent modify the corresponding

parameter values according to the actual data situation and use the GPU to run

the program, that is, "use os to set gpu id as 4, set unlabeled_category as

'unlabeled'". Finally, when saving the integrated data, the agent is prompted to

save the scANVI integration results of highly variable genes to the original adata,

i.e., "save the integration result of scanvi to the original adata instead of

adata_hvg".

1191

1192 Hierarchical clustering. User provides the task and dataset descriptions, that is,

1193 " Perform multi-level clustering of the cells in the HLCA. Note that counting the

1194 initial clustering, the total number of clustering levels is 4. For the final HLCA,

1195 you also need calculate marker genes for every clustering. xxx.h5ad: the

1196 integrated single-cell data with scANVI that needed to be multi-level clustered.

The integrated representation is in "X_scANVI" of the adata.". The main steps of coarse-level planning include: (i) Load the dataset; (ii) Initial clustering (level 1); (iii) Subsequent clustering (levels 2-4); (iv) Calculate marker genes for each cluster; (v) Save the final annotated dataset. When hierarchical clustering is performed, sub-cluster labels need to be generated and saved to adata and csv files for subsequent analysis. Therefore, this prompt is provided, "generate new sub-clustering labels for each cluster and update dataset with new sub-cluster labels.". When calculating marker genes for each cluster, the agent needs to be prompted to provide the groups parameter in sc.tl.rank_genes_groups according to the cluster label. In addition, two perspectives "sister" and "all" are adopted to calculate marker genes, and the difference between them needs to be suggested to the agent, i.e., "all is a standard computational logic. sister refers to the situation where when the cluster depth is greater than 1, you need to use the clusters within groups as adata to calculate marker genes.". Besides, parameters such as resolution used in clustering can also be artificially specified.

Cell type annotation. Similarly, user provides the task and dataset descriptions, that is, " Perform cell types annotation with python packages. xxx.h5ad: stores 3 level clustering label (cluster_level_2, cluster_level_3, cluster_level_4) which is used for annotation. highly_variable parameter can be used for selecting highly variable genes.". The mainly steps of the coarse-level planning include: (i) Load the necessary libraries for analysis; (ii) Load and preprocess the data; (iii) Prepare the database of marker genes for Decoupler; (iv) Run Decoupler for cell type annotation; (v) Save the annotated data. During the planning phase, human intervention removes unnecessary steps, "Delete the step that Initialize the Decoupler model with the default cell marker information. please annotation on all cluster levels.". In addition, when multiple agents cannot identify data structures or some personalized data processing is required, users also need to intervene through human interaction interfaces in a timely manner. For

example, in the step of preparing the database of marker genes for Decoupler, provides "Set adata.var_names to 'gene_symbols' in adata.var" or "Retain data where adata.var.highly_variable is true for cell annotation and copy it.", and similar instructions.

Rare cell type analysis in downstream analysis. Firstly, user needs to describe the task and dataset, i.e., "I now have clustering and annotation results. I want to discover rare cell types. What should I do? I will provide you with all the data and information as follows. hlca_decoupler_annotation.h5ad: Already annotated cell data. The multi-level clustering results are stored in 'cluster_level_1', 'cluster_level_2', 'cluster_level_3', 'cluster_level_4'.". The main steps of coarse-level planning include: (i) Load the annotated cell data; (ii) Identify and validate rare cell types; (iii) Validate rare clusters using annotation; (iv) Further analysis to confirm rare cell types; (v) Save the results. In the planning stage, user needs to guide the agent to conduct further analysis on possible rare cell types, providing guidance such as "You need to do further analysis to confirm rare cells, rather than simply judging by the existing clustering and annotation results." or "The current clustering and annotation results are all multi-level results. Can you use this information to do further analysis?" When confirming possible rare cell type clusters, the agent sets a threshold by default, and the user need to guide the specific threshold setting.

Variance explained by covariates in downstream analysis. User provides the task and dataset description as the initial input, i.e., "Determine how much of the variance in the integrated HLCA embedding is explained by each of the metadata covariates including ... . You need to use the results of the fourth level annotation in 'ann_level_4_dc_final' for analysis. Note that your analysis should be conducted from sample-level observations." The main steps of coarse-level planning include: (i) Load the data, (ii) Extract and aggregate relevant data, (iii) Perform variance analysis, (iv) Save the model results. Since the task contains

a lot of personalized data processing and conditional judgments, the user needs to provide relevant prompts. For instance, in the data load and preprocessing steps, unnecessary processing is eliminated, and the prompt "do not need to handle missing values" is given. When integrating data from the sample level (step (ii)), Bio-Copilot will save all dimensions of "X_scANVI" into one parameter, which makes subsequent variance analysis impossible. Therefore, the user must provide the prompt as "Store each component of the X_scanvi_embed as a separate row in the aggregated_row. You can first fill other data into aggregated_row. Then use a for loop to add component keys into aggregated_row with changing key names". In variance analysis (step (iii)), users need to give a prompt like "Y may be NAN or string value, you should deal with these conditions.". Besides, users can provide necessary parameter settings to Bio-Copilot. Otherwise, Bio-Copilot will automatically set parameter values or generate code according to default values.

C. Evaluation Metrics

Metrics for Bio-Copilot benchmarking

Task planning evaluation. This section aims to verify whether Bio-Copilot can achieve superior planning performance compared to control group and ablation group. We have selected the following 10 metrics to measure the performance of different methods:
- Clarity. It evaluates the explicitness and logical coherence of the generated plan in its expression. A clear plan should allow the executor to understand and implement it without ambiguity.
- Technical Feasibility. It considers the practical operability of the solutions proposed in the plan. Technical feasibility includes assessing the necessary resources, current technological limitations, and potential risks.

- Structurality. The structurality metric focuses on the organization and layout

of the plan. Good structurality implies that the plan has a clear beginning,

middle, and end phases, with logical coherence between each stage.

- Comprehensiveness. The comprehensiveness metric measures whether the

plan has considered all relevant constraints and objectives. A comprehensive

plan should cover all aspects of the issue without omitting key execution steps

or objectives.

- Rationality of Method Selection. It assesses the match between the chosen

algorithm and the needs of the plan. A rational choice of algorithm should be

based on the problem's characteristics and constraints to ensure the plan's

efficiency and effectiveness.

- Risk Management. Assesses the identification, analysis, and mitigation

strategies for potential risks and uncertainties in the plan.

- Data Management. Refers to systematic organization, storage, and handling

of data to ensure its accuracy, accessibility, and security throughout the

research process.

- Scientific Rigor. Involves the strict application of scientific methods and

principles to ensure the reliability, validity, and reproducibility of research

findings.

- Resource Allocation. Examines the efficiency and appropriateness of the

resources (time, budget, personnel, equipment) allocated for the task.

- Scalability. Evaluates the potential for the plan to be scaled up or adapted for

larger or different contexts if successful.

1307

1308 We use GPT-4 to score the above indicators for task planning evaluation in all

1309 tasks, where the prompt is illustrated in Supplementary Figure 1a.

1310

Code quality evaluation. This section aims to validate the effectiveness of Bio-

Copilot in generating reliable and executable task code. We have adopted the

following 12 metrics to measure and compare the performance of different

methods:

- Accuracy. Assesses whether the generated code can accurately implement

the established functions and requirements.

- Efficiency. It focuses on the performance of the code in terms of resource

consumption, including but not limited to execution time, memory usage, and

CPU utilization rate.

- Completeness. Measures whether the generated code includes all necessary

components to achieve the intended functionality.

- Readability. Evaluates the clarity and understandability of the code, involving

the appropriateness of naming conventions, structural organization, and

comments.

- Logicality. It checks the coherence and rationality of the internal logical flow

of the code, including the correct application of conditional statements, loop

structures, and exception handling.

- Portability. Evaluates the code's ability to be transferred between different

environments or datasets.

- Maintainability. This dimension assesses how easily the code can be modified

or extended in the future. It includes factors like modularity, use of comments,

and adherence to coding standards.

- Reusability. This dimension evaluates the extent to which parts of the code

can be reused in different projects or contexts. It looks at the generality and

modularity of the code.

- Robustness. This dimension assesses the code's ability to handle unexpected

inputs or conditions without crashing or producing incorrect results. It includes

error handling and validation mechanisms.

- Security. This dimension assesses the code's ability to protect against

unauthorized access, data breaches, and other security threats. It includes

secure coding practices and data protection measures.

- Usability. This dimension evaluates how user-friendly the code is, particularly

for non-developers or domain experts. It includes aspects like clear

documentation, intuitive interfaces, and ease of use.

- Scalability. This dimension measures how well the code can handle increasing

amounts of data or more complex computations without significant performance

degradation.

1348

1349 We also use GPT-4 to score the above indicators for code quality evaluation in

1350 all tasks, where the prompt is illustrated in Supplementary Figure 1b.

1351

Execution efficiency evaluation.

This section aims to evaluate the task completeness, user interventions,

runtime, computing resource cost of Bio-Copilot during task execution.

- Task completeness. The proportion of completed steps to the total number of

steps.

- User interventions. The total number of conversations initiated by users, each

of which is counted as one human-agent interaction round.

- Runtime. The total time from the start of a task until completion or termination.

- Computing resource cost. Average CPU, GPU, and memory usage during

task execution.

1362

1363 **Comprehensive score.**

1364 We use the following formula to synthesize task planning evaluation, code

1365 quality evaluation, and execution efficiency evaluation to calculate a

1366 comprehensive performance score for each method,

1367
$$overall\ score = \omega_1 * \left(\frac{1}{N_p}\sum_{i=1}^{p} P_i + \frac{1}{N_c}\sum_{j=1}^{c} C_j\right) + \omega_2 * tc + \omega_3 * \frac{tc}{ha+1} + \omega_4 * tc$$

1368
$$* \left(\frac{1}{rt} + \frac{1}{N_{cpu} + N_{gpu} + N_{mem}}\right)$$

where $\omega_1 \sim \omega_4$ indicate the weights, $N_p = 10$ indicates the 10-evaluation
metrics for task planning, $N_c = 12$ indicates the 12-evaluation metrics for code
quality, tc indicates task completeness, ha indicates the number of user
interventions, rt indicates the runtime of a task, $N_{cpu}, N_{gpu}, N_{mem}$ indicate
average CPU, GPU, and memory usage during task execution. In this study,
the weights are set as $\omega_1 = 2, \omega_2 = 20, \omega_3 = 5, \omega_4 = 1$ for the
comprehensive performance score, as illustrated in Figure 3a.

1376

1377 Metrics for lung cell atlas analysis

1378 **Entropy.** We employ Shannon entropy to quantify the amount of uncertainty or
1379 information content inherent in a discrete distribution. Formally, it measures the
1380 average amount of information conveyed by each event in a discrete probability
1381 distribution. The Shannon entropy is defined as

1382
$$H(X) = -\sum_{i=1}^{n} p(x_i) log_b(p(x_i))$$

where n is the number of possible outcomes, $p(xi)$ represents the probability
of the ith outcome occurring, and the base of the logarithm b determines the
unit of measurement (commonly, $b = 2$ for bits). A higher entropy value
suggests higher uncertainty or disorder; conversely, a lower entropy implies
more predictability or order within the system. In this study, Shannon entropy
helps in identifying cell type label disagreement for a specific level of annotation,
and calculating the diversity of donors or tissue sampling methods in a cluster.

1390

VI. Data availability and Code availability

1393 Data and code are available in https://doi.org/10.5281/zenodo.11210015 and
1394 https://github.com/lyyang01/Bio-Copilot respectively.
1395

Acknowledgements

1397 This work was supported by self-supporting Program of Guangzhou National

Laboratory (Grant No. SRPG22007), youth science foundation of Guangzhou

National Laboratory (Grant No. QNPG23-12).

1400

Author contributions

Conceptualization: Yixue Li.

Supervision: Jiao Yuan, Yixue Li.

Algorithm development and implementation: Yang Liu, Lu Zhou, Rongbo Shen.

Datasets collection, processing and application: Rongbo Shen, Yang Liu, Lu Zhou.

Methods comparisons: Yang Liu, Lu Zhou, Rongbo Shen.

Biological interpretation: Rongbo Shen.

Manuscript writing and figure generation: Rongbo Shen, Yang Liu, Lu Zhou.

Manuscript reviewing: Yixue Li.

All authors approved the manuscript.

1411

Competing interests

1413 The authors declare no competing interests.

1414

Reference

1415

1. Kanehisa, Minoru, and Peer Bork. "Bioinformatics in the post-sequence era." Nature genetics vol. 33 Suppl (2003): 305-10. doi:10.1038/ng1109

2. Gauthier, Jeff et al. "A brief history of bioinformatics." Briefings in bioinformatics vol. 20,6 (2019): 1981-1996. doi:10.1093/bib/bby063

3. Soon, Wendy Weijia et al. "High-throughput sequencing for biology and medicine." Molecular systems biology vol. 9 (2013): 640. doi:10.1038/msb.2012.61

4. Lan, Freeman et al. "Single-cell genome sequencing at ultra-high-throughput with microfluidic droplet barcoding." Nature biotechnology vol. 35,7 (2017): 640-646. doi:10.1038/nbt.3880

5. Shendure, Jay, and Hanlee Ji. "Next-generation DNA sequencing." Nature biotechnology vol. 26,10 (2008): 1135-45. doi:10.1038/nbt1486

6. Kalisky, Tomer, and Stephen R Quake. "Single-cell genomics." Nature methods vol. 8,4 (2011): 311-4. doi:10.1038/nmeth0411-311

7. Gawad, Charles et al. "Single-cell genome sequencing: current state of the science." Nature reviews. Genetics vol. 17,3 (2016): 175-88. doi:10.1038/nrg.2015.16

8. Tanay, Amos, and Aviv Regev. "Scaling single-cell genomics from phenomenology to mechanism." Nature vol. 541,7637 (2017): 331-338. doi:10.1038/nature21350

9. Sandberg, Rickard. "Entering the era of single-cell transcriptomics in biology and medicine." Nature methods vol. 11,1 (2014): 22-4. doi:10.1038/nmeth.2764

10. Stegle, Oliver et al. "Computational and analytical challenges in single-cell transcriptomics." Nature reviews. Genetics vol. 16,3 (2015): 133-45. doi:10.1038/nrg3833

11. Doerr, Allison. "Single-cell proteomics." Nature methods vol. 16,1 (2019): 20. doi:10.1038/s41592-018-0273-y

12. Marx, Vivien. "A dream of single-cell proteomics." Nature methods vol. 16,9 (2019):
809-812. doi:10.1038/s41592-019-0540-6

13. Schoof, Erwin M et al. "Quantitative single-cell proteomics as a tool to characterize
cellular hierarchies." Nature communications vol. 12,1 3341. 7 Jun. 2021,
doi:10.1038/s41467-021-23667-y

14. Zenobi, R. "Single-cell metabolomics: analytical and biological
perspectives." Science (New York, N.Y.) vol. 342,6163 (2013): 1243259.
doi:10.1126/science.1243259

15. Seydel, Caroline. "Single-cell metabolomics hits its stride." Nature methods vol.
18,12 (2021): 1452-1456. doi:10.1038/s41592-021-01333-x

16. Cook, Charles E et al. "The European Bioinformatics Institute in 2016: Data growth
and integration." Nucleic acids research vol. 44,D1 (2016): D20-6.
doi:10.1093/nar/gkv1352

17. Manzoni, Claudia et al. "Genome, transcriptome and proteome: the rise of omics
data and their integration in biomedical sciences." Briefings in bioinformatics vol.
19,2 (2018): 286-302. doi:10.1093/bib/bbw114

18. Akhtar, Asifa et al. "A decade of molecular cell biology: achievements and
challenges." Nature reviews. Molecular cell biology vol. 12,10 669-74. 23 Sep. 2011,
doi:10.1038/nrm3187

19. Hamburg, Margaret A, and Francis S Collins. "The path to personalized
medicine." The New England journal of medicine vol. 363,4 (2010): 301-4.
doi:10.1056/NEJMp1006304

20. Chin, Lynda et al. "Cancer genomics: from discovery science to personalized
medicine." Nature medicine vol. 17,3 (2011): 297-303. doi:10.1038/nm.2323

21. Topol, Eric J. "High-performance medicine: the convergence of human and artificial
intelligence." Nature medicine vol. 25,1 (2019): 44-56. doi:10.1038/s41591-018-
0300-7

22. Elemento, Olivier et al. "Artificial intelligence in cancer research, diagnosis and
therapy." Nature reviews. Cancer vol. 21,12 (2021): 747-752. doi:10.1038/s41568-
021-00399-1

23. Stegle, Oliver et al. "Computational and analytical challenges in single-cell transcriptomics." Nature reviews. Genetics vol. 16,3 (2015): 133-45. doi:10.1038/nrg3833

24. Argelaguet, Ricard et al. "Computational principles and challenges in single-cell data integration." Nature biotechnology vol. 39,10 (2021): 1202-1215. doi:10.1038/s41587-021-00895-7

25. Min, Seonwoo et al. "Deep learning in bioinformatics." Briefings in bioinformatics vol. 18,5 (2017): 851-869. doi:10.1093/bib/bbw068

26. Wainberg, Michael et al. "Deep learning in biomedicine." Nature biotechnology vol. 36,9 (2018): 829-838. doi:10.1038/nbt.4233

27. Mahmud, Mufti et al. "Applications of Deep Learning and Reinforcement Learning to Biological Data." IEEE transactions on neural networks and learning systems vol. 29,6 (2018): 2063-2079. doi:10.1109/TNNLS.2018.2790388

28. Woolley, Anita Williams et al. "Evidence for a collective intelligence factor in the performance of human groups." Science (New York, N.Y.) vol. 330,6004 (2010): 686-8. doi:10.1126/science.1193147

29. Karpatne, Anuj, et al. "Theory-guided data science: A new paradigm for scientific discovery from data." IEEE Transactions on knowledge and data engineering vol. 29,10 (2017): 2318-2331. doi:10.1109/TKDE.2017.2720168

30. Holzinger, Andreas et al. "AI for life: Trends in artificial intelligence for biotechnology." New biotechnology vol. 74 (2023): 16-24. doi:10.1016/j.nbt.2023.02.001

31. Messeri, Lisa, and M J Crockett. "Artificial intelligence and illusions of understanding in scientific research." Nature vol. 627,8002 (2024): 49-58. doi:10.1038/s41586-024-07146-0

32. Sourati, Jamshid, and James A Evans. "Accelerating science with human-aware artificial intelligence." Nature human behaviour vol. 7,10 (2023): 1682-1696. doi:10.1038/s41562-023-01648-z

33. Inkpen, Kori, et al. "Advancing Human-AI complementarity: The impact of user expertise and algorithmic tuning on joint decision making." ACM Transactions on Computer-Human Interaction vol. 30,5 (2023): 1-29. doi:10.1145/3534561

34. Thirunavukarasu, Arun James et al. "Large language models in medicine." Nature medicine vol. 29,8 (2023): 1930-1940. doi:10.1038/s41591-023-02448-8

35. Singhal, Karan et al. "Large language models encode clinical knowledge." Nature vol. 620,7972 (2023): 172-180. doi:10.1038/s41586-023-06291-2

36. Zhao, Wayne Xin, et al. "A survey of large language models." arXiv preprint arXiv:2303.18223 (2023). doi:10.48550/arXiv.2303.18223. Preprint.

37. Hadi, Muhammad Usman, et al. "A survey on large language models: Applications, challenges, limitations, and practical usage." Authorea Preprints (2023). doi:10.36227/techrxiv.23589741.v1. Preprint.

38. Lander, E S et al. "Initial sequencing and analysis of the human genome." Nature vol. 409,6822 (2001): 860-921. doi:10.1038/35057062

39. International Human Genome Sequencing Consortium. "Finishing the euchromatic sequence of the human genome." Nature vol. 431,7011 (2004): 931-45. doi:10.1038/nature03001

40. Gibbs, Richard A. "The Human Genome Project changed everything." Nature reviews. Genetics vol. 21,10 (2020): 575-576. doi:10.1038/s41576-020-0275-3

41. Nurk, Sergey et al. "The complete sequence of a human genome." Science (New York, N.Y.) vol. 376,6588 (2022): 44-53. doi:10.1126/science.abj6987

42. Mardis, Elaine R. "Next-generation DNA sequencing methods." Annual review of genomics and human genetics vol. 9 (2008): 387-402. doi:10.1146/annurev.genom.9.081307.164359

43. Goodwin, Sara et al. "Coming of age: ten years of next-generation sequencing technologies." Nature reviews. Genetics vol. 17,6 (2016): 333-51. doi:10.1038/nrg.2016.49

44. Wang, Zhong et al. "RNA-Seq: a revolutionary tool for transcriptomics." Nature reviews. Genetics vol. 10,1 (2009): 57-63. doi:10.1038/nrg2484

45. Davidson, Eric H, and Douglas H Erwin. "Gene regulatory networks and the
evolution of animal body plans." Science (New York, N.Y.) vol. 311,5762 (2006):
796-800. doi:10.1126/science.1113832

46. Badia-I-Mompel, Pau et al. "Gene regulatory network inference in the era of single-
cell multi-omics." Nature reviews. Genetics vol. 24,11 (2023): 739-754.
doi:10.1038/s41576-023-00618-5

47. Feng, Suhua et al. "Epigenetic reprogramming in plant and animal
development." Science (New York, N.Y.) vol. 330,6004 (2010): 622-7.
doi:10.1126/science.1190614

48. Sharma, Shikhar, Theresa K. Kelly, and Peter A. Jones. "Epigenetics in
cancer." Carcinogenesis 31.1 (2010): 27-36. doi: 10.1093/carcin/bgp220

49. Deng, Qiaolin et al. "Single-cell RNA-seq reveals dynamic, random monoallelic
gene expression in mammalian cells." Science (New York, N.Y.) vol. 343,6167 (2014):
193-6. doi:10.1126/science.1245316

50. Carter, Benjamin, and Keji Zhao. "The epigenetic basis of cellular
heterogeneity." Nature reviews. Genetics vol. 22,4 (2021): 235-250.
doi:10.1038/s41576-020-00300-0

51. Ciccarelli, Francesca D et al. "Toward automatic reconstruction of a highly resolved
tree of life." Science (New York, N.Y.) vol. 311,5765 (2006): 1283-7.
doi:10.1126/science.1123061

52. Koonin, Eugene V. "The origin and early evolution of eukaryotes in the light of
phylogenomics." Genome biology vol. 11,5 (2010): 209. doi:10.1186/gb-2010-11-
5-209

53. Hanahan, D, and R A Weinberg. "The hallmarks of cancer." Cell vol. 100,1 (2000):
57-70. doi:10.1016/s0092-8674(00)81683-9

54. Hanahan, Douglas, and Robert A Weinberg. "Hallmarks of cancer: the next
generation." Cell vol. 144,5 (2011): 646-74. doi:10.1016/j.cell.2011.02.013

55. Dobson, Christopher M. "Protein folding and misfolding." Nature vol. 426,6968
(2003): 884-90. doi:10.1038/nature02261

56. Collins, Francis S, and Harold Varmus. "A new initiative on precision medicine." The

1559   New England journal of medicine vol. 372,9 (2015): 793-5.

1560   doi:10.1056/NEJMp1500523

1561 57. Robinson, Dan R et al. "Integrative clinical genomics of metastatic

1562   cancer." Nature vol. 548,7667 (2017): 297-303. doi:10.1038/nature23306

1563 58. Cancer Genome Atlas Network. "Comprehensive molecular portraits of human

1564   breast tumours." Nature vol. 490,7418 (2012): 61-70. doi:10.1038/nature11412

1565 59. Carpenter, Anne E et al. "CellProfiler: image analysis software for identifying and

1566   quantifying cell phenotypes." Genome biology vol. 7,10 (2006): R100.

1567   doi:10.1186/gb-2006-7-10-r100

1568 60. Bannon, Dylan et al. "DeepCell Kiosk: scaling deep learning-enabled cellular image

1569   analysis with Kubernetes." Nature methods vol. 18,1 (2021): 43-45.

1570   doi:10.1038/s41592-020-01023-0

1571 61. Senior, Andrew W et al. "Improved protein structure prediction using potentials

1572   from deep learning." Nature vol. 577,7792 (2020): 706-710. doi:10.1038/s41586-

1573   019-1923-7

1574 62. Jumper, John et al. "Highly accurate protein structure prediction with

1575   AlphaFold." Nature vol. 596,7873 (2021): 583-589. doi:10.1038/s41586-021-

1576   03819-2

1577 63. Baek, Minkyung et al. "Accurate prediction of protein structures and interactions

1578   using a three-track neural network." Science (New York, N.Y.) vol. 373,6557 (2021):

1579   871-876. doi:10.1126/science.abj8754

1580 64. Abramson, Josh et al. "Accurate structure prediction of biomolecular interactions

1581   with AlphaFold 3." Nature, 10.1038/s41586-024-07487-w. 8 May. 2024,

1582   doi:10.1038/s41586-024-07487-w

1583 65. Aibar, Sara et al. "SCENIC: single-cell regulatory network inference and

1584   clustering." Nature methods vol. 14,11 (2017): 1083-1086. doi:10.1038/nmeth.4463

1585 66. Bravo González-Blas, Carmen et al. "SCENIC+: single-cell multiomic inference of

1586   enhancers and gene regulatory networks." Nature methods vol. 20,9 (2023): 1355-

1587   1367. doi:10.1038/s41592-023-01938-4

67. Nishino, Mizuki et al. "Monitoring immune-checkpoint blockade: response
evaluation and biomarker development." Nature reviews. Clinical oncology vol.
14,11 (2017): 655-668. doi:10.1038/nrclinonc.2017.88

68. Golub, T R et al. "Molecular classification of cancer: class discovery and class
prediction by gene expression monitoring." Science (New York, N.Y.) vol. 286,5439
(1999): 531-7. doi:10.1126/science.286.5439.531

69. Keiser, Michael J et al. "Predicting new molecular targets for known
drugs." Nature vol. 462,7270 (2009): 175-81. doi:10.1038/nature08506

70. Zhavoronkov, Alex et al. "Deep learning enables rapid identification of potent
DDR1 kinase inhibitors." Nature biotechnology vol. 37,9 (2019): 1038-1040.
doi:10.1038/s41587-019-0224-x

71. Zhang, Linlin et al. "Crystal structure of SARS-CoV-2 main protease provides a
basis for design of improved α-ketoamide inhibitors." Science (New York, N.Y.) vol.
368,6489 (2020): 409-412. doi:10.1126/science.abb3405

72. Vandereyken, Katy et al. "Methods and applications for single-cell and spatial
multi-omics." Nature reviews. Genetics vol. 24,8 (2023): 494-515.
doi:10.1038/s41576-023-00580-2

73. Cui, Haotian et al. "scGPT: toward building a foundation model for single-cell
multi-omics using generative AI." Nature methods, 10.1038/s41592-024-02201-0.
26 Feb. 2024, doi:10.1038/s41592-024-02201-0

74. Eid, John et al. "Real-time DNA sequencing from single polymerase
molecules." Science (New York, N.Y.) vol. 323,5910 (2009): 133-8.
doi:10.1126/science.1162986

75. Keren, Hadas et al. "Alternative splicing and evolution: diversification, exon
definition and function." Nature reviews. Genetics vol. 11,5 (2010): 345-55.
doi:10.1038/nrg2776

76. Gebert, Luca F R, and Ian J MacRae. "Regulation of microRNA function
in animals." Nature reviews. Molecular cell biology vol. 20,1 (2019): 21-37.
doi:10.1038/s41580-018-0045-7

77. Rupaimoole, Rajesha, and Frank J Slack. "MicroRNA therapeutics: towards a new
era for the management of cancer and other diseases." Nature reviews. Drug
discovery vol. 16,3 (2017): 203-222. doi:10.1038/nrd.2016.246

78. Kozomara, Ana et al. "miRBase: from microRNA sequences to function." Nucleic
acids research vol. 47,D1 (2019): D155-D162. doi:10.1093/nar/gky1141

79. Vaswani, Ashish, et al. "Attention is all you need." Advances in neural information
processing systems 30 (2017).

80. Yao, Shunyu, et al. "Tree of thoughts: Deliberate problem solving with large
language models." Advances in Neural Information Processing Systems 36 (2024).

81. Devlin, Jacob, et al. "Bert: Pre-training of deep bidirectional transformers for
language   understanding." arXiv   preprint   arXiv:1810.04805 (2018).
Doi:10.48550/arXiv.1810.04805. Preprint.

82. Radford, Alec, et al. "Improving language understanding by generative pre-
training." (2018).

83. Brown, Tom, et al. "Language models are few-shot learners." Advances in neural
information processing systems 33 (2020): 1877-1901.

84. Achiam,   Josh,   et   al.   "Gpt-4   technical   report." arXiv   preprint
arXiv:2303.08774 (2023). doi:10.48550/arXiv.2303.08774. Preprint.

85. Touvron, Hugo, et al. "Llama: Open and efficient foundation language
models." arXiv preprint arXiv:2302.13971 (2023). doi:10.48550/arXiv.2302.13971.
Preprint.

86. Touvron, Hugo, et al. "Llama 2: Open foundation and fine-tuned chat
models." arXiv preprint arXiv:2307.09288 (2023). doi:10.48550/arXiv.2307.09288.
Preprint.

87. Raffel, Colin, et al. "Exploring the limits of transfer learning with a unified text-to-
text transformer." Journal of machine learning research vol. 21,140 (2020): 1-67.

88. Liu, Yixin, et al. "Sora: A Review on Background, Technology, Limitations, and
Opportunities of Large Vision Models." arXiv preprint arXiv:2402.17177 (2024).
doi:10.48550/arXiv.2402.17177. Preprint.

89. Mnih, Volodymyr, et al. "Playing atari with deep reinforcement learning." arXiv preprint arXiv:1312.5602 (2013). doi:10.48550/arXiv.1312.5602. Preprint.

90. Hernandez-Leal, Pablo, Bilal Kartal, and Matthew E. Taylor. "A survey and critique of multiagent deep reinforcement learning." Autonomous Agents and Multi-Agent Systems vol. 33,6 (2019): 750-797. doi: 10.1007/s10458-019-09421-1

91. Xi, Zhiheng, et al. "The rise and potential of large language model based agents: A survey." arXiv preprint arXiv:2309.07864 (2023). doi:10.48550/arXiv.2309.07864. Preprint.

92. Wang, Lei, et al. "A survey on large language model based autonomous agents." Frontiers of Computer Science vol. 18,6 (2024): 1-26. doi: 10.1007/s11704-024-40231-1

93. Cheng, Yuheng, et al. "Exploring Large Language Model based Intelligent Agents: Definitions, Methods, and Prospects." arXiv preprint arXiv:2401.03428 (2024). doi:10.48550/arXiv.2401.03428. Preprint.

94. Gao, Shanghua, et al. "Empowering Biomedical Discovery with AI Agents." arXiv preprint arXiv:2404.02831 (2024). doi:10.48550/arXiv.2404.02831. Preprint.

95. Park, Joon Sung, et al. "Generative agents: Interactive simulacra of human behavior." Proceedings of the 36th Annual ACM Symposium on User Interface Software and Technology (2023).

96. Yang, Hui, Sifu Yue, and Yunzhong He. "Auto-gpt for online decision making: Benchmarks and additional opinions." arXiv preprint arXiv:2306.02224 (2023). doi:10.48550/arXiv.2306.02224. Preprint.

97. Shen, Yongliang, et al. "Hugginggpt: Solving ai tasks with chatgpt and its friends in hugging face." Advances in Neural Information Processing Systems 36 (2024).

98. Boiko, Daniil A et al. "Autonomous chemical research with large language models." Nature vol. 624,7992 (2023): 570-578. doi:10.1038/s41586-023-06792-0

99. M. Bran, Andres, et al. "Augmenting large language models with chemistry tools." Nature Machine Intelligence (2024): 1-11. doi:10.1038/s42256-024-00832-8

100. Lu, Ming Y et al. "A Multimodal Generative AI Copilot for Human Pathology." Nature (2024). doi:10.1038/s41586-024-07618-3

101. Talebirad, Yashar, and Amirhossein Nadiri. "Multi-agent collaboration: Harnessing
the power of intelligent llm agents." arXiv preprint arXiv:2306.03314 (2023).
doi:10.48550/arXiv.2306.03314. Preprint.

102. Amirkhani, Abdollah, and Amir Hossein Barshooi. "Consensus in multi-agent
systems: a review." Artificial Intelligence Review vol. 55,5 (2022): 3897-3935.
doi:10.1007/s10462-021-10097-x

103. Talebirad, Yashar, and Amirhossein Nadiri. "Multi-agent collaboration: Harnessing
the power of intelligent llm agents." arXiv preprint arXiv:2306.03314 (2023).
doi:10.48550/arXiv.2306.03314. Preprint.

104. Hong, Sirui, et al. "Metagpt: Meta programming for multi-agent collaborative
framework." arXiv   preprint   arXiv:2308.00352 (2023).
doi:10.48550/arXiv.2308.00352. Preprint.

105. Li, Guohao, et al. "Camel: Communicative agents for" mind" exploration of large
language model society." Advances in Neural Information Processing Systems 36
(2024).

106. Wu, Qingyun, et al. "Autogen: Enabling next-gen llm applications via multi-agent
conversation   framework."   arXiv   preprint   arXiv:2308.08155   (2023).
doi:10.48550/arXiv.2308.08155. Preprint.

107. Shinn, Noah, et al. "Reflexion: Language agents with verbal reinforcement
learning." Advances in Neural Information Processing Systems 36 (2024).

108. Regev, Aviv et al. "The Human Cell Atlas." eLife vol. 6 e27041. 5 Dec. 2017,
doi:10.7554/eLife.27041

109. Eisenstein, Michael. "Seven technologies to watch in 2024." Nature vol. 625,7996
(2024): 844-848. doi:10.1038/d41586-024-00173-x

110. Sikkema, Lisa et al. "An integrated cell atlas of the lung in health and
disease." Nature medicine vol. 29,6 (2023): 1563-1577. doi:10.1038/s41591-023-
02327-2

111. Xu, Chenling et al. "Probabilistic harmonization and annotation of single-cell
transcriptomics data with deep generative models." Molecular systems biology vol.
17,1 (2021): e9620. doi:10.15252/msb.20209620

112. Badia-I-Mompel, Pau et al. "decoupleR: ensemble of computational methods to
infer biological activities from omics data." Bioinformatics advances vol. 2,1
vbac016. 8 Mar. 2022, doi:10.1093/bioadv/vbac016

113. Hou, Wenpin, and Zhicheng Ji. "Assessing GPT-4 for cell type annotation in single-
cell RNA-seq analysis." Nature methods, 10.1038/s41592-024-02235-4. 25 Mar.
2024, doi:10.1038/s41592-024-02235-4

114. Zeng, Hongkui. "What is a cell type and how to define it?." Cell 185.15 (2022):
2739-2755. doi:10.1016/j.cell.2022.06.031

115. Kuleshov, Maxim V et al. "Enrichr: a comprehensive gene set enrichment analysis
web server 2016 update." Nucleic acids research vol. 44,W1 (2016): W90-7.
doi:10.1093/nar/gkw377

116. Xie, Zhuorui et al. "Gene Set Knowledge Discovery with Enrichr." Current
protocols vol. 1,3 (2021): e90. doi:10.1002/cpz1.90

117. White, Jules, et al. "A prompt pattern catalog to enhance prompt engineering with
chatgpt." arXiv preprint arXiv:2302.11382 (2023). doi:10.48550/arXiv.2302.11382.
Preprint.

118. Chrisley, Ron. "Embodied artificial intelligence." Artificial intelligence vol. 149,1
(2003): 131-150.

119. Jin, Dongdong, and Li Zhang. "Embodied intelligence weaves a better
future." Nature Machine Intelligence vol. 2,11 (2020): 663-664.
doi:10.1038/s42256-020-00250-6

120. Gupta, Agrim et al. "Embodied intelligence via learning and evolution." Nature
communications vol. 12,1 5721. 6 Oct. 2021, doi:10.1038/s41467-021-25874-z

121. Ha, David, and Jürgen Schmidhuber. "World models." arXiv preprint
arXiv:1803.10122 (2018). doi:10.48550/arXiv.1803.10122. Preprint.

122. Juarez, Maria G., Vicente J. Botti, and Adriana S. Giret. "Digital twins: Review and
challenges." Journal of Computing and Information Science in Engineering vol. 21,3
(2021): 030802. doi:10.1115/1.4050244

123. Habermann, Arun C et al. "Single-cell RNA sequencing reveals profibrotic roles of distinct epithelial and mesenchymal lineages in pulmonary fibrosis." Science advances vol. 6,28 eaba1972. 8 Jul. 2020, doi:10.1126/sciadv.aba1972

124. Natri, Heini M et al. "Cell type-specific and disease-associated eQTL in the human lung." bioRxiv: the preprint server for biology 2023.03.17.533161. (2023). doi:10.1101/2023.03.17.533161. Preprint.

125. Deprez, Marie et al. "A Single-Cell Atlas of the Human Healthy Airways." American journal of respiratory and critical care medicine vol. 202,12 (2020): 1636-1645. doi:10.1164/rccm.201911-2199OC

126. Travaglini, Kyle J et al. "A molecular cell atlas of the human lung from single-cell RNA sequencing." Nature vol. 587,7835 (2020): 619-625. doi:10.1038/s41586-020-2922-4

127. Morse, Christina et al. "Proliferating SPP1/MERTK-expressing macrophages in idiopathic pulmonary fibrosis." The European respiratory journal vol. 54,2 1802441. 22 Aug. 2019, doi:10.1183/13993003.02441-2018

128. Madissoon, E et al. "scRNA-seq assessment of the human lung, spleen, and esophagus tissue stability after cold preservation." Genome biology vol. 21,1 1. 31 Dec. 2019, doi:10.1186/s13059-019-1906-x

129. Bharat, Ankit et al. "Lung transplantation for patients with severe COVID-19." Science translational medicine vol. 12,574 (2020): eabe4282. doi:10.1126/scitranslmed.abe4282

130. Reyfman, Paul A et al. "Single-Cell Transcriptomic Analysis of Human Lung Provides Insights into the Pathobiology of Pulmonary Fibrosis." American journal of respiratory and critical care medicine vol. 199,12 (2019): 1517-1536. doi:10.1164/rccm.201712-2410OC

131. Vieira Braga, Felipe A et al. "A cellular census of human lungs identifies novel cell states in health and in asthma." Nature medicine vol. 25,7 (2019): 1153-1163. doi:10.1038/s41591-019-0468-5

132. Goldfarbmuren, Katherine C et al. "Dissecting the cellular specificity of smoking
effects and reconstructing lineages in the human airway epithelium." Nature
communications vol. 11,1 2485. 19 May. 2020, doi:10.1038/s41467-020-16239-z
133. Church, Deanna M et al. "Extending reference assembly models." Genome
biology vol. 16,1 13. 24 Jan. 2015, doi:10.1186/s13059-015-0587-3
134. Harrison, Peter W et al. "Ensembl 2024." Nucleic acids research vol. 52,D1 (2024):
D891-D899. doi:10.1093/nar/gkad1049
135. Lun, Aaron T L et al. "Pooling across cells to normalize single-cell RNA sequencing
data with many zero counts." Genome biology vol. 17 75. 27 Apr. 2016,
doi:10.1186/s13059-016-0947-7
136. Polański, Krzysztof et al. "BBKNN: fast batch alignment of single cell
transcriptomes." Bioinformatics (Oxford, England) vol. 36,3 (2020): 964-965.
doi:10.1093/bioinformatics/btz625
137. Haghverdi, Laleh et al. "Batch effects in single-cell RNA-sequencing data are
corrected by matching mutual nearest neighbors." Nature biotechnology vol. 36,5
(2018): 421-427. doi:10.1038/nbt.4091
138. Korsunsky, Ilya et al. "Fast, sensitive and accurate integration of single-cell data
with Harmony." Nature methods vol. 16,12 (2019): 1289-1296.
doi:10.1038/s41592-019-0619-0
139. Hie, Brian et al. "Efficient integration of heterogeneous single-cell transcriptomes
using Scanorama." Nature biotechnology vol. 37,6 (2019): 685-691.
doi:10.1038/s41587-019-0113-3
140. Lotfollahi, Mohammad et al. "scGen predicts single-cell perturbation
responses." Nature methods vol. 16,8 (2019): 715-721. doi:10.1038/s41592-019-
0494-8
141. Lopez, Romain et al. "Deep generative modeling for single-cell
transcriptomics." Nature methods vol. 15,12 (2018): 1053-1058.
doi:10.1038/s41592-018-0229-2
142. Stuart, Tim et al. "Comprehensive Integration of Single-Cell Data." Cell vol. 177,7
(2019): 1888-1902.e21. doi:10.1016/j.cell.2019.05.031

143. Luecken, Malte D et al. "Benchmarking atlas-level data integration in single-cell
genomics." Nature methods vol. 19,1 (2022): 41-50. doi:10.1038/s41592-021-
01336-8

144. Wolf, F Alexander et al. "SCANPY: large-scale single-cell gene expression data
analysis." Genome biology vol. 19,1 15. 6 Feb. 2018, doi:10.1186/s13059-017-1382-
0

145. Hu, Congxue et al. "CellMarker 2.0: an updated database of manually curated cell
markers in human/mouse and web tools based on scRNA-seq data." Nucleic acids
research vol. 51,D1 (2023): D870-D876. doi:10.1093/nar/gkac947

146. Bio-OS   Team.   "Bio-OS: Open   System   for   Bioinformatics
Analysis." Https://Github.Com/Bio-OS, 19 May 2024, https://github.com/Bio-OS.

147. Lotfollahi, Mohammad et al. "Mapping single-cell data to reference atlases by
transfer   learning." Nature   biotechnology vol.   40,1   (2022):   121-130.
doi:10.1038/s41587-021-01001-7

1806

Figure 1. a. Data-intelligence-intensive research paradigm. Synergizing human expertise with AI capabilities forms intensive intelligence, that leverage big biological data to propel hypothesis-free exploratory research driven by a data-intelligence-intensive methodology. b. The architecture of Bio-Copilot. It comprises multiple agents with diverse roles, a coordination layer, and an environment.

Figure 2. The workflow of Bio-Copilot. Bio-Copilot adopts a consistent procedure for each task, comprising coarse-level planning, fine-level planning, and action execution. The procedure involves close collaboration between multiple agents with human experts.

Figure 3. a. Overall benchmarking results. A overall evaluation formula is used to synthesize the task planning evaluation, code quality evaluation and execution efficiency evaluation for all methods. b. The results of task planning evaluation and code quality evaluation. In the task planning evaluation, GPT-4 employs 10 evaluation metrics to score the execution plans generated by all methods. In the code quality evaluation, GPT-4 employs 12 evaluation metrics to score the codes generated by all methods.

Figure 4. a. Visualizations of hierarchical cell type annotations by Decoupler. Bio-Copilot employs the Decoupler tool to annotate the cell clusters from level 2 to level 4. b. The diversity and entropy of original independent datasets for each well-annotated cell type. The majority of cell types comprise cells from multiple datasets. c. UMAP visualization of the re-annotated cell types in level 4. A total of 4,579 cells are classified as unknown cell types at level 4.

Figure 5. a. UMAP visualization of unknown cell types annotated by Decoupler. Most unknown cell types are located in outliers. b. The diversity and entropy of original independent datasets for each unknown cell type. Most unknown cell types comprise cells from individual dataset and the number of cells is relatively small. c. The original cell type distribution of '0_5'. The rare cell type '0_5' can be traced back to epithelial cells. d. The enrichment results of typical rare cell types. Bio-Copilot employs Enrichr enrichment analysis tool to parse the biological processes of each rare cell type. e. Variance explained per covariate across different cell types. Bio-Copilot employs the embeddings of scANVI to conduct variance analysis. f. Variance explained by tissue sampling methods versus their entropy. Cell types that incorporate a greater variety of tissue sampling methods display more significant variation, with a positive correlation coefficient.

a

I provide you with the user's need and data description:\n{task}.\n\nNow there are four plans for the task, and you need to rate these plans from different dimensions including Clarity, Technical Feasibility, Structurality, Comprehensiveness, Rationality of Method Selection, Risk Management, Data Management, Scientific Rigor, Resource Allocation, and Scalability. The rating score range can be 0-5. Please summarize all the scores in a table at the end.

Descriptions of these dimensions are as follows:
… …

The first plan:\n"+{first_plan}+'\n\nThe second plan:\n'+{second_plan} + '\n\nThe third plan:\n'+{third_plan} + '\n\nThe fourth plan:\n'+{fourth_plan}

Here are the ratings for each plan based on the given dimensions:

Dimension	Plan 1	Plan 2	Plan 3	Plan 4
Clarity	5	4	3	4
Technical Feasibility	5	4	4	4
Structurality	5	5	4	5
Comprehensiveness	5	4	3	5
Rationality of Method Selection	5	4	4	4
Risk Management	4	3	2	4
Data Management	5	4	3	5
Scientific Rigor	5	4	3	5
Resource Allocation	4	3	3	4
Scalability	5	4	3	5

b

prompt = f'''
I provide you with the user's need and data description:\n{task}.\n\nNow there is one code for the task, and you need to score the code from different dimensions including Accuracy, Efficiency, Completeness, Readability, Logicality, Portability, Maintainability, Reusability, Robustness, Usability, Scalability and Security. The rating score range can be 0-5. When scoreing, please use human-written code as the benchmark to judge your scores. Note that you do not need to grade human-written code. Please summarize all the scores in a table at the end.

Human-written code as reference:
{refer_code}

Descriptions of these dimensions are as follows:
… …

The code is:\n"+{i}

Dimension	Score
Accuracy	4.5
Efficiency	4
Completeness	4.5
Readability	4.5
Logicality	5
Portability	4
Maintainability	4
Reusability	4.5
Robustness	4
Security	5
Usability	4.5
Scalability	4

The code provided is a series of scripts for single-cell data integration. It reads the data, normalizes and log-transforms it, identifies highly variable genes, scales the data, reduces dimensionality using PCA, integrates data using Harmony, clusters using the Leiden algorithm, visualizes using UMAP, annotates clusters based on scanvi_label, validates using differential expression analysis, and finally writes a comprehensive report.
…
…

Supplementary Figure 1. a. The prompt of GPT-4 to score task planning. b. The prompt of GPT-4 to score code quality.

Supplementary Figure 2. a. The scores of task planning in control group. b. The scores of task planning in ablation group. c. The scores of code quality in control group. d. The scores of code quality in ablation group.

e

Method	Bio-Copilot	AutoGen	GPT-4o	AutoBA
Open Source	✔	✔	✔	✔
Flexibility	--	✔	✔	✖
Robustness	✔	--	✖	✖
User-Friendliness	✔	✔	✔	✖
Human Involvement	✔	--	✖	✖
Complex Problem	✔	✖	✖	✖
External Knowledge	✔	✖	✖	✖
Efficiency	--	✔	✔	✔
Generality	✔	✖	✖	✖

Supplementary Figure 3. a. The performance of task completeness. b. The performance of user interventions. c. The performance of runtime. d. The performance of computing resource cost. e. Features of methods.

Supplementary Figure 4. a. The workflow of Bio-Copilot with self-reflective learning. b. The workflow of Bio-Copilot without self-reflective learning.

Supplementary Figure 5. a. The workflow of Bio-Copilot with knowledge empowerment. b. The workflow of Bio-Copilot without knowledge empowerment.

Supplementary Figure 6. a. The workflow of Bio-Copilot with document retrieval. b. The workflow of Bio-Copilot without document retrieval.

Supplementary Figure 7. a. UMAP visualizations of the hierarchical clustering results. b. UMAP visualizations of the re-annotated cell types in level 2 and level 3.

Supplementary Figure 8. a. Differential expression analysis of well-annotated cell types. b. Correlation between well-annotated cell types.

Supplementary Figure 9. a-c. Differences between the cell types re-annotated by Bio-Copilot and the original cell types at level 2, 3, and 4, respectively.

Supplementary Figure 10. a-b. Relationship between the unknown cell types from level 2 to level 4. c. The original cell type distribution of '1_5'. d. The original cell type distribution of '3_3'. e. Variance explained by biological versus technical covariates. f. Mean variance explained per covariate.