1

Context-dependent neural preparation for information relevance vs. probability

José M.G. Peñalver[1], Carlos González-García[1], Ana F. Palenciano[1];
David López-García[2], María Ruz[1]

[1]Mind, Brain and Behavior Research Center (CIMCYC), University of Granada, Granada 18071, Spain
[2]Data Science & Computational Intelligence Institute, Universidad de Granada, CP 18071

Correspondence: mruz@ugr.es

Abstract

Preparation is a top-down phenomenon known to improve performance across different situations.
In light of recent electrophysiological findings that suggest that anticipatory neural preactivations
linked to preparation are context-specific and do not generalize across domains, in the current
study we used fMRI to investigate the brain regions involved in these differential patterns. We
applied multivariate decoding to data obtained in a paradigm where, in different blocks, cues
provided information about the relevance or probability of incoming target stimuli. Results showed
that the anticipated stimulus category was pre-activated in both conditions, mostly in different
brain regions within the ventral visual cortex and with differential overlap with actual target
perception. Crucially, there was little cross-classification across attention and expectation contexts,
indicating lack of common neural coding across relevance and probability contexts. Finally, a
model-based fMRI-EEG fusion showed that these regions differentially code for specific conditions
during preparation, as well as specifically preparing for category anticipation in a ramping-up
manner. Overall, our results stress the specificity of anticipatory neural processing depending on
its informative role.

1. Introduction

In recent times, cognitive neuroscience has experienced a resurgence of interest in proactive cognition, highlighting the central role of endogenous top-down brain processes. Within this framework, preparation can be conceptualized as an endogenous neural function that takes place prior to planned action and that improves subsequent behavior (Battistoni et al., 2017; González-García et al., 2016). It has been shown in several contexts, with marked interest in selective attention, or the ability to prioritize information relevant for behavior (e.g. Nobre & Serences, 2018) and expectation, or the generation of probabilistic predictions based on previous experiences (e.g. Schröger et al., 2015).

A large part of the investigation on attention and expectation has focused on their consequences on target processing (reviewed in Summerfield & Egner, 2009, 2016), which leads to contrasting effects on brain activation levels. While studies in human and non-human primates have found increased firing rates in neurons tuned to attended features (Chelazzi et al., 1998; Cohen & Maunsell, 2011; Kastner et al., 1999; Peelen & Kastner, 2011; Serences et al., 2004), studies of expectation classically show activation decreases (also known as expectation suppression, e.g. Kok et al., 2012; Walsh & McGovern, 2018; see Feuerriegel et al., 2021 for a detailed review). Overall, results suggest that relevance and probability play different roles during target processing (Auksztulewicz & Friston, 2016; Gordon et al., 2019; Simon et al., 2018; Wyart et al., 2012).

However, at the anticipatory level separate studies of attention and expectation have shown similar preactivation profiles across domains. Selective attention cues (Battistoni et al., 2017; Nobre & Serences, 2018) preactivate specific shape patterns in visual cortex (Stokes et al., 2009), relevant regions of spatial processing (Giesbrecht et al., 2006), as well as object- (M. V. Peelen & Kastner, 2011; Soon et al., 2013) and category-selective (Esterman & Yantis, 2010; González-García et al., 2018) perceptual regions. Relatedly, probabilistic cues lead to the preactivation of specific perceptual templates of oriented gabors (Kok et al., 2017), direction (Ekman et al., 2017), motor patterns (de Lange et al., 2013) or abstract shapes (Hindy et al., 2016). However, whether the role of these regions and the specific preactivated patterns differ between contexts of relevance and probability is currently unknown.

Altogether, both attention and expectation seem to involve the preactivation of information, which nevertheless leads to different effects on target processing. This, in turn, poses the question of whether preparation is a unified phenomenon or, conversely, reflects different mechanisms. On this regard, a recent electroencephalography (EEG) study applying multivariate analyses successfully

contrasted selective attention and perceptual expectations, crucially, during the preparatory interval

(Peñalver et al., 2023). Anticipatory coding of incoming categories was found in both contexts, but

the underlying neural codes did not generalize across them. However, electrophysiological results

are agnostic regarding the brain regions supporting these processes. Differences between relevance

and probability anticipation could be due to separable anticipatory neural codes in the same regions,

or activity in different brain areas.

Here, we used functional Magnetic Resonance Imaging (fMRI) to study the specificity of anticipatory

representations in two key cognitive domains: relevance vs. probability. We adapted the task used

in Peñalver et al. (2023) to fMRI, aiming at replicating and extending the findings that indicate that

attention and expectation elicit different profiles of preparation. To do so, we performed a series of

multivariate analyses tailored to study the representational characteristics of preparation and to

disentangle different patterns of activity that may be taking place in similar regions. We then

leveraged a model-based EEG-fMRI fusion approach to detail the temporal profile of preparation in

crucial brain areas.

Based on the differences between attention and expectation observed during anticipatory (Peñalver

et al., 2023) and target processing (e.g. Gordon et al., 2019; Zuanazzi & Noppeney, 2019), our overall

hypothesis was that relevance and probabilistic preparation would lead to context-specific

preactivations, which would translate into specific and non-generalizable anticipatory brain

patterns in the attention and expectation conditions.

2. Methods

Methods are reported in accordance with the COBIDAS protocol (Nichols et al., 2016). The code used

to preprocess and analyze the data is available at https://github.com/CIMCYC/MRI.

2.1. Participants

Forty-six participants (mean age = 21.98, range = 18-30; 23 women, 23 men) from the University of

Granada were recruited and received 20-25 euros as compensation, depending on their

performance. They were all native Spanish speakers, right-handed and with normal or corrected

vision. The study was approved by the Ethics Committee for Research with Humans from the

University of Granada, and all participants signed informed consent prior to participation. Besides,

to comply with COVID-19 safety guidelines, they wore a face mask during the whole session,

including the behavioral practice outside the scanner. Six additional participants completed the task

but were discarded, two due to poor behavioral performance (<80% in any of the main conditions,
attention or expectation), two due to excessive head movement (either over the voxel size or over
0.1° of translation and rotation in 2 runs or more) and other two due to technical issues during data
collection. Sample size was calculated in advance to achieve a statistical power of 80% for an
estimated small effect size (Cohen's d = 0.3) and three within-subject independent variables (Block
x Category x Cueing), and to match the one used in a previous experiment with a similar paradigm
(Peñalver et al., 2023). Using PANGEA we estimated a minimum of 32 participants to detect the Block
x Cueing interaction in reaction times and behavioral accuracy, our main behavioral prediction. Our
final sample size (46 participants) provided an estimated power of 94% under the described
parameters. Due to an incomplete orthogonalization of the cue-shape pairing in cases of movement
in only one run, 2 participants were left out of some specific decoding analyses (n = 44).

2.2. Apparatus, stimuli, and procedure

Stimulus presentation and behavioral data collection were done with The Psychophysics Toolbox 3
(Brainard, 1997) on MATLAB (r2020) in a Microsoft PC. Stimuli were presented on an LCD screen
(Benq, 1920x1080 resolution, 60 Hz refresh rate) over a grey background. The task, stimuli and
parameters followed those used in our previous study (Peñalver et al., 2023) except that to adapt
the task to fMRI we employed longer and jittered inter-event intervals, which reduced the total trial
count. We employed 160 male and female faces (50% each, extracted from The Chicago Face
Database (Ma et al., 2015) plus 160 unique Spanish male and female names (50% each). Four
different geometrical shapes (circle, square, teardrop and diamond with thin black outlines,
unfilled) were used as cues in the main task.

The task involved a paradigm in which cues provided information about the relevance (attention)
or probability (expectation) of upcoming face or word targets (Figure 1). Half of the blocks belonged
to the attention condition and the other half to the expectation condition. To control for perceptual
confounds, two cue shapes were associated with faces and two with names (counterbalanced across
participants). For each participant, cue pairs changed across the experiment although their
predicted category remained; the first cue for faces (e.g. a circle) appeared in half of the blocks with
the first cue for names (e.g. a square) and the other half with the second cue for names (e.g.
diamond). The task of participants was to indicate the sex/gender of the stimulus, responding
whether or not the target belonged to the gender stated at the beginning of each block. Each block
started with a screen in which they were informed about the block (attention or expectation), the
target sex/gender ("Is the target male/female?"), and the two cues (one for faces and one for names).
Given that attention and expectation are involved in almost any act of visual perception, we aimed

at manipulating one process while keeping the other constant. In attention blocks, the cue indicated
the relevant stimulus category to select (faces or names). Only if the stimulus belonged to the
relevant category (50% trials, cued; e.g. is the target a female *face*?), the participant had to perform
the gender discrimination task on the target. Otherwise, participants had to answer 'no' regardless
of the stimulus sex/gender (non-relevant category, uncued). This manipulation of relevance, where
further processing has to be applied only to selected stimuli, is similar to that employed in previous
literature (e.g. Baldauf & Desimone, 2014; Saenz et al., 2002; Summerfield et al., 2006; Womelsdorf
et al., 2006). Both relevant and non-relevant targets were matched in expectation, as by design they
appeared with a 50% probability after each attention cue. In expectation blocks, the cue indicated
the probable category of the target with a 75% likelihood (e.g. de Lange et al., 2013; Kok et al., 2017
for similar manipulations). Here, participants had to perform the gender discrimination task for
both categories of stimuli, whether or not the target was cued (e.g. is the target a female *stimulus*?).
This way, both the expected and unexpected targets were equally relevant. Participants were
verbally instructed to use the cues in the two blocks to respond as fast as possible while avoiding
errors.

Figure 1. Behavioral paradigm. We employed a gender judgment task embedded in a cue-
target paradigm. Participants had to respond with an index finger to indicate whether or
not the target belonged to the gender indicated at the beginning of the block.

In every trial of the main task, the sequence of events was as follows: a 500 ms cue (~1.5º) was
followed by a jittered CTI and then the target appeared for 500 ms (~7º). Both the CTI and the inter-
trial duration were jittered between 2500-6000 ms intervals, spaced in 700 ms steps following a
uniform distribution (average 4250 ms). Each trial lasted on average 9.5 seconds and each run 7.6
minutes. The experiment was composed by 8 blocks of 48 trials each, or 384 trials in total. Attention

and expectation blocks appeared in separate runs in a fully alternated order, and the condition of
the first block was counterbalanced across participants. Cues and target stimuli were also fully
counterbalanced across participants. In total, the whole experimental session lasted 60 minutes
approximately, plus additional practice outside the scanner.

2.3. Data acquisition and preprocessing

A single session of imaging was carried out with a 3T Siemens Prisma MRI scanner, equipped with a
64-channel head coil. T1-weighted anatomical images were obtained using a rapid acquisition
gradient echo (MPRAGE) sequence (TR = 2250 ms, TE = 4.18 ms, TI = 900 ms, flip angle=9°, voxel
size = 1 × 1 × 1 mm). In addition, two field map images (phase and magnitude) were collected to
correct for magnetic field inhomogeneities (TR = 520 ms, TE1 = 4.92 ms, TE2 = 7.38 ms, flip
angle=60°, voxel size = 2.5 × 2.5 × 2.5 mm). Whole-brain functional images were acquired using an
echo planar imaging (EPI) sequence (TR = 1730 ms, TE = 30 ms, image matrix = 84 × 84, FOV = 210
mm flip angle=66°, slice thickness = 2.5 mm, voxel size = 2.5 × 2.5 × 2.5 mm, distance factor=0%, 50
slices with an acceleration factor of 2 (Simultaneous Multi-Slice acquisition). Slices were oriented
along the AC-PC line for each participant.

The experiment consisted of 8 runs, each corresponding to a block of the behavioral task. For each
run, 275 volumes were acquired, with the first 4 discarded from all runs. Anatomical images were
defaced to ensure anonymization. MATLAB R2020 was used for preprocessing, which involved
converting the raw DICOM images from the scanner into NIfTI files with BIDS format (Gorgolewski
et al., 2017). For functional images, preprocessing (with SPM12 v7771) involved the following: (1)
realignment and unwarping to correct for movement artifacts (using the first scan as the reference
slice) and magnetic field inhomogeneities (using previously estimated fieldmaps); (2) slice timing
correction; (3) corregistration with T1 using a rigid-body transformation and normalized mutual
information cost function with 4th degree B-spline interpolation; (4) registration to MNI space using
forward deformation fields from segmentation with 4th degree B-spline interpolation and MNI 2mm
template space; (5) smoothing using an 8mm FWHM kernel. Multivariate analyses were performed
with the unsmoothed, individual participant's functional data space. Resulting images were later re-
registered to the MNI space, smoothed and masked before second-level analyses.

2.4. Analyses

Behavioral

The task design had three within-subject factors: Block type (attention vs. expectation), Cueing

(cued vs. uncued) and Stimulus category (faces vs. names). We calculated three-way repeated
measures ANOVA for behavioral accuracy and reaction times (RTs) employing JASP (Love et al.,
2019). For each participant and condition, trials with longer or shorter RTs than the average ± 2 SDs
were discarded (11.5% on average).

fMRI General Linear Model (GLM)

A GLM was implemented to estimate activity changes across conditions, and to obtain the beta
coefficients to be used in subsequent multivariate analyses. We included condition-wise cue and
target regressors in the model. Cue regressors were modeled using their presentation time (500 ms)
plus the subsequent jitter for each trial. They were divided by Block (attention and expectation),
Category prediction (Faces and Names) and Cue shape (Shape 1 and Shape 2). Importantly, although
there was a total of 8 different cue regressors, these were distributed across the different runs. That
is, in one run/block, cues could only be of a particular condition (e.g. Expectation), and the cues
predicting a certain category had the same shape during the run (e.g. Face-shape 1 and Name-shape
2). Hence, each run included only 2 cue regressors. Target events were modeled as the presentation
time of the stimulus on screen (500 ms), and consisted on regressors for the conditions of Block
(attention and expectation), Category (faces and names) and Cueing (cued vs. uncued). Again,
although there were 8 different regressors, they belonged to particular runs, which resulted in runs
having 4 target regressors each. The model also included movement information of each participant,
obtained during realignment. The regressors were convolved using the canonical hemodynamic
response function (HRF). We estimated two sets of GLMs, one for univariate (with smoothed data)
and another one for multivariate (without normalization and smoothing).

Mass Univariate Tests

We first carried out a univariate, voxel-level test to address the different activations in attention and
expectation during the preparatory interval. To do so, we locked the events to the onset of cues, and
directly contrasted both conditions by performing a paired t-test, collapsing across category and cue
regressors. We performed this contrast for each participant, limited to grey-matter voxels, and then
obtained statistical values from a second-level analysis, where they were compared using a one
sample *t*-test against zero. Significance was established by first selecting voxels that passed a
threshold of $p<0.001$, and the cluster size to a number of voxels corresponding with $p<0.05$, FWE-
corrected (Eklund et al., 2016).

Decoding Analysis

Decoding was performed with The Decoding Toolbox (v 3.999F), using the beta images from the cue
events obtained in the GLM. In all cases, we employed a two-class decoding approach with
searchlight (sphere of 4 voxels radii, 251 voxels). A Support Vector Machine (SVM), with a leave-one-
run-out cross-validation, was trained with all but one run, and then tested on the remaining one.
This was repeated with all runs, and the results were averaged. To ensure unbiased classifications,
we report balanced accuracies, which account for over-representation of one category over the
other. Group statistics applied a one-sample t-test against zero. To correct for multiple comparisons,
we identified individual voxels that passed a threshold of $p < 0.001$, and then the minimum cluster
size was set to the number of voxels corresponding to $p < 0.05$, FWE-corrected.

With this approach, we performed two analyses. First, we classified attention vs. expectation. Since
there is evidence of the involvement of frontoparietal regions in both attention (Dodds et al., 2011;
Greenberg et al., 2010) and expectation (González-García & He, 2021), we intended to examine
whether information in these regions is distinguishable between both conditions even if they
generate similar activation levels. We used data from all cues (identical in shape and numbers across
blocks) and both categories (faces and names) to train the SVM classifier. Since the attention and
expectation manipulations appeared in different runs, for this analysis we grouped them in pairs of
continuous blocks, obtaining four pseudo-runs that included one of each condition, and were
suitable to leave-one-run-out classification. Importantly, this analysis is informative regarding the
regions where the overall process of anticipation takes place differently depending on the relevance
vs. probability manipulation.

Next, we queried the regions that carried specific anticipated content by performing the
classification of predicted categories (faces vs. names) separately for attention and expectation.
Specifically, for each condition, we classified all the cues (two shapes) that predicted faces versus all
the cues (two shapes) that predicted names. As in the previous section, the analysis was locked on
cue regressors, modeled to include the entire anticipation jitter. Note that we did not compare cued
vs. uncued targets, but cues that predicted (relevant or probable, depending on the block) face vs.
word stimuli within the same block. Similarly to univariate analyses, to compare decoding levels
across attention and expectation, for each participant we subtracted the results of the two
conditions and applied a second-level one sample t-test.

Cross-decoding Analysis

Cross-decoding was performed to assess the extent to which different conditions shared coding
patterns. That is, we trained a classifier in a particular condition, and then tested it on a different
one. Significant above-chance classification suggests the existence of similar patterns of brain

activity in the two conditions. The crossvalidation approach was adapted to each analysis to avoid

confounds, which are detailed in the following paragraphs. Searchlight and second-level analyses

were applied identically as in the two-class decoding, described above.

Our primary goal was to estimate the degree to which patterns of brain activity are shared for

preparation for relevant vs. probable contents. We reasoned that if anticipatory attention and

expectation recruit differential patterns of brain activity, category cross-classification should not

yield any significant results. We trained the classifier with cues predicting faces vs. names in one

condition (e.g. attention), and then tested it on the other one (e.g. expectation). This analysis was

performed without applying cross-validation to increase the number of observations included in the

analysis. Note that this approach, although not identical to the original analysis, does not entail any

statistical limitation, since the datasets used for training and testing are independent.

The second goal was to examine pattern similarity between preparation and actual target

perception. Thus, we trained the classifier to discriminate between faces and names with cue

information, and then tested it on target data. We applied a leave-one-run-out cross-validation

approach, by training with three cue runs, and then testing on the target of the remaining one. We

did this separately for the cues in attention and expectation. We chose this direction of cross-

decoding (train in the cue, test in the target) to ensure that the results showed similarity based on

anticipatory representations, since target perception elicits a much larger level of activation engaged

by sole stimulus input (targets or cues) which was not of interest. Again, we compared attention and

expectation cross-decoding results by subtracting participant-wise results and performing a second

level analysis.

Regions of Interest (ROI) extraction

We formulated 5 ROIs in total, corresponding to the regions returning significant decoding results

during the previous analyses. First, to study the consequences of better anticipated stimulus

discriminability, we focused on the regions resulting from category decoding separately for attention

and expectation during the preparatory window. Second, to study the source of the similarity

between cue and target regressors, we employed the regions resulting from the cue-target cross-

decoding analysis. Since this returned two distant enough clusters, one in the ventral visual cortex

and another in the Frontal Operculum (FO), we split this result into two ROIs. Hence, the 5 ROIs were

(1) bilateral Inferior Temporal Cortex (ITG), (2) occipital cortex, (3) left FO, (4) left anterior ITG and

(5) occipital + temporo-ventral cortex.

ROI parcellation proceeded as follows. To avoid double dipping (Kriegeskorte et al., 2009), we

performed a leave-one-subject-out procedure (LOSO, Esterman et al., 2010). For each participant,

we repeated the second-level analysis while leaving that participant out of the sample, so that the
particular ROI was not based on his/her own data. Then, the resulting clusters went through the
same statistical correction described above. Finally, we registered the resulting ROIs back to each
participant's native space using the inverse deformation fields obtained during segmentation.

Voxel selectivity ranking

We applied a voxel selectivity ranking analysis to study whether neural tuning to different stimuli
(instead of multivariate activity patterns) generalized from anticipation to stimulus perception. That
is, whether the neurons that are most responsive to certain condition during anticipation are similar
to those responsive to the same condition during target processing (see González-García & He, 2021;
Richter et al., 2018 for similar approaches).

This analysis was performed on the 5 ROIs mentioned above. First, for each block type (attention or
expectation) we obtained 8 different conditions to rank per each voxel. These were obtained from
crossing category (faces and names) with runs (4 runs per block type). Then, for each ROI,
participant and voxel, we obtained the betas associated with each condition as a measure of voxel
activity during the cue, and ordered them from least to most activity induced. Next, for each voxel,
we applied the same order obtained during anticipation to target perception. We reasoned that if
voxel selectivity during the cue generalizes to the target window, the order of the eight conditions
for each voxel when applied to the target should maintain a positive slope. Note that the order of the
eight conditions depends on each voxel, and is not relevant by itself, but rather a means to sort target
betas and study the corresponding slope. Next, we averaged all voxels of the ROI, obtaining a vector
of the eight ranked values, and evaluated the slope of this vector by fitting a linear regression to the
ranked parameter estimates. We obtained a slope value per participant, ROI and condition. Finally,
we determined whether the slope was positive (and therefore suggesting generalization from cue to
target perception) by performing a right-tailed one-sample *t*-test against 0, and then used False
Discovery Rate (FDR) to correct for multiple comparisons. Then, if there was a positive slope in at
least one of the two conditions (attention or expectation) we compared them using a two-tailed
paired *t*-test, again corrected for multiple comparisons using FDR (González-García & He, 2021;
Richter et al., 2018).

Model-Based EEG-fMRI Fusion

To investigate the spatial and temporal features of the findings, we employed an RSA-based EEG-
fMRI Fusion (Cichy & Oliva, 2020; López-García et al., 2022). EEG data was obtained from a previous
experiment (Peñalver et al., 2023) in which 48 participants performed the same task. The only

differences were in the timing of stimulus presentation, since cues and targets were onscreen for 50
ms and 100 ms, respectively, and trial intervals were not jittered.

In both datasets, we employed cross-validated Mahalanobis distance (also known as Linear
Discriminant Contrast, or LDC, see Walther et al., 2016) to estimate the dissimilarity between all
combinations of condition (attention vs. expectation) , category (cues predicting names vs. faces)
and cueing (two cue shapes per predicted stimulus), rendering 8-by-8 Representational
Dissimilarity Matrices (RDMs). LDC was chosen because it provides a continuous measure, making
it highly informative and avoiding ceiling effects. Moreover, since it includes a cross-validation loop,
we ensured that results were not affected by block-wise dependencies in either dataset. We
calculated LDC following Bueno & Cravo, (2021). For every ROI (or time point) and each pair of
conditions, we calculated the mean of each voxel (or EEG channel) splitting the data into two folds,
a training and testing set. The distance between the two conditions was multiplied by the pseudo-
inverse covariance matrix between the residuals of the first and the second conditions in the training
set, and the distance values were then averaged across the two folds.

To perform the fusion, since participants were different in each experiment, we employed the group
average of all RDMs in both modalities, obtaining one EEG-RDM per time-point, and 5 fMRI-RDMs,
one for each of the ROIs (adapting the procedures in Hebart et al., 2018). For each time-point and
region, we obtained the lower triangle of the symmetrical matrix, excluding the diagonal, and
vectorized it for further calculations. The fusion value was the result of a squared Pearson
correlation between the EEG-RDM and the fMRI-RDM, since this R^2 coefficient is mathematically
equivalent to the coefficient of determination of fMRI that explains the variance of EEG (Hebart et
al., 2018). For each region, the procedure was repeated in every time point, rendering a time-
resolved vector of R^2 values for each ROI.

Although EEG-fMRI fusion reflects the spatial and temporal profile of the similarities between EEG
and fMRI, it does not provide information regarding the cognitive information (in our case,
condition, category or cue differences) that the results reflect. To obtain this, we employed a model-
based approach (Hebart et al., 2018, Cichy & Oliva, 2020). First, we built three 8 by 8 theoretical
RDMs, each one for a model, stating the predicted distances among conditions (see Supplementary
Figure 1). These matrices were composed of 1s and 0s, with 1s reflecting large distances and 0s
reflecting more similarity. The condition model predicts large between attention and expectation.
The category model predicts large distances between cues predicting different categories,
regardless of block or cue. Finally, the cue model predicts that conditions would be different when
the physical shape of the cue differed. Then, we applied a commonality analysis (Seibold & McPhee,

1979) to study the variance shared by the different variables (in our case, EEG, fMRI and model

RDMs, again following Hebart et al., 2018). We compared the two squared semi-partial correlation

coefficients. One coefficient represents the shared variance between MEG and fMRI after controlling

for all model variables except one variable (the model of interest) in fMRI. The other coefficient

represents the shared variance when controlling for all model variables, including the model of

interest, in fMRI. The variance shared between EEG and fMRI, explained by the variable of interest,

is extracted by calculating the difference between these coefficients of determination (R^2). We

repeated this for every model, time-point and ROI. Importantly, to increase signal-to-noise ratio we

smoothed EEG information by applying a 5-time point moving average. For every time point, the

value was the average of that point, the two previous and the two posterior ones (see Peñalver et al.

2023 for a similar approach). Importantly, although correlation values can be either positive or

negative, R^2 is always positive, describing the overall relationship, but not the direction. However,

commonality results respond to correlation, making it possible to find some negative values and

results higher than the theoretical limit that is R^2 (see Hebart and Baker, 2018 and Flounders et al.

2019 for similar cases). To make the interpretation of the results easier, in Figure 8 we represent the

absolute value of the commonality analyses. Supplementary Figure 2 shows the original result.

In a first approach, we employed all the three models described above. Commonality (C) was

calculated as follows:

353
$$C_{(EEG.MRI,A)} = R^2_{(EEG.MRI.B,C)} - R^2_{(EEG.MRI.A,B,C)}$$

where A reflects the first model, B the second and C the third one. However, the block model

explained a large proportion of the fusion results, possibly masking effects that could be accounted

for by the other two models. Since regions were chosen because they revealed significant category

decoding, we reasoned that condition (attention or expectation) differences could explain enough

variance to mask any other interesting effects. Therefore, we repeated the analysis only with

category and cue RDMs, to obtain a clearer representation of the possible underlying effects (see

Flounders et al. 2019 for a similar approach). Note that data were still composed of two conditions,

and hence we kept 8 by 8 RDMs. Two-model commonality is described as:

362
$$C_{(EEG.MRI,A)} = R^2_{(EEG.MRI.B)} - R^2_{(EEG.MRI.A,B)}$$

Statistical significance was calculated using a cluster-based permutation analysis. For each EEG-

RDM, we permuted the data 5000 different times, obtaining as many permuted RDMs. Then, we

repeated the analyses and obtained an empirical distribution of commonality values and cluster

sizes. A window was considered significant if all the values lied over the 95% largest permuted

results, and these were continued in more data points than the 95% of the cluster sizes. For similar
approaches see Hebart et al. (2018), Flounders et al. (2019) and Peñalver et al. (2023).

3. Results

3.1. Behavioral

371 Participants' overall performance showed high accuracies (M = 0.93, SD = 0.05). To assess behavioral
372 effects, we used a three-way repeated measures ANOVA (Figure 2) on accuracy (Supplementary
373 Table 1) and reaction times (Supplementary Table 2).

Figure 2. Behavioral results. Reaction times (top row, in seconds) and accuracy (bottom row) in attention and expectation blocks, for cued (green) and uncued (orange) trials. Dots represent individual participant's scores per experimental condition. Grey lines connect each participant's score in the two conditions of each block. The horizontal black line inside boxes represents the median, while the limits of the box indicate the first and third quartiles. Whiskers mark the 1.5 inter quartile range for the upper and lower quartiles. Lateral plots show the kernel distribution of each data value.

Behavioral accuracy only showed a main effect of Category ($F_{45,1}$ = 13.02, $p < 0.001$, $\eta p2$ = 0.22), with

less accurate responses to faces than to names (M = 0.92, SD = 0.06 vs. M= 0.94, SD = 0.07). Crucially,

there was no main effect of Condition ($F_{45,1}$ =0.31), indicating that attention and expectation did not

differ in difficulty. Although the interaction between Block and Cueing was not significant ($F_{45,1}$ =

1.98, p=0.16, see Supplementary Table 1 for the complete result), given our hypothesis of better

performance in cued that uncued trials in the expectation condition, we performed the planned

comparisons and observed better accuracies for expected vs. unexpected targets ($t_{45,1}$=2.75, p =

0.004, Cohen's d = 0.41, M = 0.94 vs. 0.91), which was not found in the attention condition ($t_{45,1}$=0.08,

p = 0.93).

Only the main effect of Cueing showed a significant main effect in reaction times (RT; $F_{45,1}$ = 9.45, p

= 0.004, $\eta p2$ = 0.17), as responses were generally faster in cued trials compared to uncued trials (M

= 0.701 ms, SD = 0.17 vs. M = 0.732, SD =0.18). Again, although there was no Condition by Cueing

interaction ($F_{45,1}$ = 1.29, p=0.26), we studied the effect of expectations guided by our a priori

hypotheses. Expectation trials showed faster responses for cued than for uncued trials ($t_{45,1}$=3.14, p

= 0.014, Cohen's d = 0.14, M = 703 vs. 728 ms), which was not significant for attention ($t_{45,1}$=1.78, p

= 0.3).

3.2. Global differences between attention and expectation

Our first goal was to outline the regions that are involved in general anticipatory states during

attention and expectation, either in global activations or in different patterns of activity. To do so, we

first performed a univariate contrast for attention > expectation and vice versa, which revealed only

small univariate differences during the preparatory window (Supplementary Table 3, Figure 3A).

Since previous literature has linked frontoparietal regions to anticipation in both conditions, we

reasoned that even with similar univariate activation values, the patterns of voxel-wise activations

should be different if attention and expectation lead to different effects. We studied this by

performing a searchlight decoding of expectation and attention during the cue and preparation

interval. Our results showed significant classification in two different clusters (Supplementary Table

4, Figure 3B). The first one included several frontoparietal regions associated with the multiple

demand network (MD), such as the intraparietal sulcus (IS), Supramarginal gyrus (SMG), Superior

Parietal Cortex (SPC), left anterior Insula and the Dorsolateral Prefrontal Cortex (DLPFC), with the

peak voxel in the Supplementary Motor Area (SMA). The second one included broad visual regions,

including the occipital gyri (OcG), with the peak voxel being at the left lingual gyrus (LiG). Note that

both blocks were perceptually identical and were also equated in behavioral performance measures.

Figure 3. Global attention vs. expectation results. (A) Contrast GLM results for cue-locked attention vs. expectation trials. Scales reflect t-values. Yellow areas highlight significant clusters for attention>expectation trials, while blue shows results for expectation>attention. (B) Attention and expectation decoding during the anticipatory interval.

3.3. Differences in anticipatory category representations in attention and expectation

When looking at anticipatory activity separately for attention and expectation (Figure 4A [yellow – attention; blue – expectation] and Supplementary Table 4), we first observed significant coding of the anticipated relevant (attended) target category in two bilateral clusters in the Visual Ventral stream, with peaks at the left and right Inferior Temporal Gyri (ITG). In contrast, probable (expectation) category anticipations showed decoding mostly restricted to the early ventral visual cortex and Fusiform gyrus, with a peak at the Lingual gyrus. The comparison of these two results, by subtracting the maps of attention and expectation and performing a one-sample t-test against zero revealed that, although each condition peaked in different regions, decoding levels were overall not significantly different. This could be due to overall accuracies being low (as expected during

416   anticipation) or to both conditions recruiting broad regions of the occipital and ventral cortices,
417   although peaking in different areas. As mentioned before, these results are not driven by perceptual
418   confounds, given that decoding was performed including two different cues for each category, which
419   were differentially paired with the two cues of the other condition across blocks.

Figure 4. Cue-locked face vs. name MVPA. (A) Results in different blocks. Attention results are shown in orange, and expectation in blue. (B) Cross-classification results between attention and expectation.

3.4. Category anticipation shows restricted generalization between attention and expectation

The previous results raise the possibility that preparatory neural codes are to certain extent shared
between contexts of attention and expectation. To test for this, we performed a cross-classification
analysis between relevance vs. probability anticipation. This analysis revealed a single cluster in the
left FG (k = 756, Figure 4B and Supplementary Table 5).

3.5. Regions involved in anticipation partially overlap with those related to target perception

Results in the previous two sections show that category anticipation in attention and expectation
engages similar but not completely overlapping regions, which employ mostly different coding
patterns across contexts. This could be due to anticipatory representations in both conditions
differing in their level of similarity with target perception. Therefore, we investigated the potential
pattern overlap between preparation and the actual perception of face and name stimuli, separately
for attention and expectation. To do so, we trained the classifier during cue processing and tested it
during target processing (Figure 5 and Supplementary Table 5). In attention blocks (Fig. 5A, yellow),
the left anterior ITG and left Frontal Operculum (FO) showed common patterns for both processing
stages. For expectation (Fig. 5A, blue), results were limited to the bilateral Occipital Gyri (OcG),

peaking at the left Inferior Occipital Gyrus (IOG). A conjunction analysis only returned a cluster in

the left FG, matching the coordinates of the significant regions of the previous cross-classification

Figure 5. Cue-Target Cross-decoding results. (A) Attention results are shown in orange, and expectation in blue. (B) Common significant voxels across conditions (binarized conjunction). (C) Areas where expectation is significantly better cross-decoded than attention.

analysis (Section 3.4; Figures 4B and 5B). We compared both conditions by performing a t-test,

which returned an occipital bilateral cluster where cue-target cross-decoding was largest for

expectation (Figure 5C and Supplementary Table 5). This suggest a larger involvement of early visual

areas in the coding of probable stimuli that is specific to the cognitive context of expectation.

A mechanistic explanation for the similarities found between preparatory and perceptual coding

might be accounted for by neurons in both epochs of the trial being tuned to similar stimuli. We

studied the stability of neural tunning from cue to target stimuli in a univariate manner, which also

allowed direct comparisons between attention and expectation. We established a voxel selectivity

ranking during anticipation, and regressed it onto image preference during the target. We

performed this analysis in the five ROIs obtained from category decoding during the cue, and cue-

target cross-decoding. We separately analyzed the slope of each condition (see Figure 6 for results).

The slope was only significantly positive for expectation, in the ventral visual ROI associated with

cue-target cross-decoding for expectation ($t_{43,1}$=3.27, p = 0.001). Moreover, the result was also

significantly more positive than in the attention condition ($t_{43,1}$=2.86, p = 0.004). This result suggests

that voxels within early occipital and temporo-ventral regions are tuned in a similar way during cue

and target epochs, but in expectation trials, in line with the previous cross-decoding results.

Figure 6. Voxel selectivity results. Each plot depicts the results for one ROI. The Y axes show average beta values across all voxels and participants. The X axes show selectivity preference from least (one) to most (eight) of the eight conditions during anticipation, which was then applied to target activity (see methods). Dots represent mean voxel and participant beta values, and vertical lines the SD. Continuous lines indicate the slope obtained after fitting a linear regression to each condition. Asterisks indicate statistical significance. ITG = Inferior Temporal Gyrus; FO = Frontal Operculum.

453 *3.6. EEG-fMRI fusion shows category and block coding in ventral regions*

454 Model-based EEG-fMRI fusion results (Figure 7, grey shaded area) showed similarity between EEG

455 and fMRI data that in most regions increased with time, with the exception of the most occipital area

456 (ROI 2). This result stands out in the left FO (ROI 3), where similarity is large during the whole

457 interval. Crucially, the most ventral regions showed evidence of similarity that was less present in

Figure 7. Model-based EEG-fMRI fusion results. Fusion (grey area and black outline) results. Y axes show R^2 values, and X depicts time. Vertical dashed line indicates cue cue onset, while the 1550 ms limit is the target onset in the EEG experiment. The left column shows commonality results for three models: block (blue), category (red) and cue (green). The right column shows commonality for two models, category and cue. Significance appears in horizontal lines below the axis, colored as the corresponding significant model. Note that fusion values are identical in both columns. The two first ROIs are extracted from significant clusters of the decoding of face and name anticipated targets, yellow in attention and blue in expectation. The second pair comes from cue-target cross-decoding, following the same color pattern. Note that the scale of the Y axis on ROI 3 is larger. ITG = Inferior Temporal Gyrus; FO = Frontal Operculum.

occipital areas. This might suggest that this area represents anticipated contexts with high detail but

with a relatively late latency.

To investigate the cognitive functions subserving the fusion results we applied commonality
analyses (Figure 7 – left column). We designed three RDMs based on three models accounting for
condition (attention vs expectation), category (face vs name) and cue (the actual shapes of the cues),
depicted in Supplementary Figure 2. The analysis revealed that most of the similarity between EEG
and fMRI patterns was explained by the condition model, especially in the FO from 200 ms to the
end of the preparatory interval. This suggests a sustained pattern of differences in attention and
expectation, that was common across both experiments and that is maintained while anticipating
incoming information. However, these regions were selected because they showed a significant level
of category decoding in previous analyses, which is also the main focus of this investigation. We
reasoned that the variance explained by the condition model might have masked relevant
information pertaining to the category model. Hence, we performed a second commonality analysis,
this time only including category and cue models. Results are shown in Figure 7 – right column.

In this latter analysis the category model explained a significant part of the variance in three out of
the five regions. Moreover, the pattern of commonality in all of them, except in the occipital cortex,
described a ramping-up tendency, akin to the one found for similar analyses in Peñalver et al., 2023.
Interestingly, the FO also showed evidence of cue shape representation, which was not present in
more visual areas, suggesting the involvement of this region in the whole anticipatory process,
including shape interpretation. Overall, ventral regions showed persistent coding of the contextual
condition, which was largest in more anterior the region was. However, category anticipation was
also present in more occipital areas. Overall, fusion analyses showed that block differences were
sustained in visual regions, while the anticipated category was represented during most of the
interval, peaking before target onset.

4. Discussion

The current study characterizes the specificity of the anticipation of relevant (selective attention)
vs. probable (perceptual expectations) information content. Our findings show that top-down
preparation is highly specific, evidenced by relevance and probability contexts leading to
distinguishable brain states that extend from cue to target processing. Moreover, although
anticipated stimulus categories are coded in the brain before their actual presentation in both
contexts, the underlying preparatory patterns are mostly unique for attention and expectation.
Overall, these results challenge the notion that preparatory templates in selective attention and
perceptual expectation are equivalent, favoring a view instead where the informational role of
mental contents shapes their underlying neural patterns.

Our first goal was to study whether attention and expectation contexts lead to different anticipatory
states. We found small univariate differences in preparatory coding of different task sets (González-
García et al., 2018; Hebart et al., 2018; Peñalver et al., 2023). Multivariate results extended these
findings, showing that although activation levels were similar in attention and expectation in
frontoparietal regions (Greenberg et al., 2010; Summerfield et al., 2006), their subserving patterns
differed. Note that these results cannot be explained by differences in perceptual factors or task
difficulty, since behavioral results in attention and expectation were equated. We found two clusters,
one comprising a wide range of left occipital areas, extending from early visual regions to the left
posterior ventral cortex, and another one in frontoparietal sites typically associated with the
Multiple Demand network (MD), including the anterior insula, FO, SPC and MFC (Dosenbach et al.,
2007; Wen et al., 2018). This network has been related to attention and cognitive control, memory
load (Manoach et al., 1997) or task switching (Wager et al., 2004). Overall differences in our task are
likely related to the mechanisms recruited to anticipate demands and their relevance vs. probability
informational function in the selection of the appropriate response (e.g. Woolgar et al., 2015).

Crucial to our research was to investigate whether the representational nature of relevant or
probable category information about incoming stimuli was also different. Results showed that it was
possible to decode the anticipated stimulus category (faces vs. names) in both contexts, but the
regions associated with this effect differed for the most part. The bilateral ITG, represented
anticipated information in relevance contexts. This region has been associated with object
recognition, including faces (Verhoef et al., 2015) and words (Willems et al., 2016), also in
anticipatory settings (Willems et al., 2016). The expectation manipulation, in contrast, led to
category decoding in earlier visual regions including the lingual gyrus, associated with initial visual
processing (Mechelli et al., 2000). Interestingly, attention and expectation differed in the anterior-
to-posterior location of the anticipatory representations, with the former being in higher regions of
the hierarchy, while the latter engaging earlier perceptual sites. This is similar to what was found by
Kok et al. (2016), where a spatial attention manipulation had larger effects on higher order visual
areas (V2, V3) while expectation was detected in V1. The reasons for this potential gradient are
unknown and could be partially due to the characteristics of the paradigm used, although it is
suggestive of attention codes relying in category-based representations, while expectation affecting
more basic perceptual coding of anticipated stimuli.

In addition, to query the similarity of neural patterns across conditions, we implemented a cross-
classification analysis between attention and expectation blocks. There was scarce evidence of
cross-decoding, being limited to a cluster in the left Fusiform Gyrus. This adds support to the idea
that the anticipation of specific relevant vs. probable stimulus categories is mostly based on different

mechanisms, replicating and extending previous results (Peñalver et al., 2023). This finding provides
further evidence in favor of anticipation sharing characteristics in attention and expectation
contexts, while, at the same time, being subserved by distinct patterns of brain activity.

A potential source for differences between attention and expectation could be that they engage
different levels of overlap with actual target perception, similarly to what has been suggested for
visual imagery (e.g. Cichy et al., 2012). Cross-classification between cues and targets was evident in
both conditions, however these effects appeared in mostly different areas. Attention showed cross-
decoding on the left ITG, plus in the IFG. On the other hand, this analysis revealed more anterior
occipital and temporal ventral regions for expectation. Surprisingly, significant regions did not fully
match the ones found during anticipated category decoding, which suggests that anticipatory coding
was taking place also in these areas but did not reach statistical significance levels. Interestingly,
there was a small region in the FG that appeared in both attention and expectation (see Figure 5B).
Altogether, this suggest the left FG might be a key hub to code relevant and probable incoming
information similarly in otherwise different preparation contexts.

A voxel selectivity ranking analysis provided further evidence regarding the degree of generalization
of neural patterns from cue to target stimuli. We did this in the regions related to category
anticipation in previous analyses: cue decoding and cue-target cross-decoding for attention and
expectation. Out of the four regions, we only found evidence of generalization in the cue-target
region for expectation, in broad ventral stream sites. There, only expectation showed evidence of
generalization, and it was also significantly larger than for attention. Hence, this set of results
highlights that probabilistic preparation for different categories, compared to context of relevance,
is more akin to stimulus perception.

As a last step, we detailed the temporal profile of the fMRI results through a RSA-based fusion (Cichy
& Oliva, 2020; Flounders et al., 2019; Hebart et al., 2018) in the ROIs obtained in previous analysis.
This approach is also relevant to provide further support to the true anticipatory nature of the
findings obtained with the fMRI methodology. Although the paradigm jittered the time intervals
between cue and targets to minimize overlap in the signal, the sluggish nature of the BOLD response
hinders a clean separability of both task epochs. However, this is not an issue with the EEG data,
which has excellent temporal resolution. Results of the fMRI-EEG fusion provide the temporal profile
of the activation patterns in the selected ROIs. These indicated that while the ITG showed sustained
similarity with EEG activity, more occipital regions were associated with specific peaks at the middle
and the end of the preparatory window, which might indicate specific transient reinstatement of the
anticipated information. A further model-based commonality analysis revealed that the majority of
these results were accounted for differences between attention and expectation. Furthermore, when

studying only the category and cue models of anticipation, we found that the anticipated category
explained the similarity between EEG and fMRI patterns during most of the preparation interval,
and in a similar ramping-up fashion as the one found in Peñalver et al. (2023). Our results further
reveal that this ramping-up pattern takes place in visual regions, but also engages regions of the
Frontal Operculum, which could be acting as a source of bias of more perceptual regions (e.g. Baldauf
& Desimone, 2014). Ramping-up mechanisms have been suggested to serve working memory in
reinstating useful information in contexts of temporal anticipation (Barbosa et al., 2020; Jin et al.,
2020; Ruz & Nobre, 2008), an explanation that fits with our findings. However, further research is
needed to clarify the computational role of these patterns, and their differential role across contexts.

Overall, our results add to the evidence that attention and expectation engage neural preparation,
aligning with predictive processing accounts of the anticipatory effects in both contexts
(Auksztulewicz & Friston, 2016; Feldman & Friston, 2010; Kok et al., 2017). Attention consistently
showed anticipatory coding in regions of the ventral visual cortex that are related to categorical
stimulus perception, while expectation was often related to earlier visual areas. In this scenario,
selection could be operating on representations of the relevant stimulus categories, perhaps more
closely related to brain imagery (Christophel et al., 2015; Lawrence et al., 2019). This could happen
by preparatory increases of gain in neurons tuned to relevant categories, which could enhance
information sensory weights during target processing (Feldman & Friston, 2010). On the other hand,
expectation could induce an excitability increases in earlier regions tuned to more basic stimulus
features, allowing for a more flexible representation and induction of prediction errors to reduce
noise during visual processing. Importantly, this is further supported by the voxel selectivity ranking
results showing how voxel tunning remained stable only in expectation, adding to the notion of
neural excitability and responsiveness to probable stimuli.

Altogether, with a paradigm that manipulated the anticipation of relevant or probable contents in
tasks equated perceptually and in difficulty levels, our neuroimaging results show that the
preactivation of specific patterns in anticipation of task demands is mostly different for attention
and expectation. In both conditions cues pre-activated patterns similar to those reinstated during
subsequent target perception. However, this overlap happened in mostly different regions, and only
in expectation it was possibly due to specific neural tuning to probable stimuli. Our findings suggest
that selection acts through complex stimulus representations, while expectation increases
excitability in earlier, more basic perceptual regions. Crucially, results show that preparation is a
complex phenomenon, where different cognitive processes share representational structures,
although implementing advantageous effects via mechanisms that are mostly specific to their
contexts, complemented by activity constant through different forms of preparation. Overall, our

results replicate and extend previous findings, thus stressing the specificity of anticipatory

processing depending on the informative role it plays for further target processing.

Declaration of Interest

The authors declare no competing interests

Acknowledgements

This research was supported by grants PID2019-111187GB-100, PID2022-138940NB-I00 funded

by MICIU/AEI/10.13039/501100011033 and FEDER, UE, awarded to MR. JMGP was supported by

a post-doctoral contract granted by the University of Granada and funded by grant RYC2021-

033536-I to CGG. CGG was supported by Project PID2020-116342GA-I00 funded by

MCIN/AEI/10.13039/501100011033, and Grant RYC2021-033536-I funded by

MCIN/AEI/10.13039/501100011033 and by the European Union NextGeneration EU/PRTR. We

are grateful to Marta Becerra Losada for assistance with data collection.

References

Alink, A., & Blank, H. (2021). Can expectation suppression be explained by reduced attention to predictable stimuli? *NeuroImage*, *231*, 117824. https://doi.org/10.1016/j.neuroimage.2021.117824

Amunts, K. (2020). *Julich-Brain: A 3D probabilistic atlas of the human brain's cytoarchitecture | Science*. https://www.science.org/doi/10.1126/science.abb4588

Auksztulewicz, R., & Friston, K. (2016). Repetition suppression and its contextual determinants in predictive coding. *Cortex*, *80*, 125–140. https://doi.org/10.1016/j.cortex.2015.11.024

Auksztulewicz, R., Friston, K. J., & Nobre, A. C. (2017). Task relevance modulates the behavioural and neural effects of sensory predictions. *PLOS Biology*, *15*(12), e2003143. https://doi.org/10.1371/journal.pbio.2003143

Baldauf, D., & Desimone, R. (2014). Neural mechanisms of object-based attention. *Science*, *344*(6182), 424–427. https://doi.org/10.1126/science.1247003

Barbosa, J., Stein, H., Martinez, R. L., Galan-Gadea, A., Li, S., Dalmau, J., Adam, K. C. S., Valls-Solé, J., Constantinidis, C., & Compte, A. (2020). Interplay between persistent activity and activity-silent dynamics in the prefrontal cortex underlies serial biases in working memory. *Nature Neuroscience*, *23*(8), 1016–1024. https://doi.org/10.1038/s41593-020-0644-4

Battistoni, E., Stein, T., & Peelen, M. V. (2017a). Preparatory attention in visual cortex. *Annals of the New York Academy of Sciences*, *1396*(1), 92–107. https://doi.org/10.1111/nyas.13320

Battistoni, E., Stein, T., & Peelen, M. V. (2017b). Preparatory attention in visual cortex. *Annals of the New York Academy of Sciences*, *1396*, 92–107. https://doi.org/10.1111/nyas.13320

Bichot, N., Rossi, A., & Desimone, R. (2005). *Parallel and Serial Neural Mechanisms for Visual Search in Macaque Area V4*. https://www.science.org/doi/epdf/10.1126/science.1109676?src=getftr&

Bueno, F. D., & Cravo, A. M. (2021). Post-interval EEG activity is related to task-goals in temporal discrimination. *PLOS ONE*, *16*(9), e0257378. https://doi.org/10.1371/journal.pone.0257378

Burrows, B. E., Zirnsak, M., Akhlaghpour, H., Wang, M., & Moore, T. (2014). Global selection of saccadic target features by neurons in area v4. *The Journal of Neuroscience: The Official Journal of the Society for Neuroscience*, *34*(19), 6700–6706. https://doi.org/10.1523/JNEUROSCI.0867-13.2014

Chelazzi, L., Duncan, J., Miller, E. K., & Desimone, R. (1998). Responses of neurons in inferior temporal cortex during memory-guided visual search. *Journal of Neurophysiology*, *80*(6), 2918–2940. https://doi.org/10.1152/jn.1998.80.6.2918

Christophel, T. B., Cichy, R. M., Hebart, M. N., & Haynes, J.-D. (2015). Parietal and early visual cortices encode working memory content across mental transformations. *NeuroImage*, *106*, 198–206. https://doi.org/10.1016/j.neuroimage.2014.11.018

Cichy, R. M., Heinzle, J., & Haynes, J.-D. (2012). Imagery and Perception Share Cortical Representations of Content and Location. *Cerebral Cortex*, *22*(2), 372–380. https://doi.org/10.1093/cercor/bhr106

Cichy, R. M., & Oliva, A. (2020). A M/EEG-fMRI Fusion Primer: Resolving Human Brain Responses in Space and Time. *Neuron*, *107*(5), 772–781.

652 https://doi.org/10.1016/j.neuron.2020.07.001

653 Cohen, M. R., & Maunsell, J. H. R. (2011). When Attention Wanders: How Uncontrolled
654 Fluctuations in Attention Affect Performance. *Journal of Neuroscience*, *31*(44), 15802–15806.
655 https://doi.org/10.1523/JNEUROSCI.3063-11.2011

656 de Lange, F. P., Heilbron, M., & Kok, P. (2018). How Do Expectations Shape Perception? *Trends*
657 *in Cognitive Sciences*, *22*(9), 764–779. https://doi.org/10.1016/j.tics.2018.06.002

658 de Lange, F. P., Rahnev, D. A., Donner, T. H., & Lau, H. (2013). Prestimulus oscillatory activity
659 over motor cortex reflects perceptual expectations. *Journal of Neuroscience*, *33*(4), 1400–
660 1410. https://doi.org/10.1523/JNEUROSCI.1094-12.2013

661 Dodds, C. M., Morein-Zamir, S., & Robbins, T. W. (2011). Dissociating Inhibition, Attention, and
662 Response Control in the Frontoparietal Network Using Functional Magnetic Resonance
663 Imaging. *Cerebral Cortex*, *21*(5), 1155–1165. https://doi.org/10.1093/cercor/bhq187

664 Dosenbach, N. U. F., Fair, D. A., Miezin, F. M., Cohen, A. L., Wenger, K. K., Dosenbach, R. A. T.,
665 Fox, M. D., Snyder, A. Z., Vincent, J. L., Raichle, M. E., Schlaggar, B. L., & Petersen, S. E. (2007).
666 Distinct brain networks for adaptive and stable task control in humans. *Proceedings of the*
667 *National Academy of Sciences*, *104*(26), 11073–11078.
668 https://doi.org/10.1073/pnas.0704320104

669 Eklund, A., Nichols, T. E., & Knutsson, H. (2016). Cluster failure: Why fMRI inferences for
670 spatial extent have inflated false-positive rates. *Proceedings of the National Academy of*
671 *Sciences*, *113*(28), 7000–7005. https://doi.org/10.1073/pnas.1602413113

672 Ekman, M., Kok, P., & De Lange, F. P. (2017). Time-compressed preplay of anticipated events in
673 human primary visual cortex. *Nature Communications*, *8*(May), 1–9.
674 https://doi.org/10.1038/ncomms15276

675 Esterman, M., Tamber-Rosenau, B. J., Chiu, Y.-C., & Yantis, S. (2010). Avoiding non-
676 independence in fMRI data analysis: Leave one subject out. *NeuroImage*, *50*(2), 572–576.
677 https://doi.org/10.1016/j.neuroimage.2009.10.092

678 Esterman, M., & Yantis, S. (2010). Perceptual expectation evokes category-selective cortical
679 activity. *Cerebral Cortex*, *20*(5), 1245–1253. https://doi.org/10.1093/cercor/bhp188

680 Feldman, H., & Friston, K. (2010). Attention, Uncertainty, and Free-Energy. *Frontiers in Human*
681 *Neuroscience*, *4*. https://www.frontiersin.org/articles/10.3389/fnhum.2010.00215

682 Feuerriegel, D., Vogels, R., & Kovacs, G. Z. (2021). Evaluating the evidence for expectation
683 suppression in the visual system | Elsevier Enhanced Reader. *Neuroscience and Biovahavioral*
684 *Reviews*. https://doi.org/10.1016/j.neubiorev.2021.04.002

685 Flounders, M. W., González-García, C., Hardstone, R., & He, B. J. (2019). Neural dynamics of visual
686 ambiguity resolution by perceptual prior. *eLife*, *8*, e41861. https://doi.org/10.7554/eLife.41861

687 Giesbrecht, B., Weissman, D. H., Woldorff, M. G., & Mangun, G. R. (2006). Pre-target activity in
688 visual cortex predicts behavioral performance on spatial and feature attention tasks. *Brain*
689 *Research*, *1080*(1), 63–72. https://doi.org/10.1016/j.brainres.2005.09.068

690 González-García, C., Arco, J. E., Palenciano, A. F., Ramírez, J., & Ruz, M. (2017). Encoding,
691 preparation and implementation of novel complex verbal instructions. *NeuroImage*, *148*, 264–
692 273. https://doi.org/10.1016/j.neuroimage.2017.01.037

693 González-García, C., Flounders, M. W., Chang, R., Baria, A. T., & He, B. J. (2018a). Content-
694 specific activity in frontoparietal and default-mode networks during prior-guided visual

695 perception. *eLife*, *7*, 1–25. https://doi.org/10.7554/eLife.36068

696 González-García, C., Flounders, M. W., Chang, R., Baria, A. T., & He, B. J. (2018b). Content-
697 specific activity in frontoparietal and default-mode networks during prior-guided visual
698 perception. *eLife*, *7*, e36068. https://doi.org/10.7554/eLife.36068

699 González-García, C., & He, B. J. (2021). A Gradient of Sharpening Effects by Perceptual Prior
700 across the Human Cortical Hierarchy | Journal of Neuroscience. *Journal of Neuroscience*, *41*(1),
701 167–178.

702 González-García, C., Mas-Herrero, E., de Diego-Balaguer, R., & Ruz, M. (2016). Task-specific
703 preparatory neural activations in low-interference contexts. *Brain Structure and Function*,
704 *221*(8), 3997–4006. https://doi.org/10.1007/s00429-015-1141-5

705 Gordon, N., Tsuchiya, N., Koenig-Robert, R., & Hohwy, J. (2019a). Expectation and attention
706 increase the integration of top-down and bottom-up signals in perception through different
707 pathways. *PLOS Biology*, *17*(4), e3000233. https://doi.org/10.1371/journal.pbio.3000233

708 Gordon, N., Tsuchiya, N., Koenig-Robert, R., & Hohwy, J. (2019b). Expectation and attention
709 increase the integration of top-down and bottom-up signals in perception through different
710 pathways. *PLoS Biology*, *17*(4), e3000233. https://doi.org/10.1371/journal.pbio.3000233

711 Greenberg, A. S., Esterman, M., Wilson, D., Serences, J. T., & Yantis, S. (2010). Control of Spatial
712 and Feature-Based Attention in Frontoparietal Cortex. *Journal of Neuroscience*, *30*(43),
713 14330–14339. https://doi.org/10.1523/JNEUROSCI.4248-09.2010

714 Hebart, M. N., Bankson, B. B., Harel, A., Baker, C. I., & Cichy, R. M. (2018). The representational
715 dynamics of task and object processing in humans. *eLife*, *7*, e32816.
716 https://doi.org/10.7554/eLife.32816

717 Hindy, N. C., Ng, F. Y., & Turk-Browne, N. B. (2016). Linking pattern completion in the
718 hippocampus to predictive coding in visual cortex. *Nature Neuroscience*, *19*(5), 665–667.
719 https://doi.org/10.1038/nn.4284

720 Jin, W., Nobre, A. C., & van Ede, F. (2020). Temporal Expectations Prepare Visual Working Memory
721 for Behavior. *Journal of Cognitive Neuroscience*, 5/20/24 5:52:00 PM*32*(12), 2320–2332.
722 https://doi.org/10.1162/jocn_a_01626

723 Kok, P., Jehee, J. F. M., & de Lange, F. P. (2012). Less Is More: Expectation Sharpens
724 Representations in the Primary Visual Cortex. *Neuron*, *75*(2), 265–270.
725 https://doi.org/10.1016/j.neuron.2012.04.034

726 Kok, P., Lieshout, L. L. F. van, & Lange, F. P. de. (2016). Local expectation violations result in
727 global activity gain in primary visual cortex. *Scientific Reports*, *6*.
728 https://doi.org/10.1038/srep37706

729 Kok, P., Mostert, P., & de Lange, F. P. (2017a). Prior expectations induce prestimulus sensory
730 templates. *Proceedings of the National Academy of Sciences*, 201705652.
731 https://doi.org/10.1073/pnas.1705652114

732 Kok, P., Mostert, P., & de Lange, F. P. (2017b). Prior expectations induce prestimulus sensory
733 templates. *Proceedings of the National Academy of Sciences*, *114*(39), 10473–10478.
734 https://doi.org/10.1073/pnas.1705652114

735 Kok, P., Rahnev, D., Jehee, J. F. M., Lau, H. C., & de Lange, F. P. (2012). Attention reverses the
736 effect of prediction in silencing sensory signals. *Cerebral Cortex (New York, N.Y.: 1991)*, *22*(9),
737 2197–2206. https://doi.org/10.1093/cercor/bhr310

Kriegeskorte, N., Mur, M., & Bandettini, P. (2008). Representational Similarity Analysis –
Connecting the Branches of Systems Neuroscience. *Frontiers in Systems Neuroscience*, *2*, 4.
https://doi.org/10.3389/neuro.06.004.2008

Kriegeskorte, N., Simmons, K., Patrick S. F., and Baker, C. (2009). Circular Analysis in Systems
Neuroscience: The Dangers of Double Dipping. Nature Neuroscience, 12, 5. 535-40.
https://doi.org/10.1038/nn.2303

Lawrence, S. J. D., Formisano, E., Muckli, L., & de Lange, F. P. (2019). Laminar fMRI:
Applications for cognitive neuroscience. *NeuroImage*, *197*, 785–791.
https://doi.org/10.1016/j.neuroimage.2017.07.004

López-García, D., Peñalver, J. M. G., Górriz, J. M., & Ruz, M. (2022). MVPAlab: A machine learning
decoding toolbox for multidimensional electroencephalography data. *Computer Methods and*
Programs in Biomedicine, *214*, 106549. https://doi.org/10.1016/j.cmpb.2021.106549

Mechelli, A., Humphreys, G. W., Mayall, K., Olson, A., & Price, C. J. (2000). Differential effects of
word length and visual contrast in the fusiform and lingual gyri during. *Proceedings of the*
Royal Society of London. Series B: Biological Sciences, *267*(1455), 1909–1913.
https://doi.org/10.1098/rspb.2000.1229

Nichols, T. E., Das, S., Eickhoff, S. B., Evans, A. C., Glatard, T., Hanke, M., Kriegeskorte, N.,
Milham, M. P., Poldrack, R. A., Poline, J.-B., Proal, E., Thirion, B., Essen, D. C. V., White, T., & Yeo,
B. T. T. (2016). *Best Practices in Data Analysis and Sharing in Neuroimaging using MRI* (p.
054262). bioRxiv. https://doi.org/10.1101/054262

Nobre, A. C., & Serences, J. T. (2018a). Building on a Solid Baseline: Anticipatory Biases in
Attention. *Trends in Neurosciences*, *41*(3), 120–122.
https://doi.org/10.1016/j.tins.2018.01.005

Nobre, A. C., & Serences, J. T. (2018b). Building on a Solid Baseline: Anticipatory Biases in
Attention. *Trends in Neurosciences*, *41*(3), 120–122.
https://doi.org/10.1016/j.tins.2018.01.005

Palenciano, A. F., Senoussi, M., Formica, S., & González-García, C. (2023). Canonical template
tracking: Measuring the activation state of specific neural representations. *Frontiers in*
Neuroimaging, *1*. https://www.frontiersin.org/articles/10.3389/fnimg.2022.974927

Peelen, M. V., & Kastner, S. (2011). A neural basis for real-world visual search in human
occipitotemporal cortex. *Proceedings of the National Academy of Sciences of the United States*
of America, *108*(29), 12125–12130. https://doi.org/10.1073/pnas.1101042108

Pelzer, L., Haffmann, J., Naefgen, C., Gaschler, R., & Haider, H. (2022). Task-separation in dual-
tasking: How action effects support the separation of the task streams. *Acta Psychologica*, *222*,
103464. https://doi.org/10.1016/j.actpsy.2021.103464

Peñalver, J. M. G., López-García, D., González-García, C., Aguado-López, B., Górriz, J. M., & Ruz,
M. (2023). Top-down specific preparatory activations for selective attention and perceptual
expectations. *NeuroImage*, *271*, 119960. https://doi.org/10.1016/j.neuroimage.2023.119960

Richter, D., & de Lange, F. P. (2019). Statistical learning attenuates visual activity only for
attended stimuli. *eLife*, *8*. Scopus. https://doi.org/10.7554/eLife.47869

Richter, D., Ekman, M., & de Lange, F. P. (2018). Suppressed Sensory Response to Predictable
Object Stimuli throughout the Ventral Visual Stream. *The Journal of Neuroscience*, *38*(34),
7452–7461. https://doi.org/10.1523/JNEUROSCI.3421-17.2018

Ruz, M., & Nobre, A. C. (2008). Dissociable top-down anticipatory neural states for different
linguistic dimensions. *Neuropsychologia*, *46*(4), 1151–1160.
https://doi.org/10.1016/j.neuropsychologia.2007.10.021

Saenz, M., Buracas, G. T., & Boynton, G. M. (2002). Global effects of feature-based attention in
human visual cortex. *Nature Neuroscience*, *5*(7), 631–632. https://doi.org/10.1038/nn876

Schröger, E., Kotz, S. A., & SanMiguel, I. (2015). Bridging prediction and attention in current
research on perception and action. *Brain Research*, *1626*, 1–13.
https://doi.org/10.1016/j.brainres.2015.08.037

Seibold, D. R., & McPhee, R. D. (1979). Commonality Analysis: A Method for Decomposing
Explained Variance in Multiple Regression Analyses. *Human Communication Research*, *5*(4), 355–
365. https://doi.org/10.1111/j.1468-2958.1979.tb00649.x

Simon, A., Schatner, J., & Gallen, C. (2018). *Disentangling expectation from selective attention*
during perceptual decision making | Journal of Neurophysiology.
https://journals.physiology.org/doi/full/10.1152/jn.00639.2018

Soon, C. S., Namburi, P., & Chee, M. W. L. (2013). Preparatory patterns of neural activity
predict visual category search speed. *NeuroImage*, *66*, 215–222.
https://doi.org/10.1016/j.neuroimage.2012.10.036

Stokes, M., Thompson, R., Nobre, A. C., & Duncan, J. (2009a). Shape-specific preparatory
activity mediates attention to targets in human visual cortex. *Proceedings of the National*
Academy of Sciences, *106*(46), 19569–19574.

Stokes, M., Thompson, R., Nobre, A. C., & Duncan, J. (2009b). Shape-specific preparatory
activity mediates attention to targets in human visual cortex. *Proceedings of the National*
Academy of Sciences, *106*(46), 19569–19574. https://doi.org/10.1073/pnas.0905306106

Summerfield, C., & Egner, T. (2009). Expectation (and attention) in visual cognition. *Trends in*
Cognitive Sciences, *13*(9), 403–409. https://doi.org/10.1016/j.tics.2009.06.003

Summerfield, C., & Egner, T. (2016). Feature-Based Attention and Feature-Based Expectation.
Trends in Cognitive Sciences, *20*(6), 401–404. https://doi.org/10.1016/j.tics.2016.03.008

Summerfield, C., Egner, T., Greene, M., Koechlin, E., Mangels, J., & Hirsch, J. (2006). Predictive
Codes for Forthcoming Perception in the Frontal Cortex. *Science*, *314*(November), 1311–1314.
https://doi.org/10.1017/cbo9781139167291.033

Sy, J. L., Guerin, S. A., Stegman, A., & Giesbrecht, B. (2014). Accurate expectancies diminish
perceptual distraction during visual search. *Frontiers in Human Neuroscience*, *8*(MAY), 1–18.
https://doi.org/10.3389/fnhum.2014.00334

Van Ede, F., De Lange, F. P., & Maris, E. (2012). Attentional Cues Affect Accuracy and Reaction
Time via Different Cognitive and Neural Processes. *Journal of Neuroscience*, *32*(30), 10408–
10412. https://doi.org/10.1523/JNEUROSCI.1337-12.2012

Verhoef, B.-E., Bohon, K. S., & Conway, B. R. (2015). Functional Architecture for Disparity in
Macaque Inferior Temporal Cortex and Its Relationship to the Architecture for Faces, Color,
Scenes, and Visual Field. *Journal of Neuroscience*, *35*(17), 6952–6968.
https://doi.org/10.1523/JNEUROSCI.5079-14.2015

Walsh, K. S., & McGovern, D. P. (2018). Expectation Suppression Dampens Sensory
Representations of Predicted Stimuli. *Journal of Neuroscience*, *38*(50), 10592–10594.
https://doi.org/10.1523/JNEUROSCI.2133-18.2018

Walther, A., Nili, H., Ejaz, N., Alink, A., Kriegeskorte, N., & Diedrichsen, J. (2016). Reliability of
dissimilarity measures for multi-voxel pattern analysis. *NeuroImage*, *137*, 188–200.
https://doi.org/10.1016/j.neuroimage.2015.12.012

Wen, T., Mitchell, D. J., & Duncan, J. (2018). Response of the multiple-demand network during
simple stimulus discriminations. *Neuroimage*, *177*, 79–87.
https://doi.org/10.1016/j.neuroimage.2018.05.019

Willems, R. M., Frank, S. L., Nijhof, A. D., Hagoort, P., & van den Bosch, A. (2016). Prediction
During Natural Language Comprehension. *Cerebral Cortex*, *26*(6), 2506–2516.
https://doi.org/10.1093/cercor/bhv075

Wimber, M., Alink, A., Charest, I., Kriegeskorte, N., & Anderson, M. C. (2015). Retrieval induces
adaptive forgetting of competing memories via cortical pattern suppression. *Nature*
Neuroscience, *18*(4), 582–589. https://doi.org/10.1038/nn.3973

Womelsdorf, T., Fries, P., Mitra, P. P., & Desimone, R. (2006). Gamma-band synchronization in
visual cortex predicts speed of change detection. *Nature*, *439*(7077), 733–736.
https://doi.org/10.1038/nature04258

Woolgar, A., Williams, M. A., & Rich, A. N. (2015). Attention enhances multi-voxel
representation of novel objects in frontal, parietal and visual cortices. *NeuroImage*, *109*, 429–
437. https://doi.org/10.1016/j.neuroimage.2014.12.083

Wyart, V., Nobre, A. C., & Summerfield, C. (2012). Dissociable prior influences of signal
probability and relevance on visual contrast sensitivity. *Proceedings of the National Academy*
of Sciences, *109*(9), 3593–3598. https://doi.org/10.1073/pnas.1120118109

Zuanazzi, A., & Noppeney, U. (2019). Distinct Neural Mechanisms of Spatial Attention and
Expectation Guide Perceptual Inference in a Multisensory World. *Journal of Neuroscience*,
39(12), 2301–2312. https://doi.org/10.1523/JNEUROSCI.2873-18.2019

848