1 **HRannot: An accurate and user-friendly gene annotation pipeline for vertebrates**
2

Siwen Wu[1,2*], Sisi Yuan[2*], Wei-ming Li[3*], Zhengchang Su[2#]

[1]Institute of Medical Biology, Chinese Academy of Medical Sciences, Peking Union Medical

College, Kunming, Yunnan, China.

[2]Department of Bioinformatics and Genomics, the University of North Carolina at Charlotte,

Charlotte, NC 28223, USA.

[3]The Second Affiliated Hospital of Kunming Medical University, Kunming, Yunnan, China.

*These authors contributed equally to the work.

[#]The author supervised this work and should be addressed to zcsu@uncc.edu (ZS).

Abstract

With the development of long reads sequencing technologies and assembly tools, high-quality

genome assembly becomes routine in individual labs. In the past few years, numerous high-

quality genome assemblies for various vertebrate individuals and species have been deposited

in public databases. However, most of these genomes are not annotated for the protein-coding

genes, the major working horse in cells, limiting their applications. This dilemma is caused by

the reality that the existing easily-used tools cannot achieve accurate annotation, whereas

accurate tools such as the NCBI's eukaryotic genome annotation pipeline are unavailable to

individual labs due to the complexity of their use and their high demand for computing

resources. Here, we developed an accurate and user-friendly gene annotation pipeline HRannot,

enabling accurate annotation of both protein-coding genes and pseudogenes in vertebrate

genomes using limited computing resources. Based on both homologous genes in related

species and and RNA-seq data from the same species, HRannot is able to annotate both known

and novel genes. HRannot outperforms all available well-regarded gene annotation tools, and is

comparable or even better in some cases than the NCBI's gene annotation pipeline.

Keywords

Gene annotation, homology-based, RNA-seq data-based, protein-coding genes, pseudogenes.

Introduction

The Sanger sequencing technique developed in 1977 [1] had been the most commonly used technology to sequence genomes before the advent of next-generation sequencing (NGS) technology [2] developed in 2005. Since 2014, the single molecule real time (SMRT) sequencing technology developed by PacBio Inc. [3] and nanopore-based sequencing technology developed by Oxford Nanopore Technology (ONT) [4, 5] enabled the generation of long reads up to 100 kbp in length. Although the earlier long reads had a high error rate, when combined with highly accurate short reads, they enable high quality chromosome-level genome assemblies. Recent development of highly accurate long reads sequencing technologies and assembly tools has made gap-less telomer to telomer (T2T) genome assembly routine in individual labs [6]. Numerous genomes of different species as well as of different individuals of the same species have been assembled and released by individual labs and large consortia. Particularly, the Vertebrate Genomes Project (VGP) plans to assemble the genomes of all the roughly 70,000 extant vertebrate species, enabling a new era of discovery across the life sciences [7]. The Earth BioGenome Project (EBP) aims to sequence and characterize the genomes of all eukaryotes on Earth over a period of 10 years [8], providing unprecedented opportunities to study the biological process of eukaryotes on Earth. Moreover, hundreds of thousands of individual human genomes have also been sequenced [9-11], and it is expected that more and more genomes will be made available in public databases. However, most of the assembled genomes in public database lack gene annotations. For example, until September 2025, only 6,613 (23%) of 28,754 vertebrate genomes deposited in NCBI's GenBank have the annotation for at least one coding sequence (CDS) [12].

Clearly, accurate annotation of all genes and pseudogenes in the genome of an

organism is important to understand the biology and evolutionary history of the organism. And

in fact, many gene annotation tools have been developed, and they can be roughly classified

into *de novo* -based methods, RNA-based methods, and homology-based methods. Tools

combining multiple methods have also been developed [13-15]. However, none of the existing

tools could sufficiently and accurately annotate both protein-coding genes and pseudogenes.

De novo gene annotation tools such as AUGUSTUS [16], GENSCAN [17] and GeneMark-ES [18]

tend to have high false-positive and false-negative rates. RNA-based tools such as Trinity [19]

are often limited to genes expressed in the sampled tissues or experimental conditions.

Homology-based tools such as Genomix [20], GeMoMa [21] and Scipio [22] are likely to miss

new genes that are unique to the reference genome. Combined tools such as Braker3 [13]

(combining AUGUSTUS [16], GeneMark-ETP [23] and RNA-seq reads mapping), CAARs [14]

(combing GeneMark-ETP [23] and RNA-seq reads mapping) and FINDER [15] (combing gene

family alignments and RNA-seq reads mapping) tend to have high false-positive rates. Although

NCBI [24] and ENSEMBL [25] have developed eukaryotic genome annotation pipelines and

made great efforts to generate high-quality annotations for the so-called reference genome of

each sequenced species, these tools are not run in a fully automatic mode, and often need

tedious manual corrections. In addition, these pipelines are not available to individual research

groups.

To fill these gaps, we developed an accurate and user-friendly gene annotation pipeline

named HRannot. By using a combination of homology-based and RNA-seq data-based

approaches, HRannot is able to annotate both protein-coding genes and pseudogenes in a

broad spectrum of vertebrates accurately. By comparing with the state-of-the-art gene

annotation tools, we find that HRannot outperforms them and is comparable or even better in

some cases than the NCBI's annotation pipeline. Thus, HRannot is a useful tool for annotate

genes and pseudogenes in an increasing number of assembled genomes.

Materials and Methods

Overall flowchart of HRannot

We designed HRannot to predict both known and novel genes in a genome by combining a

homology-based method and an RNA-seq-based method. Moreover, HRannot is also designed

to annotate both protein-coding genes and pseudogenes in the genome. As shown in Figure 1,

both the homology-based method and RNA-seq-based method consist of a data preparation

procedure and a gene prediction procedure.

The Homology-based method

In the data preparation step, given a target genome to be annotated, we collected a set of

reference genomes with gene annotations. Ideally, the set consists of as many as possible well-

annotated genomes in the same class as the target genome. We map the CDSs of each genes in

each reference genome to the target genome using Splign (2.0.0) with default settings [26]. We

sort the reference genomes in the descending order according to their average CDS mapping

identity to the target genome. Moreover, we map the high-quality DNA sequencing reads

(Illumina DNA short reads or HiFi long reads) from the same individual using bowtie (2.4.1) [27]

with no gaps and mismatches permitted.

In the prediction step, for each reference genome, for each of its annotated genes

whose CDSs can be mapped to the same contig/scaffold/chromosome of the target genome,

we predict each mapped region in the target genome to be an exon/CDS and the intervals

between the putative exons/CDS to be introns. We concatenate all the putative CDSs to form a

putative full-length CDS, and predict the corresponding locus (including the putative CDSs and

introns) to be an intact genes, if and only if the putative full-length CDS forms an open reading

frame (ORF), i.e., it has a length of an integer time of three and its last three nucleotides form

the only stop codon. If the putative full-length CDS contains a premature stop codon (nonsense

mutation), or its length is not an integer time of three (ORF shift mutation), we check whether

the locus can be completely covered by at least n (by default, n=10, or n= ¼ of the average

genome coverages) DNA short reads from the same individual. If the answer is yes, we consider

the pseudogenization (nonsense mutation or ORF shift mutation) is supported by the high-

quality DNA sequencing reads, and predict the sequence to be a pseudogene. Otherwise, we

consider the pseudogenization is not supported by the high-quality sequencing reads, and call

the sequence a partially supported gene, because the pseudogenization might be artificially

caused by errors of the assembled target genome. We call these intact genes, partially

supported genes, and pseudogenes to be the predictions based on the reference genome.

To combine all the predictions based on different reference genomes, we initiate the

current predictions as those based on the first genome in the set of sorted reference genomes,

and update them iteratively by considering each of the predictions based on each remaining

reference genomes in their resorted order. More specifically, for each putative

gene/pseudogene g based on the next reference genome, we replace with a gene/pseudogene

q in the current predictions, if g overlaps q by more than 0.95 of q's length (the number could

be set by users) and g's template mapping identity is higher than that of q's. If g does not

overlap any of the genes/pseudogenes in the current predictions, and its template mapping

identity is greater than 0.99 (the number could be set by users), we added g to the current

predictions. We consider all intact genes and partially supported genes as homology-based

protein-coding genes (Figure 1).

RNA-seq-based method

In the data preparation step, we first collect as many as possible RNA-seq data from various

tissues of the target species or its closely related species. We then map all the RNA-seq reads to

the rRNA database [28] using bowtie (2.4.1) with default settings [27]. We remove the reads

that map to rRNAs.

In the prediction step, we first predict non-coding RNA genes using infernal (1.1.2) [29]

with Rfam as the reference database [30]. We then align the cleaned reads to the target

genome using STAR (2.7.0c) [31] with default settings and assemble transcripts using Trinity

(2.8.5) [19] with its genome-guided option. We next map the well-assembled transcripts to the

target genome using Splign (2.0.0) [26] with default settings, and remove those that at least

partially overlap non-coding RNAs, protein-coding genes or pseudogenes predicted by the

homology-based method. For each of the remaining mappings, we use the same approach

mentioned in the homology-based method to obtain the putative full-length CDS. If the

putative full-length CDS contains at least one ORF, we predict the longest one to be a protein-

coding gene if it is at least 300 bp (the number could be determined by users) and has an

average identity of at least 0.985 (the number could be determined by users) (Figure 1).

Annotations of the human, mouse, chicken, Tibetan ground-tit and turtle genomes

To evaluate HRannot and other state-of-the-art genome annotation tools, we downloaded the

best-assembled genomes available in GenBank for humans (T2T-CHM13v2.0), mice

(PAHARI_EIJ_v1.1), chickens (GRCg6a), Tibetan ground-tits (PseHum1.0) and turtles

(GSC_CCare_1.0) with accession numbers GCF_009914755.1, GCF_900095145.1,

GCF_000002315.6, GCF_000331425.1, and GCF_023653815.2, respectively. We downloaded

high-quality DNA sequencing data collected from the host individual of each genome from the

GEO database with the accession numbers listed in Table S1. For homology-based annotations,

we selected a set of reference genomes consisting of all annotated genomes of species in

GenBank's RefSeq, belonging to the same taxonomic class as the target species. More

specifically, these include 242 mammalian genomes (Table S2) for the human and mouse

genomes, 145 avian genomes (Table S3) for the chicken and Tibetan ground-tit genomes, and

47 reptile genomes (Table S4) for the turtle genome. Gene annotation files of these genomes as

well as those of the target genomes are downloaded from GenBank using corresponding

accession numbers (Tables S1-S4). For RNA-based annotations, we downloaded RNA-seq data

sets for each species from the GEO databases, whose accession numbers are listed in Table S1.

For computational efficiency, we only used RNA-seq data from the individual or cell line whose

assembled genome would be annotated, except for the chicken genome, for which we used 40

datasets collected from 10 tissues of four individual chickens [32].

Comparison of HRannot with state-of-the-art methods AUGUSTUS, Braker3, GeMoMa, and

the NCBI annotation pipeline

For AUGUSTUS [16], we used its *de novo* function with default settings. For Braker3 [13], we

used its ETP mode (annotate using both RNA-seq data and protein data) with default settings.

For GeMoMa [21], we used both RNA-seq data and homologous annotations with default

settings. For the homology-based predictions of GeMoMa [21], we used the same reference

genomes as used in HRannot for each target genome (Tables S2-S4).

Assessment of genes overlapping with NCBI's annotations

We define a predicted gene/pseudogene q to match an NCBI annotated gene/pseudogene g if q

overlaps more than 50% length of g and the identity of the mapping parts are 100%.

BUSCO assessment

We used BUSCO (5.7.1) [33] to assess the quality of the annotated CDSs and exons of the

protein-coding genes and pseudogenes in each species by each tool. More specifically, for the

human and mouse genomes, we used mammalia_odb10; for the chicken and Tibetan ground tit

genomes, we used aves_odb10; and for the turtle genome, we used tetrapoda_odb10.

Precision and Recall assessment

For the precision and recall of each tool against NCBI's annotations in each genome, we used

the following formulas:

Precision = # Overlapped genes / # Predicted genes by each tool

Recall = # Overlapped genes / # Genes predicted by NCBI

Results

The homology-based and RNA-based predictions of HRannot are complementary with each

other

HRannot starts with the homology-based approach to predict homologous genes in a target

genome using annotated CDSs in multiple reference genomes, and then uses the RNA-seq-

based approach to predict genes that are missed by the former approach (Materials and

Methods). To evaluate HRannot, we applied it with default settings to the best-assembled

genomes in GenBank for five vertebrate species including humans, mice, chickens, Tibetan

ground-tits and turtles (as of October 2025), using the default settings with the selected sets of

reference genomes and RNA-seq datasets for each species (Materials and Methods). To see the

relationship between the number of predicted homology-supported genes and the number of

reference genomes used, we plot the accumulative number of predicted genes in each target

genome as a function of the number of reference genomes with the highest mean mapping

identities used (Materials and Methods). As shown in Figures 2a-2e, the few reference genomes

with the highest mean mapping identities are able to predict the vast majority of homology-

supported genes in each target genome, and the accumulative number of predicted genes

saturates after more than 20 reference genomes with the highest mean mapping identities are

used. This is particularly true in the human, mouse, chicken and Tibetan ground-tit genomes

compared to the case of the turtle genome, due probably to the better annotations of

reference genomes in mammals and birds than those of reptiles. These results suggest that the

reference genomes that we selected for each target genome are adequate for homology-based

gene predictions, and that using more than 20 reference genomes with the highest mean

mapping identities contributes little to the total number of predicted homology-supported

genes. The number of predicted homology-supported protein-coding genes and pseudogenes

using all the selected reference genomes in each species are listed in Tables 1 and 2. Most of

these genes are covered by RNA-seq reads from the tissues of each species, suggesting that

they are transcribed and thus are likely to be authentic.

To see the relationship between the predicted RNA-supported genes and the RNA-seq

datasets used, we choose datasets from 1, 2, …, 10 chicken tissues and used them to predict

RNA-supported genes. As shown in Figure 2f, the accumulative number of predicted RNA-

supported genes increases rapidly with the increase in the number of datasets used, followed

by a slow linear increase, suggesting that using additional diverse datasets can potentially

predict more RNA-supported genes. The number of predicted RNA-supported protein-coding

genes using all the selected RNA-seq datasets in each species are listed in Tables 1 and 2.

Notably, the number of RNA-supported genes are much smaller than that of homology-

supported genes in each species, as the RNA-based approach is designed to predict genes that

are missed by the homology-based method (Materials and Methods).

HRannot outperforms the state-of-the-art gene annotation tools in the human, mouse,

chicken and turtle genomes

We compared the results of HRannot in four target genomes (human, mouse, chicken and

turtle) with those of three state-of-the-art tools AUGUSTUS [16], Braker3 [13] and GeMoMa

[21], obtained by applying each of them to the four target genomes using the default settings of

the tool and the same sets of reference genomes and RNA-seq datasets if the tool support such

datasets as inputs. We chose AUGUSTUS [16], Braker3 [13] and GeMoMa [21] for comparison,

as they represent *de novo*-based, RNA-seq + protein-based, and homology + RNA-seq-based

annotation methods, respectively. As NCBI has made great efforts to annotate these genomes,

we used the NCBI's annotations as the standard for evaluations. We first compared the number

of genes predicted by each tool with those annotated by NCBI. As shown in Table 1, for all the

four species, HRannot achieved the closest number of protein-coding genes (20,717, 18,272,

20,624 and 19,670, for human, chicken, mouse and turtle, respectively) to those of NCBI's

annotations (20,090, 17,485, 20,482 and 20,259, for human, chicken, mouse, turtle,

respectively). By contrast, GeMoMa [21] predicted the largest number of protein-coding genes

for each species (59,002, 29,054, 39,398 and 38,766 for human, chicken, mouse, turtle,

respectively), which is 1.7-2.9 times higher than those of NCBI's annotations (Table 1). Both

AUGUSTUS [16] and Braker3 [13] predicted considerably fewer or more genes than NCBI's

annotation pipeline (Table 1).

Next, we compared the tools for their ability to recall the genes annotated in each

genome by NCBI. As shown in Table 1, in the human and turtle genomes, AUGUSTUS [16]

recalled the highest numbers of NCBI-annotated genes (15,424 and 15,955, respectively), while

HRannot achieved the second highest numbers (15,340 and 14,862, respectively). In the

chicken genome, GeMoMa [21] recalled the highest number (13,300) and HRannot had the

second highest number (13,071), while GeMoMa [21] predicted 10,782 more genes than

HRannot (Table 1). In the mouse genome, HRannot recalled the highest number (15,667), and

GeMoMa [21] had the second highest number (15,385) (Table 1). Moreover, AUGUSTUS [16]

tends to have higher precision with the trade-off of lower recall; and braker3 [13] and GeMoMa

[21] tends to have higher recall with the trade-off of lower precision (Table 1, Figure 3). In

contrast, HRannot always had the most balanced performance for precision and recall among

the tools (Table 1, Figure 3).

Finally, we compared the tools by the BUSCO [33] completeness assessment. HRannot

achieved more than 91% completeness in all the four species (Table 1), suggesting that its

annotations of these genomes are quite complete. Although GeMoMa [21] obtained similarly

high BUSCO [33] completeness values (90.9%-97.7%) in the genomes, however, it produced too

many false positives (Table 1). Braker3 [13] had BUSCO [33] completeness values arranging

from 81.4% to 92.1% in the genomes, which is much lower than those obtained by HRannot and

GeMoMa [21] (Table 1). AUGUSTUS [16] obtained the lowest BUSCO [33] completeness values

ranging from 35.5% in the mouse genome to 71.9% in the chicken genome (Table 1), suggesting

that it misses a large number of genes in these genomes, although its precision and recall are

higher than some other tools, because it generates many fragmental predictions (Figure 4,

Table S5). More specifically, HRannot achieved the highest BUSCO [33] completeness value in

mouse and turtle (Table 1). In human, HRannot was only 0.1% lower than that of GeMoMa [21],

while GeMoMa [21] predicted 38,285 more protein-coding genes than HRannot (Table 1). In

chicken, GeMoMa [21] achieved 1% higher BUSCO completeness value than HRannot, while

GeMoMa predicted 10,782 more protein-coding genes than HRannot (Table 1). By checking the

details of the BUSCO [33] assessment results, we found that except for chicken, HRannot had

the highest value of complete and single-copy BUSCOs (Figure 4, Table S5), suggesting that

there is little over-annotation. The complete and duplicated BUSCOs value is lower than 1% for

HRannot in all the four annotations (Figure 4, Table S5), suggesting again that HRannot achieves

a complete but few redundant annotations.

In addition, all the other three tools do not annotate pseudogenes in the target

genomes. In contrast, as shown in Table 1, HRannot predicted 784, 541, 56 and 1,952

pseudogenes in the human, chicken, mouse and turtle genomes, respectively, with 134, 9, 24

and 170 overlapping with NCBI-annotated pseudogenes in the four genomes, respectively.

Notably, all the pseudogenes predicted by HRannot were supported by the high-quality

sequencing reads of the corresponding individual of the species (Methods and Materials),

suggesting that the pseudogenes predicted by HRannot are reliable. However, since HRannot

mainly predicts unprocessed pseudogenes, and NCBI mainly predicted processed pseudogenes,

there are a few overlaps between the pseudogenes predicted by the two tools.

HRannot are comparable or even outperforms the NCBI annotation pipeline on the Tibetan

ground tit genome

Although HRannot outperforms the three state-of-the-art methods in almost all the measures

computed, it underforms the NCBI annotation pipeline due probably to the fact that greater

efforts have been made by the NCBI team to annotate these genomes using larger volumes of

RNA-seq data available in these species, particularly, the human, mouse and chicken genomes.

To further demonstrate the prediction accuracy of HRannot, we used it to annotate the

genome of a Tibetan ground-tit individual (Table S1), a less-studied avian species with limited

availability of RNA-seq data, and compared the results with the annotations from NCBI. By

using the CDS isoforms of 145 well-annotated avian species from NCBI RefSeq (Table S3) as the

references, the homology-based method of HRannot predicted 15,352 intact genes, 448

partially supported genes and 81 pseudogenes (Table 2). By using the RNA-seq reads from

multiple tissues of the individual (Table S1), the RNA-based method of HRannot annotated 102

genes for the individual (Table 2). In total, HRannot predicted 15,902 protein-coding genes and

81 pseudogenes for the genome (Table 2), while NCBI annotated 15,814 protein-coding genes

and 83 pseudogenes in it (Table 2). There are 14,030 protein-coding genes shared by the two

pipelines, suggesting that HRannot is able to annotate most of the protein-coding genes (88.7%)

predicted by the NCBI annotation pipeline (Table 2). HRannot achieved a similar BUSCO

completeness value (99.0%) to that of NCBI's annotation (99.5%) (Table 2). However, there is

no overlap of the pseudogenes predicted by the two pipelines (Table 2).

To find the reason for the inconsistent protein-coding genes and pseudogenes predicted

by the two pipelines, we examined the gene-bodies of the unique genes and pseudogenes

predicted by each method. We found that NCBI's pipeline could mistakenly predict our

predicted protein-coding genes as pseudogenes, or mistakenly predict our predicted

pseudogenes as protein-coding genes. For examples, genes *PTCD*2 and *DIO*3 are annotated as

protein-coding genes by the NCBI's pipeline, while they are annotated as pseudogenes by

HRannot since there are stop codons in the middle of their ORFs (Figures 5a and 5b); gene

*LOC*102109485 (named *LOC*107212260 in our annotation) is annotated as a pseudogene by the

NCBI's pipeline, while it is annotated as protein-coding genes by HRannot since there are

neither stop codons nor ORF shift mutations in its ORFs (Figure 5c). Thus, these results suggest

that our HRannot is more accurate in annotating some genes and pseudogenes.

Discussion

We developed a homology- and RNA-based gene annotation pipeline HRannot that

demonstrates superior performance compared to several established tools, including

AUGUSTUS [16], Braker3 [13] and GeMoMa [21], three popular and widely used gene

annotation tools. Through comprehensive benchmarking, our pipeline consistently achieved

higher annotation accuracy, as evidenced by a BUSCO completeness score [33] exceeding 91%

across diverse test vertebrate genomes (Table 1). Importantly, our method maintains a well-

balanced trade-off between precision and recall, addressing a common limitation observed in

other annotation tools that often sacrifice one for the other (Figure 2). While Braker3 [13] and

GeMoMa [21] rely heavily on homology and transcript evidence, respectively, our pipeline

integrates both sources more effectively, resulting in improved gene model prediction.

Compared to AUGUSTUS [16], which primarily depends on *de novo* prediction, our pipeline

shows substantial gains in both structural accuracy and biological relevance. These results

underscore the robustness and reliability of our approach, making it particularly valuable for

annotating newly sequenced or non-model genomes.

Besides, HRannot is also comparable or even more sensitive in some cases compared

with the NCBI gene annotation pipeline, i.e. correcting some pseudogenes or protein-coding

genes that are mistakenly annotated as the other type by the NCBI's pipeline (Figure 5). In

addition, a particular advantage of our pipeline lies in its ability to identify unprocessed

pseudogenes, which retain intron-exon structures and closely resemble their functional

counterparts. In contrast, the NCBI's pipeline primarily annotates processed pseudogenes,

which lack introns and often arise from retrotransposition. The detection of unprocessed

pseudogenes is especially challenging due to their structural similarity to active genes and their

typically low expression levels. Our pipeline's success in capturing these elements highlights its

enhanced sensitivity and specificity in distinguishing subtle genomic features. Although the

BUSCO [33] completeness value of NCBI's annotations are always higher than those of HRannot,

there are always many manual corrections of NCBI's annotation, while HRannot is completely

automatic, causing the relatively lower BUSCO [33] completeness value.

Given its demonstrated effectiveness, our pipeline HRannot offers a compelling

alternative to current standards and holds promise for broad applications in genomics research.

Declarations

Consent for publication
Not applicable.
342
343 **Availability of data and materials**
344 The annotation results of the five species using HRannot are available at
345 https://doi.org/10.6084/m9.figshare.30462191.v1. The code and pipeline description for
346 HRannot are available at https://github.com/zhengchangsulab/HRannot.
347
348 **Competing interests**
349 The authors declare that they have no competing interests.
350
351 **Authors' contributions**
352 ZS supervised and conceived the project; SW and ZS designed the pipeline; SW, SY, WL and ZS
353 performed data analysis; and SW and ZS wrote the manuscript.
354

References

1. Sanger, F., S. Nicklen, and A.R. Coulson, *DNA sequencing with chain-terminating*
inhibitors. Proc Natl Acad Sci U S A, 1977. **74**(12): p. 5463-7.
2. Mardis, E.R., *Next-generation DNA sequencing methods.* Annu Rev Genomics Hum
Genet, 2008. **9**: p. 387-402.
3. van Dijk, E.L., et al., *Ten years of next-generation sequencing technology.* Trends Genet,
2014. **30**(9): p. 418-26.
4. Clarke, J., et al., *Continuous base identification for single-molecule nanopore DNA*
sequencing. Nat Nanotechnol, 2009. **4**(4): p. 265-70.
5. Eisenstein, M., *Oxford Nanopore announcement sets sequencing sector abuzz.* Nat
Biotechnol, 2012. **30**(4): p. 295-6.
6. Nurk, S., et al., *The complete sequence of a human genome.* Science, 2022. **376**(6588): p.
44-53.

7.   Rhie, A., et al., *Towards complete and error-free genome assemblies of all vertebrate*
species. Nature, 2021. **592**(7856): p. 737-746.
8.   Lewin, H.A., et al., *Earth BioGenome Project: Sequencing life for the future of life.* Proc
Natl Acad Sci U S A, 2018. **115**(17): p. 4325-4333.
9.   Telenti, A., et al., *Deep sequencing of 10,000 human genomes.* Proc Natl Acad Sci U S A,
2016. **113**(42): p. 11901-11906.
10. Mao, Q., et al., *The whole genome sequences and experimentally phased haplotypes of*
over 100 personal genomes. Gigascience, 2016. **5**(1): p. 42.
11. Bergström, A., et al., *Insights into human genetic variation and population history from*
929 diverse genomes. Science, 2020. **367**(6484).
12. Brůna, T., et al., *Galba: genome annotation with miniprot and AUGUSTUS.* BMC
Bioinformatics, 2023. **24**(1): p. 327.
13. Gabriel, L., et al., *BRAKER3: Fully automated genome annotation using RNA-seq and*
protein evidence with GeneMark-ETP, AUGUSTUS, and TSEBRA. Genome Res, 2024.
34(5): p. 769-777.
14. Rey, C., et al., *CAARS: comparative assembly and annotation of RNA-Seq data.*
Bioinformatics, 2019. **35**(13): p. 2199-2207.
15. Banerjee, S., et al., *FINDER: an automated software package to annotate eukaryotic*
genes from RNA-Seq data and associated protein sequences. BMC Bioinformatics, 2021.
22(1): p. 205.
16. Stanke, M. and S. Waack, *Gene prediction with a hidden Markov model and a new intron*
submodel. Bioinformatics, 2003. **19 Suppl 2**: p. ii215-25.
17. Burge, C. and S. Karlin, *Prediction of complete gene structures in human genomic DNA.* J
Mol Biol, 1997. **268**(1): p. 78-94.
18. Lomsadze, A., et al., *Gene identification in novel eukaryotic genomes by self-training*
algorithm. Nucleic Acids Res, 2005. **33**(20): p. 6494-506.
19. Grabherr, M.G., et al., *Full-length transcriptome assembly from RNA-Seq data without a*
reference genome. Nat Biotechnol, 2011. **29**(7): p. 644-52.
20. Coghlan, A. and R. Durbin, *Genomix: a method for combining gene-finders' predictions,*
which uses evolutionary conservation of sequence and intron-exon structure.
Bioinformatics, 2007. **23**(12): p. 1468-75.
21. Keilwagen, J., F. Hartung, and J. Grau, *GeMoMa: Homology-Based Gene Prediction*
Utilizing Intron Position Conservation and RNA-seq Data. Methods Mol Biol, 2019. **1962**:
p. 161-177.
22. Kollmar, M., *Predicting Genes in Closely Related Species with Scipio and WebScipio.*
Methods Mol Biol, 2019. **1962**: p. 193-206.
23. Brůna, T., A. Lomsadze, and M. Borodovsky, *GeneMark-ETP significantly improves the*
accuracy of automatic annotation of large eukaryotic genomes. Genome Res, 2024.
34(5): p. 757-768.
24. NCBI, *https://www.ncbi.nlm.nih.gov/refseq/annotation_euk/process/#references*.
25. ENSEMBL, *https://useast.ensembl.org/info/genome/genebuild/index.html*.
26. Kapustin, Y., et al., *Splign: algorithms for computing spliced alignments with*
identification of paralogs. Biol Direct, 2008. **3**: p. 20.

27.   Langmead, B. and S.L. Salzberg, *Fast gapped-read alignment with Bowtie 2.* Nat
412   Methods, 2012. **9**(4): p. 357-9.
413   28.   Quast, C., et al., *The SILVA ribosomal RNA gene database project: improved data
414   processing and web-based tools.* Nucleic Acids Res, 2013. **41**(Database issue): p. D590-6.
415   29.   Nawrocki, E.P. and S.R. Eddy, *Infernal 1.1: 100-fold faster RNA homology searches.*
416   Bioinformatics, 2013. **29**(22): p. 2933-5.
417   30.   Kalvari, I., et al., *Rfam 14: expanded coverage of metagenomic, viral and microRNA
418   families.* Nucleic Acids Res, 2021. **49**(D1): p. D192-d200.
419   31.   Dobin, A., et al., *STAR: ultrafast universal RNA-seq aligner.* Bioinformatics, 2013. **29**(1): p.
420   15-21.
421   32.   Wu, S., et al., *High quality assemblies of four indigenous chicken genomes and related
422   functional data resources.* Sci Data, 2024. **11**(1): p. 300.
423   33.   Simão, F.A., et al., *BUSCO: assessing genome assembly and annotation completeness
424   with single-copy orthologs.* Bioinformatics, 2015. **31**(19): p. 3210-2.
425

Table 1: Comparison of the annotations of different tools from several aspects

Species	Category	HRannot Protein-coding gene	HRannot Pseudogene	AUGUSTUS Protein-coding gene	AUGUSTUS Pseudogene	Braker3 Protein-coding gene	Braker3 Pseudogene	GeMoMa Protein-coding gene	GeMoMa Pseudogene	NCBI Protein-coding gene	NCBI Pseudogene
Human	# Annotation by the tool	20717	784	23489	-	24869	-	59002	-	20090	15534
	# Overlap with NCBI's annotation	15340	134	15424	-	11425	-	13456	-	-	-
	BUSCO completeness	91.1%	-	61.3%	-	81.4%	-	91.2%	-	99.3%	-
Chicken	# Annotation by the tool	18272	541	15898	-	18984	-	29054	-	17485	240
	# Overlap with NCBI's annotation	13071	9	12370	-	12080	-	13300	-	-	-
	BUSCO completeness	96.7%	-	71.9%	-	92.1%	-	97.7%	-	97.7%	-
Mouse	# Annotation by the tool	20624	56	10897	-	18848	-	39398	-	20482	5091
	# Overlap with NCBI's annotation	15667	24	9116	-	13361	-	15385	-	-	-
	BUSCO completeness	93.2%	-	35.5%	-	86.0%	-	92.5%	-	98.4%	-
Turtle	# Annotation by the tool	19670	1952	19641	-	20848	-	38766	-	20259	705
	# Overlap with NCBI's annotation	14862	170	15955	-	12956	-	13309	-	-	-
	BUSCO completeness	94.7%	-	53.7%	-	89.7%	-	90.9%	-	97.8%	-

Table 2: Comparison of gene annotation results of the Tibetan ground-tit genomes by HRannot and NCBI's pipeline

Methods	Homology-based # Intact genes	Homology-based # Partially supported genes	Homology-based # Pseudogenes	# RNA-based genes	# Total protein-coding genes	# Total pseudogenes	BUSCO completeness
HRannot	15,352	448	81	102	15,902	81	99.0%
NCBI	-	-	-	-	15,814	83	99.5%
Common	-	-	-	-	14,030	0	-

Figure 1. Flowchart of the HRannot pipeline. HRannot predicts protein-coding genes using a
combination of homology-based and RNA-based approaches. After proper data preparations,
HRannot first uses the homology-based method to predict homologous genes based on each
gene model in each reference genome in an order described in the main text, and then it
employs the RNA-based method to predict genes that are missed by the homology-based
method using RNA-seq data.

Figure 2. Relationship between the number of predicted homologues genes/RNA-based genes
and the number of reference genomes/tissues whose RNA-seq data are used. a. The
accumulative number of predicted homologues genes in the human genome as a function of
the number of reference mammalian genomes used. **b.** The accumulative number of predicted
homologues genes in the chicken genome as a function of the number of reference bird
genomes used. **c.** The accumulative number of predicted homologues genes in the mouse
genome as a function of the number of reference mammalian genomes used. **d.** The
accumulative number of predicted homologues genes in the turtle genome as a function of the
number of reference reptile genomes used. **e.** The accumulative number of predicted
homologues genes in the Tibetan ground-tit genome as a function of the number of reference
bird genomes used. **f.** The accumulative number of predicted RNA-based genes in the chicken
genome as a function of the number of tissues whose RNA-seq data are used.

452
453   **Figure 3.** Precision and Recall assessment of the annotations by different tools for the human
454   (a), chicken (b), mouse (c) and turtle (d) genomes.

455
Figure 4. BUSCO completeness of the annotations in different genomes. a-d. BUSCO
completeness values of the annotations from different annotation tools for human, chicken,
mouse and turtle genomes, respectively. In each subfigure, S represents Complete and single-
copy BUSCOs, D represents Complete and duplicated BUSCOs, F represents Fragmented
BUSCOs, and M represents Missing BUSCOs. Specifically, BUSCOs completeness in Tables
mentioned above consists of S and D.

Figure 5. Examples of different annotations for the same gene/pseudogene from the NCBI
and HRannot annotation pipelines. **a.** Part of ORFs of gene *PTCD*2 annotated by both the two
pipelines contains a stop codon labeled in red. **b.** Part of ORFs of gene *DIO*3 annotated by both
the two pipelines contains a stop codon labeled in red. **c.** The ORF of gene *LOC*102109485
annotated by the two pipelines. The sequence contains no pseudogenization mutations.