Predicting the Future States of Physicochemical Systems Using Transformer-Based generative Machine Learning Model

Palash Bera* and Jagannath Mondal*

Tata Institute of Fundamental Research Hyderabad, Telangana 500046, India

Abstract

Capturing the time evolution and predicting future conformational states of physicochemical systems present significant challenges due to the precision and computational effort required. In this study, we demonstrate that the transformer, a machine learning model renowned for machine translation and natural language processing, can be effectively adapted to learn the molecular dynamics (MD) simulation trajectory of biologically relevant physicochemical systems. Specifically, by using sequences of time-discretized states from MD trajectories as input, we show that a transformer can learn the complex syntactic and semantic relationships within the trajectory. This enables it to generate kinetically accurate sequences of future states for a diverse set of models and biomolecules of varying complexity. Remarkably, the transformer-based model can predict future states much faster than traditional MD simulations. We show that it is particularly adept at forecasting the time evolution of an out-of-equilibrium active system that do not maintain detailed balance. We demonstrate that the self-attention mechanism inherent in transformers is crucial for capturing the long-range correlations necessary for accurate state-to-state transition predictions. Overall, our results highlight the ability of transformer based machine learning model in generating future states of physicochemical systems with statistical accuracy.

Introduction

The time evolution of any physical system undergoes various state-to-state transitions. Understanding the dynamics of these systems particularly at the molecular level, poses a significant challenge due to the complexity of their transitions between various states. Traditional approaches, such as molecular dynamics simulations (MDs) offer valuable insights into these transitions. However, the MDs are computationally very expensive, limiting their applicability to large-scale systems or long-time predictions. Moreover, describing the actual phase space of a physical system typically involves handling data of very high dimensions. The lower dimensional representation of this data along some order parameters can provide information about various states and transitions between them. Nonetheless, achieving a comprehensive understanding of these transitions over a very long time requires performing highly resource-intensive MD simulations.

In recent years, state-of-the-art machine learning (ML)/artificial intelligence (AI), especially recurrent neural networks (RNN) and large language models (LLM) have become a promising tool in addressing these challenges.[1–7] The RNN-based ML architecture was developed for time series prediction, particularly for forecasting the weather, electricity consumption, revenue, etc.[8–11] They are mainly known for their ability to remember the memory of past inputs while processing current ones. Their capability to capture sequential patterns makes them particularly well-suited for tasks where the order of data matters. However, RNNs suffer from a key limitation known as the vanishing gradients problem.[12] As the length of the input sequence increases, the gradients used to update the RNN's weights tend to become smaller and smaller. To address this issue, an advanced version of RNNs called Long Short-Term Memory (LSTM)[13] was developed. LSTM can solve this vanishing gradients problem by using specialized memory cells and a gating mechanism. They can dynamically adjust their memory by remembering or forgetting information across multiple time steps. This enables them to effectively capture long-term patterns present in sequential data.

Apart from the forecasting problem, the LSTM-based architecture can be used for a variety of sequence-to-sequence tasks, such as language modelling, machine translation, and speech recognition.[2,14,15] However, for large language modelling (LLM) the LSTM might not work to capture the complex syntactic and semantic relationships present in natural language. To overcome these issues, the pioneering work by Vaswani et al.[7] introduced the attention-based model known as Transformer. The concept of self-attention mechanisms can encode contextual information from the input text and generate coherent and contextually relevant responses. Although the original work of the Transformer was mainly designed for machine translation, the various parts of the Transformer can be used for different purposes. For instance, the encoder component can be applied to classification problems, while the decoder component can be used for sequence-to-sequence generation.

In our study, we have utilized the decoder component of the Transformer architecture to predict the future states of diverse physicochemical as well as biologically relevant systems. Our investigations primarily focus on set of systems of hiererchical complexity: including hand-crafted multi-state (three-state and four-state) model potentials, a globular folded protein namely Trp-cage , and an intrinsically disordered protein (IDP) α-Synuclein, as well as an active system, a 32-bead active worm-like polymer chain and its passive counterpart. We demonstrate that our protocol can effectively learn the time evolution of different states in MD or other kinetic simulations along certain low-dimensional order parameters. As a result, the model can generate future states that are kinetically and thermodynamically accurate. Interestingly, the model is remarkably powerful, as it can accurately generate the future state even for an active system that is out of equilibrium. Moreover, for the more complex systems, we have found that the attention mechanism plays a crucial role in maintaining the relationships between the states, enabling the model to generate the future state correctly.

Results

Learning Molecular dynamics trajectory using transformer model

In any language model, the input is a series of characters or words. During the training process, the weights and biases of the various layers are optimized, enabling the model to understand the context and relationships between different parts of the input sequence. Once the model is trained, it can generate the subsequent sequence for a given input sequence in an auto-regressive manner. As illustrated in figure 1, here we implement a comprehensive scheme to learn kinetic trajectory via transformer and then to generate future states that could be segmented into three stages:

- A. Segmentation of MD trajectory into discrete states.

- B. Training a decoder-only transformer using MD-derived states as input.

- C. Generating future states from pre-trained transformer.

Below we describe the different stages of our scheme.

A. Discretization of Molecular Dynamics trajectory into meaningful state-space: The time evolution of a physical system involves various conformational or state changes and transitions between them. Our study aims to predict the future state of physicochemical systems using a large language model, specifically a decoder-only transformer. Interestingly, the state prediction problem can be mapped to the sequence generation of any language model where each state corresponds to a distinct vocabulary item within a corpus. For all of the systems, we have utilized molecular dynamics (MD) simulation trajectories to predict their future state. However, MD trajectories are continuous, requiring discretization of the trajectory into grid points or states before inputting it into a language model. For simple systems, particle position can be used for discretization. However, complex systems with high dimensionality or degrees of freedom require defining some order parameters or collective variables (CVs) to discretize the trajectory into a certain number of states. To

Figure 1: **A schematic representation of training data preparation and the architecture of the decoder-only transformer.** The left-hand side figure represents the schematic representation of the discretization of molecular dynamics simulation (MDs) trajectory achieved through the identification of collective variables (CVs) and K-means clustering. A total of $n_s = 10$ segments are randomly selected from the discretized trajectory to train an equal number of independent GPT models. Each trained model generates subsequent sequences starting from where the respective segment ended, using a few sequences as prompts. The right-hand side figure depicts the various layers of a decoder-only transformer. The model architecture consists of input embedding, positional embeddings, and multiple blocks of masked multi-head attention, normalization, and feed-forward layers. The model is optimized using cross-entropy as the loss function.

identify the various states of a physical system, we performed K-means clustering along CVs. Consequently, the trajectory is segmented into distinct sequences of states. These sequences can then be used as inputs for a decoder-only transformer model. Hereafter, these sequences of state will be referred to as sequences of token. For training the decoder-only transformer model, we randomly chose n_s number of segments from the discretized trajectory and trained n_s number of independent models with the same architecture. From each independent trained model, we generated the next sequences from where the corresponding segment ended by providing a few sequences as a prompt. All the results presented here are averaged over these independent runs. The left side of Figure 1 illustrates a schematic overview of this process. The specific details regarding the amounts of data used for training, validation, and testing across the various systems are provided in Table-S1. Our approach and model are different from the methodology employed by Tsai et al.[16] In their study, they utilized an LSTM-based architecture to learn the MD simulation trajectory, and the states were generated from the training data itself.

B. Training a decoder-only transformer with MD-derived states as input: Now we will delve into the architecture of the decoder-only transformer model. The neural network-based decoder-only transformer[7] consists of several layers as depicted in the right side of the Figure 1. The first layer is an input embedding or token embedding layer which transforms each token of the input sequence into a dense vector. The dimension of the vector is a hyperparameter which is called embedding dimension. For a sequence of length l and embedding dimension d, this layer transforms each token into a d-dimensional vector. Consequently, the embedding layer generates a $(l \times d)$-dimensional matrix, often referred to as the embedding or weight matrix. Throughout the training process, the elements of this weight matrix undergo optimization and the model will learn the semantic relationship between different tokens of the time sequence data.

To enable the GPT model to learn the sequence order of time series data, the positional information for each token is required which can be achieved through positional embeddings.

For an input sequence of length l, the position of the k^{th} token can be represented as follows [7]

$$PE(k, 2i) = sin(k/10000^{2i/d}) \tag{1}$$

$$PE(k, 2i + 1) = cos(k/10000^{2i/d}) \tag{2}$$

where d is the dimension of output embedding and, for each $k(0 \leq k < l)$, i can take value from 0 to $d/2$. Hence, one can achieve the final embedding layer by adding these two embeddings.

The final embedding layer is followed by multiple blocks of layer (N_b). Each block typically comprises various components, including masked multi-head attention with a specified number of heads, N_h, normalization layers, and feed-forward layers. Among these, the masked multi-head attention layer is particularly significant, serving as a communication mechanism between each token in the sequence. To calculate the key (K), query (Q), and value (V) tensors, the final embedded vector, denoted as X_f, is multiplied with three trainable weight matrices (W_k, W_q, and W_v) as: $K = X_f \cdot W_k$, $Q = X_f \cdot W_q$, and $V = X_f \cdot W_v$. The attention score A_s is then calculated as $A_s = \text{softmax}(\frac{QK^T}{\sqrt{d}})$, and the output of the attention layer is given by [7]

$$\text{Attention}(Q, K, V) = A_s V = \text{softmax}(\frac{QK^T}{\sqrt{d}})V \tag{3}$$

where $\text{softmax}(x_i) = \frac{\exp(x_i)}{\sum_j \exp(x_j)}$. This mechanism enables the model to discern the relative importance of tokens to each other, providing a clear sense of context and relationships between them.

Finally, the normalized outputs of the N_b layer are used as inputs of a fully connected dense linear layer. Given that the GPT model functions as a probabilistic model, the output of this dense layer is passed through a softmax function to yield categorical probabilities. We have used cross-entropy as our loss function to minimize the loss between the final output

of the model $\hat{O}^{(t)}$ and actual target output $O^{(t)}$ which is defined as

$$\mathcal{L} = -\sum_{t=0}^{T-1} O^{(t)} \cdot \ln(\hat{O}^{(t)}) \tag{4}$$

where T represents the total time of the trajectory, equivalent to the sequence length (l). The model has been trained over 10000 epochs, with all hyperparameters across all of the systems provided in the Table-S2. Figures S1(a-f) show the training and validation loss as a function of epochs for six distinct systems that would be elaborated in the upcoming sections of the present article. The plots indicate that the loss curves saturate or fluctuate slightly about the mean after a certain number of epochs, suggesting robust training of the GPT model without overfitting.

C. Generating future states from pre-trained transformer: After training the GPT model, it can generate any desired number of time series future states by inputting an initial sequence of tokens as a prompt. For a given sequence, the model will generate a probability distribution over the entire vocabulary/states. From this probability distribution, the next element of the sequence can be sampled using a multinomial distribution (see supplemental results SR1 for details). As we have generated the future states across all systems using our trained model, hereafter we will refer to it as the Generative Pre-Trained Transformer (GPT) model. The GPT model was built using PyTorch[17] and our implementation is available in Github at the following URL: https://github.com/palash892/gpt_state_generation

Testing on model multi-state systems

To begin, we will delve into two hand-crafted model systems: 2D Brownian dynamics (BD) simulations of a single particle in 3-state and 4-state potentials. The mathematical representations of the potentials and simulation details are provided in the "Methods" section. We employ the BD trajectories to compute the 2D free energy of the two model systems within their X and Y coordinate space, defined as $\frac{F}{kT} = -\log P$, where P is the probabil-

ity, calculated by using a 2D histogram of the coordinates. Figure 2(a) represents the free energy surface (FES) plot for the 3-state toy models. The plot exhibits three minima in the FES and the particle can hop from one minimum to another. The states are marked in the plots using magenta color, identified through K-means clustering in coordinate space (Figure 2(b)). After clustering the data, the entire trajectory is discretized into a specific number of states. Figure 2(c) shows the trajectory after spatial discretization, where each cluster index corresponds to a metastable state. The trajectory demonstrates that the particle can stay in a particular state for some time, and also exhibits transitions between various states. Now, from both the actual i.e. BD-generated and GPT-generated time series data, we can compute the probability of each state by counting the occurrences of that particular state and dividing by the total count. For instance, if the count of state 0 is C_0 and the total count of all states is C_{tot}, then the probability of state 0 is $P(0) = \frac{C_0}{C_{tot}}$. Figure 2(d) depicts a comparison between the actual and GPT-generated state probabilities for the 3-state model. The plot suggests that there is a close match between the actual and GPT-generated state probabilities.

To effectively compare the kinetics between actual and GPT-generated time series data, one must analyze the transitions between different states over time. To facilitate this analysis, we utilized the concept of "commitment time or commit time". This metric represents the duration a particle remains in a given state before transitioning to another.[16] We calculated the total transition count for different commit times, considering all possible state pairs ($^nC_2$, n is the total number of states) and both forward and backward directions. Figures 2(e-g) represent the transition count as a function of commit time for a 3-state toy model. These plots reveal that the decay of transition counts as a function of commit time is very similar between actual and GPT-generated data in both directions. Furthermore, the 2D FES plot (Figure 2(a)) indicates that states 0 and 2 are spatially distant. The actual data corroborates this by showing no direct transitions between these states. Quite interestingly, the GPT model captures a maximum of three transitions, showcasing its capability to capture the

Figure 2: **Kinetics and thermodynamics for toy model system.** (a) Free energy surface (FES) plot for 3-state toy model in their X and Y coordinate space. The particle can transition from one minimum to the other. (b) Scatter plots of the X and Y coordinate, with distinct clusters representing metastable states identified through K-means clustering. (c) The trajectory of the particle in 3-state potential after state decomposition. (d) The comparison of state probabilities between the actual and GPT-generated time series data for the 3-state toy model. The plot highlights the accuracy of the GPT model in predicting the state probabilities. (e-g) Transition counts as a function of commit time for a 3-state toy model. These plots indicate the ability of the GPT model to learn contextual relationships among the states and generate future states that are kinetically and thermodynamically significant. Here the error bar represents the standard error and the commit time is in the unit of τ_{BD} (see "Methods").

underlying dynamics.

We assessed the accuracy of this approach for a 4-state toy model system, as depicted in Figures S2(a-j). , Barring slight deviations in probabilities and a few transitions (Figure S2(f) and Figure S2(i)), the results are very similar for both actual and GPT-generated states. The free energy surface (FES) plot in Figure S2(a) indicates that states 1 and 0, as well as states 2 and 3, are spatially distant, with no direct transitions between them in the actual data. Remarkably, the GPT-generated states capture these trends very nicely. However, upon closer examination, the FES (Figure S2(a)) suggests that although states 0

and 2, and states 1 and 3, are spatially proximate, the trajectory is not sampled properly. This discrepancy may contribute to the slight deviations in transition counting between actual and GPT-generated data for these pair of states (0-2, 2-0, 3-1, and 1-3). Nevertheless, the results collectively indicate that the GPT model effectively learns the context and relationships between states, enabling it to generate future states that are both kinetically and thermodynamically significant.

Predicting the ensemble probabilities and state-to-state transition kinetics in Trp-cage mini protein

Encouraged by the promising results in model potential, we extended our approach on a globular 20-residue mini-protein Trp-cage. This biomolecule is known for complex and multistate conformational ensemble, despite its small size and remains an ideal candidate for experimental and computational studies of protein folding. Towards this end, we utilized a long ($100\mu s$) unbiased simulation trajectory of Trp-cage , provided by D. E. Shaw Research (DESRES).[18,19] For this system, due to higher degrees of freedom, it is necessary to define suitable order parameters or collective variables (CVs) to discretize the time series data into a certain number of states. Nonetheless, the identification of precise CVs is a challenging problem. To address these challenges, we employ an encoder-decoder-based unsupervised deep neural network called Autoencoder.[20,21] An Autoencoder is a powerful non-linear dimension reduction technique that is used to transform the high-dimensional input data in a lower-dimensional space known as the latent space. The encoder component of the Autoencoder maps the input data to the latent space, while the decoder reverses this process, reconstructing the original input from the latent space. During this process, the model optimizes its weights and biases to preserve the most important information from the input data in the lower-dimensional representation. Figure 3(a) represents a schematic of autoencoder architecture where the distances between C_α atoms serve as input features. During the training of the Autoencoder, we monitor the fraction of variation explained (FVE) score to

Figure 3: **Kinetics and thermodynamics for Trp-cage mini protein.** (a) A schematic representation of the Autoencoder. In this setup, $d_1, d_2, \ldots, d_n$ denote the input and output nodes, delineating the dimensions of the input and output data, while $h_1, h_2, \ldots, h_n$ represent the hidden nodes. Furthermore, $\chi_1, \ldots, \chi_3$ represent the latent nodes. (b) 2D FES plot along latent space χ_1 and χ_2 for Trp-cage with three distinct minima and extracted conformations. (c) The state decomposition of the MD trajectory is achieved through k-means clustering on the latent space, which divides the entire trajectory into distinct sequences of states. (d) The trajectory of the Trp-cage after state decomposition. (e) The comparison of state probabilities for between actual and GPT-generated time series data. These plots suggest that the GPT model effectively captures the probabilities with minor deviations. (f-h) Comparison of transition counts between actual and GPT-generated states, showcasing the GPT model's ability to accurately capture state transitions. Here error bar represents the standard error.

determine the optimal dimension of the latent space. A detailed description of the Autoencoder architecture and the various hyperparameters are provided in the ("Methods" section and Table-S3).

Figure 3(b) represents the 2D FES plot along the latent space χ_1 and χ_2, obtained from Autoencoder. The figure clearly shows three distinct minima in the FES plot, indicating dis-

tinct conformations. To visualize different conformations, we extracted a few conformations near each minimum in the FES and overlaid them. The superimposed conformations reveal mainly three metastable states: folded α-helix (state-0), partially folded α-helix (state-1), and unfolded random coils (state-2). After clustering in the latent space, the entire trajectory comprises metastable states and their transitions, as depicted in Figure 3(c). Figure 3(d) illustrates the discretized trajectory, with the majority of transitions occurring between states 1 and 2. Figure 3(e) represents a comparison of the state probabilities between the actual and GPT-generated time series data for the Trp-cage protein. These figures demonstrate that the GPT model has effectively captured the probabilities, with minor deviations observed for a few states. Importantly, these deviations are within the error bars.

Next, to probe the kinetics between various states of the Trp-cage protein, we calculated the transition counts as a function of commit time, akin to methodologies employed for 3-state and 4-state toy models. Figures 3(f-h) compare the transition counts between actual and GPT-generated states for the Trp-cage protein. These figures encompass all possible pairs and transitions in both forward and reverse directions. The results indicate that the GPT model accurately captures the transitions between states. Quite interestingly, the GPT model can also predict the highest number of transitions between states 1 and 2 accurately which aligns with our observations from the trajectory itself (Figure 3(e)). In summary, together these results suggest that the GPT model effectively captures the probability and the transition counts between various states of the Trp-cage protein, providing valuable insights into the kinetics and thermodynamics of these systems.

On more complex system: intrinsically disordered protein α-Synuclein

Next, we turn our attention to an intricately complex system: α-Synuclein. It is a prototypical intrinsically disordered protein (IDP) that predominantly resides in the human brain, especially nerve cells.[22] It plays a crucial role in the communication between these cells by releasing neurotransmitters which are messengers chemicals.[23] However, the exces-

Figure 4: **The radius of gyration** (R_g) **and transition count comparison for α-Synuclein.** (a) The (R_g) as a function of time for α-Synuclein (red plot). The magenta color plot represents the trajectory after state decomposition via K-means clustering. (b) The diverse conformational states are identified as intermediated compact (state-0), collapsed (state-1), and extended (state-2). (c-e) Transition count comparison between the actual and GPT-generated time series data as a function of commit time for α-Synuclein. The transition dynamics fairly match with actual and GPT-generated data except at a smaller commit time. Here the error bar represents the standard error.

sive accumulation of these proteins can lead to several neurodegenerative disorders such as Parkinson's disease and other synucleinopathies.[24–26] For α-Synuclein, we utilize the $73\mu s$ trajectory provided by D. E. Shaw Research (DESRES).[18,19]

For this complex system, we have observed that the Autoencoder is not trained properly for certain dimensions of the latent space. Consequently, we used the radius of gyration as CVs to decompose the entire trajectory into a specific number of states. Figure 4(a) represents the radius of gyration (R_g) (red color) of the α-Synuclein as a function of time, showcasing the protein's diverse conformational possibilities. Through K-means clustering in the R_g space,[27] we discretize the total trajectories into distinct states (Figure 4(a) magenta color plot). Specifically, three states have been identified: intermediated compact (state-0), collapsed (state-1), and extended (state-2), with a superimposition of snapshots revealing significant conformational heterogeneity within each state (Figures 4(b)).

Figure S3 compares the state probabilities between actual and GPT-generated time series data for α-Synuclein. The figure clearly shows the deviation in the state probability values. Next, to analyze the transition dynamics, we have calculated the transition count of each state. Figures 4(d-f) depict the comparison of transition count as a function of commit time between actual and GPT-generated time series data for α-Synuclein. While there are some deviations in probability values, the transition dynamics align fairly well with actual and GPT-generated data, except for a smaller commit time. Specifically, the GPT model generates a lower count for transition $(2 \rightarrow 0)$ compared to actual data. The deviations in state probability and transition dynamics indicate the intricacies involved in accurately predicting the dynamical behavior of such a complex system.

Assessing transformer's predictive ability in far-from-equilibrium system: active worm-like polymer chain

In the preceding sections, we have mainly focused on capturing kinetics and thermodynamics of various models and real systems that are in thermodynamic equilibrium. Finally, in this section, we shift our attention to an active system. Most living organisms are active and their movement is powered by energy consumption from internal or external sources. The continuous consumption and dissipation of energy drive these systems far from equilibrium. Notably, the activity or self-propulsion force plays a crucial role in the formation of many self-organized collective phenomena such as pattern formation,[28–30] motility-induced phase separation,[31–33] swarming motion,[34–37] etc. In this study, we employ a model system, an active worm-like polymer chain,[38] where the activity or self-propulsion force acts tangentially along all bonds. We have utilized our in-house BD simulation trajectory to study the active polymer chain (see Methods for details).

After training the Autoencoder by using inter-bead distances as features, we have chosen two-dimensional latent space as CVs. Figure 5(a) shows the FES plot across the latent space χ_1 and χ_2 for the active polymer chain and the corresponding metastable states are

Figure 5: **The free energy surface and transition count comparison for the active worm-like polymer chain.** (a) The FES plot of the active polymer chain across the latent space χ_1 and χ_2. This plot highlights two metastable states: a bending state (state-1) and a spiral state (state-0). (b) The latent space has been clustered via K-means clustering to discretize the trajectory. (c) The comparison of transition count between actual and GPT-generated data for the active polymer chain, reflecting the system's long stay at particular states before transition and the violation of detailed balance. The GPT model accurately generates future states, maintaining saturation and detailed balance violation, albeit with some small deviation from actual data. Here the error bar represents the standard error and the commit time is in the unit of τ_{BD} (see "Methods").

highlighted in magenta color. The overlaid plots suggest that there are mainly two metastable states: a bending state (state-1) and a spiral state (state-0). Notably, despite the apparent simplicity of the two states, the visualization of the trajectory (Figure S4(a)) suggests that the system spends a very long time within each state along with spontaneous spiral formation and breakup occurrences. Subsequently, we employ K-means clustering on the latent space derived from Autoencoder to discretize the trajectory (Figure 5(b)).

Figure S4(b) compares the state probabilities between actual and GPT-generated time

series data for active polymer chain. The comparison reveals the deviations in the state probability. Figure 5(c) depicts the comparison of transition count as a function of commit time between actual and GPT-generated time series data. However, interestingly, the GPT model accurately generates the transition for the active system. As mentioned earlier, for the active polymer chain, the system stays at a particular state for a long time before transit to the other state. This behaviour is reflected in the plots, where both curves saturate after a certain commit time. Moreover, the forward and backward transition curves suggest a violation of detailed balance, which is an inherent feature of active systems that are far from thermodynamic equilibrium. Remarkably, the GPT model successfully generates future states that maintain the saturation nature as well as the violation of detailed balance, albeit with some deviation from actual data within the error bar. These findings indicate that the GPT model is very powerful for future state predictions, even in complex active systems. In a similar spirit, for comparison purpose, we have also computed similar metrics for a 'passive' polymer chain for an enhanced clarity (Figures S5). Here too, we observed a strong alignment between the kinetics and thermodynamics captured by the GPT model and the actual BD-generated data.

The profound impact of the attention layer

In the previous sections, our focus has been on exploring the thermodynamics and kinetics of diverse model and real systems, whether in thermodynamic equilibrium or out of equilibrium. We have observed that despite variations in state probabilities, the GPT model generates future states that accurately maintain transition dynamics in a statistical sense. Now, in this section, we delve into identifying the pivotal factors that maintain these precise transition dynamics.

In the field of natural language processing (NLP), the seminal work by Vaswani et al. titled "Attention Is All You Need"[7] introduces the paradigm-shifting concept of self-attention. The state-of-the-art transformer model, based on attention mechanisms, has demonstrated

Figure 6: **Attention score for all the systems analyzed.** (a-f) The heat map of the attention score computed from the multi-head attention layer of a trained GPT model, for six distinct systems under consideration. These scores reveal that there is finite attention among various tokens and highlight the evidence of long-range attention.

superior performance compared to traditional recurrent neural networks (RNNs). To understand the role of attention, we computed the attention score from the multi-head attention layer which is defined as $A_s = \text{softmax}(\frac{QK^T}{\sqrt{d}})$ (see equation 3 for details), where Q, K, and d are the query, key, and the dimension of the embedding layer, respectively. In our study, we randomly selected 20 chunks of sequence length 128 from GPT-generated time series data and fed them as inputs for the trained GPT model. Subsequently, we computed the attention scores from each head, averaging them across all heads and the 20 random chunks. Physically, these attention scores unveil correlations among different tokens within a sequence of time series data. Figures 6(a-f) show the heat map of the masked attention score for all the systems. These plots highlight the presence of significant finite, non-zero attention among various tokens within sequences. Notably, some tokens exhibit clear evidence of long-range attention, underscoring the model's ability to understand the relationships between events that are far apart.

Figure 7: **Impact of Attention on Transition Dynamics in GPT Model.** (a-j) The comparison of transition counts over commit time between the actual and GPT-generated time series data for all of the systems in absence of attention mechanisms. There are significant deviations in GPT-generated transition dynamics compared to the actual data. While the GPT model can sometimes accurately predict transitions in one direction, it frequently mispredicts transitions in another direction.

Based on our examination of attention scores, we now pose the following question: How does attention impact the transition dynamics between different states? To address this, we trained the GPT model on all six systems by removing the multi-head attention layer, while maintaining other hyperparameters consistent with our previous model architecture. This approach ensures that the model can no longer capture any short or long-range correlations between tokens. Our findings indicate that for simple systems, such as a 3-state toy model, the transition dynamics captured by the GPT model remain similar regardless of the presence or absence of the attention layer (see Figure S6). This suggests that attention may not play a significant role in these simple systems. However, for other systems, there are substantial deviations in GPT-generated transition dynamics compared to actual data. Figure 7(a-j) represents the comparison of transition count as a function of commit time between the actual and GPT-generated time series data for all of the systems under consideration as highlighted in the text of each plot. These plots suggest that while in many cases the GPT model can recover the transition counts in one direction, it completely predicts the wrong transitions in other directions. Here, we have only shown the plots where the deviations are prominent. The comprehensive plots for all the systems with all possible transitions are

given in SI (Figures S7-S10). Together these analyses identify the power of the attention layer. Even in physicochemical systems, attention is crucial for learning the context and relationships or correlations among various tokens of time series data, enabling the model to generate a physically meaningful future state.

Performance Comparison: MD Simulation vs. GPT State Generation

After training the GPT model, the generation of the future state is extremely fast compared to conventional MD simulations of equivalent systems. For example, the model can generate 20000 next sequence for α-Synuclein within ~ 6.0 minutes, corresponding to a 20 μs simulation of this system with a data saving frequency of 1 ns. Similarly, the model can generate 100000 sequences for the Trp-cage mini protein within ~ 32 minutes, equivalent to 20 μs simulation with a data dumping frequency of 200 ps. As mentioned earlier, we have analyzed six systems among them the Trp-cage mini protein and α-Synuclein are particularly relevant in biophysical contexts, and their simulations were conducted in real-time units. Thus, our primary focus here is to compare the performance of these two systems. To compare this generation efficiency against actual MD simulation times, we conducted 10 ns simulations for these systems, maintaining all parameters such as box size, salt concentration, temperature, and time step as per the study by Robustelli et al.[18] As the data saving frequency for these two systems is different, we define a quantity $P_{\mathrm{MD/GPT}}^{N} = \frac{P_{\mathrm{MD/GPT}}}{f_{\mathrm{dump}}}$ where $P_{\mathrm{MD/GPT}}$ is the performance of MD or GPT model and f_{dump} is the saving frequency of the data. This metric can normalize the performance of each system by its respective data saving frequency. All the MD simulations and training of the GPT models were performed on an Intel(R) Xeon(R) Platinum 8352Y CPU at 2.20GHz, along with an NVIDIA RTX A6000 GPU. Table 1 represents all of the details of the performance of the MD simulations as well as GPT state generation. The table 1 suggests that the performance and normalized

performance of the GPT model outstrip those of traditional MD simulations, demonstrating its efficiency in generating future states of the systems.

Table 1: The comparison of the performance between MD simulation and GPT state generation.

System	f_{dump}	P_{MD} (ns/day)	P_{MD}^N (/day)	Training time (minutes)	Gen. sequence	Gen. time (minutes)	P_{GPT} ($\mu s/day$)	P_{GPT}^N (10^3/day)
α-Synuclein	1.0 ns	~ 35.0	~ 35.0	~ 127.0	20,000	~ 6.0	~ 4800.0	~ 4800.0
Trp-cage	200 ps	~ 832.0	~ 4160.0	~ 35.0	100,000	~ 32.0	~ 900.0	~ 4500.0

Discussions

The time evolution of biophysical systems undergoes various conformation changes, depending on environmental conditions. Understanding these dynamics typically requires experiments or Molecular Dynamics (MD) simulations. However, comprehending the long-term behaviour of these systems requires running computationally expensive simulations. In this study, we present a comprehensive approach, employing state-of-the-art machine learning models, particularly decoder-only transformers to predict the future states of physicochemical systems. Through an extensive analysis of the MD trajectory of various models and real systems, we have demonstrated the efficacy of the GPT model in capturing both the kinetics and thermodynamics of these systems.

Our study began with simplified model systems, namely 3-state and 4-state toy models. We employed K-means clustering on coordinate space for this simple system to discretize the trajectory. Subsequently, we delved into more complex systems such as the Trp-cage mini protein, 32-bead passive polymer chain, and intrinsically disordered protein α-Synuclein. However, for these systems, we utilized another ML-based technique Autoencoder, to identify the relevant collective variables for discretization. Our results highlight the ability of the GPT model to accurately predict the probabilities of different states and capture the transition dynamics between them. Furthermore, we extended our analysis to include an

active system, a 32-bead active worm-like polymer chain, where the system is far from thermodynamic equilibrium. Remarkably, the GPT model successfully predicted the kinetics and thermodynamics of the active system.

An interesting aspect of our study is to dissect the role of the attention mechanism within the transformer architecture. Through attention score analysis, we noticed that there are significant correlations among different tokens within sequences, indicating the model's capacity to understand long-range dependencies. Furthermore, by removing the attention layer from the model, we observed substantial deviations in transition dynamics for complex systems. Therefore, these findings strongly suggest that the attention mechanism plays a pivotal role in maintaining accurate predictions.

Although the transformer-based large language models (LLM) were specially developed for tasks like machine translation and natural language processing, our study demonstrates their effectiveness in predicting the kinetics and thermodynamics of a diverse array of biophysical systems. One notable limitation of our GPT model is that it never generates new states beyond its training data. In terms of language, the transformer-based model is always unable to generate new vocabulary. Nonetheless, the model can learn the complex syntactic and semantic relationships present in the sequence of tokens which help them to generate future states of the system very correctly. If some system shows a completely new state at a very long time that is not present in the training sequence, the model can not generate that particular state. This suggests that one needs very good MD sampling data for a physical system to predict the future state of the system. However, recent advances in ML have introduced innovative techniques such as variational autoencoders (VAE),[39–41] generative adversarial networks (GANs),[42,43] diffusion models,[44,45] etc., which can be utilized for generating new conformations and improving sampling in biophysical systems.[46–48] While these techniques enhance sampling quality, they may lack the temporal information crucial for understanding the dynamics of the system. In conclusion, our findings highlight the potential of LLMs as powerful tools for advancing our understanding of biophysical systems, offering

new avenues for further exploration and improvement in this field.

Methods

3-state and 4-state toy model

To simulate a particle in a 2D 3-state and 4-state potential well, we adopted the same functional form for the potential as Tsai et al.[16] The potential for the 3-state model is given by:

$$V_3(x, y) = W_3(x^6 + y^6) - G(x, x_1)G(y, y_1)$$
$$- G(x, x_2)G(y, y_2) - G(x, x_3)G(y, y_3) \tag{5}$$

Similarly, the potential for the 4-state model is given by:

$$V_4(x, y) = W_4(x^4 + y^4) + G(x, x_1)G(y, y_1)$$
$$- G(x, x_2)G(y, y_2) - G(x, x_3)G(y, y_3)$$
$$- G(x, x_4)G(y, y_4) - G(x, x_5)G(y, y_5) \tag{6}$$

Where G is a Gaussian function as $G(x, x_0) = \exp(-\frac{(x-x_0)^2}{2\sigma^2})$. Here x_0 and σ are the mean and standard deviation of the distribution. In our simulation we kept $W_3 = W_4 = 0.0001$ and $\sigma = 0.8$. The mean values of Gaussian distribution for the 3-state model are given by $x_1 = 0.0, y_1 = 0.0$, $x_2 = -1.5, y_2 = -1.5$, and $x_3 = 1.5, y_3 = 1.5$. Similarly, for the 4-state model, these values are $x_1 = 0.0, y_1 = 0.0$, $x_2 = 2.0, y_2 = -1.0$, $x_3 = 0.5, y_3 = 2.0$, $x_4 = -0.5, y_4 = -2.0$, and $x_5 = -2.0, y_5 = 1.0$. We performed Brownian dynamics simulations for these two systems by integrating the equation of motion:

$$\frac{d\vec{r}}{dt} = -\frac{1}{\gamma}\vec{\nabla}V + \vec{\eta}(t) \tag{7}$$

where γ is the friction coefficient, V is the potential energy, and $\vec{\eta}(t)$ is a random noise, satisfying fluctuation dissipation theorem i.e $\langle \vec{\eta}(t) \cdot \vec{\eta}(t') \rangle = 4kT\gamma^{-1}\delta(t-t')$. Here all simulations time is in the unit of $\tau_{BD} = \frac{\sigma^2\gamma}{kT}$, where $\sigma = 1$ is the diameter of the particle. Integration of the equation 7 was performed using Euler method with a time step $\delta t = 0.01\tau_{BD}$ by setting $\beta = \frac{1}{kT} = 9.5$.

Passive polymer chain

We performed a very long molecular dynamics simulation $(5.74\mu s)$ for a passive polymer chain, with the model and simulation parameters of the polymer system detailed in a previous study by our group.[49]

Trp-cage mini protein and α-Synuclein

For Trp-cage and α-Synuclein, we utilized very long molecular dynamics simulation trajectories from D. E. Shaw Research (DESRES).[18] The Trp-cage trajectory spanned $100\mu s$, while the α-Synuclein trajectory was $73\mu s$ long. These simulations were performed using the a99SB-disp force field on Anton specialized hardware.[19] The detailed simulation protocols can be found in the original paper by Robustelli et al.[18] However, in the original paper, the trajectory of α-Synuclein was $30\mu s$ long. Due to some periodic image issues in the original trajectory, the authors provided the extended $73\mu s$ trajectory for α-Synuclein, maintaining the same simulation setup as before but increasing the box size.

Active worm-like polymer chain

The two-dimensional worm-like polymer chain consists of $N = 32$ beads connected by a stiff spring with spring constant k_0. Each bead has a diameter of σ and an equilibrium bond length of d_0. The dynamics of the polymer chain are governed by overdamped motion,

described by the equation:

$$\frac{d\vec{r}_i}{dt} = -\frac{1}{\gamma}\vec{\nabla}V_{tot} + \frac{\vec{f}_m^{(i)}}{\gamma} + \vec{\eta}_i(t) \tag{8}$$

where γ is the friction coefficient, and V_{tot} is the total potential energy of the system, which includes bonding potential V_{bond}, bending potential V_{bend}, and non-bonded potential V_{nb}. The bonding potential V_{bond} is given by:

$$V_{bond} = \frac{k_0}{2}\sum_{i=1}^{N-1}(|\vec{r}_{i,i+1}| - d_0)^2 \tag{9}$$

The bending potential V_{bend} is given by:

$$V_{bend} = \frac{k_{ang}}{2}\sum_{i=1}^{N-2}(\theta_i - \theta_0)^2 \tag{10}$$

where k_{ang} is the bending rigidity and θ_0 is the equilibrium bond angle. The non-bonded potential V_{nb} is taken as the Hertzian potential:

$$V_{nb} = \frac{2}{5}E\sigma^{1/2}(\sigma - r)^{5/2} \tag{11}$$

These potentials are very generic for the simulation of any passive polymer chain. However, the most important force for an active polymer chain is the motility or self-propulsion force. Here, $\vec{f}_m$ represents the self-propulsion force which acts tangentially along all bonds. The random noise $\vec{\eta}_i(t)$ maintains the fluctuation-dissipation theorem i.e $\langle\vec{\eta}_i(t)\cdot\vec{\eta}_j(t')\rangle = 4kT\gamma^{-1}\delta_{i,j}\delta(t - t')$. All lengths and energies are in the units of σ and kT, respectively, and the simulation time is in the units of $\tau_{BD} = \frac{\sigma^2\gamma}{kT}$. The Brownian dynamics simulation for an active polymer chain was performed using a time step of $dt = 0.001\tau_{BD}$. The other simulation parameters are $kT = 1.0$, $\sigma = 1.0$, $d_0 = 0.5\sigma$, $k_0 = 5000.0\frac{kT}{\sigma^2}$, $k_{ang} = 45.0kT$,

$\gamma = 200kT\tau_{BD}/\sigma^2$, $f_m = 5.0kT/\sigma$, $\theta_0 = \pi$, and $E = 10000.0kT/\sigma^3$

Training details of Autoencoder

The Autoencoder architecture and training hyperparameters are presented in Table **??**. For the Trp-cage mini protein, we utilized the distance between all C_α atoms as input features, resulting in 190 ($^{20}C_2 = 190$) features for its 20 residues. Conversely, for active and passive polymer chains, we employed inter-beads distances, selecting 8 effective beads in an arithmetic progression with a step of 4, providing 28 ($^8C_2 = 28$) input features.[50] Throughout the Autoencoder training process, we monitored two metrics: training loss and the fraction of variation explained (FVE) score. The FVE is defined by the equation:

$$\text{FVE} = 1 - \frac{\sum_{i=1}^{N} \|\mathbf{X}(i) - \mathbf{Y}(i)\|^2}{\sum_{i=1}^{N} \|\mathbf{X}(i) - \overline{\mathbf{X}}\|^2} \tag{12}$$

where, $\mathbf{X}(i)$, $\mathbf{Y}(i)$, and $\overline{\mathbf{X}}$ represent the input, output, and mean input, respectively, and N corresponds to the total number of features. The FVE score indicates the proportion of input data variance explained by the Autoencoder's reconstruction. Figures S11(a-f) depict the plots of these two metrics for all systems as described within the figure text. For active and passive polymer chains, a 2D latent dimension was chosen, whereas for the Trp-cage mini protein, a 4D latent dimension was utilized. Across all these latent dimensions, the FVE scores exceed 0.80, indicating that the Autoencoder's reconstruction explains at least 80% of the original data variance. Furthermore, the gradual decrease followed by saturation of the training loss curve suggests no overfitting during the Autoencoder's training process. However, in the case of the IDP α-Synuclein, even with a high latent dimension of $L_d = 7$, we have observed a relatively low FVE score (~ 0.60) (Figure S12(a)). Additionally, we have plotted the FES using the first two components of the latent space (Figure S12(b)). This plot indicates a lack of distinct minima in the free energy surface. Consequently, clustering the data for a proper state decomposition within this latent space is not feasible. Therefore,

for α-Synuclein, we have opted to use the radius of gyration (R_g) as the reaction coordinate to discretize the trajectory into a specific number of states.

We conducted simulations for 3-state, 4-state, and active worm-like polymer chains using our in-house scripts written in C++. To simulate passive polymer chains, we utilized the open-source Software GROMACS-2022.[51,52] Our Autoencoder model was trained using Python implementation of Tensorflow[53] and Keras[54] and the GPT model was built using PyTorch.[17]

Data and code availability

The manuscript contains all the data. The code and detailed documentation for training the Autoencoder and GPT model are available on GitHub at the following URL: https://github.com/palash892/gpt_state_generation

Acknowledgments

All the authors acknowledge Tata Institute of Fundamental Research Hyderabad, India for providing the support of computing resources. We acknowledge support of the Department of Atomic Energy, Government of India, under Project Identification No. RTI 4007. JM acknowledges Core Research grants provided by the Department of Science and Technology (DST) of India (CRG/2023/001426). We would like to thank D. E. Shaw Research for providing us with access to a long simulation trajectory of Trp-cage and monomeric α-Synuclein.

References

(1) Cho, K.; Van Merriënboer, B.; Gulcehre, C.; Bahdanau, D.; Bougares, F.; Schwenk, H.; Bengio, Y. Learning phrase representations using RNN encoder-decoder for statistical

machine translation. *arXiv preprint arXiv:1406.1078* **2014**,

(2) Sundermeyer, M.; Schlüter, R.; Ney, H. Lstm neural networks for language modeling. Interspeech. 2012; pp 194–197.

(3) Lukoševičius, M.; Jaeger, H. Reservoir computing approaches to recurrent neural network training. *Computer science review* **2009**, *3*, 127–149.

(4) Schuster, M.; Paliwal, K. K. Bidirectional recurrent neural networks. *IEEE transactions on Signal Processing* **1997**, *45*, 2673–2681.

(5) Sutskever, I.; Martens, J.; Hinton, G. E. Generating text with recurrent neural networks. Proceedings of the 28th international conference on machine learning (ICML-11). 2011; pp 1017–1024.

(6) Lipton, Z. C.; Berkowitz, J.; Elkan, C. A critical review of recurrent neural networks for sequence learning. *arXiv preprint arXiv:1506.00019* **2015**,

(7) Vaswani, A.; Shazeer, N.; Parmar, N.; Uszkoreit, J.; Jones, L.; Gomez, A. N.; Kaiser, Ł.; Polosukhin, I. Attention is all you need. *Advances in neural information processing systems* **2017**, *30*.

(8) Shi, X.; Chen, Z.; Wang, H.; Yeung, D.-Y.; Wong, W.-K.; Woo, W.-c. Convolutional LSTM network: A machine learning approach for precipitation nowcasting. *Advances in neural information processing systems* **2015**, *28*.

(9) Chen, K.; Zhou, Y.; Dai, F. A LSTM-based method for stock returns prediction: A case study of China stock market. 2015 IEEE international conference on big data (big data). 2015; pp 2823–2824.

(10) Chollet, F. *Deep learning with Python*; Simon and Schuster, 2021.

(11) Qing, X.; Niu, Y. Hourly day-ahead solar irradiance prediction using weather forecasts by LSTM. *Energy* **2018**, *148*, 461–468.

(12) Hochreiter, S.; Bengio, Y.; Frasconi, P.; Schmidhuber, J., et al. Gradient flow in recurrent nets: the difficulty of learning long-term dependencies. 2001.

(13) Hochreiter, S.; Schmidhuber, J. Long short-term memory. *Neural computation* **1997**, *9*, 1735–1780.

(14) Singh, S. P.; Kumar, A.; Darbari, H.; Singh, L.; Rastogi, A.; Jain, S. Machine translation using deep learning: An overview. 2017 international conference on computer, communications and electronics (comptelix). 2017; pp 162–167.

(15) Graves, A.; Jaitly, N.; Mohamed, A.-r. Hybrid speech recognition with deep bidirectional LSTM. 2013 IEEE workshop on automatic speech recognition and understanding. 2013; pp 273–278.

(16) Tsai, S.-T.; Kuo, E.-J.; Tiwary, P. Learning molecular dynamics with simple language model built upon long short-term memory neural network. *Nature communications* **2020**, *11*, 5115.

(17) Paszke, A.; Gross, S.; Massa, F.; Lerer, A.; Bradbury, J.; Chanan, G.; Killeen, T.; Lin, Z.; Gimelshein, N.; Antiga, L., et al. Pytorch: An imperative style, high-performance deep learning library. *Advances in neural information processing systems* **2019**, *32*.

(18) Robustelli, P.; Piana, S.; Shaw, D. E. Developing a molecular dynamics force field for both folded and disordered protein states. *Proceedings of the National Academy of Sciences* **2018**, *115*, E4758–E4766.

(19) Shaw, D. E.; Dror, R. O.; Salmon, J. K.; Grossman, J.; Mackenzie, K. M.; Bank, J. A.; Young, C.; Deneroff, M. M.; Batson, B.; Bowers, K. J., et al. Millisecond-scale molecular dynamics simulations on Anton. Proceedings of the conference on high performance computing networking, storage and analysis. 2009; pp 1–11.

(20) Zhai, J.; Zhang, S.; Chen, J.; He, Q. Autoencoder and its various variants. 2018 IEEE international conference on systems, man, and cybernetics (SMC). 2018; pp 415–419.

(21) Liou, C.-Y.; Cheng, W.-C.; Liou, J.-W.; Liou, D.-R. Autoencoder for words. *Neurocomputing* **2014**, *139*, 84–96.

(22) Maroteaux, L.; Campanelli, J. T.; Scheller, R. H. Synuclein: a neuron-specific protein localized to the nucleus and presynaptic nerve terminal. *Journal of Neuroscience* **1988**, *8*, 2804–2815.

(23) Vekrellis, K.; Rideout, H. J.; Stefanis, L. Neurobiology of α-synuclein. *Molecular neurobiology* **2004**, *30*, 1–21.

(24) Spillantini, M. G.; Schmidt, M. L.; Lee, V. M.-Y.; Trojanowski, J. Q.; Jakes, R.; Goedert, M. α-Synuclein in Lewy bodies. *Nature* **1997**, *388*, 839–840.

(25) Breydo, L.; Wu, J. W.; Uversky, V. N. α-Synuclein misfolding and Parkinson's disease. *Biochimica et Biophysica Acta (BBA)-Molecular Basis of Disease* **2012**, *1822*, 261–285.

(26) Kahle, P. J.; Haass, C.; Kretzschmar, H. A.; Neumann, M. Structure/function of α-synuclein in health and disease: rational development of animal models for Parkinson's and related diseases. *Journal of neurochemistry* **2002**, *82*.

(27) Menon, S.; Mondal, J. Conformational plasticity in α-synuclein and how crowded environment modulates it. *The Journal of Physical Chemistry B* **2023**, *127*, 4032–4049.

(28) Farrell, F.; Marchetti, M.; Marenduzzo, D.; Tailleur, J. Pattern formation in self-propelled particles with density-dependent motility. *Physical review letters* **2012**, *108*, 248101.

(29) Tyson, R.; Lubkin, S.; Murray, J. D. A minimal mechanism for bacterial pattern formation. *Proceedings of the Royal Society of London. Series B: Biological Sciences* **1999**, *266*, 299–304.

(30) Ben-Jacob, E.; Cohen, I.; Levine, H. Cooperative self-organization of microorganisms. *Advances in Physics* **2000**, *49*, 395–554.

(31) Cates, M. E.; Tailleur, J. Motility-induced phase separation. *Annu. Rev. Condens. Matter Phys.* **2015**, *6*, 219–244.

(32) Fily, Y.; Marchetti, M. C. Athermal phase separation of self-propelled particles with no alignment. *Physical review letters* **2012**, *108*, 235702.

(33) Buttinoni, I.; Bialké, J.; Kümmel, F.; Löwen, H.; Bechinger, C.; Speck, T. Dynamical clustering and phase separation in suspensions of self-propelled colloidal particles. *Physical review letters* **2013**, *110*, 238301.

(34) Ariel, G.; Rabani, A.; Benisty, S.; Partridge, J. D.; Harshey, R. M.; Be'Er, A. Swarming bacteria migrate by Lévy Walk. *Nature communications* **2015**, *6*, 8396.

(35) Ilkanaiv, B.; Kearns, D. B.; Ariel, G.; Be'er, A. Effect of cell aspect ratio on swarming bacteria. *Physical review letters* **2017**, *118*, 158002.

(36) Be'er, A.; Ilkanaiv, B.; Gross, R.; Kearns, D. B.; Heidenreich, S.; Bär, M.; Ariel, G. A phase diagram for bacterial swarming. *Communications Physics* **2020**, *3*, 66.

(37) Bera, P.; Wasim, A.; Mondal, J.; Ghosh, P. Mechanistic underpinning of cell aspect ratio-dependent emergent collective motions in swarming bacteria. *Soft matter* **2021**, *17*, 7322–7331.

(38) Isele-Holder, R. E.; Elgeti, J.; Gompper, G. Self-propelled worm-like filaments: spontaneous spiral formation, structure, and dynamics. *Soft matter* **2015**, *11*, 7181–7190.

(39) Kingma, D. P.; Welling, M. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114* **2013**,

(40) Kingma, D. P.; Welling, M., et al. An introduction to variational autoencoders. *Foundations and Trends® in Machine Learning* **2019**, *12*, 307–392.

(41) Doersch, C. Tutorial on variational autoencoders. *arXiv preprint arXiv:1606.05908* **2016**,

(42) Goodfellow, I.; Pouget-Abadie, J.; Mirza, M.; Xu, B.; Warde-Farley, D.; Ozair, S.; Courville, A.; Bengio, Y. Generative adversarial nets. *Advances in neural information processing systems* **2014**, *27*.

(43) Brock, A.; Donahue, J.; Simonyan, K. Large scale GAN training for high fidelity natural image synthesis. *arXiv preprint arXiv:1809.11096* **2018**,

(44) Sohl-Dickstein, J.; Weiss, E.; Maheswaranathan, N.; Ganguli, S. Deep unsupervised learning using nonequilibrium thermodynamics. International conference on machine learning. 2015; pp 2256–2265.

(45) Ho, J.; Jain, A.; Abbeel, P. Denoising diffusion probabilistic models. *Advances in neural information processing systems* **2020**, *33*, 6840–6851.

(46) Sidky, H.; Chen, W.; Ferguson, A. L. Molecular latent space simulators. *Chemical Science* **2020**, *11*, 9459–9467.

(47) Wang, Y.; Herron, L.; Tiwary, P. From data to noise to data for mixing physics across temperatures with generative artificial intelligence. *Proceedings of the National Academy of Sciences* **2022**, *119*, e2203656119.

(48) Mehdi, S.; Smith, Z.; Herron, L.; Zou, Z.; Tiwary, P. Enhanced Sampling with Machine Learning. *Annual Review of Physical Chemistry* **2024**, *75*.

(49) Mukherjee, M.; Mondal, J. Osmolyte-Induced collapse of a charged macromolecule. *The Journal of Physical Chemistry B* **2019**, *123*, 4636–4644.

(50) Bandyopadhyay, S.; Mondal, J. A deep autoencoder framework for discovery of metastable ensembles in biomacromolecules. *The Journal of Chemical Physics* **2021**, *155*.

(51) Abraham, M. J.; Murtola, T.; Schulz, R.; Páll, S.; Smith, J. C.; Hess, B.; Lindahl, E. GROMACS: High performance molecular simulations through multi-level parallelism from laptops to supercomputers. *SoftwareX* **2015**, *1*, 19–25.

(52) Van Der Spoel, D.; Lindahl, E.; Hess, B.; Groenhof, G.; Mark, A. E.; Berendsen, H. J. GROMACS: fast, flexible, and free. *Journal of computational chemistry* **2005**, *26*, 1701–1718.

(53) Abadi, M.; Agarwal, A.; Barham, P.; Brevdo, E.; Chen, Z.; Citro, C.; Corrado, G. S.; Davis, A.; Dean, J.; Devin, M., et al. Tensorflow: Large-scale machine learning on heterogeneous distributed systems. *arXiv preprint arXiv:1603.04467* **2016**,

(54) Bisong, E.; Bisong, E. Tensorflow 2.0 and keras. *Building Machine Learning and Deep Learning Models on Google Cloud Platform: A Comprehensive Guide for Beginners* **2019**, 347–399.