diaTracer enables spectrum-centric analysis of diaPASEF proteomics data

Kai Li[1], Guo Ci Teo[2], Kevin L. Yang[1], Fengchao Yu[2*], Alexey I. Nesvizhskii[1,2*]

1. Department of Computational Medicine and Bioinformatics, University of Michigan, Ann Arbor, MI, USA.

2. Department of Pathology, University of Michigan, Ann Arbor, MI, USA.

*Corresponding Authors: yufe@umich.edu, nesvi@med.umich.edu

Abstract

Data-independent acquisition (DIA) has become a widely used strategy for peptide and protein quantification in mass spectrometry-based proteomics studies. The integration of ion mobility separation into DIA analysis, such as the diaPASEF technology available on Bruker's timsTOF platform, further improves the quantification accuracy and protein depth achievable using DIA. We introduce diaTracer, a new spectrum-centric computational tool optimized for diaPASEF data. diaTracer performs three-dimensional (m/z, retention time, ion mobility) peak tracing and feature detection to generate precursor-resolved "pseudo-MS/MS" spectra, facilitating direct ("spectral-library free") peptide identification and quantification from diaPASEF data. diaTracer is available as a stand-alone tool and is fully integrated into the widely used FragPipe computational platform. We demonstrate the performance of diaTracer and FragPipe using diaPASEF data from cerebrospinal fluid (CSF) and plasma samples, data from phosphoproteomics and HLA immunopeptidomics experiments, and low-input data from a spatial proteomics study. We also show that diaTracer enables unrestricted identification of post-translational modifications from diaPASEF data using open/mass offset searches.

Introduction

Liquid chromatography-mass spectrometry (LC-MS) is a commonly used method to analyze proteomics data[1]. There are two primary approaches for acquiring high-throughput data: data-dependent acquisition (DDA) and data-independent acquisition (DIA). DDA isolates and fragments each peptide ion individually to produce a tandem mass spectrum (MS/MS) that contains information on the peptide sequence. In contrast, DIA isolates and fragments multiple peptide ions within specific mass and retention time ranges, resulting in more complex spectra[2-4]. As mass spectrometers have become faster and more sensitive over the years, the popularity of DIA has increased. Furthermore, the use of ion mobility (IM) separation, in addition to liquid chromatography, to further separate peptides and reduce co-elution[5] has made DIA an even more attractive strategy. The Bruker timsTOF mass spectrometer platform, which couples trapped ion mobility separation with the parallel accumulation serial fragmentation (PASEF)[6] technique and supports both DDA (ddaPASEF) and DIA (diaPASEF) modes, has proven to offer excellent performance for a wide range of quantitative proteomics applications.

Although ion mobility separation helps resolve co-eluted peptides, it presents new challenges for computational analyses. Most peptide identification and quantification tools were not initially designed to support additional ion mobility dimensions. We have proposed an efficient solution[7,8] for analyzing timsTOF data in DDA mode, but there are still open questions regarding the analysis of diaPASEF data generated by timsTOF. The first critical step in any DIA workflow is the creation of a so-called "spectral library" containing a list of peptide ions to be quantified in the acquired DIA data. For each target peptide ion, the library contains its separation coordinates (LC retention time and ion mobility value) and an empirical or predicted fragmentation spectrum (fragment m/z values and intensities) that are used to locate and quantify the peptide ion signal in each of the acquired DIA runs. A spectral library can be built using DDA data acquired from the same or similar samples, often using additional fractionation steps to increase the proteome depth. This remains an effective strategy for building spectral libraries, including for diaPASEF data analysis[9], however, additional efforts are required to acquire DDA data for building the library.

An alternative computational strategy, first proposed by us and implemented in the DIA-Umpire algorithm[10], is to identify peptides from DIA data directly and then use these identifications to build a spectral library for the subsequent targeted protein quantification step. Known as direct

DIA or "library-free" strategy (contrasting with the requirement of having a DDA-based library in some DIA analysis tools[11, 12]), it has now become the main mode of analysis of DIA data in a typical shotgun proteomics experiment. Direct identification of peptides from DIA data can be performed using either the spectrum-centric approach of DIA-Umpire[10, 13] (also adopted by Spectronaut[14]), which starts with the detection of extracted ion chromatogram (XIC) features to generate DDA-like pseudo-MS/MS spectra[10] that are compatible with conventional search engines such as MSFragger. Alternatively, direct identification can be performed using a peptide-centric data analysis strategy[15-17], including the library-free mode of DIA-NN[9, 18]. Furthermore, MSFragger-DIA[19] implements a hybrid strategy in which full DIA MS/MS scans are searched against a protein sequence database[19, 20], followed by targeted precursor and fragment peak tracing and rescoring of the top peptide candidates for each MS/MS scan[19]. Both spectrum-centric and peptide-centric strategies take advantage of deep-leaning-based predictions[21, 22] of peptide spectra and separation coordinates (LC and IM), but with significant differences in the use of prediction models. In the fully spectrum-centric approach and in the hybrid MSFragger-DIA strategy, predictions of peptide properties are performed only for a restricted set of top scoring peptides identified from the data[19, 21], whereas peptide-centric methods such as DIA-NN require *in-silico* predictions for all possible candidate peptides given the user-specific protein sequence database and search parameters. One important advantage of the spectrum-centric DIA-Umpire strategy of deconvoluting full DIA MS/MS spectra into pseudo-MS/MS spectra is that it facilitates analysis if data in experiments that require a very large search space. These include studies focusing on post-translational modifications (PTMs), studies requiring nonspecific (e.g., HLA or endogenous peptidomics) or semi-enzymatic (e.g., N-terminomic) searches, or when spectra and/or retention times of chemically labelled peptides cannot be accurately predicted (e.g., in chemoproteomics). However, although successful and frequently used for the analysis of DIA data from the Thermo Fisher Scientific Orbitrap and Sciex tripleTOF mass spectrometry platforms, neither DIA-Umpire nor MSFragger-DIA are capable of processing diaPASEF data because of the challenges of detecting XIC features with the additional ion mobility dimension. Although Spectronaut supports direct identification from diaPASEF data to the best of our knowledge, the details of the algorithm have not been publicly disclosed.

To address the need for an efficient and versatile method for analyzing diaPASEF data, we developed a new spectrum-centric tool called diaTracer. diaTracer has been designed to perform highly efficient processing of three-dimensional (m/z, retention time, ion mobility)

information encoded in diaPASEF data to detect precursor and fragment ion features, followed by the generation of pseudo-MS/MS spectra that can be easily analyzed with peptide identification tools such as MSFragger[23]. diaTracer was fully integrated into the widely used FragPipe computational platform. We demonstrate the performance of diaTracer using diaPASEF data from cerebrospinal fluid (CSF) and plasma proteome datasets, using data from phosphoproteomics and immunopeptidomics experiments, and low-input data from a spatial proteomics study. We also show that our strategy enables unrestricted PTM searches via the application of the open/mass offset mode of MSFragger to diaTracer-extracted files. Overall, our study demonstrates that diaTracer and FragPipe computational platform enable fast and sensitive analysis of diaPASEF data from a wide range of biological applications.

Results

diaTracer workflow in FragPipe

diaTracer takes diaPASEF data (as input d files) and generates pseudo-MS/MS spectra[24] (in mzML format) for DDA-like database searching. It employs a three-dimensional feature detection method that leverages retention time and ion mobility dimensions to enhance signals and reduce noise interference. In our previous study[25], we demonstrated that summing scans with closed ion mobilities contributed to the accurate identification of the correct XIC features. Therefore, diaTracer starts with the aggregation of neighboring scans, followed by a two-dimensional (m/z-1/K0) adaptive Gaussian feature detection algorithm for the merged scans. The same approach is used to detect all precursor and fragment XIC features. Ion mobility and m/z values of the signals are determined using the apex scans. An isotope grouping method filters precursor signals and identifies potential charge states in the MS1 data. diaTracer then calculates the Pearson correlation coefficient of the XIC features between all detected precursors and fragments within user-defined ion mobility and retention time tolerance to assemble pseudo-MS/MS spectra (see **Methods**).

diaTracer was fully integrated into FragPipe for streamlined, direct analysis of diaPASEF data (**Figure 1**). FragPipe (https://fragpipe.nesvilab.org) is a comprehensive computational platform that automates all the data analysis steps. The pseudo-MS/MS spectra extracted by diaTracer are searched using MSFragger[26] in the DDA mode, enabling tryptic, semi-tryptic, nonspecific,

mass-offset, or even open database searches. Peptide-spectrum matching (PSM) with MSFragger[23, 27] is followed by deep learning-based rescoring of PSMs using MSBooster[21] and Percolator[28] (default option; alternatively, using PeptideProphet[29]), protein inference with ProteinProphet[30], and FDR filtering (by default 1% FDR at the PSM, ion, peptide, and protein levels) using Philosopher[31]. PTMProphet[32] is enabled for PTM workflows that require site localization (e.g., phosphoproteomics). The spectral library is generated using EasyPQP, followed by the extraction of quantification from the DIA data using DIA-NN[9, 18] (alternatively, using Skyline[33]). Furthermore, a hybrid spectral library[10, 19] can also be generated from both diaPASEF data and additional ddaPASEF data when available. Users have a choice to run FragPipe using an easy-to-use graphical user interface (GUI) or a command line version of the pipeline that is fully compatible with high-performance computing or cloud-based environments. A data visualization module, FragPipe-PDV (an extension of the PDV viewer[34]), is integrated into FragPipe and provides a convenient way to view pseudo-MS/MS spectra and peptide-to-spectrum matches. Quantitative matrices (with quantification extracted by DIA-NN) can be conveniently analyzed using FragPipe-Analyst[35] or MSStats[36].

Performance evaluation: CSF data

We first assessed the performance of diaTracer and FragPipe using the cerebrospinal fluid (CSF) dataset from Mun et al.[37]. This dataset contained 24 ddaPASEF and 34 diaPASEF runs. We performed quantification of 34 diaPASEF samples using the following three FragPipe workflows: 1) Using the library built from 24 ddaPASEF fractionated runs (abbreviated 'FP-DDALib'). 2) Using the library built from the 34 diaPASEF runs with the help of diaTracer ('FP-diaTracer'). 3) Using the hybrid library obtained by combining 24 ddaPASEF fractionated runs and 34 diaPASEF runs ('FP-diaTracer hybrid'). We also used the standalone DIA-NN tool in the library-free module ('DIA-NN lib-free'). Additionally, we used the diaTracer-extracted files to conduct semi-tryptic and comprehensive PTM searches (using the mass offset mode of MSFragger). We did not attempt to perform semi-tryptic searches using the DIA-NN library-free mode.

Using the FragPipe-diaTracer workflow (tryptic search), using the 34 diaPASEF files only, we quantified an average of 951 proteins per file, with 1,019 proteins in total (**Figure 2a**; **Supplementary Figure 1a**). In comparison, DIA-NN library-free analysis identified fewer proteins per file, with 844 proteins on average, despite reporting a higher total number of

proteins (**Supplementary Figure 1a**). The number of proteins quantified per file using the DDA-based library was 23% (222 proteins) higher than that obtained from the direct analysis of the diaPASEF data. Using both ddaPASEF and diaPASEF data (i.e., building the hybrid library) yielded the best results, with an 18% increase (205 proteins) in the average number of quantified proteins per file compared with using the DDA-based library. This also resulted in the highest total number of proteins (**Supplementary Figure 1a)** and precursors (**Supplementary Figure 1b)** across the four workflows**.** Interestingly, the average number of quantified precursors per file in the direct DIA analysis with diaTracer was 14% (1,217 precursors) higher than that using the DDA-based library (**Figure 2b**).

The semi-tryptic search of these data did not result in a significant change in the average number of quantified proteins per file (**Figure 1a**) and a minor increase (e.g., 87 in the case of direct DIA analysis) in the total number of proteins (**Supplementary Figure 1a)**. However, this resulted in a noticeable increase in the number of quantified precursors (39% on average per file) compared to the tryptic search (e.g., 9,771 and 13,997 precursors per file, on average, in tryptic and semi-tryptic searches for the direct diaPASEF analysis workflow, respectively). A deeper investigation into the nature of the additional peptides identified in the semi-tryptic search revealed that many of them were derived from immunoglobulin proteins and secreted proteins (**Supplementary Table 1**). For 158 proteins, we found semi-tryptic peptides mapping to the region immediately following the signal peptides in the N-terminal portion of the corresponding protein (**Supplementary Table 2**). **Figure 2c** shows an example of protein hemopexin (HPX), in which the removal of the signal peptide in the mature form of the protein creates a peptide that does not conform to the trypsin cleavage rules. Multiple additional semi-tryptic peptides were identified for this and other proteins (**Figure 2c**). Overall, this confirms the presence of proteolytic cleavage events expected in CSF (and plasma, see below) samples and highlights the importance of monitoring such events using our diaTracer-enabled direct diaPASEF analysis workflow.

We also benchmarked the running time of diaTracer and the rest of the FragPipe workflow **(Figure 2d)**. diaTracer required 661 min to generate pseudo-MS/MS spectra (19.4 min per diaPASEF file, on average), and the rest of FragPipe (tryptic search) required 87 minutes to complete the analysis (including running DIA-NN for quantification). In contrast, the DIA-NN library-free analysis took 1,496 min, more than twice the time of the diaTracer workflow.

Importantly, repeating FragPipe analysis (starting with the existing pseudo-MS/MS mzML files) using semi-tryptic search required only an additional 110 min.

We also tested the possibility of performing mass-offset searches using the FragPipe's "Mass-Offset-CommonPTMs" workflow and the same pseudo-MS/MS spectra from diaTracer. **Figure 2e** displays the most abundant PTMs identified in these data, as summarized by PTM-Shepherd[38]. The list of PTMs included common chemical artifacts, but also biological modifications such as phosphorylation. The analysis took 341 min (or 10 min per file), from MSFragger search to PTM-Shepherd reports. Similar mass shift histogram was observed in the open search, albeit at a 2x longer computational analysis time. These analyses demonstrate the feasibility of comprehensive PTM searches using diaPASEF data.

Plasma proteomics

Another evaluation was conducted using the plasma dataset from Vitko et al[39]. In the original study, the authors performed a plasma profiling workflow using Seer's Proteograph Assay Kit, which includes five distinct nanoparticles (NP1-5). We selected 40 diaPASEF runs of NP2 enriched plasma samples analyzed with a 60SPD gradient on a timsTOF HT mass spectrometer. Pseudo-MS/MS spectra were generated from these 40 diaPASEF runs using diaTracer, and the rest of the analysis was completed in FragPipe using MSFragger tryptic and semi-tryptic search settings. The data were also analyzed using the DIA-NN library-free mode. With at least 50% non-missing value filtering (i.e., proteins must be quantified in at least 50% of the runs) and performing tryptic searches, the DIA-NN library-free analysis quantified 2,347 proteins, whereas diaTracer coupled with FragPipe quantified 2,922 proteins (**Figure 3a**). Similarly, although the DIA-NN library-free mode quantified most precursors across all runs in total, the diaTracer workflow in FragPipe resulted in 77% more precursors when requiring a precursor to be quantified in at least 50% of the runs. This demonstrates the improved ability of the diaTracer workflow in FragPipe to consistently quantify peptides across a large sample cohort.

Furthermore, as with the CSF dataset described above, performing a semi-tryptic search significantly increased the number of quantified precursors (but not proteins). Among the 40 samples in this plasma dataset, 20 were from patients with stage IV non-small cell lung cancer

(NSCLC) and 20 were from patients in the non-cancer control group. We applied FragPipe-Analyst[40] to conduct differential expression analysis between the NSCLC and control groups using both tryptic and semi-tryptic search results. We detected 69 more significantly differentially expressed proteins from the semi-tryptic results under the same filtering criteria (**Supplementary Table 3**). In the semi-tryptic results, 35 proteins were upregulated, and 140 proteins were downregulated (**Figure 3c**). **Figure 3d** shows two examples of proteins showing statistically significant upregulation in the NSCLC vs. control group with the semi-tryptic search, for which a non-significant difference was observed with the tryptic search. These two proteins, AKT2 and H2AX, have been previously reported to be associated with NSCLC[41, 42]. Overall, while in-depth interpretation of these examples goes beyond the scope of this work, our results highlight the importance of accounting for proteolytic cleavage events in the analysis of plasma data.

HLA immunopeptidomics

Applying peptide-centric strategies to the analysis of HLA or endogenous peptidome data is not practically feasible, given the time required to generate an *in-silico* predicted spectral library for all candidate database peptides under nonspecific protein cleavage rules. The diaTracer approach of extracting pseudo-MS/MS spectra offers a clear advantage for analyzing this type of data. We used an HLA dataset[43] to evaluate the performance of our method and compare it with the results reported in the original study using Spectronaut 17. We selected three replicates of an HLA peptidome sample purified from a healthy donor's plasma sample and analyzed using a Whisper40 gradient (31 min length) on a timsTOF Ultra instrument. Since the full Spectronaut results files were not available as part of the original publication, we compared with the number of quantified immunopeptides, as reported by the authors. As shown in **Figure 4a,** from the three replicates**,** we identified and quantified 2,840 immunopeptides, which was 25% more than the 2,130 peptides reported in the original publication.

To further evaluate our results, we used NetMHCPan-4.1[44] to predict the binding affinity of the identified immunopeptides with the donor's HLA allele information provided in the original study. We identified 2,328 (89%) strong and 132 (5%) weak binders from 2,619 immunopeptides of lengths 8–14 (**Figure 4b**). Most of these binders are derived from the HLA-A*24:02 allele, as reported in the original publication. We further summarized the length and charge state distributions of the quantified immunopeptides (**Figure 4c** and **d**). Most immunopeptides had a

length of nine and were observed as singly or doubly charged ions. This finding aligns well with the general expectations for HLA data and the specific findings reported for this dataset in the original study. We also selected one peptide to demonstrate the utility of our integrated FragPipe-PDV[34] viewer for inspecting PSMs and MS/MS spectra. The peptide VYQHLFTRI is predicted to be a strong binder. We visualized one of its PSMs along with the predicted spectrum generated by MSBooster[21] (**Figure 4e**). The pseudo-MS/MS spectrum extracted by diaTracer exhibited a high degree of similarity (spectrum entropy score of 0.9863) with the predicted spectrum, demonstrating the high quality of the pseudo-MS/MS spectra.

Phosphoproteomics

To evaluate the performance of our method in quantifying phosphorylated peptides, we applied our diaTracer-based direct diaPASEF workflow in FragPipe to a phosphorylation-enriched dataset acquired using six gradient lengths[45]. It took diaTracer, on average, 13.5 minutes to extract signals and produce pseudo-MS/MS spectra for a single 60-minute gradient file. For site localization, PTMProphet was enabled, and the site localization information was propagated from the PSM files to the final quantification matrices generated by DIA-NN. We identified 6844 and 11281 phosphopeptide sequences in the 7-minute and 60-minute gradient data, respectively (**Figure 5a**). In contrast to the original study, where the number of phosphorylated peptide sequences plateaued at a 21-minute gradient (**Supplementary Figure 2a**), we observed an increase in the number of quantified phosphorylated peptides with longer gradients. This trend also holds for class I phosphosites (sites with PTMProphet site localization probability > 0.75) (**Figure 5b; Supplementary Figure 2b**).

Although our pipeline computes site localization scores at the spectral library building stage, manual inspection of peptide elution profiles and site localizing fragments observed in a specific sample may be desired. In addition to the FragPipe-PDV viewer mentioned above, the output from FragPipe is fully compatible with the Skyline computational environment for advanced visualization of peptide precursors and fragment ion signals in diaPASEF data. We visualized the PSMs and XICs of two co-eluted isobaric positional isomers, S(pho)PSPPDGSPAATPEIR and SPSPPDGS(pho)PAATPEIR, quantified in a 60-minute gradient run. diaTracer successfully separated these two precursor signals along with their corresponding fragment signals into two separate pseudo-MS/MS scans. Both isomers were identified with a site probability > 0.75. They eluted approximately 35 s apart in retention time and were 0.02 1/K0 apart in the ion mobility

dimension (**Figures 5c-f**). Several fragment peaks that contributed to the localization of the phosphorylation site were clearly visible in the spectra.

Low-input, spatial proteomics data

We then investigated the performance of our method using low-input data from a recent spatial proteomics study[46]. The study profiled 148 microregions from four areas (Epithelium, Germinal center, Mantel zone, and T-cell zone) of a human tonsil obtained using laser capture microdissection (LCM). In the original study, the authors first used the DIA-NN library-free mode to generate a comprehensive human tonsil spectral library using 46 runs acquired in the diaPASEF mode from samples with a high protein amount (referred to as high-input samples below). The authors then applied this high-input spectral library to quantify proteins in the 148 low-input samples. The authors did not attempt to perform a direct analysis of the low-input samples, that is, without using the high-input spectral library. For comparison with the original study, we performed two analyses using the diaTracer workflow in FragPipe. In the first analysis, we used diaTracer and FragPipe to build the library from the 46 high-input samples ("FP-diaTracer high-input Lib"), similar to the original study that used DIA-NN. Second, we performed a direct analysis of the 148 low-input samples without using high-input data ("FP-diaTracer").

The results of our diaTracer-FragPipe workflow, with high-input data used for building the library, produced identification numbers very similar to those based on DIA-NN library-free analysis, using the reports taken from the original publication (**Figure 6a**; **Methods**). As expected, the high-input library resulted in more proteins, 3,342 in total (1,990 proteins per sample), compared to 1,595 proteins (1,301 proteins per sample) identified using direct analysis of low-input samples. However, the total number of identified proteins is a misleading metric; proteins detected in one or a few samples have little value for downstream analysis. Indeed, all analyses reported by the authors in the original paper were performed after the application of a missing value filter. More specifically, they required at least 70% non-missing values across all samples in at least one group (the four sample groups mentioned above). With this filter in place, the use of high-input data resulted in 2,170 proteins (1,690 per sample) compared with 1,471 proteins (1,262 per sample) quantified directly from low-input samples. Increasing the stringency of the missing value filter further diminishes the impact of using high-input data. Requiring 90% non-missing values, we identified 1,649 (1,397 per sample) and 1,333 proteins (1,180 per sample) with and without using high-input samples alone, respectively.

Figure 6b displays the overlap between proteins quantified with at least 70% non-missing values in at least one class in the original study and using FragPipe with diaTracer with and without high-input sample data. All of these approaches exhibited a high degree of overlap. Overall, the biological observations were consistent across all analyses. We specifically investigated whether similar results could be obtained with direct identification from low-input samples, despite quantifying fewer proteins compared to using a larger high-input library. Following the same data filtering procedure as in the original study, the quantified proteins clearly separated into four distinct cell types (**Figure 6c**). We also examined cell type markers reported in the original study, including CD19 (B-cell marker), CD3D (T-cell marker), and CDH1 (epithelial marker), which were all highly expressed in the anticipated sample groups (**Figure 6d**). Furthermore, a global comparison between Mantel zone and T cells revealed significant proteomic differences (**Figure 6e**). The list of differentially expressed proteins derived from the results with and without using high-input data, when submitted to FragPipe-Analyst, produced a similar list of enriched pathways (**Supplementary Figure 3**). Overall, our analysis demonstrates that FragPipe with diaTracer can be effectively used to identify and quantify proteins from a large cohort of low-input diaPASEF samples, even in the absence of high-input data (although having such data is beneficial), especially if focusing on a subset of proteins consistently identified across a large fraction of the samples in the cohort.

Discussion

We presented a new computational method and software, diaTracer, which can deconvolute diaPASEF data to produce DDA-like pseudo-MS/MS spectra. These pseudo-MS/MS spectra can be searched using conventional DDA peptide identification tools, such as MSFragger. diaTracer is available as a stand-alone tool and is integrated into FragPipe, enabling a complete diaPASEF data analysis workflow, including peptide identification, deep-learning-based rescoring, protein inference, FDR filtering, PTM site localization, spectral library generation, quantification, and data visualization. We used several datasets from different types of biological studies to demonstrate the speed and high sensitivity of our new computational strategy for analyzing diaPASEF data.

diaTracer enables direct, spectrum-centric analysis of diaPASEF data, which is more versatile than the peptide-centric approach. Advances in deep learning methods have enabled the creation of tools that can predict fragment intensities, ion mobilities, and retention times of peptides with high accuracy, thereby facilitating the generation of *in-silico* spectral libraries. However, current deep learning prediction tools have limitations. Peptide-centric strategies coupled with *in-silico* library prediction work well for conventional experiments involving quantitative protein profiling of cell lines and tissues. In contrast, their application to endogenous peptidome or immunopeptide data is generally not feasible because of the large number of peptide candidates that require predictions. Even semi-tryptic searches that are often beneficial (e.g., CSF and plasma samples) or required (N-terminomics[47, 48]) are challenging. Furthermore, peptide-centric analyses struggle with searches involving more than a few common PTMs. Even for phosphorylation, a PTM that receives a great deal of attention, the peptide-centric approach can be computationally prohibitive. Furthermore, for peptides harboring less common PTMs or chemical labels that are not included in the training set used to build prediction models there is an additional risk of poor prediction accuracy.

In contrast, the spectrum-centric approach of DIA-Umpire, and now diaTracer for diaPASEF data, does not have these limitations. After diaTracer generates pseudo-MS/MS spectra, well-established DDA peptide identification tools can be used to perform semi-enzymatic or nonspecific searches. We demonstrated that the semi-enzymatic search provides a significant boost in the number of quantified precursors and improves the accuracy of quantification in the analysis of CSF and plasma datasets. We also illustrated the high sensitivity and accuracy of our strategy in the analysis of HLA immunopeptidome data. We note that spectrum-centric strategies still benefit from deep-learning predictions and rescoring; however, predictions need to be made only after the search of pseudo-MS/MS spectra and for a relatively small number of peptides. The accuracy of the predictions is also less critical (e.g., a very inaccurate retention time prediction would not automatically exclude the peptide from being identified), making the pipeline more robust for peptides harboring less common PTMs or chemical labels. Thus, we hope that our strategy will be especially useful for chemoproteomics applications involving different types of chemical labels, such as affinity-based proteome profiling (ABPP) workflows[49, 50]. Finally, the spectrum-centric approach enables unrestricted PTM analysis via open or mass-offset searches of pseudo-MS/MS spectra, which is currently not possible using the peptide-centric approach.

The computational time required for processing diaPASEF data is an important consideration. In our tests of diaTracer and FragPipe, the analysis time was less than the time it took to acquire the mass spectrometry data. Furthermore, the conversion of diaPASEF raw files to pseudo-MS/MS spectra can start with the already acquired files while the data acquisition is still ongoing. Finally, the conversion needs to be performed only once. The resulting deconvoluted files can be used in multiple ways, for example, searched using different search parameters, or using different search engines or their combination, all without the need to reprocess the files.

In this study, we focused on the conventional diaPASEF data. At the same time, the rapid technological development of the timsTOF platform led to the introduction of several related data acquisition methods, including Synchro-PASEF[51], Slice-PASEF[52], and midiaPASEF[53]. These techniques aim to increase the efficiency of signal detection by redesigning the schema of the quadrupole selection windows. These new methods better preserve the relationships between the precursor peptide and its fragments, facilitating downstream data analysis. The spectrum-centric approach of diaTracer is well-suited for analyzing data from these new acquisition methods. We plan to extend diaTracer to support these new data types in the future.

Methods

diaTracer algorithm

In a single scan, the data are stored as sparse matrices sized at $N \times W$, where W is the number of ion mobility (IM) bins determined by the IM window width and resolution. N is the number of m/z bins, which is determined by the isolation window width and mass resolution. To enhance the signal and reduce noise interference[25], data from adjacent neighbor scans are aggregated to form a composite 3D matrix, subsequently removing the data points lacking proximate neighbors. A 2D Gaussian filter is then employed to smoothen the composite 3D matrix data. Local maxima are identified within the composite 3D matrix and used as seeds for Gaussian fitting to find the 2D peaks. The center of the 2D Gaussian peak determines the m/z and IM values of the corresponding feature.

In diaTracer, several attributes are defined for each extracted signal, including the m/z and IM centers, as well as the m/z and IM signal ranges. Subsequently, these attributes are partially initialized based on the 2D Gaussian distribution. The sum of the intensities within the signal range represents the peak intensity of the current scan. While traversing through the scans

along the retention time, the algorithm determines the apex scan for every signal. Upon locating the apex scan, its signal attributes are finalized, and the intensities from the other scans are adjusted relative to it. Signal boundaries are determined based on certain predefined criteria to ensure a bell-shaped extracted ion chromatogram (XIC). However, if a defined endpoint of the peak is missed, an extended signal is recorded. diaTracer then executes Savitzky-Golay smoothing and applies a Z-Score[54] peak detection algorithm to segment an elongated peak into multiple separated peaks.

To separate authentic signals from background noise and assign charge states to precursors, diaTracer employs an isotope peak-grouping technique for the MS1 data. The traced MS1 peaks are organized into isotopic clusters based on retention time (RT) and IM tolerances. Peaks that do not belong to any cluster ae discarded. To minimize redundancy, highly confident peaks are removed from subsequent isotopic clustering. The charge state is determined by comparing against the theoretical isotopic distribution. When the charge state cannot be confidently determined, multiple values are retained. The extraction of MS2 peaks follows a similar process but with more relaxed constraints, including reduced neighbor requirements and no isotopic clustering.

After detecting precursor and fragment XIC features, they are grouped into clusters. An optional mass defect filter ("Mass Defect Filter" parameter) can be employed to reduce the number of peaks before clustering without any impact on the outcomes of most conventional searches[13] (the mass defect filter is not recommended for certain PTM searches, such as phosphopeptide searches, or nonspecific digest searches). Clustering begins with the precursor peaks, considering all fragment peaks that met the IM and RT tolerances within the same isolation window ("Delta Apex IM" and "Delta Apex RT" parameters). Subsequently, the Pearson correlation coefficient is calculated between the smoothed XIC of the monoisotopic precursor and raw XICs of the fragments. Only fragment peaks that surpass the correlation threshold ("Corr threshold" parameter) are included in the construction of the pseudo-spectrum. The intensity values in the pseudo-MS/MS spectrum are derived from the peak intensities of the fragment XICs. All produced pseudo-MS/MS spectra are used to generate an mzML file, which can be processed by MSFragger in FragPipe or any other search engine.

Cerebrospinal fluid data analysis

The cerebrospinal fluid (CSF) dataset from Mun et al.[37] contains 24 ddaPASEF runs used to generate a DDA-based library and 34 diaPASEF runs from 15 patients with Alzheimer's disease (AD) and 19 control subjects. We ran FragPipe 22 (pre-release version) with the "SpecLib_Quant_diaPASEF" workflow to generate a spectral library and perform quantification for the raw .d files. Within diaTracer, "Delta Apex IM" was set to 0.01, "Delta Apex RT" was set to 3, "RF max" was set to 500, and "Corr threshold" was set to 0.3. The mass defect filter was disabled. In the MSFragger database search, the initial precursor and fragment mass tolerances were set to 10 ppm and 20 ppm, respectively. Spectrum deisotoping[55], mass calibration, and parameter optimization[27] were enabled. The isotope error was set to "0/1/2". The reviewed *Homo sapiens* protein sequence database obtained from UniProt (downloaded on November 15, 2023; 20,461 proteins), appended with common contaminants and decoys, was used in the search. Enzyme specificity was set to "stricttrypsin" and the maximum allowed missed cleavages were set to 2. For semi-tryptic searches, the cleavage parameter was adjusted to "SEMI". The peptide length was set from 7 to 50 with a peptide mass range of 500 to 5,000 Da. Oxidation of methionine and N-terminal acetylation were set as variable modifications. Carbamidomethylation of cysteine was used as a fixed modification. The maximum number of variable modifications for each peptide was set to 3. MSBooster and Percolator were used to predict the RT and MS/MS spectra, and to rescore PSMs. The final FDR-filtered PSMs and the pseudo-MS/MS mzML spectral files were used by EasyPQP to generate the spectral library. The spectral library was then used with the DIA-NN quantification module to quantify the library peptide ions in the individual patient diaPASEF data. The same settings were employed for all experiments, unless mentioned otherwise. For comparison, DIA-NN (version 1.8.1) standalone tool was run in the library-free mode using default settings. The precursor m/z range was set 300 to 1800. Methionine oxidation was set as a variable modification. Carbamidomethylation of cysteine was used as a fixed modification. A maximum of 1 missed cleavage was allowed. An *in-silico* predicted spectral library was generated from the same database file as described above except without adding decoys. DIA-NN generated report.tsv files (from the FragPipe-diaTracer workflow or DIA-NN library-free analysis) were processed using the *iq* R package[56] to count the number of peptides and proteins identified passing the specified confidence thresholds (see **Result processing and statistical analysis).** To conduct a comprehensive PTM search using the mass offset mode of MSFragger, FragPipe's "Mass-Offset-CommonPTMs" workflow was used under default settings.

Plasma data analysis

The subset of the plasma dataset from Vitko et al.[39] used in this study contained 40 files (20 patients with stage IV non-small cell lung cancer, NSCLC, and 20 control samples) acquired using the Seer Proteograph nanoparticle conjugation kit NP2 and a timsTOF HT mass spectrometer. Data was processed as described for the CSF dataset. Differential expression analysis was performed using FragPipe-Analyst[40]. When loading data in FragPipe-Analyst, the "data type" parameter was set to DIA, and both "report.pr_matrix.tsv" and "experiment_annotation.tsv" files were uploaded to the FragPipe-Analyst website. The "min percentage of non-missing values globally" and "Min percentage of non-missing values in at least one condition" parameters were set to 25%, with all other parameters at default values. "DE Adjusted p-value cutoff" was set to 0.05. "DE Log2 fold change cutoff" was set to 1. The imputation type was set to "Perseus-type". The FDR correction type was set to "Benjamini Hochberg". The DE_result.tsv file was downloaded and sued for downstream analysis.

HLA data analysis

We used a subset of the HLA dataset from Wahle et al.[43], using a sample from one donor profiled in triplicate. FragPipe with diaTracer was run using the built-in "nonspecific-HLA-diaPASEF" workflow. Compared to the "SpecLib_Quant_diaPASEF" workflow described above, the enzyme cleavage was set to "nonspecific" and the peptide length was restricted to 7 to 25. Carbamidomethylation of cysteine was not specified. Cysteinylation (+119) was added as a variable modification. The isotope error was set to 0/1. NetMHCpan 4.1[44] was used to predict the binding affinities of the identified peptides (considering peptides of length 8-12 only). Six MHC class I alleles of the donor were provided as additional input information. The immunopeptides were ranked according to their MHC-binding affinities expressed as a percentile rank. Immunopeptides with a percentage rank of less than 0.5% were classified as strong binders, whereas those with a percentage rank of less than 2% were considered weak binders. PDV[34], integrated into FragPipe, was used to visualize the PSMs. Both the predicted spectrum and spectral entropy scores were generated using MSBooster[21].

Phosphoproteome data analysis

The phosphopeptide enriched dataset from Oliinyk et al.[45] contained runs from six gradient lengths ranging from 7 to 60 min. Each gradient condition was replicated four times. To analyze the dataset using FragPipe with diaTracer, we employed the built-in "SpecLib_Quant_Phospho_diaPASEF" workflow. Compared to the "SpecLib_Quant_diaPASEF" workflow described above, Phosphorylation on STY was added as a variable modification in

MSFragger, and site localization with PTMProphet was enabled. FragPipe propagated the site localization information from the PSM.tsv files to the quantification files produced by DIA-NN (report.tsv and report_pr_matrix.tsv files). Phosphopeptide counts, representing the number of non-redundant sequences of all identified phosphopeptides, were obtained from FDR-filtered results. When counting the number of phosphorylation sites, sites with the PTMProphet localization probability greater than 0.75 were considered s localized. The PSMs for selected peptides were visualized using PDV, whereas XICs were visualized using Skyline[57].

Low-input, special proteomics data

We used the dataset from Anuar et al.[46], 148 microregions from a patient' tonsil sections. In addition, there were 42 diaPASEF runs (from seven different sizes of human tonsil tissue, six replicates each) that were used to build a comprehensive tonsil library. FragPipe with diaTracer results were compared to the DIA-NN results from the original study. Differential expression analysis was performed using FragPipe-Analyst based on "report.pr_matrix.tsv" and "experiment_annotation.tsv" files generated by FragPipe.

Result processing and statistical analysis

To ensure a fair comparison of peptide and protein identification numbers, DIA-NN report.tsv files from the diaTracer workflows in FragPipe and from DIA-NN stand-alone analyses were filtered using the *iq* R package[56] to achieve a 1% FDR at run-specific precursor, global precursor, and global protein levels. Differential expression analyses conducted using FragPipe-Analyst were based on DIA-NN's report_pg_matrix.tsv files. Subsequent result processing and plot generation were performed within the RStudio environment using the R statistical software. The R packages ggplot2, tidyverse, ggrepel, plotly, and eulerr were used in our analysis.

Runtime comparison

The runtimes for FragPipe with diaTracer and for the DIA-NN library-free mode analyses were measured on a Linux desktop with an Intel Core i9-13900K CPU (32 logical cores) and 128GB memory. All analyses were configured to utilize all 32 CPUs.

Acknowledgements

Abbreviations

CSF: cerebrospinal fluid; DIA: data-independent acquisition; DDA: data-dependent acquisition; FDR: False discovery rate; FP: FragPipe; GUI: graphical user interface; HLA: Human leukocyte antigens; IM: ion mobility; LC-MS: Liquid chromatography-mass spectrometry; MS/MS: tandem mass spectrum; NP: nanoparticles; NSCLC: non-small cell lung cancer; PASEF: parallel accumulation serial fragmentation; PTM: post-translational modifications; PSM: Peptide-spectrum matching; RT: retention time; XIC: extracted ion chromatogram.

Author Contributions

K.L. and A.I.N. developed the diaTracer algorithm. K.L. wrote the software and analyzed the results. F.Y. and G.T. assisted with the algorithm and software development. K.L.Y helped modify MSBooster. F.Y. assisted with the integration of diaTracer into FragPipe. K.L., F.Y., and A.I.N. wrote the manuscript. A.I.N. conceived the study. A.I.N. and F.Y. supervised the study.

Data availability

The raw MS/MS files used in this study can be found at the ProteomeXchange Consortium and PRIDE partner repository[58] or at the MassIVE repository with the following accession codes:

- CSF data: PXD035249
- Plasma data: PXD047839
- HLA data: MSV000092557
- Phosphoproteomics data: PXD033904
- Low-input, spatial proteomics data: PXD042367

diaTracer converted mzML files and FragPipe results have been uploaded to MassIVE repository with the identifier MSV000094803.

Code availability

The standalone version of diaTracer can be downloaded as a single JAR file at https://diatracer.nesvilab.org. FragPipe is available at GitHub https://github.com/Nesvilab/FragPipe. Python and R scripts for summarizing the results and generating the figures are available at https://github.com/nesvilab/diaTracer-manuscript.

Competing interests

A.I.N. and F.Y. receive royalties from the University of Michigan for the sale of MSFragger and IonQuant software licenses to commercial entities. All license transactions are managed by the University of Michigan Innovation Partnerships office, and all proceeds are subject to university technology transfer policy. Other authors declare no other competing interests.

References

1. Aebersold, R.; Mann, M., Mass-spectrometric exploration of proteome structure and function. *Nature* **2016,** *537* (7620), 347-55.
2. Gillet, L. C.; Navarro, P.; Tate, S.; Röst, H.; Selevsek, N.; Reiter, L.; Bonner, R.; Aebersold, R., Targeted Data Extraction of the MS/MS Spectra Generated by Data-independent Acquisition: A New Concept for Consistent and Accurate Proteome Analysis*. *Molecular & Cellular Proteomics* **2012,** *11* (6), O111.016717.
3. Panchaud, A.; Scherl, A.; Shaffer, S. A.; von Haller, P. D.; Kulasekara, H. D.; Miller, S. I.; Goodlett, D. R., Precursor Acquisition Independent From Ion Count: How to Dive Deeper into the Proteomics Ocean. *Analytical Chemistry* **2009,** *81* (15), 6481-6488.
4. Venable, J. D.; Dong, M.-Q.; Wohlschlegel, J.; Dillin, A.; Yates, J. R., Automated approach for quantitative analysis of complex peptide mixtures from tandem mass spectra. *Nature Methods* **2004,** *1* (1), 39-45.
5. May, J. C.; McLean, J. A., Ion mobility-mass spectrometry: time-dispersive instrumentation. *Anal Chem* **2015,** *87* (3), 1422-36.
6. Meier, F.; Brunner, A. D.; Koch, S.; Koch, H.; Lubeck, M.; Krause, M.; Goedecke, N.; Decker, J.; Kosinski, T.; Park, M. A.; Bache, N.; Hoerning, O.; Cox, J.; Rather, O.; Mann, M., Online Parallel Accumulation-Serial Fragmentation (PASEF) with a Novel Trapped Ion Mobility Mass Spectrometer. *Mol Cell Proteomics* **2018,** *17* (12), 2534-2545.
7. Yu, F.; Haynes, S. E.; Teo, G. C.; Avtonomov, D. M.; Polasky, D. A.; Nesvizhskii, A. I., Fast Quantitative Analysis of timsTOF PASEF Data with MSFragger and IonQuant. *Mol Cell Proteomics* **2020,** *19* (9), 1575-1585.
8. Yu, F.; Haynes, S. E.; Nesvizhskii, A. I., IonQuant Enables Accurate and Sensitive Label-Free Quantification With FDR-Controlled Match-Between-Runs. *Mol Cell Proteomics* **2021,** *20,* 100077.
9. Demichev, V.; Szyrwiel, L.; Yu, F.; Teo, G. C.; Rosenberger, G.; Niewienda, A.; Ludwig, D.; Decker, J.; Kaspar-Schoenefeld, S.; Lilley, K. S.; Mülleder, M.; Nesvizhskii, A. I.; Ralser, M., dia-PASEF data analysis using FragPipe and DIA-NN for deep proteomics of low sample amounts. *Nat Commun* **2022,** *13* (1), 3944.
10. Tsou, C. C.; Avtonomov, D.; Larsen, B.; Tucholska, M.; Choi, H.; Gingras, A. C.; Nesvizhskii, A. I., DIA-Umpire: comprehensive computational framework for data-independent acquisition proteomics. *Nat Methods* **2015,** *12* (3), 258-64, 7 p following 264.
11. Röst, H. L.; Rosenberger, G.; Navarro, P.; Gillet, L.; Miladinović, S. M.; Schubert, O. T.; Wolski, W.; Collins, B. C.; Malmström, J.; Malmström, L.; Aebersold, R., OpenSWATH enables automated, targeted analysis of data-independent acquisition MS data. *Nat Biotechnol* **2014,** *32* (3), 219-23.
12. Wang, J.; Tucholska, M.; Knight, J. D. R.; Lambert, J.-P.; Tate, S.; Larsen, B.; Gingras, A.-C.; Bandeira, N., MSPLIT-DIA: sensitive peptide identification for data-independent acquisition. *Nature Methods* **2015,** *12* (12), 1106-1108.
13. Tsou, C. C.; Tsai, C. F.; Teo, G. C.; Chen, Y. J.; Nesvizhskii, A. I., Untargeted, spectral library-free analysis of data-independent acquisition proteomics data generated using Orbitrap mass spectrometers. *Proteomics* **2016,** *16* (15-16), 2257-2271.
14. Bruderer, R.; Sondermann, J.; Tsou, C. C.; Barrantes-Freer, A.; Stadelmann, C.; Nesvizhskii, A. I.; Schmidt, M.; Reiter, L.; Gomez-Varela, D., New targeted approaches for the quantification of data-independent acquisition mass spectrometry. *Proteomics* **2017,** *17* (9).
15. Ting, Y. S.; Egertson, J. D.; Payne, S. H.; Kim, S.; MacLean, B.; Käll, L.; Aebersold, R.; Smith, R. D.; Noble, W. S.; MacCoss, M. J., Peptide-Centric Proteome Analysis: An Alternative Strategy for the Analysis of Tandem Mass Spectrometry Data. *Mol Cell Proteomics* **2015,** *14* (9), 2301-7.

16.   Searle, B. C.; Pino, L. K.; Egertson, J. D.; Ting, Y. S.; Lawrence, R. T.; MacLean, B. X.; Villén, J.; MacCoss, M. J., Chromatogram libraries improve peptide detection and quantification by data independent acquisition mass spectrometry. *Nature Communications* **2018,** *9* (1), 5128.

17.   Ting, Y. S.; Egertson, J. D.; Bollinger, J. G.; Searle, B. C.; Payne, S. H.; Noble, W. S.; MacCoss, M. J., PECAN: library-free peptide detection for data-independent acquisition tandem mass spectrometry data. *Nature Methods* **2017,** *14* (9), 903-908.

18.   Demichev, V.; Messner, C. B.; Vernardis, S. I.; Lilley, K. S.; Ralser, M., DIA-NN: neural networks and interference correction enable deep proteome coverage in high throughput. *Nat Methods* **2020,** *17* (1), 41-44.

19.   Yu, F.; Teo, G. C.; Kong, A. T.; Frohlich, K.; Li, G. X.; Demichev, V.; Nesvizhskii, A. I., Analysis of DIA proteomics data using MSFragger-DIA and FragPipe computational platform. *Nat Commun* **2023,** *14* (1), 4154.

20.   Lu, Y. Y.; Bilmes, J.; Rodriguez-Mias, R. A.; Villén, J.; Noble, W. S., DIAmeter: matching peptides to data-independent acquisition mass spectrometry data. *Bioinformatics* **2021,** *37* (Supplement_1), i434-i442.

21.   Yang, K. L.; Yu, F. C.; Teo, G. C.; Li, K.; Demichev, V.; Ralser, M.; Nesvizhskii, A. I., MSBooster: improving peptide identification rates using deep learning-based features. *Nat Commun* **2023,** *14* (1).

22.   Gessulat, S.; Schmidt, T.; Zolg, D. P.; Samaras, P.; Schnatbaum, K.; Zerweck, J.; Knaute, T.; Rechenberger, J.; Delanghe, B.; Huhmer, A.; Reimer, U.; Ehrlich, H.-C.; Aiche, S.; Kuster, B.; Wilhelm, M., Prosit: proteome-wide prediction of peptide tandem mass spectra by deep learning. *Nature Methods* **2019,** *16* (6), 509-518.

23.   Kong, A. T.; Leprevost, F. V.; Avtonomov, D. M.; Mellacheruvu, D.; Nesvizhskii, A. I., MSFragger: ultrafast and comprehensive peptide identification in mass spectrometry-based proteomics. *Nat Methods* **2017,** *14* (5), 513-520.

24.   Tsou, C. C.; Avtonomov, D.; Larsen, B.; Tucholska, M.; Choi, H.; Gingras, A. C.; Nesvizhskii, A. I., DIA-Umpire: comprehensive computational framework for data-independent acquisition proteomics. *Nat Methods* **2015,** *12* (3), 258-+.

25.   Avtonomov, D. M.; Polasky, D. A.; Ruotolo, B. T.; Nesvizhskii, A. I., IMTBX and Grppr: Software for Top-Down Proteomics Utilizing Ion Mobility-Mass Spectrometry. *Anal Chem* **2018,** *90* (3), 2369-2375.

26.   Kong, A. T.; Leprevost, F. V.; Avtonomov, D. M.; Mellacheruvu, D.; Nesvizhskii, A. I., MSFragger: ultrafast and comprehensive peptide identification in mass spectrometry-based proteomics. *Nat Methods* **2017,** *14* (5), 513-+.

27.   Yu, F. C.; Teo, G. C.; Kong, A. T.; Haynes, S. E.; Avtonomov, D. M.; Geiszler, D. J.; Nesvizhskii, A. I., Identification of modified peptides using localization-aware open search. *Nat Commun* **2020,** *11* (1).

28.   Käll, L.; Canterbury, J. D.; Weston, J.; Noble, W. S.; Maccoss, M. J., Semi-supervised learning for peptide identification from shotgun proteomics datasets. *Nature Methods* **2007,** *4* (11), 923-925.

29.   Keller, A.; Nesvizhskii, A. I.; Kolker, E.; Aebersold, R., Empirical statistical model to estimate the accuracy of peptide identifications made by MS/MS and database search. *Anal Chem* **2002,** *74* (20), 5383-92.

30.   Nesvizhskii, A. I.; Keller, A.; Kolker, E.; Aebersold, R., A statistical model for identifying proteins by tandem mass spectrometry. *Anal Chem* **2003,** *75* (17), 4646-58.

31.   da Veiga Leprevost, F.; Haynes, S. E.; Avtonomov, D. M.; Chang, H.-Y.; Shanmugam, A. K.; Mellacheruvu, D.; Kong, A. T.; Nesvizhskii, A. I., Philosopher: a versatile toolkit for shotgun proteomics data analysis. *Nature Methods 2020 17:9* **2020,** *17* (9), 869-870.

32.   Shteynberg, D. D.; Deutsch, E. W.; Campbell, D. S.; Hoopmann, M. R.; Kusebauch, U.; Lee, D.; Mendoza, L.; Midha, M. K.; Sun, Z.; Whetton, A. D.; Moritz, R. L., PTMProphet: Fast and Accurate Mass Modification Localization for the Trans-Proteomic Pipeline. *J Proteome Res* **2019,** *18* (12), 4262-4272.

33.   Pino, L. K.; Searle, B. C.; Bollinger, J. G.; Nunn, B.; MacLean, B.; MacCoss, M. J., The Skyline ecosystem: Informatics for quantitative mass spectrometry proteomics. *Mass Spectrom Rev* **2020,** *39* (3), 229-244.

34.   Li, K.; Vaudel, M.; Zhang, B.; Ren, Y.; Wen, B., PDV: an integrative proteomics data viewer. *Bioinformatics* **2019,** *35* (7), 1249-1251.

35.   Hsiao, Y.; Zhang, H.; Li, G. X.; Deng, Y.; Yu, F.; Kahrood, H. V.; Steele, J. R.; Schittenhelm, R. B.; Nesvizhskii, A. I., Analysis and visualization of quantitative proteomics data using FragPipe-Analyst. *bioRxiv* **2024,** 2024.03.05.583643.

36.   Kohler, D.; Staniak, M.; Tsai, T. H.; Huang, T.; Shulman, N.; Bernhardt, O. M.; MacLean, B. X.; Nesvizhskii, A. I.; Reiter, L.; Sabido, E.; Choi, M.; Vitek, O., MSstats Version 4.0: Statistical Analyses of Quantitative Mass Spectrometry-Based Proteomic Experiments with Chromatography-Based Quantification at Scale. *J Proteome Res* **2023,** *22* (5), 1466-1482.

37.   Mun, D. G.; Budhraja, R.; Bhat, F. A.; Zenka, R. M.; Johnson, K. L.; Moghekar, A.; Pandey, A., Four-dimensional proteomics analysis of human cerebrospinal fluid with trapped ion mobility spectrometry using PASEF. *Proteomics* **2023,** *23* (10).

38.   Geiszler, D. J.; Kong, A. T.; Avtonomov, D. M.; Yu, F.; Leprevost, F. d. V.; Nesvizhskii, A. I., PTM-Shepherd: Analysis and Summarization of Post-Translational and Chemical Modifications From Open Search Results. *Molecular & Cellular Proteomics* **2021,** *20,* 100018.

39.   Vitko, D.; Chou, W. F.; Golmaei, S. N.; Lee, J. Y.; Belthangady, C.; Blume, J.; Chan, J. K.; Flores-Campuzano, G.; Hu, Y. T.; Liu, M.; Marispini, M. A.; Mora, M. G.; Ramaswamy, S.; Ranjan, P.; Williams, P. B.; Zawada, R. J. X.; Ma, P. L.; Wilcox, B. E., timsTOF HT Improves Protein Identification and Quantitative Reproducibility for Deep Unbiased Plasma Protein Biomarker Discovery. *J Proteome Res* **2024,** *23* (3), 929-938.

40.   Hsiao, Y.; Zhang, H.; Li, G. X.; Deng, Y.; Yu, F.; Kahrood, H. V.; Steele, J. R.; Schittenhelm, R. B.; Nesvizhskii, A. I., Analysis and visualization of quantitative proteomics data using FragPipe-Analyst. *bioRxiv* **2024.**

41.   Liu, T.; Zhu, J. J.; Du, W. W.; Ning, W. W.; Zhang, Y.; Zeng, Y. Y.; Liu, Z. Y.; Huang, J. A., AKT2 drives cancer progression and is negatively modulated by miR-124 in human lung adenocarcinoma. *Resp Res* **2020,** *21* (1).

42.   Matthaios, D.; Hountis, P.; Karakitsos, P.; Bouros, D.; Kakolyris, S., H2AX a promising biomarker for lung cancer: a review. *Cancer Invest* **2013,** *31* (9), 582-99.

43.   Wahle, M.; Thielert, M.; Zwiebel, M.; Skowronek, P.; Zeng, W. F.; Mann, M., IMBAS-MS Discovers Organ-Specific HLA Peptide Patterns in Plasma. *Mol Cell Proteomics* **2024,** *23* (1), 100689.

44.   Reynisson, B.; Alvarez, B.; Paul, S.; Peters, B.; Nielsen, M., NetMHCpan-4.1 and NetMHCIIpan-4.0: improved predictions of MHC antigen presentation by concurrent motif deconvolution and integration of MS MHC eluted ligand data. *Nucleic Acids Res* **2020,** *48* (W1), W449-W454.

45.   Oliinyk, D.; Meier, F., Ion mobility-resolved phosphoproteomics with dia-PASEF and short gradients. *Proteomics* **2023,** *23* (7-8), e2200032.

46.   Makhmut, A.; Qin, D.; Fritzsche, S.; Nimo, J.; König, J.; Coscia, F., A framework for ultra-low-input spatial tissue proteomics. *Cell Syst* **2023,** *14* (11), 1002-+.

47.   Chang, C.-H.; Chang, H.-Y.; Rappsilber, J.; Ishihama, Y., Isolation of Acetylated and Unmodified Protein N-Terminal Peptides by Strong Cation Exchange Chromatographic Separation of TrypN-Digested Peptides. *Molecular & Cellular Proteomics* **2021,** *20,* 100003.

48.   Klein, T.; Eckhard, U.; Dufour, A.; Solis, N.; Overall, C. M., Proteolytic Cleavage—Mechanisms, Function, and "Omic" Approaches for a Near-Ubiquitous Posttranslational Modification. *Chemical Reviews* **2018,** *118* (3), 1137-1168.

49.   Kuljanin, M.; Mitchell, D. C.; Schweppe, D. K.; Gikandi, A. S.; Nusinow, D. P.; Bulloch, N. J.; Vinogradova, E. V.; Wilson, D. L.; Kool, E. T.; Mancias, J. D.; Cravatt, B. F.; Gygi, S. P., Reimagining high-

throughput profiling of reactive cysteines for cell-based screening of large electrophile libraries. *Nature Biotechnology* **2021,** *39* (5), 630-641.

50. Desai, H. S.; Yan, T.; Yu, F.; Sun, A. W.; Villanueva, M.; Nesvizhskii, A. I.; Backus, K. M., SP3-Enabled Rapid and High Coverage Chemoproteomic Identification of Cell-State–Dependent Redox-Sensitive Cysteines. *Molecular & Cellular Proteomics* **2022,** *21* (4).

51. Skowronek, P.; Krohs, F.; Lubeck, M.; Wallmann, G.; Itang, E. C. M.; Koval, P.; Wahle, M.; Thielert, M.; Meier, F.; Willems, S.; Raether, O.; Mann, M., Synchro-PASEF Allows Precursor-Specific Fragment Ion Extraction and Interference Removal in Data-Independent Acquisition. *Mol Cell Proteomics* **2023,** *22* (2), 100489.

52. Lukasz Szyrwiel, L. S., Markus Ralser, Vadim Demichev, Slice-PASEF: fragmenting all ions for maximum sensitivity in proteomics. *bioRxiv* **2022**.

53. Ute Distler, M. K. Ł., Michał Piotr Startek, David Teschner, Sven Brehmer, Jens Decker, Thilo Schild, Jonathan Krieger, Florian Krohs, Oliver Raether, Andreas Hildebrandt, Stefan Tenzer, midiaPASEF maximizes information content in data-independent acquisition proteomics. *bioRxiv* **2023**.

54. Brakel, J. P. G. v., Robust peak detection algorithm using z-scores. 2014.

55. Teo, G. C.; Polasky, D. A.; Yu, F. C.; Nesvizhskii, A. I., Fast Deisotoping Algorithm and Its Implementation in the MSFragger Search Engine. *J Proteome Res* **2021,** *20* (1), 498-505.

56. Pham, T. V.; Henneman, A. A.; Jimenez, C. R., : an R package to estimate relative protein abundances from ion quantification in DIA-MS-based proteomics. *Bioinformatics* **2020,** *36* (8), 2611-2613.

57. MacLean, B.; Tomazela, D. M.; Shulman, N.; Chambers, M.; Finney, G. L.; Frewen, B.; Kern, R.; Tabb, D. L.; Liebler, D. C.; MacCoss, M. J., Skyline: an open source document editor for creating and analyzing targeted proteomics experiments. *Bioinformatics* **2010,** *26* (7), 966-968.

58. Perez-Riverol, Y.; Csordas, A.; Bai, J.; Bernal-Llinares, M.; Hewapathirana, S.; Kundu, D. J.; Inuganti, A.; Griss, J.; Mayer, G.; Eisenacher, M.; Pérez, E.; Uszkoreit, J.; Pfeuffer, J.; Sachsenberg, T.; Yilmaz, Ş.; Tiwary, S.; Cox, J.; Audain, E.; Walzer, M.; Jarnuczak, A. F.; Ternent, T.; Brazma, A.; Vizcaíno, J. A., The PRIDE database and related tools and resources in 2019: improving support for quantification data. *Nucleic Acids Research* **2019,** *47* (Database issue), D442-D442.

Figure 1: Overview of diaTracer and FragPipe computational platform. diaTracer applies a 3D feature detection algorithm to detect signals from all possible precursors and fragments in MS1 and MS2 diaPASEF data. Pseudo-MS/MS spectra are generated through precursor-fragment clustering and can be processed as DDA data using MSFragger and FragPipe to build a spectral library directly from the data. A hybrid spectral library can also be generated if DDA data are available. This spectral library is then used to extract quantification using DIA-NN.

Figure 2: CSF data. a) Box plot showing the numbers of quantified proteins using different methods, with colors representing cleavage types (green: trypsin cleavage; orange: allowing semi-tryptic peptides). In the boxplot, the central line represents the median of the numbers. The lower and upper edges of the box represent the first (Q1) and third quartiles (Q3). The interquartile range (IQR) is the box between Q1 and Q3. Whiskers extend from the box to the smallest and largest data points within 1.5 times the IQR from Q1 and Q3, respectively. Data points outside this range are considered outliers and are shown as individual dots. **b)** Box plot showing the numbers of quantified precursors using different methods. The box plots' median, edges, and whiskers are same as the ones in a). **c)** Distribution of identified peptides for protein HPX, with the red segment indicating the signal peptide region at the N-terminal. Orange segments represent tryptic peptides, while green segments represent semi-tryptic peptides. **d)** Running time comparison. FragPipe* indicated the FragPipe run time (including DA-0NN for quantification) starting from diaTracer-extracted files. **e)** Modifications identified using the common offset workflow in FragPipe using pseudo-MS/MS spectra generated by diaTracer.

Figure 3: Plasma data. a) Histogram showing the number of quantified proteins using diaTracer-based FragPipe workflows (tryptic and semi-tryptic search), using DIA-NN library-free mode, colored from deep to light blue corresponding to different non-missing value filters. **b)** Same as a) for quantified precursors. **c)** Volcano plot comparing protein abundance between stage IV non-small cell lung cancer (NSCLC) and non-cancer control samples, highlighting NSCLC-overexpressed proteins (Log2 fold change >= 0.6; adjusted p-value <= 0.05). **d)** Boxplots of protein abundance distribution of AKT2 (top) and H2AX (bottom)proteins in semi-tryptic (left) and tryptic (right) searches between NSCLC (red) and control (blue) samples. In the boxplot, the central line represents the median of the numbers. The lower and upper edges of the box represent the first (Q1) and third quartiles (Q3). The interquartile range (IQR) is the box between Q1 and Q3. Whiskers extend from the box to the smallest and largest data points within 1.5 times the IQR from Q1 and Q3, respectively. Data points outside this range are considered outliers and are shown as individual dots. Tr: tryptic search; Semi: semi-tryptic search.

a)

Figure 4: HLA immunopeptidomics data. a) Number of quantified immunopeptides obtained using FragPipe with diaTracer and that reported in the original study based on Spectronaut 17. **b)** Histogram of predicted binders for all HLA alleles of the corresponding sample donor, colored by binder type (light: weak binder; dark: strong binder). **c)** Length distribution of quantified immunopeptides. **d)** Charge state distribution of quantified immunopeptides. **e)** Pseudo-MS/MS

spectrum generated by diaTracer and the predicted spectrum for one of identified immunopeptides, VYQHLFTRI. The entropy score between the two spectra is 0.9863. Visualization using FragPipe-PDV viewer.

Figure 5: Phosphoproteomics data. **a)** Histogram of quantified phosphorylated peptide sequences across different gradients. **b)** Histogram of class 1 phosphorylation sites (prob > 0.75) across different gradients. **c)** and **d)** PSM and fragments XICs of phosphorylated peptide S(Pho)PSPPDGSPAATPEIR. **e)** and **f)** PSM and fragments XICs of phosphorylated peptide SPSPPDGS(Pho)PAATPEIR. XICs are visualized using Skyline.

Figure 6: Low-input, spatial proteomics data. a) Number of quantified proteins after application of non-missing value (in at least one group) filter ranging from 0% to 100%, with line colors representing different methods. Red: results from the original study based on the library built using high-input samples; Green: results based on FragPipe with diaTracer, also using high-input data to build the library ("FP-diaTracer, high-input Lib"); Blue: result using diaTracer and FragPipe with low-input data only ("FP-diaTracer"). **b)** Venn diagram of quantified proteins between the three methods, with data filtered to keep proteins with at least 70% non-missing values in at least one group. **c)** Principal-component analysis (PCA) plot of 148 samples based on 1471 proteins (after missing value filtering and data imputation) quantified using the FP-diaTracer workflow (using low-input data only). **d)** Log2 transformed protein level abundance distribution of selected cell-type-specific proteins in different regions. In the boxplot, the central line represents the median of the numbers. The lower and upper edges of the box represent the first (Q1) and third quartiles (Q3). The interquartile range (IQR) is the box between Q1 and Q3. Whiskers extend from the box to the smallest and largest data points within 1.5 times the IQR from Q1 and Q3, respectively. Data points outside this range are considered outliers and are shown as individual dots. **e)** Volcano plot showing protein abundance differences between Mantel zone and T cell zone, highlighting tissue-specific proteins (Log2 fold change >= 1; adjusted p-value <= 0.05).

dia-PASEF .d data

IM

m/z

IM

3D feature tracing

Precursor-fragment clustering

Pseudo-MS/MS spectrum

DDA library raw data

MSFr⚡GGER

MSBooster

Percolator

DIA-NN for Quant

Spectral library

EasyPQP

ProteinProphet 1% FDR filtering