Selective Labeling Meets Semi-Supervised Neuron Segmentation

Yanchao Zhang[a,b,1], Hao Zhai[a,b,1], Jinyue Guo[a,c], Jing Liu[a], Hua Han[a,b,*]

[a]*Key Laboratory of Brain Atlas and Brain-inspired Intelligence, Institute of Automation, Chinese Academy of Sciences, Beijing 100190, China*
[b]*School of Future Technology, University of Chinese Academy of Sciences, Beijing 101408, China*
[c]*School of Artificial Intellengace, University of Chinese Academy of Sciences, Beijing 101408, China*

ARTICLE INFO

Article history:

Keywords: Connectomics, Volume electron microscopy, Neuron segmentation, Semi-supervised learning, Selective labeling

ABSTRACT

Semi-supervised learning holds promise for cost-effective neuron segmentation in Electron Microscopy (EM) volumes. This technique fully leverages extensive unlabeled data to regularize supervised training for robust predictions. However, diverse neuronal patterns and limited annotation budgets may lead to distribution mismatch between labeled and unlabeled data, hindering the generalization of semi-supervised models. To address this issue, we propose an improved pipeline for cost-effective neuron segmentation by integrating selective labeling and semi-supervised training. For selective labeling, we present an unsupervised heuristic tailored for labeled dataset selection in EM volumes. Guided by self-supervised learning on local patches, representative sub-volumes comprising spatially associated patches are greedily selected via a coverage-based criterion. Those sub-volumes can effectively reflect unlabeled data distribution within a limited budget. For semi-supervised training, we introduce spatial mixing into neuron segmentation and integrate it within a Siamese architecture. This enhancement allows us to reinforce cross-view consistency through intra- and inter-mixing of labeled and unlabeled datasets. The proposed strategies bridge the distribution gap and encourage the model to learn shared semantics across datasets, promoting more effective semi-supervised learning. Extensive experiments on public datasets consistently demonstrate the effectiveness of the proposed pipeline, providing a practical and efficient solution for large-scale neuron reconstruction. Codes and data will be available.

1. Introduction

The field of connectomics aims to gain a comprehensive understanding of brain mechanisms and intelligence by reconstructing and interpreting neural circuits at the synaptic level Ngai (2022). Currently, only volume Electron Microscopy (EM) with nanoscale resolution supports imaging of intricate morphology of neurons and individual synapses in brain tissue. However, this technique generates massive volumetric datasets, ranging from several hundred terabytes to petabytes Abbott et al. (2020); Shapson-Coe et al. (2024); Zheng et al. (2018); Dorkenwald et al. (2023); Scheffer et al. (2020); Liu et al. (2022). The unprecedented data quantity and complexity call for automatic methods to accelerate data processing and analysis. Efficient and accurate neuron reconstruction from EM volumes has become a bottleneck that hinders progress in digitiz-

ing the complete atlas of nervous systems. Consequently, automatic methods based on deep neural networks have been developed for neuron reconstruction Lee et al. (2017); Januszewski et al. (2018); Lee et al. (2021); Funke et al. (2018); Sheridan et al. (2022). Nevertheless, optimizing such networks faces two major challenges. Firstly, the massive EM data spanning different neural structures leads to diverse textures and patterns (Fig. 1(a)). Secondly, labeled data typically takes up a small fraction of the overall volume due to the high cost of expert annotations. For instance, in the reconstruction of a fly hemi-brain, the segmentation model was trained using just 8 manually selected sub-volumes, which account for a mere 0.003% of the entire dataset (0.8GB out of 26TB) Scheffer et al. (2020).

Semi-supervised learning holds immense potential to tackle these issues by leveraging large-scale unlabeled data to enhance model generalization. Related works in biomedical image segmentation have developed techniques, such as consistency learning Huang et al. (2022); Luo et al. (2021); Yu et al. (2019) and self-training Wang et al. (2022b); Shi et al. (2021), to regularize supervised training on insufficient labeled data,

Fig. 1. (a) Background and motivation. 3D Neuron segmentation aims to assign a unique label to every voxel in the EM volumes that belongs to the same neurite Zheng et al. (2018); Dorkenwald et al. (2023, 2022). The vast amount of EM data spanning diverse brain regions introduces a wide array of textures and patterns. Limited by annotation budgets, the labeled data may inadequately depict the distribution of unlabeled data. This distribution mismatch violates the same distributional hypothesis between labeled and unlabeled datasets, resulting in sub-optimal semi-supervised learning and degradation in segmentation performance. (b) Illustration of the improved semi-supervised pipeline for neuron segmentation. Selective labeling and cross-view consistency learning reduce the gap between labeled and unlabeled distributions at the data and model levels, respectively.

aiming to reduce the performance gap between fully supervised and semi-supervised methods. Note that these studies typically assume that labeled data and unlabeled data are drawn from the same distribution, thereby enabling network optimization with the aid of unlabeled data. However, ensuring matched distribution can be challenging in practical scenarios, and it is prominent in dense neuron segmentation because of the intricate nature of neural structures, the large-scale database, and limited annotation budgets. The mismatch problem, as shown in Fig. 1(a), may lead to the discarding of knowledge learned from limited labeled data, hindering the generalization of semi-supervised models.

From the data level, such an obstacle would be overcome mainly if the labeled data could be carefully selected to reflect the overall data distribution. Unfortunately, there is a lack of research on the targeted annotation of volumetric sub-regions within unlabeled EM data. The challenges lie in two aspects: (1) Continuous volumetric data, extracting representative sub-regions with flexible sizes from continuously distributed EM volume requires data discretization and specific evaluation criteria. In contrast, selective annotation of discrete instances (*e.g.*, ImageNet Russakovsky et al. (2015)) can be achieved directly through diversity sampling Wang et al. (2022a); Mannix and Bondell (2023). (2) Unsupervised scene, selecting the most representative data for labeling becomes challenging in the absence of initial labeled data, as it is difficult to assess the potential value of raw data Zheng et al. (2019); Jin et al. (2022).

From the model level, promoting the mutual transfer of information between labeled and unlabeled data in semi-supervised training can further narrow the distribution gap by fostering the network to learn shared semantics Bai et al. (2023); Wang et al. (2019). However, existing efforts on semi-supervised neuron segmentation treat labeled and unlabeled data separately and thus lead to asymmetry in knowledge extraction and feature learning. Establishing a connection between labeled and unlabeled EM data within a semi-supervised framework poses another challenge for solving the mismatch problem in neuron segmentation.

In this paper, we propose the first framework that combines selective labeling with semi-supervised learning for cost-effective neuron segmentation, as illustrated in Fig. 1(b). The key idea is that alleviating the mismatched distribution between labeled and unlabeled EM data can promote semi-supervised learning. We commence by conducting self-supervised learning on the unlabeled EM dataset, offering an embedding network capable of providing meaningful representations for local patches. On this basis, we present a greedy algorithm to identify informative and diverse sub-volumes using a constrained coverage-based criterion. Specifically, each candidate sub-volume is constructed from a collection of adjacent patches, allowing for flexibility in its size. Afterward, we train a segmentation model using selectively labeled sub-volumes and the unlabeled data in a semi-supervised fashion. By extending CutMix Yun et al. (2019); French et al. (2019) to neuron segmentation, we introduce inter- and intra-dataset mixing to connect labeled and unlabeled data by enforcing cross-view consistency. This two-stage approach promotes more effective semi-supervised learning by reducing the distribution gap at both the data and model levels, demonstrating practical value in large-scale neuron reconstruction.

Our contributions are summarized as follows:

1. We present an improved semi-supervised pipeline for neuron segmentation that reduces the mismatch between labeled and unlabeled distributions via coverage-based selective labeling and cross-view consistency learning.

2. We introduce an unsupervised method to measure the distribution of volumetric EM datasets. On this basis, a coverage-based heuristic is developed for identifying valuable sub-volumes, which ensures a fine representation of the overall data distribution and various neuronal structures even within a limited annotation budget.

3. We make the first attempt to integrate spatial mixing into semi-supervised neuron segmentation. This approach establishes a connection between labeled and unlabeled datasets and enables cross-view consistency regularization through inter- and intra-dataset mixing.

4. We investigate the impact of distribution mismatch on the outcome of semi-supervised models, and validate the effectiveness of the proposed pipeline on representative EM datasets and large-scale scenarios, offering novel insights for cost-effective neuron segmentation.

2. Related work

2.1. Neuron Segmentation

As an instance segmentation problem, neuron reconstruction aims to assign a unique label to every voxel in the EM volumes that belongs to the same neuron. This task is challenging due to the unprecedented scale of EM data, the varied textures of neuronal structures, and the scarcity of expert annotations. State-of-the-art methods can be sketchily categorized as boundary-based and object-based. Specifically, boundary-based approaches first use 3D U-Net Çiçek et al. (2016) variants to predict descriptors for neuron boundaries (*e.g.*, voxel affinity graphs, dense voxel embeddings Lee et al. (2021), and local shape descriptors Sheridan et al. (2022)). After over-segmentation via watershed transform, graph-based agglomeration is adopted to group supervoxels for instance segmentation. In contrast, object-based approaches, as seen in Januszewski et al. (2018); Meirovitch et al. (2019); Schmidt et al. (2024), extend the segmented area from the seed points to complete neurites iteratively. while effective, large-scale neuron reconstructions still require years of manual proofreading before they can be used for connectivity analysis Zheng et al. (2018). Pursuing higher accuracy in the automatic segmentation stage plays a vital role in cost-effective connectomics.

In this study, we employ a boundary-based pipeline that starts with a 3D network to predict voxel affinities along the x, y, and z axes. We aim to improve affinity predictions by leveraging both limited labeled and extensive unlabeled data in a semi-supervised manner, ultimately achieving better instance segmentation results and reducing proofreading costs.

2.2. Selective Labeling

Selective Labeling (SL), the focus of active learning, seeks to annotate a valuable subset of an unlabeled dataset to optimize supervised learning under limited budgets. Active learning can be divided into two categories based on whether or not the data are selected iteratively: ITerative Active Learning (ITAL) and One-Shot Active Learning (OSAL).

ITAL has received significant attention in prior research Yang et al. (2017); Sener and Savarese (2018); Lin et al. (2020). It typically involves the iterative selection and labeling of valuable samples under uncertainty- or diversity-based strategies, accompanied by continual network fine-tuning as more labeled data become available. However, ITAL rarely discusses which samples to choose initially when no trained model is available. Worse still, the iterative training, inference, and annotation procedures can be computationally expensive and time-consuming, particularly in large-scale neuron segmentation. In contrast, OSAL selects all valuable samples simultaneously before network training. Specifically, OSAL algorithms first measure unlabeled distribution via unsupervised representation learning, which projects raw data onto a low-dimensional embedding space. Then, customized selection strategies Zheng et al. (2019); Jin et al. (2022); Wang et al. (2022a) are proposed to identify representative and informative instances as labeled data. Unfortunately, limited attention has been given to the selective labeling of volumetric data including EM volumes. Due to the continuity and significant variance in the size of neuronal structures, labeled data in practical neuron reconstruction are typically sub-volumes with flexible sizes, from which local patches are randomly cropped for model training. Nevertheless, existing OSAL algorithms operate on patch-level discrete instances for selective labeling. Those annotations lack flexibility in size and fail to reflect the continuous changes in neuron boundaries, resulting in performance degradation of the network.

In this work, we design a novel OSAL approach for EM volumes. This unsupervised algorithm allows for selecting sub-regions with flexible sizes from the continuous unlabeled volume, which ensures a better representation of the overall data distribution even within a limited annotation budget.

2.3. Semi-supervised Segmentation

Labeled data often constitutes a tiny fraction of the total volume in practical connectomics reconstruction. Semi-supervised learning (SSL) is a promising method to address limited annotation by leveraging unlabeled data to improve model generalization. Self-training and consistency regularization are notable techniques for generating supervision signals from unlabeled data. Self-training typically involves assigning pseudo labels to unlabeled data and combining them with the labeled for iterative model retraining Wang et al. (2022b); Shi et al. (2021); Yang et al. (2022). In contrast, the premise of consistency regularization is that the prediction of unlabeled data should remain consistent under various perturbations Luo et al. (2021); Yu et al. (2019); Zhao et al. (2023); Wu et al. (2021). SSNS-Net Huang et al. (2022) makes the first effort in semi-supervised neuron segmentation using consistency learning and validates the effectiveness of specific perturbations for EM data, highlighting the potential of semi-supervised techniques in this field. Notably, SSL is based on the assumption that labeled and unlabeled data are sampled from the identical distribution Berthelot et al. (2019b,a). However, distribution mismatch between labeled and unlabeled data is prominent in semi-supervised neuron segmentation due to the complex neural structures and limited budgets. Still, it has received little attention in the research community.

In this paper, we aim to address the distribution mismatch issue inherent in semi-supervised neuron segmentation. At the data level, we conduct unsupervised selective labeling on unlabeled EM volumes for representative sub-volumes as labeled data. At the model level, we introduce intra- and inter-dataset mixing to encourage shared feature learning within a semi-supervised framework. Both strategies narrow the distribution gap between labeled and unlabeled datasets, paving the way for more effective semi-supervised learning.

Fig. 2. Selective labeling. (a) After patch discretization (presented as non-overlapping for clarity), we employ an unsupervised trained network $f(\cdot)$ to map unlabeled data to the embedding space for EM representation. Then a quantitative heuristic (*i.e.*, CGS) is designed to identify representative sub-volumes as labeled data iteratively. Well-selected sub-volumes, represented by bound embedding vectors, can effectively reflect the overall data distribution with typical and diverse patches. (b) The embedding network $f(\cdot)$ for 3D EM patches is optimized via contrastive learning.

3. Method

As illustrated in Fig. 1(b), the pipeline highlights two primary components: selective labeling of valuable sub-volumes and semi-supervised training via cross-view consistency regularization, trying to tackle the mismatch issue synergistically.

3.1. Unsupervised Selective Labeling for EM Sub-volumes

Given an unlabeled dataset D_u and a labeling budget, the task is to identify and annotate sub-volumes that effectively represent the entire dataset. As in Fig. 2(a), we devise a two-step approach: 1) unsupervised representation learning for 3D EM patches, and 2) coverage-based sub-volume selection.

3.1.1. Unsupervised Representation Learning for EM Patches

To begin with, we perform self-supervised learning to develop an embedding network that can generate low-dimensional and semantic-rich representations for 3D EM patches. Specifically, the framework, constructed with Siamese networks Chen and He (2021), is optimized by maximizing the similarity between two variations of one volumetric image in the learned feature space, as depicted in Fig. 2(b). We cautiously employ perturbation strategies to augment EM inputs without substantially altering the semantic content, including reflections, rotations, Gaussian blurring, Gaussian noise, simulated misalignment, photometric perturbation, and randomly masked pixels.

During training, each input $u \in \mathbb{R}^{D \times H \times W}$ is sampled from unlabeled dataset D_u and randomly augmented to produce two views $\widetilde{u}_1$ and $\widetilde{u}_2$. These views are then fed into Siamese networks, which comprise two weight-sharing encoders (denoted as f), two weight-sharing projectors (denoted as g), and a predictor (denoted as h). The networks' parameters are updated by minimizing a symmetrized loss function given by

$$\mathcal{L}_{Sim} = \mathcal{N}(h(g(f(\widetilde{u}_1))), \underline{g(f(\widetilde{u}_2))}), \tag{1}$$

where $\mathcal{N}(A, B)$ represent the negative cosine similarity between A and B. The underlined items are treated as constants and not involved in gradient calculation. The trained encoder, referred to as $f(\cdot)$, then serves as an embedding network that projects EM patches onto an L-dimensional hyperspace.

3.1.2. Coverage-based Sub-volume Selection

With the embedding network for local patches, this subsection proposed a coverage-based heuristic to select representative and informative sub-volumes within the allocated budget.

For clarity, we highlight the difference between a patch and a sub-volume. A patch serves as the smallest unit for representation learning, whereas a sub-volume represents an arbitrarily sized sub-region cropped from the EM volume. The sub-volume annotation technique is customized for neuron segmentation. It addresses the limitations of patch-level annotation, such as the lack of size flexibility and the inability to capture the morphology of continuously distributed neural structures. Specifically, We employ spatially neighboring patches to jointly represent each candidate sub-volume. This enables us to utilize patch embeddings to represent sub-volumes directly in feature space. Well-selected sub-volumes covering typical and diverse patches can provide a comprehensive reflection of the overall data distribution.

By discretizing the unlabeled volume(s) into local patches via sliding window inference, we can leverage the embedding network to measure the unlabeled distribution. Specifically, the unlabeled data can be embedded as the *universal set* $U : \{v_n = f(u_n)\}_{n=1}^N$, where $u_n \in \mathbb{R}^L$ is the output of the embedding network $f(\cdot)$ applied to a 3D input patch u_n. Depending on the stride of patch discretization, this measurement approach can be readily extended to datasets of different scales. The above process maps the continuously distributed data to discrete vectors on a learned feature space. On this basis, candidate sub-volumes that are composed of patches with spatial constraints can be mapped to the *selected set* $S : \{v_m | v_m \in U\}_{m=1}^M$ by extracting corresponding vectors from U, as depicted in Fig. 2(a) sub-volume representation.

Intuitively, the distance between embedding vectors can reflect the semantic similarity between their corresponding patches. We postulate that each selected vector in S can rep-

---

Algorithm 1: Coverage-based Greedy Selection for Suv-volumes (CGS)

Input: unlabeled volume D_u, embedding network f_θ,
　　　　sub-volume sizes $\{s_i\}_{i=1}^t$
Output: selected sub-volumes D_l

selected set : $S \leftarrow \emptyset$, *universal set* : $U \leftarrow$ patch-level sliding window inference on D_u using $f(\cdot)$
for each sub-volume of size $s_i \in s_1, s_2, \ldots, s_t$ **do**
$best\_subset \leftarrow \emptyset, best\_rate \leftarrow -\infty$
for each position p in raw volume using sliding window of size s_i **do**
$subset \leftarrow$ extract vectors from U with $\{p, s_i\}$
$coverage\_rate \leftarrow \text{CCR}(subset \cup S, U)$
if $coverage\_rate > best\_rate$ **then**
$best\_subset \leftarrow subset$,
　　　　　　　 $best\_rate \leftarrow coverage\_rate$
9   **end**
10   **end**
11    $selected\_set \leftarrow selected\_set \cup best\_subset$
12   **end**
13   $D_l \leftarrow$ extract sub-volumes from D_u according to S

---

resent its K-nearest neighbors in U (denoted as covered vectors). We call it **semantic coverage** in the embedding space. In this case, a fixed-distance coverage strategy is not suitable due to variations in the distribution density of embedding vectors across different semantic distinctions, which may result in over- or under-representation of particular semantics. We have validated this statement in the experiments. We notice that some selected vectors may cover the same vector in U, leading to local **semantic redundancy** and insufficient data diversity. Therefore, well-selected sub-volumes, as illustrated in Fig. 2(a) sub-volume evaluation, ensure a fine representation of the overall data distribution and various neuronal structures with diverse and representative local patches.

With this in mind, we establish a criterion, **C**onstrained **C**overage **R**ate (CCR), to measure the semantic coverage ability of the *selected set S*. Formally,

$$V(v, U) = \{v_n \in U \mid \|v_n - v\|_2 \leq \|u - v\|_2, \ u \in U, \ |V| = K\}, (2)$$

$$C(S, U) = \bigcup_{v_m \in S} V(v_m, U), \tag{3}$$

$$\text{CCR}(S, U) = \frac{|C(S, U)|}{|U|}, \tag{4}$$

where $\| \cdot \|_2$ represent l_2-norm, $V(v, U)$ returns the K-nearest neighbors of v in U, and thus *covered set C* contains all the vectors in U that are within the K-nearest neighbors of at least one vector in S. CCR defines the coverage rate as the percentage of covered vectors in U. A higher CCR indicates that the selected sub-volumes cover a larger portion of the neural structures in the entire volume and thus better represent the overall data distribution.

Given a labeling budget, we aim to select a subset S in U to maximize the $\text{CCR}(S, U)$, where the vectors in S have spatial binding constraints. The optimal subset can be obtained by

calculating the constrained coverage rate across all sub-volume combinations. However, as the data scale grows and the annotation budget increases, the computational complexity of identifying the optimal sub-volumes becomes infeasible. As a compromise, we propose a **C**overage-based **G**reedy **S**election (CGS) algorithm to tackle the issue with linear time complexity, providing a promising approach for labeled data selection in large-scale EM volumes. Specifically, each iteration of CGS involves traversing the entire volume for the candidate sub-volume and extracting the corresponding vectors from U. These vectors are then added to the S to evaluate the selected sub-volume(s). At the end of each iteration, the sub-volume that garners the highest coverage rate is chosen for labeling. This process is repeated until the desired number of sub-volumes has been selected. CGS effectively mitigates the bias between labeled and unlabeled distributions. Please refer to Algorithm 1 for more details.

3.2. Semi-supervised Neuron Segmentation via Cross-view Consistency Learning

To integrate information from selected sub-volumes D_l and unlabeled data D_u, we present IIC-Net, a novel consistency-based SSL framework for neuron segmentation. As illustrated in Fig. 3 (a), introducing spatial mixing to the 3D neuron segmentation task enables us to model cross-view consistency via intra- and inter-mixing of labeled and unlabeled datasets. Supervision from mixed data not only encourages the network to learn shared semantics but also enhances the discriminability of neuron boundaries. Consequently, we establish a connection between datasets, which mitigates the distribution mismatch between datasets at the model level.

3.2.1. Axial-through Spatial Mixing for Neuron Segmentation

The affinity graph used to characterize neuron boundaries is generated from dense instance annotations. Each affinity value ranges between 0 and 1, which indicates whether two associated voxels belong to the same instance (1) or not (0) along the $x/y/z$ axis. Let two patches with affinity map be $\{(x_i, y_i), (x_j, y_j)\}$, where $x_i, x_j \in \mathbb{R}^{D \times H \times W}$ and $y_i, y_j \in \{0, 1\}^{C \times D \times H \times W}$. Spatical mixing for raw patches and affinities are denoted as $\text{M}^R(\cdot)$ and $\text{M}^A(\cdot)$, respectively.

Currently, large-scale volume EM data exhibits strong anisotropy Zheng et al. (2018); Shapson-Coe et al. (2024),, *i.e.* the z-axis resolution is much lower than that of the x- and y-axes. To prevent potential semantic ambiguity caused by asymmetric axial and tangential resolution, we employ axial-through masking strategies in spatial mixing, as shown in Fig. 4. The mixed result for x_i and x_j is

$$\text{M}^R(x_i, x_j) = \Pi^R \odot x_i + (\mathbf{1} - \Pi^R) \odot x_j, \tag{5}$$

where $\odot$ denote Hadamard product, $\Pi^R \in \{0, 1\}^{D \times H \times W}$ is a binary matrix determined by the masking strategy, which indicates whether the voxel comes from x_i (1) or x_j (0). The mixed result for c-channel affinities y_i and y_j is computed by

$$\text{M}^A(y_i, y_j) = \Pi^A \odot y_i + (\mathbf{1} - \Pi^A) \odot y_j, \tag{6}$$

where $\Pi_{c,d,h,w}^A \equiv \Pi_{d,h,w}^R$, indicating that the same masking operation is performed on each channel of the affinity graph.

Fig. 3. Semi-supervised neuron segmentation. (a) Training. Initially, representative and diverse sub-volumes are extracted and annotated from the unlabeled EM volume. All data resources are then fully exploited through intra- and inter-dataset mixing. On this basis, we reinforce cross-view consistency to encourage shared semantic learning across datasets. (b) Inference. The trained network first predicts affinities for EM volume. After over-segmentation via watershed transform, graph-based agglomeration is adopted to group supervoxels for instance segmentation.

Fig. 4. Axial-through mixing. The lower resolution of anisotropic EM volume in the axial direction (Axial: 30 *nm*, Tangential: 6 *nm*) brings semantic confusion in axial-affinities when using a regular 3D mixing strategy (top), leading to performance degradation of the segmentation network. Axial-through strategy (bottom) avoids drastic changes in the affinity values and mixes the neuron structures from x_i and x_j.

3.2.2. Cross-view Consistency Learning

Given that architectural design is not the primary focus, we utilize a modified 3D U-Net as the segmentation network $S(\cdot)$, which is widely used in neuron segmentation in anisotropic EM data Lee et al. (2017, 2021); Huang et al. (2022). During training, two labeled pairs $\{(l_1, y_1), (l_2, y_2)\}$ and two unlabeled inputs $\{u_1, u_2\}$ are randomly cropped from D_l and D_u. M_i denotes the mixing operation with the masking matrix Π_i. Random data augmentation (including Gaussian blurring, simulated misalignment, Gaussian noise, randomly masked pixels, and photometric perturbation) is performed before mixing, providing diverse combinations of augmented views. As in Fig. 3, the supervision signal is built on intra- and inter-dataset mixing. Specifically,

Intra-dataset mixing. To maximize the utility of limited annotations and facilitate network adaptation to cross-view inputs, the mixing strategy is employed within both labeled and unlabeled datasets. For labeled data, the supervised loss $\mathcal{L}^L_{Intra}$ is

defined as follows,

$$\mathcal{L}^L_{Intra} = \mathcal{L}_{CE}(S(M^R_1(\widetilde{l_1}, \widetilde{l_2})), M^A_1(y_1, y_2)), \tag{7}$$

where $\mathcal{L}_{CE}$ represents cross entropy loss, $\widetilde{l_1}$ and $\widetilde{l_2}$ are randomly augmented views of l_1 and l_2, respectively.

We leverage unlabeled data by imposing consistency constraints between predictions of perturbated and original inputs. Specifically, the pseudo labels for randomly augmented inputs $\widetilde{u_1}$ and $\widetilde{u_2}$ are computed by $S(u_1)$ and $S(u_2)$, and thus the cross-view consistency loss for unlabeled data is given by

$$\mathcal{L}^U_{Intra} = \mathcal{L}_{SE}(S(M^R_2(\widetilde{u_1}, \widetilde{u_2})), M^A_2(\underline{S(u_1)}, \underline{S(u_2)})), \tag{8}$$

where $\mathcal{L}_{SE}$ represents square error loss.

Inter-dataset mixing. Spatial mixing is also performed across datasets to connect labeled and unlabeled data. In detail, the annotated area in the mixed image $M^R_3(\widetilde{l_1}, \widetilde{u_1})$ is supervised under label map y_1, while the unlabeled area with the pseudo label $S(u_1)$. $\Pi^A_3 \in \{0, 1\}^{C \times D \times H \times W}$ is a binary mask for the affinity graph, which indicates whether the voxel comes from labeled part (1) or unlabeled part (0) under M^R_3. Therefore, the supervision signal of the mixed image can be divided into two parts, denoted as $\mathcal{L}^L_{Inter}$ and $\mathcal{L}^U_{Inter}$, respectively. Formally,

$$\mathcal{L}^L_{Inter} = \Pi^A_3 \odot \mathcal{L}_{CE}(S(M^R_3(\widetilde{l_1}, \widetilde{u_1})), y_1), \tag{9}$$

$$\mathcal{L}^U_{Inter} = (1 - \Pi^A_3) \odot \mathcal{L}_{SE}(S(M^R_3(\widetilde{l_1}, \widetilde{u_1})), \underline{S(u_1)}). \tag{10}$$

Given that expert-annotated masks for labeled patches are typically more accurate than soft pseudo labels assigned to unlabeled patches, we apply λ as a weighting coefficient to balance the contribution of labeled and unlabeled data. The full loss function is formally given by,

$$\mathcal{L}_{Semi} = \mathcal{L}^L_{Intra} + \mathcal{L}^L_{Inter} + \lambda(\mathcal{L}^U_{Intra} + \mathcal{L}^U_{Inter}). \tag{11}$$

Warming-up. Consistency regularization operates effectively when applied to meaningful predictions of unlabeled

data. However, achieving this condition can be challenging when the weights of the segmentation network are randomly initialized. To prevent convergence to sub-optimal solutions, we first train the network with $\mathcal{L}_{Intra}^{L}$, and then fine-tune it with the complete loss function.

4. Experiments setup

4.1. Dataset

The experimental evaluations are conducted on two representative and competitive public datasets with different visual appearances and spatial resolutions, *i.e.*, AC3/AC4, CREMI. Moreover, Kasthuri is utilized to evaluate the practical application value of the pipeline on large-scale datasets.

AC3/AC4[1]. This dataset consists of two densely labeled subsets of the Kasthuri[2] dataset Kasthuri et al. (2015), which was imaged from the mouse somatosensory cortex by scanning EM (SEM). AC3 and AC4 consist of 256 and 100 sequential images of size 1024×1024, respectively, at $6 \times 6 \times 29$ nm^3 voxel resolution. To ensure the reliability of the experimental results, we carefully divide them into two parts: the bottom 100 layers of AC3 and the complete 100 layers of AC4 are used to simulate unlabeled data D_u; the top 100 layers of AC3 are used for testing. Notably, the myelin regions in AC3/AC4 annotations are ignored, leading to confusion in boundary learning. Therefore, we adopt a revised version of annotation for AC4 with myelin annotation (*i.e.*, the training set of SNEMI[3]) and restrict all algorithms to select sub-volumes (D_l) from AC4 only. The sub-volume size for AC3/AC4 datasets is set as $18 \times 380 \times 380$.

CREMI[4]. The CREMI dataset comes from an adult Drosophila brain, imaged using serial section transmission EM (TEM) at a resolution of $4 \times 4 \times 40$ nm^3. The CREMI dataset comprises three labeled subsets (CREMI-A/B/C), each containing 125 sequential images associated with different regions. Since CREMI-A features a homogenous neuron pattern, our experiments employ the CREMI-B/C dataset. Similarly, we divide them into two parts: the top 60 layers of CREMI-B and CREMI-C are considered unlabeled data, denoted as D_u; the bottom 60 layers are used for testing. We select and label sub-volumes (D_l) of size $18 \times 340 \times 340$ from D_u. Moreover, the unlabeled set of CREMI, *i.e.* CREMI-B+/C+, is used for the investigation of distribution mismatch in Sec. 5-C.

Kasthuri. The size of the Kasthuri dataset is $1850 \times 10747 \times 12895$, with a voxel resolution of $6 \times 6 \times 29$ nm^3. Our method is evaluated on a sparsely annotated subset cropped from the Kasthuri15 dataset, measuring 300×4096×4096. The bounding box of this volume ranges from (1050, 6500, 3200) to (1350, 10596, 7296). In the experiments, the top 200 layers serve as unlabeled data (D_u), while the bottom 100 layers are designated as the test data. Since the myelin regions are also ignored in official annotations, we select labeled sub-volumes (D_l) sized

---

[1]https://lichtman.rc.fas.harvard.edu/vast/AC3AC4Package.zip
[2]https://neurodata.io/data/kasthuri15
[3]https://snemi3d.grand-challenge.org
[4]https://cremi.org

$18 \times 380 \times 380$ from the training set of SNEMI based on embeddings of the unlabeled volume D_u.

4.2. Evaluation Metrics

Two widely-used metrics for neuron segmentation Funke et al. (2018); Sheridan et al. (2022); Lee et al. (2021); Huang et al. (2022), the variation of information VI Nunez-Iglesias et al. (2013) and adapted Rand error ARAND Arganda-Carreras et al. (2015), are adopted to evaluate the results.

VI is defined as a sum of the conditional entropies H($\cdot|\cdot$) between the segmentation proposal A and the ground truth T, and can be broken down into two distinct components as

$$\text{VI} = \text{VI}_s + \text{VI}_m = \text{H}(S|T) + \text{H}(T|S) \tag{12}$$

where VI_s and VI_m, corresponding to split and merge errors, respectively. Define p_{ij} as the probability that a randomly selected voxel belongs to the segment i in A and the segment j in T, the ARAND is formally given by

$$\text{ARAND} = 1 - \frac{2 \sum_{ij} p_{ij}^2}{\sum_i (\sum_j p_{ij}^2)^2 + \sum_j (\sum_i p_{ij}^2)^2} \tag{13}$$

Lower values correspond to higher segmentation quality in both metrics. The background is ignored when evaluating.

4.3. Implementation Details

All models are trained on 2 NVIDIA RTX 3090 GPUs using Adam optimizer. The input patch size is fixed at $18 \times 160 \times 160$, the batch size is 4, and the learning rate is set as 1e-4 during unsupervised and semi-supervised training. For selective labeling, the discretization of unlabeled volume is implemented by sliding window cropping with a stride of $8 \times 40 \times 40$. The dimension of the embedding space L is 80, and the number of neighbors K in CCR is set as 30. For semi-supervised learning, the segmentation network is the residual symmetric U-Net (RSU-Net) proposed in Lee et al. (2017) that is widely adopted in neuron segmentation. We employ the rectangle and quarter masking strategies in spatial mixing. The weighting coefficient λ in $\mathcal{L}_{semi}$ is set as 0.2. The affinity graph has three channels (*i.e.*, $C = 3$), each representing the likelihood between a pixel and its nearest neighbors along the z, x, and y directions. Once the affinity map is predicted, we obtain the instance segmentation with two commonly adopted approaches, Multicut Beier et al. (2017) and Waterz Funke et al. (2018).

5. Results

5.1. Effectiveness of Selective Labeling for Sub-volumes

In the following, we perform a comparative study on AC3/AC4 and CREMI datasets to confirm the superiority of the proposed sub-volume selection algorithm.

Table 1. The quantitative comparisons of selective labeling strategies on the AC3/AC4 and CREMI datasets.

Methods			Multicut Beier et al. (2017)				Waterz Funke et al. (2018)			
			$VI_s \downarrow$	$VI_m \downarrow$	$VI \downarrow$	ARAND ↓	$VI_s \downarrow$	$VI_m \downarrow$	$VI \downarrow$	ARAND ↓
AC3/AC4	Patch-level	*Random*	0.9042	0.3883	1.2925	0.1477	0.9822	0.3837	1.3659	0.1637
		Equispaced	0.9459	0.3270	1.2729	0.1224	0.9441	0.3249	1.2690	0.1220
		K-means	0.9818	0.5333	1.5152	0.2147	0.9859	0.4220	1.4079	0.1401
		K-media Kolluru et al. (2021)	0.9826	0.3037	1.2863	0.1245	0.9467	0.3692	1.3159	0.1602
		FPS Jin et al. (2022)	0.9594	0.3583	1.3177	0.1225	0.9314	0.3769	1.3083	<u>0.1177</u>
		RA Zheng et al. (2019)	0.9424	0.3091	1.2515	0.1158	0.9212	0.2999	1.2211	0.1193
		USL Wang et al. (2022a)	0.8997	0.3507	1.2504	0.1201	0.8974	0.3678	1.2651	0.1288
	Sub-volume	*Random*	0.8774	0.3256	1.2030	0.1182	0.8915	0.3417	1.2307	0.1432
		Equlispaced	0.8407	0.3430	1.1837	0.1189	0.8520	0.3986	1.2506	0.1499
		CGS (FD)	0.8733	0.2888	<u>1.1622</u>	<u>0.1150</u>	0.9000	0.2958	<u>1.1958</u>	0.1239
		CGS (Ours)	0.8546	0.2717	**1.1263**	**0.1103**	0.7705	0.3196	**1.0901**	**0.1144**
		Δ ↑	-	-	+6.4%	+6.7%	-	-	+11.4%	+20.1%
CREMI	Patch-level	*Random*	1.0034	0.9599	1.9633	0.2280	1.2531	1.4793	2.7324	0.3742
		Equispaced	1.0014	0.8144	1.8158	0.2026	1.0643	1.1739	2.2382	0.3161
		K-means	1.0656	0.8106	1.8761	0.2240	1.1551	1.2520	2.4070	0.3061
		K-media Kolluru et al. (2021)	0.9511	0.7897	1.7407	0.2034	1.1473	1.3617	2.5090	0.3919
		FPS Jin et al. (2022)	1.0391	0.8372	1.8763	0.1817	1.2892	1.3643	2.6706	0.3406
		RA Zheng et al. (2019)	0.9810	0.7769	1.7579	0.1790	1.2552	1.5709	2.8261	0.4077
		USL Wang et al. (2022a)	1.0014	0.8144	1.8158	0.2026	1.0643	1.1739	2.2381	0.3161
	Sub-volume	*Random*	0.9775	0.7039	1.6814	0.1843	1.0961	1.2460	2.3421	0.3360
		Equispaced	0.8838	0.7897	1.6735	0.1626	1.0758	1.0967	2.1725	0.3219
		CGS (FD)	0.9463	0.5881	<u>1.5326</u>	<u>0.1503</u>	1.0152	1.0728	<u>2.0880</u>	<u>0.2595</u>
		CGS (Ours)	0.9169	0.5675	**1.4843**	**0.1281**	0.9693	0.8520	**1.8208**	**0.1944**
		Δ ↑	-	-	+11.7%	+30.5%	-	-	+22.3%	+14.2%

Δ shows the gain of CGS over random sub-volume selection. **Bold** and <u>underlined</u> items indicate the first and second scoring results.

Fig. 5. Quantitative Comparisons of constrained coverage score (CCR) between CGS and random sub-volume selections on AC3/AC4 and CREMI dataset with different annotation budgets. Random selections are repeated 1000 times and shown with error bars.

5.1.1. Quantitative Comparisons

All strategies, including patch-level and sub-volume selection algorithms, are quantitatively evaluated through supervised training on the selected datasets, and their ability to reflect overall data distribution is assessed through segmentation performance. In this subsection, the labeling budget for all baseline methods applied to AC3/AC4 and CREMI datasets is set at 7.5% and 6%, respectively.

For patch-level selective labeling, we consider the following competitors: (a) Random sampling, we repeat the random selection four times under different seeds and report the average value *Random*. (b) Equispaced sampling denotes as *Equispaced*. (c) One-shot active learning methods include *K*-median Kolluru et al. (2021), *K*-means Arthur and Vassilvitskii

(2007), Farthest Point Sampling (FPS) Moenning and Dodgson (2003), Representative Annotation (RA) Zheng et al. (2019) and Consistency-based Patch Selection (CPS) Lou et al. (2022). For sub-volume selection methods, we only compare CGS with random and equispaced selection due to the lack of related research. Similarly, we repeat the random selection process four times and calculate the average value. Note that we also compare with CGS's selection under the fixed-distance coverage function (*i.e.*, each patch can represent patches within a fixed radius in the embedding space), denoted as CGS (FD).

To ensure a fair comparison, we use the same unlabeled volumes and embedding network for all the competing methods. Quantitative results provided in TABLE 1 support the following conclusions: (1) The sub-volume annotation technique achieves a significant improvement compared to patch-level annotation in neuron segmentation. Notably, even random sub-volume annotation outperforms most patch-level selection baselines. This highlights the limitations of existing OSAL methods when directly applied to volumetric EM segmentation tasks. (2) As a greedy strategy, CGS provides data selection with linear time complexity, which can effectively reflect the unlabeled distribution and produce excellent segmentation results. As in Fig. 5, the coverage rate of the CGS algorithm is significantly higher than that of random selections, and the gain increases with the rise in labeling costs. (3) The superior performance on both SEM and TEM datasets shows good adaptability and stability of the proposed heuristic. (4) The fixed-distance coverage strategy, *i.e.*, CGS (FD), fails to account for variations in the dis-

Fig. 6. UMAP projection of patch embeddings extracted by $f(\cdot)$ **on AC3/AC4 dataset.** (a) Spectral clustering results exhibit biologically meaningful distinctions (legend writes dominant structures). (b) The sub-volumes selected via CGS are represented by selected and covered vectors in the embedding space. (c) Patch examples from each distinction. (d) CGS-selected sub-volumes cover diverse and representative patches.

Table 2. Quantitative Comparisons on AC3/AC4 dataset with different sub-volume sizes with a budget of 7.5%.

Size	Method	Multicut		Waterz	
		VI ↓	ARAND ↓	VI ↓	ARAND ↓
Patch	*Random*	1.2925	0.1477	1.3659	0.1637
220 (x, y)	*Random*	1.2254	0.1432	1.2838	0.1538
	CGS	**1.1524**	**0.1138**	**1.1870**	**0.1170**
300 (x, y)	*Random*	1.1958	0.1214	1.2127	0.1406
	CGS	**1.1484**	**0.1111**	**1.1241**	**0.1121**
380 (x, y)	*Random*	1.2030	0.1182	1.2307	0.1432
	CGS	**1.1263**	**0.1103**	**1.0901**	**0.1144**
460 (x, y)	*Random*	1.1620	0.1348	1.2445	0.1744
	CGS	**1.1024**	**0.1163**	**1.1210**	**0.1130**

Bold item indicates the first scoring result.

tribution density of patch embeddings, leading to a degradation in segmentation performance compared to K-nearest coverage function.

Furthermore, we explore the influence of sub-volume size on segmentation outcomes through a comparison between CGS and random selections. We repeat the random selection four times and show the average value *Random*. The quantitative results presented in TABLE 2 demonstrate several key findings. Firstly, CGS exhibits stable performance and consistent improvements over random selections across different sizes. Secondly, when the size is too small, such as Patch and 220 (x, y), labeled data may fail to capture the continuous changes in neuronal structures, leading to suboptimal performance for both random selections and CGS. Conversely, in the case of a large size, such as 460 (x, y), randomly selected data might struggle to cover diverse and informative neuronal patterns, whereas CGS effectively mitigates this issue and demonstrates superior robustness.

5.1.2. Visualization of Selection Strategy in Feature Space

To visually demonstrate the effectiveness of CGS, we employ the UMAP to project the patch embeddings for the AC3/AC4 dataset into a two-dimensional feature space. Clustering those vectors allows for identifying biologically meaningful distinctions. We visualize the selected sub-volumes with associated

patch embeddings, *i.e.*, selected and covered vectors. As in Fig. 6, representative neural structures in the raw volume are semantically covered by the selected sub-volumes, including myelin, dendrite shaft (or soma), dendrite spine, mitochondria, vesicle cloud, and axon. The visualization demonstrates the validity and rationality of CGS in extracting informative and diverse sub-regions from EM volume.

5.2. Effectiveness of Cross-view Consistency Learning

In this subsection, we verify the state-of-the-art performance of the proposed semi-supervised paradigm, *i.e.*, IIC-Net. Experiments on AC3/AC4 and CREMI datasets are conducted on CGS-selected sub-volumes D_l and unlabeled data D_u. The labeling budget is consistent with the setting in Sec. 5-A.

5.2.1. Quantitative Comparisons

Two supervised learning methods and five semi-supervised learning methods are adopted for comparison, including (1) RSU-Net Lee et al. (2017), using only labeled data in a supervised manner, (2) RSU-Net w/ Mixing, incorporating spatial mixing for labeled data, (3) FixMatch Sohn et al. (2020), a classical semi-supervised approach that enforces consistency between unlabeled data and hard pseudo labels, (4) UA-MT Yu et al. (2019), utilizing plausible predictions to guide consistency learning, (5) SASSNet Li et al. (2020), employs an adversarial learning strategy to enforce a geometric shape constraint between the affinity maps of labeled and unlabeled data, (6) MC-Net Wu et al. (2021), proposes mutual consistency regulation to encourage low-entropy predictions, and (7) SSNS-Net Huang et al. (2022), the first semi-supervised neuron segmentation framework introducing innovative network initialization and modeling consistency between soft pseudo labels and perturbed predictions of unlabeled data. Additionally, we perform an ablation study to demonstrate the benefits of intra- and inter-dataset mixing, respectively. We consider the following variants: IIC-Net w/o Inter-mixing, where we disable $\mathcal{L}_{Inter}^{L}$ and $\mathcal{L}_{Inter}^{U}$, and IIC-Net w/o Intra-mixing, where Π in M_1 and M_3 are set as $\mathbf{1}$.

For a fair comparison, we use consistent network architecture and augmentation strategies across all baseline methods. The quantitative results under two post-processing algorithms

Table 3. The quantitative comparisons of semi-supervised methods on the AC3/AC4 and CREMI datasets.

		Methods	Multicut Beier et al. (2017)				Waterz Funke et al. (2018)			
			$VI_s \downarrow$	$VI_m \downarrow$	$VI \downarrow$	$ARAND \downarrow$	$VI_s \downarrow$	$VI_m \downarrow$	$VI \downarrow$	$ARAND \downarrow$
AC3/AC4	Sup.	RSU-Net Lee et al. (2017)	0.8546	0.2717	1.1263	0.1103	0.7705	0.3196	1.0901	0.1144
		RSU-Net *w/* Mix	0.7877	0.3482	1.1059	0.1061	0.7983	0.3144	1.1127	0.1031
	Semi.	FixMatch Sohn et al. (2020)	0.8190	0.2687	1.0876	0.1073	0.8489	0.2934	1.1424	0.1270
		UA-MT Yu et al. (2019)	0.8018	0.2645	1.0662	0.0998	0.8588	0.2886	1.1473	0.1172
		SASSNet Li et al. (2020)	0.7784	0.2914	1.0698	0.1143	0.8434	0.2467	1.0902	0.1086
		MC-Net Wu et al. (2021)	0.7945	0.2592	1.0538	0.1082	0.8329	0.2390	1.0719	0.1049
		SSNS-Net Huang et al. (2022)	0.7308	0.3166	1.0473	0.1025	0.7781	0.3113	1.0894	0.1165
		IIC-Net *w/o* Inter-mix	0.7395	0.2899	1.0293	0.1008	0.7732	0.2882	<u>1.0614</u>	**0.0960**
		IIC-Net *w/o* Intra-mix	0.7335	0.2792	<u>1.0127</u>	<u>0.0937</u>	0.8136	0.2559	1.0695	0.1072
		IIC-Net (Ours)	0.6895	0.2855	**0.9751**	**0.0922**	0.7813	0.2693	**1.0506**	<u>0.1002</u>
		Δ ↑	-	-	+13.4%	+16.4%	-	-	+3.6%	+12.4%
CREMI	Sup.	RSU-Net Lee et al. (2017)	0.9169	0.5675	1.4843	0.1281	0.9693	0.8520	1.8208	0.1944
		RSU-Net *w/* Mix	0.8462	0.6004	1.4466	0.1336	0.9451	0.8743	1.8193	0.2034
	Semi.	FixMatch Sohn et al. (2020)	0.9068	0.5406	1.4474	0.1362	0.9819	0.8659	1.8478	0.2289
		UA-MT Yu et al. (2019)	0.8966	0.5420	1.4386	<u>0.1216</u>	0.9718	0.7593	1.7311	0.1730
		SASSNet Li et al. (2020)	0.8917	0.5552	1.4469	0.1265	0.9804	0.7711	1.7514	0.1815
		MC-Net Wu et al. (2021)	0.8970	0.5409	1.4379	0.1235	0.9678	0.7537	1.7215	0.1942
		SSNS-Net Huang et al. (2022)	0.8922	0.5329	1.4251	0.1217	0.9451	0.7229	1.6679	0.1633
		IIC-Net *w/o* Inter-mix	0.8472	0.5367	1.3838	0.1229	0.9323	0.7099	1.6400	0.1831
		IIC-Net *w/o* Intra-mix	0.8767	0.4986	<u>1.3753</u>	0.1258	0.8886	0.6707	<u>1.5593</u>	<u>0.1576</u>
		IIC-Net (Ours)	0.8534	0.4992	**1.3526**	**0.1122**	0.8669	0.6830	**1.5499**	**0.1416**
		Δ ↑	-	-	+8.9%	+12.4%	-	-	+14.9%	+27.2%

Sup. and Semi. are abbreviations for supervised and semi-supervised learning. Δ shows improvements of our approach over the supervised baseline (RSU-Net). **Bold** and <u>underlined</u> items indicate the first and second scoring results, respectively.

Fig. 7. UMAP projection of patch embeddings extracted by the encoder of the segmentation network $S(\cdot)$ on AC3/AC4 dataset. (a) Distribution of learned features of labeled and unlabeled data without mixing. (b) Distribution of learned features of mixed data.

present in TABLE 3 support the following conclusions: (1) Performing spatial mixing on labeled data (RSU-Net w/ Mix) can directly improve the segmentation performance in the supervised setting. This reveals the effectiveness of mixing strategies in promoting a better understanding of neuron boundaries. (2) The superior performance of soft pseudo-labeling strategies (UA-MT, SASSNet, MC-Net, SSNS-Net) substantiates its greater efficacy compared to hard pseudo-labeling (FixMatch) in semi-supervised neuron segmentation. (3) The proposed IIC-Net achieves consistent and considerable improvements over all baselines, which confirms the effectiveness of cross-view consistency regularization. (4) The performance of IIC-Net decreases when intra-dataset mixing is turned off (w/o Intra-mix), emphasizing its critical role in facilitating adaptation to mixed inputs. Notably, when inter-dataset mixing (w/o Inter-mix) is disabled, the performance drops even more. Such results sug-

gest that inter-mixing serves as a key factor. It connects labeled and unlabeled datasets and encourages the network to learn shared semantics.

5.2.2. Visualization of Mixing Strategy in Feature Space

We make a UMAP projection for learned features of the segmentation network before and after dataset mixing on the AC3/AC4 dataset. As in Fig. 7, the mixing strategy, including intra- and inter-mixing, further bridges the distribution gap between CGS-selected labeled sub-volume and unlabeled data, paving the way for more effective semi-supervised learning.

5.3. Investigation of Distribution Mismatch

In the following, we conducted semi-supervised training with IIC-Net on the AC3/AC4 and CREMI datasets under different data settings to investigate the impact of the mismatch between labeled and unlabeled distributions.

Building on the conclusions from Sec. 5-A, the labeled data (D_l) selected by CGS can ensure a matching distribution with the original unlabeled dataset (D_u), establishing a baseline (Match) for other data combinations. For comparison, we introduce mismatch by changing labeled and unlabeled distributions respectively: (1) Fix the unlabeled data and randomly change the labeled data. These labeled sub-volumes are randomly cropped from the original unlabeled datasets four times under the same budget. (2) Fix the labeled data and randomly change the unlabeled data. For AC3/AC4, we took eight unlabeled volumes of size 100×1024×1024 from the Kasthuri dataset; for CREMI, we randomly cropped eight unlabeled volumes from

Table 4. Investigation of distribution mismatch by changing labeled and unlabeled data on AC3/AC4 and CREMI dataset.

	Methods		Multicut Beier et al. (2017)				Waterz Funke et al. (2018)			
			$VI_s \downarrow$	$VI_m \downarrow$	$VI \downarrow$	ARAND $\downarrow$	$VI_s \downarrow$	$VI_m \downarrow$	$VI \downarrow$	ARAND $\downarrow$
AC3/AC4	Match	D_l (CGS), D_u	0.6895	0.2855	**0.9751**	**0.0922**	0.7813	0.2693	**1.0506**	**0.1002**
	Mismatch	Changing Labeled Data	0.7765	0.2929	1.0694	0.1036	0.8229	0.2978	1.1207	0.1088
		Changing Unlabeled Data	0.8061	0.3077	1.0629	0.1107	0.8043	0.3146	1.1189	0.1141
CREMI	Match	D_l (CGS), D_u	0.8534	0.4992	**1.3526**	**0.1122**	0.8669	0.6830	**1.5499**	**0.1416**
	Mismatch	Changing Labeled Data	0.8349	0.5418	1.3767	0.1264	0.8727	0.7904	1.6631	0.2006
		Changing Unlabeled Data	0.8762	0.5550	1.4313	0.1362	0.9349	0.7879	1.7227	0.1990

Mismatch shows the mean performance of four random selection experiments. **Bold** item indicates the first scoring result.

Table 5. Evaluation on Kasthuri15 with the proposed pipeline.

Budget	SL	SSL	$VI \downarrow$	ARAND $\downarrow$
10%	CGS	*w/o*	0.8540	0.1810
	CGS	IIC-Net	0.8100	0.1741
	-	-	+5.15%	+3.81%
20%	CGS	*w/o*	0.8236	0.1795
	CGS	IIC-Net	0.7842	0.1710
	-	-	+4.78%	+4.74%
100%	*w/o*	*w/o*	0.7751	0.1731
	w/o	IIC-Net	0.7362	0.1632
	-	-	+5.02%	+5.72%

SL and SSL denote selective labeling and semi-supervised learning. Multicut Beier et al. (2017) algorithm is adopted for graph-based agglomeration.

Table 6. Quantitative Comparisons on AC3/AC4 dataset using different label budgets.

Budget	SL	SSL	$VI \downarrow$	ARAND $\downarrow$
5%	*Random**	*w/o*	1.4155	0.2082
	*Random**	IIC-Net	1.0745	0.1422
	CGS	*w/o*	1.2458	0.1468
	CGS	SSNS-Net	<u>1.0680</u>	<u>0.1220</u>
	CGS	IIC-Net	**1.0436**	**0.1107**
7.5%	*Random**	*w/o*	1.1608	0.1135
	*Random**	IIC-Net	<u>1.0225</u>	0.1057
	CGS	*w/o*	1.1263	0.1103
	CGS	SSNS-Net	1.0473	<u>0.1025</u>
	CGS	IIC-Net	**0.9751**	**0.0922**
10%	*Random**	*w/o*	1.0649	0.0998
	*Random**	IIC-Net	<u>0.9753</u>	0.1053
	CGS	*w/o*	1.0343	0.0953
	CGS	SSNS-Net	1.0110	<u>0.0936</u>
	CGS	IIC-Net	**0.9688**	**0.0899**
100%	*w/o*	*w/o*	**0.9583**	**0.0899**

SL and SSL denote selective labeling and semi-supervised learning. Multicut Beier et al. (2017) algorithm is used for post-processing. **Bold** and <u>underlined</u> items indicate the first and second scoring results, respectively.

CREMI-B+/C+, each containing 60 sequential images. Both are grouped equally into four sets.

The quantitative results, as depicted in TABLE 4, indicate that: (1) Mismatched distribution hinders the generalization of segmentation models and leads to significant degradation in performance. (2) The CGS algorithm provides a practical and effective solution for the mismatch problem in semi-supervised neuron segmentation from the data level.

5.4. Evaluation on Large-scale Data

In this section, we conduct the proposed pipeline, *i.e.* selective labeling via CGS, and semi-supervised training via IIC-Net, on the Kasthuri dataset to study the practical value of the proposed method in large-scale neuron reconstruction.

Quantitative results are shown in TABLE 5. The performance of the fully supervised method (VI: 0.7751, ARAND: 0.1731) is matched by the proposed pipeline with only 20% of labeled data (VI: 0.7842, ARAND: 0.1710), which demonstrate the effectiveness of cooperation between selective labeling and semi-supervised training. In addition, under the same labeling budget including 100%, IIC-Net achieves consistent improvements over the supervised baseline on the segmentation results. Since expert proofreading is extremely time-consuming and expensive, semi-supervised training can reduce reconstruction costs with more robust predictions under the same labeling budget, which holds great potential in cost-effective connectomics.

5.5. Collaboration between Selective Labeling and Semi-supervised Training

After evaluating the effectiveness of selective labeling and cross-view consistency learning individually, we explore how these work together for cost-effective neuron segmentation in different labeling budgets. This subsection can be regarded as an ablation study of the proposed pipeline.

We gradually increase the labeling cost on AC3/AC4 and evaluate the performance under supervised and semi-supervised settings. For selective labeling, we compare CGS with random sub-volume selection, and the optimal result under four experiments is reported, denoted as *Random**. For semi-supervised learning, we adopt the most representative baseline, SSNS-Net Huang et al. (2022), for comparison. The results under Multicut post-processing are presented in TABLE 6. The proposed framework, utilizing labeled data selected via CGS and a segmentation network trained by IIC-Net, demonstrates consistent improvements over other combinations across all annotation budgets. It achieves comparable performance with fully supervised methods, even with only 10% labeled data on the

Fig. 8. 2D visual comparison of affinity (left) and segmentation (right) results on the AC3/AC4 dataset with labeling cost of 7.5%. The red and yellow boxes represent merge and split errors, respectively. Multicut Beier et al. (2017) algorithm is adopted for graph-based agglomeration.

Ground Truth   CGS + IIC-Net   *Random**+ IIC-Net   CGS+ SSNS-Net

Fig. 9. 3D visual comparison of segmentation results on the AC3/AC4 dataset with labeling cost of 7.5%. The red and yellow arrows represent merge and split errors, respectively. Multicut Beier et al. (2017) algorithm is adopted for graph-based agglomeration.

AC3/AC4 dataset. Also, we provide both 2D and 3D visual comparisons in Fig. 8 and Fig. 9, respectively. The proposed method shows significant advantages in maintaining the precise connectivity of reconstructed structures.

6. Summary and Discussion

Automatic neuron segmentation produces merge and split errors, which require years of manual proofreading before they can be used for connectivity analysis. Semi-supervised learning offers a pathway to enhance segmentation accuracy through the utilization of easily available unlabeled data.

This study introduces a novel semi-supervised pipeline designed specifically for 3D neuron segmentation in electron microscopy volumes. By integrating selective labeling and cross-view consistency regularization, we mitigate the mismatch between labeled and unlabeled distributions for more effective semi-supervised learning. Extensive experiments validate the method's superiority and generalizability, demonstrating its potential to reduce the manual workload and expedite scientific analysis in connectomics.

As there are still some limitations of this pipeline, the opportunities to improve them fall into three aspects:

1. Given the added expense of retraining the embedding network on unseen datasets, we aim to design a generalist embedding model for volumetric EM data. This model will not only support coverage-based selective labeling but also facilitate the discovery and analysis of local patterns from unlabeled EM data.

2. Noisy regions in pseudo labels can substantially degrade the performance of semi-supervised models. Hence, we will investigate a denoising technique for pseudo-labels in affinity graphs for neuron instance segmentation to enhance consistency learning.

3. While OSAL demonstrates computational efficiency, integrating ITAL technology with semi-supervised training for neuron segmentation can leverage both model performance feedback and data distribution to improve labeled data selection, potentially enhancing segmentation accuracy for large-scale reconstructions.

Acknowledgments

This work was supported in part by the STI 2030–Major Projects under Grant 2021ZD0204500 and Grant 2021ZD0204503, in part by the National Natural Science Foundation of China under Grant 32171461 and in part by the Scientific Research Instrument and Equipment Development Project of Chinese Academy of Sciences under Grant YJKYYQ20210022.

References

Abbott, L.F., et al., 2020. The mind of a mouse. Cell 182, 1372–1376.

Arganda-Carreras, I., et al., 2015. Crowdsourcing the creation of image segmentation algorithms for connectomics. Frontiers in Neuroanatomy 9, 142.

Arthur, D., Vassilvitskii, S., 2007. K-means++ the advantages of careful seeding, in: Proceedings of the eighteenth annual ACM-SIAM symposium on Discrete algorithms, pp. 1027–1035.

Bai, Y., Chen, D., Li, Q., Shen, W., Wang, Y., 2023. Bidirectional copy-paste for semi-supervised medical image segmentation, in: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pp. 11514–11524.

Beier, T., et al., 2017. Multicut brings automated neurite segmentation closer to human performance. Nature Methods 14, 101–102.

Berthelot, D., Carlini, N., Goodfellow, I., Papernot, N., Oliver, A., Raffel, C.A., 2019a. Mixmatch: A holistic approach to semi-supervised learning. Advances in Neural Information Processing Systems 32.

Berthelot, D., et al., 2019b. Remixmatch: Semi-supervised learning with distribution matching and augmentation anchoring, in: International Conference on Learning Representations.

Chen, X., He, K., 2021. Exploring simple siamese representation learning, in: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pp. 15750–15758.

Çiçek, Ö., Abdulkadir, A., Lienkamp, S.S., Brox, T., Ronneberger, O., 2016. 3d u-net: learning dense volumetric segmentation from sparse annotation, in: International Conference on Medical Image Computing and Computer Assisted Intervention, Springer. pp. 424–432.

Dorkenwald, S., , et al., 2023. Neuronal wiring diagram of an adult brain. bioRxiv .

Dorkenwald, S., McKellar, C.E., Macrina, T., Kemnitz, N., Lee, K., Lu, R., Wu, J., Popovych, S., Mitchell, E., Nehoran, B., et al., 2022. Flywire: online community for whole-brain connectomics. Nature methods 19, 119–128.

French, G., Laine, S., Aila, T., Mackiewicz, M., Finlayson, G.D., 2019. Semi-supervised semantic segmentation needs strong, varied perturbations. British Machine Vision Conference .

Funke, J., et al., 2018. Large scale image segmentation with structured loss based deep learning for connectome reconstruction. IEEE Transactions on Pattern Analysis and Machine Intelligence 41, 1669–1680.

Huang, W., et al., 2022. Semi-supervised neuron segmentation via reinforced consistency learning. IEEE Transactions on Medical Imaging 41, 3016–3028.

Januszewski, M., et al., 2018. High-precision automated reconstruction of neurons with flood-filling networks. Nature Methods 15, 605–610.

Jin, Q., Yuan, M., Qiao, Q., Song, Z., 2022. One-shot active learning for image segmentation via contrastive learning and diversity-based sampling. Knowledge-Based Systems 241, 108278.

Kasthuri, N., et al., 2015. Saturated reconstruction of a volume of neocortex. Cell 162, 648–661.

Kolluru, C., Lee, J., Gharaibeh, Y., Bezerra, H.G., Wilson, D.L., 2021. Learning with fewer images via image clustering: Application to intravascular oct image segmentation. IEEE Access 9, 37273–37280.

Lee, K., Lu, R., Luther, K., Seung, H.S., 2021. Learning and segmenting dense voxel embeddings for 3d neuron reconstruction. IEEE Transactions on Medical Imaging 40, 3801–3811.

Lee, K., Zung, J., Li, P., Jain, V., Seung, H.S., 2017. Superhuman accuracy on the snemi3d connectomics challenge. arXiv:1706.00120 .

Li, S., Zhang, C., He, X., 2020. Shape-aware semi-supervised 3d semantic segmentation for medical images, in: Medical Image Computing and Computer Assisted Intervention, Springer. pp. 552–561.

Lin, Z., et al., 2020. Two stream active query suggestion for active learning in connectomics, in: European Conference on Computer Vision, Springer. pp. 103–120.

Liu, J., et al., 2022. Fear memory-associated synaptic and mitochondrial changes revealed by deep learning-based processing of electron microscopy data. Cell Reports 40.

Lou, W., Li, H., Li, G., Han, X., Wan, X., 2022. Which pixel to annotate: a label-efficient nuclei segmentation framework. IEEE Transactions on Medical Imaging 42, 947–958.

Luo, X., Chen, J., Song, T., Wang, G., 2021. Semi-supervised medical image segmentation through dual-task consistency, in: Proceedings of the AAAI Conference on Artificial Intelligence, pp. 8801–8809.

Mannix, E.J., Bondell, H.D., 2023. Cold paws: Unsupervised class discovery and the cold-start problem. arXiv:2305.10071 .

Meirovitch, Y., Mi, L., Saribekyan, H., Matveev, A., Rolnick, D., Shavit, N., 2019. Cross-classification clustering: An efficient multi-object tracking technique for 3-d instance segmentation in connectomics, in: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pp. 8425–8435.

Moenning, C., Dodgson, N.A., 2003. Fast marching farthest point sampling for implicit surfaces and point clouds. Computer Laboratory Technical Report 565, 1–12.

Ngai, J., 2022. Brain 2.0: Transforming neuroscience. Cell , 4–8.

Nunez-Iglesias, J., Kennedy, R., Parag, T., Shi, J., Chklovskii, D.B., 2013. Machine learning of hierarchical clustering to segment 2d and 3d images. PloS one 8, e71715.

Russakovsky, O., et al., 2015. Imagenet large scale visual recognition challenge. International Journal of Computer Vision 115, 211–252.

Scheffer, L.K., et al., 2020. A connectome and analysis of the adult drosophila central brain. Elife 9, e57443.

Schmidt, M., Motta, A., Sievers, M., Helmstaedter, M., 2024. Roboem: automated 3d flight tracing for synaptic-resolution connectomics. Nature Methods , 1–6.

Sener, O., Savarese, S., 2018. Active learning for convolutional neural networks: A core-set approach, in: International Conference on Learning Representations.

Shapson-Coe, A., et al., 2024. A petavoxel fragment of human cerebral cortex reconstructed at nanoscale resolution. Science 384, eadk4858.

Sheridan, A., et al., 2022. Local shape descriptors for neuron segmentation. Nature Methods , 1–9.

Shi, Y., et al., 2021. Inconsistency-aware uncertainty estimation for semi-supervised medical image segmentation. IEEE Transactions on Medical Imaging 41, 608–620.

Sohn, K., et al., 2020. Fixmatch: Simplifying semi-supervised learning with consistency and confidence. Advances in Neural Information Processing Systems 33, 596–608.

Wang, Q., Li, W., Gool, L.V., 2019. Semi-supervised learning by augmented distribution alignment, in: Proceedings of the IEEE/CVF International Conference on Computer Vision, pp. 1466–1475.

Wang, X., Lian, L., Yu, S.X., 2022a. Unsupervised selective labeling for more effective semi-supervised learning, in: European Conference on Computer Vision, Springer. pp. 427–445.

Wang, X., et al., 2022b. Ssa-net: Spatial self-attention network for covid-19 pneumonia infection segmentation with semi-supervised few-shot learning. Medical Image Analysis 79, 102459.

Wu, Y., Xu, M., Ge, Z., Cai, J., Zhang, L., 2021. Semi-supervised left atrium segmentation with mutual consistency training, in: Medical image computing and computer assisted intervention, Springer. pp. 297–306.

Yang, L., Zhang, Y., Chen, J., Zhang, S., Chen, D.Z., 2017. Suggestive annotation: A deep active learning framework for biomedical image segmentation, in: International Conference on Medical Image Computing and Computer Assisted Intervention, Springer. pp. 399–407.

Yang, L., Zhuo, W., Qi, L., Shi, Y., Gao, Y., 2022. St++: Make self-training work better for semi-supervised semantic segmentation, in: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pp. 4268–4277.

Yu, L., Wang, S., Li, X., Fu, C.W., Heng, P.A., 2019. Uncertainty-aware self-ensembling model for semi-supervised 3d left atrium segmentation, in: International Conference on Medical Image Computing and Computer Assisted Intervention, Springer. pp. 605–613.

Yun, S., Han, D., Oh, S.J., Chun, S., Choe, J., Yoo, Y., 2019. Cutmix: Regularization strategy to train strong classifiers with localizable features, in: Proceedings of the IEEE/CVF International Conference on Computer Vision, pp. 6023–6032.

Zhao, X., et al., 2023. Rcps: Rectified contrastive pseudo supervision for semi-supervised medical image segmentation. IEEE Journal of Biomedical and Health Informatics .

Zheng, H., Yang, L., Chen, J., et al., 2019. Biomedical image segmentation via representative annotation, in: Proceedings of the AAAI Conference on Artificial Intelligence, pp. 5901–5908.

Zheng, Z., et al., 2018. A complete electron microscopy volume of the brain of adult drosophila melanogaster. Cell 174, 730–743.