Mapping and modeling

the semantic space of math concepts

6 Samuel Debray[1*], Stanislas Dehaene[1,2*]

[1] Cognitive Neuroimaging Unit, Institut National de la Santé et de la Recherche Médicale,

Commissariat à l'Energie Atomique et aux énergies alternatives, Centre National de la

Recherche Scientifique, Université Paris-Saclay, NeuroSpin center, Gif-sur-Yvette, France

[2] Collège de France, Université Paris Sciences & Lettres, Paris, France

* Corresponding author

E-mail: samuel.debray@ens-paris-saclay.fr (SaD) or stanislas.dehaene@cea.fr (StD)

Abstract

Mathematics is an underexplored domain of human cognition. While many studies have focused on subsets of math concepts such as numbers, fractions, or geometric shapes, few have ventured beyond these elementary domains. Here, we attempted to map out the full space of math concepts and to answer two specific questions: can distributed semantic models, such a GloVe, provide a satisfactory fit to human semantic judgments in mathematics? And how does this fit vary with education? We first analyzed all of the French and English Wikipedia pages with math contents, and used a semi-automatic procedure to extract the 1,000 most frequent math terms in both languages. In a second step, we collected extensive behavioral judgments of familiarity and semantic similarity between them. About half of the variance in human similarity judgments was explained by vector embeddings that attempt to capture latent semantic structures based on cooccurence statistics. Participants' self-reported level of education modulated familiarity and similarity, allowing us to create a partial hierarchy among high-level math concepts. Our results converge onto the proposal of a map of math space, organized as a database of math terms with information about their frequency, familiarity, grade of acquisition, and entanglement with other concepts.

Author summary

Most studies in mathematical cognition focus on subdomains such as numbers, fractions, or geometric shapes. A broader picture of the full extent of mathematical cognition is lacking. Here, as a first step, we use behavioral and computational methods to create a comprehensive vocabulary of advanced math. We prove that statistical cooccurence vectors from large corpora (Wikipedia) provide an approximation of the meaning and organization of these concepts, as measured by human similarity ratings in participants of varying levels of education. Results are similar in French and in English, suggesting that our findings do not

44 depend on the language. In future work, we plan to leverage this vocabulary to explore the

45 brain mechanism of math cognition at various levels of expertise.

Introduction

Mathematical cognition is a vast domain of human knowledge, essential to daily life as

well as to scientific inquiry, and yet vastly underexplored compared to other domains of

language or culture. Most cognitive studies tackle specific and narrow subdomains of

elementary mathematics such as integers (1–4), fractions (5–7) or geometric shapes (8–10),

and only a few researchers have explored higher-level mathematical concepts in professional

mathematicians (11,12). Without attempting to perform an extensive review, it seems fair to

say that, in between those two extremes lies a vast space of mathematical concepts that

remains largely unexplored from the cognitive viewpoint, to such an extent that they are not

even systematically listed. Although a few dictionaries of mathematical concepts are available

(13,14), they are often technical, aimed for experts, and therefore uneasy to use as a lexical

source for cognitive research.

Here, our goal is to take a first step towards a systematic study of the basic vocabulary

of math cognition and how it varies with education, ranging from primary school to university

level concepts. Inspired by the *THINGS* initiative (15), where researchers from different labs

collectively gathered a large database on object recognition including behavioral similarity

judgements, fMRI, MEG and EEG (in humans and non-human primates) studies as well as

modeling by deep neural networks, we started by creating a dataset of 1,000 mathematical

words that could then be used for future studies using behavioral and brain imaging methods.

Importantly, we used an unbiased computational method, GloVe (16), to analyze a large

mathematical corpus and extract the most frequent words for mathematical concepts, with the

goal to obtain an objective picture of the space of math concepts.

From this first step, we obtained a lexicon of the most frequent math concepts, their

frequency, their tentative age of acquisition, and a vector-based representation of their

putative semantics, based on distributional cooccurence statistics. We then aimed to provide

a first test of the cognitive validity of these measures. To this aim, we collected ratings of

semantic similarity, which are often used as a marker of the organization of mental

representations. This idea dates back to the seminal work of Shepard and Chipman (17).

Using the principle of second order isomorphism – which states that there is a relation between

the similarities of the internal representation of two objects and the similarities of the

corresponding external objects – one can construct psychological representations of the

structure of a set of stimuli by collecting subjective similarity measures and analyzing them,

for instance using multi-dimensional scaling (18) or more sophisticated feature-reconstruction

methods (19). This approach was first applied to numbers by Shepard et al. (1), who presented

pairs of numbers to participants in various notations (e.g. Arabic numerals, number words, dot

patterns) and asked them to rate their conceptual similarity. They showed that the similarity

ratings only depended on the judgment task, not the original notation, and that MDS enabled

retrieving a conceptual space for the numbers, organized by interpretable semantic

dimensions such as number magnitude and odd-even status.

The idea that mental objects, including high-level concepts, are encoded by vectors in

a multi-dimensional mental space later became influential in both neuroscience (20) and

computational semantics (21). Latent Semantic Analysis (22) was one of the earliest methods

to obtain semantic vector embedding for words. Since then, many algorithms and similarity

measures have been proposed in order to compare human judgements with distributed

semantic representations (19,23–25). Importantly, distributed semantic representations have

also been shown to capture context-dependent information about specific semantic

dimensions such as size or dangerosity, which also compares favorably to human judgements

(26). Finally, beyond behavioral judgements, such embeddings have also been shown to

predict neuroimaging data (27–31). Recently, the use of context-dependent embeddings from

large language models has permitted an even better fit to brain activity during sentence

processing (32–36).

Here, we extend this logic to math concepts. We asked people to provide similarity

ratings between pairs of math words, and compared these similarities with those predicted by

semantic embeddings learnt by the GloVe algorithm on a large math corpus. Although it may

seem obvious that math concepts should behave similarly to other concepts, brain imaging

indicates that math sentences activate a network of brain areas entirely different from classical

language regions (11,37,38), thus leaving open the possibility that a different logic or language

may be needed to account for the mental organization of math concepts (39).

A third goal of our study was to evaluate the impact of math education on such similarity

ratings and their putative underlying vector representations. The mental representation of

math concepts changes dramatically with education (2,40–42). Using brain imaging, Amalric

and Dehaene (11) showed a drastic enhancement of brain activity in a large-scale math-

responsive network in professional mathematicians compared to other adults with more limited

math education. Longitudinal, cross-sectional, and cross-cultural comparisons indicate that

even the representation of simple integers exhibits massive change in the course of education

to counting and the number line (43–47). Here, we tested the possibility that similarity ratings

would also show a sensitivity to education and could therefore serve as a sensitive marker of

the expansion of the conceptual space of mathematics.

In summary, we aimed to provide a 1,000-word vocabulary of math concepts covering

all levels and domains. Anticipating on the results, we showed that similarity ratings collected

during an online experiment are well captured by GloVe embeddings of the concepts of the

vocabulary, and that the quality of the fit increases with participants' education. In addition, we

showed that the spatial layout of the embeddings makes sense and can be used to make

predictions about how humans organize their mental map of math concepts.

Results

Creation of a vocabulary of 1,000 words in French and English

We first created a math vocabulary of 1,000 French words by manually reviewing the 39,345 most frequent words in the French Wikipedia math articles. Then, using GloVe (16), we obtained vector embeddings for the words of this vocabulary. Three distinct embeddings were obtained from three different corpora: the above math corpus (math embedding); a non-math corpus consisting of all non-math pages of the French Wikipedia (non-math embedding); and their concatenation (global embedding) (Fig 1A). Our logic was that many words have both math and non-math meanings. For a given word, we hypothesized that its math embedding would primarily carry information about its math meaning (e.g. "ring" in the context of commutative algebra), while its non-math embedding would carry information about its meaning in everyday language (e.g. "ring" as in engagement ring). We also estimated, for each word of the vocabulary, its school grade of acquisition (hereafter referred to as "word grade") by examining in which class the corresponding concept was introduced according to the national French curriculum. Finally, we used the above corpora to obtain estimates of each word's log frequency per million in math and non-math corpora. A summary of the main characteristics of the vocabulary is provided in Table 1. The vocabulary was also translated into English, for which the same measures were obtained. The math vocabulary is available online from https://osf.io/dxg2w.

140 **Table 1. Summary of the main characteristics of the French vocabulary.** Note: Frequency

141 is expressed in Log10 units per million.

Category		Count	Mean math freq	STD math freq	Mean non math freq	STD non math freq
Word grade	*primary*	214	1.90	0.63	1.24	0.91
	6-7th grade	81	2.04	0.58	0.76	1.78
	8-9th grade	52	1.89	0.70	0.44	1.13
	10th grade	60	1.83	0.68	0.44	1.23
	11-12th grade	110	1.80	0.51	0.31	1.06
	bachelor	245	1.58	0.50	0.12	1.19
	licence	121	1.38	0.40	-1.08	2.84
	master	55	1.40	0.43	-1.61	3.85
Grammatical category	*adjective*	301	1.65	0.55	-0.13	2.39
	noun	534	1.82	0.62	0.45	1.88
	verb	56	1.62	0.49	0.84	0.79
	proper noun	126	1.39	0.38	-0.52	1.35
	adverb	10	1.45	0.42	-0.16	1.01
	number	24	1.83	0.85	1.91	0.77
	symbol	9	1.87	1.00	0.91	1.31

Figure 1. Experimental design. (A) Creation of corpora and embedding. (B) Behavioral experiment with a subset of words: familiarity and similarity ratings. (C) Relation to research questions.

Behavioral data collection

We ran a massive online experiment (n = 1230 participants) to collect familiarity ratings for a subset of 429 words of the vocabulary and similarity ratings for 3,756 pairs of these words (Fig 1B). The selected words were nouns, numbers or symbols which have a clear and precise mathematical meaning (see Methods). Our goal was to probe whether (1) the familiarity ratings from humans with different levels of education could be predicted by our estimated word grade and frequency in the math corpus; and (2) the similarity of GloVe embeddings is a good

predictor of human similarity ratings (Fig 1C). All participants gave an estimate of their math

education level, which ranged from primary school (n = 4) to PhD (n = 133) (see Methods).

This experiment was also run in English for the English vocabulary (n = 174 participants).

Before anything else, participants answered a short survey and provided their last

grade of education in mathematics and a self-assessment of their current math skills on a

scale from 1 to 10. We found a moderate relation between these two variables, both in French

(Spearman's r_S(1228) = .54, $p <$ .001) and in English (Spearman's r_S(172) = .37, $p <$ .001). For

this reason, in the rest of this work, we used participants' education as an indicator of their

math level.

163 Familiarity ratings are predicted by the estimated grade of 164 acquisition

Each participant first rated their familiarity with 50 words drawn randomly from the 429

selected for the experiment. Ratings were provided on a discrete 9-level Likert scale from 0

(totally unknown concept) to 8 (fully mastered concept) (see Fig 1 for the full calibration labels).

The results, shown in Fig 2, support two conclusions: (1) for a given participant's math

education level, familiarity ratings decrease as word grade increases; and (2) for a given word

grade, familiarity ratings increase as participant education increases.

Figure 2. Familiarity ratings as a function of participant education and word grade. Note that, for greater readability, the dependent variable (rating of word familiarity) is on the x axis. Colors represent different categories of words, sorted according to the grade at which they are introduced in the French curriculum.

We confirmed those conclusions statistically by entering all of the participants' familiarity ratings into a rank-order linear regression with participant education, word grade, word log frequency per million (in the math corpus), and their interactions as independent variables (see Methods). We found that these variables predicted familiarity ratings ($R^2 = .35$, $F(7, 61792) = 4673$, $p < .001$). All variables and their two-ways interactions were significant predictors ($p < .001$), and the three-ways interaction also was significant ($p = .02$). Out of all the predictors, word grade had the largest effect ($\beta = -1.01$, $t(61792) = -116.42$, $p < .001$): as seen on Fig 2, familiarity ratings decreased monotonically as the predicted word grade increased. This effect was modulated by a main effect of participant education ($\beta = 0.67$, $t(61792) = 77.90$, $p < .001$) indicating that familiarity ratings increased with education, and an

interaction of education and word grade (β = 0.32, t(61792) = 36.33, p < .001), revealing that

the effect of word grade was steeper in less educated participants. As can be seen on Fig 2,

familiarity ratings became much flatter, although still increasing with education, when

participants' education fell above the postulated word grade. For instance, the familiarity rating

of words assumed to be learned in 11-12th grade (green curve in Fig 2) reached a plateau

around 7 once participants' education reached or exceeded college level.

Finally, word frequency also had an effect on familiarity ratings (β = 0.33, t(61792) =

41.81, p < .001), but it was smaller than that of participant education and word grade. This

effect indicated that, over and above word grade, the more frequent a word was in the math

corpus, the more participants declared to be familiar with it. An interaction with word grade (β

= 0.36, t(61792) = 43.53, p < .001) indicated that the effect of frequency on familiarity ratings

was higher for more advanced math words, which is unsurprising because among the

advanced words, the least frequent tend to be niche words, applicable only to a narrower

domain of math, and therefore less familiar on average. There was also a small but significant

interaction of frequency with participant education, indicating that higher education attenuated

the impact of frequency (β = -0.05, t(61792) = -5.74, p < .001). This suggests that, while

familiarity with math concepts is driven by frequency for participants with little math education,

higher-level participants gained enough experience to mitigate the effect of frequency when

judging their familiarity with a given concept: for them, even rare terms can be highly familiar.

These observations were replicated in English (R^2 = .28, F(7, 8792) = 498.7, p < .001),

except for the interaction of word frequency and participant education which did not reach

significance.

Item Response Theory

Mean familiarity ratings provide only a coarse idea of how advanced a math concept

is. Likewise, a self-reported education level provides only a coarse estimate of a person's math

knowledge. Furthermore, those two parameters are linked: mean familiarity depends on the

education level of the specific participants tested. We reasoned that item-response theory

(IRT; 48) could disentangle those parameters and provide a more refined estimation of them.

IRT can jointly infer a latent ability for each participant, roughly capturing a person's math

knowledge, as well as a difficulty and a discrimination parameter for each word, evaluating

respectively the overall likelihood that a word is judged familiar, and the amount of variation in

this familiarity rating as a function of participants' math knowledge.

Because the IRT package that we used (`mirt` in R) requires dichotomous outputs, we

dichotomized the familiarity ratings into "unknown" (0, 1, 2 and 3 ratings) versus known (above

3). We reviewed manually all predictions made by the IRT algorithm and discarded 20% of all

items for which the algorithm had extreme values of discrimination or difficulty parameters

which did not fit with the data. Indeed, IRT cannot converge when human ratings are very

skewed toward one value (either always known, or always unknown). Manual review of the

data led us to only keep the first nine deciles of IRT discrimination parameters and the central

95% of IRT difficulty parameters (2.5th to 97.5th percentiles) for further analyses. After this

curation phase, we were left with 289 words out of our original 363 for which the IRT algorithm

converged. The resulting estimates are reported in the vocabulary database, and plots are

provided in File S1.

For each word tested, we obtained two difficulty estimates, based either on mean

familiarity rating or on IRT, and two discrimination estimates: the standard deviation (STD) of

familiarity ratings across participants and the IRT discrimination estimate. We then compared

the two approaches and correlated the descriptive parameters with those derived by the IRT

algorithm. We found that IRT difficulty parameter and mean familiarity rating were strongly

correlated across words (Spearman's $r_S(287) = .90$, $p < .001$). IRT difficulty parameter was

also correlated with word grade (Spearman's $r_S(287) = .51$, p < .001) and, to a lesser extent,

to word frequency (Spearman's $r_S(287) = .14$, p < .001). Likewise, the IRT-estimated

participant latent ability and the reported participant education were highly correlated across

participants (Spearman's r_S(1228) = .61, $p < .001$). However, the IRT discrimination parameter

was not well estimated by the STD of familiarity ratings ($p = .57$), suggesting that IRT indeed

provided a finer-grained approach.

We used the IRT results to manually select a subset of 80 words covering various

difficulty levels, whose discriminability was high, and which were therefore highly selective of

a given participant's math knowledge (they are flagged in the database as "80 high-

discriminability items"). In the future, we propose that collecting familiarity ratings on those

words and analyzing them with IRT could serve as a quick assessment of a participant's math

knowledge. Similarly, the word difficulty and discrimination parameters that we collected could

be used to select, within our vocabulary, a subsample of words adequate to participants of a

given education range.

GloVe embeddings predict human math similarity ratings

We then turned to the similarity rating part of the experiment. Note that, to avoid asking

ratings for unknown words, each participant only rated on a continuous Likert scale the

similarity of word pairs at or below their grade level. Thus, more educated participants were

asked to rate a large number of word pairs (20 pairs per grade level). Furthermore, for each

word, in order to cover a large spectrum of similarities, we selected 3 pairs within each of four

categories: (1) very similar pairs, as predicted by their GloVe embeddings; (2) moderately

similar pairs, close to the mean similarity; (3) pairs of words with orthogonal embeddings; (4)

pairs of words with opposite embeddings, i.e. negative cosine similarity (see Methods). This

manipulation was adopted after piloting showed that a random choice of word pairs would

have generated an excessive number of "unrelated" judgements, thus, making the task

uninteresting for participants. Furthermore, it allowed for a first test of GloVe similarity: non-

parametric Kruskal-Wallis (H(3, n = 3756) = 1520.11, $p < .001$) followed by pairwise Dunn's

tests with Bonferroni correction showed that similarity ratings showed systematic pairwise

differences across those four categories (mean ratings = 3.2, 1.9, 1.2 and 1.0 respectively; all

p's < .001). In particular, even the negative cosine pairs were rated as slightly, but significantly

less similar than orthogonal items. These observations were also replicated in English except

for the negative cosine versus orthogonal comparison (mean ratings = 2.9, 1.9, 1.5 and 1.4

respectively; non-parametric Kruskal-Wallis: $H(3, n = 2421) = 531.93$, $p < .001$; Dunn's test:

all p's < .001 except for the negative cosine versus orthogonal categories).

The next question we asked was whether human similarity ratings could be

continuously predicted by the similarity of their GloVe embeddings. Following Pereira et al.

(24), we tested both euclidean distance and cosine similarity, which are respectively defined

as

$$\text{euclidean}(\mathbf{u}, \mathbf{v}) = \sqrt{\sum_i (u_i - v_i)^2} \quad \text{and} \quad \text{cosine}(\mathbf{u}, \mathbf{v}) = \frac{\langle \mathbf{u}, \mathbf{v} \rangle}{\|\mathbf{u}\| \cdot \|\mathbf{v}\|}.$$

In all following work, as a measure of fit, we computed Spearman's rank-order

correlation r_S between the similarity of 50-dimensional GloVe embeddings and the mean

human similarity rating for each pair of words. Rank-order correlation seemed more

appropriate, given that the Likert scale used to collect similarity ratings is not necessarily linear

(see below).

When computing the correlation for word pairs aggregated over percentile bins of

predicted similarity (Fig 3A), we found a strong correlation for both the cosine similarity and

the euclidean distance (euclidean: Spearman's $r_S(3754) = -0.56$, $p < .001$; cosine: Spearman's

$r_S(3754) = .66$, $p < .001$). Note that the correlation was positive for the cosine similarity while

it was negative for the euclidean distance as the latter is a measure of dissimilarity, so it should

decrease as the similarity ratings increase. The correlation was slightly better for cosine, so it

is the measure we used for subsequent analyses (ΔAIC = 734.31, $p < .001$). However, similarly

to what was observed by Pereira et al. (24), the difference between the cosine similarity and

euclidean distance was small.

Figure 3. The perceived similarity between two math concepts is well predicted by the

similarity of their GloVe 50-dimensional embeddings. The plot shows human similarity

rating (on a scale from 0 to 5, y axis) as a function of their predicted similarity based on the

cosine of the angle between their 50-dimensional vector embeddings derived from the math

corpus (x axis), (A) in French (n = 3756); and (B) in English (n = 2421). Data were averaged

over percentile bins. Marginal distributions of the x and y variables are also shown.

The results were also replicated in English (Fig 3B). Again, the correlation for cosine

similarity was slightly better than that for euclidean distance (euclidean: Spearman's r_S(2419)

= -0.42, p < .001; cosine: Spearman's r_S(2419) = .48, p < .001; ΔAIC = 174.92, p < .001).

An interesting observation, visible in Fig 3, is that human similarity ratings were not

linearly related to GloVe cosine similarity. Indeed the curves for French and English were both

convex, meaning that, for small values of similarities predicted by GloVe (between 0 and 0.4),

human ratings varied little with GloVe similarities (though still significantly: Spearman's

$r_S(2061) = .37$, $p < .001$), whereas for larger GloVe cosine similarities, they changed in a much

steeper fashion.

We compared those GloVe fits with an estimate of the noise ceiling in our data (see

Methods), in order to get an idea of how good those fits were relative to the explainable

variance. To this end, we recomputed the correlations on the unaggregated, trial-by-trial data,

without averaging the ratings for each pair of words across participants. This noise ceiling can

be thought of as the fraction of variance in the data from one participant that could be

accounted for by all the other participants (leave-one-out cross validation). We found that (1)

the single-trial similarity ratings were highly reliable, exhibiting an explainable variance (R^2) or

noise ceiling of 42.84% across participants; (2) the cosine similarity of 50-dimensional GloVe

embeddings, on the other hand, led to a single-trial correlation of 20.28%, i.e. about half of the

explainable variance. Thus, while GloVe provides a first-approximation model of math

concepts, it still leaves much to be explained.

Comparing different embeddings for math concepts

316   We examined the impact of the dimensionality of GloVe embeddings (Fig 4A). The

317   above analyses were based on 50-dimensional embeddings, which is GloVe's default, but we

318   wondered whether increasing the dimensionality of the embeddings would also increase the

319   correlation of their cosine similarities with human ratings.

Figure 4. Factors affecting the correlation between human similarity ratings and the similarities predicted by GloVe embeddings. (A) Percentage of variance explained by a rank correlation of human similarity ratings against the cosine angle of Glove math embeddings, as a function of the dimensionality of those embeddings. The dashed line shows the noise ceiling, estimated as the fraction of variance in the data from one participant that could be accounted for by all the other participants (leave-one-out cross validation, see Methods). 50-dimensional embeddings were used in the rest of this work. (B) Variation in the percentage of explained variance depending on word grade of acquisition and the corpus used to compute the embeddings; (C) Same, depending on participant education level.

The results showed that, for French words, the Spearman correlation coefficient increased with the number of dimensions of GloVe embeddings up to approximately 50 dimensions, with a sharp initial increase for dimensionality 1 to ~15, and then reached a plateau for 50 to 500-dimensional embeddings. Therefore, the choice of 50-dimensional embeddings was felicitous. We observed the same trend for English words, although both the noise ceiling and the correlation coefficients were lower.

We also probed whether embeddings derived from the math corpus were better at

predicting human similarity ratings than those derived from the non-math and global corpora.

We therefore computed the rank correlation between the similarity ratings and the cosine

similarity of the 50-dimensional embeddings derived from the math, non-math and global

corpora. We indeed found that the math corpus was a better predictor, followed by the global

and the non-math corpora (math: Spearman's r_S(97593) = .45, $p < .001$; global: Spearman's

r_S(97593) = .25, $p < .001$; non-math: Spearman's r_S(97593) = .20, $p < .001$; $\Delta AIC_{math\text{-}global}$ =

15792.95, $p < .001$; $\Delta AIC_{math\text{-}nonmath}$ = 18264.42, $p < .001$). These findings were replicated in

English (math: Spearman's r_S(13611) = .35, $p < .001$; global: Spearman's r_S(13611) = .21, $p <$

.001; non-math: Spearman's r_S(13611) = .19, $p < .001$; $\Delta AIC_{math\text{-}global}$ = 1049.85, $p < .001$;

$\Delta AIC_{math\text{-}nonmath}$ = 1347.46, $p < .001$).

To get a finer-grained view of the differences between the different corpora, we

repeated the same analysis for each word grade of acquisition. We expected that (1) basic

concepts might be modeled equally well by all corpora, but (2) as word grade increases,

embeddings derived from the math corpus would become better predictors of human similarity

ratings while correlations with embeddings derived from the other corpora would drop. These

predictions were partly confirmed (Fig 4B): the correlation of the cosine of embeddings derived

from the non-math corpus with human ratings decreased as the word grade increased

(Spearman's r_S(6) = -0.83, $p = .010$), but the Spearman correlation between cosines from

global corpus and word grade was not significant. Furthermore, embeddings derived from the

non-math and global corpora were consistently poorer predictors of human ratings than those

derived from the math corpus (exact one-sided Wilcoxon signed-rank test: math vs non-math:

$W = 36$, $p = .004$; math vs global: $W = 36$, $p = .004$), even for very basic math concepts studied

in primary school. In addition, the correlation between the cosine of math embeddings and

human ratings also decreased as the word grade increased (Spearman's r_S(6) = -0.87, $p =$

.007), probably due to the fact that advanced concepts were only rated by a smaller number

of highly educated participants and, as a consequence, the estimation of their human similarity

rating might be noisy.

To counter this possibility, we also analyzed the quality of GloVe fits as a function of

education level. We hypothesized that the math corpus would be a better predictor of expert

mathematicians than of people with a lower level of math education. Indeed, the math corpus

comprised very advanced math content such as category theory or algebraic topology.

Conversely, the non-math corpus should well predict the ratings of mathematically uneducated

people, but not those of more advanced mathematicians, as the math words in the non-math

corpus were either very low level (e.g. fractions or basic shapes) or advanced concepts which

have several meanings outside the math domain (e.g. "ring" or "field"). We ran the same fine-

grain analysis as for word grade (Fig 4C) and found that these predictions were verified: all

corpora predicted ratings of non-educated participants equally well, and then diverged for

educated participants. The correlation for the math corpus increased with participants' level of

education (Spearman's $r_S(8) = .85$, $p = .002$), while that for the non-math and global corpora

decreased as participants' level of education increased (global: Spearman's $r_S(8) = -0.65$, $p =$

.043; non-math: Spearman's $r_S(8) = -0.88$, $p < .001$).

Visualizations of the semantic space of math concepts

Given the relatively good fit of the GloVe vectors to human judgments, we close our

work with an analysis of the geometry of those vectors, as a proxy for human representations

of the semantic space of math concepts (in the future, this model could be compared to actual

measurements using fMRI or MEG; Kriegeskorte, Mur, & Bandettini, 2008; Kriegeskorte, Mur,

Ruff, et al., 2008).

We first tried to obtain a global visualization of the semantic space of math concepts.

To this end, we created a 2D map following the procedure in (30). First, we separated the

1,000 vectors in 18 clusters using spectral clustering (51). Then we projected all vectors along

with the cluster centers in two dimensions using t-SNE (52). Finally, we used Voronoi

tessellation around the projected centers to visualize the boundaries between the clusters.

The number of clusters (18) was chosen out of a range from 2 to 100 using the elbow method.

The resulting map is shown on Fig 5. We were able to label all clusters with a tentative

semantic description. Different regions were dedicated to analysis, algebra, arithmetic,

geometry, and, more tentatively, for arithmetics and to linear algebra. Thus, numbers had a

dedicated cluster (Fig 5B). Likewise, an entire area of the map was dedicated to proper nouns,

which were separate from the rest of the concepts (for instance, "Burnside" was closer to

"Weierstrass" than they were respectively to other group theory and analysis concepts, see

Fig 5B). However, some proper nouns, especially those that can be used as adjectives were

also sometimes integrated to the cluster related to their field (e.g. "Poisson" is located in a

probability cluster, as shown on Fig 5B). It was also striking that geometry occupied a whole

distinct sector of the map, diametrically opposite to numbers. This observation may perhaps

be related to Amalric and Dehaene's finding that the only detectable difference in fMRI

activation between the various domains of math separated geometry from the rest of

mathematics (11).

Figure 5. Global visualizations of the vector space for math semantics. We used the

Glove embeddings of the French math vocabulary to visualize the organization of the putative

semantic space by projecting it in two dimensions using spectral clustering and t-SNE. (A)

Each region was associated with a tentative label describing the words contained in the

cluster. (B) We also show five words contained in different regions: numbers, proper nouns,

matrix calculus, euclidean geometry and probabilities.

It is worth noting that the map continued to make sense when we increased the number

of clusters. Indeed, we reproduced this methodology with 100 clusters, and found that the

above mentioned clusters were refined in an interesting way. For instance, proper nouns were

also classified into sub-clusters depending on the area of math that they relate to (e.g. "Fermat"

and "Markov" fell in different clusters, as the former worked on number theory and the later

worked on probability). Similarly, the number cluster was split into smaller adjacent clusters

distinguishing between and small numbers, multiples of ten and powers of ten.

We then turned to more local visualizations of the semantic space to get a better idea

of the organizations of specific domains. The first things we looked into were numbers. We

projected the embeddings of numbers from 1 to 100 (only those whose French name only

consists of one word, which excluded for instance 70 or 21) on their first principal component

(PC1) (Fig 6A). We found that this projection orders numbers by their magnitude. Furthermore,

larger numbers are grouped together, suggesting a logarithmic organization (correlation with

log(n): Pearson's $r(20) = .90$, $p < .001$) similar to that reported in earlier work (2,42,53,54).

Following earlier work indicating that high-dimensional embeddings can be projected onto

oriented axes for properties such size or ferocity (26), we also looked at the line joining the

embeddings of "one" to "billion" and projected the embeddings of the other numbers on this

axis. Indeed, this projection revealed a systematic organization of other numbers based on

their relative size (Fig 6B). Again, the numbers were roughly organized by magnitude, in a

compressive manner.

Figure 6. Partial visualizations of the vector space for math semantics. We used the Glove embeddings of the French math vocabulary to visualize the organization of specific concepts in this putative semantic space. (A-B) Projection of the vector embeddings of numbers from 1 to 100 on their first principal component (PC1) (A), or on the line joining the two vectors for "one" and for "billion" (B). In panel A, the x axis is the log of the number magnitude in base 10, which shows a tight though non-linear correspondence with PC1. (C-D) Projection of the embeddings of two groups of related concepts on their first two principal components: numbers and shapes (C), and numbers and fractions (D). (E) Cosine similarity matrix for two domains of advanced math: complex analysis and logic (8 words each).

440 We then looked into the association between related concepts. GloVe is known to

441 capture the meaning specified by the juxtaposition of two words (e.g. the difference between

442 "king" and "queen" is the same as that between "man" and "woman") (55). We first focused on

443 the correspondence between numbers and shapes (e.g. "three" and "triangle", "four" and

444 "square"; Fig 6C). In Fig 6C-D, we projected the embeddings on their first two principal

445 components and drew a line to connect related concepts. The vectors for numbers and shapes

446 were indeed systematically related (Fig 6C): In GloVe embeddings, a similar vector is needed

447 to go from "three" to "triangle" as to go from "four" to "square". In addition, PC1 made a clear

448 distinction between numbers and shapes, while PC2 ordered numbers by their magnitude and

449 shapes by their number of sides.

450 A similar analysis for numbers and fractions (e.g. "two" and "half", "three" and "third",

451 etc) revealed different results (Fig 6D). Note that, contrary to English, the French for the

452 fractions ⅓ ("tiers") and ¼ ("quart") are different from those for the ordinals 3rd ("troisième")

453 and 4th ("quatrième"). On Fig 6D, we see that the correspondence was not well captured by

454 GloVe. PC1 still made a clear distinction between numbers and fractions, but along PC2,

455 numbers were grouped together (still ordered by magnitude), while fractions were separated

456 from each other. More work will be required to examine if a systematic but non-linear

457 relationship between numbers and their corresponding fractions can be found using more

458 sophisticated methods such as tensor decomposition (56).

459 Finally, we wanted to probe whether higher-level math concepts were also accurately

460 represented in the math semantic space computed by GloVe. We selected sixteen concepts

461 from distinct, advanced math fields, namely complex analysis and logic, and asked whether

462 the concepts from the same domain were consistently more similar than concepts from

463 different domains. The correlation matrix between the sixteen concepts is shown on Fig 6E.

464 We found that the intra-domain GloVe similarity was indeed greater than the inter-domain

465 similarity (intra: $\mu = 0.34$, $\sigma = 0.17$; inter: $\mu = 0.13$, $\sigma = 0.14$; $t(118) = 7.34$, $p < .001$).

Discussion

We created a comprehensive 1,000-word vocabulary of math concepts in French,

covering basic and advanced levels and provided vector embeddings for words in this

vocabulary. We then validated the embeddings by showing that they explain up to 47% of the

explainable variance from human similarity ratings. In addition, we proved that education

affects both familiarity and similarity ratings: the higher the math education level, the more

accurate the prediction of similarity ratings by GloVe embeddings extracted from Wikipedia

math pages. We also showed that the spatial layout of the vectors makes sense and captures

important regularities in number concepts, geometric words, and other higher-level concepts.

Importantly, we provided a translation of the vocabulary into English and proved that the main

results were replicated in both languages.

Possible use of the vocabulary and vectors

The purpose of this database is to enable a more systematic exploration of math

cognition, beyond the elementary concepts of numbers, geometry and algebra on which the

vast majority of current cognitive neuroscience research is concentrated. Our approach may

help provide a standardized approach to this field, cover the mathematical domain in an

unbiased manner, and increase the comparability between different studies. Our dataset may

also be used to devise benchmarks, test sets, and stimuli – for instance, we provide a reduced

set of 80 high-discriminability items that may suffice to quickly determine a participant's level

of math knowledge. Following a method similar to Pereira et al. (30), one could use the

embeddings we provide to ensure a full coverage of the entire math semantic space.

Limitations of this work

The first limitation of this work concerns the vocabulary itself. A subset of mathematical

words were reviewed and manually selected. The threshold of 1,000 words was arbitrary, and

rare words could have been missed, although we tried to improve the vocabulary at different

stages in the process. The grade level we assigned is necessarily only approximate and, since

it was based on the French national curriculum, could be different in other countries.

Furthermore, the very notion of a grade level may not be appropriate for ambiguous words

(e.g. "order") or very frequent words (e.g. "line"), as the depth of their understanding and,

indeed, their very meaning evolves with education. Furthermore, our focus on single words

may not do full justice to the combinatorial nature of mathematical concepts. To take just one

example, the concept of "vector space", being expressed by two words, was not represented

in the present embeddings. In spite of these limits, the fact that we observed meaningful

variations of both familiarity and similarity with grade and education indicates that the present

work provides a useful first approximation to an exhaustive dictionary of the most frequent

math concepts.

The second limitation concerns the embeddings. As explained above, GloVe vectors

only accounted for 43% of the noise ceiling of participants' similarity ratings. Further work will

be needed to increase the percentage of explained variance. One possible solution could be

to use deep neural networks instead of embeddings derived from single-word cooccurence

statistics. In recent years, Transformer models (57) have drawn a lot of attention and have

been shown to be able to predict brain activations in fMRI studies (32,35,36), although their

capacity to capture even elementary mathematical knowledge remains highly debated, and

specialized math models may be required (58,59). Further investigation is needed in this

direction. Another option would also be to obtain distributed semantic representations from a

larger corpus. Indeed, math articles are only a small fraction of Wikipedia, and adding more

content to the corpus (Bourbaki textbooks for instance) may be beneficial to the estimation of

the embeddings. Finally, language-of-thought approaches to mathematics (9,60), which focus

on the hierarchical compositional nature of mathematical concepts, may provide a more

appropriate cognitive foundation for the construction of higher level concepts in the course of

education.

Future directions

We provide a comparison between human similarity ratings and the embeddings we

propose. A natural continuation would be to compare the present embeddings and similarity

ratings to vectors obtained from the human brain using brain imaging or intracranial recording

techniques. We would then be able to leverage representational similarity analysis (49) tools

to gain insight in the organization of math concepts in the brain, including their topographic

organization on the cortical surface of individual subjects, going beyond existing group fMRI

studies of mathematicians (11,38). Ultimately, this could lead to the creation of a math-specific

brain viewer, similar to that proposed by Huth et al. (27).

Material and methods

Creation of the corpora

The corpora were extracted from HuggingFace's Wikipedia `20220301.fr` dataset. In

order to divide the dataset into a math and a non-math corpus, we parsed all the pages and

located them in the `wikipedia_fr_all_maxi_2022-04.zim` dump. A bot then decided

whether each page was math or not. To do so, it reached the bottom of the page and searched

for an occurence of one of the following strings: "Portail des mathématiques"; "Portail de la

géométrie"; "Portail de l'analyse"; "Portail de l'algèbre"; "Portail des probabilités et de la

statistique"; "Arithmétique et théorie des nombres"; "Portail de la logique"; "Portail de

l'informatique théorique". These labels indicate that a page belongs to the portal of

mathematics or theoretical computer science.

The math (resp. non-math) pages were aggregated to form the math (resp. non-math)

corpus, and the two corpora were also merged to form the global corpus.

In total, the math corpus comprised 16,455 pages out of the 2,402,095 included in the

dataset, and the non-math corpus comprised 2,236,840 pages (the remaining pages were

redirections and disambiguation articles).

Extraction of the vocabulary and generation of the embeddings

In order to ensure that the vocabulary did not contain several occurrences of the same

word (e.g. singular and plural for a noun, or infinitive and conjugated forms for a verb), we

performed a lemmatization step on each corpus (math, non-math and global). Two

lemmatization passes were carried out using Python `spacy`'s `fr_core_news_md` model. The

lemmatized math corpus was then provided as an input to the GloVe pipeline (16). The pipeline

has three steps: it first creates a 50,000-word vocabulary sorted by decreasing frequency,

then builds a cooccurrence matrix on the vocabulary words in the corpus and finally runs

GloVe on this matrix. Roughly, GloVe uses the cooccurrence matrix of a vocabulary in a

corpus to derive semantic vectors for each word by taking into account ratios of

cooccurrences. The window size for cooccurrence was set to 15 words. As reported in the

main text, the number of dimensions of the embedding vectors was varied from 1 to 500 (all

values between 1 and 50, and from 50 to 500 with an increment of 50).

The vocabulary output by GloVe on the math corpus actually contained only 39,345

words, because the GloVe pipeline did not count words with fewer than five occurrences in

the corpus. We then applied the same procedure to the non-math and global corpora, while

imposing the vocabulary to correspond to the output from the math corpus.

Words of the vocabulary were reviewed manually in decreasing order of frequency by

a person with extensive math training. Only the 1,000 first words which belonged to the math

domain (whether elementary or advanced) were kept, thereby constituting the final thousand-

word math vocabulary.

The vocabulary was then complemented with word frequency in the math and non-

math corpora. We also estimated words' school grade of acquisition ("word grade") by

examining when the corresponding concept was introduced in the French national curricula

(the following levels were distinguished: primary school, 6-7th grade, 8-9th grade, 10th grade,

11-12th grade, bachelor, *licence*, master), grammatical category (number, symbol, noun,

name, adverb, adjective, verb or any combination of these when applicable) and meta-

information such as whether the words are meta-mathematical meta-math (e.g. "theory" or

"example") and whether they have several different math meanings (polysemy, e.g. "tangent").

Familiarity ratings and similarity judgements

Selection of the pairs

For the behavioral experiment, we only kept those numbers, nouns and symbols which

were not flagged as too polysemic or meta-math, leaving us with 429 words. As these numbers

would have yielded 91,378 different pairs, we did not attempt to measure their full similarity

matrix. Furthermore, a random sampling of this large matrix would have yielded a vast majority

of unrelated words, thus making the experiment quite monotonous for participants. Instead, to

select target pairs for a given participant, we computed the distribution of cosine similarities

between pairs of words with the same grade of acquisition using 50-dimensional GloVe

vectors obtained from the math corpus. For each of the 429 target words, we identified the

three furthest words (cosine similarity close to -1), closest words (cosine similarity close to 1),

most orthogonal words (cosine similarity close to 0) and words whose similarity was closest

to the average similarity between words of the same grade (n = 14,790, μ = 0.24, σ = 0.20).

With this procedure, we obtained a total of 3,756 pairs that we used for the similarity rating

experiment (see below, and Table S2).

Design of the online experiment

The experiment was coded in PHP (server side) and JavaScript (client side) using the

jsPsych library. It was hosted on the secure server of NeuroSpin and no personal data was

collected.

In the design of this experiment, pairs of words from 6-7th grade and 8-9th grade, 10th

grade and 11-12th grade, and license and master were merged. This yielded five groups of

grade of acquisition for the words of our vocabulary.

The experiment consisted of three different parts. The first was a short demographic

survey, in which we asked participants, among other things, their last grade of education in

mathematics and a self-assessment of their current math skills on a scale from 1 to 10. In the

second part, participants were asked to judge how familiar they were with 50 words chosen at

random from our pool of 429 words. The familiarity ratings were made on a discrete scale from

0 to 8. To make the scale as objective as possible for participants 0 was labeled as "totally

unknown", 2 as "familiar word but unfamiliar concept", 4 as "vague idea", 6 as "familiar

concept", and 8 as "fully mastered concept".

Finally, in the last part, participants were shown 20 pairs of words at each grade of

education at or below theirs (e.g. participants who reported a high-school level of math

education were shown 20 word pairs from primary school, 20 pairs of 6-9th grade and 20 pairs

of 10-12th grade). The similarity judgements were made on a continuous scale from 0 to 5,

and labels indicated that 0 meant "totally unrelated" and 5 "'closely related". The similarity

rating block was preceded by a training block consisting of 8 pairs of words from everyday life

("father - mother", "boat - car", "table - god", "toothbrush - television", "Gandhi - Hitler", "stool -

crown", "clock - Julius Caesar", "carrot - asparagus") covering the whole scale of possible

similarities, presented in a randomized order, and 1 pair from the sailing jargon ("jib - capstan"),

always presented last. This training period ensured that scale was calibrated in the same way

for all participants. The order of presentation of words within each pair was randomized across

participants.

In total, we recruited 1,230 participants (809 males and 421 females; age 18-25 : n =

309, 25-40: n = 385, 40-60: n = 468, > 60: n = 68) on X (Twitter at the time). The math

education of participants varied between primary school to PhD (primary school: n = 4;

medium school: n = 8; high school: n = 232; 1st year college: n = 58; 2nd year college: n =

170; 3rd year college: n = 199; 4th year college: n = 122; master: n = 304; PhD: n = 133).

619   Analysis pipeline

620   All analyses were run in Python 3.11 using the `numpy`, `statsmodels`, `scipy` and

621   `scikit-learn` libraries. The plots were obtained using the `matplotlib` and `seaborn`

622   modules.

623   Rank linear regressions

Because many of our variables were not quantitative nor linearly ordered, we first

transformed them into ranks before entering them into regressions or general linear models

(GLMs). We used the `scipy.stats.rankdata` function in Python, with the default option

which   assigns   the   mean   rank   to   ties.   We   then   used   the

`statsmodels.regression.linear_model.OLS` class to fit the GLMs, and manually

added   an   intercept   (as   it   is   not   added   by   default)   using   the

`statsmodels.tools.add_constant` function.

Noise ceiling

In order to get an approximation of the amount of noise in the behavioral data, we computed a noise ceiling. The ceiling captures the average amount of variance present in one participant's responses that cannot be explained by the average responses of the other participants.

To compute the noise ceiling, we performed a leave-one-out cross validation. For each individual participant, we computed the correlation between its answers and the average answers of the other participants. We then computed the average R^2.

In the case of noise ceiling in subgroups (for instance for groups of participants with the same level of math education), there sometimes was not enough overlap between the stimuli seen by one particular participant and all the others. Therefore, when computing noise ceiling in any given subgroup, we correlated the answers of each participant of the subgroup with the average answers of all participants (and not only those belonging to the same subgroup). It must be noted that the noise ceiling is an approximation of the level of noise in the data, and our measure probably overestimates this level.

Comparison of similarities judged by humans with those predicted by GloVe

When computing the correlation between human judgements and GloVe-predicted similarities, we first averaged human judgements for a given pair over all trials and then computed the correlation across pairs (Fig 3). However, to compare with the within-participant noise ceiling, we also recomputed correlations across all individual trials, without performing the averaging step (Fig 4).

Item Response Theory (IRT)

In order to apply Item Response Theory (48) to the familiarity ratings provided by participants, we dichotomised the answers: familiarity ratings comprised between 0 and 3 (included) were considered grouped in a low category ("unknown"), and ratings equal to or above 4 meant that the word was known to participant. This dichotomization step was needed since we wanted to model participants' responses as a single sigmoid, and not as several logistic curves as standard methods for polytomous data would do (61).

IRT aims to estimate jointly a latent ability for participants and a discrimination and difficulty parameter for each item. This is done using expectation-maximization algorithms. Given an item (i.e. a word in the vocabulary) i and a participant with latent ability θ, the probability T_i that the participant answers that they know the item (familiarity rating equal to 4, 5, 6, 7 or 8) is modeled as

$$T_i(1 \mid \theta) = \frac{1}{1 + \exp(-a_i(\theta - b_i))}$$

where a_i is the item's discrimination parameter and b_i is its difficulty parameter.

Note that, for this particular analysis only, we used R 4.1 and its `mirt` package.

Model comparison

Whenever we compared two or more statistical models, we used Akaike Information Criterion (AIC). For each model i, we report the ΔAIC_i, which is defined as: $\Delta AIC_i = AIC_i - AIC_{min}$, where AIC_{min} is the lowest AIC obtained among the models under consideration (i.e. the AIC of the preferred model). The *p*-value associated with ΔAIC_i is given by $p_i = \exp(-\Delta AIC_i/2)$ (62).

Replication in English

We applied a similar method as in French to create a math, non-math and global corpora from Wikipedia pages in English. This time, we used HuggingFace's Wikipedia `20220301.en` dataset and the classification of math versus non-math pages was done using the `wikipedia_en_mathematics_nopic_2023-09.zim` dump, which was already curated to only contain the math pages from Wikipedia. The corpora gather 22,889 math pages and 6,435,781 non-math pages.

We also obtained GloVe embeddings using the same methodology, after two passes of lemmatization using `spacy`'s `en_core_web_lg` model, and used the vocabulary output by the GloVe pipeline on the math corpus to create a 1,000-word vocabulary of math words.

We then manually translated every single word of the French math vocabulary into English. For the online experiment, out of the original 429 stimuli tested with French participants, we selected only the 296 which had a unique translation in the English math vocabulary. Following the same procedure as in French, these stimuli yielded 2,458 pairs for the similarity rating task.

We translated the behavioral experiment in English and ran it online. In total, we recruited 174 participants (88 males and 86 females; age 18-25: n = 14, 25-40: n = 64, 40-60: n = 71, > 60: n = 25). The math education of participants varied from medium school to PhD (medium school: n = 1; high school: n = 37; 1st year college: n = 26; 2nd year college: n = 19; 3rd year college: n = 22; 4th year college: n = 12; master: n = 39; PhD: n = 18). The analysis pipeline was exactly the same in English as in French, but because of the lower number of participants, we did not attempt to perform within-level analyses.

Acknowledgements

We are grateful to Alexandre Pasquiou for his daily support in the creation of the corpora and the extraction of the embeddings. We also thank Mathias Sablé-Meyer for his tutorial on how to get started with jsPsych, and all participants who took part in our online experiment.

Data availability statement

All human data, statistical analysis code, GloVe embeddings and online experiments source code are available on OSF at link https://osf.io/dxg2w. The math vocabulary and its 50-dimensional embeddings are also available in the OSF repository. Due their large size, the corpora used to train GloVe models could not be shared online but are available from the corresponding author SaD on request.

References

1. Shepard RN, Kilpatric DW, Cunningham JP. The internal representation of numbers. Cognit Psychol. 1975 Jan 1;7(1):82–138.
2. Dehaene S. The number sense: how the mind creates mathematics. Rev. and updated ed. New York: Oxford university press; 2011.
3. Kutter EF, Bostroem J, Elger CE, Mormann F, Nieder A. Single Neurons in the Human Brain Encode Numbers. Neuron. 2018 Nov;100(3):753-761.e4.
4. Eger E. Neuronal foundations of human numerical representations. In: Progress in Brain Research [Internet]. Elsevier; 2016 [cited 2022 Jun 30]. p. 1–27. Available from: https://linkinghub.elsevier.com/retrieve/pii/S0079612316300413
5. Behr MJ, Lesh R, Post TR, Silver EA. Rational Number Concepts. In: Lesh R, Landau M, editors. Acquisition of Mathematics Concepts and Processes. New York: New York: Academic Press; 1983. p. 91–125.
6. Ni Y, Zhou YD. Teaching and Learning Fraction and Rational Numbers: The Origins and Implications of Whole Number Bias. Educ Psychol. 2005 Mar;40(1):27–52.
7. Siegler RS, Fazio LK, Bailey DH, Zhou X. Fractions: the new frontier for theories of numerical development. Trends Cogn Sci. 2013 Jan;17(1):13–9.
8. Dillon MR, Huang Y, Spelke ES. Core foundations of abstract geometry. Proc Natl Acad Sci. 2013 Aug 27;110(35):14191–5.
9. Sablé-Meyer M, Ellis K, Tenenbaum J, Dehaene S. A language of thought for the mental representation of geometric shapes. Cognit Psychol. 2022 Dec;139:101527.
10. Izard V, Pica P, Spelke ES, Dehaene S. Flexible intuitions of Euclidean geometry in an

Amazonian indigene group. Proc Natl Acad Sci. 2011 Jun 14;108(24):9782–7.

11. Amalric M, Dehaene S. Origins of the brain networks for advanced mathematics in
expert mathematicians. Proc Natl Acad Sci. 2016 Apr 11;201603205.

12. Zeki S, Romaya JP, Benincasa DMT, Atiyah MF. The experience of mathematical
beauty and its neural correlates. Front Hum Neurosci. 2014;8:68.

13. Clapham C, Nicholson J. The Concise Oxford Dictionary of Mathematics [Internet]. 4th
ed. Oxford University Press; 2009 [cited 2024 Mar 20]. Available from:
http://www.oxfordreference.com/view/10.1093/acref/9780199235940.001.0001/acref-
9780199235940

14. Dictionnaire des mathématiques. 10e édition mise à jour. Paris: PUF; 2019.

15. Hebart MN, Dickter AH, Kidder A, Kwok WY, Corriveau A, Van Wicklin C, et al. THINGS:
A database of 1,854 object concepts and more than 26,000 naturalistic object images.
Soto FA, editor. PLOS ONE. 2019 Oct 15;14(10):e0223792.

16. Pennington J, Socher R, Manning C. Glove: Global Vectors for Word Representation. In:
Proceedings of the 2014 Conference on Empirical Methods in Natural Language
Processing (EMNLP) [Internet]. Doha, Qatar: Association for Computational Linguistics;
2014 [cited 2022 Apr 8]. p. 1532–43. Available from: http://aclweb.org/anthology/D14-
1162

17. Shepard RN, Chipman S. Second-order isomorphism of internal representations:
Shapes of states. Cognit Psychol. 1970 Jan 1;1(1):1–17.

18. Shepard RN. Multidimensional Scaling, Tree-Fitting, and Clustering. Science. 1980 Oct
24;210(4468):390–8.

19. Hebart MN, Zheng CY, Pereira F, Baker CI. Revealing the multidimensional mental
representations of natural objects underlying human similarity judgements. Nat Hum
Behav. 2020 Oct 12;4(11):1173–85.

20. Ebitz RB, Hayden BY. The population doctrine in cognitive neuroscience. Neuron. 2021
Oct 6;109(19):3055–68.

21. Bhatia S, Richie R, Zou W. Distributed semantic representations for modeling human
judgment. Curr Opin Behav Sci. 2019 Oct;29:31–6.

22. Landauer TK, Dumais ST. A solution to Plato's problem: The latent semantic analysis
theory of acquisition, induction, and representation of knowledge. Psychol Rev. 1997
Apr;104(2):211–40.

23. Kramer MA, Hebart MN, Baker CI, Bainbridge WA. The features underlying the
memorability of objects. Sci Adv. 2023 Apr 26;9(17):eadd2981.

24. Pereira F, Gershman S, Ritter S, Botvinick M. A comparative evaluation of off-the-shelf
distributed semantic representations for modelling behavioural data. Cogn
Neuropsychol. 2016 May 18;33(3–4):175–90.

25. Richie R, Bhatia S. Similarity Judgment Within and Across Categories: A
Comprehensive Model Comparison. Cogn Sci [Internet]. 2021 Aug [cited 2023 Jan
25];45(8). Available from: https://onlinelibrary.wiley.com/doi/10.1111/cogs.13030

26. Grand G, Blank IA, Pereira F, Fedorenko E. Semantic projection recovers rich human
knowledge of multiple object features from word embeddings. Nat Hum Behav. 2022
Jul;6(7):975–87.

27. Huth AG, de Heer WA, Griffiths TL, Theunissen FE, Gallant JL. Natural speech reveals
the semantic maps that tile human cerebral cortex. Nature. 2016 Apr;532(7600):453–8.

28. Millet J, Caucheteux C, Orhan P, Boubenec Y, Gramfort A, Dunbar E, et al. Toward a
realistic model of speech processing in the brain with self-supervised learning [Internet].
arXiv; 2022 [cited 2022 Jun 28]. Available from: http://arxiv.org/abs/2206.01685

29. Mitchell TM, Shinkareva SV, Carlson A, Chang KM, Malave VL, Mason RA, et al.
Predicting Human Brain Activity Associated with the Meanings of Nouns. Science. 2008
May 30;320(5880):1191–5.

30. Pereira F, Lou B, Pritchett B, Ritter S, Gershman SJ, Kanwisher N, et al. Toward a
universal decoder of linguistic meaning from brain activation. Nat Commun. 2018

Dec;9(1):963.

31. Tong J, Binder JR, Humphries C, Mazurchuk S, Conant LL, Fernandino L. A Distributed
Network for Multimodal Experiential Representation of Concepts. J Neurosci. 2022 Sep
14;42(37):7121–30.

32. Caucheteux C, King JR. Brains and algorithms partially converge in natural language
processing. Commun Biol. 2022 Feb 16;5(1):1–10.

33. Goldstein A, Zada Z, Buchnik E, Schain M, Price A, Aubrey B, et al. Shared
computational principles for language processing in humans and deep language models.
Nat Neurosci. 2022 Mar;25(3):369–80.

34. Kumar S, Sumers TR, Yamakoshi T, Goldstein A, Hasson U, Norman KA, et al. Shared
functional specialization in transformer-based language models and the human brain
[Internet]. 2022 [cited 2024 Apr 8]. Available from:
http://biorxiv.org/lookup/doi/10.1101/2022.06.08.495348

35. Pasquiou A, Lakretz Y, Hale J, Thirion B, Pallier C. Neural Language Models are not
Born Equal to Fit Brain Data, but Training Helps [Internet]. arXiv; 2022 [cited 2023 Jan
10]. Available from: http://arxiv.org/abs/2207.03380

36. Schrimpf M, Blank IA, Tuckute G, Kauf C, Hosseini EA, Kanwisher N, et al. The neural
architecture of language: Integrative modeling converges on predictive processing. Proc
Natl Acad Sci. 2021 Nov 9;118(45):e2105646118.

37. Amalric M, Dehaene S. Cortical circuits for mathematical knowledge: evidence for a
major subdivision within the brain's semantic networks. Philos Trans R Soc B Biol Sci.
2018 Feb 19;373(1740):20160515.

38. Amalric M, Dehaene S. A distinct cortical network for mathematical knowledge in the
human brain. NeuroImage. 2019 Apr;189:19–31.

39. Dehaene S, Al Roumi F, Lakretz Y, Planton S, Sablé-Meyer M. Symbols and mental
programs: a hypothesis about human singularity. Trends Cogn Sci. 2022 Sep;26(9):751–
66.

40. Carey S. Conceptual differences between children and adults. Mind Lang. 1988;3:167–
81.

41. Carey S. The origins of concepts. New York: Oxford University Press; 2009.

42. Siegler RS, Opfer JE. The Development of Numerical Estimation: Evidence for Multiple
Representations of Numerical Quantity. Psychol Sci. 2003 May;14(3):237–50.

43. Halberda J, Feigenson L. Developmental change in the acuity of the 'number sense':
The approximate number system in 3-, 4-, 5-, and 6-year-olds and adults. Dev Psychol.
2008;44(5):1457–65.

44. Opfer J, Siegler R. Representational change and children's numerical estimation. Cognit
Psychol. 2007 Nov;55(3):169–95.

45. Piazza M, Pica P, Izard V, Spelke ES, Dehaene S. Education Enhances the Acuity of the
Nonverbal Approximate Number System. Psychol Sci. 2013 Apr 26;24(6):1037–43.

46. Piazza M, De Feo V, Panzeri S, Dehaene S. Learning to focus on number. Cognition.
2018 Dec 1;181:35–45.

47. Pica P, Lemer C, Izard V, Dehaene S. Exact and Approximate Arithmetic in an
Amazonian Indigene Group. Science. 2004 Oct 15;306(5695):499–503.

48. Cai L, Choi K, Hansen M, Harrell L. Item Response Theory. Annu Rev Stat Its Appl.
2016 Jun 1;3(1):297–321.

49. Kriegeskorte N, Mur M, Bandettini P. Representational similarity analysis - connecting
the branches of systems neuroscience. Front Syst Neurosci [Internet]. 2008 [cited 2022
Oct 27];2. Available from: https://www.frontiersin.org/articles/10.3389/neuro.06.004.2008

50. Kriegeskorte N, Mur M, Ruff DA, Kiani R, Bodurka J, Esteky H, et al. Matching
Categorical Object Representations in Inferior Temporal Cortex of Man and Monkey.
Neuron. 2008 Dec 26;60(6):1126–41.

51. von Luxburg U. A Tutorial on Spectral Clustering. ArXiv07110189 Cs [Internet]. 2007
Nov 1 [cited 2022 Mar 30]; Available from: http://arxiv.org/abs/0711.0189

52. van der Maaten LJP, Hinton GE. Visualizing High-Dimensional Data Using t-SNE. J
Mach Learn Res. 2008;9(nov):2579–605.

53. Dehaene S. The neural basis of the Weber–Fechner law: a logarithmic mental number
line. Trends Cogn Sci. 2003;7(4):145–7.

54. Dehaene S, Marques JF. Cognitive Euroscience: Scalar variability in price estimation
and the cognitive consequences of switching to the Euro. Q J Exp Psychol.
2002;55(3):705–31.

55. Mikolov T, Chen K, Corrado G, Dean J. Efficient Estimation of Word Representations in
Vector Space [Internet]. arXiv; 2013 [cited 2022 Dec 1]. Available from:
http://arxiv.org/abs/1301.3781

56. McCoy RT, Linzen T, Dunbar E, Smolensky P. RNNs Implicitly Implement Tensor
Product Representations. ArXiv181208718 Cs [Internet]. 2019 Mar 5 [cited 2020 Mar
28]; Available from: http://arxiv.org/abs/1812.08718

57. Vaswani A, Shazeer N, Parmar N, Uszkoreit J, Jones L, Gomez AN, et al. Attention Is All
You Need. ArXiv170603762 Cs [Internet]. 2017 Dec 5 [cited 2022 Jan 19]; Available
from: http://arxiv.org/abs/1706.03762

58. Anand A, Gupta M, Prasad K, Singla N, Sanjeev S, Kumar J, et al. Mathify: Evaluating
Large Language Models on Mathematical Problem Solving Tasks [Internet]. arXiv; 2024
[cited 2024 May 1]. Available from: http://arxiv.org/abs/2404.13099

59. Peng S, Yuan K, Gao L, Tang Z. MathBERT: A Pre-Trained Model for Mathematical
Formula Understanding. ArXiv210500377 Cs [Internet]. 2021 May 1 [cited 2022 Jan 7];
Available from: http://arxiv.org/abs/2105.00377

60. Dehaene S, Al Roumi F, Lakretz Y, Planton S, Sablé-Meyer M. Symbols and mental
programs: a hypothesis about human singularity. Trends Cogn Sci. 2022 Sep
1;26(9):751–66.

61. Samejima F. Graded Response Model. In: Van Der Linden WJ, Hambleton RK, editors.
Handbook of Modern Item Response Theory [Internet]. New York, NY: Springer New
York; 1997 [cited 2023 Oct 17]. p. 85–100. Available from:
http://link.springer.com/10.1007/978-1-4757-2691-6_5

62. Burnham KP, Anderson DR. Multimodel Inference: Understanding AIC and BIC in Model
Selection. Sociol Methods Res. 2004 Nov;33(2):261–304.

Supporting information

867 **S1 PDF File. Individual IRT plots for the 429 words selected in the online experiment**

868 **based on participants' familiarity ratings.**

869 **S2 Table. Number of pairs selected for the similarity rating experiment for each word**

870 **grade.**