Likelihood-based Fine-tuning of Protein Language Models for Few-shot Fitness Prediction and Design

Alex Hawkins-Hooker*
AI Centre
University College London

Shikha Surana*
InstaDeep Ltd.

Jack Simons*
InstaDeep Ltd.

Jakub Kmec
InstaDeep Ltd.

Oliver Bent
InstaDeep Ltd.

Paul Duckworth*
InstaDeep Ltd.

Abstract

Protein language models (PLMs) implicitly learn distributional constraints on protein sequences upheld over the course of evolution. As a consequence, the sequence and mutation-level likelihoods of such models form effective zero-shot predictors of mutations. Various schemes have been proposed for exploiting the distributional knowledge captured by PLMs to enhance supervised fitness prediction and sequence design. Of vital importance is the ability to accurately predict fitness in low-data settings. We propose to extend ranking-based loss functions, specifically designed for low data settings, for usage with *family-based* and *masked* PLMs. The literature lacks head-to-head comparisons between different prediction strategies, fine-tuning strategies, and different classes of PLMs, making it challenging to identify the best-performing methods. We fill this gap by offering head-to-head comparisons of state-of-the-art approaches. We demonstrate that directly fine-tuning likelihoods via a ranking loss consistently outperforms the current SOTA approaches. Furthermore, we show that when leveraged during multi-round optimisation campaigns, they can drastically improve sequence design.

1 Introduction

Natural protein sequences are the result of evolution via natural selection. Protein language models (PLMs) fit to the distribution of natural sequences and therefore learn to implicitly model functional and structural constraints relevant to protein fitness [Albanese et al., 2025]. PLM likelihoods form effective zero-shot predictors of the fitness effects of mutations [Meier et al., 2021, Notin et al., 2022]. These distribution learning capabilities are also highly informative for protein sequence design. Mutations assigned high likelihoods by the PLM can be iteratively incorporated to improve fitness [Hie et al., 2023], or entire sequences can be generatively sampled [Madani et al., 2023].

In multi-round design scenarios, experimental techniques are often used to generate labelled datasets associating a collection of sequences with measurements of biological properties of interest. Although in some cases these properties are amenable to high-throughput experimental screening methodologies whose resulting datasets are typically large [Rocklin et al., 2017, Tsuboyama et al., 2023], in general, experimental constraints mean that it might only be feasible to generate measurements for tens or hundreds of proteins in each round [Biswas et al., 2021]. It is therefore of considerable interest to ask how to best leverage the zero-shot prediction capacities of PLMs alongside small labelled datasets to improve fitness prediction and sequence design.

---

*Work was initiated during Alex's internship at Instadeep, and subsequently completed by the research team.

One popular paradigm for exploiting the information in pretrained PLMs involves extracting sequence representations and utilising these as (frozen) inputs into task-specific downstream predictive models (or 'heads') [Alley et al., 2019, Biswas et al., 2021, Rao et al., 2019, Dallago et al., 2021, Khan et al., 2023, Notin et al., 2023b, Groth et al., 2024]. However, trends in natural language processing have shown the benefits of directly adapting the distributions of models using task-specific labelled data or pairwise preferences [Ouyang et al., 2022, Rafailov et al., 2023] to fine-tune all parameters, thereby fully exploiting the distributional knowledge contained in the original pretrained model.

While pairwise ranking losses have shown promise adapting the likelihoods of unconditional autoregressive PLMs (in the context of protein fitness prediction) [Krause et al., 2021, Lee et al., 2023], it remains under-explored whether similar strategies can effectively be applied across other popular classes of PLMs. Here, we introduce likelihood scoring functions for *masked* PLMs, e.g. ESM-1v Meier et al. [2021] and ESM-2 Lin et al. [2022], along with *family-based* autoregressive models e.g. PoET [Truong Jr and Bepler, 2023] that condition predictions on multiple-sequence alignments (MSA) and often outperform unconditional autoregressive models for fitness prediction. For the first time we are able to directly compare fine-tuning strategies for different classes of PLMs, including the current state-of-the-art approaches that operate on frozen PLM embeddings, e.g. ProteinNPT [Notin et al., 2023b] and Kermut [Groth et al., 2024].

In this paper we (i) extend pairwise ranking loss functions to fine-tune the likelihoods of leading zero-shot fitness predictors trained with both masked- and family-based autoregressive language model objectives, (ii) provide direct comparison with SOTA approaches based on frozen embeddings, as well as regression-based fine-tuning approaches, providing compelling empirical evidence that *practitioners should make use of ranking-based fine-tuning schemes*, regardless of the specific PLM at hand, especially in low-data regimes, and (iii) develop ensemble strategies compatible with these fine-tuning schemes, demonstrate their effectiveness in multi-round Bayesian optimisation campaigns.

In such design campaigns, we study the problem *in silico* which mimics ground truth values being available from wet lab experiments. We first evaluate our proposed methods on a supervised fitness prediction task and secondly, a pool-based optimisation task as proposed in Notin et al. [2023b]. We evaluate across a broad range of low-data settings, demonstrating consistently better performance than traditional approaches. Further, unlike their work, we evaluate performance on a diverse subset of ProteinGym landscapes [Notin et al., 2023a] containing multiple mutations, a more realistic and challenging setting.

2 Related work

Zero-shot protein fitness prediction: The most successful models for zero-shot prediction of protein fitness effects attempt to predict the likelihood of particular sets of mutations occurring within a natural protein given its evolutionary context. Traditional methods within this category involve statistical models trained directly on multiple sequence alignments (MSAs) for each protein of interest, such as profile models [Hopf et al., 2017], Potts models [Figliuzzi et al., 2016, Hopf et al., 2017] and VAEs [Frazer et al., 2021, Riesselman et al., 2018]. More recent generalisations of such methods involve pretraining large PLMs across all natural proteins, e.g. ESM-1v [Meier et al., 2021] and ESM-2 Lin et al. [2022], which are trained using a masked language modelling objective. Alternatively, autoregressive models can directly compute the likelihood of entire protein sequences, making them more appropriate for scoring sequences containing multiple mutations [Notin et al., 2022, Nijkamp et al., 2023, Madani et al., 2023, Bhatnagar et al., 2025]. However, unconditional PLMs suffer from a lack of context, often requiring fine-tuning to specialise their distributions towards a particular protein family of interest [Madani et al., 2023]. As a result, the leading autoregressive models exploit additional information to improve predictions, either by biasing likelihoods with statistics from the MSA, e.g. Tranception [Notin et al., 2022], or by explicitly conditioning on the MSA [Hawkins-Hooker et al., 2021, Ram and Bepler, 2022, Truong Jr and Bepler, 2023]. Analogously, Metalic [Beck et al., 2025] meta-learns to condition on query sets to improve zero-shot predictions[2].

Supervised protein fitness prediction: Fitness prediction has been studied as a supervised learning task in many prior works. Several works have sought to exploit the pretrained representations of PLMs

---

[2]An earlier version of this work was cited by Beck et al. [2025], and they make use of the part of our work dedicated to ranking-based losses for masked language models.

to improve performance, using either fine-tuned [Rao et al., 2019] or frozen embeddings [Dallago et al., 2021, Notin et al., 2023b, Groth et al., 2024]. Nonetheless, approaches based on embeddings risk discarding useful distributional information captured in the models' output layers [Krause et al., 2021]. The importance of fully leveraging distribution information for fitness prediction is highlighted by the success of 'augmented density' predictors [Hsu et al., 2022a], which combine zero-shot fitness predictions with either one-hot encoded [Hsu et al., 2022a], or embedded [Notin et al., 2023b] representations of input sequences. ProteinNPT [Notin et al., 2023b] combines these strategies, training a bespoke non-parametric Transformer [Kossen et al., 2021] to reason over both zero-shot predictions and associated sequence embeddings to produce fitness predictions. Similarly, Kermut [Groth et al., 2024] introduces a composite Gaussian process kernel informed by frozen sequence embeddings and structure predictions, and models zero-shot predictions as GP prior mean function.

Methods seeking to adapt the distributions learned by PLMs directly have been less well studied. Rives et al. [2021] propose to use the log-likelihood ratio between mutant and wild-type amino acids as a regression function, fine-tuning the full model. Krause et al. [2021] suggest using a ranking-based loss function to fine-tune autoregressive PLMs, showing improvements over augmented density baselines on a small set of fitness landscapes. A similar ranking-based loss function was proposed for training non-pretrained CNN architectures on fitness datasets in Brookes et al. [2023]. Most recently, Lee et al. [2023] apply ranking-based loss functions derived from the literature on large language model alignment [Rafailov et al., 2023] to fine-tune unconditional autoregressive PLMs. For a precise comparison to Rafailov et al. [2023] see Appendix B.2. The application of ranking-based loss functions to masked PLMs is also considered in concurrent work [Zhao et al., 2024].

Lastly, related to our work, there is literature which proposes variants of Bayesian optimization (BO) for multi-round protein sequence design, details of which can be found in Appendix B.1.

3 Background

Ranking-based loss functions: While mean squared error has been widely used as a loss function in training sequence-based predictive models of fitness landscapes, two recent works have advocated the use of ranking-based loss functions [Krause et al., 2021, Brookes et al., 2023]. In particular, they suggest parameterising a Bradley-Terry model [Bradley and Terry, 1952] with a learned function of the sequence. The Bradley-Terry model represents the probability that a given sequence x_i has higher fitness $y(x_i)$ than another sequence x_j by parameterising a binary classifier via the difference in scores of each sequence under a learned scoring function $s_\theta(x)$:

$$p(y(x_i) > y(x_j)) = \sigma(s_\theta(x_i) - s_\theta(x_j)) \,, \tag{1}$$

where σ is the logistic sigmoid function. The model is trained by maximising the likelihood of the complete set of pairwise comparisons between the fitness values of sequences with respect to the parameters θ of the scoring function. Concretely, given a batch of B sequences $x_1, ..., x_B$, the loss is given by:

$$\mathcal{L} = \sum_{i=1}^{B} \sum_{j=1}^{B} -\mathbb{I}(y(x_i) > y(x_j)) \log \sigma(s_\theta(x_i) - s_\theta(x_j)) \,, \tag{2}$$

where $\mathbb{I}$ is an indicator function. In this way, fitness prediction for a dataset of size N is converted from a regression problem with N labels into a binary classification problem with $N \times N$ labels.

Fine-tuning autoregressive PLMs: To use the ranking-based loss functions to fine-tune an autoregressive protein language model, Krause et al. [2021] propose an unconditional sequence log-likelihood score function:

$$s_\theta(x) = \sum_{i=1}^{L} \log p(x^i | x^{<i}) \,, \tag{3}$$

where x^i denotes the i^{th} amino acid, and $x^{<i}$ represents the subsequence of amino acids preceding position i in the sequence x. Since the log-likelihoods of autoregressive protein language models are strong zero-shot predictors of the fitness effects of mutations [Notin et al., 2022], the difference in log-likelihoods used to parameterise the Bradley-Terry model of Equation 1 can produce an effective pairwise classifier at initialisation, which makes this fine-tuning method particularly relevant in low-data regimes.

4 Likelihood-based fine-tuning of masked and family-based PLMs

We describe below how pairwise ranking losses can be extended to fine-tune the likelihoods of other widely used classes of protein language models: masked language models and family-based autoregressive models. These extensions are derived from the principle that fine-tuning strategies should exploit as far as possible the properties of models that lead to strong zero-shot performance [Krause et al., 2021]. We enforce this principle by suggesting an appropriate choice of the scoring function s_θ used to parameterise the Bradley-Terry model in each case.

4.1 Conditional scoring functions

Previous applications of the ranking-based loss to fine-tune PLMs have focussed on unconditional autoregressive models. However, these models often underperform when compared to other classes of models, such as conditional autoregressive models and masked language models, in fitness prediction settings Notin et al. [2023a]. We therefore propose new likelihood scoring strategies, amenable to the Bradley-Terry model, to accommodate these newer PLM classes. To do so, we incorporate the additional conditioning information c exploited by these models into the conditional scoring function $s_\theta(x, c)$:

$$p\big((y(x_i) > y(x_j))|c\big) = \sigma(s_\theta(x_i, c) - s_\theta(x_j, c)). \tag{4}$$

Below, we will consider cases where c represents either a wild-type sequence or a multiple sequence alignment (MSA), since conditioning on evolutionary context is especially effective in fitness prediction [Truong Jr and Bepler, 2023]. Note the same approach could be applied to models which condition on protein structure [Hsu et al., 2022b].

4.2 Scoring functions for masked PLMs

Masked language models do not define a sequence-level likelihood, meaning that it is not immediately obvious how to define a scoring function for the Bradley-Terry model. Meier et al. [2021] and Johnson et al. [2024] have proposed a variety of strategies for zero-shot scoring of mutants using the likelihoods assigned to sets of mutations by masked language models. We propose to use these zero-shot scoring-functions to parameterise the Bradley-Terry model in Equation 4, allowing the models to be fine-tuned with ranking-based losses, similar to concurrent work [Zhao et al., 2024]. In Appendix C.4 Table 7 we empirically compare a range of masked PLM scoring strategies. From this study, we choose the wild-type marginal strategy for its combination of computational efficiency and strong performance as a zero-shot scoring function.

Concretely, the 'wild-type marginals' (wt-marginals) scoring function [Meier et al., 2021] is given by the summation of the log-likelihood ratios between mutated and wild-type amino acids across mutated positions, given the unmasked wild-type sequence as input:

$$s_\theta(x, x_{\text{wt}}) = \sum_{\{i : x_{\text{wt}}^i \neq x^i\}} \log p(x^i | x_{\text{wt}}) - \log p(x_{\text{wt}}^i | x_{\text{wt}}). \tag{5}$$

The wt-marginal strategy assumes an additive likelihood function over mutations, and thus, as our results imply, may not be appropriate for multi-mutant landscapes where epistasis can occur, i.e. where the combined effect of mutations at different positions is not simply the additive result of their individual effects. In these settings we expect an alternative scoring strategy will perform better.

4.3 Scoring functions for family-based PLMs

Family-based PLMs represent the conditional distribution over family members given a subset of other family members [Rao et al., 2021, Hawkins-Hooker et al., 2021, Ram and Bepler, 2022, Truong Jr and Bepler, 2023]. These models have proved effective as zero-shot fitness predictors, due to their ability to explicitly condition on evolutionary context to predict the effects of mutations.

In this paper we work with PoET [Truong Jr and Bepler, 2023], which models entire protein families autoregressively. To produce predictions given a mutant sequence x and an MSA $M = \{m_1, ..., m_N\}$ of homologues of a wild-type sequence x_{wt}, PoET computes the likelihood of the mutant x conditional on the MSA M. To exploit this capacity to condition on family members during fine-tuning, we condition the autoregressive scoring function in Equation 3 on the MSA sequences: $s_\theta(x, M) =$

$\sum_{i=1}^{L} \log p(x^i | x^{<i}, M)$. Since PoET operates natively on unaligned sequences and is sensitive to alignment depth, we subsample a small set of sequences from the MSA and discard gaps before feeding them into the model, following [Truong Jr and Bepler, 2023] (details in Appendix A.1).

To increase the efficiency of fine-tuning PoET, in practice we cache a single set of hidden layer representations obtained by passing the subsampled MSA M through the model, and fine-tune only the mapping between these frozen representations and the sequence likelihoods (Appendix A.2). This effectively decouples the encoding of prior context from the decoding of future amino acids.

5 Low-n fitness prediction

5.1 Experiment details

Protein fitness landscapes We study the performance of fitness prediction strategies on mutational landscapes from ProteinGym [Notin et al., 2023a]. Each landscape contains a set of protein sequences together with experimentally determined fitness values. The protein sequences within a landscape contain a small number of mutations relative to the 'wild-type' protein, and the fitness values are quantitative measurements of a functional property associated with the wild-type. We utilise two subsets of ProteinGym: the first is the validation set of 8 representative single-mutant landscapes selected by Notin et al. [2023b]. The second is a set of 5 landscapes containing multiple mutations, that constitutes a non-redundant set of diverse landscapes available in ProteinGym (more details in Appendix A).

In contrast to the experiments considered in ProteinNPT and Kermut [Notin et al., 2023b, Groth et al., 2024], we focus on fine-tuning across a broad range of low-data settings. For each landscape, we train all methods on $n = 24, 32, 48, 128$ or 512 sequences randomly sampled from the landscape and evaluate on either 2000 (single-mutants) or 5000 (multi-mutants) randomly sampled held-out sequences. All methods use an additional set of 128 randomly sampled sequences as a validation set to select the best model. For each landscape, and each n, we generate three sets of random splits, and report test set Spearman correlation averaged across the three splits. For models trained with ranking losses, the Spearman correlation is computed between the scoring function $s_\theta(x, c)$ and the ground truth fitness values.

Prior work has also considered non-random splits [Dallago et al., 2021, Notin et al., 2023b, Groth et al., 2024], which test the generalisation of model predictions to sequences with mutations at positions unseen in the training dataset. We note that such generalisation is already implicitly required in the low-data setting, as not all mutation positions will be present in the small training sets. That being said, in Section 5.2 we assess generalisation by computing metrics on subsets of the test sets containing mutations at positions for which no mutations were present in the training set.

Fitness prediction strategies We evaluate the performance of the fine-tuning strategies introduced in Section 4 on the selected landscapes. To attain an understanding of the effectiveness of these strategies across different classes of PLM, we apply them to the masked language model ESM-1v [Meier et al., 2021] and ESM-2 [Lin et al., 2022], and the family-based autoregressive model PoET [Truong Jr and Bepler, 2023]. In each case, we fine-tune all model parameters by parameterising the Bradley-Terry model of Equation 1 via the corresponding scoring functions in Section 4, and minimising the ranking loss in Equation 2.

Additionally, we compare to two further sets of baselines representative of widely used approaches, that either (i) fine-tune PLMs by adding a regression head [Rao et al., 2019], or (ii) train new models on top of frozen language model embeddings. In the first case, we add a linear regression head to ESM-1v, ESM-2 and PoET, and fine-tune all parameters with an MSE loss (additional details in Appendix A.1.1). As leading examples of the second class of approaches, we compare to ProteinNPT [Notin et al., 2023b] and Kermut [Groth et al., 2024], that both learn models over frozen language model embeddings via MSE and negative log-likelihood (NLL) respectively. Kermut results are obtained without the usage of a structure model (referred to as Kermut-sequence in [Groth et al., 2024]) to allow for fair comparisons between models.

As additional baselines, we include the 'augmented density' strategies used as baselines in Notin et al. [2023b]. These are regression models, taking as input the zero-shot predictions of a PLM as well as either a one-hot representation of the mutated sequence [Hsu et al., 2022a], or an embedding extracted

Figure 1: Supervised fitness prediction for a range of fine-tuning dataset sizes n (x-axis) for ESM-1v (left), ESM-2 (center) and PoET (right). We directly compare Spearman correlation (higher is better) on the test set after fine-tuning using our likelihood ranking-based strategy (blue) vs the regression-based MSE strategy (orange). In both cases all PLM parameters are fine-tuned. Average over 8 single mutant ProteinGym landscapes (top), and 5 multi-mutant landscapes (bottom). Error bars are $\pm\sigma$.

from a PLM (further details in Appendix A.4). We refer to these distinct choices of augmented density representation as 'OHE augmented' (OHE aug.) and 'Embedding augmented' (Emb. aug.) respectively, following code made available in Notin et al. [2023b].

All hyperparameters are selected based on performance on the single mutant set, i.e. the practice used in ProteinNPT.

5.2 Results

A full table of fitness prediction results is provided in Appendix C.1 Table 4 and Appendix C.2 Table 5. Each model is fine-tuned on the low-n dataset and evaluated via Spearman correlation on the held out test set.

Result 1: Ranking-based fine-tuning outperforms regression fine-tuning We first focus on the comparison between ranking-based fine-tuning and regression-based fine-tuning *using the same models* over a range of low-n data sizes. In Figure 1, we see a clear trend across all models and n: directly fine-tuning via a likelihood ranking loss improves performance over a parametric regression regime. For example, ranking-based fine-tuning of ESM-1v with just 24 sequences outperforms the standard regression approach using over five times more data ($n = 128$), and for PoET $n = 24$ outperforms the standard regression method using twice the sequences. We observe the gap in performance between the two fine-tuning approaches shrinks with increasing n. These observations are explained by observing the fact that the parameters introduced by the linear head require more data to be learned effectively. In the $n = 512$ multi-mutant setting, for ESM-1v the reverse result is likely due to the linear head accounting for epistasis effects better than the wild-type marginal likelihood scoring rule used in ranking (as discussed further in Appendix C.4 Table 7).

Result 2: Ranking-based fine-tuning outperforms SOTA models trained on frozen embeddings We next focus on the comparison between the best-performing ranking fine-tuning schemes and the current SOTA baselines: ProteinNPT, Kermut-sequence, and augmented density methods that each utilise frozen embeddings from a base model. In Figure 2, we show that directly adapting the PLM learned distributions via ranking-based fine-tuning, PoET outperforms all baseline approaches across all data settings, with the gap largest in the lowest data regimes. Notably this performance is not simply by virtue of PoET producing better zero-shot predictions. In Appendix C.6 we provide the

Figure 2: Supervised fitness prediction for best performing PoET and ESM-2 fine-tuning strategies over different dataset sizes n ($x-$axis), against SOTA baselines ProteinNPT (MSAT), Kermut$-$seq and augmented density 'Emb aug (MSAT)'. Average Spearman correlation (higher is better) over 8 single mutant landscapes (left) and 5 multiple mutant landscapes (right). Error bars plotted are $\pm\sigma$.

zero-shot results in which ESM-1v outperforms PoET and ESM-2, but they lead to inferior fine-tuned ProteinNPT results when used as frozen embeddings. Full results are in Appendix C.1 and C.2.

For completeness, in Appendix C.1 Table 4 we ablate other possible configurations: i) the MSE loss applied to the PLM likelihood score function, and ii) the ranking loss in Equation (2) applied to the PLM with a linear regression head. Whilst an interesting ablation, the application of MSE loss directly to the likelihoods does not perform well. However, the ranking loss applied to the regression target is a strong baseline, especially in the $n = 128$ and 512 multi-mutant settings, demonstrating improved performance for ESM-1v and ESM-2 over the standard MSE fine-tuning.

Result 3: Ranking-based fine-tuning generalises better to unseen positions   In Table 1 we assess the capability of the fine-tuning methods to generalise to mutations at unseen positions in the test set sequences. That is, random splits provide an estimate of performance on heldout data. However, similar mutations can occur in both train and test sets (e.g. related amino acid substitutions at the same position), meaning that measuring performance on predicting the effects of these mutations does not necessarily test a model's capacity for generalisation [Notin et al., 2023b].

We provide results here for the single mutant landscapes, and a complete table of results for the multi-mutant landscape in Appendix C.3 Table 6. We report the performance for mutations in the $n = 128$ test sets occurring at positions at which no mutations were present in the training set sequences. While there is a clear and expected drop in performance at these unseen positions, ranking-based fine-tuning directly on the likelihoods for all models demonstrates the best out-of-distribution behaviour at unseen positions.

Table 1: Spearman correlations for test set mutations at seen vs. unseen residue positions (n=128). Test set sequences are assigned to the unseen set if they contain mutations at residue positions at which none of the training set sequences have mutations. Protein-NPT (MSAT) (referred to as PNPT).

Model	Scoring fn.	Loss	Seen	Unseen
ESM-1v	linear head	MSE	0.460	0.331
	wt-marginals	rank	**0.592**	**0.509**
ESM-2	linear head	MSE	0.453	0.297
	wt-marginals	rank	**0.568**	**0.455**
PoET	linear head	MSE	0.571	0.517
	likelihood	rank	**0.612**	**0.549**
PNPT	-	MSE	0.563	0.462
Kermut-seq	GP head	NLL	0.464	0.363

6   Multi-round sequence design

6.1   Experiment details

We next ask whether the improvements in fitness prediction translate to benefits in multi-round sequence design experiments. Sequence design is formulated as a pool-based optimisation task over the sequences in an empirical fitness landscape. For a given landscape, the goal is to retrieve as

Figure 3: Multi-round sequence design for a range of acquisition batch sizes N over 10 rounds ($x-$axis) for PoET (top) and ESM-2 (bottom). We compare top 100 recall (higher is better) over the ProteinGym landscapes after fine-tuning using our likelihood ranking-based strategy (blue) or the regression- based MSE strategy (orange). In both cases all PLM parameters are fine-tuned. Average over 8 single mutant landscapes (top), and 5 multi-mutant landscapes (bottom). Error bars are $\pm\sigma$.

many high-scoring sequences as possible in 10 optimisation rounds (recall). We follow a similar multi-round sequence design setting to that introduced by Notin et al. [2023b]. In each round, the model is fine-tuned and its predictions are used to guide the acquisition of a batch of N sequences from a pool of candidate sequences (with a max pool size of 5000 sequences on the multi-mutant landscapes). More precisely, in each round we rank all remaining sequences in the pool by their acquisition values, and select the top N to add to the training set. We use a greedy acquisition when the model does provide uncertainty in their prediction, and the UCB acquisition function with $\lambda = 0.1$ otherwise. For ProteinNPT we use Monte Carlo dropout [Gal and Ghahramani, 2016] to produce uncertainty estimates. We initialise all models with 100 sequences randomly sampled from the landscape. All experiments are run on three random seeds.

Result 1: Ranking-based fine-tuning improves multi-round sequence design Figure 3 compares fine-tuning the likelihoods via a ranking loss versus regression across a wide range of acquisition batch sizes (N). We demonstrate that using a ranking loss improves the performance on multi-round pool-based sequence design, ultimately leading to acquiring more high value candidates earlier in the design campaign. We see that PoET fine-tuned with a ranking-based loss can achieve comparable performance to a regression method with significantly fewer sequences. For example, PoET achieves >40% recall of the top 100 sequences with 10 rounds of $N = 24$, in comparison to regression-based approach requiring 10 rounds of $N = 64$ to reach similar results.

6.2   Uncertainty quantification with evolutionary context ensembles

Typically multi-round design tasks make use of acquisition functions to select the next batch of candidates. Acquisition functions leverage uncertainty in predictions to explicitly encode exploration/-exploitation. PLMs do not inherently give uncertainty, and thus further work is required if we want to make use of uncertainty-aware acquisitions. We propose to exploit the fact that PLM predictive distributions depend heavily on sequence context to build ensembles of fine-tuned PLMs, in which each ensemble member sees a different, but functionally equivalent, sequence context. Concretely, we do this for both family-based and masked PLMs.

For *family-based* models we fine-tune an ensemble of PoET models, for each fitness landscape we sub-sample a set of K input MSAs $M_{1:K}$ from the full MSA associated with the wild-type sequence. We then fine-tune a separate set of parameters to minimise the loss conditioned on each

Table 2: Multi-round sequence design recall AUC metric (higher is better) for acquiring the top 100 sequences in the candidate pool. Averaged over 8 single mutant landscapes and 5 multiple mutant landscapes. Full recall curves are provided in Appendix C.8 Figure 4, 5, and 6.

Model Name	Scoring Fn.	Loss	Singles	Multiples
ESM-2 Ensemble	linear head	mse	4.57 (0.11)	3.34 (0.23)
	wt-marginals	**ranking**	**5.30** (0.06)	**3.91** (0.14)
PoET MSA Ensemble	linear head	mse	5.11 (0.02)	4.29 (0.20)
	likelihood	**ranking**	**5.59** (0.05)	**4.45** (0.28)
ProteinNPT + MC dropout	-	mse	5.57 (0.02)	4.12 (0.13)

MSA, producing K sets of parameters, each specialised to a single input MSA (further details are provided in Appendix A.2). To score sequences, we define the ensemble scoring function as: $s_{\theta_{1:K}}(x, \{M_{1:K}\}) = \frac{1}{K} \sum_{k=1}^{K} s_{\theta_k}(x, M_k)$. This procedure extends the practice of MSA ensembling used to improve the zero-shot predictions of MSA-based PLMs [Truong Jr and Bepler, 2023], to the supervised learning and sequence design setting.

For *masked* models we instead sample a set of K input masks, and fine-tune a separate set of parameters for each input mask, exploiting the intuition that differently masked sequences remain functionally equivalent, but may nonetheless produce different outputs when passed through the model. Further details are provided in Appendix A.3.

We provide fitness prediction results comparing the PLM ensembles for dataset sizes $n = 128$, and 512 in Appendix C.7 Table 10.

Result 2: PLM-ensembles improve multi-round sequence design In Table 2 we present pool-based optimisation results AUC (area under curve) for the top 100 recall guided by our context-ensemble models for PoET and ESM-2 comparing directly to ProteinNPT (MSAT). A complete table of all method's AUC top 30% recall and top 100 recall is provided in the Appendix Table 11. Additionally, we include a comprehensive set of design curves in Appendix C.8, directly comparing likelihood ranking to regression as well as comparing ensembles to their non-ensembled counterparts: ESM-2 (Figure 4), PoET (Figure 5), and ProteinNPT baselines (Figure 6).

In general, the recall design curves show similar trends to the supervised results. Ranking-based fine-tuning outperforms regression-based fine-tuning, and leveraging our novel ensemble strategies leads to the best overall design performance. Across both sets of landscapes, the PoET ranking-based MSA-ensemble outperforms all other methods. Interestingly, results in Table 11 show that PLM models that leverage greedy acquisition strategies are almost as effective as those that use acquisition functions. We hypothesise this is because either the uncertainty is poorly calibrated, or the tasks themselves favour a greedy approach; however investigation of this phenomena is left to future work.

While recall of high-fitness sequences saturates for the single mutant landscapes, it improves steadily for the multiple mutant landscapes, since the starting pools are larger, and it is not possible to reach perfect recall within the fixed budget of acquisitions.

Finally, per landscape design curves are provided in Appendix C.8.4 (singles) and Appendix C.8.5 (multiples). The relative ordering of the methods is reasonably stable across individual landscapes, although there are some cases where the non-PLM baselines perform comparably to the best-performing methods, suggesting these landscapes may contain noisy or otherwise difficult-to-predict fitness labels [Notin et al., 2023b].

7 Conclusion

In this paper, we extend existing ranking-based scoring functions to the masked- and autoregressive family-based PLM settings, explicitly conditioning on evolutionary information. We demonstrate that these likelihood scoring functions allow for effective ranking-based fine-tuning from as few as 24 experimental measurements - of the order of a typical low batch size in biological experiments. In both supervised and design tasks our proposed methods surpasses the performance of leading baseline approaches ProteinNPT and Kermut. Our work provides strong empirical evidence that

practitioners should make use of ranking-based losses regardless of PLM choice, especially in low-data regimes. Finally, we provide ensembling strategies that are compatible with likelihood fine-tuning. We demonstrate that these ensembling strategies can further enhance performance in multi-round sequence design tasks.

Despite ProteinGym providing real-world biological datasets, future work should consider experiments beyond curated benchmarks.

References

Katherine I Albanese, Sophie Barbe, Shunsuke Tagami, Derek N Woolfson, and Thomas Schiex. Computational protein design. *Nature Reviews Methods Primers*, 5(1):13, 2025.

Ethan C. Alley, Grigory Khimulya, Surojit Biswas, Mohammed AlQuraishi, and George M. Church. Unified rational protein engineering with sequence-based deep representation learning. *Nature Methods*, 16(12):1315–1322, 2019. URL https://www.nature.com/articles/s41592-019-0598-1.

Alan Nawzad Amin, Nate Gruver, Yilun Kuang, Lily Li, Hunter Elliott, Calvin McCarter, Aniruddh Raghu, Peyton Greenside, and Andrew Gordon Wilson. Bayesian optimization of antibodies informed by a generative model of evolving sequences. In *International Conference on Learning Representations, ICLR*, 2025.

Jacob Beck, Shikha Surana, Manus McAuliffe, Oliver Bent, Thomas D Barrett, Juan Jose Garau Luis, and Paul Duckworth. Metalic: Meta-learning in-context with protein language models. In *International Conference on Learning Representations, ICLR*, 2025.

Aadyot Bhatnagar, Sarthak Jain, Joel Beazer, Samuel C Curran, Alexander M Hoffnagle, Kyle Ching, Michael Martyn, Stephen Nayfach, Jeffrey A Ruffolo, and Ali Madani. Scaling unlocks broader generation and deeper functional understanding of proteins. *bioRxiv*, pages 2025–04, 2025.

Surojit Biswas, Grigory Khimulya, Ethan C. Alley, Kevin M. Esvelt, and George M. Church. Low-N protein engineering with data-efficient deep learning. *Nature Methods*, 18(4):389–396, 2021. URL https://www.nature.com/articles/s41592-021-01100-y.

Ralph Allan Bradley and Milton E. Terry. Rank analysis of incomplete block designs: the mehod of paired comparisons. *Biometrika*, 39(3-4):324–345, 1952. URL https://doi.org/10.1093/biomet/39.3-4.324.

David H. Brookes, Jakub Otwinowski, and Sam Sinai. Contrastive losses as generalized models of global epistasis. *arXiv*, 2023. URL https://arxiv.org/abs/2305.03136.

Martin Buttenschoen, Garrett M Morris, and Charlotte M Deane. Posebusters: Ai-based docking methods fail to generate physically valid poses or generalise to novel sequences. *Chemical Science*, 2024.

Christian Dallago, Jody Mou, Kadina E. Johnston, Bruce Wittmann, Nick Bhattacharya, Samuel Goldman, Ali Madani, and Kevin K. Yang. FLIP: Benchmark tasks in fitness landscape inference for proteins. *bioRxiv*, 2021. URL https://openreview.net/forum?id=p2dMLEwL8tF.

Matteo Figliuzzi, Hervé Jacquier, Alexander Schug, Oliver Tenaillon, and Martin Weigt. Coevolutionary Landscape Inference and the Context-Dependence of Mutations in Beta-Lactamase TEM-1. *Molecular Biology and Evolution*, 33(1):268–280, 2016. URL https://doi.org/10.1093/molbev/msv211.

Jonathan Frazer, Pascal Notin, Mafalda Dias, Aidan Gomez, Joseph K. Min, Kelly Brock, Yarin Gal, and Debora S. Marks. Disease variant prediction with deep generative models of evolutionary data. *Nature*, 599(7883):91–95, 2021.

Yarin Gal and Zoubin Ghahramani. Dropout as a bayesian approximation: Representing model uncertainty in deep learning. In *Proceedings of The 33rd International Conference on Machine Learning*, volume 48, pages 1050–1059, 2016. URL https://proceedings.mlr.press/v48/gal16.html.

Louisa Gonzalez Somermeyer, Aubin Fleiss, Alexander S Mishin, Nina G Bozhanova, Anna A Igolkina, Jens Meiler, Maria-Elisenda Alaball Pujol, Ekaterina V Putintseva, Karen S Sarkisyan, and Fyodor A Kondrashov. Heterogeneity of the GFP fitness landscape and data-driven protein design. *eLife*, 11:e75842, 2022. URL https://doi.org/10.7554/eLife.75842.

Kevin P. Greenman, Ava P. Amini, and Kevin K. Yang. Benchmarking uncertainty quantification for protein engineering. *PLOS Computational Biology*, 21(1):1–19, 01 2025. doi: 10.1371/journal.pcbi.1012639. URL https://doi.org/10.1371/journal.pcbi.1012639.

Peter Mørch Groth, Mads Kerrn, Lars Olsen, Jesper Salomon, and Wouter Boomsma. Kermut: Composite kernel regression for protein variant effects. *Advances in Neural Information Processing Systems*, 37:29514–29565, 2024.

Nate Gruver, Samuel Stanton, Polina Kirichenko, Marc Finzi, Phillip Maffettone, Vivek Myers, Emily Delaney, Peyton Greenside, and Andrew Gordon Wilson. Effective Surrogate Models for Protein Design with Bayesian Optimization. In *The 2021 ICML Workshop on Computational Biology*, 2021.

Alex Hawkins-Hooker, David T Jones, and Brooks Paige. MSA-Conditioned Generative Protein Language Models for Fitness Landscape Modelling and Design. In *Machine Learning in Structural Biology Workshop at NeurIPS*, 2021.

Brian L. Hie and Kevin K. Yang. Adaptive machine learning for protein engineering. *Current Opinion in Structural Biology*, 72:145–152, 2022. URL https://www.sciencedirect.com/science/article/pii/S0959440X21001457.

Brian L. Hie, Varun R. Shanker, Duo Xu, Theodora U. J. Bruun, Payton A. Weidenbacher, Shaogeng Tang, Wesley Wu, John E. Pak, and Peter S. Kim. Efficient evolution of human antibodies from general protein language models. *Nature Biotechnology*, pages 1–9, 2023. URL https://www.nature.com/articles/s41587-023-01763-2.

Thomas A. Hopf, John B. Ingraham, Frank J. Poelwijk, Charlotta P. I. Schärfe, Michael Springer, Chris Sander, and Debora S. Marks. Mutation effects predicted from sequence co-variation. *Nature Biotechnology*, 35(2):128–135, 2017.

Chloe Hsu, Hunter Nisonoff, Clara Fannjiang, and Jennifer Listgarten. Learning protein fitness models from evolutionary and assay-labeled data. *Nature Biotechnology*, 40(7):1114–1122, 2022a.

Chloe Hsu, Robert Verkuil, Jason Liu, Zeming Lin, Brian Hie, Tom Sercu, Adam Lerer, and Alexander Rives. Learning inverse folding from millions of predicted structures. In *Proceedings of the 39th International Conference on Machine Learning*, pages 8946–8970, 2022b. URL https://proceedings.mlr.press/v162/hsu22a.html.

Moksh Jain, Emmanuel Bengio, Alex Hernandez-Garcia, Jarrid Rector-Brooks, Bonaventure F. P. Dossou, Chanakya Ajit Ekbote, Jie Fu, Tianyu Zhang, Michael Kilgour, Dinghuai Zhang, Lena Simine, Payel Das, and Yoshua Bengio. Biological Sequence Design with GFlowNets. In *Proceedings of the 39th International Conference on Machine Learning*, pages 9786–9801, 2022. URL https://proceedings.mlr.press/v162/jain22a.html.

Sean R Johnson, Xiaozhi Fu, Sandra Viknander, Clara Goldin, Sarah Monaco, Aleksej Zelezniak, and Kevin K Yang. Computational scoring and experimental evaluation of enzymes generated by neural networks. *Nature biotechnology*, pages 1–10, 2024.

Asif Khan, Alexander I. Cowen-Rivers, Antoine Grosnit, Derrick-Goh-Xin Deik, Philippe A. Robert, Victor Greiff, Eva Smorodina, Puneet Rawat, Rahmad Akbar, Kamil Dreczkowski, Rasul Tutunov, Dany Bou-Ammar, Jun Wang, Amos Storkey, and Haitham Bou-Ammar. Toward real-world automated antibody design with combinatorial Bayesian optimization. *Cell Reports Methods*, 3(1): 100374, 2023.

Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *3rd International Conference on Learning Representations, ICLR*, 2015. URL http://arxiv.org/abs/1412.6980.

Jannik Kossen, Neil Band, Clare Lyle, Aidan N Gomez, Thomas Rainforth, and Yarin Gal. Self-Attention Between Datapoints: Going Beyond Individual Input-Output Pairs in Deep Learning. In *Advances in Neural Information Processing Systems*, volume 34, pages 28742–28756, 2021. URL https://proceedings.neurips.cc/paper_files/paper/2021/file/f1507aba9fc82ffa7cc7373c58f8a613-Paper.pdf.

Ben Krause, Nikhil Naik, Wenhao Liu, and Ali Madani. Don't throw away that linear head: Few-shot protein fitness prediction with generative models. *OpenReview*, 2021. URL https://openreview.net/forum?id=hHmtmT58pSL.

Minji Lee, Kyungmin Lee, and Jinwoo Shin. Fine-tuning protein language models by ranking protein fitness. In *NeurIPS 2023 Generative AI and Biology (GenBio) Workshop*, 2023. URL `https://openreview.net/forum?id=DUjUJCqqA7`.

Lin Li, Esther Gupta, John Spaeth, Leslie Shing, Rafael Jaimes, Emily Engelhart, Randolph Lopez, Rajmonda S. Caceres, Tristan Bepler, and Matthew E. Walsh. Machine learning optimization of candidate antibody yields highly diverse sub-nanomolar affinity antibody libraries. *Nature Communications*, 14(1):3454, 2023. URL `https://www.nature.com/articles/s41467-023-39022-2`.

Zeming Lin, Halil Akin, Roshan Rao, Brian Hie, Zhongkai Zhu, Wenting Lu, Nikita Smetanin, Allan dos Santos Costa, Maryam Fazel-Zarandi, Tom Sercu, Sal Candido, et al. Language models of protein sequences at the scale of evolution enable accurate structure prediction. *bioRxiv*, 2022.

Ali Madani, Ben Krause, Eric R. Greene, Subu Subramanian, Benjamin P. Mohr, James M. Holton, Jose Luis Olmos, Caiming Xiong, Zachary Z. Sun, Richard Socher, James S. Fraser, and Nikhil Naik. Large language models generate functional protein sequences across diverse families. *Nature Biotechnology*, 41(8):1099–1106, 2023. URL `https://www.nature.com/articles/s41587-022-01618-2`.

Joshua Meier, Roshan Rao, Robert Verkuil, Jason Liu, Tom Sercu, and Alex Rives. Language models enable zero-shot prediction of the effects of mutations on protein function. In *Advances in Neural Information Processing Systems*, volume 34, pages 29287–29303, 2021.

Erik Nijkamp, Jeffrey A. Ruffolo, Eli N. Weinstein, Nikhil Naik, and Ali Madani. ProGen2: Exploring the boundaries of protein language models. *Cell Systems*, 14(11):968–978.e3, 2023. URL `https://www.cell.com/cell-systems/abstract/S2405-4712(23)00272-7`.

Pascal Notin, Mafalda Dias, Jonathan Frazer, Javier Marchena Hurtado, Aidan N. Gomez, Debora Marks, and Yarin Gal. Tranception: Protein Fitness Prediction with Autoregressive Transformers and Inference-time Retrieval. In *Proceedings of the 39th International Conference on Machine Learning*, pages 16990–17017, 2022. URL `https://proceedings.mlr.press/v162/notin22a.html`.

Pascal Notin, Aaron Kollasch, Daniel Ritter, Lood van Niekerk, Steffanie Paul, Han Spinner, Nathan Rollins, Ada Shaw, Rose Orenbuch, Ruben Weitzman, Jonathan Frazer, Mafalda Dias, Dinko Franceschi, Yarin Gal, and Debora Marks. ProteinGym: Large-scale benchmarks for protein fitness prediction and design. In *Advances in Neural Information Processing Systems*, volume 36, pages 64331–64379, 2023a.

Pascal Notin, Ruben Weitzman, Debora Marks, and Yarin Gal. Proteinnpt: Improving protein property prediction and design with non-parametric transformers. In *Advances in Neural Information Processing Systems*, volume 36, pages 33529–33563, 2023b.

Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, John Schulman, Jacob Hilton, Fraser Kelton, Luke Miller, Maddie Simens, Amanda Askell, Peter Welinder, Paul F Christiano, Jan Leike, and Ryan Lowe. Training language models to follow instructions with human feedback. In S. Koyejo, S. Mohamed, A. Agarwal, D. Belgrave, K. Cho, and A. Oh, editors, *Advances in Neural Information Processing Systems*, volume 35, pages 27730–27744. Curran Associates, Inc., 2022.

Rafael Rafailov, Archit Sharma, Eric Mitchell, Christopher D Manning, Stefano Ermon, and Chelsea Finn. Direct preference optimization: Your language model is secretly a reward model. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023. URL `https://openreview.net/forum?id=HPuSIXJaa9`.

Soumya Ram and Tristan Bepler. Few Shot Protein Generation. *arXiv*, 2022. URL `http://arxiv.org/abs/2204.01168`.

Roshan Rao, Nicholas Bhattacharya, Neil Thomas, Yan Duan, Peter Chen, John Canny, Pieter Abbeel, and Yun Song. Evaluating Protein Transfer Learning with TAPE. In *Advances in Neural Information Processing Systems*, volume 32, 2019.

Roshan M Rao, Jason Liu, Robert Verkuil, Joshua Meier, John Canny, Pieter Abbeel, Tom Sercu, and Alexander Rives. Msa transformer. In *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, pages 8844–8856, 2021. URL `https://proceedings.mlr.press/v139/rao21a.html`.

Adam J. Riesselman, John B. Ingraham, and Debora S. Marks. Deep generative models of genetic variation capture the effects of mutations. *Nature Methods*, 15(10):816–822, 2018. URL `https://www.nature.com/articles/s41592-018-0138-4`.

Alexander Rives, Joshua Meier, Tom Sercu, Siddharth Goyal, Zeming Lin, Jason Liu, Demi Guo, Myle Ott, C. Lawrence Zitnick, Jerry Ma, and Rob Fergus. Biological structure and function emerge from scaling unsupervised learning to 250 million protein sequences. *Proceedings of the National Academy of Sciences*, 118(15):e2016239118, 2021. URL `https://www.pnas.org/doi/10.1073/pnas.2016239118`.

Gabriel J. Rocklin, Tamuka M. Chidyausiku, Inna Goreshnik, Alex Ford, Scott Houliston, Alexander Lemak, Lauren Carter, Rashmi Ravichandran, Vikram K. Mulligan, Aaron Chevalier, Cheryl H. Arrowsmith, and David Baker. Global analysis of protein folding using massively parallel design, synthesis and testing. *Science (New York, N.Y.)*, 357(6347):168–175, 2017. URL `https://www.ncbi.nlm.nih.gov/pmc/articles/PMC5568797/`.

Karen S. Sarkisyan, Dmitry A. Bolotin, Margarita V. Meer, Dinara R. Usmanova, Alexander S. Mishin, George V. Sharonov, Dmitry N. Ivankov, Nina G. Bozhanova, Mikhail S. Baranov, Onuralp Soylemez, Natalya S. Bogatyreva, Peter K. Vlasov, Evgeny S. Egorov, Maria D. Logacheva, Alexey S. Kondrashov, Dmitry M. Chudakov, Ekaterina V. Putintseva, Ilgar Z. Mamedov, Dan S. Tawfik, Konstantin A. Lukyanov, and Fyodor A. Kondrashov. Local fitness landscape of the green fluorescent protein. *Nature*, 533(7603):397–401, 2016. URL `https://www.nature.com/articles/nature17995`.

Samuel Stanton, Wesley Maddox, Nate Gruver, Phillip Maffettone, Emily Delaney, Peyton Greenside, and Andrew Gordon Wilson. Accelerating Bayesian Optimization for Biological Sequence Design with Denoising Autoencoders. In *Proceedings of the 39th International Conference on Machine Learning*, pages 20459–20478, 2022. URL `https://proceedings.mlr.press/v162/stanton22a.html`.

Martin Steinegger, Markus Meier, Milot Mirdita, Harald Vöhringer, Stephan J. Haunsberger, and Johannes Söding. HH-suite3 for fast remote homology detection and deep protein annotation. *BMC Bioinformatics*, 20(1):473, 2019. URL `https://doi.org/10.1186/s12859-019-3019-7`.

Shikha Surana, Nathan Grinsztajn, Timothy Atkinson, Paul Duckworth, and Thomas D Barrett. Overconfident oracles: Limitations of in silico sequence design benchmarking. In *ICML 2024 AI for Science Workshop*, 2024.

Timothy Fei Truong Jr and Tristan Bepler. PoET: A generative model of protein families as sequences-of-sequences. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023. URL `https://openreview.net/forum?id=1CJ8D7P8RZ`.

Kotaro Tsuboyama, Justas Dauparas, Jonathan Chen, Elodie Laine, Yasser Mohseni Behbahani, Jonathan J. Weinstein, Niall M. Mangan, Sergey Ovchinnikov, and Gabriel J. Rocklin. Mega-scale experimental analysis of protein folding stability in biology and design. *Nature*, 620(7973): 434–444, 2023. URL `https://www.nature.com/articles/s41586-023-06328-6`.

Junming Zhao, Chao Zhang, and Yunan Luo. Contrastive Fitness Learning: Reprogramming Protein Language Models for Low-N Learning of Protein Fitness Landscape. *bioRxiv*, 2024. URL `https://www.biorxiv.org/content/10.1101/2024.02.11.579859v1`.

A Additional experimental details

We use the set of 8 single-mutant landscapes selected for ablations and hyperparameter selection by [Notin et al., 2023b]. The names of these landscapes in ProteinGym are:

- BLAT_ECOLX_Jacquier_2013
- CALM1_HUMAN_Weile_2017
- DYR_ECOLI_Thompson_2019
- DLG4_RAT_McLaughlin_2012
- REV_HV1H2_Fernandes_2016
- TAT_HV1BR_Fernandes_2016
- RL40A_YEAST_Roscoe_2013
- P53_HUMAN_Giacomelli_WT_Nutlin

We additionally select a set of 5 of the most diverse multi-mutant landscapes in ProteinGym. To select these landscapes, we identified the landscapes with the largest number of mutations in ProteinGym, and discarded redundant landscapes (for example the GFP landscapes of [Gonzalez Somermeyer et al., 2022] are landscapes of close homologues of the GFP protein whose landscape was reported by [Sarkisyan et al., 2016]. We therefore include only the latter.

The selected multi-mutant landscapes are:

- PABP_YEAST_Melamed_2013
- CAPSD_AAV2S_Sinai_2021
- GFP_AEQVI_Sarkisyan_2016
- GRB2_HUMAN_Faure_2021
- HIS7_YEAST_Pokusaeva_2019

Table 3: Additional details of the 8 single mutation, and 8 multiple mutation landscapes we use from ProteinGym. wt-length is the number residues in the wild-type protein. Mutations refers to whether the landscape contains single mutant sequences, or a range of the number of mutations present in the landscape. Fitness score distribution is provided as mean and std.

Landscape Name	wt length	Mutations	Num of seqs	Fitness Score Distr.
BLAT_ECOLX_Jacquier_2013	286	Single	989	-1.558 ± 1.952
CALM1_HUMAN_Weile_2017	149	Single	1813	0.742 ± 0.365
DLG4_RAT_McLaughlin_2012	724	Single	1,576	-0.172 ± 0.406
DYR_ECOLI_Thompson_2019	159	Single	2,363	-0.391 ± 0.742
P53_HUMAN_Giacomelli_2018_WT_Nutlin	393	Single	7,467	-0.020 ± 1.035
REV_HV1H2_Fernandes_2016	116	Single	2,147	-0.121 ± 0.218
RL40A_YEAST_Roscoe_2013	128	Single	1,195	-0.265 ± 0.345
TAT_HV1BR_Fernandes_2016	86	Single	1,577	-0.116 ± 0.197
CAPSD_AAV2S_Sinai_2021	735	Multiple (1-28)	42,328	-1.226 ± 3.045
GFP_AEQVI_Sarkisyan_2016	238	Multiple (1-15)	51,714	2.658 ± 1.059
GRB2_HUMAN_Faure_2021	217	Multiple (1-2)	63,366	-0.793 ± 0.467
HIS7_YEAST_Pokusaeva_2019	220	Multiple (1-28)	496,137	0.619 ± 0.449
PABP_YEAST_Melamed_2013	577	Multiple (1-2)	37,708	0.524 ± 0.391

A.1 Hyperparameter details

Hyperparameters for the fine-tuning methods were selected based on performance on the single mutant set, consistent with the practice used to select hyperparameters for the baselines from ProteinNPT. We report metrics obtained when using these hyperparameters on both single-mutant and multiple-mutant landscapes for each method.

ESM-1v, ESM-2 and PoET models were fine-tuned using the Adam optimizer [Kingma and Ba, 2015] using gradient accumulation with an effective batch size of 32. Learning rates for regression-based and ranking-based fine-tuning were selected separately in each case after after a sweep over the values $1e-4, 3e-5, 1e-5$ on the 8 single mutant landscapes. For ESM models, we computed the loss by scoring all sequences using the wt-marginal strategy. In the fitness prediction experiments, the models were trained for 50 epochs. During training on each landscape the Spearman correlation, computed on a separate validation set of 128 sequences from the landscape, was used to determine the epoch whose checkpoint should be used to produce predictions on the test set.

A.1.1 Regression heads

Linear regression heads were added to embeddings extracted from ESM-1v, ESM-2 and PoET. In the former case, we averaged embeddings across the sequence dimension before inputting them to the regression head, in the latter case we used final token embeddings.

A.1.2 Ensembles

Contextual ensemble models of size 5 were used for both ESM-2 and PoET. During design, the ensemble members were trained for 20 epochs each round. In each round all ensemble members were reinitialised from the pretrained model and retrained on the latest training dataset.

A.2 PoET: more details

Decoder-only fine-tuning   PoET parameterises a sequence of conditional distributions over the amino acids in a set of protein sequences in the same family. The model represents the joint likelihood of a set of sequences $M = \{m_1, ..., m_N\}$, via an autoregressive factorisation over sequences and over positions within each sequence:

$$p(M) = \prod_i p(m_i|m_{<i}) = \prod_{i,j} p(m_i^j|m_i^{<j}, m_{<i}) \,. \tag{6}$$

To parameterise this distribution, PoET uses a causally masked Transformer architecture, which maps from previous amino acids to logits for the current amino acid. Conceptually, this function can be decomposed into two stages: first the entire history of previous sequences $m_{<i}$ is encoded into a sequence of embeddings $H_{<i} \in \mathbb{R}^{L \times (i-1) \times D \times E}$, where D is the number of layers and E is the embedding dimension, via a stack of causally masked layers:

$$H_{<i} = f_\theta(m_{<i}) \,. \tag{7}$$

The current sequence m_i is then decoded by a function which maps these prior sequence embeddings and previous amino acids in the current sequence to logits for each position j:

$$\text{logit}_{ij} = g_\theta(m_i^{<j}, H_{<i}) \,. \tag{8}$$

To fine-tune PoET from fitness data, we propose to fine-tune only the weights of the function g, representing the 'decoding' of the current sequence given its context. To achieve this, we first clone the PoET weights, producing a set of 'encoder' weights ϕ and a set of 'decoder' weights θ. We use the frozen encoder weights to produce an embedding $H \in \mathbb{R}^{L_M \times D \times E}$ of the input MSA sequences: $H = f_\phi(\{m_1, ..., m_N\})$, where L_M is the total length of all sequences in the input MSA. We then fine-tune the weights θ of the cloned 'decoder' to minimise the cross-entropy loss of Equation 2 on the labelled data. Concretely, the scoring function used to parameterise the Bradley-Terry model becomes:

$$s_\theta(x, M) \equiv s_\theta(x, H) = \sum_i \log p_\theta(x^i|x^{<i}, H) \tag{9}$$

To maximise computational efficiency, the MSA embeddings H are pre-computed before the start of the fine-tuning process, and remain frozen throughout.

PoET MSA subsampling   For PoET, in both single-model and ensemble configurations, we sampled context sequences from the same filtered MSAs used to extract MSA Transformer embeddings for ProteinNPT. These MSAs are generated from the full MSAs provided with ProteinGym by running hhfilter [Steinegger et al., 2019], requiring a minimum coverage of 75% and a maximum sequence identity of 90%. Subsequently, we use weighted sampling as described in Truong Jr and Bepler [2023] to select sequences to pass as context to PoET, up to a maximum context length of 8192 tokens. The MSA is encoded using a frozen copy of the PoET model into a set of cached hidden representations, as described in Appendix A.2. When ensembling, a separate MSA is sampled for each ensemble member, and held fixed during the fine-tuning of that ensemble member.

A.3 ESM-1v and ESM-2: more details

ESM-2 ensembling strategy To fine-tune an ensemble of models given a single ESM-2 checkpoint, we randomly sampled a set of 5 masks. Within each mask, each sequence position had a 15% probability of being masked. We fine-tuned one model for each mask, by using the correspondingly masked wild-type sequence $\tilde{x}_{\text{wt}}^{(k)}$ as input to the model, instead of the unmasked wild-type sequence. The ensembled scoring function used to generate predictions is:

$$s(x, x_{\text{wt}}) = \frac{1}{K} \sum_k s(x, \tilde{x}_{\text{wt}}^{(k)}). \tag{10}$$

A.4 Baseline models

ProteinNPT, the embeddings augmented (Emb. aug.) baselines, and the one-hot encoding augmented (OHE aug.) baselines were all run using the code released by Notin et al. [2023b]. The one-hot and embedding augmented models both use the strategy from Hsu et al. [2022a], combining the zero-shot predictions from a pretrained model with sequence features in a regression framework. They differ in the way sequence features are extracted: in the former case, ridge regression is performed directly on the one-hot encoded sequences. In the latter case, PLM embeddings are used to featurise the sequences. We refer to Notin et al. [2023b] for further details.

For the fitness prediction experiments, separate ProteinNPT models were trained for 2000 and 10000 steps, and the results of the best-performing model were reported. The other baselines appeared to benefit more from longer training and were trained for 10000 steps, as in Notin et al. [2023b]. For design experiments, we used the Monte Carlo dropout uncertainty quantification strategy proposed by Notin et al. [2023b] for both ProteinNPT and other baselines. Notin et al. [2023b] report best results with a 'hybrid' uncertainty quantification strategy, however this strategy is not implemented in the publicly available code.

A.5 Upper confidence bound acquisition function

For all ensembles, we use a parameter of $\lambda = 0.1$ within the upper confidence bound acquisition function $a(x, \lambda) = \mu(x) + \lambda\sigma(x)$, where $\mu(x)$ and $\sigma(x)$ respectively are the mean and standard deviation of the predictions of the model given an input sequence x.

A.6 Implementation of ranking loss

We implement a pairwise ranking loss by using binary cross-entropy to train the model on ranking tasks by comparing predicted scores for all pairs in a batch. It computes the difference in predictions for every pair, determines the ground-truth ranking based on actual values, and applies BCE loss to these pairwise comparisons, excluding self-comparisons via a diagonal mask. An example PyTorch implementation can be found below:

```python
import torch
import torch.nn.functional as F

def full_ranking_bce(preds: torch.Tensor, targets: torch.Tensor) ->
    torch.Tensor:
    # Calculate pairwise differences between all predictions
    pairwise_diffs = preds[:, None] - preds[None, :]

    # Determine if each target is greater than others in a pairwise
        manner
    target_comparisons = targets[:, None] > targets[None, :]

    # Compute binary cross-entropy loss for pairwise comparisons
    ranking_loss = F.binary_cross_entropy_with_logits(pairwise_diffs,
        target_comparisons.float(), reduction='none')

    # Create a mask to exclude diagonal elements (self-comparisons)
    batch_size = preds.size(0)
    diag_mask = 1 - torch.eye(batch_size, device=preds.device)
```

```
# Apply the mask and calculate the mean loss, excluding the
    diagonal
masked_loss = 0.5 * ranking_loss * diag_mask
return masked_loss.mean((-1, -2))
```

B Protein Design Related Work

B.1 Model-guided protein design

Several works have proposed variants of Bayesian optimization (BO) for designing biological sequences, including proteins [Gruver et al., 2021, Jain et al., 2022, Khan et al., 2023, Stanton et al., 2022, Hie and Yang, 2022, Amin et al., 2025]. It is common to evaluate BO approaches in an unconstrained setting, where sequences are proposed by an optimiser and evaluated with a black-box oracle. However, recent work suggests that designing such biological oracles is a challenging task in itself [Buttenschoen et al., 2024, Surana et al., 2024]. An alternative *in silico* evaluation strategy avoids the challenge of defining a meaningful oracle function by adopting a pool-based optimisation problem formulation over experimentally determined fitness landscapes [Notin et al., 2023b]. Another line of work has sought to provide direct experimental validation of approaches combining uncertainty estimates with PLMs, in settings ranging from zero- [Hie et al., 2023] to few-shot design [Biswas et al., 2021], to single-round design with large training sets of sequence-fitness pairs [Li et al., 2023].

Gruver et al. [2021] study various choices of surrogate model for protein design with BO, finding CNN ensembles to be particularly robust to the kinds of distribution shift encountered during online design. More recently, Greenman et al. [2025] studied a range of uncertainty quantification strategies applied to models trained directly on sequences, and on frozen language model embeddings.

B.2 Relationship to preference learning for LLMs

Direct preference optimisation (DPO) [Rafailov et al., 2023] is a recently proposed method for aligning large language models (LLMs) using datasets of human preference data. DPO also uses scoring functions from pretrained models to parameterise a Bradley-Terry model. Instead of parameterising a classifier directly via differences in log likelihoods, DPO uses the difference in scaled log likelihood *ratios* between the fine-tuned model and a frozen reference model. Thus the probability that a completion x_1 is preferred to a completion x_2 given an input prompt c is modelled as:

$$p_\theta(x_1 \succ x_2|c) = \sigma\left(\beta\log\frac{p_\theta(x_1|c)}{p_{\text{ref}}(x_1|c)} - \beta\log\frac{p_\theta(x_2|c)}{p_{\text{ref}}(x_2|c)}\right). \tag{11}$$

In our notation, the DPO preference model therefore amounts to a particular choice of scoring function $s_\theta(x,c) = \beta\log\frac{p(x|c)}{p_{\text{ref}}(x|c)}$. Assuming an autoregressive decomposition of $p(x|c)$, this scoring function is equivalent to the conditional autoregressive scoring function,

$$s_\theta(x,c) = \sum_{i=1}^{L}\log p(x^i|x^{<i},c)\,, \tag{12}$$

if the reference model is constant and $\beta = 1$.

The non-constant reference model in DPO imposes a KL penalty on the deviation between the fine-tuned p_θ and the reference model, which helps prevent collapse in the fine-tuned distribution [Rafailov et al., 2023]. Although some recent work has reported success in adapting DPO to the protein fitness prediction setting [Lee et al., 2023], in our own experiments we did not find this regularisation necessary to achieve good performance. We hypothesise that this is because we do not require generations from the model, unlike typical applications of DPO.

C   Additional Results

C.1   Fitness Prediction: Score function and Loss Ablation

A core contribution of our work is the application of ranking-based loss function to directly fine-tune the likelihoods of masked (ESM-1v and ESM-2) and conditional autoregressive (PoET) PLM models. As an additional ablation study, we apply i) the ranking loss function in Equation (2) to the setting where a linear regression head is applied to the model embeddings, and ii) an MSE loss function is applied to the likelihood scoring functions. Below is the full table of results for each of the four settings.

Whilst we notice that the ranking loss function applied to the regression setting performs quite well, the MSE loss directly applied to the likelihood scoring functions does not.

Table 4: Low-n fitness prediction comparing masked and family-based PLM scoring strategies and loss functions on the Spearman correlation (higher is better). Evaluated on 5 multiple mutant landscapes from ProteinGym. (Standard deviation over three seeds in parenthesis).

| | | | **Single Mutants** | | | | |
Model	Scoring Fn.	Loss	$n = 24$	$n = 32$	$n = 48$	$n = 128$	$n = 512$
ESM-1v	linear head	mse	0.236 (0.07)	0.263 (0.04)	0.325 (0.02)	0.415 (0.00)	0.535 (0.02)
(650M)		ranking	0.312 (0.01)	0.326 (0.05)	0.353 (0.02)	0.437 (0.02)	0.590 (0.01)
	wt-marginals	mse	0.300 (0.01)	0.301 (0.01)	0.246 (0.00)	0.282 (0.02)	0.495 (0.01)
		ranking	0.457 (0.01)	0.479 (0.02)	0.481 (0.02)	0.552 (0.01)	0.641 (0.00)
ESM-2	linear head	mse	0.263 (0.02)	0.275 (0.06)	0.308 (0.02)	0.398 (0.01)	0.535 (0.02)
(650M)		ranking	0.321 (0.01)	0.301 (0.03)	0.330 (0.02)	0.411 (0.02)	0.563 (0.01)
	wt-marginals	mse	0.298 (0.01)	0.330 (0.02)	0.258 (0.03)	0.267 (0.03)	0.475 (0.01)
		ranking	0.449 (0.01)	0.455 (0.02)	0.466 (0.02)	0.530 (0.01)	0.627 (0.01)
PoET	linear head	mse	0.429 (0.01)	0.445 (0.03)	0.472 (0.02)	0.555 (0.01)	0.644 (0.00)
		ranking	0.456 (0.03)	0.468 (0.01)	0.502 (0.03)	0.575 (0.00)	0.664 (0.01)
	likelihood	mse	0.416 (0.01)	0.409 (0.01)	0.403 (0.01)	0.378 (0.01)	0.230 (0.03)
		ranking	0.513 (0.01)	0.514 (0.01)	0.541 (0.01)	0.594 (0.00)	0.672 (0.01)
Kermut	GP head	NLL	0.299 (0.02)	0.309 (0.05)	0.341 (0.01)	0.425 (0.01)	0.553 (0.01)
			Multiple Mutants				
Model	Scoring Fn.	Loss	$n = 24$	$n = 32$	$n = 48$	$n = 128$	$n = 512$
ESM-1v	linear head	mse	0.469 (0.05)	0.494 (0.01)	0.520 (0.02)	0.634 (0.01)	0.771 (0.01)
(650M)		ranking	0.438 (0.02)	0.474 (0.02)	0.524 (0.02)	0.644 (0.00)	**0.777** (0.01)
	wt-marginals	mse	0.459 (0.02)	0.451 (0.01)	0.411 (0.01)	0.402 (0.02)	0.544 (0.00)
		ranking	**0.567** (0.04)	**0.585** (0.01)	**0.588** (0.03)	**0.649** (0.01)	0.753 (0.01)
ESM-2	linear head	mse	0.438 (0.03)	0.427 (0.04)	0.481 (0.03)	0.596 (0.02)	0.743 (0.02)
(650M)		ranking	0.429 (0.03)	0.447 (0.02)	0.503 (0.04)	0.648 (0.01)	**0.773** (0.00)
	wt-marginals	mse	0.454 (0.02)	0.461 (0.01)	0.345 (0.02)	0.407 (0.00)	0.522 (0.02)
		ranking	**0.577** (0.00)	**0.593** (0.01)	**0.603** (0.02)	**0.651** (0.02)	0.758 (0.01)
PoET	linear head	mse	0.558 (0.04)	0.582 (0.03)	0.627 (0.03)	0.715 (0.00)	0.793 (0.01)
		ranking	0.571 (0.00)	0.574 (0.02)	0.632 (0.01)	0.723 (0.01)	0.801 (0.00)
	likelihood	mse	0.600 (0.00)	0.601 (0.00)	0.600 (0.01)	0.583 (0.00)	0.424 (0.01)
		ranking	**0.672** (0.01)	**0.667** (0.01)	**0.689** (0.00)	**0.736** (0.01)	**0.805** (0.01)
Kermut	GP head	NLL	0.397 (0.02)	0.426 (0.02)	0.504 (0.02)	0.614 (0.01)	0.724 (0.01)

C.2   Fitness Prediction: ProteinNPT Baseline methods

Similarly, we ablate fine-tuning the ProteinNPT model, with both ESM-1v or MSAT frozen embeddings, using the MSE loss, as proposed in [Notin et al., 2023b], and also with the ranking loss function in Equation (2). We see that the ranking loss function improves the results across all the single mutant landscapes, but results are mixed for the multi-mutant landscapes.

ProteinNPT baselines [Notin et al., 2023b] that utilize frozen embeddings. Spearman correlation (higher is better) on 8 single mutant landscapes and 5 multiple mutant landscapes from ProteinGym.

Table 5: Multi mutants: ProteinNPT baselines [Notin et al., 2023b] that utilize frozen embeddings. Spearman correlation (higher is better) on 8 single mutant landscapes and 5 multiple mutant landscapes from ProteinGym.

Model Name	Frozen Emb.	Single Mutants				
		$n = 24$	$n = 32$	$n = 48$	$n = 128$	$n = 512$
ProteinNPT	MSAT	0.408 (0.02)	0.433 (0.02)	0.470 (0.03)	0.541 (0.02)	0.602 (0.02)
	ESM-1v	0.376 (0.03)	0.415 (0.02)	0.428 (0.02)	0.489 (0.01)	0.60 (0.02)
Emb. aug.	MSAT	0.419 (0.02)	0.424 (0.01)	0.456 (0.02)	0.507 (0.01)	0.553 (0.0)
	ESM-1v	0.446 (0.01)	0.451 (0.01)	0.477 (0.01)	0.505 (0.0)	0.550 (0.0)
OHE aug.	MSAT	0.418 (0.01)	0.429 (0.01)	0.441 (0.0)	0.467 (0.01)	0.496 (0.0)
	ESM1v	0.457 (0.01)	0.466 (0.01)	0.478 (0.0)	0.502 (0.01)	0.526 (0.0)
OHE	-	0.116 (0.01)	0.144 (0.03)	0.179 (0.01)	0.314 (0.01)	0.488 (0.0)
Kermut-seq	ESM-2	0.299 (0.02)	0.309 (0.05)	0.341 (0.01)	0.425 (0.01)	0.553 (0.01)

Model Name	Frozen Emb.	Multiple Mutants				
		$n = 24$	$n = 32$	$n = 48$	$n = 128$	$n = 512$
ProteinNPT	MSAT	0.505 (0.02)	0.511 (0.03)	0.591 (0.02)	0.696 (0.01)	0.791 (0.01)
ProteinNPT	ESM-1v	0.425 (0.07)	0.438 (0.05)	0.501 (0.03)	0.640 (0.01)	0.769 (0.0)
Emb. aug.	MSAT	0.577 (0.02)	0.581 (0.01)	0.614 (0.0)	0.696 (0.01)	0.764 (0.0)
Emb. aug.	ESM1v	0.455 (0.02)	0.440 (0.01)	0.505 (0.02)	0.624 (0.01)	0.702 (0.01)
OHE aug.	MSAT	0.607 (0.01)	0.616 (0.01)	0.622 (0.01)	0.684 (0.01)	0.763 (0.01)
OHE aug.	ESM1v	0.443 (0.01)	0.460 (0.01)	0.475 (0.02)	0.566 (0.02)	0.711 (0.01)
OHE		0.255 (0.02)	0.268 (0.02)	0.314 (0.02)	0.473 (0.01)	0.664 (0.01)
Kermut-seq	ESM-2	0.397 (0.02)	0.426 (0.02)	0.504 (0.02)	0.614 (0.01)	0.724 (0.01)

C.3 Additional Results: Generalisation of Seen vs Unseen residue positions

We provide Spearman correlation results for the $n = 128$ fitness prediction setting specifically looking at out-of-distribution generalisation at unseen mutated residues. That is, for single mutant landscapes the number of *seen* mutant positions in the training datasets (varies per landscape): min=60, max=114, mean=82.67, and the number of *unseen* mutant positions: min=17, max=657, mean=172.46. For single-mutant landscapes, we classify test set sequences as seen (mutation present in the train set) or unseen (mutation absent). For multi-mutant landscapes, a test set sequence is considered seen if it has up to two mutations that occur in the train set sequences; otherwise, it is unseen. The number of seen sequences in the test set of multi-mutant landscapes is on average 2,124 (equivalent to approximately 42% of sequences in the test set) and 2,875 unseen sequences. Note, the test set size varies per protein landscape, however, for multi-mutant landscapes we limit it to 5,000 sequences.

C.4 Additional Results: More Expressive Masked Scoring Functions

In Table 7 we show the complete results for additional masked PLM scoring functions that attempt to capture the epistasis effects in the multi-mutant landscapes. We provide results for ESM-1v and ESM-2 for the additional strategies applied to five multi-mutant landscapes, as introduced in Meier et al. [2021] and Johnson et al. [2024].

Note, due to GPU memory requirement of the masked-modulo strategy, we reduce the hyperparameters relative to the length of the protein sequence in order to fit on an H100 GPU. For example, batch size (B) and K for each landscape were set to GRB: (B=8, K=8), GFP: (B=4, K=8), HIS: (B=8, K=8), PABP: (B=4, K=4) and CAP: (B=2, K=7).

For each strategy proposed in Meier et al. [2021], as an ablation, we modify them to consider the likelihood of every token in the sequence when computing the score, rather than just the likelihood at the mutations (we denote these modified strategies with $'$). As a result, the summation in Equation (5) is modified from $\sum_{i:x_{wt}^i \neq x^i}$ to $\sum_i$.

For the first time, we demonstrate that whilst not all additional compute improves over the highly efficient wt-marginal strategy, the 'modulo' masking strategy [Johnson et al., 2024] outperforms all others with $n = 128$ or 512, but requires $K \cdot B$ times more forward passes, where $K = 4$ or 8 depending on landscape (specified in Appendix C.4).

Table 6: Seen vs Unseen Spearman correlation scores (higher is better) evaluated on the 8 single mutant landscapes (left) and 5 multi-mutant landscapes (right) for the $n = 128$ dataset setting.

Model Name	Scoring Function	Loss Type	single-mutants Seen	Unseen	multi-mutants Seen	Unseen
ESM-1v (650M)	linear head	mse	0.460	0.331	0.646	0.604
		ranking	0.492	0.315	0.651	0.609
	wt-marginals	mse	0.350	0.234	0.412	0.387
		ranking	**0.592**	**0.509**	0.652	0.643
ESM-2 (650M)	linear head	mse	0.453	0.297	0.605	0.556
		ranking	0.447	0.335	0.649	**0.622**
	wt-marginals	mse	0.329	0.192	0.423	0.385
		ranking	**0.568**	**0.455**	**0.658**	0.620
PoET	linear head	mse	0.571	0.517	0.700	0.695
		ranking	0.601	0.535	0.716	0.715
	likelihood	mse	0.382	0.366	0.576	0.613
		ranking	**0.612**	**0.549**	**0.728**	**0.741**
Kermut	GP head	NLL	0.464	0.363	0.607	0.558
ProteinNPT (MSAT)	-	mse	0.563	0.462	0.694	0.670
	-	ranking	0.579	0.474	0.675	0.664
ProteinNPT (ESM-1v)	-	mse	0.529	0.420	0.641	0.601
	-	ranking	0.553	0.465	0.642	0.607

Table 7: Masked PLM scoring strategies evaluated on five multi-mutant ProteinGym landscapes, where M is the number of mutations in a sequence, B is the batch size, and K is the masked-modulo constant (set to 4 or 8 depending on landscape).

Scoring Function	Steps	Loss	ESM-1v $n = 32$	$n = 128$	$n = 512$	ESM-2 $n = 32$	$n = 128$	$n = 512$
wt-marginals	1	mse	0.446	0.414	0.544	0.461	0.407	0.522
Meier et al. [2021]		ranking	0.577	0.642	0.753	**0.593**	**0.651**	0.758
masked-mt-marginals	B	mse	0.389	0.362	0.562	0.392	0.328	0.561
Meier et al. [2021]		ranking	0.522	0.650	0.755	0.559	0.651	0.766
masked-mt-marginals$'$	B	mse	0.572	0.604	0.602	0.571	0.629	0.632
		ranking	0.555	0.586	0.647	0.558	0.606	0.635
mt-marginals	B	mse	0.214	0.291	0.533	0.264	0.330	0.530
Meier et al. [2021]		ranking	0.351	0.578	0.754	0.398	0.591	0.750
mt-marginals$'$	B	mse	**0.579**	0.617	0.622	0.565	0.612	0.627
		ranking	0.552	0.644	0.767	0.525	0.646	**0.771**
masked-modulo	$K \cdot B$	mse	**0.579**	0.621	0.645	0.568	0.586	0.620
Johnson et al. [2024]		ranking	0.529	**0.654**	**0.769**	0.534	**0.661**	**0.774**

C.5 Compute requirements

All experiments were run on either A100 or H100 NVIDIA GPUs. Compute required for a single fine-tuning run varies based on the model, the length of the protein sequences, and the size of the dataset. We provide representative timings averaged over the 8 single mutant landscapes for $n = 512$ in Table 8. Design experiments involved 10 rounds of fine-tuning and therefore required roughly ten times the computation of a single fine-tuning run.

During this research, the compute resources used were more than required for the experiments detailed in the paper, as additional compute was utilised for preliminary experimentation.

Table 8: Representative run times for fine-tuning ($n = 512$) averaged over 8 single-mutant landscapes and across 3 seeds, on an H100 GPU.

Model name	Time
ProteinNPT (MSAT)	24 m
ProteinNPT (ESM-1v)	34 m
ESM-1v (linear head, mse)	35 m
ESM-1v (wt-marginals, rank)	7 m
ESM-2 (linear head, mse)	15 m
ESM-2 (wt-marginals, rank)	4 m
PoET (linear head, mse)	7 m
PoET (likelihood, rank)	7 m

C.6 Zero-shot PLM performance

As discussed in Section 5.2 Result 2, the ranking-based fine-tuning performance of PoET is not attributed directly to higher zero-shot performance of the base PLM. We evaluate the zero-shot performance of the base models here, on the single mutant landscapes using the $n = 128$ test split and report the Spearman correlation between likelihood scoring function and the fitness measurement. The MSAT zero-shot predictions are taken from Notin et al. [2023a] for our test splits.

Table 9: Zero-shot Spearman correlation on the $n = 128$ test splits for the base PLM models.

Base Model	Zero-shot Spearman
MSA Transformer (MSAT)	0.399
ESM-1v (wt-marginals, rank)	0.437
ESM-2 (wt-marginals, rank)	0.372
PoET (likelihood, rank)	0.417

C.7 Low-n Fitness Prediction with Ensemble Models

Table 10: Low-n fitness prediction Spearman results comparing the masked- and family-based MSA-ensemble models to their single model counterparts. Averaged over three seeds and 8 single mutant landscapes (left) and five multi-mutant landscapes (right).

Model Name	Scoring Fn.	Loss	Single-mutants		Multi-mutant	
			$n = 32$	$n = 128$	$n = 32$	$n = 128$
PNPT (MSAT)	-	mse	0.420	0.532	0.511	0.696
PNPT (MSAT) w/ dropout	-	mse	0.421	0.532	0.512	0.696
ESM-2	wt-marginal	ranking	0.455	0.530	0.593	0.651
		mse	0.330	0.267	0.461	0.407
	linear head	ranking	0.307	0.411	0.447	0.648
		mse	0.280	0.398	0.427	0.596
ESM-2 ensemble	wt-marginal	**ranking**	**0.477**	**0.553**	**0.621**	**0.683**
		mse	0.347	0.335	0.507	0.440
	linear head	ranking	0.357	0.435	0.511	0.694
		mse	0.342	0.428	0.505	0.658
PoET	likelihood	ranking	0.514	0.594	0.667	0.736
		mse	0.409	0.378	0.601	0.583
	linear head	ranking	0.468	0.575	0.574	0.723
		mse	0.445	0.554	0.582	0.715
PoET MSA-ensemble	likelihood	**ranking**	**0.524**	**0.607**	**0.696**	**0.757**
		mse	0.412	0.390	0.623	0.609
	linear head	ranking	0.504	0.598	0.618	0.744
		mse	0.486	0.591	0.632	0.736

C.8 Additional sequence design recall curves

C.8.1 ESM-2 masked-ensembles

ESM-2 masked-ensembles comparing the wt-marginal scoring strategy fine-tuning via ranking loss to the linear regression head fine-tuned with MSE loss. AUC = area under the curve (higher is better). Each ensemble contains 5 members, with more details specified in Appendix A.3. Evaluated on 8 single mutant landscapes (left) and 5 multiple mutant landscapes (right).

Figure 4: ESM-2 (650) masked-ensembles (left): single mutation landscapes. (right) multiple mutation landscapes.

C.8.2 Family-based PLMs

PoET MSA-ensemble comparing the likelihood fine-tuning via ranking loss to the linear regression head fine-tuned with MSE loss. AUC = area under the curve (higher is better). Each ensemble contains 5 members, with more details specified in Appendix A.2. Evaluated on 8 single mutant landscapes (left) and 5 multiple mutant landscapes (right).

Figure 5: PoET MSA-ensembles (left): single mutants landscapes. (right) multiple mutant landscapes.

C.8.3 ProteinNPT Baselines

ProteinNPT baseline methods taken from [Notin et al., 2023b]. AUC = area under the curve (higher is better). Uncertainty is calculated using MC dropout, with more details specified in Appendix A.4. Evaluated on 8 single mutant landscapes (left) and 5 multiple mutant landscapes (right).

Figure 6: ProteinNPT baselines (left): single mutation landscapes. (right) multiple mutation landscapes.

C.8.4 Single mutant landscape results

Each method is evaluated on each of the 8 single mutation landscapes and each of the 5 multiple mutation landscape, repeated across 3 random seeds.

Figure 7: Sequence design top 100 sequences recall results on each of the single mutation landscapes. Masked PLM ESM-2 and ESM-2 masked-ensembles (left), Family-based PoET and PoET MSA-ensemble (right).

e. P53_HUMAN_Giacomelli_2018_WT_Nutlin

f. RL40A_YEAST_Roscoe_2013

g. REV_HV1H2_Fernandes_2016

h. TAT_HV1BR_Fernandes_2016

Figure 8: Sequence design top 100 sequences recall results on each of the single mutation landscapes. Masked PLM ESM-2 and ESM-2 masked-ensembles (left), Family-based PoET and PoET MSA-ensemble (right).

C.8.5 Multiple mutant landscape results

a. CAPSD_AAV2S_Sinai_2021

b. GFP_AEQVI_Sarkisyan_2016

c. GRB2_HUMAN_Faure_2021

Figure 9: Sequence design top 100 sequences recall results on each of the multiple mutation landscapes. Masked PLM ESM-2 and ESM-2 masked-ensembles (left), Family-based PoET and PoET MSA-ensemble (right).

d. HIS7_YEAST_Pokusaeva_2019

e. PABP_YEAST_Melamed_2013

Figure 10: Sequence design top 100 sequences recall results on each of the single mutation landscapes. Masked PLM ESM-2 and ESM-2 masked-ensembles (left), Family-based PoET and PoET MSA-ensemble (right).

D   Broader Societal Impacts

We provide a framework of fine-tuning PLMs to predict protein fitness. The idea is that these protein fitness predictor can then be used to design novel proteins. We understand that malicious actors could use our work to design harmful proteins. That being said, our work sits within the wider literature of protein design, and thus this threat is not unique to our work. However, we strongly urge the community to only use our work for purposes which are beneficial to society.

Table 11: Sequence design full table of AUC results, across models, scoring functions, loss functions, ensembles, and baseline methods. AUC = area under the curve (higher is better) presented for both Top 30% recall (as per Notin et al. [2023b], and recall over the Top 100 sequences in the pool. Averaged over 8 single mutant landscapes (left) and 5 multiple mutant landscapes (right).

Model Name	Scoring Fn.	Loss	Top 100 Recall	Top 30% Recall
Single Mutants				
ESM2 (650M)	linear head	mse	4.35 (0.07)	4.40 (0.06)
		ranking	4.87 (0.18)	4.61 (0.06)
	wt-marginals	mse	4.52 (0.05)	4.46 (0.03)
		ranking	5.30 (0.08)	5.03 (0.03)
ESM2 (650M) ensemble	linear head	mse	4.57 (0.11)	4.60 (0.07)
	wt-marginals	ranking	5.30 (0.06)	5.12 (0.02)
PoET	linear head	mse	5.04 (0.14)	4.97 (0.02)
		ranking	5.53 (0.12)	5.21 (0.03)
	likelihood	mse	3.68 (0.14)	3.70 (0.02)
		ranking	5.52 (0.08)	5.21 (0.03)
PoET ensemble	linear head	mse	5.11 (0.02)	5.06 (0.01)
		ranking	5.60 (0.05)	5.28 (0.04)
	likelihood	mse	3.78 (0.09)	3.74 (0.06)
		ranking	5.59 (0.05)	5.26 (0.02)
PNPT (MSAT) + dropout	-	mse	5.57 (0.02)	5.10 (0.03)
Emb. aug. (ESM1v)	-	mse	5.07 (0.11)	4.95 (0.02)
OHE	-	mse	4.19 (0.09)	4.44 (0.04)
OHE aug. (MSA)	-	mse	4.54 (0.04)	4.68 (0.02)
OHE aug. (ESM1v)	-	mse	4.52 (0.02)	4.76 (0.03)
Multiple Mutants				
ESM2 (650M)	linear head	mse	2.96 (0.36)	2.14 (0.03)
		ranking	3.58 (0.14)	2.36 (0.01)
	wt-marginals	mse	2.79 (0.29)	2.01 (0.01)
		ranking	3.85 (0.25)	2.58 (0.02)
ESM2 (650M) ensemble	linear head	mse	3.34 (0.23)	2.31 (0.03)
	wt-marginals	ranking	3.91 (0.14)	2.59 (0.03)
PoET	linear head	mse	3.71 (0.32)	2.24 (0.06)
		ranking	4.08 (0.51)	2.44 (0.31)
	likelihood	mse	1.58 (0.20)	1.50 (0.03)
		ranking	3.73 (0.18)	2.30 (0.02)
PoET ensemble	linear head	mse	4.29 (0.20)	2.78 (0.02)
		ranking	4.40 (0.22)	2.78 (0.04)
	likelihood	mse	1.73 (0.16)	1.78 (0.08)
		ranking	4.45 (0.28)	2.80 (0.03)
PNPT (MSAT) + dropout	-	mse	4.12 (0.13)	2.60 (0.03)
Emb. aug. (ESM1v)	-	mse	3.61 (0.22)	2.62 (0.03)
OHE	-	mse	3.10 (0.22)	2.33 (0.06)
OHE aug. (MSA)	-	mse	3.73 (0.23)	2.68 (0.03)
OHE aug. (ESM1v)	-	mse	3.37 (0.28)	2.47 (0.04)