Solu – a cloud platform for real-time genomic pathogen surveillance

Timo J Moilanen[1*], Kerkko Visuri[1], Jonatan Lehtinen[1], Irene Ortega-Sanz[2], Jacob L
Steenwyk[3], Samuel Sihvonen[1]

1 Solu Healthcare Oy, Fredrikinkatu 63 A 302, 00100 Helsinki, Finland

2 Department of Food Technology, Safety and Health, Faculty of Bioscience Engineering,
Ghent University, Coupure Links 653, 9000 Ghent, Belgium

3 Howards Hughes Medical Institute and the Department of Molecular and Cell Biology,
University of California, Berkeley, Berkeley, CA, USA

*Corresponding author: timo@solugenomics.com (Timo J Moilanen)

Abstract

Background

Genomic surveillance is extensively used for tracking public health outbreaks and healthcare-associated pathogens. Despite advancements in bioinformatics pipelines, there are still significant challenges in terms of infrastructure, expertise, and security when it comes to continuous surveillance. The existing pipelines often require the user to set up and manage their own infrastructure and are not designed for continuous surveillance that demands integration of new and regularly generated sequencing data with previous analyses. Additionally, academic projects often do not meet the privacy requirements of healthcare providers.

Results

We present Solu, a cloud-based platform that integrates genomic data into a real-time, privacy-focused surveillance system.

Evaluation

Solu's accuracy for taxonomy assignment, antimicrobial resistance genes, and phylogenetics, was comparable to established pathogen surveillance pipelines. In some cases, Solu identified antimicrobial resistance genes that were previously undetected. Together, these findings demonstrate the efficacy of our platform.

Conclusions

By enabling reliable, user-friendly, and privacy-focused genomic surveillance, Solu has the potential to bridge the gap between cutting-edge research and practical, widespread

37 application in healthcare settings. The platform is available for free academic use at

38 platform.solugenomics.com.

39 Keywords: Workflow, Genomics, Whole-genome sequencing, Infection prevention,

40 Outbreak, Phylogeny, Privacy

41 Background

Bacterial and fungal pathogens, along with their antimicrobial resistance, are causing an

increasing burden on healthcare and public health (1–3). Advances in microbial genomics

have significantly enhanced infection prevention and outbreak surveillance by providing

detailed information about pathogen species, antimicrobial resistance, and phylogenetics

(4,5). As the cost of Whole-Genome Sequencing (WGS) has decreased rapidly, continuous

genomic surveillance has become a cost-effective method for infection prevention and

control (6,7). The interest towards genomic analysis has led to the emergence of several

pathogen analysis tools, such as nf-core (8), TheiaProk (9), ASA3P (10), CamPype (11),

Nullarbor (12), Bactopia (13), and Galaxy (14), which enable genomic analysis also for users

without in-depth expertise in bioinformatics or computer science.

Despite these advancements, bioinformatics still remains a bottleneck for the widespread

adoption on pathogen genomic surveillance due to limitations in usability, speed, and

security (7).

Most existing pipelines (8–13) are operated using the command-line interface (CLI) and

require the user to manage their own data storage and computation infrastructure. While it is

possible to learn their usage without advanced computational knowledge (15), many

practitioners simply don't have the time or willingness for it and prefer graphical user

interfaces instead. Additionally, most existing tools are designed for single-use execution,

which is a challenge for continuous surveillance where new sequencing data is often

generated in small batches (6,16). To facilitate ongoing analysis, users must implement their

own processes for integrating new and old data.

Fast time to results has been identified as a key component for effective genomic

surveillance (6,16). As new samples arrive in batches and need to be compared to all

previously accumulated samples, computation time can become a significant bottleneck if

using a single-workstation installation. Also, unless the pipelines are highly automated,

running the analyses often requires specially trained personnel who might not be available

immediately upon the arrival of new data.

Academia-led projects developed under FAIR (Findable, Accessible, Interoperable,

Reusable) principles often lack the necessary privacy focus to meet the stringent

requirements of healthcare providers (17). In contrast, healthcare providers must adhere to

stringent legal requirements, such as the U.S. HIPAA Privacy Rule (18), ruling out many

existing online platforms for genomic surveillance.

It is possible for healthcare providers to overcome these limitations by implementing their

own automated pipelines, but it requires significant investments in bioinformatics and

computational infrastructure, and the lack of these resources is a challenge in many facilities

(19). To fill this gap, we present Solu – an automated, fast, and secure web application for

analyzing WGS samples.

Implementation

80 Solu is a cloud-based platform for the analysis of bacterial and fungal WGS samples. Its

81 automated bioinformatics pipeline includes genomic characterization and phylogenetic

82 comparison. Its cloud implementation is built to match the usability, speed, and security

83 requirements of ongoing genomic surveillance in healthcare facilities.

84 Bioinformatics pipeline

The platform runs a fully automated pathogen analysis pipeline, which is illustrated in Figure

1. The pipeline includes *de novo* assembly, quality assurance (QA), species identification

and genomic characterization for each uploaded sample, and phylogenetic comparison

between all uploaded samples of the same species. It is triggered automatically after each

file upload and cannot be configured by the user. This section presents an overview of the

pipeline, and a detailed description can be found in Supplementary Material 1.

Figure 1. Bioinformatics pipeline

Input format

The supports three input types: paired-end short reads in FASTQ format, long reads in

FASTQ format, or an assembled genome in FASTA format. Analysis of long reads is still

considered an experimental feature.

Assembly, QA, and species detection

Short reads are quality checked using FastQC (20), quality corrected with fastp (21), and

assembled using Shovill (22). Long reads are pre-processed, assembled and polished with

Dragonflye (23). After assembly, all samples are standardized using any2fasta (24) and

quality assessed with Quast (25).

Species is identified with Bactinspector (26). To identify fungal species, Bactinspector's

default database was augmented with all fungal reference genomes from the NCBI

Taxonomy (27). The augmented database also includes clade-level reference genomes for

Candida auris.

Genomic characterization

Analysis of bacterial species includes multi-locus sequence typing (MLST) with mlst (28),

AMR annotation using AMRFinderPlus (29), and plasmid analysis with MOB-suite (30).

The pipeline also includes an experimental antifungal resistance (AFR) gene annotation for

the species *Candida auris.* AFR annotation is implemented using AMRFinderPlus with a

custom database of known AFR point mutations sourced from AFRBase (31).

Phylogenetic comparison

The pipeline's phylogeny is based on constructing a multiple sequence alignment for each

species. Based on the species in question, multiple sequence alignment is computed by

either a reference-based or reference-free method.

The reference-based alignment is considered more robust and has been implemented for 21

commonly analyzed species. It includes aligning each sample to the species' reference

genome using Snippy (32), creating a multiple-sequence alignment using snippy-core (32),

and filtering out low quality SNPs using an in-house script.

The reference-free alternative is implemented to support analysis of species that are not yet

supported by the reference-based alignment. It is computed using the split-kmer analysis

tool SKA (33).

After constructing the multiple sequencing alignment, the phylogenetic comparison includes

pairwise SNP distances, clustering, and phylogenetic tree inference. SNP distances are

counted from the multiple sequence alignment using snp-sites (34) and snp-dists (35).

Samples are clustered with a 20-SNP single-linkage clustering threshold using an in-house

Python script. Phylogenetic trees are inferred using a general time reversible maximum

likelihood model from IQ-TREE 2 (36) and midpoint-rooted using TreeTime (37). Both IQ-

TREE 2 and TreeTime are run using the Augur toolkit (38).

Automated cloud infrastructure

The cloud infrastructure of Solu is built on three principles: usability, speed, and security.

Figure legend

☐ User action

☐ Managed by Solu

Figure 2. Solu's cloud platform implementation

Usability

The Solu Platform is web based, enabling practitioners to use it without installing software or

running command-line tools (Figure 2). New samples are uploaded using the drag-and-drop

web UI, which automatically triggers a bioinformatics pipeline. The pipeline requires zero

configuration from the user, which promotes repeatability and alleviates the need for in-depth

bioinformatics knowledge. The analysis results are stored in the cloud, eliminating the need

for a self-implemented storage system and enabling effortless result sharing between

colleagues.

Each newly uploaded sample is also automatically compared to previously uploaded

samples of the same species, which enables detecting potential new outbreaks quickly. For

instance, when a user uploads a *Salmonella enterica* sample, the platform automatically re-

computes the phylogenetics for all uploaded *Salmonella enterica* samples and highlight

possible clusters.

Speed

The platform's cloud infrastructure is optimized for speed even during peak usage. This is

achieved by running each computation-intensive workload in a separate Docker container

with optimized resource (CPU and memory) distribution. These containers are orchestrated

by a cloud computing cluster that is automatically scaled up and down based on usage, up

to a maximum of 512 CPUs and 2 TB of memory. The cluster also contains a pool of hot

standby resources, which allows starting the analysis of a new sample within seconds of its

upload.

This auto-scaling capability brings the user substantial speed improvements by allowing the

parallelization of some of the analyses in the pipeline. In addition, it allows analyzing a whole

batch of samples simultaneously, leading to a significant reduction in overall time-to-results

when analyzing a batch of samples. Importantly, these speed improvements are achieved

without a significant increase in computation costs.

Security

The platform's data is stored in a secure cloud storage with set read and write permissions.

All computations occur within a virtual private network, monitored by automated access

control checks. Solu implements strict data security protocols, including appropriate access

permissions, encryption, continuous monitoring, code reviews, staff training, and other

cybersecurity measures. Accordingly, Solu adheres to the U.S. HIPAA rule, and can sign a

Business Associate Agreement (BAA) for enterprise customers. Solu also allows enterprise

customers to choose between U.S. or EU as their data storage. Further information

regarding data security practices can be found at https://solugenomics.trust.site/.

169 Evaluation

To evaluate the Solu platform, we reproduced four outbreak investigation studies using

published genomic data (**Table 1**). Data was obtained from the European Nucleotide Archive

as raw reads and uploaded to the Solu platform. All samples were paired-end short-reads in

FASTQ format.

We evaluated Solu's performance by computing metric scores for species identification,

MLST, clade construction, and AMR predictions against the references. Phylogenetic trees

were exported from Solu. Tree topologies were compared visually, and where raw tree data

was available, we calculated a Robinson-Foulds distance using TreeDist (39). Both

reference-based and reference-free phylogenetic pipelines were run for all datasets and

compared against each other to validate the platform's internal consistency.

We also measured the required time for analysis of each sample. Plasmids were not

evaluated in this study due to the absence of plasmid annotations in the original studies.

Table 1. Overview of evaluation datasets

Species	BioProject accession	Number of samples	Raw data size (GB, zipped)
Staphylococcus aureus	PRJNA400143 (40)	135	16.47
Enterococcus faecium	PRJEB34664 (41)	99	15.18
Salmonella enterica	Multiple (42)	23	5.03

| Candida auris | PRJNA328792 (43) | 47 | 50.94 |

Results

Evaluation results

186 The Solu platform successfully completed the bioinformatics pipeline for all 304 samples. A

187 screenshot of the platform's home screen is shown in Figure 3. This workspace, including all

188 samples and results, is also accessible at a user-friendly web interface at

189 https://platform.solugenomics.com/w/solu-publication-2 and

190 https://platform.solugenomics.com/w/solu-publication-3.

191
Figure 3. Summary of the samples shown in Solu

Species, MLST and clade assignment

Solu accurately identified the species of all 304 samples and assigned the correct clade for

all 47 *Candida auris* samples.

Exact MLST matches were observed in 210 out of 230 (91.3%) isolates with known

sequence types (Table 2). However, 18 of 20 non-exact MSLT matches were single-locus

variants.

Table 2. Species identification and MLST concordance. Solu's results compared to the original

publications when available there

Species	Species identification accuracy	MLST exact match accuracy	MLST accuracy including single-locus variants
S. aureus	100.0% (135/135)	87.1% (115/132)	98.4% (130/132)
E. faecium	100.0% (99/99)	96.9% (95/98)	100.0% (98/98)
S. enterica	100.0% (23/23)	*MLST not reported in the original article*	
C. auris	100.0% (47/47)	*MLST scheme not defined*	

Antimicrobial resistance

The antimicrobial resistance (AMR) gene detection results from Solu were compared with

those of the references. Concordance varied by species, ranging from 99.6% for *E. faecium*

to 93.1% for *S. aureus*. Table 3 summarizes some commonly studied AMR loci, while the full

results can be viewed online.

Table 3. Sensitivity of Solu's AMR prediction

Species	Overall AMR locus sensitivity	*vanA*	*vanB*	*mecA*	Other key genes
S. aureus	93.1% (309/332)	N/A	N/A	98.8% (81/82)	*mupA*: 100% (3/3), *blaZ*: 90.9% (100/110)
E. faecium	99.6% (515/517)	100.0% (30/30)	100.0% (69/69)	N/A	*ermB*:100.0% (95/95) *tet*: 100.0% (4/4)
S. enterica	*AMR results not reported in the original article*				
C. auris	90.9% (40/44)	N/A	N/A	N/A	*ERG11_K143R*: 100.0% (8/8)

Note: N/A indicates that the gene is not typically relevant for the species.

Key AMR genes, such as the *vanA/vanB* type and *mecA*, were detected with 100% and

98.8% sensitivity, respectively. Antifungal resistance mutation detection for Candida auris

showed a 90.9% sensitivity. The results matched the original findings for 43 isolates.

However, Solu identified the *ERG11_K143R* mutation in 2 Clade I isolates, which were

originally reported as having the *Y123F* mutation, and detected 2 isolates lacking ERG

mutations.

The main reason for lower agreement in the *S. aureus* dataset was Solu's inability to find

any *dfrA* matches, whereas the original article reported 10 isolates with *dfrA*. (44)

Phylogenetics

Solu automatically generated phylogenetic trees for all four datasets, which can be viewed

and downloaded in the published workspace in "Tree view" (Figure 4).

The *E. faecium* phylogenetic tree generated by Solu demonstrated a high degree of

concordance with the reported SNP subclusters, complex types (CTs) and sequence types

(STs) of the reference (Figure 5). For the *Salmonella enterica* dataset, Solu produced a

similar topology to the reference tree (Figure 6) where the outbreak samples are separate

from the outgroup. Robinson-Foulds distance to the *S. enterica* reference tree was 2.

Figure 4. Screenshot of the *Salmonella enterica* tree in the graphical user interface

Figure 5. Solu's *E. faecium* phylogenetic tree shown as a cladogram (inner) vs. SNP

clusters, complex types (CT), and sequence types (ST) from the original publication (outer

rings). The cladogram visualization was created using Dendroscope (45).

235
Figure 6. Tanglegram of Solu's *Salmonella enterica* phylogenetic tree (left) vs. the reference

tree (right).

For the *S. aureus* and *C. auris* datasets, Solu generated phylogenetic trees in which isolates

with identical sequence types or clades consistently clustered together. Further detailed

comparisons were not possible due to the lack of raw tree data and subtyping information.

The resulting trees are provided in Supplementary Material 2.

In comparing the reference-free and reference-based pipelines, Solu's reference-free

pipeline generated highly concordant phylogenetic trees with the reference-based pipeline.

The Robinson-Foulds distances ranged from 0.08 to 0.46, as computed using TreeDist (46),

indicating a high level of similarity (see Supplementary Material 2)

Time-to-results

Time-to-results for the four datasets are presented in Table 4 and Figure 7. For bacterial

samples, Solu completed de novo assembly in an average of 7.2 minutes and variant calling

in 9.5 minutes from upload. For *C. auris* samples, de novo assembly averaged 17 minutes,

and variant calling took 23.6 minutes from upload.

Table 4. Average time-to-results per dataset**.** Shortest and longest recorded times in

parentheses. Genome size (27) and sample count of each dataset included for additional

context.

	Genome size (Mb)	Sample count	Average total time from sample upload (minutes)		
			Read quality analysis and correction	De novo assembly	Variant calling
Enterococcus faecium	2.9	99	1.5 (1.0-2.8)	5.2 (1.9-11.8)	7.4 (3.7–14.4)
Salmonella enterica	5.0	23	1.4 (1.1–1.8)	5.0 (2.9–10.1)	7.6 (5.4–12.7)
Staphylococcus aureus	2.8	135	1.9 (1.0–6.1)	9.0 (2.4–21.9)	11.4 (4.2–25.6)
Candida auris	12.2	47	3.5 (2.4–5.9)	17.0 (10.4–32.3)	23.6 (15.1–37.9)

257
Figure 7. Box plot of Solu's total time-to-results for each dataset.

Discussion

Bioinformatics remains a bottleneck to widespread use of genomic pathogen surveillance.

Usability, speed, and security are additional requirements for practical outbreak analysis in a

healthcare setting.

Our evaluation demonstrates that the Solu platform produces outputs that are largely

consistent with prior outbreak studies, using raw sequencing reads and requiring zero

configuration, with a runtime of approximately 10 minutes for bacterial samples and 20

minutes for fungal samples. Solu's phylogenetic pipelines produced results that were

internally and externally consistent.

The largest discrepancies were observed in the *Staphylococcus aureus* dataset, where the

original study used PCR for MLST assignment and applied 90% identity and 75% coverage

thresholds for AMR gene detection. We hypothesize that the different pipeline parameters

allow for higher sensitivity, at the cost of potential misidentification.

Compared to some other pipelines, Solu platform's zero-configuration design prevents users

from customizing pipeline parameters, which may result in some variation in the results. This

approach was chosen to promote usability and prevent users from inadvertently selecting

unsuitable parameters. Despite this limitation, default tool configurations provide sufficient

accuracy for a wide variety of research applications, including AMR gene characterization

and clonality assessment (47). Future studies leveraging more in-depth datasets and

epidemiologically validated outbreaks hold great potential to further strengthen and expand

the applicability of our findings.

We aim to improve the analytical capacity of the platform in future iterations, featuring

additional tooling, modifications to the analytical workflow, broader support for species and

databases, and improved runtimes among other features. We encourage users to contact

the authors to request any additional analyses or databases of interest.

In conclusion, by focusing on a robust, privacy-focused infrastructure, Solu facilitates

broader adoption of genomic pathogen surveillance, potentially bridging the gap between

research and practice.

287 Availability and requirements

Project name: Solu Platform

Project home page: https://platform.solugenomics.com

Operating system(s): Platform independent

Programming language: Typescript

Other requirements: Modern internet browser such as Google Chrome, Mozilla Firefox or

Safari

Pricing, academic free plan, and non-academic license descriptions:

www.solugenomics.com/pricing

296 List of abbreviations

297   AFR: antifungal resistance; AMR: antimicrobial resistance; CPU: Central Processing Unit;

298   CT: complex type; FAIR: Findable, Accessible, Interoperable, Reusable; HIPAA: Health

299   Insurance Portability and Accountability Act; MLST: Multi-locus Sequence Typing; QA:

300   quality assurance; SNP: single nucleotide polymorphism; ST: sequence type; WGS: Whole-

301   Genome Sequencing.

302 Declarations

303 Ethics approval and consent to participate

304   Not applicable.

305 Consent for publication

306   Not applicable.

Availability of data and materials

The data analyzed in the study are available from the European Nucleotide Archive at https://www.ebi.ac.uk/ena using the accessions provided in Table 1. The Solu workspace, including all samples and results, is accessible at https://platform.solugenomics.com/w/solu-publication-2 and https://platform.solugenomics.com/w/solu-publication-3

Competing interests

TJM, JL, KV and SS have been employed by Solu Healthcare Oy. JLS is an advisor for ForensisGroup Inc.

Funding

JLS is a Howard Hughes Medical Institute Awardee of the Life Sciences Research Foundation.

.

Authors' contributions

TM: Conceptualization, Software, Formal Analysis, Investigation, Project Administration, Writing. KV: Software, Visualization, Methodology, Validation, Writing. JL: Software, Methodology, Validation, Writing. IOS: Methodology, Review & Editing, Visualization. JLS: Writing -- Review & Editing, Funding Acquisition, and Visualization. SS: Conceptualization, Writing. All authors read and approved the final manuscript.

325 Acknowledgements

326 The authors thank the anonymous reviewers for their constructive comments.

References

1. Murray CJL, Ikuta KS, Sharara F, Swetschinski L, Robles Aguilar G, Gray A, et al. Global burden of bacterial antimicrobial resistance in 2019: a systematic analysis. The Lancet. 2022 Feb;399(10325):629–55.

2. Vallabhaneni S, Mody RK, Walker T, Chiller T. The Global Burden of Fungal Diseases. Infect Dis Clin. 2016 Mar 1;30(1):1–11.

3. Van Rhijn N, Arikan-Akdagli S, Beardsley J, Bongomin F, Chakrabarti A, Chen SCA, et al. Beyond bacteria: the growing threat of antifungal resistance. The Lancet. 2024 Sep;404(10457):1017–8.

4. Eyre DW. Infection prevention and control insights from a decade of pathogen whole-genome sequencing. J Hosp Infect. 2022 Apr;122:180–6.

5. Steenwyk JL, Rokas A, Goldman GH. Know the enemy and know yourself: Addressing cryptic fungal pathogens of humans and beyond. Chowdhary A, editor. PLOS Pathog. 2023 Oct 19;19(10):e1011704.

6. Forde BM, Bergh, Haakon, Cuddihy, Thom, Hajkowich, Kristin, Hurst, Trish, Playford, E, et al. Clinical Implementation of Routine Whole-genome Sequencing for Hospital Infection Control of Multi-drug Resistant Pathogens. Clin Infect Dis. 2023 Feb 1;76(3):e1277–84.

7. Fox JM, Saunders NJ, Jerwood SH. Economic and health impact modelling of a whole genome sequencing-led intervention strategy for bacterial healthcare-associated infections for England and for the USA. Microb Genomics [Internet]. 2023 Aug 9 [cited 2024 Sep 17];9(8). Available from: https://www.microbiologyresearch.org/content/journal/mgen/10.1099/mgen.0.001087

8. Ewels PA, Peltzer A, Fillinger S, Patel H, Alneberg J, Wilm A, et al. The nf-core framework for community-curated bioinformatics pipelines. Nat Biotechnol. 2020 Mar;38(3):276–8.

9. Libuit KG, Doughty EL, Otieno JR, Ambrosio F, Kapsak CJ, Smith EA, et al. Accelerating bioinformatics implementation in public health. Microb Genomics. 2023 Jul 10;9(7).

10. Schwengers O, Hoek A, Fritzenwanker M, Falgenhauer L, Hain T, Chakraborty T, et al. ASA3P: An automatic and scalable pipeline for the assembly, annotation and higher-level analysis of closely related bacterial isolates. Pertea M, editor. PLOS Comput Biol. 2020 Mar 5;16(3):e1007134.

11. Ortega-Sanz I, Barbero-Aparicio JA, Canepa-Oneto A, Rovira J, Melero B. CamPype: an open-source workflow for automated bacterial whole-genome sequencing analysis focused on Campylobacter. BMC Bioinformatics. 2023 Jul 20;24(1).

12. Seemann T. nullarbor [Internet]. [cited 2024 Sep 17]. Available from: https://github.com/tseemann/nullarbor

13. Petit RA, Read TD. Bactopia: a Flexible Pipeline for Complete Analysis of Bacterial
Genomes. Segata N, editor. mSystems. 2020 Aug 25;5(4).

14. Jalili V, Afgan E, Gu Q, Clements D, Blankenberg D, Goecks J, et al. The Galaxy
platform for accessible, reproducible and collaborative biomedical analyses: 2020
update. Nucleic Acids Res. 2020 Jul 2;48(W1):W395–402.

15. Carriço JA, Rossi M, Moran-Gilad J, Van Domselaar G, Ramirez M. A primer on
microbial bioinformatics for nonbioinformaticians. Clin Microbiol Infect. 2018
Apr;24(4):342–9.

16. Roberts LW, Forde BM, Hurst T, Ling W, Nimmo GR, Bergh H, et al. Genomic
surveillance, characterization and intervention of a polymicrobial multidrug-resistant
outbreak in critical care. Microb Genomics. 2021 Mar 1;7(3).

17. Stacey D, Wulff K, Chikhalla N, Bernardo T. From FAIR to FAIRS: Data security by
design for the global burden of animal diseases. Agron J. 2022 Sep;114(5):2693–9.

18. U.S. Department of Health & Human Services, Rights (OCR) O for C. The HIPAA
Privacy Rule [Internet]. 2008 [cited 2024 Sep 17]. Available from:
https://www.hhs.gov/hipaa/for-professionals/privacy/index.html

19. Afolayan AO, Bernal JF, Gayeta JM, Masim ML, Shamanna V, Abrudan M, et al.
Overcoming Data Bottlenecks in Genomic Pathogen Surveillance. Clin Infect Dis. 2021
Dec 1;73(Supplement_4):S267–74.

20. Andrews S. FastQC: a quality control tool for high throughput sequence data.
Cambridge, United Kingdom; 2010.

21. Chen S, Zhou Y, Chen Y, Gu J. fastp: an ultra-fast all-in-one FASTQ preprocessor.
Bioinformatics. 2018 Sep 1;34(17):i884–90.

22. Seemann T. Shovill [Internet]. 2024 [cited 2024 Sep 17]. Available from:
https://github.com/tseemann/shovill

23. Craddock HA, Motro Y, Zilberman B, Khalfin B, Bardenstein S, Moran-Gilad J. Long-
Read Sequencing and Hybrid Assembly for Genomic Analysis of Clinical Brucella
melitensis Isolates. Microorganisms. 2022 Mar 14;10(3):619.

24. Seemann T. any2fasta [Internet]. 2024 [cited 2024 Sep 17]. Available from:
https://github.com/tseemann/any2fasta

25. Gurevich A, Saveliev V, Vyahhi N, Tesler G. QUAST: quality assessment tool for
genome assemblies. Bioinformatics. 2013 Apr 15;29(8):1072–5.

26. Underwood A. BactInspector [Internet]. 2020 [cited 2024 Sep 17]. Available from:
https://gitlab.com/antunderwood/bactinspector

27. Schoch CL, Ciufo S, Domrachev M, Hotton CL, Kannan S, Khovanskaya R, et al. NCBI
Taxonomy: a comprehensive update on curation, resources and tools. Database

[Internet]. 2020 Jan 1 [cited 2024 Sep 17];2020. Available from:
https://academic.oup.com/database/article/doi/10.1093/database/baaa062/5881509

28. Seemann T. mlst [Internet]. 2024 [cited 2024 Sep 17]. Available from:
https://github.com/tseemann/mlst

29. Feldgarden M, Brover V, Gonzalez-Escalona N, Frye JG, Haendiges J, Haft DH, et al.
AMRFinderPlus and the Reference Gene Catalog facilitate examination of the genomic
links among antimicrobial resistance, stress response, and virulence. Sci Rep. 2021 Jun
16;11(1).

30. Robertson J, Nash JHE. MOB-suite: software tools for clustering, reconstruction and
typing of plasmids from draft assemblies. Microb Genomics. 2018 Aug 1;4(8).

31. Jain A, Singhal N, Kumar M. AFRbase: a database of protein mutations responsible for
antifungal resistance. Martelli PL, editor. Bioinformatics. 2023 Nov 1;39(11).

32. Seemann T. Snippy [Internet]. 2024 [cited 2024 Sep 17]. Available from:
https://github.com/tseemann/snippy

33. Harris SR. SKA: Split Kmer Analysis Toolkit for Bacterial Genomic Epidemiology
[Internet]. Cold Spring Harbor Laboratory; 2018 [cited 2024 Sep 17]. Available from:
http://biorxiv.org/lookup/doi/10.1101/453142

34. Page AJ, Taylor B, Delaney AJ, Soares J, Seemann T, Keane A, et al. SNP-sites: rapid
efficient extraction of SNPs from multi- FASTA alignments. Microb Genomics.

35. Seemann T. snp-dists [Internet]. 2024 [cited 2024 Sep 17]. Available from:
https://github.com/tseemann/snp-dists

36. Minh BQ, Schmidt HA, Chernomor O, Schrempf D, Woodhams MD, Von Haeseler A, et
al. IQ-TREE 2: New Models and Efficient Methods for Phylogenetic Inference in the
Genomic Era. Teeling E, editor. Mol Biol Evol. 2020 May 1;37(5):1530–4.

37. Sagulenko P, Puller V, Neher RA. TreeTime: Maximum-likelihood phylodynamic
analysis. Virus Evol. 2018 Jan 1;4(1).

38. Hadfield J, Megill C, Bell SM, Huddleston J, Potter B, Callender C, et al. Nextstrain: real-
time tracking of pathogen evolution. Kelso J, editor. Bioinformatics. 2018 Dec
1;34(23):4121–3.

39. Smith MR. Robust Analysis of Phylogenetic Tree Space. Hoehna S, editor. Syst Biol.
2022 Aug 10;71(5):1255–70.

40. Manara S, Pasolli E, Dolce D, Ravenni N, Campana S, Armanini F, et al. Whole-genome
epidemiology, characterisation, and phylogenetic reconstruction of Staphylococcus
aureus strains in a paediatric hospital. Genome Med [Internet]. 2018 Dec [cited 2024
Sep 17];10(1). Available from:
https://genomemedicine.biomedcentral.com/articles/10.1186/s13073-018-0593-7

41. Eisenberger D, Tuschak C, Werner M, Bogdan C, Bollinger T, Hossain H, et al. Whole-
genome analysis of vancomycin-resistant Enterococcus faecium causing nosocomial
outbreaks suggests the occurrence of few endemic clonal lineages in Bavaria, Germany.
J Antimicrob Chemother. 2020 Jun 1;75(6):1398–404.

42. Timme RE, Rand H, Shumway M, Trees EK, Simmons M, Agarwala R, et al. Benchmark
datasets for phylogenomic pipeline validation, applications for foodborne pathogen
surveillance. PeerJ. 2017 Oct 6;5:e3893.

43. Lockhart SR, Etienne KA, Vallabhaneni S, Farooqi J, Chowdhary A, Govender NP, et al.
Simultaneous Emergence of Multidrug-Resistant*Candida auris*on 3 Continents
Confirmed by Whole-Genome Sequencing and Epidemiological Analyses. Clin Infect
Dis. 2017 Jan 15;64(2):134–40.

45. Huson DH, Scornavacca C. Dendroscope 3: An Interactive Tool for Rooted Phylogenetic
Trees and Networks. Syst Biol. 2012 Dec 1;61(6):1061–7.

46. Smith MR. Information theoretic generalized Robinson–Foulds metrics for comparing
phylogenetic trees. 2020;36(20):5007–13.

47. Harris PNA, Ben Zakour NL, Roberts LW, Wailan AM, Zowawi HM, Tambyah PA, et al.
Whole genome analysis of cephalosporin-resistant Escherichia coli from bloodstream
infections in Australia, New Zealand and Singapore: high prevalence of CMY-2
producers and ST131 carrying blaCTX-M-15 and blaCTX-M-27. J Antimicrob
Chemother. 2018 Mar 1;73(3):634–42.

solu-publication-2

Samples ⌄
- All samples
- E. faecium — 99
- S. enterica — 23
- S. aureus — 135

Clusters >

☐	ERR3569619	Enterococcus faecium	80 ⌄	15 VRE	⌄	8	⌄	Not computed	KV	2 months ago
☐	ERR3569664	Enterococcus faecium	117 ⌄	33 VRE	⌄	11	⌄	Not computed	KV	2 months ago
☐	ERR3569663	Enterococcus faecium	117 ⌄	35 VRE	⌄	10	⌄	Not computed	KV	2 months ago
☐	ERR3569662	Enterococcus faecium	- ⌄	43 VRE	⌄	11	⌄	Not computed	KV	2 months ago
☐	ERR3569661	Enterococcus faecium	80 ⌄	15 VRE	⌄	10	⌄	Not computed	KV	2 months ago
☐	ERR3569660	Enterococcus faecium	117 ⌄	14 VRE	⌄	8	⌄	Not computed	KV	2 months ago
☐	ERR3569659	Enterococcus faecium	80 ⌄	15 VRE	⌄	9	⌄	Not computed	KV	2 months ago
☐	ERR3569658	Enterococcus faecium	80 ⌄	15 VRE	⌄	8	⌄	Not computed	KV	2 months ago
☐	ERR3569657	Enterococcus faecium	117 ⌄	35 VRE	⌄	9	⌄	Not computed	KV	2 months ago
☐	ERR3569656	Enterococcus faecium	117 ⌄	19 VRE	⌄	10	⌄	Not computed	KV	2 months ago
☐	ERR3569655	Enterococcus faecium	80 ⌄	35 VRE	⌄	11	⌄	Not computed	KV	2 months ago
☐	ERR3569653	Enterococcus faecium	78 ⌄	16 VRE	⌄	9	⌄	Not computed	KV	2 months ago
☐	ERR3569652	Enterococcus faecium	117 ⌄	19 VRE	⌄	10	⌄	Not computed	KV	2 months ago
☐	ERR3569651	Enterococcus faecium	117 ⌄	35 VRE	⌄	10	⌄	Not computed	KV	2 months ago

Help & feedback

Sign up for your own Solu workspace!

SNP cluster (reference)
- I
- II
- III
- IV
- V

ST (reference)
- ST-
- ST117
- ST552
- ST612
- ST78
- ST80

CT (reference)
- CT1065
- CT1791
- CT2051
- CT2052
- CT2318
- CT2478
- CT2479b
- CT2510
- CT2511
- CT2543
- CT469
- CT894 like