Contextual Expectations in the Real-World Modulate Low-Frequency Neural Oscillations

Victoria I. Nicholls[1,2*], Alexandra Krugliak[1], Benjamin Alsbury-Nealy[3,4], Klaus Gramann[5], Alex Clarke[1]

1. Department of Psychology, University of Cambridge, Cambridge, CB2 3EB, UK

2. Department of Psychology and Sports Sciences, Goethe University Frankfurt, Frankfurt am Main, 60323, Germany

3. Silicolabs, Toronto, Canada

4. Department of Psychology, University of Toronto, Toronto, M5S 1A1, Canada

5. Department of Biological Psychology and Neuroergonomics, Technische Universität Berlin, Berlin, 10623, Germany

*Corresponding author, email: nicholls@psych.uni-frankfurt.de

1   **Abstract**

Objects in expected locations are recognised faster and more accurately than objects

in incongruent environments. This congruency effect has a neural component, with

increased activity for objects in incongruent environments. Studies have increasingly

shown differences between neural processes in realistic environments and tasks, and

neural processes in the laboratory. Here, we aimed to push the boundaries of

traditional cognitive neuroscience by tracking the congruency effect for objects in real

world environments, outside of the lab. We investigated how object recognition is

modulated when objects are placed in real environments using augmented reality

while recording mobile EEG. Participants approached, viewed, and rated how

congruent they found the objects with the environment. We found significantly higher

theta-band power for objects in incongruent contexts than objects in congruent

contexts. This demonstrates that real-world contexts impact on how we recognize

objects, and that mobile brain imaging and augmented reality are effective tools to

study cognition in the wild.

16   **Introduction**

Every day we explore our environment, look at, and recognise objects. Being able to

recognise objects quickly is important, for example, when crossing a road it is

important to recognise if a vehicle is approaching to prevent a collision. Specific

objects are generally experienced in certain locations and environments, knowledge

about which we learn through experience in the form of schemas. This knowledge can

aid recognition, such that objects which appear in expected (or congruent)

environments are typically recognised faster and more accurately than objects which

appear in unexpected (or incongruent) environments (1, 2, 3, 4, 5, 6, 7). This

congruency effect also has a neural component, with studies showing a larger neural

response for incongruent objects between around 250 and 500ms after the object

appears, present in ERPs (e.g. the N400) and in theta oscillations (8, 9, 10, 11, 12, 13,

14). These findings have been linked to the integration of new semantic information

into memory when the item was more unexpected (11, 12, 14, 15, 16, 17). However,

the majority of studies investigating the congruency effect have been conducted in

well-controlled laboratory environments, where objects and scenes are presented

together on a computer monitor before being replaced by an unrelated object and

scene, breaking the temporal and spatial coherence that structure real-life experiences.

Moreover, the participant is typically separated from the environment the objects are

in, instead experiencing the 'environment' while being in a testing cubicle. This is

different from how the real world is experienced, where there is a clear spatiotemporal

coherence in the environment. As a consequence, we have little information about

whether the tasks participants perform in laboratory settings are a good approximation

of behaviours and associated neural processes in the real world. Indeed, recent

findings have increasingly shown differences between neural processes in realistic

environments and tasks, and neural processes in the laboratory (18, 19, 20, 21, 22,

23). This raises the question to what extent do research findings translate to real

environments, and stress the importance of pursuing neurocognitive issues within

their true dynamic functional context.

There is increasing acknowledgment that neuroscience must seek out more

naturalistic ways to study cognition (24, 25, 26, 27, 28), however significant

challenges remain for taking our experimental techniques out of the lab. With the

developments in mobile electroencephalography (mEEG) technology over the last ten

to fifteen years, such as the development of the MoBI framework (29) and improved

signal processing tools (30), mEEG has become a reliable method which provides the

opportunity to perform neuroimaging in the real world (25, 29, 31, 32, 33, 34).

However, in experiments, we typically want to control or manipulate the stimuli we

study, which poses technical barriers when experiments are situated in the real world.

The development of mixed reality methods, such as head-mounted augmented reality

(AR), allows researchers to control when and where stimuli are presented to

participants while they freely move around the real world. While AR has been utilized

to study assembly systems (35), pedagogy (36) and treatment of psychological

disorders (37), a relatively novel approach is to use mobile EEG and head-mounted

AR together, to study the neural processes underpinning cognition in real settings

(38).

Here we study how object recognition processes are modulated by the relationship

between the object and the environment, by presenting virtual objects in real locations

using AR, while neural activity is recorded with mobile EEG. Participants walked

around a large indoor and outdoor area seeing virtual objects that were either more or

less congruent with their settings. Concurrent EEG then allows us to ask how the

processing of objects is modulated by the congruency between the objects and the

environment, thereby allowing us to test if our knowledge about the world modulates

the processing of visual objects.

Results

The initial challenges were first to create a mixed reality experiment where objects

were embedded into the real environment, set to appear at specific locations when the

participant was in proximity to an augmented marker, and second to have sufficient

synchronisation between the AR and EEG systems for millisecond precision in the

analyses regarding the onset of augmented objects. We used a large indoor and

outdoor space near the Department of Psychology at the University of Cambridge as

our testing arena, with the 80 virtual objects being assigned a physical location (Fig.

1C). The objects and locations were chosen such that approximately 40 objects would

be more congruent and 40 less congruent with the environment. The study followed

the procedures described in our previous protocol article (39).

Fig. 1. ***Experimental paradigm, example setup, and object locations.*** *(Ai). Example of the blue virtual arrow indicators participants searched for, these indicated the object locations. (Aii) Example green arrow which would appear when participants moved close enough to the blue arrows. (Aiii) Example stimulus object which appeared for 5s after participants pressed the button on the button box once the arrows had turned green. (Aiv) Example congruency rating question participants were presented with once the stimulus object disappeared. For panel (A) the top row shows an example congruent trial, and the bottom row an example incongruent trial. (B) Example setup on one of the authors who consented to having their picture taken and shared. Author is wearing the Brain Products EEG system, with a shower cap, and then the Hololens 2 placed on top of the shower cap and EEG system. The author is holding the button box that was connected to the Hololens 2 and the LiveAmp. An example virtual object (Brachiosaurus) is presented to the author, the Brachiosaurus was not one of the objects presented to the participants. (C). A birds-eye view of the experiment environment taken from Google Earth v.10.55.01 (May 15th 2024), Cambridge, UK, and edited. The yellow dashed line indicates the full area that objects were placed in. The heatmap indicates locations a participant gazed at the*

Once the participants were fitted with the mobile EEG system, the AR device was placed over the top of the electrodes. We used an initial calibration to align the real and virtual worlds, after which the experiment began (Fig. 1.B). On each trial, a virtual blue arrow appeared at the location of the object (Fig.1.Ai). To facilitate finding the object, the arrow could be seen through walls and surfaces. Once the participant was near the arrow, it turned green (Fig.1.Aii), signalling the participant could press a button after which the arrow would change into an object (Fig.1.Aiii). The object was presented for 5s, after which, a virtual display appeared to collect an expectancy rating on a 5-point scale, which is used to accommodate individual differences in how congruent each item was with its setting (Fig. 1.Aiv). The experiment had four blocks, two indoors and two outdoors, each containing 20 objects to find. The order of the blocks was counter-balanced between participants.

Following EEG data preprocessing pipelines developed for mobile EEG (30), we extracted EEG signals around the onset of the virtual objects. As a first step towards characterising the object recognition process in real world contexts, we examined the averaged EEG signals from the onset of the objects. Presenting participants with AR stimuli produced a clear visual evoked response over posterior electrodes, including a P100 followed by an N170, and P300 component (Fig. 2a), with ERPs declining after approximately 500ms. These peaks and characteristics were also present in the global field power of the EEG signals (Fig. 2b). A grand average time-frequency representation was also calculated (Fig. 2c), which showed a post-stimulus increase in low frequency power (lower-alpha/high-theta) between 100 and 400ms, followed by a decrease in power between 500 and 1000ms. There was a further increase in delta/theta power between 500ms and 1000ms, along with decreased gamma power

130   throughout the post-stimulus period. These signals are in line with lab-based studies

131   when presenting visual stimuli, suggesting that mobile EEG in combination with AR

132   is a feasible approach to examining cognitive processes in real environments.

Fig. 2. Example of mEEG data quality *(A) Butterfly plot averaged across all participants and trials. Each line corresponds to an EEG channel. Above this are topographical plots showing the average amplitude at timepoints of: 100, 170, 350, 500, 700, and 900ms. (B) Global field power plot taken from the data used in A. The central line is the mean GFP and the lines above and below indicate the standard error. (C) Time-frequency representation of the EEG data from -100 to 1000ms and frequencies 2-101Hz. The frequencies are logarithmically scaled. The data was smoothed using a Gaussian kernel (3Hz, 40ms) across times and frequencies, and plotted using a filled 2D contour plot.*

We next sought to determine if EEG activity was modulated based on the congruency

between the objects and the environment. Previous lab-based EEG studies have

typically shown a congruency effect in the N300 and N400 time range (250 to 500

ms) across central electrodes, with a larger negativity for objects that are incongruent

with the environment than for objects that are congruent with the environment. We

attempted to replicate this finding in our data using the same data analysis approach as

that in (10). We computed the mean EEG amplitude in two response windows:

between 250 and 350ms (N300), and between 350 and 500ms (N400), across the

central electrodes FC1, CP1, CP2, Cz, FC2, C1, CPz, and C2. As we had five levels of

congruency ratings we averaged 1 and 2 into one incongruent level, and 4 and 5 into

one congruent level. We computed t-tests in the N300 and N400 time-windows

between the congruent and incongruent levels. We found no significant congruency

effect (Fig. 3; N300: $t(33)=0.63$, SE=0.15, p=0.536, Cohen's d=0.096; N400:

$t(33)=0.20$, SE=0.13, p=0.841, Cohen's d=0.024).

We next performed a more exploratory analysis to test for congruency effects across

all electrodes and time points, whilst also utilising the full range of the 5-point

congruency scores provided for each trial. A linear regression was performed at each

electrode and time point to determine how EEG signals varied with congruency

ratings alongside a cluster-based permutation test. Like for our more restrictive

analysis, we found no evidence for a modulation of ERPs by the congruency between

objects and the real-world setting.

Given the more fluid dynamics of real-world experiences, and that the context was

ever present, it may be that analyses less dependent on strict time-locking across trials

might be more sensitive. As such, we explored whether the congruency between the

object and the environment modulated different neural oscillations (Fig. 4). EEG

power for each frequency and time-point was calculated for each trial, and averaged

within each of the 5 congruency ratings. We then ran a cluster-based permutation

linear regression analysis across all electrodes, timepoints, and frequencies. This

revealed a significant cluster showing a positive relationship between incongruency

(congruency rating 1) and power between approximately 100 and 600ms post-

stimulus onset, centred in the theta range (Fig. 4a; 4-7Hz; cluster $p = 0.014$). The

cluster was primarily located over posterior electrodes, both centrally and on the right.

This positive relationship indicates that there was significantly more power in the

theta range between 100-600ms for objects that were more incongruent with the

environment compared to those that were more congruent. This shows that when

more unexpected events occur, low-frequency neural responses increase over sensory

and parietal electrodes in proportion to how unexpected the item was (Fig. 4a-d).

Fig. 4. Figures demonstrating the time-frequency analyses. (a) T-values calculated across time and frequencies of the EEG data. The black line indicates the significant cluster for electrode O2. (b) The z-scored theta power (4-7Hz) averaged across each of the five congruency ratings for each participant. The black line is a first-degree polynomial fitted to the z-scored theta power. The colours indicate an increase in congruency (light to dark blue), an increase in incongruency (red to dark red), or neither (light purple). (c) The mean difference topography showing the difference in theta power between trials where objects were rated as highly incongruent (1) and highly congruent (5), between 200 and 500ms, averaged across participants. (d) Topographies for the mean theta power (5-7Hz) between 200 and 500ms at each congruency rating sorted so that objects rated as highly congruent (5) are on the left to objects rated as highly incongruent (1) are on the right.

Discussion

Here we set out to determine whether object recognition is impacted by context, when the context is a real spatiotemporally coherent environment, the real world. Using mEEG and AR we examined whether neural object recognition processes that are impacted by scene context are also impacted by real-world outdoor and indoor contexts. We found that context modulated theta-band power, with significantly

higher theta-band power for objects in incongruent contexts than objects in congruent contexts. This demonstrates that real-world contexts impact on how we recognise objects, and that mobile brain imaging and AR are effective tools to study cognition in the wild.

Our main finding concerned context effects in the theta band across posterior electrodes between 100 and 600ms, where theta-band power was higher for objects that were incongruent with the environment than for objects that were congruent with the environment. This is in line with previous research that has shown an increase in theta power when targets are incongruent, for example critical words not matching the preceding sentence (11, 12, 13, 14), which has been suggested to reflect memory processes relating to the integration of semantic information into the currently held representations of the semantic context (11, 12, 14, 15, 16, 17). Our results expand on these findings by showing that even in real spatiotemporally consistent environments, expectations about which objects appear in the environment influences how objects are recognised. These results give promising support to findings from laboratory studies applying to real world scenarios even though the laboratory studies are highly reduced compared to the real world.

Theta oscillations have also been linked to the ongoing semantic processing of objects and words in the ventral visual pathway, at a similar time range to our modulations of theta activity (40, 41, 42). This might suggest that the knowledge we have about the environment we are in, modulates how we access semantic information, which is primarily reflected through theta oscillations. This is also consistent with recent EEG work showing that semantic representations for objects that are incongruent with the scene are associated with enhanced and extended sematic processing compared to more congruent objects (43). This points towards a system whereby the semantic

processing of objects that are incongruent with the environment show enhanced theta activity as a consequence of the object recognition process not benefiting from the schema-based predictions generated by the immersion in a particular environment. While our EEG analyses do not allow us to make claims about the neural regions involved, it is noteworthy that previous studies suggest that the precuneus might integrate object sensory information with expectations generated prior to the presentation of an object (3, 44), which would correspond with the location of our theta effects over occipital and parietal electrodes. The intriguing question of how activity in this posterior medial system interacts with the ventral visual pathway could be explored in future studies using more spatially specific methods such as MEG or fMRI.

In addition to our oscillatory analysis, we also examined ERPs. Previous ERP research examining the impact context has on the neural processes involved in object recognition has found an impact on the N300 and N400 components (8, 9, 10), with a greater amplitude being shown for objects that are incongruent with the environment than objects that are congruent with the environment. This amplitude increase has been associated with an increase in semantic processing. As a first step we attempted to replicate this effect using the same electrodes as (10), but found no evidence of a modulation. As our reference electrode was placed at FCz, while theirs was placed at the mastoids, any potential N400 effects in our study may be pushed to different electrodes than that seen by (10). Therefore, we performed a cluster-based permutation test across all electrodes and timepoints to determine whether a congruency effect existed in the ERPs. We found no impact of congruency on the amplitude across any electrodes or timepoints. It is unclear why we did not replicate the well-established N400 congruency effect, although a combination of three

possibilities might go some way to explaining this. First, we cautiously suggest there

could be differences between the neural processes behind the congruency effect when

participants are placed in a real environment compared to a laboratory environment,

as has been shown for other neural effects recently (18, 19, 20, 21, 22, 23). For

example, in laboratory experiments objects are often presented as pictures within a

scene that appears for a short period of time before being replaced with another

picture, removing the spatial and temporal coherence that exists when moving from

one environment to the next in a real-world setting. Removing this spatial and

temporal coherence may artificially increase the N400 effect. Indeed, previous studies

have shown that an N400 is generated when an unexpected ending of an action

occurs, such as an incorrect dance step (45, 46) or when spatial coherence is

disrupted, such as a plane in a parking lot rather than the sky of the same scene (47).

Therefore, the combined disruption of semantic, temporal, and spatial coherence of

the scene context in controlled lab-based contexts may artificially inflate the N400

compared to real-world environments where the temporal and spatial coherence of the

context is preserved.

A second possibility is that real world cognitive effects might be less time-locked

across events compared to lab-based tasks – for instance, in the lab there is a

relatively short, largely fixed, time between a scene and object appearing, meaning

that the dynamics of expectations influencing object processing are relatively

predictable, which might lead to more stable congruency effects in time over trials. In

our experiment, whilst our objects have discrete onsets that we align our analysis to,

the context is ever present and relatively stable over time. This might add variability

to when expectations impact object processing, and reduce the ability of time-locked

ERPs to reveal congruency effects. A third possibility is that ERP effects are partly

produced by very low frequency signals, which are more problematic for mobile

EEG. Our ERP analysis filtered out signals below 1 Hz due to artefacts caused by

movement. The removal of these very low frequency signals is known to distort ERP

morphologies (48, 49), which may in turn reduce our ability to see clear N300 or

N400 effects. However, our paradigm and analyses clearly suggest that modulations

of theta activity (4-7 Hz) are present, and that time-frequency analyses, with less

reliance on time-locked activity (50), are a fruitful analytic approach for mobile EEG.

Recently there has been increasing interest in examining human neural processes

where participants perform tasks in more naturalistic contexts, such as VR or even the

real world, whilst performing increasingly natural behaviours (25, 29, 31, 51, 52, 53,

54). We make a significant expansion to these studies by demonstrating the use of AR

in combination with mEEG to investigate fundamental neural processes such as those

underpinning object recognition. This novel combination opens the door to a whole

new direction for neuroscience research, where not only can one conduct highly

controlled studies in the laboratory or in highly realistic VR, but also studies in real-

world locations beyond the lab. This allows for the exploration of neuroscience while

participants perform natural behaviours within real environments, giving us a way to

understand our neural processes involved in going about our day to day lives.

Moreover, AR allows to explore what can help us improve our environments and the

efficiency of our neural processing. For example, one could examine whether we can

improve our memory when viewing augmented information compared to information

presented in a text or static display (e.g. 55, 56). Mobile EEG and AR also allows us

to explore these questions in diverse arenas, such as museums and galleries, where

standard text displays and exhibits could be augmented with animations to enhance

memory and visitor engagement.

One limitation of our paradigm, is that the objects were not permanently embedded into the environment, but rather appeared on a button press. We chose this as a first step towards testing object recognition in the real world with mobile EEG and AR, as it allowed us to have control over the objects and clear time periods to analyse. However, it enforces an artificial temporal constraint which would not normally be present in the real world when examining objects. As these methods and analytical approaches develop, it will become important to be able to track object recognition in a more ecologically valid way if we are to study natural cognitive processes. This may be facilitated through continued development of the integration of head-mounted AR devices, eye tracking, body sensors and mobile brain imaging, where the visual and semantic processing of our visual world can be modelled continuously depending on what we fixate upon and choose to interact with.

Conclusion

This study provides some of the first insights into how interactions between objects and real environments modulate object recognition. Previously, research has described in detail how object congruency modulates object recognition processes in well controlled laboratory environments. However, what has been missing is information on how this process occurs when participants are present in the same environment as the stimulus objects, the environment is relatively stable and long lasting, and while participants perform naturalistic behaviours. We find that even real environments impact on how we recognise objects. These results are a positive for laboratory studies as it would seem even with low ecological validity, some findings appear universal, or to be similar in highly ecologically valid conditions. Moreover, we

342   suggest mobile brain imaging and AR are excellent tools to study real world

343   cognition.

Materials and Methods

345   The methods follow the protocol described in (39), with the details pertinent to this

346   study reported below. The RSA analyses of the EEG data and analyses of the eye

347   tracking data will be reported separately. In addition to the ERP analyses described in

348   (39), we have conducted additional exploratory analyses of the time-frequency data

349   described in the EEG Analyses subsection.

Participants

To determine the number of participants required, a power analysis was conducted on

data from (10) who examined EEG congruency effects of object-scene processing.

The power analysis was conducted using the 'sampsizepwr()' function in MATLAB

(57), based on the mean difference between the amplitude of the N400 for congruent

and incongruent conditions, to obtain a power of 0.8, at an alpha of 0.05. The analysis

showed that a minimum sample size of 34 participants was required.

Overall forty-two participants took part in the experiment (13 female, aged 18-35

years). Eight participants had exceptionally noisy data and were excluded from the

analysis, leaving a total of 34 participants for the final analyses in line with the

outcome of the power analysis. All participants had normal or corrected to normal

vision and reported no history of neurological conditions. Ethical approval for the

study was granted by the ethics committee of the Department of Psychology at the

University of Cambridge. Participants signed informed consent prior to the start of the

experiment. This study was performed in accordance with all appropriate institutional

guidelines and international guidelines and regulations, in line with the principles of

the Helsinki Declaration.

Apparatus

Participants were presented with virtual stimuli using a Hololens 2 device

(https://www.microsoft.com/en-us/hololens/). The Hololens 2 is a mixed reality

headset with a horizontal field of view of 42°, a vertical field of view of 29°, and

presents images at 60Hz. EEG was recorded using the Brainvision LiveAmp 64

mobile system (Brain Products GmbH, Gilching, Germany), with an online low pass

filter of 131Hz. In all sessions we recorded 64-channel EEG through ActiCap Slim

active Ag/AgCl electrodes located in an elastic cap (actiCAP snap) positioned

according to the international 10/20 system (58), with a reference electrode placed at

FCz, ground electrode placed at Fpz and a sampling rate of 500Hz. The EEG

electrodes were placed on the participant with the Hololens 2 placed on top of the

electrodes, and the LiveAmp and electrode cables placed in a backpack that the

participant wore while performing the experiment. A custom-built button box was

plugged into the Hololens 2 USB-C port and the LiveAmp 1-bit trigger port, meaning

that when the button was pressed, it simultaneously sent a signal to Hololens 2 and a

5V signal to the LiveAmp. The LiveAmp then converted that signal to a trigger that

was marked in the EEG recording. The signal to the Hololens 2 triggered the

appearance of an object during the experiment. An example of the setup can be seen

in Fig. 1.B.

Hololens takes a scan of the environment

The scan is then imported into Unity and Experimenter

The stimuli are also imported and placed in locations using the scan as a map

The experiment application is run on the Hololens presenting objects in the intended locations in the real world

Fig. 5. A description of how the experiment was created. *First the Hololens 2 is used to take a scan of the real world. This is done by walking around the real world and looking at as many parts of the world as possible. For example, to scan a door one would first look at the top left corner of the door then move their head down slowly to the bottom left corner. Then look slightly to the right and move your head slowly upwards. This would be repeated until you had looked at all parts of the door. As you*

are looking and scanning the environment, the Hololens constructs 3D models or maps of the real world, an example of our environment is shown in A. This 3D map can be downloaded from the device and then imported into Unity, shown in panel B, and used in the same way as a virtual environment. The stimuli were then placed in the intended locations. As the 3D map is an accurate map of the real world, the locations the objects are placed in within Unity correspond to their real world locations. Therefore, when exporting the virtual environment, with the stimuli objects, back to the Hololens 2, the device will present the objects in the intended locations in the real world (As in panel C).

Stimuli and environments

During the experiment, participants explored a large real-world environment, including an indoor space (consisting of three offices, a corridor, and a meeting room) and an outdoor space (consisting of a parking lot and a picnic area) where they were presented with virtual objects in various locations (Fig. 1.C). A total of 80 images corresponding to concepts from a property norming study (59) were presented to the participants, and five additional images used as practice trials.

The 80 images used in the main experiment were selected from the one thousand images in the property norms set. The one thousand images were narrowed down to 400 by the lead author, based on which objects could plausibly appear in the experimental locations. These objects were then rated as either congruent or incongruent with the indoor and outdoor environments. From this we extracted 40 objects that were the most expected in the environments, and 40 objects that were the most unexpected in the environments. For the unexpected objects we made sure that they were highly unexpected, but not impossible. For example, a reindeer in a parking lot in the UK is highly unexpected but not impossible. However, if an object would be highly unexpected and impossible, we would not use that object (for example a dinosaur in the picnic area). The congruency ratings for the 80 objects were then

| 422 | verified by a second experimenter. All objects were placed in plausible locations |
| 423 | within the environments (i.e. a bottle on a table, not floating in the air). |

| 424 | *Constructing the paradigm* |

425	To place the stimuli in the correct locations in the real world, a virtual 3D map of the
426	real-world testing area was created. This involved scanning the experimental
427	environment through the Hololens 2, which uses spatial mapping to create detailed
428	representations of real-world surfaces which are built into a map. This spatial map
429	was then downloaded from the device, and imported into Unity for use as a virtual
430	environment to place the objects within. The locations used in the virtual environment
431	would correspond to the matching locations in the real world (an example is shown in
432	Fig. 5). The experiment was coded using SilicoStudio (beta testing version, formerly
433	Experimenter, https://www.silicolabs.ca/), an experimental design software package
434	built for the Unity engine, and presented to participants with the Hololens 2.
435	SilicoStudio was used to place the objects in the correct real-world locations and to
436	enable interactions between the participant and the objects. The locations of the
437	stimuli were the same for all participants. A list of the stimuli used and their locations
438	in the experiment can be found in the Supplementary Materials (Supplementary Table
439	S1, Supplementary Figs. S1 and S2). The interactions included the changing of the
440	object indicator arrow colour when participants stepped close enough to the indicator.
441	The second interaction included changing the indicator into an object when the
442	participants pressed the button on the button box. Furthermore, SilicoStudio was used
443	to manage the order in which objects appeared, and to record behavioural data which
444	included head, and eye tracking, and behavioural responses.

| 445 | *Procedure* |

The 80 images were presented to participants in four blocks of 20. The images in each block were matched on the following predictors: congruency, category, domain, hit rate on a visual task, hit rate on a lexical task, false alarm rate for a lexical task, false alarm rate for a visual task, image energy, image size, proportion of non-white space in the image, hue of the image, saturation of the image, frequency in the COCA database, proportion of participants identifying the modal name of the object, and the number of non-taxonomic features. Except for congruency and environment, the predictors for each image were taken from (59). The matching was performed using the Match software (version 2.09.02, 57).

To familiarise the participants with the Hololens and the appearance of AR stimuli they performed five practice trials in an indoor environment. The trials follow the same procedure as for the experiment described below. During the experiment participants walked through an environment, with indoor and outdoor sub-environments. In each sub-environment, participants completed two blocks of 20 trials (40 total per sub-environment). In each trial participants needed to find an arrow indicating the location of the next object (Fig. 1.Ai). When participants were close enough to the arrow, the arrow changed colour (Fig. 1.Aii) indicating that the participants could press the button on their button box (Fig. 1.A). Once the button was pressed, an object appeared for five seconds (Fig. 1.Aiii). At the same time a trigger was sent to the 1-bit TTL input of the LiveAmp by the button press. Participants were instructed to look at the object for the entire time it was visible, and to keep as still as possible. After the object disappeared, participants were presented with a virtual screen, asking them how expected or congruent they found the object within the environment on a scale from one to five (Fig. 1.Aiv). One was unexpected (incongruent), three was neither, and five was expected (congruent). Participants

indicated their rating by pressing the appropriate button on the virtual screen. We

included participant ratings as participants may have different ideas or experiences of

which objects are congruent and incongruent in the environments. The next trial

began once they had responded. This process was repeated until all 80 objects were

found. During the whole session, the participants' EEG activity and eye movements

were recorded. The four blocks took approximately 60 minutes to complete.

EEG Pre-processing

Pre-processing was performed using the EEGLAB toolbox (61) with the BeMoBIL

pipeline (30), which allowed for the automated analyses of mobile brain imaging

signals. The single-subject data were truncated by removing parts of the EEG

recording that occurred before the start of the experiment, the inter-block intervals,

and after the end of the experiment. The data were then downsampled to 250Hz and

power line noise was cleaned using the Zapline toolbox (62). Noisy channels were

automatically identified using the EEGLAB clean_artifacts() function with the

maximum tolerated fraction of the recording duration during which the channel was

flagged as 'bad' was set to 0.5 and the minimum channel correlation was set to 0.75.

Otherwise the template configuration settings from the BeMoBIL pipeline were used

for the clean_artifacts() function. The identified bad channels were then interpolated

(mean interpolated = 3, SD = 3) and an average reference was applied to the data.

At this point, the dataset was duplicated so that IC weights could be computed on a

filtered version of the data and then applied to a non-filtered dataset. For ICA, the

duplicated data were highpass filtered using a zero-phase Hamming window FIR filter

with a cutoff frequency of 1.5 Hz (order 1650, transition width 0.5Hz). Independent

components (ICs) were then identified using an adaptive mixture component analysis

(AMICA; 63). The AMICA decomposition uses an automatic time domain cleaning

where samples are removed based on the log likelihood that the samples do not

correspond to the algorithm's estimate of model fit. Three standard deviations were

used as the removal criterion. The ICs identified by AMICA were copied into the

original unfiltered dataset, and classified as 'brain', 'eye', 'heart', 'channel noise',

'line noise', 'muscle', and 'other' using IClabel Lite (64). ICs that were labelled as

'eye', 'heart', 'channel noise', and 'line noise' were then excluded from the

reconstructed dataset (mean excluded = 8, SD = 3). Another version of the data

analysis results where ICs labelled as 'muscle' are shown in Supplementary Fig. 3 in

the Supplementary Materials. All effects reported in the Results remained when

'muscle' components were removed. However, as IClabel is trained on a very small

portion of mobile EEG data we are not confident that IClabel accurately labels

'muscle' ICs over 'brain' ICs (30), therefore, we went with the preprocessing pipeline

where we were confident no 'brain' ICs were removed.

The IC-cleaned data were then filtered with a one-pass zero-phase Blackman-

windowed sinc FIR filter with cutoff frequencies of 1 and 40Hz, and a transition

width of 0.1Hz for the ERP analyses, and cutoff frequencies of 1 and 100Hz for the

time-frequency analyses.

The data were then epoched between -2 and 3 seconds around the onset of the images.

Channel baseline means were removed between -100 and 0ms before the onset of the

stimulus. Noisy epochs were automatically removed using the

bemobil_reject_epochs() function, based on the mean of channel means (to detect

general large shifts), the mean of channel standard deviations (SDs; to detect large

fluctuations in many channels, e.g. large muscle activity), the SD of channel means

(to detect phases where single channels had large fluctuations), and the SD of channel

SDs (to detect large fluctuations in single channels). We used an automatic kneepoint

with an offset of 5% to determine a threshold for epoch rejection. On average, 8 trials

were rejected per participant (SD=4).

EEG Analyses

We analysed event-related potentials (ERPs) and time-frequency representations

(TFRs) from channel data using cluster-based permutation tests from the FieldTrip

toolbox (65).

For the calculation of the ERPs, we first calculated the mean ERPs for objects rated as

congruent and incongruent. As participants gave congruency ratings between 1 and 5,

we averaged 1 and 2 into one incongruent ERP, and 4 and 5 into one congruent ERP.

The ERPs were calculated from 0 to 600ms post-image appearance. This was done for

every channel individually giving two mean ERPs per channel per participant. For the

ERP analysis we attempted to replicate the data analysis approach taken in (10). We

computed the mean EEG amplitude in two response windows: between 250 and

350ms (N300), and between 350 and 500ms (N400), across the central electrodes

FC1, CP1, CP2, Cz, FC2, C1, CPz, and C2. We computed t-tests in the N300 and

N400 time-windows between the congruent and incongruent levels.

For the TFR calculation, we followed a similar process as for the ERPs. The TFRs

were calculated for each trial, and averaged for each congruency rating the

participants gave, giving five TFRs per participant. The TFRs were calculated using 5

cycle Morlet wavelets for 40 logarithmically scaled frequencies from 1 to 100Hz, a

time window of interest of -2 to +3ms around the appearance of the image. The TFRs

were calculated for each channel individually giving five mean TFs per channel per

participant.

The cluster based permutation tests were then performed on the ERP and TFR data.

For each channel, time point, and frequency (TFR only), a linear regression was

performed determining the relationship between EEG amplitude and congruency

rating, producing t-values for each channel-time (and frequency) sample. All samples

with t-values below the 2.5th and 97.5th quantile were selected and clustered based on

temporal, spatial, and spectral adjacency. The t-values in each cluster are then

summed giving a cluster mass.

The significance of each cluster was determined by using the Monte Carlo method.

For this the trials for each of the congruency rating levels were placed in a single set.

Trials are randomly drawn out from this set that match the number of trials for each

congruency rating. The same regression analysis as above is then performed on this

randomised dataset. The random drawing and regression analysis on the randomised

dataset was repeated 5000 times and a histogram of the test statistic was constructed.

If the original cluster mass is below the 2.5th or above the 97.5th quantile of the

constructed histogram, then they were considered to be significant at an alpha level of

0.025.

References

References

1. Bar, M. Visual objects in context. *Nat. Rev. Neurosci.* **5**(8), 617-629 (2004)

2. Biederman, I., Mezzanotte, R. J., Rabinowitz, J. C. Scene perception: Detecting and
judging objects undergoing relational violations. *Cogn. Psychol.* **14**(2), 143-177
(1982)

3. Brandman, T. & Peelen, M. V. Interaction between scene and object processing
revealed by human fMRI and MEG decoding. *J. Neurosci.* **37**(32), 7700-771 (2017)

4. Cornelissen, T. H., & Võ, M.L.H. Stuck on semantics: Processing of irrelevant
object-scene inconsistencies modulates ongoing gaze behaviour. *Atten., Percept., &*
Psychophys. **79**, 154-168 (2017)

5. Davenport, J. L., & Potter, M. C. Scene consistency in object and background
perception. *Psychol. Sci.* **15**(8), 559-564 (2004)

6. Henderson, J. M., Weeks Jr, P. A., & Hollingworth, A. The effects of semantic
consistency on eye movements during complex scene viewing. *J. Exp. Psychol. Hum.*
Percept. Perform. **25**(1), 210 (1999)

7. Loftus, G. R. & Mackworth, N. H. Cognitive determinants of fixation location
during picture viewing. *J. Exp. Psychol. Hum. Percept. Perform.* **4**(4), 565 (1978)

8. Coco, M. I., Araujo, S. & Petersson, K. M. Disentangling stimulus plausibility and
contextual congruency: Electro-physiological evidence for differential cognitive
dynamics. *Neuropsychologia,* **96**, 150-163.0 (2017)

9. Coco, M. I., Nuthmann, A. & Dimigen, O. Fixation-related brain potentials during
semantic integration of object–scene information. *J. Cogn. Neurosci.* **32**(4), 571-589
(2020)

10. Draschkow, D., Heikel, E., Vo, M. L. H., Fiebach, C. J. & Sassenhagen, J. No

evidence from MVPA for different processes underlying the N300 and N400

incongruity effects in object-scene processing. *Neuropsychologia,* **120**, 9-17. (2018)

11. Bastiaansen, M. C., Van Der Linden, M., Ter Keurs, M., Dijkstra, T. & Hagoort, P.

Theta responses are involved in lexical—Semantic retrieval during language

processing. *J. Cogn. Neurosci.* **17**(3), 530-541 (2005)

12. Willems, R. M., Oostenveld, R. & Hagoort, P. Early decreases in alpha and

gamma band power distinguish linguistic from visual information during spoken

sentence comprehension. *Brain Res.* **1219**, 78-90 (2008)

13. Davidson, D. J. & Indefrey, P. An inverse relation between event-related and

time–frequency violation responses in sentence processing. *Brain Res.,* **1158***,* 81-92

(2007)

14. Klimesch, W. EEG alpha and theta oscillations reflect cognitive and memory

performance: a review and analysis. *Brain Res. Rev.* **29**(2-3), 169-195 (1999)

15. Riddle, J., Scimeca, J. M., Cellier, D., Dhanani, S. & D'Esposito, M. Causal

evidence for a role of theta and alpha oscillations in the control of working memory.

Curr. Biol. **30**(9), 1748-1754 (2020)

16. Metzner, P., von der Malsburg, T., Vasishth, S. & Rösler, F. Brain responses to

world knowledge violations: A comparison of stimulus-and fixation-triggered event-

related potentials and neural oscillations. *J. Cogn. Neurosci.* **27**(5), 1017-1028 (2015)

17. Hald, L. A., Bastiaansen, C. M. & Hagoort, P. EEG theta and gamma responses to

semantic violations in online sentence processing. *Brain Lang.* **96**(1), 90-105 (2006)

18. David, S. V., Vinje, W. E. & Gallant, J. L. Natural stimulus statistics alter the receptive field structure of v1 neurons. *J. Neurosci.* **24**(31), 6991-7006 (2004)

19. Aghajan, Z. M., *et al.* Impaired spatial selectivity and intact phase precession in two-dimensional virtual reality. *Nat. Neurosci.* **18**(1), 121-128 (2015)

20. Hölle, D., & Bleichner, M. G. Smartphone-based ear-EEG to study sound processing in everyday life. Preprint at https://doi.org/10.1101/2023.01.31.526197 2023-01 (2023).

21. Hampton, R. R., Hampstead, B. M. & Murray, E. A. Selective hippocampal damage in rhesus monkeys impairs spatial memory in an open-field test. *Hippocampus,* **14***(*7), 808-818 (2004)

22. Redcay, E. & Schilbach, L. Using second-person neuroscience to elucidate the mechanisms of social interaction. *Nat. Rev. Neurosci.* **20**(8), 495-505 (2019)

23. Maimon, G., Straw, A. D. & Dickinson, M. H. Active flight increases the gain of visual motion processing in Drosophila. *Nat. Neurosci.* **13**(3), 393-399 (2010)

24. Nastase, S. A., Goldstein, A. & Hasson, U. Keep it real: rethinking the primacy of experimental control in cognitive neuroscience. *NeuroImage,* **222**, 117254 (2020)

25. Gramann, K., Ferris, D. P., Gwin, J. & Makeig, S. Imaging natural cognition in action. *Int. J. Psychophysiol.* **91**(1), 22-29 (2014)

26. Grasso-Cladera, A., Bremer, M., Ladouce, S. & Parada, F. J. A Systematic Review of Mobile Brain/Body Imaging Studies Using the P300 Event-Related Potentials to Investigate Cognition Beyond the Laboratory. *Cogn. Affect. & Behav. Neurosci.* 1-29 (2024).

27. Shamay-Tsoory, S. G. A. Mendelsohn, Real-life neuroscience: an ecological

approach to brain and behavior research. *Perspect. Psychol. Sci.* **14**(5), 841-859

(2019)

28. Stangl, M., Maoz, S. L. & Suthana, N. Mobile cognition: imaging the human brain

in the 'real world'. *Nat. Rev. Neurosci.* **24**(6), 347-362 (2023)

29. Makeig, S., Gramann, K., Jung, T. P., Sejnowski, T. J. & Poizner, H. Linking

brain, mind and behavior. *Int. J. Psychophysiol.* **73**(2), 95-100 (2009)

30. Klug, M. *et al*. The BeMoBIL Pipeline for automated analyses of multimodal

mobile brain and body imaging data. Preprint at

https://doi.org/10.1101/2022.09.29.510051 (2022).

31. Niso, G., Romero, E., Moreau, J. T., Araujo, A. & Krol, L. R. Wireless EEG: A

survey of systems and studies. *NeuroImage,* **269**, 119774 (2023)

32. Griffiths, B., Mazaheri, A., Debener, S. & Hanslmayr, S. Brain Oscillations track

the formation of episodic memories in the real world. *NeuroImage*. **143**, 256-266

(2016)

33. Mustile, M., *et al*. Characterising neurocognitive impairments in Parkinson's

disease with mobile EEG when walking and stepping over obstacles. *Brain Commun.*

5(6), 326 (2023).

34. Ladouce, S., Donaldson, D. I., Dudchenko, P. A. & Ietswaart, M. Mobile EEG

identifies re-allocation of attention during real world activity. *Sci. Rep.* **9**(1), 15851

(2019)

35. Wang, X., Ong, S. K. & Nee, A. Y. A comprehensive survey of augmented reality

assembly research. *Adv. Manuf.* **4***,* 1-22 (2016)

36. Saidin, N. F., Halim, N. D. A. & Yahaya, N. A review of research on augmented

reality in education: Advantages and applications. *Int.l Educ. Stud.* **8**(13), 1-8 (2015)

37. Giglioli, I. A. C., Pallavicini, F., Pedroli, E., Serino, S. & Riva, G. Augmented

reality: A brand new challenge for the assessment and treatment of psychological

disorders. *Comput. Math. Methods Med.* **862942**, 1-13 (2015)

38. Krugliak, A. & Clarke, A. Towards real-world neuroscience using mobile EEG

and augmented reality. *Sci. Rep.* **12**(1), 2291 (2022)

39. Nicholls, V. I., Alsbury-Nealy, B., Krugliak, A. & Clarke, A. Context effects on

object recognition in real-world environments: A study protocol. *Wellcome Open Res.*

7 (2022)

40. Clarke, A., Devereux, B. J. & Tyler, L. K. Oscillatory dynamics of perceptual to

conceptual transformations in the ventral visual pathway. *J. Cogn. Neurosci.* **30**(11),

1590-1 (2018)

41. Clarke, A. Dynamic activity patterns in the anterior temporal lobe represents

object semantics. *Cogn. Neurosci.* **11**(3), 111-121 (2020)

42. Halgren, E., *et al.* Laminar profile of spontaneous and evoked theta: Rhythmic

modulation of cortical processing during word integration. *Neuropsychologia,* **76**,

108-124 (2015)

43. Krugliak, A., Draschkow, D., Võ, M. L. H. & Clarke, A. Semantic object

processing is modulated by prior scene context. *Lang. Cogn. Neurosci.* 1-10 (2023)

44. Clarke, A., Crivelli-Decker, J. & Ranganath, C. Contextual expectations shape

cortical reinstatement of sensory representations. *J. Neurosci.* **42**(30), 5956-5965

(2022)

45. Amoruso, L., *et al.* Time to tango: Expertise and contextual anticipation during action observation. *Neuroimage,* **98**, 366-385 (2014)

46. Wu, Y. C. & Coulson, S. Meaningful gestures: Electrophysiological indices of iconic gesture comprehension. *Psychophysiology,* **42**(6), 654-667 (2005)

47. Demiral, Ş. B., Malcolm, G. L. & Henderson, J. M. ERP correlates of spatially incongruent object identification during scene viewing: Contextual expectancy versus simultaneous processing. *Neuropsychologia,* **50**(7), 1271-1285 (2012)

48. Zhang, G., Garrett, D. R. & Luck, S. J. Optimal filters for ERP research II: Recommended settings for seven common ERP components. *Psychophysiology*, e14530 (2024)

49. Tanner, D., Morgan-Short, K. & Luck, S. J. How inappropriate high-pass filters can produce artifactual effects and incorrect conclusions in ERP studies of language and cognition. *Psychophysiology,* **52**(8), 997-1009 (2015)

50. Tallon-Baudry, C. & Bertrand, O. Oscillatory gamma activity in humans and its role in object representation. *Trends Cogn. Sci.,* **3**(4), 151-162 (1999)

51. Iggena, D., *et al*. Multisensory input modulates memory-guided spatial navigation in humans. *Commun. Biol.* **6**(1), 1167 (2023)

52. Gramann, K., Hohlefeld, F. U., Gehrke, L. & Klug, M. Human cortical dynamics during full-body heading changes. *Sci. Rep.* **11**(1), 18186 (2021)

53. Hilton, C., Kapaj, A. & Fabrikant, S. I. Fixation-related potentials during mobile map assisted navigation in the real world: The effect of landmark visualization style. *Atten., Percept., & Psychophys.* 1-16 (2024)

54. Delaux, A., *et al.* Mobile brain/body imaging of landmark-based navigation with

high-density EEG. *Eur. J. Neurosci.* **54**(12), 8256-8282 (2021)

55. Mahmoudi, T. M., Badie, K. & Valipour, M. Assessing the role of AR-based

content in improving learning performance considering Felder-Silverman learning

style. In 2015 International Conference on Interactive Collaborative Learning (ICL)

IEEE. 838-843 (2015)

56. Capuano, N., Gaeta, A., Guarino, G., Miranda, S. & Tomasiello, S. Enhancing

augmented reality with cognitive and knowledge perspectives: A case study in

museum exhibitions. *Behav. Inf. Tech.* **35**(11), 968-979 (2016)

57. MATLAB: version 9.11.0 (R2021b). Natick, Massachusetts: The MathWorks

Inc.2021.

58. Jasper, H. H. Ten-twenty electrode system of the international federation.

Electroencephalogr. Clin. Neurophysiol. **10**, 371-375 (1958)

59. Hovhannisyan, M., *et al*. The visual and semantic features that predict object

memory: Concept property norms for 1,000 object images. *Mem. Cognit.* **49**, 712-731

(2021)

60. van Casteren, M. & Davis, M. H. Match: A program to assist in matching the

conditions of factorial experiments. *Behav. Res. Methods.* **39**(4), 973-978 (2007)

61. Delorme, A. & Makeig, S. EEGLAB: an open source toolbox for analysis of

single-trial EEG dynamics including independent component analysis. *J. Neurosci.*

Methods. **134**(1), 9-21 (2004)

62. de Cheveigné, A. ZapLine: A simple and effective method to remove power line

artifacts. *NeuroImage,* **207**, 116356 (2020)

63. Palmer, J. A., Makeig, S., Kreutz-Delgado, K. & Rao, B. D. Newton method for the ICA mixture model.In: 2008 IEEE International Conference on Acoustics, Speech and Signal Processing. IEEE, 1805–1808 (2008)

64. Pion-Tonachini, L., Kreutz-Delgado, K. & Makeig, S. ICLabel: An automated electroencephalographic independent component classifier, dataset, and website. *NeuroImage,* **198**, 181-197 (2019)

65. Oostenveld, R., Fries, P., Maris, E. & Schoffelen, J. M. FieldTrip: open source software for advanced analysis of MEG, EEG, and invasive electrophysiological data. *Comput. Intell. Neurosci.* **2011**, 1-9 (2011)

Acknowledgements

Funding: This research was funded in whole, or in part, by the Wellcome Trust

[Grant number 211200/Z/18/Z to AC]. For the purpose of open access, the author has

applied a CC BY public copyright licence to any Author Accepted Manuscript version

arising from this submission.

Author Contributions:

Conceptualisation: VIN, AK, AC

Methodology: VIN, AK, BA-N, KG, AC

Investigation: VIN, AK, AC

Visualisation: VIN, AC

Supervision: AC, KG

Writing – original draft: VIN, AC

Writing – review & editing: VIN, AK, BA-N, KG, AC

Competing interests: Benjamin Alsbury-Nealy is the CEO and founder of SilicoLabs,

which provided the software for the experiment creation. Alex Clarke is a scientific

advisor for SilicoLabs.

Data materials and availability: All data, code, and materials can be found on zenodo at:

https://zenodo.org/doi/10.5281/zenodo.11394630