Main Manuscript for

Structural dynamics and neural representation of wing deformation.

Alexandra M. Yarger[1]*, Masateru Maeda[2], Igor Siwanowicz[3], Haruhiro Kajiyama[4], Simon M.
Walker[5], Richard J. Bomphrey[6], & Huai-Ti Lin[1]*

[1]Department of Bioengineering, Imperial College London; London, UK.
[2]Faculty of Engineering, Takushoku University; Tokyo, Japan.
[3]HHMI Janelia Research Campus; Ashburn, USA.
[4]Graduate School of Engineering, Takushoku University; Tokyo, Japan.
[5]School of Biomedical Sciences, University of Leeds; Leeds, UK.
[6]Department of Comparative Biomedical Sciences, Royal Veterinary College; London, UK.

Corresponding authors: Alexandra M. Yarger, Huai-Ti Lin
Email: a.yarger@imperial.ac.uk, h.lin@imperial.ac.uk

Author Contributions: Conceptualization: AMY, HTL, RJB; Methodology: AMY, HK MM, SMW,
RJB, HTL; Investigation: AMY, HK MM, SMW, RJB, HTL Visualization AMY, HK MM, SMW, RJB,
HTL; Supervision: HTL, RJB; Writing: AMY, RJB, HTL

Competing Interest Statement: Authors declare that they have no competing interests.

Keywords: mechanosensation, deformation, dragonfly, flight, aeroelastic

Abstract: Locomotor control is facilitated by mechanosensory inputs that report how the body
interacts with a physical medium. Effective representation of compliant wing deformations is
particularly challenging due to the many degrees of freedom. Structural configurations can
constrain the stimulus space, and strategic placement of sensors can simplify computation. Here,
we measured and modelled wing displacement fields and characterized spatiotemporal encoding
of the wing mechanosensors. Our data show how dragonfly wing architecture prescribes
deformation modes consistent across models and measurements. We found that the wing's state
under normal flapping conditions is detected by the spike timing of few sensors, with additional
sensors recruited under perturbation. The functional integration of wing biomechanics and sensor
placement enables a straightforward solution for information transfer.

Significance Statement: Many systems in nature precisely control highly deformable structures,
yet monitoring structural deformations has posed a significant challenge for biologists and
engineers. By measuring and modelling the intricate structure of compliant dragonfly wings, we
demonstrate an elegant solution for mechanosensory representation. We show that the functional
integration of natural wing biomechanics and sensor placement provides a straightforward
solution for information transfer. Wing morphology passively constrains the range of natural
deformations, producing strain patterns that align with sensor locations, allowing them to monitor
the wing using a simple timing-dependent encoding strategy. The way insects monitor
aerodynamic and inertial forces via wing deformations during flight could apply to many sensory
systems in nature and inspire artificial neural networks for controlling diverse dynamic systems.

Main Text:

Introduction

To produce effective outputs during fast behaviours, where time constraints limit the
amount of information that can be detected, nervous systems must have efficient and robust
mechanisms in place for processing sensory inputs. An extreme example of this is the wing

sensory systems of flying animals. Wings experience high loads at high speeds, which are complex but crucial for propulsion, stability and control. The unsteady aerodynamics of gliding and flapping flight interact with the wing's structural properties, resulting in passive wing deformations. Dramatic wing deformation is characteristic of animal flight and has been tied to inertial loads, lift generation, steering, and stall prevention(1–3). But with so many degrees of freedom and dynamic states, how do flying animals extract sufficient information from aeroelastic wings in real-time? Insect wings are often used as a model to study this problem because there is no actuation beyond the wingbase, so deformation can be attributed to passive effects. Insect wings also have a large range of mechanosensors, with dragonfly wings being among the most sensor-dense (4, 5). Wing mechanoreceptors can also convey information from multiple sources, highlighting the potential complexity of wing sensory systems(6).

In the context of behaviour, it isn't always necessary to represent every possible input condition constantly. In general, the precise tuning of insect sensors results from anatomy and neural encoding mechanisms that have evolved to extract only relevant information from the environment(7–13). Sensor tuning is modulated at multiple stages of the nervous system to allow dynamic and context-specific sensorimotor control(14–16). The stimulus space can be reduced *prior* to transduction by 'morphological computation', where information is filtered by structural mechanics, sensor location, or both. Sensor specificity is already well-documented for mechanosensation at the level of individual sensor morphology(17); for example, shape determines directional selectivity of strain-sensing campaniform sensilla (CS)(4, 18–21). Structural and location-based spatiotemporal filters for relevant mechanical inputs including cuticular strain, fluid flow, and sound are known across taxa(17–20, 22–25).

Similar mechanosensory encoding mechanisms and sensor distributions have been observed across insects(4, 5, 21, 26), but what are the features that determine optimal sensor locations? Thin rectangular plate wing models have previously identified sparse sensor placements for optimal representation of body rotations(27–29), but three-dimensional geometry is likely to have dramatic effects on deformations and hence sensor placement for optimal detection of the loading state during flight(2). To investigate this, we took a multipronged approach, measuring and modelling local and global deformation displacements and strains across the surface of the wings of tethered and freely flying dragonflies. We describe the effective stimulus space (the natural range of deformations that wings encounter) using dimensional reduction techniques and then characterize how only certain features are encoded (and are therefore available to the flight controller). Using information theory, we identify the most information-rich areas on the wings in relation to the actual sensor distribution (30, 31). With this synthesis (summarized in Movie S1), we demonstrate an elegant mechanism of morphological computation for mechanosensory representation in a biological system. The general principle, based on insects' ability to monitor instantaneous aeroelastic loading conditions via deformations during flight, is likely to be applicable across sensory systems in nature and could form the basis of guidelines for the design of sensor arrays for artificial neural networks used to control diverse dynamical systems.

Results

Free-flight control

Steering control has been extensively studied in insects(32–36). However, wing elevation, sweep, and pitch are typically the only kinematic variables considered, despite documentation of considerable variation in deformations, consistent with a role in flight control(2, 3, 37). To demonstrate that wing deformations are significant and correlated to flight maneuvers, we used a nine-camera, high-speed, free-flight arena to measure wing kinematics throughout the stroke cycles of freely flying dragonflies (*Sympetrum striolatum*; Fig. 1A). We found that even relatively straight flight trajectories result in differences in the patterns of deformation between

wing strokes; for example, bend amplitude (displacement from resting state = 0) varied between
the two forewings, though the phase relationship between them remained stable (Fig. 1B-D).
During a rolling turn (highlighted), there were changes to the deformation patterns compared with
straight flight; and clear asymmetries in the left and right forewing twist and bending patterns (Fig.
1E). Given the mechanosensory array at their disposal, these results suggest that strain patterns
would be encoded differently by each wing's sensory system.

To determine whether wing sensors are important for flight control, in a separate
experiment, we ablated the wing sensors by lesioning the anterior wing nerves. These nerves
contain the wing mechanosensory afferents and project to wing motor neurons (Fig. S9B). We
measured how sensor ablation affected the animals' ability to perform take-offs - a key flight
maneuver that has been described in detail and can be broken down into stereotypic
components(38). Here we focused on the first four full wingbeats, during which time the fore- and
hindwings move in synchronous phase. Nerve-ablated take-off attempts resulted in lower
elevation gains than nerve-intact and sham-ablation take-offs (Fig. S1A). Nerve-ablated
dragonflies also frequently abandoned take-off attempts once airborne and would glide or fall to
the ground (Movie S3).

Within individual conditions (either intact, sham, or nerve-ablated), there were no
significant differences between each consecutive wingbeat (Fig. S1), so all four wingbeats were
pooled for comparisons between conditions. There were no differences in forewing-hindwing
phase between all conditions and there were no differences in wingbeat frequency (WBF)
between intact and sham. However, nerve-ablated animals did have significantly lower WBFs
compared to both intact and sham animals (Fig. 1F). This is consistent with a previous study
where it was shown that the central nervous system contains all the neuronal machinery required
to produce the flapping motion but sensory feedback (including information from the wings) is
required to maintain appropriate flapping frequency(39). Having confirmed that wing sensors are
necessary to maintain frequencies that generate adequate lift during take-off, we moved on to
identifying inputs that the wing sensors are monitoring.

Wing deformation patterns

To understand how dragonflies monitor wing structural deformations, we first characterized
the natural range of wing deformation patterns using three parallel experimental approaches. Each
approach was designed to measure displacement of the wing relative to the wingbase reference
frame, ensuring that deformation within the wing was captured independently from displacements
due to wing hinge articulation (i.e. flapping). First, we drove a wing into aeroelastic flutter(40) using
an unsteady wind stimulus. The fluttering wing, immobilized at the hinge, was filmed using a high-
speed camera. A digital image correlation (DIC; see Methods) analysis was then used to
reconstruct the wing's displacement field (Fig. 2B). Second, we re-processed the wing deformation
from the nine-camera free-flight data in the same format as the flutter displacement field maps
(Movie S4). Finally, we produced a high-fidelity wing model incorporating fine details of vein
geometry for finite element modal analysis (FEA) and fluid-structure interaction (FSI) gliding
simulations (Fig. 2C). FEA also yielded high-resolution strain fields, which we later use to assess
the efficacy of the CS strain sensor distribution (Fig. 4G).

To characterize the natural wing deformations, we sought to represent the overall wing
motion with the fewest necessary variables by dimensional reduction. A principal component
analysis (PCA) of the fluttering wing data revealed that 99% of the wing's displacement variance
can be described by the first three components, interpreted as bending, twist, and camber
structural modes ("Flutter", Fig. 2Di). The same modes were also present in our flapping flight
measurements ("Flapping", Fig. 2Dii) except for the mode representing camber, which is not
currently measurable as the method only reconstructs the leading and trailing edges. However,
camber has previously been documented in free-flight in dragonflies(41) and is a known essential

feature of insect wing deformation(2, 35, 42). Nevertheless, the bend and twist modes
represented 96% of the displacement variance. PCA of FSI simulation (Movie S1) revealed the
same modes ("FSI", Fig. 2Diii), and they also emerged as natural modes in FEA simulations (Fig.
2E) demonstrating that our high-fidelity wing geometry model captures the physics of deformation
(Fig. S2). Together, they show that a linear decomposition of wing displacements reveals a
handful of modes inherent to the wing structure that are excited during gliding and flapping flight.
Could the wing sensory system leverage the structural properties to encode the wing deformation
using a handful of modes? We investigated this possibility by characterizing the mechanosensor
encoding mechanisms.

Temporal selectivity

Does the sensory array detect the spatial modes excited during flight? To test this, we
recorded neural activity simultaneously with airflow stimulation (Fig. 2A). The wing deformed
periodically in response to the airflow and the frequency of deformation contains information
about the system's mechanical behaviour(43–46). We anticipated that deformations could be
phasically encoded and looked for phase information in afferent signals passing into the thoracic
ganglia through the wing's anterior nerve. A template-matching custom spike sorting
application(47) was used to separate the responses of sensory neurons into individual 'units'
within each tethered recording; typically, recordings contained 1-3 distinguishable units. To
identify the primary deformation features driving each unit, we first performed PCA on the high-
dimensional wing displacement data to extract the most significant modes for each unit. Spike-
triggered averages (STA) were then computed and visualized along these PCA-derived modes
(Fig. 3A), providing an intuitive representation of the temporal response while preserving the
underlying multidimensional feature structure. Covariance analysis also confirmed that PCA
accurately captures the dominant response features (Fig. S4D). The recorded sensors are
sparsely activated and cannot be recorded for long periods due to their proximity to the
mechanical stimulation. As a result, applying nonlinear models such as maximum noise entropy
or maximally informative dimensions led to overfitting and unintuitive results. In general, STA
combined with simple feature identification methods (e.g. PCA) are sufficient for describing
signals in peripheral neurons, especially mechanosensors(48), and serve the purpose of this
study. Due to the high dimensionality of our data, we performed feature extraction prior to STA.
However, covariance analysis of the spike-triggered raw displacements was also performed on
the trial shown in Figure 2 and two features were identified: bend and twist (Fig. S4D).

Across trials, the 1-2 largest units (signal to noise ratio>4) dominated the overall activity
of the recording and were consistently phase-locked to the bending and twisting modes (and, less
strongly, to camber) at the wing's natural frequency (Fig. 3B). It should be noted that these
modes are always present simultaneously and were only separated here to simplify analysis and
allow 2D visualization of the STA. When all three features are recombined, we still find that these
units responded to the same patterns of deformation at different phases (Fig. 3C); the phase of
activation for these units was observed to shift depending on the displacement magnitude (Fig.
3B). These responses enable the dragonflies to encode derived conditions: for example,
asymmetries between contralateral wings, or bending mode magnitude at different points within
the stroke cycle. To avoid misrepresenting responses to cyclical stimulation using STA, units that
were not phase-locked were excluded in the analysis (Fig. 3C). Phase-locked units are defined by
vector strength (Fig. S4)(49, 50). Importantly, in our tethered preparation the wing base is fixed,
so inertial rotations of the wing relative to the body are absent. This indicates that the phase-
locked neural responses we observe are driven by aeroelastic deformations arising from
aerodynamic and structural forces, rather than by inertial or gyroscopic effects.

An important feature of biological control systems is that they should be robust to novel
stimuli. To understand how wing sensors respond to deformations outside the observed spatial
modes and frequencies, we presented unnatural perturbations using a lever arm attached at a

single point, the nodus, vibrating with uniform white noise (0-500Hz). Vibration-induced
displacements were confirmed to be outside of the range observed in our tethered and free-flight
experiments by comparing spatial modes (Fig. 3E) and frequencies (Fig. S6) to those previously
identified (Fig. 2E). These differences were also reflected in the neural signal; white noise vibration
resulted in increased spike frequency, and the recruitment of additional units at lower displacement
amplitudes (Fig. 3F). In airflow stimulus recordings, all large units were phase-locked (vector
strength>0.5) with good signal to noise ratio (>2). These units were also activated in response to
lever-arm stimuli, but reliable unit identification was not possible due to additional overlapping units
that emerged. Though these new units could not be characterized here, our results suggest that
the large number of strain sensors may be critical for monitoring unnatural perturbations.

Spatial selectivity: sensor localization

Extracellular recordings do not allow direct identification of the neurons. However, due to
the causal effect, the mechanosensor activity should maximally correlate to the wing area where
the strain sensors are located. To identify candidate sensors, we calculated coherence between
the activity of each unit and the displacement or strain within small spatial bins (akin to pixels)
across the wing surface (Fig. 4A). Coherence is a measurement of the correlation between two
signals across frequencies and represents how well one signal predicts another. High coherence
represents more accurate predictions, in this case how well a unit predicts the wing's deformation
or vice versa. The coherence and peak coherence frequency of a single unit and the
displacement of the wing across spatial bins is shown in Fig. 4A-C.

Coherence was high across a range of frequencies, so to capture the stimulus-response
correlation for all frequencies, we converted coherence to information rate using information theory
(see Supplementary Material). Unsteady airflow stimulation is inherently unrepeatable so we used
the most conservative lower bound method(31) to estimate the information rate for each bin (Fig.
4D). Bins with the highest information rates normalized by spike count are shown for each recorded
unit within an animal for both displacement and strain measurements (Fig. 4E). Regions of
maximum information rate are broadly consistent for multiple individuals (Fig. 4F), corresponding
to the same areas of the wing that our FEA modelling identified as experiencing the largest strains
from bend, twist, and camber (Fig. 4G). Overlaying these regions onto a wing sensor distribution
map suggests individual CS candidates for the units recorded (Fig. 4H). The highest sensor
densities are found where there is the highest information transfer between strain measurement
and sensor response (Fig. S7). Sensor activity also remains when the distal portion of the wing is
removed (Fig. S8).These are particularly effective locations for observing the strains associated
with key wing deformation modes, and away from the wing margins where damage occurs
throughout the animal's life (51). The information rate of dragonfly wing CS is broadly comparable
with other spiking sensory systems (Fig. 4I). This is expected, as all mechanosensors abide by the
same biophysical principles.

Discussion
229
Here, we reaffirm that insect wings, in common with all structures, have finite spatial
patterns and ranges of deformation that are excited at particular frequencies. The naturally
occurring range of spatial states can be simplified by dimensional reduction methods and are
dominated by bending and twisting. When wings are discretized to finite elements with sufficient
geometric fidelity, simulations reproduce the same patterns as their primary modes. This FEA
model therefore enables detailed analyses of the effect of architectural features and their
relationship to sensor distribution (Fig. 4). While bend, twist, and camber may be mechanically
inevitable responses for any flexible thin blade, the specific 3D morphology of dragonfly wings
shapes the unique bend, twist and camber lines. Wing veins, corrugations, and material
heterogeneities collectively enhance and concentrate deformations to specific locations. Placing
sensors within these regions of high strain enables more precise tuning and efficient detection of

wing loading. Thus, although the presence of these modes (bend, twist, and camber) may be a
general mechanical property of flexible wings, our data shows how the dragonfly wing's detailed
architecture facilitates effective sensing and control. Sparse sensors capturing wing deformation
is a well-established principle, but our results demonstrate exactly how the dragonfly's 3D wing
geometry shapes the strain patterns and sensor placement on a real wing blade.

Mode-specific strain detection has been observed in other systems. Fly halteres
(modified hindwings that detect inertial forces) also demonstrate how biomechanical constraints
can shape sensor placement and specificity (10, 13, 14, 18, 48, 52). Whereas haltere
mechanosensors are arranged to detect Coriolis forces arising from body rotations, wing
mechanosensors also capture the fluid-structure interactions that shape aeroelastic deformations
which underly force production and flight control. This is true of all insect wings, where specific
morphologies and sensor distributions have arisen as a result of individual behavioural,
ecological, and control demands. In dragonflies, we found that the wing's structural properties act
as a computational device that prescribes and constrains deformations into predictable oscillatory
patterns, reducing the effective stimulus space prior to neurophysiological transduction. The
amplitude of these deformations changes appreciably during free-flight manoeuvres (Fig. 1) and
these changes are reflected in the timing of the recorded sensors' activation (Fig. 3). Comparing
the timing of the sensors between wings or relative to the wingbeat cycle would allow dragonflies
to monitor the instantaneous loading conditions during these manoeuvres. The timing of these
units is not as precise as some other systems, such as dipteran halteres (Fig. S4B; 49), but the
decreased timing precision might be explained by dragonfly wings having slower dynamics than
fly halteres, more degrees of freedom, and being exposed to less predictable aerodynamic forces
in addition to inertial forces. Despite the added complexity of the wing's stimulus space, we show
that these sensors are nevertheless capable of monitoring the natural range of deformations
using a simple phase-dependent encoding strategy.

Strain sensors (CS) are most densely clustered in a region of the wing found proximally
along the major wing veins where aeroelastic loads give peak strains during gliding and flapping
flight. Moreover, this evolved sensor placement was predicted by the areas offering the highest
information rates for the recorded units. There is strong spatial correlation across the wing, so
sensors could potentially be placed in many different locations and extract similar information.
However, small differences in sensor accuracy can have a huge impact when monitoring complex
behaviours like flight, and it is unlikely that these sensors are placed by chance in the region
which contains the most accurate information. Prior work on generic deformable wings produced
optimal sensor placements and information patterns that differ from what we observed in
dragonflies (28, 29). These locations were influenced by wing stiffness and neural threshold, but
in general, modelled sensors tended to cluster along the outer edges of the wing tip or base. In
contrast, insect wing strain sensors are most often concentrated at the wing base along the
interior veins (4, 6, 53). This comparison supports the idea that natural wing morphology
specifically shapes sensor placement and information encoding in ways that cannot be captured
by simplified flat wing models.

Dragonflies have hundreds of wing mechanosensors(5), yet we found just a few large
amplitude units are activated and dominate the signal in the wing nerve under natural conditions
(in the absence of perturbation). The additional sensors recruited during white noise perturbations
may be necessary under circumstances where unusual temporal and/or spatial deformations
occur and are likely tuned to higher velocity changes, consistent with the fact that white noise
perturbations contain higher frequency displacements than airflow-induced flutter. Our results
suggest that while the wing sensory system uses few sensors to monitor the wing state, many
additional sensors are present and poised to detect deviations from the normal expected modes –
i.e. continuous oscillations primarily composed of bend and twist. The speed at which dragonflies
must react to changes in their expected sensory environments and the number of sensors
recruited during these perturbations indicates that deviations from the natural wing state are likely

represented as a population code. This population code may also be adaptable. Sensor locations
and even axonal paths can vary between individuals(5) and dragonflies can experience
significant wing damage throughout their lives(51). We hypothesize that when wing mechanics
change – either during development as they harden over time, or if they are damaged -
adaptation is accomplished further downstream by integrating interneurons that receive inputs
from multiple modalities. In this case, visual, ocellar, or proprioceptive information would also be
necessary to augment the wing sensory inputs when the wing mechanics change. Other senses
could provide a ground truth comparison for the animal's perception of self-motion which would
allow recalibration of their sensorimotor control internal models(54, 55).

Invertebrates have historically provided a significant source for bioinspiration in
engineered technologies(56–62). There have been many studies on dragonfly wing
aerodynamics and some on material properties, yet 3D anatomy has rarely been addressed with
sufficiently high fidelity for accurate structural analysis and assessed in the context of free-flight.
Similarly, the distribution of mechanosensor types have been identified(5) but this is the first
characterization of how the loading states are monitored. Accurate state estimation using wing-
mounted strain sensors has recently been demonstrated as a promising avenue for the
development of 'fly-by-feel' biomimetic aerial vehicles(63, 64). Other deformable objects, from
bridges to prosthetics, have been extensively studied across fields with much effort placed on
displacement and strain field measurement and reconstruction techniques (65–72). Here, we
have shown how morphology dictates and limits the range of the stimulus space, and strategically
placed sensors enable sufficient sensitivity, while reducing detection of redundant signals. The
dragonfly's morphology and sensor distribution allow their relatively small nervous systems to
produce simple and scalable representations of natural deformations.

Materials and Methods

Free-flight kinematics

S. striolatum were filmed taking off from a vertical perch using nine high-speed cameras
(five Photron AX200 and four Photron SA3, Photron Ltd) recording at 2000 fps and 1024 x
1024px. Sequences were trimmed to exclude time when the body was within approximately one
body length of the perch and all four wings were engaged in stereotypical flapping flight. A voxel-
carving method was used to measure the six degrees of freedom of the body and wingtip
spherical coordinates(73). Fifth order polynomials were fitted to the voxels corresponding to the
leading and trailing edge of the wing (from 10% to 90% wing length), which were then
transformed into the wingbase reference frame, aligned with the basal twist of the wing. Wing
deformations (MovieS4; Fig. 2Di) were then calculated by fitting a 80x50 point surface to the
leading and trailing edge polynomials. In total, 14 sequences were processed, including 99
wingbeats (pooling left and right forewings).

Nerve ablations

S. striolatum were collected from artificial ponds at Imperial College London Silwood Park
campus. Animals were kept at 7°C prior to experiments and restrained on a 13°C Peltier during
surgery. Animals were subjected to either a sham surgery where the anterior nerves were
exposed but kept intact or an ablation surgery where the anterior nerves were lesioned. After
surgery, parafilm was used to cover the incision site and secured with beeswax. Animals were
allowed 20-30 minutes recovery time and were screened prior to and after surgery to ensure they
were healthy and capable of sustained lift in free-flight. This was defined by whether, when
dropped, individuals were able to navigate to the ceiling or wall of the filming tent at or above the
initial drop height. To encourage animals to take off, they were placed on a 75x75 mm platform
with a Peltier heating element underneath. The Peltier warmed to a maximum of 59°C over 1.5
minutes. Take-offs were filmed at 1000 fps using two Chronos 2.1-HD cameras (Kron

Technologies Inc., Canada) and digitised using DLT DataViewer(74). Data were not normally
distributed, so comparisons were made using Kruskal-Wallice (WBF) or Multi-sample test for
equal median directions (phase) with Bonferroni correction for six comparisons (Table S1)(50).

Deformations

To identify the global motion patterns of the wing we aimed to represent the overall wing
state with few variables. To measure local motion and strain, we filmed the fluttering wing during
electrophysiological recordings at 1000 fps using a Chronos 2.1-HD camera (Kron Technologies
Inc., Canada) and performed digital image correlation (DIC)(75) on the recorded video frames
(Fig. 2B). DIC requires a material's surface to be patterned, typically by painting with a splatter
coat, however painting the wing would alter its mechanics and we found that the wing venation
pattern alone provides sufficient visual patterns for DIC to extract displacement and strain. To
accommodate electrode and stimulus while maximising visualisation of the largest deflections
(dorso-ventral), animals were positioned on their side and angled upward at 40° with the camera
placed approx. 20° behind the animal. Perspective correction, cropping, and contrast
enhancement were performed on each frame prior to DIC analysis. Subset window sizes varied
slightly between animals depending on the wing size and amount of motion blur but were typically
1% of the total wing size. Single camera (2D-DIC) measurements with perspective correction
were sufficient to capture the same measured displacements as two camera (3D-DIC)
measurements(76) (Figure S3A).

Electrophysiology

The wing was stimulated using either airflow or direct mechanical vibration. The airflow
stimulation apparatus consists of an axial fan and airflow straightener to blow air across the wing
at behaviourally relevant speeds (1-3m/s) and angles of attack (-/+20° & 0° relative to the
chordwise plane between the costa and arculus veins; Fig. S3). The direct mechanical stimulation
was provided by a precision lever-arm system (Aurora Scientific 300C: Dual-Mode Muscle Lever).
The lever was attached at the nodus on the wing, and vibration stimuli included uniform white
noise (0-500Hz) or aeroelastic flutter playback (Fig. S5). The flutter displacement data were
derived from digitising the nodus during airflow stimulation using DLT DataViewer (74). This
stimulus replicated the natural nodus motion in the absence of airflow. The forewing was fixed at
the hinge in a natural (gliding) flight position using a 50/50 mixture of paraffin and beeswax.
Fixing the hinge largely excludes internal proprioceptors from stimulation, allowing only wing
surface sensors to be activated. The airflow stimulation apparatus or lever-arm system was
aligned to the fixed wing sample rather than to the body axis to account for any difference across
specimens. Hindwings were folded dorsally out of view of the camera and restricted with a folded
strip of paper and paper clip. To record the activity of wing mechanosensors, we performed a side
entry dissection and removed a single layer of trachea to access the anterior wing nerve. A
borosilicate glass suction electrode was pulled using a Sutter P-2000 Laser-Based Micropipette
Puller, cut with a ceramic tile to match the diameter of each nerve (30-50 μm), and used to record
extracellularly from anterior nerve primary afferents. Anterior nerves receive inputs from all wing
vein CS (Fig. 4H). The posterior wing nerve only receives inputs from the wing hinge, so posterior
nerve recordings were not included here. Recordings where muscle contractions occurred were
easily identified from the large movement artefacts and were subsequently discarded.

Finite Element Analysis and Fluid-Structure Simulation

The wing's structural properties largely dictate the modes of deformation. Combes and
Daniel (2003) found that the hawkmoth's wing deformation patterns are still sufficiently predicted
when fluid-dynamic forces are excluded from damped finite element models(77, 78). Thus, we
also performed a modal analysis simulation for a dragonfly forewing model retaining realistic
corrugation with Ansys Mechanical 2024 R2 (Movie S5). The wing model geometry was

constructed by combining the µCT scanning for a *S. striolatum* wing for vein cross-sections and
the 3D venation from the direct linear transform (DLT) from a pair of stereo photos. See Fabian et
al., 2022 for the details of the model construction method. The wing density (except for the
pterostigma) was assumed to be 1200 kg/m3, while the pterostigma mass was set to be 9% of
the total wing mass[79]. The Young's modulus was 4.9 GPa for the entire wing[80]. Using the
same wing model, we performed a fluid-structure interaction simulation on a gliding dragonfly
forewing. The fluid dynamics solver (Ansys Fluent) for unsteady laminar simulation and structural
dynamics solver (Ansys Mechanical) for transient structural simulation were loosely coupled
(Ansys System Coupling) to obtain the converged solution for each time step. The example
sequence shown in Movie S1 is a gliding simulation where wind speed is 2.6 m/s and angle of
attack is 15° (Reynolds number is approximately 970).

Temporal Analysis

In this study, STA was sufficient in providing the first approximation to the sensory
encoding especially when the input information was linearly represented. Non-linear models such
as maximum noise entropy (MNE) and maximally informative dimensions (MID) were not
applicable for several reasons. Firstly, the recorded sensors are sparsely activated, and the
recording cannot be maintained for long periods due to their proximity to the mechanical
stimulation. The limited spikes led to overfitting in MNE and MID with uninterpretable results.
Secondly, the stimulus space dimensionality of a fast deforming wing is an order of magnitude
larger than what is typically used for non-linear models[81]. To accurately represent the local
deformations across the wing surface requires ~30,000 variables (bins) per time point (frame).
Typically, only 1-2 variables are used in these models, so the computational requirements for
30,000 are not realistic. To reduce computational requirements, dimensionality reduction
techniques can be performed prior to modelling, but this requires making more assumptions
about the data. Units which were not phase-locked with the periodic stimuli were excluded from
STA analysis (see Fig. S4B for further explanation). Phase-locked units were classified using
vector strength (Fig. S4)[49, 50]. Phase was calculated for each unit relative to PC scores by
measuring the time between oscillation peaks and normalizing this to radians. The time point
between peaks where the spike occurs is the phase value in radians. Phase-locked units were
identified by calculating vector strength (see Eq.1). Units with vector strength >0.6 were
considered phase-locked and vector strength between 0.5-0.6 were classified as weakly phase-
locked. Units that were not phase-locked were likely a result of inaccurate sorting due to the low
signal to noise ratio of smaller units.

Equation S1: $$Vector\ strength = \frac{1}{N}\sqrt{\left(\sum_i \cos \theta_i^2\right) + \left(\sum_i \sin \theta_i^2\right)}$$

Perturbations

In addition to white noise vibrations, we also replayed natural deformations generated
from airflow-induced oscillations. Airflow-induced oscillations and airflow playback vibration PCs
are the same, but with different rank orders (Fig. S5A). Airflow playback resulted in an
intermediate sensory response with more recruitment than airflow, but less than white noise
vibration (Fig. S5B). These differences were likely a result of the frequency content (Fig. S6) of
vibration-induced deformations being different from airflow-induced and free-flight. The
amplitudes tested were initially matched to airflow-induced oscillations. However, smaller
amplitudes activated many more units for vibration-driven experiments, so while a similar range of
amplitudes were covered, on average, lower amplitudes were tested for perturbation
experiments. The mean displacement from baseline (in either direction) for airflow-induced
deformations was 2.6 +/- 1.2 mm and the maximum displacement tested was 13.6 mm. The
mean displacement from baseline (in either direction) for vibration-induced deformations was 1.2
+/- 1.1 mm and the maximum displacement tested was 15.4 mm. The maximum (positive

direction) displacement measured across trials for free-flight deformations was 2.5 +/- 0.5 mm
and the minimum (negative direction) was 2.1 +/- 0.5 mm.

Neural information

The neural response variable x represents the mechanosensory spike train converted to
a binary vector at the video frame rate (1 = spike, 0 = no spike), aligned to video frames and
mean subtracted prior to coherence analysis. This approach preserves spike timing at the video
frame resolution without additional smoothing. The magnitude-squared coherence (C_{xy}) was
estimated between each unit's activity (x) and the displacement or strain change from baseline of
each bin (y) as a function of their power spectral densities, Pxx and Pyy, and cross power
spectral density, Pxy between 0 and 500Hz(82). Numerical approximation error was reduced by
increasing the number of segments (dividing the input signals into smaller, overlapping 100 ms
sections). This allows for better averaging and reduces the influence of random fluctuations within
individual sections. Averaging across many segments decreases the frequency resolution, which
is reflected in Figure 4A where the frequencies measured appear smoothed. This can also result
in a loss of information for slowly varying components of the signal; however, these components
are not behaviourally relevant as the forces acting on the wing during flight are not slowly varying.
Coherence calculations using few segments did produce similar spatial maps but also amplified
DIC measurement errors resulting in unreliable coherence and information rate estimates.

Equation S2:
$$C_{xy} = \frac{|P_{xy}|^2}{P_{xx}P_{yy}}$$

Airflow stimulation is generally only statistically repeatable, so the more conservative
lower bound method was used to estimate information rate (I) in bits/s from coherence, which
assumes linearity and stationarity. (31, 83). For most analyses, we used displacement as a more
direct representation of the wing movement. However, for the sensor localization (Fig. 4), strain
was the more appropriate choice as the local strain pattern is what activates these sensors.
Occasially, DIC analysis could not resolve wing edges due to motion blur, so those pixels were
not included in coherence estimations. We did not remove entire frames, only the individual pixels
that could not be resolved. These pixels tended only to occur along the lateral trailing edge of the
wing where sensor density is far lower. To normalize for spike rate, high information regions were
defined as the bins with information rates within the top 1-5% (depending on the number of
unresolvable pixels removed) for each individual unit.

Equation S3:
$$I = -\int_{0Hz}^{500Hz} \log_2(1 - C_{xy})df$$

The mean information rate for dragonfly wing mechanosensors was found to be higher
than other systems (Fig. 4I), in part because we used turbulent airflow instead of white noise
(which covers a larger range and more even distribution of frequencies).

Imaging

See Fabian et al., 2022 for neural imaging and sensor distribution mapping protocols.

Acknowledgments: The authors thank Daniel Ko, Sean Lim, Janka Kluga, Rui Zhou, and
Myriam Uhrhan for their help with instrumentation. We thank Holger Krapp, Benjamin Campbell,
and Samuel Fabian for their valuable discussion and feedback.

Funding: Biotechnology and Biological Sciences Research Council, Grant/Award Numbers:
BB/R002509/1 (to HTL), BB/R002657/1 (to RJB). Numerical simulations were supported by the

Data availability: Data are available at Dryad Digital Repository: DOI: 10.5061/dryad.41ns1rnqh

References:

1.   S. Lee, J. Kim, H. Park, P. G. Jabłoński, H. Choi, The Function of the Alula in Avian Flight. *Sci
Rep* **5**, 9914 (2015).

2.   R. Wootton, The Geometry and Mechanics of Insect Wing Deformations in Flight: A
Modelling Approach. *Insects* **11**, 446 (2020).

3.   R. Wootton, Support and deformability in insect wings. *Journal of Zoology* **193**, 447–468
(2009).

4.   B. R. Aiello, *et al.*, Spatial distribution of campaniform sensilla mechanosensors on wings:
form, function, and phylogeny. *Current Opinion in Insect Science* **48**, 8–17 (2021).

5.   J. Fabian, *et al.*, Systematic characterization of wing mechanosensors that monitor airflow
and wing deformations. *iScience* **25**, 104150 (2022).

6.   B. Pratt, T. Deora, T. Mohren, T. Daniel, Neural evidence supports a dual sensory-motor
role for insect wings. *Proceedings of the Royal Society B: Biological Sciences* **284**, 20170969
(2017).

7.   D. C. O'Carroll, N. J. Bidweii, S. B. Laughlin, E. J. Warrant, Insect motion detectors matched
to visual ecology. *Nature* **382**, 63–66 (1996).

8.   H. C. Bennet-Clark, "8. Songs and the Physics of Sound Production" in *8. Songs and the
Physics of Sound Production*, (Cornell University Press, 2019), pp. 227–261.

9.   K. Schildberger, M. Hörner, The function of auditory neurons in cricket phonotaxis. *J.
Comp. Physiol.* **163**, 621–631 (1988).

10. A. Fayyazuddin, M. H. Dickinson, Haltere afferents provide direct, electrotonic input to a
steering motor neuron in the blowfly, Calliphora. *J Neurosci* **16**, 5225–5232 (1996).

11. B. Webb, R. R. Harrison, M. A. Willis, Sensorimotor control of navigation in arthropod and
artificial systems. *Arthropod Structure & Development* **33**, 301–329 (2004).

12. K. D. Longden, T. Muzzu, D. J. Cook, S. R. Schultz, H. G. Krapp, Nutritional State Modulates
the Neural Processing of Visual Motion. *Current Biology* **24**, 890–895 (2014).

13. S. J. Huston, H. G. Krapp, Nonlinear Integration of Visual and Haltere Inputs in Fly Neck
Motor Neurons. *J. Neurosci.* **29**, 13097–13105 (2009).

14. J. A. Bender, M. H. Dickinson, A comparison of visual and haltere-mediated feedback in the
control of body saccades in Drosophila melanogaster. *Journal of Experimental Biology* **209**,
4597–4606 (2006).

15. A. Dahake, A. L. Stöckl, J. J. Foster, S. P. Sane, A. Kelber, The roles of vision and antennal
mechanoreception in hawkmoth flight control. *eLife* **7**, e37606 (2018).

16. D. Rien, R. Kern, R. Kutz, Octopaminergic modulation of a fly visual motion-sensitive
neuron during stimulation with naturalistic optic flow. *Frontiers in behavioral neuroscience*
7 (2013).

17. S. P. Sane, M. J. McHenry, The biomechanics of sensory organs. *Integrative and
Comparative Biology* **49**, i8–i23 (2009).

18. J. W. S. Pringle, J. Gray, The gyroscopic mechanism of the halteres of Diptera. *Philosophical
Transactions of the Royal Society of London. Series B, Biological Sciences* **233**, 347–384
(1997).

19. M. H. Dickinson, Comparison of Encoding Properties of Campaniform Sensilla on the Fly
Wing. *Journal of Experimental Biology* **151**, 245–261 (1990).

20. M. H. Dickinson, Directional Sensitivity and Mechanical Coupling Dynamics of
Campaniform Sensilla During Chord-Wise Deformations of the Fly Wing. *Journal of
Experimental Biology* **169**, 221–233 (1992).

21. B. H. Dickerson, J. L. Fox, S. Sponberg, Functional diversity from generic encoding in insect
campaniform sensilla. *Current Opinion in Physiology* **19**, 194–203 (2021).

22. J. P. Bacon, R. K. Murphey, Receptive fields of cricket giant interneurones are related to
their dendritic structure. *J Physiol* **352**, 601–623 (1984).

23. G. A. Jacobs, J. P. Miller, Z. Aldworth, Computational mechanisms of mechanosensory
processing in the cricket. *Journal of Experimental Biology* **211**, 1819–1828 (2008).

24. F. G. Barth, Mechanics to pre-process information for the fine tuning of
mechanoreceptors. *J Comp Physiol A Neuroethol Sens Neural Behav Physiol* **205**, 661–686
(2019).

25. M. J. Uhrhan, R. J. Bomphrey, H. Lin, Flow sensing on dragonfly wings. *Annals of the New
York Academy of Sciences* **1536**, 107–121 (2024).

26. J. C. Tuthill, R. I. Wilson, Mechanosensation and adaptive motor control in insects. *Curr Biol*
26, R1022–R1038 (2016).

27. T. L. Mohren, T. L. Daniel, S. L. Brunton, B. W. Brunton, Neural-inspired sensors enable
sparse, efficient classification of spatiotemporal data. *Proc. Natl. Acad. Sci. U.S.A.* **115**,
10564–10569 (2018).

28.   A. I. Weber, T. L. Daniel, B. W. Brunton, Wing structure and neural encoding jointly
determine sensing strategies in insect flight. *PLoS Comput Biol* **17**, e1009195 (2021).

29.   A. I. Weber, *et al.*, Nonuniform structural properties of wings confer sensing advantages.
Journal of The Royal Society Interface **20**, 20220765 (2023).

30.   F. Reich, D. Warland, R. de Ruyter von Steveninck, W. Bialek, *Spikes: Exploring the Neural*
Code (1997).

31.   A. Borst, F. E. Theunissen, Information theory and neural coding. *Nat Neurosci* **2**, 947–957
(1999).

32.   G. Rüppell, Kinematic Analysis of Symmetrical Flight Manoeuvres of Odonata. *Journal of*
Experimental Biology **144**, 13–42 (1989).

33.   J. M. Wakeling, C. P. Ellington, Dragonfly Flight : II. Velocities, Accelerations and Kinematics
of Flapping Flight. *Journal of Experimental Biology* **200**, 557–582 (1997).

34.   T. L. Hedrick, T. L. Daniel, Flight control in the hawkmoth Manduca sexta: the inverse
problem of hovering. *J Exp Biol* **209**, 3114–3130 (2006).

35.   J. M. Melis, I. Siwanowicz, M. H. Dickinson, Machine learning reveals the control mechanics
of an insect wing hinge. *Nature* **628**, 795–803 (2024).

36.   S. M. Walker, *et al.*, In Vivo Time-Resolved Microtomography Reveals the Mechanics of the
Blowfly Flight Motor. *PLOS Biology* **12**, e1001823 (2014).

37.   S. M. Walker, A. L. R. Thomas, G. K. Taylor, Deformable wing kinematics in the desert
locust: how and why do camber, twist and topography vary through the stroke? *J R Soc*
Interface **6**, 735–747 (2009).

38.   Q. Li, M. Zheng, T. Pan, G. Su, Experimental and Numerical Investigation on Dragonfly Wing
and Body Motion during Voluntary Take-off. *Sci Rep* **8**, 1011 (2018).

39.   P. J. Simmons, The neuronal control of dragonfly flight. (1977).
https://doi.org/10.25911/5d7783acf1631.

40.   J. M. McCarthy, S. Watkins, A. Deivasigamani, S. J. John, Fluttering energy harvesters in the
wind: A review. *Journal of Sound and Vibration* **361**, 355–377 (2016).

41.   C. Koehler, Z. Liang, Z. Gaston, H. Wan, H. Dong, 3D reconstruction and analysis of wing
deformation in free-flying dragonflies. *Journal of Experimental Biology* **215**, 3018–3027
(2012).

42.   T. L. Hedrick, S. A. Combes, L. A. Miller, Recent developments in the study of insect flight.
Can. J. Zool. **93**, 925–943 (2015).

43.   A. M. Wilson, M. P. McGuigan, A. Su, A. J. van Den Bogert, Horses damp the spring in their
576   step. *Nature* **414**, 895–899 (2001).

577   44.   K. Ishizaka, J. L. Flanagan, Synthesis of voiced sounds from a two-mass model of the vocal
578   cords. *The Bell System Technical Journal* **51**, 1233–1268 (1972).

579   45.   A. J. Hudspeth, How the ear's works work. *Nature* **341**, 397–404 (1989).

580   46.   W. Cade, Acoustically Orienting Parasitoids: Fly Phonotaxis to Cricket Song. *Science* **190**,
581   1312–1313 (1975).

582   47.   D. Ko, H.-T. Lin, NBits-Dragonsort. (2024). Deposited 26 May 2024.

583   48.   J. L. Fox, A. L. Fairhall, T. L. Daniel, Encoding Properties of Haltere Neurons Enable Motion
584   Feature Detection in a Biological Gyroscope. *Proceedings of the National Academy of
585   Sciences of the United States of America* **107**, 3840–3845 (2010).

586   49.   A. M. Yarger, J. L. Fox, Single mechanosensory neurons encode lateral displacements using
587   precise spike timing and thresholds. *Proc Biol Sci* **285**, 20181759 (2018).

588   50.   N. I. Fisher, *Statistical Analysis of Circular Data* (Cambridge University Press, 1993).

589   51.   H. Rajabi, V. Schroeter, S. Eshghi, S. N. Gorb, The probability of wing damage in the
590   dragonfly Sympetrum vulgatum (Anisoptera: Libellulidae): a field study. *Biol Open* **6**, 1290–
591   1293 (2017).

592   52.   H. Krapp, G. Taylor, J. Humbert, "The mode-sensing hypothesis: Matching sensors,
593   actuators and flight dynamics" in *Frontiers in Sensing: From Biology to Engineering*, (2012),
594   pp. 101–114.

595   53.   E. Gettrup, Sensory Regulation of Wing Twisting in Locusts. *Journal of Experimental Biology*
596   **44**, 1–16 (1966).

597   54.   B. P. Campbell, J. A. Supple, S. T. Fabian, H.-T. Lin, H. G. Krapp, Adaptive feedforward speed
598   control in Drosophila. [Preprint] (2025). Available at:
599   https://www.biorxiv.org/content/10.1101/2025.03.03.641162v1 [Accessed 5 July 2025].

600   55.   M. Mischiati, *et al.*, Internal models direct dragonfly interception steering. *Nature* **517**,
601   333–338 (2015).

602   56.   A. A. Makarova, A. A. Polilov, D. B. Chklovskii, Small brains for big science. *Current Opinion
603   in Neurobiology* **71**, 77–83 (2021).

604   57.   F. Song, Y. Yan, J. Sun, Review of insect-inspired wing micro air vehicle. *Arthropod
605   Structure & Development* **72**, 101225 (2023).

606   58.   J. B. Bergmann, D. Moatsou, U. Steiner, B. D. Wilts, Bio-inspired materials to control and
607   minimise insect attachment. *Bioinspir. Biomim.* **17**, 051001 (2022).

608   59.   L. Díaz-García, B. Latham, A. Reid, J. Windmill, Review of the applications of principles of
609   insect hearing to microscale acoustic engineering challenges. *Bioinspir. Biomim.* **18**,
610   051002 (2023).

611   60.   L. Holden-Dye, R. J. Walker, Invertebrate models of behavioural plasticity and human
612   disease. *Brain Neurosci Adv* **2**, 2398212818818068 (2018).

613   61.   L. Sumathirathne, T. Kim, D. Q. Bower, L. F. Deravi, Cephalopods as a Natural Sensor-
614   Display Feedback System Inspiring Adaptive Technologies. *ECS Sens. Plus* **2**, 023601 (2023).

615   62.   C. Harvey, G. de Croon, G. K. Taylor, R. J. Bomphrey, Lessons from natural flight for
616   aviation: then, now and tomorrow. *Journal of Experimental Biology* **226**, jeb245409 (2023).

617   63.   T. Kim, *et al.*, Wing-strain-based flight control of flapping-wing drones through
618   reinforcement learning. *Nat Mach Intell* **6**, 992–1005 (2024).

619   64.   K. Kubota, H. Tanaka, Machine Learning-Based Wind Classification by Wing Deformation in
620   Biomimetic Flapping Robots: Biomimetic Flexible Structures Improve Wind Sensing.
621   *Advanced Intelligent Systems* **2400473**.

622   65.   V. E. Arriola-Rios, *et al.*, Modeling of Deformable Objects for Robotic Manipulation: A
623   Tutorial and Review. *Front Robot AI* **7**, 82 (2020).

624   66.   F. Nadon, A. J. Valencia, P. Payeur, Multi-Modal Sensing and Robotic Manipulation of Non-
625   Rigid Objects: A Survey. *Robotics* **7**, 74 (2018).

626   67.   D. Rus, M. T. Tolley, Design, fabrication and control of soft robots. *Nature* **521**, 467–475
627   (2015).

628   68.   J. Montagnat, H. Delingette, N. Ayache, A review of deformable surfaces: topology,
629   geometry and deformation. *Image and Vision Computing* **19**, 1023–1040 (2001).

630   69.   M. Gherlone, P. Cerracchio, M. Mattone, Shape sensing methods: Review and
631   experimental comparison on a wing-shaped plate. *Progress in Aerospace Sciences* **99**, 14–
632   26 (2018).

633   70.   Z. Ma, J. Choi, H. Sohn, Structural displacement sensing techniques for civil infrastructure:
634   A review. *Journal of Infrastructure Intelligence and Resilience* **2**, 100041 (2023).

635   71.   X. Wang, *et al.*, Recent Progress in Electronic Skin. *Advanced Science* **2**, 1500169 (2015).

636   72.   L. Chen, *et al.*, Spike timing–based coding in neuromimetic tactile system enables dynamic
637   object classification. *Science* **384**, 660–665 (2024).

638   73.   S. Walker, G. Taylor, A semi-empirical model of the aerodynamics of manoeuvring insect
639   flight. *Journal of the Royal Society, Interface* **18**, 20210103 (2021).

74. T. L. Hedrick, Software techniques for two- and three-dimensional kinematic
measurements of biological and biomimetic systems. *Bioinspir. Biomim.* **3**, 034001 (2008).

75. J. Blaber, B. Adair, A. Antoniou, Ncorr: Open-Source 2D Digital Image Correlation Matlab
Software. *Exp Mech* **55**, 1105–1122 (2015).

76. D. Solav, K. M. Moerman, A. M. Jaeger, K. Genovese, H. M. Herr, MultiDIC: An Open-Source
Toolbox for Multi-View 3D Digital Image Correlation. *IEEE Access* **6**, 30520–30535 (2018).

77. S. A. Combes, T. L. Daniel, Into thin air: contributions of aerodynamic and inertial-elastic
forces to wing bending in the hawkmoth *Manduca sexta*. *Journal of Experimental Biology*
206, 2999–3006 (2003).

78. E. Baroth, *et al.*, "IVHM (Integrated Vehicle Health Management) techniques for future
space vehicles" in *37th Joint Propulsion Conference and Exhibit*, (American Institute of
Aeronautics and Astronautics).

79. R. Åke Norberg, The pterostigma of insect wings an inertial regulator of wing pitch. *J.
Comp. Physiol.* **81**, 9–22 (1972).

80. S. R. Jongerius, D. Lentink, Structural analysis of a dragonfly wing. *Experimental Mechanics*
50, 1323–1334 (2010).

81. J. Aljadeff, B. J. Lansdell, A. L. Fairhall, D. Kleinfeld, Analysis of Neuronal Spike Trains,
Deconstructed. *Neuron* **91**, 221–259 (2016).

82. S. M. Kay, *Modern spectral estimation: theory and application* (Prentice Hall, 1988).

83. C. E. Shannon, A mathematical theory of communication. *The Bell System Technical Journal*
27, 379–423 (1948).

84. F. H. Eeckman, *Analysis and Modeling of Neural Systems* (Springer US, 1992).

85. H. Clague, F. Theunissen, J. P. Miller, Effects of adaptation on neural coding by primary
sensory interneurons in the cricket cercal system. *J Neurophysiol* **77**, 207–220 (1997).

86. D. K. Warland, P. Reinagel, M. Meister, Decoding visual information from a population of
retinal ganglion cells. *J Neurophysiol* **78**, 2336–2350 (1997).

87. R. Wessel, C. Koch, F. Gabbiani, Coding of time-varying electric field amplitude
modulations in a wave-type electric fish. *J Neurophysiol* **75**, 2280–2293 (1996).

88. M. Juusola, A. S. French, The Efficiency of Sensory Information Coding by
Mechanoreceptor Neurons. *Neuron* **18**, 959–968 (1997).

89. F. Theunissen, J. C. Roddey, S. Stufflebeam, H. Clague, J. P. Miller, Information theoretic
analysis of dynamical encoding by four identified primary sensory interneurons in the
cricket cercal system. *J Neurophysiol* **75**, 1345–1364 (1996).

90.   G. T. Buračas, A. M. Zador, M. R. DeWeese, T. D. Albright, Efficient Discrimination of
674   Temporal Patterns by Motion-Sensitive Neurons in Primate Visual Cortex. *Neuron* **20**, 959–
675   969 (1998).

676   91.   R. A. DiCaprio, C. P. Billimoria, B. C. Ludwar, Information rate and spike-timing precision of
677   proprioceptive afferents. *J Neurophysiol* **98**, 1706–1717 (2007).

678   92.   W. Bialek, F. Rieke, R. R. De Ruyter Van Steveninck, D. Warland, Reading a Neural Code.
679   *Science* **252**, 1854–1857 (1991).

680   93.   H. Wolf, The Locust Tegula: Significance for Flight Rhythm Generation, Wing Movement
681   Control and Aerodynamic Force Production. *Journal of Experimental Biology* **182**, 229–253
682   (1993).

683   94.   M. A. Frye, Effects of stretch receptor ablation on the optomotor control of lift in the
684   hawkmoth Manduca sexta. *J Exp Biol* **204**, 3683–3691 (2001).

685   95.   E. Marder, A. L. Taylor, Multiple models to capture the variability in biological neurons and
686   networks. *Nat Neurosci* **14**, 133–138 (2011).

687   96.   J. A. Supple, *et al.*, Binocular Encoding in the Damselfly Pre-motor Target Tracking System.
688   (2020). https://doi.org/10.17863/CAM.48011.

Figures and Tables

Fig. 1. Free-flight kinematics. A) Nine synchronised high-speed cameras captured free-flight
wing deformations at 2000 frames per second (fps). B) Body orientation over time of freely flying
dragonfly (see Movie S2). Orientation is relatively straight for initial two wingbeats. Roll
manoeuvre highlighted in red occurs during the third stroke cycle. C) Wing stroke angle
(calculated relative to mean stroke plane) showing comparative wing timing across three
wingbeats. D) Wing bend amplitude change across wing strokes. E) Forewing twist pattern
changes during roll manoeuvre. F) Ablated wingbeat frequency (WBF) was significantly lower
than intact (P=0.00002) and sham (P=0.0024) conditions during takeoffs filmed with one camera
at 1000 fps. There was no significant difference between intact and sham WBF, and no significant
phase difference between all conditions (see table S1).

Fig. 2. Wing deformation parameters. A) Wings were mounted in fluctuating airflows. Surface deformations were filmed with a high-speed video camera at 1000 fps and the neural activity of the wing mechanosensory afferents were recorded simultaneously. B) Wings were filmed at an angle to maximize visualization of dorso-ventral (V) displacements (distal-proximal (D) and anterior-posterior (A) displacements were negligible; see Fig. 3S2A). After perspective correction, digital image correlation (DIC) was used to measure displacement. C) A 3D external morphological model of a dragonfly forewing reconstructed by hybridizing the live wing vein pattern (determined by direct linear transformation of stereoscopic views) with vein cross-sectional geometries (isolated from μCT scans; top). Bottom shows rotated close-up view. D) PCA results. i. Deformation modes during flutter, representing 99% of overall variance (N=5 animals, 14,000-49,000 frames/animal). ii. Deformation modes during free flapping flight (base/tip interpolated from measured displacements) representing 96% of overall variance (F_2=2nd harmonic). iii. FSI (15°, 2.6 m/s) deformation modes representing 99% of overall variance E) FEA deformation modes ranked by oscillation frequency (see Movie S5). FEA camber modes have similar patterns & frequencies (dominated by deflections in both directions along the trailing edge) and are likely represented together within camber mode of the fixed wing preparation flutter experiments and FSI simulations.

749
750

Figure 3. Phase encoding. A) Principal component (PC) displacement scores and the
associated afferent spike response to airflow-induced wing deformations were used to calculate
spike-triggered averages (STA) for each unit (see also Fig. S4A). Vertical black bars represent
spike times for unit 2. B) Activation timing of phase-locked units for each PC (See Fig. S4B).
Vertical bars show spike time relative to PC oscillation. Thick and thin bars represent strong
(vector strength>0.6) and weak (0.6>vector strength>0.5) phase-locking, respectively, and bar
height corresponds to displacement amplitude (1-4 mm). Phase timing shifts with displacement
amplitude. C) Heatmap reconstructions of PC1-3 STA for airflow induced deformations with 4 mm
mean absolute displacement of the entire wing. Each image represents a single frame (1 ms).
Images highlighted in black show the spike time. D) White noise vibrations result in novel
displacement modes (colormap as in Fig. 2). E) White noise induced displacements (above)
result in greatly increased neural activity compared to airflow induced displacements (below).
Colours indicate different units.

Figure 4. Sensor localisation. A) Coherence between the activity of a single sensory unit and the displacement of the wing for three example spatial bins and the mean peak coherence for all bins across the wing surface (black) between 0-500Hz. Unit 2 peak coherence for the mean of all bins is 171Hz. B) Peak coherence values of all bins. Darker regions show higher coherence. C) Frequencies at which the peak coherences shown in panel B occurred. For this unit, most peaks occur at 171Hz. D) Information rate of unit 2 estimated from coherence between 0-500Hz of all bins using the lower bound method. E) Wing regions with the highest normalized displacement information rates for each of the recorded units previously shown in Fig. 3. The darkest region in D corresponds with the dark blue region shown here (unit 2). F) Wing regions with the highest normalized displacement (top) and strain (bottom) information rates across animals (N=5 animals, n=3,3,2,2,1 cells respectively). Colours correspond to individuals and shade variations show different units recorded from the same individual. Data in A-E are from animal 1 (A1). G) FEA spanwise strain for key deformation modes (green-compressive, purple-tensile) showing regions of high strain. H) Locations of CS on major veins. Dorsal and ventral denoted by marker

780   colour. Shaded regions show high strain information rates from F. Sensors located in these
781   regions represent likely candidates for the recorded units. I) Lower bound estimates of
782   information rate for dragonfly CS (mean of all cells' maximum rate across the wing surface)
783   compared with other spiking sensory systems(48, 84–92).

808
809
810

Supporting Information for

Sensor placement and structural dynamics simplify neural
representations of wing deformations.

Alexandra M. Yarger, Masateru Maeda, Igor Siwanowicz, Haruhiro Kajiyama, Simon M. Walker,
Richard J. Bomphrey, & Huai-Ti Lin

Alexandra M. Yarger & Huai-Ti Lin
Email: a.yarger@imperial.ac.uk, h.lin@imperial.ac.uk

This PDF file includes:

       Supporting text
       Figures S1 to S9
       Table S1
       Legends for Movies S1 to S5
       SI References

Other supporting materials for this manuscript include the following:

       Movies S1 to S5

Supporting Information Text

Model choice

To demonstrate how morphological computation contributes to the tuning of biological sensory systems, dragonflies are an ideal model. Their large, highly deformable wings are easy for structural measurements and their wing afferent signals are accessible for electrophysiological recordings. Furthermore, while all flying animals have deformable mechanosensitive wings, dragonflies are among the most agile fliers and their wings are frequently used as models for aerodynamics and wing mechanics(37, 76–84). The dragonfly wings' mechanics naturally limit their range of deformation, but there is still a large available state-space significant for flight control.

Tegula complex

In locust(1, 2) and hawkmoth(3) a mechanosensory structure on the hindwing - called the tegula - influences forewing motor control. The tegula plays an important role in the generation of rhythmic flight motor patterns in both insects but has not previously been described in dragonflies. We identified a tegula-like structure called the 'tegula complex' which comprises a hair plate and CS field (Fig. S8D). The tegula complex, like the tegula, may be responsible for maintaining wing synchrony in dragonflies. Forewing nerve ablated dragonflies are still able to maintain synchrony between their fore- and hindwings, albeit at a lower frequency, indicating that the hindwings (and hindwing tegula complex) may be responsible for maintaining wing synchrony. Afferents from the tegula complex were not recorded here but may be of interest for future studies investigating mechanisms for wing synchronization.

Phase shifts

Phase time shifts that result from changes in displacement amplitude (Fig. 3C) are descriptive of a single feature only and those features have been extracted from the overall displacement pattern. Larger amplitude bending does not scale equally with twist or camber, and here the displacement speed has also been normalized across amplitudes. This may partially explain why we often see a phase advance rather than a phase delay with increased amplitudes. Alternatively, large amplitude bending is typically caused by large aerodynamic loading. Such passive deformation can be characterized by a wave propagating tip-to-base, in contrast to the deformation driven by the flapping musculature with a base-to-tip propagation. Depending on the location of the exact strain sensor being recorded, the phase timing will shift according to the contribution from these two waves. Regardless of the specific physical mechanism, it is important to consider that the overall pattern of motion is not identical for every amplitude. However, because the stimulus space is constrained by the wing structure, the possible deformations are still limited to a finite range of patterns that can be described by bend, twist, and camber. Any motion outside of the natural wing state will necessarily activate additional sensors that can encode the deformations not represented within the natural range.

Perturbation-activated sensors

In general, individual variation and adaptability exist because the nervous systems is able to produce appropriate outputs using a variety of different mechanisms(4, 5). We did not characterize the selectivity of perturbation-activated sensors as it is outside the scope of the current study. It requires extensive cataloguing of responses across conditions, morphologies, and individuals. Selectivity and encoding strategies are unlikely to be identical between individuals(5) and input sensitivity is also likely to depend on context e.g. structural changes or behaviour state(6–8). The large number of active units also prevents accurate sorting with the current recording preparation. Future experiments will aim to resolve more units simultaneously

886   for characterizing these sensors' selectivity and other factors including sensor redundancy and
887   adaptability.

888   ***Deformation Frequency components***

889   Airflow induces consistent wing oscillations as a result of the structural and material
890   properties of the wing. The natural frequency of the wing (Fourier transform dominant frequency
891   of mean displacement of entire wing) across animals was 135+/-23Hz. Faster air speeds resulted
892   in slightly higher frequencies (18.6+/-15.2Hz increase from 1-3m/s, N=5 animals). The dominant
893   frequencies of the PCs were the same as the mean displacement frequency (Fig. S6). Vibration
894   induced deformations have higher frequencies of twist and camber motion.

Fig. S1. Nerve ablation. A) Take-off elevation over the first four wingbeats. Different shades represent different animals. Circles mark start of forewing downstroke. N=7 animals, 2 trials per condition. Two animals appear in both intact and sham (green) and two in both sham and ablated (blue). B) No significant differences in WBF between wingbeats within each condition. Grey and black bars show mean and median respectively. Ablated WBF significantly lower than intact (P=0.00002) and sham (P=0.0024). No significant difference between intact and sham WBF. C) No significant differences in the hindwing phase relative to the forewing between wingbeats within each condition. No significant differences between all conditions. Data resolution results from video frame rate (1000 fps).

937 **Fig. S2.** Pairwise correlations of displacement maps. A) The bend pattern is highly correlated
938 across all conditions. Twist is also highly correlated between conditions. Camber is only
939 correlated between Flutter and FSI because camber could not be measured during flapping. B)
940 All highly correlated pairs were significant. The only non-significant correlations were between
941 combinations with low correlation values (e.g. flapping bend & FSI camber).

Fig S3. Wing displacement PCs. A) Example frames of two camera 3D measurements of displacement magnitude (top), single camera dorso-ventral displacement measurements (middle) and displacement reconstructed from PCs 1-3 (bottom). B) Angle of attack (AoA) and air speed do not influence PCs. Example PCs calculated from 7000 frames. C) Hindwing PCs are similar to forewing PCs. PCs calculated from 5000 frames. D) PCs are the same across dragonfly species tested. PCs calculated from 100-1000 frames. All wings filmed at 1000 fps and resized to equal wingspan and cord width for easier comparison.

Fig. S4. Phase measurements. A) Sorted units shown in Figure 3 (i) and their associated PC STAs (ii). B) Phase (q) is calculated by measuring the relative time (j) between oscillation peaks normalized to radians. Phase-locked units are identified by calculating vector strength (see Eq.1). Units with vector strength above 0.5 are classified as phase-locked. C) Unit 1 phase (vertical bars) relative to PC score STAs (i) normalised to radians (ii). All phase-locked units from airflow induced deformations with 4 mm mean displacement (iii; see also Fig. 3). D) Significant features (E1-E2) identified through covariance analysis of the spike-triggered raw displacements. Camber was notably not present, indicating that this mode is less likely to be represented in the neural signal. This result was consistent across units tested.

Fig. S5. Airflow playback vibration. A) Airflow playback vibration induced deformation PCs. B) Airflow playback result in moderately increased extracellular activity compared to airflow induced displacements. Colours indicate different units.

998 **Fig. S6.** Displacement frequency components. Frequency components of mean absolute
999 displacement of the entire wing and PC scores (PC1-bend, PC2-twist, PC3-camber) for airflow
1000 (A) and white noise vibration (B) stimuli.

1001

1002

1003

1004

1005

1006

1007

1008

1009

1010

1011

1012

1013

1014

1015

1016

1017

1018

Fig. S7. Hotspot analysis. A) Sensor, information, strain maps, and shuffled bend stain map
converted to continuous greyscale images. B) Hotspots from A defined by 99th percentile plotted
as binary images. Spatial autocorrelation (Moran's I) values for each image shown in blue. Values
>0.5 suggest strong clustering. Significant values indicated by *. C) Correlation statistics for
continuous images (A). D) Correlation statistics for binary images (B).

1024

1025 **Fig. S8.** Sensor activity remains after distal portion of wing is removed. Extracellular recording
1026 from *Orthetrum cancellatum* (A) and *Celithemis elisa* (B) wing nerve in response to airflow with
1027 wing intact (top) and cut (bottom). Large sensory units highlighted in red.

1028

1029

1030

1031

1032

Fig. S9. Wing mechanosensor neuroanatomy. A) Anterior (AN) and posterior (PN) wing nerves
project ipsilaterally within T2 & T3. PN projects to T1 and brain (panel C) and a subset of AN
afferents from the tegula complex (panel D) project to T1. B) AN projects to wing motor neurons
(MN) dvm3 (pronation) and pm2 (anti-overpronation). C) PN projections to secondary ocellar
interneurons (OI) in the posterior deutocerebrum. D) Hair plate and CS comprise the tegula
complex.

1039

1040

1041

1042

1043

1044

1045

1046

1047

 Table S1.

Comparison	Between wingbeats			Between conditions		
	Intact	Sham	Ablate	Intact vs. sham	Sham vs. ablate	Intact vs. ablate
Phase	0.58	0.47	0.75	0.058	0.023	0.57
WBF	0.94	0.63	0.49	0.016	0.0024*	0.000017**

1049   Multiple comparisons P values for nerve ablation experiments.

1050

1051

1052

1053

1054

1055

1056

1057

1058

1059

1060

1061

1062

1063

1064

1065

1066

1067

1068

1069

Movie S1.

High-speed video of a dragonfly taking off in its natural environment followed by the same
behaviour captured in a nine-camera, free-flight arena. Wing kinematics of freely flying
dragonflies were tracked (left) and reconstructed in 3D (right). Wing displacements (blue-upward,
red-downward) were measured throughout the stroke cycle during free-flight and simulated
gliding (fixed-wing airflow-induced displacements). Wing displacements were measured while
simultaneously recording the neural activity of wing mechanosensory afferents (strain sensors).
99% of the measured displacements are comprised of three principal components (bend, twist,
and camber) and different sensors (coloured spikes) are activated by different ratios of those
components. Micro-CT scans of the wing were used to construct a high-fidelity morphological
model of the dragonfly forewing. Fluid-structure simulations of gliding flight show detailed
measurements of wing displacement and strain. The regions of the wing that experience the
largest strains overlap with the identified locations of the strain sensors (that encode the principal
deformation components).

Movie S2.

Free-flight kinematics: Example flight trajectory includes three wingbeats where a roll manoeuvre
is performed during the last wingbeat.

Movie S3.

Example intact vs. nerve ablated take-off. Wingbeat frequency decreases after nerve ablation and
animals often abandon take-off attempts once airborne.

Movie S4.

Free-flight deformations. Displacement field maps generated from tracked leading and trailing
wing edges.

Movie S5.

Global displacement of FEA modes. Modes 1 & 2 show bend and twist. Modes 3-4 show camber.

1095

1096

1097

1098

1099

1100

1101

1102

1103

SI References

1. E. Gettrup, Sensory Regulation of Wing Twisting in Locusts. *Journal of Experimental Biology* **44**, 1–16 (1966).

2. H. Wolf, The Locust Tegula: Significance for Flight Rhythm Generation, Wing Movement Control and Aerodynamic Force Production. *Journal of Experimental Biology* **182**, 229–253 (1993).

3. M. A. Frye, Effects of stretch receptor ablation on the optomotor control of lift in the hawkmoth Manduca sexta. *J Exp Biol* **204**, 3683–3691 (2001).

4. E. Marder, A. L. Taylor, Multiple models to capture the variability in biological neurons and networks. *Nat Neurosci* **14**, 133–138 (2011).

5. J. A. Supple, *et al.*, Binocular Encoding in the Damselfly Pre-motor Target Tracking System. (2020). https://doi.org/10.17863/CAM.48011.

6. K. D. Longden, T. Muzzu, D. J. Cook, S. R. Schultz, H. G. Krapp, Nutritional State Modulates the Neural Processing of Visual Motion. *Current Biology* **24**, 890–895 (2014).

7. S. J. Huston, H. G. Krapp, Nonlinear Integration of Visual and Haltere Inputs in Fly Neck Motor Neurons. *J. Neurosci.* **29**, 13097–13105 (2009).

8. D. Rien, R. Kern, R. Kutz, Octopaminergic modulation of a fly visual motion-sensitive neuron during stimulation with naturalistic optic flow. *Frontiers in behavioral neuroscience* **7** (2013).