BIT: Bayesian Identification of Transcriptional Regulators

Zeyu Lu[1], Lin Xu[2,5*], Xinlei Wang[3,4*]

1. Department of Statistics and Data science, Moody School of Graduate and Advanced Studies, Southern Methodist University, Dallas, TX, USA

2. Quantitative Biomedical Research Center, Peter O'Donnell Jr. School of Public Health, University of Texas Southwestern Medical Center, Dallas, TX, USA

3. Department of Mathematics, University of Texas at Arlington, Arlington, TX 76019, USA

4. Center for Data Science Research and Education, College of Science, University of Texas at Arlington, Arlington, TX 76019, USA

5. Department of Pediatrics, Division of Hematology/Oncology, University of Texas Southwestern Medical Center, Dallas, TX, USA

Corresponding author:

Lin Xu (lin.xu@utsouthwestern.edu)

Xinlei Wang (xinlei.wang@uta.edu)

Abstract:

BIT is a novel Bayesian hierarchical model capable of predicting transcriptional regulators (TRs)

from the input of user-provided epigenomic regions. TRs are critical molecules in transcriptional

regulation. Many diseases and cancers are linked to the dysfunction of TRs. Knowing TRs in

certain biological process can help find new biomarkers or therapeutic targets. Thus, BIT

formulates a novel Bayesian hierarchical model with the Pólya-gamma data augmentation

strategy. Based on collected ChIP-seq datasets, BIT can identify TRs responsible for the

genome-wide binding pattern within the user-provided epigenomic regions. BIT has been

validated by using a simulation study and three applications.

Key Words: transcriptional regulator, Bayesian hierarchical modelling, Pólya-gamma data

augmentation, epigenomics regions,

Introduction

Transcriptional regulators (TRs), comprising transcription factors, cofactors, chromatin modulators, and various regulatory molecules, play a pivotal role in regulating the gene transcription[1-3]. TRs are essential in multiple cellular processes, including growth, differentiation, morphogenesis, and apoptosis[4-6]. Dysfunction of TRs can lead to various diseases, including cancers[7-9], diabetes[10,11], and heart diseases[12,13]. Thus, gaining insight into the identity and function of TRs can be helpful in a broad range of biological and medical research, such as finding new biomarkers and therapeutic targets[14-16].

Beyond traditional labor-intensive wet lab experiments, a growing interest in leveraging statistics has emerged to discern TRs based on the NGS data and the intricate interplay between epigenomic features. However, it is noted that the current available state-of-art computational methods to identify TRs based on NGS data suffer from various significant limitations. (i) Most of these methods rely on a gene list as input[17-21], requiring the conversion of peak regions derived from epigenomic data into associated genes. However, there is a lack of clear standards on how to perform this conversion, resulting in potentially inconsistent outcomes when applying different cutoffs to the same peaks. (ii) Some methods (e.g., MEME-ChIP[22], HOMER[23], and WhichTF[24]) rely on DNA sequence motifs. However, highly similar motifs shared among many TRs make accurate identification challenging[25], motifs alone cannot characterize any in-vivo binding event, and the lack of well-defined motifs for some TRs further reduces the reliability of using motifs for identification[2,26]. (iii) Each TR's binding pattern can vary significantly in different cell types or environmental conditions. However, published methods have no rigorous treatment of the within-TR heterogeneity and homogeneity when dealing with multiple TR ChIP-seq datasets from the same TR, resulting in biased results. (iv) All the existing methods employ frequentist approaches for TR statistical significance, lacking coherent probabilistic interpretation or

uncertainty estimation. Given the dynamic nature of TR binding events, the ability to quantify

uncertainty is not just beneficial but essential.

To overcome the proposed limitations, we developed a novel Bayesian hierarchical approach for

the identification of TRs responsible for genome-wide binding patterns, named BIT (Bayesian

identification of Transcriptional regulators). Bayesian hierarchical modeling is one of the most

powerful approaches to model complicated biological phenomena and integrate diverse

information. First, BIT eliminates the need for an input gene list, taking peak regions derived

from an epigenomic dataset as input. This removes the need for peaks-to-genes conversion,

reducing false positives and broadening its application compared to the existing methods.

Moreover, BIT does not rely on DNA sequence motifs, and so avoids the use of computationally

predicted motifs that might cause unreliable TR predictions in motif-based approaches[22,23,27].

Second, via a unique hierarchical model setup, BIT integrates information across multiple TRs

and multiple ChIP-seq datasets of the same TRs, appropriately accounting for both between-

and within-TR homogeneity and heterogeneity. This formal model-based treatment leads to

more reliable and robust prediction, as shown in our results. By contrast, many existing methods

need to conduct thousands of separate ad-hoc statistical tests (e.g., BART[18], Lisa[17], and ChIP-

Atlas[28]) and therefore tend to rank TRs with many ChIP-seq datasets higher[29]. Third, BIT

employs a Bayesian framework to handle its modeling and computational needs. A Bayesian

approach is inherently attractive in that (i) it pools information from various sources for better

estimation of model parameters, which is essential for effective prediction; (ii) it offers the

advantage of readily quantifying the estimation uncertainty such as providing a standard error or

95% credible interval of any quantity of interest (e.g., a parameter estimate or predicted

importance score); (iii) in situations when meaningful prior knowledge is available, it enables

researchers to formally incorporate such knowledge through prior specification for improved

results while in all other situations, with the default non-informative prior setting, it becomes a

fully automated procedure that does not require any tuning parameter. By contrast, none of the

existing methods can offer any of these advantages.

Results

The integration of omics data has been proved as a feasible approach to identify TRs in biomedical research[30]. It is well recognized that the binding sites of TRs critical to a specific cellular process are primarily enriched in the regulatory epigenomic regions of multiple downstream genes that drive the process[31]. Such epigenomic regions can be directly measured by epigenomic technologies[32,33] (e.g., H3K27ac ChIP-seq/ATAC-seq) or converted from genes identified by transcriptomic technologies and serve as an input "fingerprint"[34]. On the other hand, the binding sites of an individual TR can be measured by TR ChIP-seq[35], representing the most accurate available in-vivo data type for TR binding, with each ChIP-seq experiment unveiling unique binding profile for a specific TR. The pre-collected TR ChIP-seq datasets act as a reference database, using stored binding profiles as distinctive "fingerprints" for individual TRs. Users can compare the "fingerprint" of a newly studied cellular process with those in this reference database to pinpoint functional TRs that have similar epigenomic chromatin profiles.

BIT relies on two biological assumptions: (i) If a TR governs the user-provided epigenomic regions, the genome-wide binding pattern of this TR should be more consistent with the input regions. (ii) The distribution formulated by the similarity of TR ChIP-seq datasets from the same TR should be able to differentiate the TR from the population. The two assumptions are commonly used in other bioinformatics tools[18]. The first assumption implies that when a functional TR is actively involved in a specific cellular process that derives the user-provided epigenomic regions, this leads to a more frequent interaction between this functional TR and the DNA. Consequently, a significant number of the captured epigenomic regions are likely to encompass or be adjacent to the binding sites of this functional TR. The second assumption recognizes that certain variations exist within ChIP-seq datasets for the same TR, stemming from factors such as measurement errors, dataset quality, and cell type specificity. Despite these variations, it is expected that the general consistency observed across these ChIP-seq

datasets — a result of the TR's preference for binding to specific sites on chromatin — will

create a distinctive binding pattern. When comparing with the input epigenomic regions, this

pattern should be substantial enough to differentiate the functional TRs from other non-

functional TRs.

BIT only requires user-provided epigenomic regions as input and consists of two main steps:

Data pre-processing and Bayesian posterior inference with Gibbs sampler. First, BIT transforms

the coordinates of user-provided epigenomic regions and ChIP-seq peaks to fixed-length binary

vectors with 0s and 1s. Second, BIT formulates a Bayesian hierarchical model to integrate

information and uses the MCMC algorithm to perform the posterior estimation of the importance

of TRs. Finally, BIT assigns each TR a "BIT score" (**Fig. 1**). Based on the assumptions stated

above, the BIT score can be used as the overall significance indicator of the TR being

functional. Alternatively, it can be interpreted as the Jaccard similarity coefficient that quantifies

the distance between the binary vector representation of the TR unique binding pattern and the

binary vector representation of the input epigenomic regions.

Figure 1 A. Transcription regulators such as transcription factors, cofactors, and chromatin
modulators mostly bind to accessible chromatin regions to regulate gene transcription. NGS

techniques such as TR ChIP-seq and ATAC-seq can acquire the information of binding sites
and accessible regions, respectively. Input regions and collected TR ChIP-seq peaks are
transformed to binary vectors, the ratio of the "Good" cases over all "informative" cases serve as
the raw score. B. BIT is a Bayesian hierarchical framework integrated with Pólya-Gamma data
augmentation strategy to pool information from multiple TR ChIP-seq datasets. C. Gibbs
sampler is used to derive the posterior estimation of TR level BIT score and give the final
ranking table. The identified TRs can then be used for future research.

To verify BIT's performance, we first used a realistic and comprehensive simulation study to

examine the accuracy of the posterior estimation. As BIT is the first Bayesian model-based

approach that directly models over the accumulated TR ChIP-seq datasets, we used the naïve

method as the baseline. Second, we examined BIT's feasibility with three different applications:

(i) the identification of TRs by using differential accessible regions (DARs) that are derived from

TR perturbation experiments. Perturbed TRs should be responsible for the DARs, and therefore

these DARs can serve as ground truth datasets. (ii) we tested BIT in the identification of TRs by

using cancer-type specific accessible epigenomic regions. The identified TRs are cross-

validated by findings in previous publications and results derived from CRISPR/Cas9 loss-of-

function analysis. We also benchmarked results from BIT against results from several other

methods to show its efficiency. (iii) given the fast development of single-cell techniques, cell-type

level accessible regions can now be easily derived from scATAC-seq data. We further applied

BIT to two sets of cell type specific accessible regions and validated the results.

Simulation shows BIT can estimate parameters with high accuracy.

It is essential to use simulation study to show the performance of BIT in the posterior estimation,

as we can generate data from known distributions. The simulation study evaluated BIT in three

steps. (i). The mean squared error (MSE) of estimating the hyperparameters μ, τ^2, σ_0^2 and TR

level parameters θ_i and $\theta_{i'}$. (ii). The ability to recover the original ranks of generated θ_i and $\theta_{i'}$.

The metric used is spearman rho. (iii). The robustness of BIT that whether it heavily depends on

the normality assumption. We used the naïve method as the baseline and generated 100

replicates in each simulation setup.

In the simulation, we aimed to mirror realistic scenarios in which approximately 1,000

transcriptional regulators are associated with single or multiple datasets. We adopted three

conditions ($I = 500, 1000, 1500$) for the total number of θ_i and $\theta_{i'}$, each θ_i or $\theta_{i'}$ represents one

TR (with or without multiple datasets). It is reasonable to examine the performance of BIT over

different total numbers of θ_i and $\theta_{i'}$. By now, we collected 10770 TR ChIP-seq datasets that can

be associated with 987 TRs. However, these numbers can further increase as more TR ChIP-

seq experiments could be conducted in the laboratory. In contrast, certain TRs could be

excluded from the analysis if they have been validated before for the cellular process that

generates the input epigenomic regions.

Based on these considerations, we varied the number of θ_i and $\theta_{i'}$ generated in the simulation

to cover more scenarios. Similarly, the true values of hyperparameters are varied to examine

their effects on the model performance. We expect BIT to be effective regardless of the number

of TRs generated and the actual value of hyperparameters used. Furthermore, given that the

distribution of the number of collected datasets for each TR is highly right skewed and has a

long tail, we therefore used truncated non-central t distribution to generate the number of

datasets (θ_{ij} and $\theta_{i'1}$.) in the simulation.

In general, BIT can successfully capture the hyperparameters with high accuracy (**Fig. 2A**).

First, it is noted that the MSE for the BIT estimation of hyperparameters μ, τ^2, and σ_0^2 are

consistently lower than the baseline method and are close to zero in all cases. Second, using a

low number of TRs can have relatively higher MSE, but the difference is negligible in BIT. Third,

the MSE for the estimation of σ_0^2 is positively correlated with the actual value, which is

reasonable: as variability increases, the spread of data and the likelihood of outliers also

increases, which leads to a greater uncertainty in the estimation. Nevertheless, BIT still

significantly outperforms the baseline method.

The min-max range of MSE for estimating the θ_i and $\theta_{i'}$ over 100 replicates also show BIT have

better performance than baseline method (**Fig. 2B**). Unlike hyperparameters μ, τ^2, and σ_0^2,

which are fixed prior to the simulation, θ_i and $\theta_{i'}$ are randomly generated in each replicate. The

MSE in this context indicates the aggregate deviation between the estimation and the true

values generated within one replicate. The result shows that BIT consistently achieves higher

precision in estimating θ_i and $\theta_{i'}$ surpassing the baseline method. Besides the aggregated

deviation, we also examine the ability of BIT to recover the original rank of randomly generated

θ_i and $\theta_{i'}$. It is noted that τ^2 and σ_0^2 can affect the performance of methods (**Fig. 2C**), which is

reasonable. τ^2 control the overall dispersion of θ_i and $\theta_{i'}$. Thus, a larger τ^2 will increase the

distances among the true value of parameters, making them more easily distinguished. σ_0^2 is the

noise used to generate dataset level parameters $\theta_{i'1}$. Increasing σ_0^2 will lead to a larger error in

the estimation of $\theta_{i'}$, reducing the performance.

We also checked the robustness of BIT as multiple Gaussian distributions are assumed in the

BIT model. We used to different non-Gaussian distributions, student t distribution and gamma

distribution, to generate the θ_i and $\theta_{i'}$. The dispersion of simulated θ_i and $\theta_{i'}$ by these two

distributions are different from those generated from Gaussian distribution (**Fig. 2E**). student t

distribution is known for heavy-tailedness, as well as gamma distribution is known for skewness.

The simulated data are shifted and scaled to recover the same mean and variability for

comparison while keeping the pattern of heavy-tailedness and skewness. We noted the

performance of BIT is not sensitive to the heavy-tailedness or skewness of the distribution of

simulated data (**Fig. 2F**).

Figure 2. A. The MSE of the estimation for hyperparameters by using 100 replicates, BIT shows very high accuracy with MSE close to 0. B. The Min-Max MSE range bar of simulated θ_i and $\theta_{i'}$, still BIT show better performance in the estimation. C. The spearman rho correlation of BIT or Naive ranked simulated TRs versus true rank of simulated TRs. It is noted the BIT method outperform naive method and stay stable regardless of the change of hyperparameters. D. The simulated number of datasets under each TR mimic the collected number of datasets to make sure the simulation is realistic. E. The normality check, by using simulated data generated from t and gamma distribution, we examine whether the heavy-tailedness or skewness will significantly affect the BIT ranked simulated TRs F. The boxplot shows that BIT will not be significantly affected by normality problem.

In summary, we conducted several simulation studies to check whether the proposed BIT model

can lead to a reasonable estimation of parameters and recover the original ranks of the TRs as

expected. In all the simulation studies, BIT performs better than the baseline method, it can

estimate the parameter with high accuracy and recover the original ranks of randomly generated

θ_i and $\theta_{i'}$. In addition, it is noted that BIT is not sensitive to the normality assumption, and the

performance stays stable when the distributions used to generate simulated data have certain

heavy-tailedness or skewness.

BIT can identify perturbed TRs from differential accessible regions (DARs)

Differentially accessible regions (DARs) derived from differential accessibility analysis between

two biological conditions are critical in understanding the activity of TRs (**Fig. 3A**). We

demonstrate the feasibility of BIT in identifying TRs by using sets of DARs derived from three

separate TR perturbation experiments. Since the perturbation experiments are designed to

target specific TRs, these regulators are expected to have a direct connection to the derived

DARs. Therefore, the derived DARs can serve as ground truth data, and BIT is expected to

identify the perturbed TRs by using them as input. The first experiment is an acute depletion of

CTCF in the MLL-rearranged human B cell lymphoblastic leukemia (B-ALL) cell line SEM[36]. The

second one is from a ZBTB7A-knockout experiment in the HUDEP-2 cell line[37]. The third

experiment involves a FOXA2-knockout in the pancreatic progenitors 1 (PP1) differential stage

of human pluripotent stem cells (hPSCs)[38]. BIT has successfully identified the perturbed TRs

from the three experiments, and it has also identified several other TRs that can be reasonably

explained (**Fig. 3D**).

CTCF was ranked top 1 in the first experiment. Other top-ranked TRs include, SMC3, and

SMC1A, which are all components of cohesion complex. SMC proteins and RAD21 are core

proteins that formulate the ring-shaped cohesion complex (cohesion ring)[39,40]. CTCF and

cohesion ring can be crucial in forming chromatin loops and topologically associating domains

(TADs). The two structures are critical in the regulation of gene transcription[41,42]. Evidence has

shown that both CTCF and cohesion ring are essential for the maintenance of the two structures

when using acute depletion assays to handle proteins[43,44], which can explain why BIT also

identified the other three TRs after the acute depletion of CTCF.

In the second experiment, except for the ZBTB7A, GATA1 and KLF1 were also ranked in the top

10. Evidence has shown that erythroid differentiation and mutation can be controlled by GATA1

dependent transcription[45,46]. A previous study found ZBTB7A is a cofactor of GATA1 and plays

an essential antiapoptotic role during terminal erythroid differentiation[47], which explains why

GATA1 was also ranked at the top after the knockout of ZBTB7A. KLF1 can have a

multifunctional role in erythropoiesis and act as one of the master regulators[48].

BIT ranked FOXA2 in the top 3 in the third experiment. Though the ranking of perturbed TR is

not as high as the previous two experiments, we observed that other TRs, including PDX1,

GATA6, FOXA1, and GATA4 were also ranked in top 10. The observation is justifiable. These

TRs are both known for regulating the development and differentiation of pancreas[49-52].

Mutations and dysregulation of these regulators have been associated with various pancreatic

disorders. FOXA1 and FOXA2 are commonly recognized as pioneer factors that can change the

accessibility of chromatin[53]. PDX1, GATA6, and GATA4 might be recruited later to the accessible

regions to co-regulate the transcription process.

We further categorized the DARs as gain or loss accessible regions based on whether these

regions show increased (gain) or decreased (loss) accessibility after the perturbation of TRs

(**Fig. 3C and 3E**). It is noted that CTCF and FOXA2 can be well identified by BIT from increased

accessibility regions. Given that ZBTB7A is widely acknowledged as a repressor, it is not

surprising to observe that ZBTB7A is more significant with reduced accessibility regions[54]. Thus,

BIT can also help understand the functional role of the identified TRs in transcription.

Figure 3. A. BIT first transforms DARs and all TR ChIP-seq datasets into binary vectors. If
perturbation of specific TR is the main reason the derivation of DARs, these DARs should
significantly match the binding sites of this TR. R1-R6 represent DARs, while red regions are
peaks from FOXA2 TR ChIP-seq datasets and blue regions are from other non-FOXA2 TR
ChIP-seq datasets. B. The Jaccard index of two transformed binary vectors randomly selected
from same or different TR, which indicates regardless of factors such as cell line measured, the
binding sites of same TR are much similar than different TR. C. The number of gain or loss
accessible regions in each experiment. D. The top 10 TRs identified by BIT in each experiment.
E. BIT score calculated by using only gain or loss accessible regions can be associated with
TRs function as activator or repressor.

The results of the three TR perturbation experiments provide strong evidence for BIT's feasibility

in identifying functional TRs from DARs. BIT not only ranks the perturbed TRs in the top

positions but also demonstrates that it can find other experimentally validated TRs strongly

related to the perturbed TR or the cellular process.

BIT can identify cancer-type specific TRs

To further validate BIT's efficacy, we leveraged cancer-type specific accessible regions obtained

from The Cancer Genome Atlas (TCGA) database (details in **Table. S1**). TRs are well-

established drivers of crucial cellular processes in various cancers. However, a significant

portion of accessible regions recur across multiple cancer types. Including these non-specific

regions can hinder the identification of TRs critical to specific cancers. Therefore, employing

cancer-type specific accessible regions offered a more focused approach. We utilized regions

specific to nine cancer types: breast, bladder, colon, lung, liver, mesothelium, prostate,

squamous cell, and testis. More precisely, the ATAC-seq samples used to generate these

regions encompassed a broad range of carcinomas, including breast invasive carcinoma

(BRCA), bladder urothelial carcinoma (BLCA), and so on. The identified TRs were cross-

validated through existing publications and CRISPR/Cas9 screening data from The Cancer

Dependency Map Consortium (DepMap)[55], which evaluates cancer cell viability after gene

knockout.

Firstly, Many BIT identified top-ranked TRs are well-known for their significant roles in regulating

normal cell behaviors such as differentiation and proliferation, and the mutation of these TRs

can be a major reason for the development of cancers. For instance, in breast cancer, top-

ranked TRs include FOXA1, ESR1, and PGR. PIAS1, AR, and HOXB13 were identified in

prostate cancer. NANOG, SOX17, and POU5F1 were identified by BIT in testicular cancer. The

detailed TR ranking list for each cancer type is in Table S2. A total of 33 TRs were cross-

validated by available publications (**Table. S3**), and some TRs have already been used as

biomarkers or therapeutic targets in cancer treatment[56,57].

Secondly, we examined whether the epigenomic regions retrieved from the TCGA database are

truly specific to the cancer types. The Jaccard similarity coefficients of the transformed binary

vectors ranged from 0.003 to 0.150, which revealed minimal overlap between different cancer

types (**Fig. 4B** and **Table. S4**), affirming the specificity of the retrieved accessible regions to

their corresponding cancer types. We further examined the overlap of top-ranked TRs identified

by BIT across different cancer types. The top 10 TRs identified by BIT vary significantly among

cancer types, consistent with the Jaccard similarity coefficients of transformed binary vectors,

confirming that BIT can identify different TRs for different cancer types.

Thirdly, it is noted that several top-ranked TRs, such as NCOA3 and TET2 in breast cancer, lack

known motifs[2]. This absence means these TRs cannot be detected using motif-based methods,

despite solid experimental evidence supporting their significant roles in these cancers

respectively[58,59]. In contrast, BIT uses TR ChIP-seq data to rank these TRs to top positions

regardless of such concerns. This finding further highlights the BIT's advantage over traditional

motif-based methods, especially in cases where known motifs are ambiguous or absent.

Next, given the critical role of many TRs in cellular viability[7,60,61], we anticipated a correlation

between BIT identified top-ranked TRs and high-dependency TRs in corresponding cancer

types. CRISPR/Cas9 knockout screenings highlighted the dependency of TRs in various cell

lines. Our analysis revealed that by counting the number of high-dependency TRs in BIT

identified top 10 and top 50 TRs in each cancer type, about half of the BIT identified TRs are

highly correlated with cancer cell viability (**Fig. 4C**, 52/90 for top 10 and 231/450 for top 50, high

dependency TRs are determined as TRs with minimum Chronos score < -0.4). The dependency

scores of the top 50 TRs identified by BIT in prostate cancer cell lines show that TRs can have

different level of influence across different cell lines (**Fig. 4E**).

Figure 4. A. The top 10 TRs identified by BIT in each cancer type, some of the TRs have wider confidence interval than other TRs, many TRs have been proved to be significant by available publications. B. the upper triangle shows the Jaccard index of cancer-specific accessible regions between any two cancer types, the bottom triangle shows the similarity between the BIT identified top TRs between any two cancer types. C. The number of BIT identified top 10 and top 50 TRs that are also high dependency TRs in each cancer type. D. The comparison of enrichment of top identified TRs with high dependency TRs from CRISPR/Cas9 loss-of-function analysis between BIT and other methods (HOMER, WhichTF, BART, i-cisTarget). E. the dependency score of BIT identified top 50 TRs in different prostate cancer cell lines.

Lastly, we compared the enrichment of BIT-identified top-ranked TRs in high-dependency TRs

from CRISPR/Cas9 data with results from other state-of-art methods, including BART, ChIP-

Atlas, i-cisTarget, WhichTF, and HOMER. Using a one-sided Fisher exact test, the results show

BIT is the best or close to the best method in all cancer types (**Fig. 4D**). However, it is important

to remember that cellular viability is not an exclusive indicator of a TR's significance in cancer

cells. Therefore, multiple factors can contribute to the variability of the results. Still, BIT proves

its efficacy in identifying TRs from cancer-type specific accessible regions.

BIT can identify cell type specific TRs

The rapid advancement towards single-cell and spatial omics highlights the growing need for

tools capable of analyzing gene transcription within cell clusters generated by common single-

cell data processing methods. To acquire an accurate epigenomic landscape of chromatin

accessibility, the analysis of scATAC-seq data frequently categorizes individual cells into

clusters to mitigate the scarcity of fragments per cell. One major task for the downstream

analysis is to investigate the activity of TRs based on the derived cell cluster level pseudo-bulk

accessible regions. Therefore, we also examined the applicability of BIT in identifying critical

TRs using cell type-specific accessible regions derived from scATAC-seq data.

Two datasets, including 10K Peripheral blood mononuclear cells (PBMCs) and primary liver

cancer samples, were used to study BIT's performance. The cells in two datasets were

previously annotated based on the dimension reduction results and marker genes. The UMAP

projection of the datasets shows a clear separation of different cell types in each dataset (**Fig.**

5A). SnapATAC2 was applied to generate cell type marker accessible regions. Specifically, we

applied BIT to marker accessible regions derived from B cells in PBMCs dataset and malignant

cells in liver cancer datasets. The results were thoroughly validated by different approaches.

We examined the credibility of top 20 TRs identified by BIT in the two investigated cell types

(**Fig. 5B**). The credibility of each TR in the list was evaluated based on existing publications and

by examining whether the TR was designated as a significantly elevated gene in the Human

Protein Atlas for the respective cell type (**Table. S4**). Notably, BIT successfully captured several

TRs critical for B cell development. These include PAX5 and EBF1, which were previously

reported for their role in maintaining B cell identity. Additionally, POU2AF1 and POU2F2 can act

as pivotal regulators in B cell proliferation, differentiation, the germinal center transcriptional

program, and immune response. The gene activity plot also shows a high specificity of identified

TRs in the two cell types (**Fig. 5D**).

For liver cancer malignant cells, consistency is observed between the top TRs identified from

the scATAC-seq data and from the aggregated bulk ATAC-seq data as shown in the previous

section. Specifically, SOX13, HNF4A, and HLF are again ranked highly by BIT. It is noted that

the accessible regions used in the previous section were generated from bulk ATAC-seq data,

while those employed here are derived from scATAC-seq data specific to malignant cells. This

observed consistency strengthens the argument for BIT's robustness in identifying critical TRs.

We further assessed the top 20 TRs identified through motif enrichment analysis implemented in

SnapATAC2. Notably, as anticipated and mentioned in the introduction, the similarity of binding

motifs can hinder the differentiation between TRs from the same protein family. This is evident in

the top-ranked TRs identified by using motif methods implemented in the SnapATAC2, where B

cell results include the POU, IRF, and PAX families, and the liver cancer malignant cells exhibit

enrichment for the ZNF and FOX families (**Fig. 5C**). It is crucial to recognize that not all

members within these protein families hold equal importance in the biological processes of their

respective cell types. Their inclusion in the top rankings solely reflects the inability of motif

enrichment analysis to identify which specific TR within the family directly interacts with the motif

site in the accessible chromatin regions. Next, we performed Gene Ontology (GO) enrichment

analysis for the top 20 TRs identified by BIT and motif enrichment in B cells. The results

revealed a strong enrichment for biological processes relevant to B cells or mononuclear cells in

the BIT-identified TRs. Conversely, the motif enrichment-identified TRs displayed enrichment for

the miRNA metabolic process (**Fig. 5E**).

Next, for BIT identified TRs from liver malignant cells, we investigated the potential of these TR

being as prognostic biomarkers for patients with liver cancers. Kaplan-Meier survival plots

revealed a statistically significant correlation between the differential expression of multiple TRs

and patient survival time (in months). This suggests that the BIT identified TRs could be

promising candidates for prognostic biomarkers in liver cancer (**Fig. 5F**). In addition, we similarly

examined the CRISPR/Cas9 post-knockout viability of top-ranked TRs in liver cancer cell lines.

The results show that BIT can identify more high dependency TRs than the motif enrichment

methods implemented in SnapATAC2 (**Fig. 5G** and **Fig. 5H**).

Collectively, our findings demonstrate the feasibility of using BIT for downstream analysis of

cluster-level accessible regions in scATAC-seq data. Beyond feasibility, BIT offers valuable

insights into potential regulatory mechanisms. This makes it a compelling alternative to the

current, dominantly motif-based enrichment methods used in scATAC-seq analysis.

Figure 5. A. Sub-clustering UMAP projection of human Peripheral blood mononuclear cells and primary liver cancer cells. B. We manually verified top 20 TRs identified by BIT by using B cell and liver malignant cell type specific ATAC-seq peaks. C. Compared to TRs identified by BIT,

motif enrichment analysis cannot accurately differentiate TRs share similar binding motifs, such
as POU family in B cell and ZNF / FOX family in malignant cells. D. UMAP visualization of TR
activity. Top ranked cell type specific TRs identified by BIT show much higher gene activity in the
respective cell types. E. Gene ontology enrichment of top 20 TRs identified by BIT given
mononuclear cell or b cell related biological process, while the enrichment of top 20 TRs
identified by motif enrichment analysis shows miRNA metabolic process. F. Kaplan-Meier Plots
show the expression level of BIT identified TRs have significant correlation with liver cancer
patient survival rate, which suggests these TRs could be potential survival biomarkers.

Discussion

In this study we proposed a Bayesian hierarchical model that uses publicly available NGS data

to identify transcriptional regulators with the input of user-provided epigenomic regions. Using

simulation and application studies, we demonstrate the effectiveness of BIT and compare it with

baseline or other existing methods. BIT has certain advantages compared to current available

methods. It is the first rigorous Bayesian hierarchical model to identify TRs from user-provided

epigenomic regions by leveraging accumulated TR ChIP-seq data. For example, BIT can give

the confidence interval of the estimation based on the MCMC algorithm, which has never been

explored before by other methods and can increase the Interpretability of the results.

We also observe several patterns that are worth to be noted. From the analysis based on

differential accessible regions (DARs), our results show perturbation of TRs that have different

functions can lead to different directionality of the change of chromatin accessibility. For

example, ZBTB7A is well known to be a major repressor in HUDEP-2 cells, and the reason why

BIT identifies it from loss accessible regions may have a direct relation to its functionality. Thus,

distinguishing the directionality of the change to chromatin accessibility is important in

identifying TRs from DARs.

The accuracy of BIT can be affected by multiple factors: (i) The quality of the data that

generates user-provided epigenomic regions. (ii) The quality and availability of the TR ChIP-seq

data. (iii) The consistency of the binding sites of TRs across different biological conditions. (iv)

The dependency of user-provided epigenomic regions to the TRs. The regulation mechanism of

gene transcription is complicated. Although BIT has been validated using multiple applications,

many factors can affect the validation results. For example, removing certain TRs might not

directly impact cell viability since other regulators can compensate for their function. The lack of

data for certain TRs due to the limited available research resources also constitutes a challenge

(e.g., lack of suitable antibodies). It also should be noted though BIT take the cellular

heterogeneity between TR ChIP-seq datasets into consideration, the current available

combination of TRs and cell lines may only represent a few of all possible combinations. The

heterogeneity between different cell types, cell states, or due to the response to the

environmental factors remains the biggest challenge so far for all TR prediction method.

In summary, BIT provides valuable insights into the regulation of gene transcription. With the

growing popularity of chromatin accessibility profiling techniques, especially the bulk and single-

cell ATAC-seq, BIT fits the emergency need for tools to properly handle omics data and provides

more rigorous identification from a Bayesian perspective by using the accumulated TR ChIP-

seq data that represent the most accurate in-vivo genome-wide binding patterns.

Conclusion

In high-throughput data analysis, TR binding profiles can provide critical information for

identifying functional TRs from the user-provided epigenomic regions. However, currently

available methods either primarily use genes as input or heavily rely on motif enrichment

analysis to identify TRs from epigenomic regions, which suffer from various limitations. These

considerations motivate us to propose BIT, a Bayesian hierarchical model to identify TRs from

user-provided epigenomic regions using accumulated TR ChIP-seq data. We have proved the

feasibility and effectiveness of BIT in simulation and multiple application studies. Our results

demonstrate that BIT is a powerful tool for identifying TRs and provides a novel Bayesian

perspective in high-throughput data analysis.

Methods

Data processing

In the TR perturbation derived DARs analysis, raw ATAC-seq sequence reads were first cleaned

for adaptors using NGmerge (v.0.3). Read quality was checked by FastQC (v.0.11.9). Paired-

end reads were mapped to the human genome (hg38) using bowtie2 (v.2.5.2) applying

parameters "bowtie2 --very-sensitive -X 2000". SAMtools (v.1.16.1) was used for the following

steps (i) convert SAM files to BAM files, (ii) remove unmapped reads and duplicates, (iii)

generate index files for BAM files. Peaks were called using MACS2 (v.2.2.9.1). BAM files, index

files, and peak files were used for DAR analysis using DiffBind (v.3.10.1). Reference TR ChIP-

seq datasets were retrieved from GTRD, datasets with too low number peaks (<100) and

individual peaks with fold enrichment <5 were removed. Cancer type specific accessible regions

were retrieved from TCGA. 10K PBMCs and primary liver cancer scATAC-seq fragment files

were retrieved from the GEO archive. The cell type marker accessible regions were generated

from each dataset using SnapATAC2. When applicable, the cell type annotations were also

retrieved and applied. Codes for the detailed data processing steps are available online.

Region mapping

BIT only requires the user-provided epigenomic regions as input, while TR ChIP-seq peaks

serve as the reference. All binding sites (peaks) or epigenomic regions from a single dataset are

mapped to nonoverlapping, pre-defined regions (or bins) of 1000 bps over the entire genome.

Each bin is assigned either "0" or "1" according to whether the summit of any of the peaks falls

into the bin (in case that the summit information of a peak is missing, the middle point is used

instead). Such mapping is also done to the user-provided epigenomic regions. Thus, all

datasets (input and references) are transformed into binary vectors of the same length. We then

compare the binary vector from the input with that from each of the TR ChIP-seq datasets,

where we define three conditions for any given bin: (i) "matching" if (1,1); (2) "mismatching" if

(1,0) or (0,1); and (3) "non-informative" if (0,0). In all input vs. reference comparisons, the first

two cases ("informative" bins) are much fewer than the third case ("non-informative" bins) and

we drop the third case to mitigate the sparsity while not losing much useful information.

BIT model

BIT is the first model-based method that formally distinguishes TRs with multiple datasets from

those with only a single dataset in the reference database, to account for both within-TR and

between-TR heterogeneity and allow for information borrowing across different TRs and

datasets via a hierarchical setup. We index TRs with multiple reference datasets by i, $i =$

$1,2,\dots,\mathcal{M}$, each with $j = 1,2,\dots,J_i$ datasets. TRs with a single reference dataset are indexed by

$i' = 1,2,\dots,\mathcal{M}^c$, all with $j \equiv 1$ dataset. Let x_{ij} ($x_{i'1}$) be the number of "matching" bins out of n_{ij}

($n_{i'1}$) "informative" bins by comparing the vectors between the user input and the jth reference

dataset of the ith TR (or the only dataset of the i' th TR). The probability of a bin being

"matching" given it is "informative" is denoted by p_{ij} ($p_{i'1}$) such that $x_{ij} \sim Binom(n_{ij}, p_{ij})$ and

$x_{i'1} \sim Binom(n_{i'1}, p_{i'1})$. Let $\theta_{ij} \equiv logit(p_{ij})$ $(\theta_{i'1} \equiv logit(p_{i'1}))$ be the logit-transformed

p_{ij} ($p_{i'1}$), which can be interpreted as the importance score at the dataset level. We further

model θ_{ij} ($\theta_{i'1}$) by $\theta_{ij} \sim N(\theta_i, \sigma_i^2)$, $\theta_{i'1} \sim N(\theta_{i'}, \sigma_0^2)$ and all θ_i, $\theta_{i'} \sim N(\mu, \tau^2)$, where μ and τ^2

represent the global mean and variability of TR-level importance scores. In this way, for each TR

with multiple datasets, we model its importance scores by a normal distribution with distinctive

mean θ_i and variance σ_i^2, reflecting its overall importance and within-TR heterogeneity,

respectively; all TRs with only one dataset share a common variance σ_0^2 for information pooling.

Unlike many existing algorithms[17,18,21], BIT inherently integrates information from reference

datasets of different TRs to assign one final rank of each TR based on the TR-level importance

score θ_i ($\theta_{i'}$) rather than conducting thousands of separate *ad-hoc* statistical tests.

$$x_{ij} \sim Binom(n_{ij}, p_{ij}),\ x_{i'1} \sim Binom(n_{i'1}, p_{i'1})$$

$$\theta_{ij} = logit(p_{ij}), \ \theta_{i'1} = logit(p_{i'1})$$

$$\theta_{ij} \sim N(\theta_i, \sigma_i^2), \ \theta_{i'1} \sim N(\theta_{i'}, \sigma_0^2)$$

$$\theta_i, \ \theta_{i'} \sim N(\mu, \tau^2)$$

The (hyper)parameters of our BIT model are collectively denoted by $\Theta = \{\mu, \tau^2, \sigma_0^2, \{\theta_i\}_{i=1}^{M},$

$\{\theta_{i'}\}_{i'=1}^{Mc}, \{\sigma_i^2\}_{i=1}^{M}, \{\theta_{ij}\}_{i=1,j=1}^{M, J_i}, \{\theta_{i'1}\}_{i'=1}^{Mc} \}$ and observed data are $X = \left\{ \{x_{ij}\}_{i=1,j=1}^{M, J_i}, \{x_{i'1}\}_{i'=1}^{Mc} \right\}$.

Then the joint distribution of (X, Θ) can be written as

504
$$
\begin{aligned}
p(X, \Theta) \ &= \left(\prod_{i=1}^{M} \prod_{j=1}^{J_i} p\left(x_{ij}|\theta_{ij}, n_{ij}\right) p(\theta_{ij}|\theta_i, \sigma_i^2) p(\theta_i|\mu, \tau^2) \right) \\
&\times \left(p(\sigma_0^2) \prod_{i'=1}^{Mc} p\left(x_{i'1}|\theta_{i'1}, n_{i'1}\right) p(\theta_{i'1}|\theta_{i'}, \sigma_0^2) \right) \\
&\times \left(\prod_{i=1}^{M} p\left(\theta_i|\mu, \tau^2\right) \prod_{i'=1}^{Mc} p\left(\theta_{i'}|\mu, \tau^2\right)) p(\sigma_i^2) \right) p(\mu, \tau^2)
\end{aligned}
$$

505 Where:

506
$$
p(x_{ij}|\theta_{ij}, n_{ij}) = \binom{x_{ij}}{n_{ij}} \frac{e^{x_{ij}\theta_{ij}}}{(1 + e^{\theta_{ij}})^{n_{ij}}}
$$

507
$$
p(x_{i'1}|\theta_{i'1}, n_{i'1}) = \binom{x_{i'1}}{n_{i'1}} \frac{e^{x_{i'1}\theta_{i'1}}}{(1 + e^{\theta_{i'1}})^{n_{i'1}}}
$$

508 logit transformed importance $\theta_{ij} \ (\theta_{i'1})$

509
$$
\theta_{ij} \quad \sim N\left(\theta_i, \sigma_i^2\right), \ \theta_{i'1} \sim N(\theta_{i'}, \sigma_0^2)
$$

510 And TR level score $\theta_i \ (\theta_{i'})$

511
$$
\theta_i, \ \theta_{i'} \sim N(\mu, \tau^2)
$$

Prior specification

The global location parameter μ and all variance parameters including τ^2, σ_0^2, and $\{\sigma_i^2\}_{i=1}^M$ are

assumed *a priori* independent. For μ, we consider the non-informative flat prior $\mu \sim$

$uniform(L_\mu, U_\mu)$, which should provide a sufficiently wide coverage for all plausible values of μ

suggested by data. For each variance parameter involved, we specify an inverse gamma prior

distribution $IG(a, b)$, where a and b are tiny positive values to make prior very vague and diffuse

(e.g., $a = b = 0.01$).

519
$$p(\mu) = \frac{1}{U_\mu - L_\mu} , L_\mu \le \mu \le U_\mu$$

520
$$p(\tau^2) = (\tau^2)^{-a-1} exp\left(-\frac{b}{\tau^2}\right)$$

521
$$p(\sigma_0^2) = (\sigma_0^2)^{-a_0-1} exp\left(-\frac{b_0}{\sigma_0^2}\right)$$

522
$$p(\sigma_i^2) = (\sigma_i^2)^{-a_i-1} exp\left(-\frac{b_i}{\sigma_i^2}\right)$$

Pólya-gamma data augmentation and Gibbs sampler

The BIT framework uses Gibbs sampler that is a specific Monte Carlo Markov chain algorithm to

generate posterior samples from complex joint probability distribution. However, to compute the

MCMC, the full conditionals should be obtained in advance. As the joint posterior distribution

can be written as $p(\Theta|X) \propto p(\Theta, X)$, the full conditional posterior distribution of each parameter

can be written as $p(\theta|X, \Theta \setminus \theta)$, where $\Theta \setminus \theta$ denote the remaining parameters after removing

the parameter θ from the parameter set Θ. For μ, τ^2, σ_0^2, and σ_i^2, these parameters full

conditional distributions are easily to be computed as

531
$$p(\mu|X, \Theta \setminus \mu) \propto N\left(\frac{\sum_{i=1}^M \theta_i + \sum_{i'=1}^{M^c} \theta_{i'}}{M + M^c}, \frac{\tau^2}{M + M^c}\right) \times \mathbf{1}\{L_\mu \le \mu \le U_\mu\}$$

532
$$p(\tau^2|X, \Theta \setminus \tau^2) \propto IG\left(a + \frac{M + M^c}{2}, b + \frac{\sum_{i=1}^M (\theta_i - \mu)^2 + \sum_{i'=1}^{M^c}(\theta_{i'} - \mu)^2}{2}\right)$$

533
$$p(\sigma_0^2|X, \Theta \setminus \sigma_0^2) \propto IG\left(a_0 + \frac{M^c}{2}, b_0 + \frac{(\theta_{i'1} - \theta_{i'})^2}{2}\right)$$

534
$$p(\sigma_i^2|X, \Theta \setminus \sigma_i^2) \propto IG\left(a_i + \frac{J_i}{2}, b_i + \frac{\sum_{j=1}^{J_i}(\theta_{ij} - \theta_i)^2}{2}\right)$$

535
$$p(\theta_i|X, \Theta \setminus \theta_i) \propto N\left(\frac{\mu\sigma_i^2 + \sum_{j=1}^{J_i} \theta_{ij}\tau^2}{\sigma_i^2 + J_i\tau^2}, \frac{1}{\frac{1}{\tau^2} + \frac{J_i}{\sigma_i^2}}\right)$$

536
$$p(\theta_{i'}|X, \Theta \setminus \theta_{i'}) \propto N\left(\frac{\mu\sigma_0^2 + \theta_{i'1}\tau^2}{\sigma_0^2 + \tau^2}, \frac{1}{\frac{1}{\sigma_0^2} + \frac{1}{\tau^2}}\right)$$

537   However, it is difficult to sample from the full conditional of $p(\theta_{ij}|X, \Theta \setminus \theta_{ij})$ and $p(\theta_{i'1}|X, \Theta \setminus \theta_{i'1})$

538   as these are intractable. Therefore, we instead implement a data augmentation strategy that is

539   based on Pólya-Gamma (PG) latent variables[62]. We further define auxiliary variables λ_{ij} and

540    $\lambda_{i'1}$, which follow the Pólya-Gamma distribution.

541
$$p(\lambda_{ij}|\theta_{ij}, X) \sim PG(n_{ij}, \theta_{ij})$$

542
$$p(\lambda_{i'1}|\theta_{i'1}, X) \sim PG(n_{i'1}, \theta_{i'1})$$

543   The full conditionals based on the defined auxiliary parameters can be easily written as the form

544   of known distribution.

545
$$p(\theta_{ij}|X, \Theta \setminus \theta_{ij}, \lambda_{ij}) \propto N(V_{ij}, m_{ij})$$

546   Where:

547
$$V_{ij} = \left(\lambda_{ij} + \frac{1}{\sigma_i^2}\right)^{-1}$$

548
$$m_{ij} = V_{ij}\left(\kappa_{ij} + \frac{\theta_i}{\sigma_i^2}\right)$$

$$\kappa_{ij} = x_{ij} - \frac{n_{ij}}{2}$$

550 Similarly, we can derive the full conditional distribution of $\theta_{i'1}$. Given that all posterior

551 conditionals are now known distributions, we can design an efficient Gibbs sampler in which all

552 quantities are drawn sequentially and generated readily without using any built-in sampling

553 algorithms (such as Metropolis-Hastings or Acceptance/Rejection sampling) that can greatly

554 slow down the computation.

Bayesian inference and TR rankings

Inference about TR-level importance parameters can be made by marginalizing over posterior

samples generated from the Gibbs sampler. Let $\theta_i^{(t)}$ and $\theta_{i'}^{(t)}$ be the posterior draw of θ_i and $\theta_{i'}$

in the tth iteration of MCMC after the burn-in period, where $t = 1, \dots, T$. Then θ_i and $\theta_{i'}$ are

estimated by $\tilde{\theta}_i = \sum_{t=1}^{T} \theta_i^{(t)} / T$ and $\tilde{\theta}_{i'} = \sum_{t=1}^{T} \theta_{i'}^{(t)} / T$. Then, these logit-transformed probabilities

$\{\tilde{\theta}_i\}_{i=1}^{M}$ and $\{\tilde{\theta}_{i'}\}_{i'=1}^{M_c}$ can be used to produce a final ranked TR list or to be further transformed

back to the 0-1 scale. To gauge prediction uncertainty, credible intervals of any parameter of

interest can be easily obtained from percentiles of draws or as highest posterior density

intervals.

Simulation naïve baseline method

565 To compare the performance of BIT in the estimation of parameters, we used naïve method as

566 baseline.

567 Where hyperparameter μ is:

568
$$\hat{\mu} = \frac{\sum_{i=1}^{M} \sum_{j=1}^{J_i} logit\left(\frac{x_{ij}}{n_{ij}}\right) + \sum_{i'=1}^{M_c} logit\left(\frac{x_{i'1}}{n_{i'1}}\right)}{\sum_{i=1}^{M} J_i + M_c}$$

569 Hyperparameter τ^2 is:

$$\hat{\tau}^2 = \frac{\sum_{i=1}^{M} \sum_{j=1}^{J_i} \left(logit\left(\frac{x_{ij}}{n_{ij}}\right) - \hat{\mu} \right)^2 + \sum_{i'=1}^{M^c} \left(logit\left(\frac{x_{i'1}}{n_{i'1}}\right) - \hat{\mu} \right)^2}{\sum_{i=1}^{M} J_i + M^c - 1}$$

571   Parameter σ_0^2 is:

$$\sigma_0^2 = \frac{1}{M^c - 1} \sum_{i'=1}^{M^c} \left(logit\left(\frac{x_{i'1}}{n_{i'1}}\right) - \hat{\mu} \right)^2 - \hat{\tau}^2$$

573   And θ_i and $\theta_{i'}$ are:

$$\hat{\theta}_i = \frac{\sum_{j=1}^{J_i} logit\left(\frac{x_{ij}}{n_{ij}}\right)}{J_i}, \ \hat{\theta}_{i'} = logit\left(\frac{x_{i'1}}{n_{i'1}}\right)$$

Though the probability is extremely low, in the case if any simulated data point has $\frac{x_{ij}}{n_{ij}} = 0$ or

$\frac{x_{i'1}}{n_{i'1}} = 0$, to allow the estimation to be done properly for naïve method, we add a tiny positive

value to these extreme cases.

Cross-validation with CRISPR-Cas9 screening data

Data of TR knock out effects on viability of cell lines were retrieved from DepMap. We filtered

out TRs that are not included in the BIT database or the DepMap data. Cell lines under the

same lineage are grouped to find TRs with a Chronos score lower than -0.4, which are classified

as high dependency TRs. 2-by-2 contingency tables were created based on whether top ranked

TRs identified by each method are also high dependency TRs. Finally, one-sided Fisher exact

tests were applied to each table to compare the capability of methods to identify TRs that are

also high dependency TRs in each cancer type.

Data Availability

TR perturbation experiments data were retrieved from GEO (GSE153237[36], GSE173416[37], and

GSE114102[38]). scATAC-seq data are retrieved from 10XGenomics and GEOXX, The reference

ChIP-seq datasets were retrieved from GTRD, and transformed binary vectors are available on

SMU Box. Cancer-type specific accessible regions were retrieved from TCGA. CRISPR-Cas9

knockout screening data were retrieved from DepMap. BIT software is available on GitHub, we

also have a reference manual available on readthedocs.

Funding

This work was supported by the following funding: the Rally Foundation, Children's Cancer Fund (Dallas), the Cancer Prevention and Research Institute of Texas (RP180319, RP200103, RP220032, RP170152 and RP180805), and the National Institutes of Health funds (R21CA259771, P30CA142543, HG011996, and R01HL144969) (to L.X.)

(R01CA258584)(to X.W.)

Zeyu Lu is a PhD candidate in the Department of Statistics and Data Science at Southern Methodist University, who focuses on statistics and epigenomics studies.

Xinlei Wang is Jenkins-Garrett Professor of Statistics and Data Science in the Department of Mathematics and Director of Division of Data Science for Research in College of Science, University of Texas at Arlington, who focuses on development of statistical methods and computational tools for biomedical data.

Lin Xu is an Assistant Professor in the Peter O'Donnell Jr. School of Public Health at University of Texas Southwestern Medical Center, who focuses on epigenomics studies.

Reference

1   Casamassimi, A. & Ciccodicola, A. Transcriptional Regulation: Molecules, Involved
Mechanisms, and Misregulation. *Int J Mol Sci* **20** (2019).
https://doi.org/10.3390/ijms20061281
2   Lambert, S. A. *et al.* The Human Transcription Factors. *Cell* **172**, 650-665 (2018).
https://doi.org/10.1016/j.cell.2018.01.029
3   Andersson, R. & Sandelin, A. Determinants of enhancer and promoter activities of
regulatory elements. *Nat Rev Genet* **21**, 71-87 (2020).
https://doi.org/10.1038/s41576-019-0173-8
4   Mullen, A. C. *et al.* Master transcription factors determine cell-type-specific
responses to TGF-beta signaling. *Cell* **147**, 565-576 (2011).
https://doi.org/10.1016/j.cell.2011.08.050
5   Whyte, W. A. *et al.* Master transcription factors and mediator establish super-
enhancers at key cell identity genes. *Cell* **153**, 307-319 (2013).
https://doi.org/10.1016/j.cell.2013.03.035
6   Hwang, J. Y. & Zukin, R. S. REST, a master transcriptional regulator in
neurodegenerative disease. *Curr Opin Neurobiol* **48**, 193-200 (2018).
https://doi.org/10.1016/j.conb.2017.12.008
7   Bradner, J. E., Hnisz, D. & Young, R. A. Transcriptional Addiction in Cancer. *Cell* **168**,
629-643 (2017). https://doi.org/10.1016/j.cell.2016.12.013
8   Chen, Y., Xu, L., Lin, R. Y., Müschen, M. & Koeffler, H. P. Core transcriptional
regulatory circuitries in cancer. *Oncogene* **39**, 6633-6646 (2020).
https://doi.org/10.1038/s41388-020-01459-w
9   Pei, H., Guo, W., Peng, Y., Xiong, H. & Chen, Y. Targeting key proteins involved in
transcriptional regulation for cancer therapy: Current strategies and future
prospective. *Med Res Rev* **42**, 1607-1660 (2022). https://doi.org/10.1002/med.21886
10   Rottner, A. K. *et al.* A genome-wide CRISPR screen identifies CALCOCO2 as a
regulator of beta cell function influencing type 2 diabetes risk. *Nat Genet* **55**, 54-65
(2023). https://doi.org/10.1038/s41588-022-01261-2
11   Balakrishnan, S., Dhavamani, S. & Prahalathan, C. beta-Cell specific transcription
factors in the context of diabetes mellitus and beta-cell regeneration. *Mech Dev*
163, 103634 (2020). https://doi.org/10.1016/j.mod.2020.103634
12   Hong, J. H. & Zhang, H. G. Transcription Factors Involved in the Development and
Prognosis of Cardiac Remodeling. *Front Pharmacol* **13**, 828549 (2022).
https://doi.org/10.3389/fphar.2022.828549
13   Bauer, A. J. & Martin, K. A. Coordinating Regulation of Gene Expression in
Cardiovascular Disease: Interactions between Chromatin Modifiers and
Transcription Factors. *Front Cardiovasc Med* **4**, 19 (2017).
https://doi.org/10.3389/fcvm.2017.00019
14   Bhagwat, A. S. & Vakoc, C. R. Targeting Transcription Factors in Cancer. *Trends*
Cancer **1**, 53-65 (2015). https://doi.org/10.1016/j.trecan.2015.07.001

15   Bushweller, J. H. Targeting transcription factors in cancer - from undruggable to
reality. *Nat Rev Cancer* **19**, 611-624 (2019). https://doi.org/10.1038/s41568-019-
0196-7
16   Darnell, J. E., Jr. Transcription factors as targets for cancer therapy. *Nat Rev Cancer*
2, 740-749 (2002). https://doi.org/10.1038/nrc906
17   Qin, Q. *et al.* Lisa: inferring transcriptional regulators through integrative modeling of
public chromatin accessibility and ChIP-seq data. *Genome Biol* **21**, 32 (2020).
https://doi.org/10.1186/s13059-020-1934-6
18   Wang, Z. *et al.* BART: a transcription factor prediction tool with query gene sets or
epigenomic profiles. *Bioinformatics* **34**, 2867-2869 (2018).
https://doi.org/10.1093/bioinformatics/bty194
19   Keenan, A. B. *et al.* ChEA3: transcription factor enrichment analysis by orthogonal
omics integration. *Nucleic Acids Res* **47**, W212-W224 (2019).
https://doi.org/10.1093/nar/gkz446
20   Puente-Santamaria, L., Wasserman, W. W. & Del Peso, L. TFEA.ChIP: a tool kit for
transcription factor binding site enrichment analysis capitalizing on ChIP-seq
datasets. *Bioinformatics* **35**, 5339-5340 (2019).
https://doi.org/10.1093/bioinformatics/btz573
21   Roopra, A. MAGIC: A tool for predicting transcription factors and cofactors driving
gene sets using ENCODE data. *PLoS Comput Biol* **16**, e1007800 (2020).
https://doi.org/10.1371/journal.pcbi.1007800
22   Machanick, P. & Bailey, T. L. MEME-ChIP: motif analysis of large DNA datasets.
Bioinformatics **27**, 1696-1697 (2011). https://doi.org/10.1093/bioinformatics/btr189
23   Heinz, S. *et al.* Simple combinations of lineage-determining transcription factors
prime cis-regulatory elements required for macrophage and B cell identities. *Mol*
Cell **38**, 576-589 (2010). https://doi.org/10.1016/j.molcel.2010.05.004
24   Tanigawa, Y., Dyer, E. S. & Bejerano, G. WhichTF is functionally important in your
open chromatin data? *PLoS Comput Biol* **18**, e1010378 (2022).
https://doi.org/10.1371/journal.pcbi.1010378
25   Jolma, A. *et al.* DNA-binding specificities of human transcription factors. *Cell* **152**,
327-339 (2013). https://doi.org/10.1016/j.cell.2012.12.009
26   Slattery, M. *et al.* Absence of a simple code: how transcription factors read the
genome. *Trends Biochem Sci* **39**, 381-399 (2014).
https://doi.org/10.1016/j.tibs.2014.07.002
27   Aibar, S. *et al.* SCENIC: single-cell regulatory network inference and clustering. *Nat*
Methods **14**, 1083-1086 (2017). https://doi.org/10.1038/nmeth.4463
28   Oki, S. *et al.* ChIP-Atlas: a data-mining suite powered by full integration of public
ChIP-seq data. *EMBO Rep* **19** (2018). https://doi.org/10.15252/embr.201846255
29   Lu, Z., Xiao, X., Zheng, Q., Wang, X. & Xu, L. Assessing NGS-based computational
methods for predicting transcriptional regulators with query gene sets. *bioRxiv*,
2024.2002.2001.578316 (2024). https://doi.org/10.1101/2024.02.01.578316
30   Tang, F. *et al.* Chromatin profiles classify castration-resistant prostate cancers
suggesting therapeutic targets. *Science (New York, N.Y.)* **376**, eabe1505 (2022).
https://doi.org/10.1126/science.abe1505

31 McLean, C. Y. *et al*. GREAT improves functional interpretation of cis-regulatory
regions. *Nat Biotechnol* **28**, 495-501 (2010). https://doi.org/10.1038/nbt.1630
32 Creyghton, M. P. *et al*. Histone H3K27ac separates active from poised enhancers
and predicts developmental state. *Proceedings of the National Academy of*
Sciences of the United States of America **107**, 21931-21936 (2010).
https://doi.org/10.1073/pnas.1016071107
33 Yan, F., Powell, D. R., Curtis, D. J. & Wong, N. C. From reads to insight: a hitchhiker's
guide to ATAC-seq data analysis. *Genome Biology* **21**, 22 (2020).
https://doi.org/10.1186/s13059-020-1929-3
34 Wang, S. *et al*. Modeling cis-regulation with a compendium of genome-wide histone
H3K27ac profiles. *Genome Research* **26**, 1417-1429 (2016).
https://doi.org/10.1101/gr.201574.115
35 Kharchenko, P. V., Tolstorukov, M. Y. & Park, P. J. Design and analysis of ChIP-seq
experiments for DNA-binding proteins. *Nature Biotechnology* **26**, 1351-1359 (2008).
https://doi.org/10.1038/nbt.1508
36 Xu, B. *et al*. Acute depletion of CTCF rewires genome-wide chromatin accessibility.
Genome Biol **22**, 244 (2021). https://doi.org/10.1186/s13059-021-02466-0
37 Deng, W. *et al*. Reactivation of developmentally silenced globin genes by forced
chromatin looping. *Cell* **158**, 849-860 (2014).
https://doi.org/10.1016/j.cell.2014.05.050
38 Lee, K. *et al*. FOXA2 Is Required for Enhancer Priming during Pancreatic
Differentiation. *Cell Rep* **28**, 382-393.e387 (2019).
https://doi.org/10.1016/j.celrep.2019.06.034
39 Gruber, S., Haering, C. H. & Nasmyth, K. Chromosomal cohesin forms a ring. *Cell*
112, 765-777 (2003). https://doi.org/10.1016/s0092-8674(03)00162-4
40 Haering, C. H., Löwe, J., Hochwagen, A. & Nasmyth, K. Molecular architecture of
SMC proteins and the yeast cohesin complex. *Mol Cell* **9**, 773-788 (2002).
https://doi.org/10.1016/s1097-2765(02)00515-4
41 Kadauke, S. & Blobel, G. A. Chromatin loops in gene regulation. *Biochim Biophys*
Acta **1789**, 17-25 (2009). https://doi.org/10.1016/j.bbagrm.2008.07.002
42 Hansen, A. S., Cattoglio, C., Darzacq, X. & Tjian, R. Recent evidence that TADs and
chromatin loops are dynamic structures. *Nucleus* **9**, 20-32 (2018).
https://doi.org/10.1080/19491034.2017.1389365
43 Nora, E. P. *et al*. Targeted Degradation of CTCF Decouples Local Insulation of
Chromosome Domains from Genomic Compartmentalization. *Cell* **169**, 930-
944.e922 (2017). https://doi.org/10.1016/j.cell.2017.05.004
44 Rao, S. S. P. *et al*. Cohesin Loss Eliminates All Loop Domains. *Cell* **171**, 305-
320.e324 (2017). https://doi.org/10.1016/j.cell.2017.09.026
45 Leonard, M., Brice, M., Engel, J. D. & Papayannopoulou, T. Dynamics of GATA
transcription factor expression during erythroid differentiation. *Blood* **82**, 1071-1079
(1993).
46 Cheng, Y. *et al*. Erythroid GATA1 function revealed by genome-wide analysis of
transcription factor occupancy, histone modifications, and mRNA expression.
Genome Res **19**, 2172-2184 (2009). https://doi.org/10.1101/gr.098921.109

47 Maeda, T. *et al.* LRF is an essential downstream target of GATA1 in erythroid
development and regulates BIM-dependent apoptosis. *Dev Cell* **17**, 527-540 (2009).
https://doi.org/10.1016/j.devcel.2009.09.005
48 Siatecka, M. & Bieker, J. J. The multifunctional role of EKLF/KLF1 during
erythropoiesis. *Blood* **118**, 2044-2054 (2011). https://doi.org/10.1182/blood-2011-
03-331371
49 Wang, H. *et al.* Pdx1 level defines pancreatic gene expression pattern and cell
lineage differentiation. *J Biol Chem* **276**, 25279-25286 (2001).
https://doi.org/10.1074/jbc.M101233200
50 Watt, A. J., Zhao, R., Li, J. & Duncan, S. A. Development of the mammalian liver and
ventral pancreas is dependent on GATA4. *BMC Dev Biol* **7**, 37 (2007).
https://doi.org/10.1186/1471-213x-7-37
51 Fujimoto, K. & Polonsky, K. S. Pdx1 and other factors that regulate pancreatic beta-
cell survival. *Diabetes Obes Metab* **11 Suppl 4**, 30-37 (2009).
https://doi.org/10.1111/j.1463-1326.2009.01121.x
52 Allen, H. L. *et al.* GATA6 haploinsufficiency causes pancreatic agenesis in humans.
Nat Genet **44**, 20-22 (2011). https://doi.org/10.1038/ng.1035
53 Iwafuchi-Doi, M. & Zaret, K. S. Pioneer transcription factors in cell reprogramming.
Genes Dev **28**, 2679-2692 (2014). https://doi.org/10.1101/gad.253443.114
54 Norton, L. J. *et al.* KLF1 directly activates expression of the novel fetal globin
repressor ZBTB7A/LRF in erythroid cells. *Blood Adv* **1**, 685-692 (2017).
https://doi.org/10.1182/bloodadvances.2016002303
55 Meyers, R. M. *et al.* Computational correction of copy number effect improves
specificity of CRISPR-Cas9 essentiality screens in cancer cells. *Nat Genet* **49**, 1779-
1784 (2017). https://doi.org/10.1038/ng.3984
56 Watson, P. A., Arora, V. K. & Sawyers, C. L. Emerging mechanisms of resistance to
androgen receptor inhibitors in prostate cancer. *Nat Rev Cancer* **15**, 701-711 (2015).
https://doi.org/10.1038/nrc4016
57 Patel, H. K. & Bihani, T. Selective estrogen receptor modulators (SERMs) and
selective estrogen receptor degraders (SERDs) in cancer treatment. *Pharmacol Ther*
186, 1-24 (2018). https://doi.org/10.1016/j.pharmthera.2017.12.012
58 Anzick, S. L. *et al.* AIB1, a steroid receptor coactivator amplified in breast and
ovarian cancer. *Science* **277**, 965-968 (1997).
https://doi.org/10.1126/science.277.5328.965
59 Kim, M. R., Wu, M. J., Zhang, Y., Yang, J. Y. & Chang, C. J. TET2 directs mammary
luminal cell differentiation and endocrine response. *Nat Commun* **11**, 4642 (2020).
https://doi.org/10.1038/s41467-020-18129-w
60 Durbin, A. D. *et al.* Selective gene dependencies in MYCN-amplified neuroblastoma
include the core transcriptional regulatory circuitry. *Nat Genet* **50**, 1240-1246
(2018). https://doi.org/10.1038/s41588-018-0191-z
61 Gryder, B. E. *et al.* Histone hyperacetylation disrupts core gene regulatory
architecture in rhabdomyosarcoma. *Nat Genet* **51**, 1714-1722 (2019).
https://doi.org/10.1038/s41588-019-0534-4

62 Polson, N. G., Scott, J. G. & Windle, J. Bayesian Inference for Logistic Models Using
Pólya–Gamma Latent Variables. *Journal of the American Statistical Association* **108**,
1339-1349 (2013). https://doi.org/10.1080/01621459.2013.829001

784