RESPAN: A Deep Learning Pipeline for Accurate and Automated Restoration, Segmentation, and Quantification of Dendritic Spines

Sergio B. Garcia,[1,2] Alexa P. Schlotter[2], Daniela Pereira[4], Aleksandra J. Recupero[2,3], Franck Polleux[2,3], Luke A. Hammond[5,6] *

[1]Department of Biological Sciences, Columbia University, New York, NY, USA
[2]Mortimer B. Zuckerman Mind Brain Behavior Institute, Columbia University, New York, NY, USA
[3]Department of Neuroscience, Columbia University, New York, NY, USA
[4]Champalimaud Neuroscience Programme
[5]Department of Neurology, The Ohio State University, Wexner Medical School, Columbus, Ohio, USA
[6]Lead contact
*Correspondence: Luke.Hammond@osumc.edu

MOTIVATION

Accurate and unbiased reconstructions of neuronal morphology and quantification of dendritic spines are widely used in neuroscience but remain a significant challenge for efficient large-scale analysis. Current methods rely heavily on parameter optimization between images and manual annotation, introducing bias and creating bottlenecks that limit large-scale studies. Additionally, existing automated tools often require complex workflows across multiple software platforms and lack integrated validation capabilities. We developed RESPAN to address these limitations by providing a comprehensive, automated pipeline that combines state-of-the-art deep learning approaches for image restoration, model training, image segmentation and analysis within one user-friendly graphic interface. This enables rapid, unbiased analysis of dendritic spine morphology across diverse imaging modalities while maintaining high accuracy and reproducibility.

SUMMARY

Quantification of dendritic spines is essential for studying synaptic connectivity, yet most current approaches require manual adjustments or the combination of multiple software tools for optimal results. Here, we present Restoration Enhanced SPine And Neuron Analysis (RESPAN), an open-source pipeline integrating state-of-the-art deep learning for image restoration, segmentation, and analysis in an easily deployable, user-friendly interface. Leveraging content-aware restoration to enhance signal, contrast, and isotropic resolution further enhances RESPAN's robust detection of spines, dendritic branches, and soma across a wide variety of samples, including challenging datasets such as those from live imaging and in vivo 2-photon microscopy with limited signal. Extensive validation against expert annotations and comparison with other software demonstrates RESPAN's superior accuracy and reproducibility across multiple imaging modalities. RESPAN offers significant improvements in usability over currently available approaches, streamlining and democratizing access to a combination of advanced capabilities through an accessible resource for the neuroscience community.

KEYWORDS

Deep learning, dendritic spines, neuronal morphology, image analysis, content-aware restoration, image segmentation, synaptic connectivity, automated analysis, resolution enhancement, graphical user interface.

INTRODUCTION

Dendritic morphology and synaptic input connectivity are among the cardinal features defining neuronal subtypes and their functional properties [1,2]. In the mammalian neocortex, pyramidal neurons (PNs)

receive the majority (>90%) of their excitatory synaptic inputs on dendritic spines – small protrusions first
described by Santiago Ramón y Cajal [3,4]. Analysis of dendritic spine density and distribution has been
used for decades as a critical anatomical proxy for assessing excitatory input across different PN
subtypes during development and in adult states, both in physiological and pathological contexts,
including neurodevelopmental disorders and neurodegeneration [5-7]. Furthermore, the size of spine heads
correlates linearly with postsynaptic AMPA receptor content, making it a key indicator of synaptic
maturation during development and synaptic strength in adults [8].

While recent deep learning (DL) approaches have improved the accuracy of dendritic spine mapping
capabilities [9-11], their utility remains constrained by limited functionality and analysis readouts. Existing
methods like Vaa3D, SpineTool, and Imaris [1,12-16], Imaris (RRID:SCR_007370)) lack robustness and
scalability across datasets and are highly sensitive to changes in signal and image quality. Consequently,
full automation is rarely achieved, as each image often requires extensive manual intervention for
parameter optimization and post-processing corrections. This reliance on manual adjustments limits
efficiency and introduces human error and bias. While these tools can be combined with DL image
restoration and segmentation tools, doing so requires significant technical expertise and creates complex,
multi-step workflows that limit throughput and broader adoption.

In recent decades, two key developments have made transformative advances in dendritic spine imaging.
First, the introduction of bright fluorescent proteins combined with improved expression methods,
including in utero electroporation (IUE), viral delivery, and transgenic mouse models, has enabled sparse,
cell-type specific labeling [17-19]. Second, improvements in single and multi-photon confocal microscopy
have dramatically enhanced spatial and temporal resolution for both in vitro and in vivo imaging [20,21].
However, accurate quantification of dendritic morphology, spine density, 3D distribution, and spine head
size remains challenging due to reliance on labor-intensive manual or semi-automated reconstructions,
which introduce subjectivity and constitute significant bottlenecks for large-scale connectivity studies.

To address these challenges, we developed Restoration Enhanced SPine And Neuron Analysis
(RESPAN), an integrated solution for automated neuron and dendritic spine analysis. RESPAN uniquely
combines state-of-the-art deep learning approaches for content-aware image restoration, enhanced axial
resolution, and robust 3D segmentation within a single, user-friendly interface. The pipeline improves
signal-to-noise, contrast, and spatial resolution before performing accurate detection and segmentation
of spine heads, spine necks, dendritic branches, and soma. Unlike existing tools, RESPAN operates
through an intuitive graphical user interface (GUI), eliminating coding requirements while enabling
analysis, model training in multiple environments, and validation. Additionally, it generates
comprehensive readouts, including visual and tabulated data detailing dendritic spine morphology, signal
intensity, spatial metrics as well as individual spine tracking for temporally longitudinal imaging. We
demonstrate RESPAN's high accuracy and robustness across multiple imaging modalities, representing
a significant advancement in making advanced automated dendritic spine analysis accessible to the
research community.

A   RESPAN Schematic Workflow

 Figure 1. Overview of the RESPAN Workflow for Dendritic Spine Analysis
(A) Schematic representation of the RESPAN workflow, beginning with the input of 2D/3D .tif image files and progressing through multiple stages including signal restoration, isotropic resolution restoration, deep learning image segmentation, and generation of quantitative outputs. RESPAN accommodates images from a variety of microscopy techniques including two-photon, confocal, and super-resolution microscopy. (B) Upper panels: Example of a raw fluorescence image acquired with a spinning disk confocal microscope, shown as a maximum intensity projection (MIP). (C) Lower panels: 3D renderings of the same dataset. Raw fluorescence images highlight reduced signal and resolution related to image acquisition. Following content aware image restoration, improvements in signal and contrast, essential for accurate spine detect, are apparent. Subsequent processing of the restored image to improve axial resolution reduces anisotropy, thus improving the accuracy of morphological measurements. Finally deep-learning-based segmentation on the restored image provides precise labels for dendrites, spine heads, and necks. Lower panel: 3D view of the final segmentation output. Scale bars: 2 µm.

RESULTS

Development of RESPAN

The RESPAN pipeline (**Figure 1**) integrates GPU image processing and multiple deep-learning approaches to enable high-throughput fluorescent image segmentation, 3D reconstruction, and analysis of dendritic branches and dendritic spines. By integrating content-aware restoration and 3D convolutional neural network segmentation, RESPAN improves spine detection accuracy and sensitivity to morphological variations, particularly in challenging experimental conditions such as in vivo two-photon microscopy and rapid volumetric imaging of large tissue volumes. To ensure broad accessibility, RESPAN is provided both as Python code and as a standalone Windows application with an intuitive, unified GUI, allowing users to run batch analysis, train models, and perform analysis validation all within the same interface. Combining these features and multiple software environments within one interface substantially increases utility and reduces barriers for researchers without programming expertise.

Step 1. Deep Learning Image Restoration (optional)

Prior to segmentation, RESPAN provides the option to perform image restoration to enhance signal quality and contrast. This is a critical step for accurate spine detection in challenging imaging conditions where phototoxicity and temporal resolution requirements limit image quality. To achieve this, RESPAN employs a 3D content-aware CSBDeep model [22], trained using paired low and high signal-to-noise ratio (SNR) image volumes. We acquired these image sets in various samples to best reflect the diversity of imaging conditions and biological features, including soma, dendritic branches, and spines, thus maximizing the generalizability of the trained model. This approach enables high-quality restoration that preserves important biological features. For spinning disk confocal microscopy, we used a set of six paired image volumes with dimensions 1500 x 1500 x 130, with a pixel size of 65nm and a Z-step size of 150nm. Prior to training, the high SNR datasets were processed using a blind deconvolution. For 2-photon microscopy, we used 30 paired image volumes with average dimensions ~300 x 600 x 12, with a pixel size of 102nm and a Z-step size of 1µm. For both models, training was performed in Python using image augmentation (rotation, mirroring, and flipping) with patch sizes of 64 x 64 x 16 for 100 epochs as previously described parameters [22]. Representative examples of CARE restoration applied to low-SNR datasets can be seen in **Figure S1**, illustrating how this approach can improve fluorescence signal while preserving morphological details crucial for downstream spine segmentation.

Next, an optional axial restoration approach is used to reduce anisotropy and improve the accuracy of spine morphology measurements. This step is particularly important for conventional microscopy techniques like confocal microscopy, where the axial resolution can be 2-3 times worse than the lateral resolution, and even more critical for two-photon microscopy, where the disparity between lateral and axial resolution can be 4-5 times or greater due to the elongated point spread function. These resolution differences significantly impact the accuracy of 3D measurements. To address such challenges, RESPAN incorporates Self-Net. This two-stage unsupervised neural network approach leverages the natural anisotropy of microscopy data to improve axial resolution without requiring paired training data [23]. By using lateral images as rational targets, Self-Net can learn to enhance axial resolution while maintaining high fidelity to genuine biological features. This approach necessitates models trained on image data that match the same specific experiment and imaging conditions for accurate results. To facilitate model training using user-specific datasets, we have integrated this capability within the RESPAN GUI using code adapted from the original implementation of Self-Net [23].

Step 2. Image segmentation

For image segmentation, RESPAN employs a 3D full-resolution nnU-Net model, a self-configuring framework for biomedical image segmentation [24]. This approach automatically optimizes network architecture and training parameters based on input data properties, ensuring robust performance across

varied imaging conditions. To ensure broad utility, we created a diverse training dataset comprising 47
image volumes containing 2,489 expert-annotated spines from multiple imaging modalities commonly
used in the field: Zeiss Airyscan confocal microscopy (63x 1.4 NA oil PlanApochromat objective),
Yokogawa W1 spinning disk confocal microscopy (100x 1.35 NA silicone PlanApochromat objective),
and Bergamo two-photon microscopy (Olympus 25x 1.0 NA SCALEVIEW-A2 Plan objective).

In addition to modality-specific models, we pooled images from different modalities to create a
generalizable high-resolution model. This involved standardizing the training data by resampling the data
from the Airyscan confocal datasets to match the spinning disk confocal datasets with a voxel size of 65
x 65 x 150nm. We expanded datasets through augmentation to further enhance model performance,
including random rotations, flips, shot noise addition, and Gaussian blurring (**Figure S2**). This
augmentation strategy improved model performance when combined with the on-the-fly patch
augmentations generated by nnU-Net during training. Models were trained for 1000 epochs with an initial
learning rate of 0.01 following established parameters [24]. To train our best-performing Global Model 1,
we leveraged nnUNet v2.4 on a single H100 GPU instance from the Lambda GPU Cloud. We used the
Lambda Stack environment, which includes PyTorch and other dependencies for nnU-Net already
compiled, enabling straightforward deployment on x86_64 architectures. Notably, we observed a marked
improvement in segmentation accuracy after increasing the training batch size to 19 and the patch size
to [32, 256, 256]. We managed the Python environment and dependencies on Ubuntu 22.04 LTS, using
Lambda Stack's preconfigured packages to streamline setup and execution. All relevant installation
commands and hardware configuration details are provided in our public repository to promote
reproducibility on multiple hardware platforms.

Validation of our high-resolution global model against ground truth labels demonstrated excellent
performance, achieving Dice scores of 0.927 for spines, 0.986 for dendrites, and 0.991 for soma. For
cases where high-resolution resampling may be undesirable due to increased memory requirements, we
recommend using a modality-specific model matching the acquisition resolution. To maximize
accessibility, RESPAN automatically scales input data to match model requirements while providing
analysis output in the original resolution. This ensures that new users and novel datasets are likely to
yield interpretable results without requiring additional preprocessing before using RESPAN.

Step 3. RESPAN output and quantification of dendritic spine morphometry.
Following segmentation, RESPAN performs a comprehensive analysis of dendritic spines, providing both
numerical measurements (**Tables 1** and **2**) and multiple validation outputs (**Figure S3**). Measurements
include the volume of each spine, its centroid location, mean, minimum, and maximum intensity across
available channels, and the distance from both the dendrite shaft and geodesic distance from the soma.
Additional derived measurements, such as spine neck length and spine head width, are computed as
previously described [25]. Users can also specify constraints (e.g., minimum/maximum spine volume or
distance from dendrite) to filter out spurious detections.

Summary statistics include per-dendrite and per-image measurements of spine number, density, dendrite
length, and average spine measurements. RESPAN also supports the export of dendritic tracings for a
single neuron or dendrite per image in standard .swc format via Vaa3D's APP2 plugin [26], as well as 2D/3D
visualization arrays of all segmented spines for rapid validation. For transparency, intermediate data (e.g.,
labeled segmentations, skeletons, and distance maps) can be saved, allowing users to verify
segmentation accuracy and further refine segmentation models.

Importantly, RESPAN also includes a built-in validation module capable of automatically comparing
results to ground truth annotations. This is essential for auditing RESPAN's performance and validating
and reporting the accuracy of new restoration and segmentation models and parameters when publishing
with RESPAN. The metrics provided by the validation module are described in **Table 3.**

Figure 2. Evaluation of Multi-User Spine Detection Variability against RESPAN.
(A) Raw fluorescence image of a dendritic segment used as input for both manual annotation by multiple experts and automated processing by RESPAN. (B) Ground truth (GT) annotations determined by a consensus of experienced researchers; colors identify unique spine. (C) Composite image merging the raw fluorescence with the GT annotations overlaid. Spine colors reflect the probability of detection per spine from four independent users, with false positive detections labeled in red. (D) Composite image merging raw fluorescence with RESPAN spine detections, with colors reflecting every unique spine identified via a connected component analysis. (E) Inter-user correlation matrix showing the pairwise detection agreement among human annotators, with values ranging from 0 (no agreement) to 1 (perfect agreement). (F-G) Box plots comparing recall and precision between human annotators and RESPAN, showing that RESPAN consistently achieves higher recall and precision, reflecting improved sensitivity and fewer false positives relative to manual human annotation. Pairwise detection agreement among human annotators (values from 0 to 1) was quantified using Pearson correlation. Recall and precision were compared between human annotators and RESPAN using a paired two-tailed t-test (n = 5 pairs) at the 90% confidence interval. The resulting p-values were p = 0.0011 for recall (F) and p = 0.0147 for precision (G). p < 0.05 was considered significant.

Comprehensive validation of RESPAN performance

We employed a comprehensive validation strategy combining both pixel-level and object-level metrics to
evaluate RESPAN's performance, following established practices in deep learning-based microscopy
analysis [22,24]. For pixel-level assessment, we measured the Intersection over Union (IoU) ($|A \cap B|/|A \cup$
$B|$) and the Dice Coefficient (DC) ($2|A \cap B|/|A| + |B|$), where A represents RESPAN output pixels and B
represents ground truth pixels. These metrics proved particularly valuable for assessing the precise
delineation of spine and dendrite boundaries. For object-level validation, to assess for accurately counting
and characterizing individual spines, we employed an IoU threshold of 50% to quantify successfully
detected objects. The object-level comparison generated true positives (TP), false positives (FP), and
false negatives (FN), which we used to calculate two key metrics: the proportion of correctly detected
objects (Precision = TP/(TP+FP)) and the proportion of true objects that were correctly detected (Recall
= TP/(TP+FN)). Spine detection demonstrated excellent performance, achieving Precision and Recall
scores of 0.988 and 0.9, respectively. We achieved a final F1 score of 0.94.

Benchmarking RESPAN accuracy against human expert annotations

To assess the accuracy and reliability of RESPAN in detecting dendritic spines, we conducted a
comprehensive comparison with manual annotations from multiple users of varying expertise (**Figure 2**).
Using spinning disk confocal microscopy, we first acquired five independent fluorescence images of
dendritic segments (**Figure 2A**). Two experts with years of experience in imaging dendritic spines and
manual spine analysis carefully annotated these images to create a ground truth (GT) consensus dataset
(**Figure 2B-2C**). We then used these GT datasets to evaluate spine detection performance against (1)
four independent users with varying levels of expertise and (2) RESPAN output of the same images.

Each user analyzed the 3D raw fluorescence images in Fiji, marking putative spines at their perceived
center of mass using the multi-point tool. We compiled the ROIs placed by each user and superimposed
them onto the GT consensus mask. We used custom Python code to quantify the number of multi-point
ROIs detected for each GT spine across all users and images, generating a comprehensive spine
probability map (**Figure 2C**). This representation illustrates visually the significant variability in users'
ability to identify spine heads in a concordant manner.

To determine inter-user agreement, we generated a correlation matrix depicting pairwise detection
agreement among users, with values ranging from 0 (no agreement) to 1 (perfect agreement) (**Figure**
2E). The analysis revealed that inter-user agreement on spine detection remained consistently low,
suggesting potential statistical biases in manual annotation approaches. Further analysis examined the
probability distribution of spines being detected by varying numbers of users: no users (0), one user
(0.25), two users (0.50), three users (0.75), or all four users (1.00) (**Figure 2C**).

We then processed these same fluorescence images through the RESPAN pipeline for automated spine
segmentation. Using custom Python code, we then overlaid RESPAN's segmentation output onto our GT
consensus mask, employing an IoU criterion of 0.50 to determine correct spine detection. Comparing
RESPAN's performance to user detection probabilities revealed two key findings: First, RESPAN showed
a marked decrease in missed detections compared to human annotators, more accurately identifying
spines present in the GT consensus mask but missed by multiple users. Second, RESPAN demonstrated
improved detection of spines identified by only a subset of users, indicating superior sensitivity in
challenging cases.

These results demonstrate that RESPAN outperforms manual spine identification while alleviating inter-
individual variability and human observer bias in image annotation. Furthermore, the automated approach

provides comprehensive morphological readouts that are not feasible with human annotation, enabling a more thorough and unbiased analysis of dendritic spine populations.

Figure 3. Importance of Image Restoration in Spine Detection Accuracy Using RESPAN.
(A–C) Maximum-intensity-projection images of a dendritic segment acquired under low SNR conditions (A), following CARE restoration (B), and at high SNR (C). The right panels in each row show RESPAN's segmentation outputs, with color-coded spines denoting true positives (TP, green), false positives (FP, orange), or false negatives (FN, magenta). Insets highlight spines that are barely distinguishable in the low-SNR dataset but become visible after restoration. Scale bar, 2 µm. (D) Detection rates (TP, FP, and FN) for low-SNR versus restored datasets. Statistical comparisons were performed via Wilcoxon matched-pairs signed-rank tests with a two-stage step-up method (Benjamini, Krieger, Yekutieli) to control the false discovery rate. (E) Spine mask intersection-over-union (IoU=0.5) for low-SNR and restored images. Each point represents a matched spine, and the line/whiskers depict the median and 95% CI. *p* values were obtained using Wilcoxon matched-pairs signed-rank tests. (F) F1 scores plotted across increasing IoU thresholds (0.1–0.9). Comparisons between low-SNR (black) and restored (magenta) curves were performed using Wilcoxon matched-pairs signed-rank tests. (G) Cumulative distributions of Hausdorff distances for low-SNR (black) and restored (pink) spines, where lower values indicate closer alignment with the ground-truth spine shape. Data were analyzed by a Kolmogorov–Smirnov test, revealing significantly reduced Hausdorff distances in restored data. All *p* values are displayed as integers within the figure.

Demonstrating the importance of image restoration in spine detection

We next investigated how content-aware restoration could improve RESPAN's segmentation performance in low-SNR imaging scenarios commonly encountered in live or in vivo two-photon experiments (**Figure 3**). Although our Global Model 1 already provides reasonable segmentation on noisy

datasets, our results indicate that applying a CARE restoration model (Weigert et al., 2018) prior to
RESPAN segmentation further enhances spine detection under these challenging conditions. Under
these optimized training conditions, CARE substantially improved spine detection and segmentation
metrics when compared to low-SNR data (**Figure 3D–G**). Notably, in this study, we deliberately used
extremely low-SNR images to reflect a "worst-case" scenario. Even under these stringent conditions, the
detection of spines with IoU ≥ 0.5 rose from a median of 0.70 to 0.75, and the fraction of true-positive
spines increased from 0.76 to 0.82. Furthermore, the F1 score, which captures both recall and precision,
showed a marked increase in its cumulative distribution as the IoU threshold became more stringent,
reflecting the improved robustness of restored segmentations.

We additionally assessed the boundary accuracy using the Hausdorff distance (**Figure 3G**), which
measures how far the most extreme mismatched boundary point lies from ground-truth surfaces. After
CARE restoration, we observed significantly lower Hausdorff distances, indicating that even at the "worst-
matching" boundary points, predicted spines were closer to their ground-truth counterparts. This
improvement is crucial for downstream measurements of spine volume or surface area, where a single
poorly placed boundary point could skew morphological calculations.

Equally important, the ability to reliably restore low-SNR data has practical benefits for experimental
design. By capturing images at lower exposure times and reduced laser power, users can shorten their
time at the microscope while mitigating photobleaching and phototoxicity. In turn, the restored images
effectively regain high-SNR features, allowing users to move forward with accurate quantification. Thus,
our workflow enables high-fidelity segmentation of spines with minimal imaging burden, which is
particularly valuable for long time-lapse series or large-volume acquisitions, where preserving sample
health and reducing acquisition time are paramount.

Figure 4. Blind Genotype/Phenotype Validation Using RESPAN.
(A) *In vivo* 2-photon microscopy images of dendritic segments from wild-type (WT) and SRGAP2A +/- mutant neurons. Neurons
were sparsely labeled through *in utero* electroporation (IUE) using low amounts of Cre recombinase and a FLEX-mGreenLantern
construct, imaged through a cortical window to capture spine morphology. Scale bar, 2 μm. (B) Spine density comparison
between WT and SRGAP2A +/- mutants, showing a significant increase in spine density per unit length in mutants. Results
analyzed using the non-parametric Kolmogorov-Smirnov test (****p < 0.0001). (C) Spine length comparison between WT and
SRGAP2A +/- mutants, with mutants exhibiting significantly longer spines. Analysis performed using the non-parametric
Kolmogorov-Smirnov test (****p < 0.0001). (D) Comparison of spine volume between WT and SRGAP2A +/- mutants, revealing
no significant difference in spine volume, as determined by the non-parametric Kolmogorov-Smirnov test (ns, not significant).

Biological validation of RESPAN using established phenotypes affecting spine density and morphology

To validate RESPAN's performance, we performed a blinded genotype/phenotype analysis using *in vivo* 2-photon microscopy of dendritic segments from layer 2/3 pyramidal neurons (PNs) of WT and SRGAP2[+/-] knockout mice. We wanted to determine if RESPAN would detect differences in spine density and morphology previously well-established. Our lab demonstrated that adult layer 2/3 PNs from SRGAP2[+/-] mice exhibit unique spine phenotypes: increased spine density, increased spine neck length but no significant change in spine volume distribution compared to adult WT littermates [1,27-30]. For this analysis, neurons were sparsely labeled via *in utero* electroporation (IUE) with a plasmid FLEX-mGreenLantern together with low amount of another plasmid expressing Cre-recombinase [31]. Imaging of individual dendritic segments of layer 2/3 PNs was performed *using in* vivo 2-photon microscope through a cortical window to capture spine morphology in live tissue (**Figure 4A**).

RESPAN analysis successfully replicated these established phenotypes through an unbiased and blinded approach. Quantitative analysis revealed that SRGAP2[+/-] mutants displayed significantly higher spine density than WT neurons (**Figure 4B**, ****$p < 0.0001$), confirming the expected increase [1,27-30]. Similarly, dendritic spines had significantly longer necks in SRGAP2[+/-] mutants compared to WT neurons (**Figure 4C**, ****$p<0.0001$), matching our previous findings using manual analysis. Notably, there was no significant difference in spine volume between WT and SRGAP2[+/-] mice (**Figure 4D**, ns), consistent with our previous results using manual measurements. This validation demonstrates RESPAN's ability to accurately detect and quantify dendritic spine phenotypes in an unbiased manner, providing results that directly align with previously published evidence.

To further validate RESPAN's quantification accuracy against established metrics, we analyzed spine morphology distributions in a larger population of WT neurons. We compared our results to previously published ground truth data where all excitatory and inhibitory spines on a single neuron were mapped and analyzed, providing a ground truth for spine distribution (**Figure 5A** and **5B**; [1]). This analysis of 81,604 spines revealed characteristic distributions: spine length following a normal distribution and spine volume showing a Poisson distribution with predominant small spines and a smaller population of large spines. Using RESPAN, we analyzed 10,945 spines from WT neurons imaged by spinning disk confocal microscopy, applying spine volume thresholds of 0.035 µm³ and 2 µm³ (**Figure 5C** and **5D**). The results

336 demonstrated that RESPAN consistently replicates established biological distribution patterns for spine
337 length and volume.

Figure 5. Measured Spine Lengths and Volumes Match Known Distributions Validation.
338
(A) Histogram displaying the relative frequency distribution of spine lengths in wild-type (WT) neurons, based on a previous
analysis of 81,604 spines, serving as ground truth. The x-axis represents spine length (μm) and the y-axis shows the percentage
of spines within each length range. (B) Histogram showing the relative frequency distribution of spine volumes in WT neurons
from the ground truth dataset. The x-axis represents spine volume (μm³) and the y-axis shows the percentage of spines within
each volume range. The inset provides an example of a dendritic spine segment, color-coded to illustrate the spine head (yellow),
spine neck (brown), and dendrite (magenta). Scale bar, 250 nm. (C) Histogram of spine length distributions in WT neurons based
on RESPAN analysis of 10,945 spines. Results demonstrate a close match to ground truth distributions, highlighting RESPAN's
accuracy. (D) Histogram of spine volume distributions in WT neurons, showing a high degree of similarity to ground truth
distributions. RESPAN analysis was performed on spinning disk confocal microscopy datasets, using spine head volume
thresholds of 0.035 μm³ (minimum) and 2.0 μm³ (maximum). Output tables were merged to include all spines within these
thresholds, with no post-processing modifications to the data.

Spine tracking

Maintaining a consistent mapping of dendritic spines across multiple time points is a key challenge in
longitudinal spine analysis, particularly under *in vivo* conditions where brain tissue may shift or deform.
To address this, RESPAN provides a comprehensive spine tracking feature that integrates 3D volumetric
registration, segmentation, and label matching into a single workflow. As depicted in **Figure 6**, we applied
this method to two separate high-resolution two-photon Z-stacks obtained via a cranial window in a living
mouse. RESPAN begins by allowing the user to perform either rigid or non-rigid 3D motion correction on
each stack, ensuring that corresponding dendritic structures align accurately across sessions.

After registration, the pipeline proceeds with the segmentation of dendrites and spines. RESPAN then
tracks these segmented objects across time, maintaining unique spine IDs: spines persisting between
sessions share the same ID (and color), whereas newly formed and eliminated spines are labeled
distinctly (**Figure 6A-B**). This color-coded visualization enables rapid identification of formation,

elimination, and stabilization events (**Figure 6C-E**). Metrics evaluated during temporal analysis are documented in **Table 4**.

A unique strength of RESPAN is that it bundles this volumetric alignment and tracking capability in a user-friendly GUI, eliminating the need for specialized coding or computational expertise. This allows researchers to process folders containing multiple imaging sessions with their desired motion-correction method and readily verify alignment quality. To our knowledge, this marks the first GUI-based pipeline that combines 3D motion correction, restoration, segmentation, and longitudinal spine tracking in an integrated, semi-automated manner. By simplifying these previously complex workflows, RESPAN expands the practical feasibility of analyzing *in vivo* spine dynamics, enabling quantitative assessment of changes in spine number and morphology over time.

Figure 6. Application of RESPAN for the Analysis and Tracking of Spines *In Vivo*.
(A) Representative two-photon microscopy images showing dendritic spines at Day 0 (left) and Day 1 (center), with their merged visualization (right). Raw fluorescence data was registered between timepoints to enable precise spine tracking. (B) Segmentation output from RESPAN, demonstrating accurate identification osf individual spines across time. Different colors indicate distinct spine categories: formation (green), elimination (red), and stable spines (same color between both timepoints). (C) Quantification of spine dynamics showing the rates (%) of stable spines across two timepoints (T1 and T2) and the relative proportions of spine formation and elimination events. Data are presented as mean ± SEM. (D) Distribution of spine volumes for newly formed and eliminated spines. (E) Volume comparison between stable spines at both timepoints. Box plots show median, quartiles, and distribution of individual measurements.

Advantages and comparison with other methods

RESPAN addresses the critical challenges of reproducibility and efficiency in spine analysis, outperforming existing tools in both ease of use and accuracy (**Figure 7**). To benchmark its performance, we directly compared RESPAN's spine detection results with those of DeepD3, a deep learning-based spine detection tool, and Imaris, a widely used commercial solution for 3D image analysis. Both, DeepD3

and Imaris exhibit higher rates of false positives (orange) and false negatives (magenta) than RESPAN
(**Figure 7 A-D**).

Quantitative metrics reinforce these observations: RESPAN achieves superior recall (p = 0.0144 vs.
DeepD3; p = 0.0954 vs. Imaris), precision (p = 0.0143 vs. DeepD3; p = 0.0177 vs. Imaris), and F1 score
(p = 0.0047 vs. DeepD3; p = 0.0473 vs. Imaris) (**Figure 7E–H**). The percentage of true positive (TP)
spines detected by RESPAN also remains consistently higher than that of the other tools, reflecting more
robust performance across different dendritic morphologies. These findings highlight RESPAN's
strengths as a fully automated, broadly applicable approach that is less sensitive to image-to-image
variability and minimizes the need for manual calibration or correction.

Figure 7. Comparison of RESPAN Performance with Other Software.
(A) MIP of a raw fluorescence volume showing a dendritic segment. (B–D) Spine detection outputs from RESPAN (B),
DeepD3 (C), and Imaris (D) overlaying the dendritic segment. Detected spines are color-coded as true positives (TP, green),
false positives (FP, magenta), and false negatives (FN, orange). (E) Percentage of true positive spines detected by each
method. (F) Recall scores for spine detection, with RESPAN demonstrating consistently higher recall, reflecting fewer false
negatives. (G) Precision scores for spine detection, with RESPAN outperforming DeepD3 and Imaris by reducing false positive
detections. (H) F1 scores for spine detection, representing the harmonic mean of precision and recall. RESPAN achieves
superior F1 scores compared to other methods.

For a broader overview of how RESPAN compares to other methods—including cost, supported
platforms, and extensibility—please refer to **Table 5**. Whereas many commonly used workflows combine
multiple software programs or rely on significant manual intervention, RESPAN integrates state-of-the-
art deep learning modules for restoration, segmentation, and validation into a single GUI. This integration
substantially reduces technical barriers and promotes reproducibility, allowing researchers to audit results
and retrain models for new datasets seamlessly.

To our knowledge, RESPAN is the only freely available tool that integrates multiple state-of-the-art deep
learning approaches - content-aware image restoration [22], axial resolution enhancement [23], and self-
configuring image segmentation [24]. While recent advances have shown the power of individual deep
learning approaches for specific tasks, such as DeepD3 for spine detection or CARE for image
restoration, combining these capabilities requires significant computational expertise and manual data
handling between different software tools. RESPAN addresses this limitation by providing a complete,
integrated solution that maintains high performance while eliminating the technical barriers and overhead
traditionally associated with using multiple separate analysis tools. This integration is valuable for
ensuring reproducibility and maintaining data provenance throughout the analysis pipeline. Additionally,
instead of performing image operations on the CPU, RESPAN leverages GPU processing to efficiently
handle images in parallel, including in the rapid generation of 2D and 3D spine arrays.

Critically, unlike other methods, RESPAN provides a built-in tool for automatically validating the quality
of analysis against ground-truth data. This addresses an unmet need, as segmentation validation is often
performed manually or less rigorously by researchers with limited coding experience. By incorporating
this capability, we believe RESPAN can encourage a rigorous approach to automated quantification and
increase the reproducibility of published results. RESPAN also facilitates training new restoration and
segmentation models directly within the GUI, which would otherwise require separate Python
environments and coding experience, significantly reducing barriers to adopting this approach.

RESPAN significantly lowers the barriers to performing advanced image quantification for researchers
without coding expertise. This addresses challenges presented by other tools that require a combination
of Python or MATLAB scripts without a GUI, including tools that have been incorporated into our
approach. Furthermore, unlike other methods that limit analysis outputs to dendritic spine coordinates [9]
or require the use of multiple programs not within the same environment [9], our approach provides
comprehensive 3D analysis within a single graphical user interface environment. RESPAN can also be
readily adapted to new research questions by correcting initial results from the provided models using Fiji
[32], a widely used image analysis software, and the tools within RESPAN.

DISCUSSION

Dendritic spine analysis remains a cornerstone for understanding neuronal connectivity. Yet, current
approaches—predominantly manual or semi-automated—are constrained by interactive annotation
steps, image-specific parameters, user-dependent variability, and limited throughput. In addressing these
challenges, RESPAN introduces a fully integrated, deep learning-enhanced solution that significantly
broadens the scope and reliability of automated spine analysis.

One of RESPAN's significant contributions lies in its integrated architecture, consolidating image
restoration, axial resolution enhancement, and 3D segmentation into a single application. This design
minimizes biases intrinsic to manual methods and facilitates reproducible and direct comparisons across
diverse imaging modalities. With increasing focus on methodological rigor, RESPAN provides a
streamlined and robust framework for quantifying synaptic plasticity, neuronal development, and disease
models.

RESPAN also addresses significant barriers related to accessibility. Harnessing state-of-the-art
computational image analysis has historically required specialized expertise or costly commercial
platforms. By integrating GPU acceleration, model training, and analysis validation into a user-friendly
interface, RESPAN lowers these barriers and democratizes the use of advanced analysis tools. This
broad accessibility has the potential to accelerate discoveries in fields ranging from basic synaptic
physiology to translational research on neurodevelopmental disorders and neurodegenerative diseases,
areas where subtle changes in spine morphology and distribution may reveal profound shifts in neuronal
function.

Looking forward, RESPAN's architecture provides a platform for future extensions. Further integration of
segmentation models and analysis tailored to related biological features, such as mitochondria and
organelle analysis along dendrites and in relation to spines, as well as pre- and post-synaptic protein
analysis, will further enhance its utility.

In conclusion, RESPAN represents a significant advancement in automated dendritic spine analysis,
delivering accurate, robust, and accessible quantification to the neuroscience community. By enabling
unbiased, high-throughput measurements of spine morphology and distribution, RESPAN paves the way
for more comprehensive and reproducible studies of neuronal connectivity. By sharing the restoration
and segmentation models along with the code as an open-source platform, RESPAN fosters collaboration
and iterative development, allowing it to evolve alongside the research community's needs and ensuring
continued relevance and impact.

Limitations of the study

Despite these advantages, RESPAN does have limitations. The pipeline's performance depends heavily
on training datasets that faithfully represent the biological and imaging conditions of interest. While
RESPAN includes tools for model retraining, future iterations could benefit from more comprehensive
pre-trained models covering a wider range of biological and imaging conditions.

RESPAN currently only supports input data in TIFF format, requiring conversion of proprietary formats to
TIFF before use in our software. To overcome this limitation, we provide a Fiji macro to facilitate batch
conversion to TIFF using OMERO Bio-Formats [33]. We also generate our output data in TIFF for ease
of use, but future releases would benefit from added support for the Zarr format to improve scalability.

Users should be aware of the challenges of applying deep learning models to microscopy data [22,34].
Content-aware restoration and axial enhancement models should ideally be trained on data matching the
specific biological features, resolution, and imaging modality of the intended application. When models
are applied to data significantly different from their training set, they may perform sub-optimally and
introduce artifacts by hallucinating features or degradation of genuine structures. This is particularly
relevant when comparing experimental conditions with substantial morphological differences - in such
cases, training data should encompass the full range of expected biological variation to ensure reliable
results. Furthermore, as demonstrated in recent studies [23], the performance of these models can degrade
when the resolution anisotropy ratio exceeds 4-fold or when input data has extremely low signal-to-noise
ratios. To address these limitations, RESPAN includes model validation and retraining tools, allowing
users to optimize performance for their specific experimental conditions.

RESOURCE AVAILABILITY

Lead contact
515 Luke A. Hammond (Luke.Hammond@osumc.edu).

Data and code availability
● RESPAN code and executable available for download at:
https://github.com/lahammond/RESPAN
○ RESPAN is provided as Python code and as a standalone Windows application with a
graphical user interface (GUI), eliminating the need for programming expertise.
● Five example spinning disk confocal datasets and expected results generated by RESPAN are
available for download at:

-

ACKNOWLEDGMENTS

We thank Emiliano Zamponi from the Polleux lab for helping with image annotation and the Polleux lab members for extensive discussions and annotations to generate the multi-user metrics. We thank Qiaolian Lu for her help with mouse colony management. Imaging was performed in the Zuckerman Institute's Cellular Imaging platform. This work was supported by internal funding from the Zuckerman Institute, the NIH (5U19NS104649 and R35 NS127232), and a NOMIS Foundation Research Project.

AUTHOR CONTRIBUTIONS

Conceptualization, S.B.G, F.P, L.A.H,; methodology development, S.B.G, A.P.S, L.A.H; data acquisition, annotation, and analysis, S.B.G, A.P.S, D.P., A.J.P, L.A.H, Investigation, S.B.G, F.P, L.A.H; writing—original draft, S.B.G, L.A.H; writing—review & editing, S.B.G, F.P, L.A.H; funding acquisition, F.P.; resources, F.P., L.A.H; supervision, F.P., L.A.H.

DECLARATION OF INTERESTS

The authors declare no competing interests.

 SUPPLEMENTAL INFORMATION

Supplemental Figure 1. Representative Examples of CARE Restoration
Isolated maximum intensity projection views of a dendritic segment are shown under three conditions: low-SNR acquisition (left), CARE-restored output (middle), and high-SNR ground truth data (right). Each row demonstrates content-aware restoration of signal and contrast, revealing spine heads, necks and fine dendritic features that are difficult to discern in low-SNR images. Scale bar, 1 µm.

Supplemental Figure 2. Enhancement of Spine Detection Performance Through Data Augmentation.
(A) Data augmentation techniques applied during model training, illustrated through representative images: original raw image and subsequent transformations including shot noise, Gaussian blur, and pixel intensity scaling, aimed at enhancing model robustness and generalizability; random rotations and flips were performed to the data to avoid overfitting during model training. Scale bar, 2 µm. (B) Comparison of the number of spines detected in original and augmented datasets by ground truth (black) and RESPAN (red), analyzed using two-way ANOVA, indicating no significant difference (ns) to significant differences (*p < 0.05, ****p < 0.0001) in detection counts.(C) Scatter plots comparing spine detection metrics—precision, recall, and total performance—between original and augmented datasets, analyzed using two-way ANOVA with statistical significance indicated (**p < 0.01). (D) Bar graph showing the fraction of true positive spines detected, comparing models trained with no augmentation (black) and with augmentation (red), analyzed using the Wilcoxon matched-pairs signed rank test. The asterisks indicate a statistically significant increase in the detection of true positives (****p < 0.0001). (E) Scatter plot illustrating the reduction in false positives and false negatives in augmented datasets, analyzed using two-way ANOVA, with statistical tests indicating significant differences in error rates (**p < 0.01, *p < 0.05).

Supplemental Figure 3. RESPAN Validation Output for Dendritic Spine Segmentation
Maximum intensity projection views generated for validating RESPAN outputs. (Left) From top to bottom: raw fluorescence image of the analyzed dendritic segment; all detected spine segmentation masks; color-coded filtered spine segmentation masks after applying morphological criteria (minimum/maximum volume; maximum distance from dendrite); and a heatmap illustrating each voxel's distance from the dendrite shaft (cooler hues, closer distance; warmer hues, greater distance). (Right) Corresponding dendrite segmentation mask, dendrite skeletonization, and color-coded geodesic distance computed along the dendrite in 3D (blue to white, proximal to distal). These validation outputs allow users to readily confirm accurate segmentation of dendritic spines and the parent dendrite. Scale bar, 5 µm.

618 **TABLES AND TEXT BOXES**

Box 1 | RESPAN Parameters

This Box describes the parameters needed in the RESPAN GUI and additional considerations.

Image Data and Model Selection

- **Select data directory:** the location of the parent folder, which contains subfolders, each with an analysis_settings.yml file and TIF files to be processed.
- **Select segmentation model directory:** the location of the nnU-Net model directory provided with this software or one trained on your data.

Spine and Dendrite Detection

- **Channel containing dendrite/neuron signal:** specify the channel best representing the dendrite/neuron. If processing a single channel dataset, leave as 1.
- **Minimum dendrite volume (µm3):** putative dendrites or neurons detected smaller than this volume and their associated spines will be excluded from the analysis.
- **Spine volume filter (µm3):** specify the minimum and maximum volume of spines to be analyzed. Putative spines detected outside this range will be excluded from the analysis.
- **Spine distance filter (µm):** maximum distance spines should extend from the dendrite. Spines located further than this distance will be excluded from the analysis.

Image Data and Model Resolution

- **Image voxel size XY (µm):** lateral sampling used for acquiring data.
- **Image voxel size XY (µm):** axial sampling or step-size used for acquiring data.
- **Model voxel size XY (µm):** lateral sampling in data used for training segmentation model.
- **Model voxel size XY (µm):** axial sampling in data used for training segmentation model.
- **Use voxel sizes in analysis_settings.yml:** If enabled, overrides the above scaling parameters in favour of those specified in the settings file. Useful when processing datasets acquired using multiple imaging conditions or requiring different restoration models.

Temporal Analysis and Spine Tracking

- **Spine tracking:** If enabled, allows subsequent tracking and temporal analysis of spines.
- **Histogram matching:** Used to match signal intensity across image volumes being used for spine tracking.
- **Registration method:** Method used for registering image volumes for spine tracking.

Additional Options

- **Save 3D validation data:** Saves complete 3D datasets including labeled spines, which is useful for 3D validation, but significantly increases data storage requirements.
- **Save intermediate data:** Saves all intermediate data for troubleshooting challenging datasets.
- **Use image restoration:** If enabled, utilizes models specified in the analysis_settings.yml file to restore signal-to-noise using CARE.
- **Use axial restoration:** If enabled, utilizes models specified in the analysis_settings.yml file to restore signal-to-noise using SelfNet.
- **Generate SWC file for dendrite/neuron:** If enabled, generates an SWC file for the dendrite/neuron using Vaa3D. Requires Vaa3D to be installed and path to be correct in the analysis_settings.yml file.

Box 2 | Analysis Settings

This Box describes the parameters in the Analysis_Settings.yml file that can be modified for the advanced use of RESPAN.

Parameters

- **input_resXY:** The input resolution in the X and Y axis.
- **input_resZ:** The input resolution in the Z axis.
- **model_resXY:** The resolution in the X and Y axis of the data used to train the model.
- **model_resZ:** The resolution in the Z axis of the data used to train the model.

Analysis:

- **tiles_for_prediction:** The number of tiles used when processing images. This can be adjusted to modify performance.
- **roi_volume_size:** The size of volume extracted for each detected spine (in µm)
- **GPU_block_size:** Parameters used to adjust the image volume used for GPU processing. This can be modified to improve performance depending on GPU specifications.

nnUnet

- **type:** The type of nnU-Net model being used for segmentation.
- **conda_path:** The directory where Anaconda is installed.
- **env:** The environment where nnU-Net is installed.

Vaa3D:

- **path:** The directory where Vaa3D is installed.

Channe1-4:

- **care_restore:** The variable used to enable image resoration for this channel (True/False).
- **care_model_path:** The directory containing the model for image restoration for this channel.
- **sn_restore:** The variable used to enable axial resoration for this channel (True/False).
- **sn_model_path:** The directory containing the model for axial restoration for this channel.

Table 1. Individual Spine Measurements

Column	Title	Contents
1	spine_id	Unique identifier for each detected spine.
2	x	X-coordinate of the spine in image space (pixels).
3	y	Y-coordinate of the spine in image space (pixels).
4	z	Z-coordinate of the spine in image space (pixels).
5	dendrite_id	Identifier for the dendrite associated with the spine.
6	geodesic_dist	Geodesic distance from the spine to its parent dendrite (µm).
7	spine_area	Cross-sectional area of the entire spine (µm²).
8	spine_vol	Volume of the entire spine (µm³).
9	spine_vol_m	Measured spine volume adjusted for voxel resolution (µm³).
10	spine_sa_m	Spine surface area adjusted for voxel resolution (µm²).
11	spine_length	Total morphological length of the spine from the dendrite base to the spine head tip (µm).
12	head_area	Cross-sectional area of the spine head (µm²).
13	head_vol	Volume of the spine head (µm³).
14	head_vol_m	Measured volume of the spine head adjusted for voxel resolution (µm³).
15	head_sa_m	Surface area of the spine head adjusted for voxel resolution (µm²).
16	head_length	Length of the spine head, measured from the neck boundary to the head tip (µm).
17	neck_area	Cross-sectional area of the spine neck (µm²).
18	neck_vol	Volume of the spine neck (µm³).
19	neck_vol_m	Measured volume of the spine neck adjusted for voxel resolution (µm³).
20	neck_sa_m	Surface area of the spine neck adjusted for voxel resolution (µm²).
21	neck_length	Length of the spine neck, measured from the dendrite boundary to the head boundary (µm).
22	spine_length_dm	Alternative spine length measurement derived from distance mapping (µm).
23	spine_C1_int_density	Fluorescence integrated density in Channel 1 within the entire spine.
24	spine_C1_max_int	Maximum fluorescence intensity in Channel 1 within the entire spine.
25	spine_C1_mean_int	Mean fluorescence intensity in Channel 1 within the entire spine.
26	dist_to_dendrite_dm	Geodesic distance from the spine to the dendrite (µm).
27	dist_to_soma	Geodesic distance from the spine to the soma (µm).

28	head_C1_mean_int	Mean fluorescence intensity in Channel 1 within the spine head.
29	head_C1_max_int	Maximum fluorescence intensity in Channel 1 within the spine head.
30	head_C1_int_density	Fluorescence integrated density in Channel 1 within the spine head.
31	neck_C1_mean_int	Mean fluorescence intensity in Channel 1 within the spine neck.
32	neck_C1_max_int	Maximum fluorescence intensity in Channel 1 within the spine neck.
33	neck_C1_int_density	Fluorescence integrated density in Channel 1 within the spine neck.

Table 2. Detected Spines Summary

Column	Title	Contents
1	Filename	Name of the analyzed image file.
2	res_XY	Lateral (XY) resolution of the image in micrometers per pixel (µm/pixel).
3	res_Z	Axial (Z) resolution of the image in micrometers per pixel (µm/pixel).
4	dendrite_id	Unique identifier for the segmented dendrite.
4	dendrite_length	Total length of the segmented dendrite, in micrometers (µm).
5	dendrite_vol	Total dendritic volume, in cubic micrometers (µm³).
6	total_spines	Total number of detected spines along dendrite.
7	spines_per_um	Number of spines per micrometer of dendrite length (spines/µm).
8	spines_per_um3	Number of spines per cubic micrometer of dendrite volume (spines/µm³).
9	avg_spine_area	Mean cross-sectional area of the detected spines, in square micrometers (µm²).
10	avg_spine_vol	Mean volume of the detected spines, in cubic micrometers (µm³).
11	avg_spine_vol_m	Mean mesh volume of spines (µm³).
12	avg_spine_sa_m	Mean surface area of spines (µm²).
13	avg_spine_length	Mean length of the spines, in micrometers (µm).
14	avg_head_area	Mean cross-sectional area of the spine heads (µm²).
15	avg_head_vol	Mean volume of the spine heads (µm³).
16	avg_head_vol_m	Mean mesh volume of spine heads (µm³).
17	avg_head_sa_m	Mean surface area of spine heads (µm²).
18	avg_head_length	Mean length of the spine heads (µm).
19	avg_neck_area	Mean cross-sectional area of the spine necks (µm²).
20	avg_neck_vol	Mean volume of the spine necks (µm³).
21	avg_neck_vol_m	Mean mesh volume of spine necks (µm³).
22	avg_neck_sa_m	Mean surface area of spine necks (µm²).
23	avg_neck_length	Mean length of the spine necks, in µm.
24	avg_spine_length_dm	Mean spine length derived from distance-map or similar metric, in µm.
25	avg_spine_C1_int_density	Mean integrated density in Channel 1 within all spines.
26	avg_spine_C1_max_int	Mean maximum fluorescence intensity in Channel 1 within all spines.
27	avg_spine_C1_mean_int	Mean fluorescence intensity in Channel 1 within all spines.
28	avg_dist_to_dendrite_dm	Mean distance from spines to the dendrite shaft, in µm.
29	avg_dist_to_soma	Mean distance from spines to the soma, in µm.

30	avg_head_C1_mean_int	Mean fluorescence intensity in Channel 1 within spine heads.
31	avg_head_C1_max_int	Maximum fluorescence intensity in Channel 1 within spine heads.
32	avg_head_C1_int_density	Mean integrated density in Channel 1 within spine heads.
33	avg_neck_C1_mean_int	Mean fluorescence intensity in Channel 1 within spine necks.
34	avg_neck_C1_max_int	Maximum fluorescence intensity in Channel 1 within spine necks.
35	avg_neck_C1_int_density	Mean integrated density in Channel 1 within spine necks.

632
633

Table 3. Spine Analysis Summary (Temporal Analysis)

Column	Title	Contents
1	timepoint	Timepoint of the recorded data.
2	res_XY	Lateral resolution (µm/pixel).
3	res_Z	Axial resolution (µm/pixel).
4	dendrite_length	Total length of the segmented dendrite (µm).
5	dendrite_vol	Total dendritic volume (μm^3).
6	total_spines	Total number of detected spines at this timepoint.
7	spines_per_um	Density of spines per unit dendritic length (spines/µm).
8	new_spines	Number of newly detected spines at this timepoint.
9	pruned_spines	Number of spines that disappeared compared to the previous timepoint.
10	spines_per_um3	Density of spines per unit dendritic volume (spines/μm^3).
11	avg_x	Mean x-coordinate of detected spines (pixels).
12	avg_spine_area	Mean spine cross-sectional area ($pixels^2$).
13	avg_spine_area_um2	Mean spine cross-sectional area (μm^2).
14	avg_spine_vol	Mean spine volume (μm^3).
15	avg_C1_mean_int	Mean fluorescence intensity in Channel 1 within spines.
16	avg_spine_length	Mean spine length (µm).
17	avg_C1_max_int	Maximum fluorescence intensity in Channel 1 within spines.
18	avg_dist_to_dendrite	Mean geodesic distance of spines to the dendrite (µm).
19	avg_dist_to_soma	Mean geodesic distance of spines to the soma (µm).
20	avg_C1_int_density	Mean fluorescence intensity density in Channel 1 within spines.

Table 4. Segmentation Validation Output

Column	Title	Contents
1	Filename	Input image filename.
2	res_XY	Lateral image resolution (µm/pixel).
3	res_Z	Axial image resolution (µm/pixel).
4	gt_total_spines	Total spines in the ground truth image.
5	gt_total_spines_filtered	Total spines analyzed post-filtering in the ground truth image.
6	output_total_spines	Total spines detected by RESPAN.
7	output_total_spines_filtered	Total spines analyzed post-filtering by RESPAN.
8	TruePos_IoU50	True positive spines detected.
9	FalsePos_IoU50	False positive spines detected.
10	FalseNeg_IoU50	False negative spines.
11	Spine_precision_IoU50	Precision of spine detection.
12	Spine_recall_IoU50	Recall of spine detection.
13	gt_total_spine_vol	Total spine volume in the ground truth image (μm^3).
14	output_total_spine_vol	Total spine volume detected by RESPAN (μm^3).
15	total_spine_iou	IoU of spine voxels between ground truth and RESPAN.
16	total_spine_vol_difference	Difference in total spine volume between ground truth and RESPAN (µm).
17	gt_dendrite_length	Total dendritic length in the ground truth image (µm).
18	output_dendrite_length	Total dendritic length detected by RESPAN (µm).
19	dendrite_length_difference	Difference in dendritic length between ground truth and RESPAN (µm).
20	gt_dendrite_vol	Total dendritic volume in the ground truth image (μm^3).
21	output_dendrite_vol	Total dendritic volume detected by RESPAN (μm^3).
22	total_dendrite_iou	IoU of dendrite voxels between ground truth and RESPAN.
23	dendrite_vol_difference	Difference in dendritic volume between ground truth and RESPAN (μm^3).

641
642

644   **Table 5. Comparison of Existing Software Tools for Spine and Dendrite Analysis**

Tool	RESPAN	SpineTool	DeepD3	3DSpan	DeepSpine Tool	Imaris
Compatible Input Formats	.tif	.tif	.tif	.tif, .hdr, .img	.tif	.ims
Machine Learning Capabilities	Image restoration (SNR, resolution), Segmentation (2D/3D U-Net)	–	Segmentation (2D U-Net)	–	Segmentation (2D U-Net)	Segmentation (pixel classification)
Image Outputs	Spine, dendrite, soma masks (.tif), 2D/3D spine arrays (.tif), dendrite tracing (.swc)	Binarized spine image (.tif), spine meshes (.off)	Spine ROIs (.rois), spine masks (.tiff), prediction maps (.prediction)	Segmented sub-volumes (.hdr/.img)	Segmentation mask (.tif)	Objects visible within Imaris and can be converted to image data for export
Tabular Outputs	Spine counts and metrics (.csv)	Spine/dendrite classification (.json)	None	Segmentation analysis (.csv)	None	Selected parameters can be manually exported
Installation Requirements	Windows, NVIDIA GPU, Python 3.9, Anaconda	Windows, 1GB RAM, Anaconda	Python 3.7, Anaconda, TensorFlow	Windows	Windows, Python 3.6, CUDA 10.1, 8GB GPU	Windows/Mac
Training Data Acquisition Modality	2-photon, spinning disk confocal, Airyscan	Confocal	2-photon	2-photon	–	–
User Interface	GUI (single/batch processing)	Jupyter Notebook	GUI (single image, scripting for batch)	GUI	GUI	GUI
Open Source	Yes	Yes	Yes	Yes	No	No
Batch Processing	Yes	No	Yes	No	No	Yes
User-Trainable Models	Yes	No	Yes	No	No	No
Spine Quantification	Yes	No	Yes	Yes	No	Yes
Validation Capability	Yes	No	Yes	No	No	No
ImageJ Compatibility	Yes	Yes	Yes	No	Yes	No

645
646

REFERENCES

1. Iascone, D.M., Li, Y., Sumbul, U., Doron, M., Chen, H., Andreu, V., Goudy, F., Blockus, H., Abbott, L.F., Segev, I., et al. (2020). Whole-Neuron Synaptic Mapping Reveals Spatially Precise Excitatory/Inhibitory Balance Limiting Dendritic and Somatic Spiking. Neuron *106*, 566-578 e568. 10.1016/j.neuron.2020.02.015.
2. Lefebvre, J.L., Sanes, J.R., and Kay, J.N. (2015). Development of dendritic form and function. Annu Rev Cell Dev Biol *31*, 741-777. 10.1146/annurev-cellbio-100913-013020.
3. Cajal, S.R. (1888). Estructura de los centros nerviosos de las aves. Rev. Trim. Histol. Norm. Patol. *1*, 1-10.
4. Garcia-Lopez, P., Garcia-Marin, V., and Freire, M. (2007). The discovery of dendritic spines by Cajal in 1888 and its relevance in the present neuroscience. Prog Neurobiol *83*, 110-130. 10.1016/j.pneurobio.2007.06.002.
5. Fiala, J.C., Spacek, J., and Harris, K.M. (2002). Dendritic spine pathology: cause or consequence of neurological disorders? Brain Res Brain Res Rev *39*, 29-54. 10.1016/s0165-0173(02)00158-3.
6. Herms, J., and Dorostkar, M.M. (2016). Dendritic Spine Pathology in Neurodegenerative Diseases. Annu Rev Pathol *11*, 221-250. 10.1146/annurev-pathol-012615-044216.
7. Yuste, R., and Bonhoeffer, T. (2004). Genesis of dendritic spines: insights from ultrastructural and imaging studies. Nat Rev Neurosci *5*, 24-34. 10.1038/nrn1300.
8. Matsuzaki, M., Ellis-Davies, G.C., Nemoto, T., Miyashita, Y., Iino, M., and Kasai, H. (2001). Dendritic spine geometry is critical for AMPA receptor expression in hippocampal CA1 pyramidal neurons. Nat Neurosci *4*, 1086-1092. 10.1038/nn736.
9. Fernholz, M.H.P., Guggiana Nilo, D.A., Bonhoeffer, T., and Kist, A.M. (2024). DeepD3, an open framework for automated quantification of dendritic spines. PLoS Comput Biol *20*, e1011774. 10.1371/journal.pcbi.1011774.
10. Vogel, F.W., Alipek, S., Eppler, J.B., Osuna-Vargas, P., Triesch, J., Bissen, D., Acker-Palmer, A., Rumpel, S., and Kaschube, M. (2023). Utilizing 2D-region-based CNNs for automatic dendritic spine detection in 3D live cell imaging. Sci Rep *13*, 20497. 10.1038/s41598-023-47070-3.
11. Xiao, X., Djurisic, M., Hoogi, A., Sapp, R.W., Shatz, C.J., and Rubin, D.L. (2018). Automated dendritic spine detection using convolutional neural networks on maximum intensity projected microscopic volumes. J Neurosci Methods *309*, 25-34. 10.1016/j.jneumeth.2018.08.019.
12. Argunsah, A.O., Erdil, E., Ghani, M.U., Ramiro-Cortes, Y., Hobbiss, A.F., Karayannis, T., Cetin, M., Israely, I., and Unay, D. (2022). An interactive time series image analysis software for dendritic spines. Sci Rep *12*, 12405. 10.1038/s41598-022-16137-y.
13. Peng, H., Bria, A., Zhou, Z., Iannello, G., and Long, F. (2014). Extensible visualization and analysis for multidimensional images using Vaa3D. Nat Protoc *9*, 193-208. 10.1038/nprot.2014.011.
14. Peng, H., Ruan, Z., Long, F., Simpson, J.H., and Myers, E.W. (2010). V3D enables real-time 3D visualization and quantitative analysis of large-scale biological image data sets. Nat Biotechnol *28*, 348-353. 10.1038/nbt.1612.
15. Das, N., Baczynska, E., Bijata, M., Ruszczycki, B., Zeug, A., Plewczynski, D., Saha, P.K., Ponimaskin, E., Wlodarczyk, J., and Basu, S. (2022). 3dSpAn: An interactive software for 3D segmentation and analysis of dendritic spines. Neuroinformatics *20*, 679-698. 10.1007/s12021-021-09549-0.
16. Pchitskaya, E., Vasiliev, P., Smirnova, D., Chukanov, V., and Bezprozvanny, I. (2023). SpineTool is an open-source software for analysis of morphology of dendritic spines. Sci Rep *13*, 10561. 10.1038/s41598-023-37406-4.
17. Feng, G., Mellor, R.H., Bernstein, M., Keller-Peck, C., Nguyen, Q.T., Wallace, M., Nerbonne, J.M., Lichtman, J.W., and Sanes, J.R. (2000). Imaging neuronal subsets in transgenic mice expressing multiple spectral variants of GFP. Neuron *28*, 41-51. 10.1016/s0896-6273(00)00084-2.
18. Saito, T., and Nakatsuji, N. (2001). Efficient gene transfer into the embryonic mouse brain using in vivo electroporation. Dev Biol *240*, 237-246. 10.1006/dbio.2001.0439.
19. Tabata, H., and Nakajima, K. (2001). Efficient in utero gene transfer system to the developing mouse brain using electroporation: visualization of neuronal migration in the developing cortex. Neuroscience *103*, 865-872. 10.1016/s0306-4522(01)00016-1.
20. Denk, W., Delaney, K.R., Gelperin, A., Kleinfeld, D., Strowbridge, B.W., Tank, D.W., and Yuste, R. (1994). Anatomical and functional imaging of neurons using 2-photon laser scanning microscopy. J Neurosci Methods *54*, 151-162. 10.1016/0165-0270(94)90189-9.

21. Fuhrmann, M., Gockel, N., Arizono, M., Dembitskaya, Y., Nagerl, U.V., Pennacchietti, F., Damenti, M.,
Testa, I., and Willig, K.I. (2022). Super-Resolution Microscopy Opens New Doors to Life at the Nanoscale.
J Neurosci *42*, 8488-8497. 10.1523/JNEUROSCI.1125-22.2022.
22. Weigert, M., Schmidt, U., Boothe, T., Muller, A., Dibrov, A., Jain, A., Wilhelm, B., Schmidt, D., Broaddus,
C., Culley, S., et al. (2018). Content-aware image restoration: pushing the limits of fluorescence
microscopy. Nat Methods *15*, 1090-1097. 10.1038/s41592-018-0216-7.
23. Ning, K., Lu, B., Wang, X., Zhang, X., Nie, S., Jiang, T., Li, A., Fan, G., Wang, X., Luo, Q., et al. (2023).
Deep self-learning enables fast, high-fidelity isotropic resolution restoration for volumetric fluorescence
microscopy. Light Sci Appl *12*, 204. 10.1038/s41377-023-01230-2.
24. Isensee, F., Jaeger, P.F., Kohl, S.A.A., Petersen, J., and Maier-Hein, K.H. (2021). nnU-Net: a self-
configuring method for deep learning-based biomedical image segmentation. Nat Methods *18*, 203-211.
10.1038/s41592-020-01008-z.
25. Li, B.Z., Sumera, A., Booker, S.A., and McCullagh, E.A. (2023). Current Best Practices for Analysis of
Dendritic Spine Morphology and Number in Neurodevelopmental Disorder Research. ACS Chem Neurosci
14, 1561-1572. 10.1021/acschemneuro.3c00062.
26. Xiao, H., and Peng, H. (2013). APP2: automatic tracing of 3D neuron morphology based on hierarchical
pruning of a gray-weighted image distance-tree. Bioinformatics *29*, 1448-1454.
10.1093/bioinformatics/btt170.
27. Charrier, C., Joshi, K., Coutinho-Budd, J., Kim, J.E., Lambert, N., de Marchena, J., Jin, W.L.,
Vanderhaeghen, P., Ghosh, A., Sassa, T., and Polleux, F. (2012). Inhibition of SRGAP2 function by its
human-specific paralogs induces neoteny during spine maturation. Cell *149*, 923-935.
10.1016/j.cell.2012.03.034.
28. Fossati, M., Pizzarelli, R., Schmidt, E.R., Kupferman, J.V., Stroebel, D., Polleux, F., and Charrier, C. (2016).
SRGAP2 and Its Human-Specific Paralog Co-Regulate the Development of Excitatory and Inhibitory
Synapses. Neuron *91*, 356-369. 10.1016/j.neuron.2016.06.013.
29. Schmidt, E.R.E., Kupferman, J.V., Stackmann, M., and Polleux, F. (2019). The human-specific paralogs
SRGAP2B and SRGAP2C differentially modulate SRGAP2A-dependent synaptic development. Sci Rep *9*,
18692. 10.1038/s41598-019-54887-4.
30. Schmidt, E.R.E., Zhao, H.T., Park, J.M., Dipoppa, M., Monsalve-Mercado, M.M., Dahan, J.B., Rodgers,
C.C., Lejeune, A., Hillman, E.M.C., Miller, K.D., et al. (2021). A human-specific modifier of cortical
connectivity and circuit function. Nature *599*, 640-644. 10.1038/s41586-021-04039-4.
31. Hand, R., and Polleux, F. (2011). Neurogenin2 regulates the initial axon guidance of cortical pyramidal
neurons projecting medially to the corpus callosum. Neural Dev *6*, 30. 10.1186/1749-8104-6-30.
32. Schindelin, J., Arganda-Carreras, I., Frise, E., Kaynig, V., Longair, M., Pietzsch, T., Preibisch, S., Rueden,
C., Saalfeld, S., Schmid, B., et al. (2012). Fiji: an open-source platform for biological-image analysis. Nat
Methods *9*, 676-682. 10.1038/nmeth.2019.
33. Linkert, M., Rueden, C.T., Allan, C., Burel, J.M., Moore, W., Patterson, A., Loranger, B., Moore, J., Neves,
C., Macdonald, D., et al. (2010). Metadata matters: access to image data in the real world. J Cell Biol *189*,
777-782. 10.1083/jcb.201004104.
34. Laine, R.F., Arganda-Carreras, I., Henriques, R., and Jacquemet, G. (2021). Avoiding a replication crisis in
deep-learning-based bioimage analysis. Nat Methods *18*, 1136-1144. 10.1038/s41592-021-01284-3.

METHODS

KEY RESOURCES TABLE

REAGENT OR RESOURCE	SOURCE	IDENTIFIER
Biological samples		
Mouse brain cortical tissue	This study	
In vivo imaging of dendrites via a cortical window	This study	
Chemicals, peptides, and recombinant proteins		
ProLong™ Glass Antifade Mountant	ThermoFisher	Cat#: P36982
Citifluor™ Mountant Solution MWL4-88	EMS	Cat#: 17977-150
Citifluor™ Mountant Solution AF100	EMS	Cat#: AF100-5
Deposited data		
RESPAN – GUI, Trained Models	This study	https://github.com/lahammond/respan
Examples Datasets and Results	This study	*link forthcoming*
Experimental models: Cell lines		
Mouse: C57BL/6J	Jackson Laboratories	RRID:IMSR_JAX:000664
Mouse: SRGAP2A +/-	Charrier, C. *et al.*	[27]
Recombinant DNA		
pCAG-Cre	This study	N/A
pEf1α-FLEX-tdTomato	Iascone et al.	[1]
pEF1α-FLEX-mGreenLantern	This study	
Software and algorithms		
RESPAN (Restoration Enhanced SPine And Neuron Analysis)	This study	https://github.com/lahammond/respan
Anaconda	Anaconda	https://www.anaconda.com/
nnU-Net	Isensee, F., Jaeger, P.F., Kohl, S.A.A. *et al.*	[24]
CARE	Weigert, M. *et al*	[22]
Fiji	ImageJ	https://imagej.net/software/fiji/
StackReg plugin	BIG-EPFL	https://bigwww.epfl.ch/thevenaz/stackreg/

NIS Elements Deconvolution Module	NIS-Elements	https://www.microscope.healthcare.nikon.com/en_EU/products/software/nis-elements
GraphPad Prism 10.4.1	Prism	https://www.graphpad.com/
Imaris	Bitplan	https://imaris.oxinst.com/
DeepD3	Fernholz, M.H.P. *et al.*	[9]
Other		
3D printed headplate for cranial windows	Zuckerman Institute – Advanced Instrumentation	N/A
Yokogawa W1 spinning disk	Yokogawa Electric Corp.	N/A
Bergamo II 2-photon microscope	Thorlabs	N/A

EXPERIMENTAL MODEL AND STUDY PARTICIPANT DETAILS

Animals and Experimental Design

All animal procedures were approved by the Institutional Animal Care and Use Committee (IACUC) at Columbia University and conducted in accordance with institutional and federal animal welfare guidelines (IACUC Protocols AC-AABL2557 and AC-AABV8659). Mice were housed in a temperature-controlled environment on a 12-hour light/dark cycle, with ad libitum access to food and water.

In Vivo Imaging

Species/Strain: C57BL/6J (B6) and constitutive heterozygous knockouts for SRGAP2A+/-

Genotype: WT (B6) and SRGAP2A+/-

Age/Developmental Stage: Mice were implanted with cranial windows at postnatal day (P)90 and imaged between P100–P120

Sex: Both male and female mice were used; sex was recorded for all animals

Housing and Maintenance: Standard housing conditions; individually housed post-surgery to prevent injury

Ethical Oversight: All procedures were approved by Columbia University IACUC

Ex Vivo Imaging

Species/Strain: C57BL/6J (B6)

Genotype: WT

Age/Developmental Stage: Neurons were labeled in utero at embryonic day (E)15.5, with brains
harvested at postnatal stages

Sex: Both male and female embryos were used; sex was not a variable in the analysis

Housing and Maintenance: Pregnant dams were housed under standard conditions until embryos
reached E15.5 for in utero electroporation

Ethical Oversight: Procedures were approved by Columbia University IACUC

Sex as a Biological Variable

Both male and female mice were used in this study. While sex was recorded for all animals, the data
were analyzed without sex-based segregation, as prior research indicates no significant sex-dependent
differences in the measured parameters. However, potential sex-related effects are acknowledged as a
limitation of this study.

METHOD DETAILS

Animal Handling and Surgical Procedures

For in vivo imaging, mice underwent cranial window implantation at P90 under isoflurane anesthesia. A
4 mm circular craniotomy was performed over primary somatosensory cortex (S1), and a glass
coverslip (No. 1, 4 mm diameter) was affixed with dental cement. A custom 3D printed headplate was
attached to facilitate head fixation during imaging. Postoperative analgesia included subcutaneous
injections of meloxicam (5 mg/kg). Mice were allowed 7–14 days for recovery before imaging.

For ex vivo experiments, in utero electroporation was performed at E15.5 to label Layer 2/3 pyramidal
cortical neurons with fluorescent plasmids. Pregnant dams were anesthetized with isoflurane (1.5–2%),
and embryos were injected with a plasmid mixture containing pCAG-Cre (1-10 ng/µL) and pCAG-FLEX-
TdTomato (1 µg/µL). Plasmids were delivered into the lateral ventricle, followed by electroporation
using five 50 ms pulses at 35 V (BTX ECM830 electroporator, 1 Hz frequency). Pups were allowed to
develop postnatally before brains were extracted for imaging.

Tissue Preparation for Ex Vivo Imaging

Mice were anesthetized with isoflurane and transcardially perfused with ice-cold phosphate-buffered
saline (PBS) followed by 4% paraformaldehyde (PFA) in PBS. Brains were dissected and post-fixed in
4% PFA overnight at 4°C, then rinsed in PBS and sectioned at 100 µm using a Leica VT1000 S
vibratome. Sections were mounted in ProLong Gold antifade reagent for imaging.

In Vivo Two-Photon Imaging

Imaging was performed using a Bergamo II two-photon microscope (Thorlabs) equipped with a
Ti:Sapphire laser (Coherent Chameleon Ultra II, 920 nm excitation). A 25× 1.0 NA water-immersion
objective (Olympus, XLPlan N) was used for data acquisition. Image stacks were acquired at 1024 ×
512 pixels with a pixel size of 0.102 µm and 1 µm axial step size. The laser operated at an 80 MHz

repetition rate with a 100 fs pulse width, and power at the sample was maintained at <15 mW to
minimize phototoxicity. Mice were head-fixed on a custom stage, and imaging sessions lasted <60 min
per session to prevent physiological stress, minimize photodamage, and minimize exposure to
anesthetic.

Spinning Disk Confocal Imaging (Ex Vivo Samples)

Sections were imaged using a Yokogawa W1 spinning disk confocal system mounted on a Nikon Ti2
inverted microscope controlled with NIS-Elements. Images were acquired with a 100× 1.35 NA SR HP
Plan Apo silicone immersion objective and a Prime BSI sCMOS camera (Teledyne Photometerics),
resulting in pixel size of 65nm and a z-step size of 150nm. 488 and 561 nm laser lines were used to
sequentially excite GFP and TdTomato, respectively, with matched bandpass emission filters installed
in a triggered high-speed filter wheel (IDEX Health & Science LLC). When appropriate, images were
further processed using a blind deconvolution algorithm with 25 iterations using the low noise
parameter in the NIS Elements.

Data Acquisition and Processing

In vivo time-lapse imaging was performed via daily imaging over 2 continuous days to track dendritic
spine dynamics across a 24 hour time interval. Ex vivo datasets were processed for 3D reconstruction
and dendritic spine analysis using RESPAN (Restoration Enhanced SPine and Neuron Analysis), which
integrates content-aware image restoration with deep learning-based segmentation. Motion correction
for in vivo imaging was conducted using StackReg (https://github.com/fiji-BIG/StackReg) to
compensate for minor movement artifacts. Spine detection and morphometric analyses were performed
using nnUNet-based segmentation models, which were trained on a diverse dataset of manually
annotated spines to ensure robustness across varying imaging conditions. Quantifications included
spine density, spine head volume, and spine-to-dendrite distance, with statistical validation performed
against expert-annotated ground truth datasets.

QUANTIFICATION AND STATISTICAL ANALYSIS

836 All statistical analyses were performed using GraphPad Prism 9.0. Statistical details for each
837 experiment, including sample sizes (n), measures of central tendency, variability, and statistical
838 significance, are reported in the figure legends and corresponding text in the Results section.

Statistical Tests and Data Distribution

To compare differences in dendritic spine density, spine length, and volume between WT and
SRGAP2A+/- mice, we used Kolmogorov-Smirnov tests, a non-parametric method suitable for
comparing distributions without assuming normality. For comparisons of imaging-based segmentation
performance (e.g., spine detection accuracy, precision, recall, and F1 score), we employed paired two-
tailed t-tests and Wilcoxon matched-pairs signed-rank tests, as appropriate. For datasets involving
multiple comparisons, two-way ANOVA followed by Benjamini-Krieger-Yekutieli correction was applied
to control the false discovery rate (FDR).

Definition of Sample Size (n)

For *in vivo* imaging, each n represents an individual dendritic segment imaged from a single neuron, and multiple neurons were imaged per animal. For ex vivo experiments, each n corresponds to an apical dendritic segment from a single neuron; multiple neurons were imaged from multiple mice. Final sample sizes were based on prior studies assessing dendritic spine morphology in similar experimental paradigms and are reported in figure legends.

Randomization and Blinding

Mice were randomly assigned to experimental groups at the time of imaging, and all spine analyses were performed blinded to genotype to reduce bias. Image processing and quantification via RESPAN also remained blind to the genotype to minimize manual intervention and ensure unbiased analysis.

Segmentation Validation and Accuracy Metrics

RESPAN's automated segmentation performance was validated against ground truth expert annotations, and performance was quantified using Dice coefficient, F1 score, precision-recall curves, and Hausdorff distance. Object-level segmentation accuracy was assessed by comparing IoU (Intersection over Union) values with a threshold of 0.50 to define correctly detected spines.

Statistical Significance Criteria

For all analyses, statistical significance was defined as $p < 0.05$, with exact p-values reported in the figures and results section. Data distributions were examined for normality, and appropriate parametric or non-parametric tests were applied based on distribution characteristics.

ADDITIONAL RESOURCES

RESPAN source code and application: https://github.com/lahammond/respan