AlphaFastPPi: a fast AlphaFold-Multimer-based pipeline for high-throughput screening

G. Bellinzona[1], D. Sassera[1,2], A.M.J.J Bonvin[3]

1 Department of Biology and Biotechnology, University of Pavia, Pavia, Italy
2 IRCCS Policlinico San Matteo, Pavia, Italy
3 Department of Chemistry, Faculty of Science, Computational Structural Biology Group, Bijvoet Centre for Biomolecular Research, Utrecht 3584 CS, The Netherlands. Email: a.m.j.j.bonvin@uu.nl

Abstract

Motivation
Discovering new protein-protein interactions (PPIs) across entire proteomes offers vast potential for understanding novel protein functions and elucidate system properties within or between an organism. While recent advances in computational structural biology, particularly AlphaFold-Multimer, have facilitated this task, scaling for large-scale screenings remains a challenge, requiring significant computational resources.

Results
Here we introduce AlphaFastPPi, a pipeline built upon AlphaFold-Multimer and AlphaPulldown. AlphaFastPPi is a streamlined pipeline which reduces resource consumption compared to other methods resulting in enhanced efficiency. This is achieved by lowering the minimum number of models required from five to one, while maintaining a good accuracy. This provides a more sustainable approach to PPI prediction. We demonstrate that this optimization does not compromise the accuracy of the method, offering a fast, efficient, and environmentally friendly solution for PPI predictions.

Availability
The AphaFastPPi code is freely available from https://github.com/MIDIfactory/AlphaFastPPi

Introduction

Mapping protein-protein interactions (PPIs) at the whole proteome level holds significant promise for uncovering new protein functions and elucidating local and global system properties within biological systems. Within an organism, PPIs are essential for vital cellular processes, such as signal transduction, metabolic pathways, and gene regulation. Interactions between different organisms, such as host-pathogen interactions, are also mediated by PPIs and are critical for understanding broader biological mechanisms.

Traditionally, studying these interactions has been laborious and often limited by the constraints of experimental techniques. The advancement of computational tools for predicting protein structures, particularly the recent introductions of Alphafold2 (Jumper *et al*., 2021) and AlphaFold-Multimer (Evans et al., 2022), has significantly enhanced our ability to study PPIs.

AlphaFold-Multimer leverages the power of GPUs to model PPIs, making the prediction process not only accurate but also relatively fast. Since its release, several optimized pipelines have been introduced to accelerate the computational workflow even further. These improvements include the separation of CPU and GPU stages to optimize processing efficiency and providing faster multisequence alignment (MSA) search options (Mirdita *et al*., 2022). Additionally, a number of tools have been developed to help with specific AlphaFold-Multimer (Evans et al., 2022) applications, including AlphaPulldown (Yu *et al.*, 2022), a python package which streamlines the screening of PPIs. Despite these advancements, large-scale PPI screening remains challenging due to the substantial requirements for computing time, disk space, and GPU resources. These constraints can limit the accessibility and scalability of AlphaFold-Multimer and AlphaPulldown for large scale studies.

Here, we present AlphaFastPPi, a python package which streamlines the AlphaFold-Multimer pipeline to screen for PPIs and reduces the number of models generated from the standard minimum of five to just one. This change aims to address several critical needs: (i) it enhances the accessibility for high-throughput PPI screenings for users with limited computational capabilities; (ii) it conserves computational resources by lowering the time required by a factor 5, which is crucial to enable more sustainable large-scale analyses; and (iii) importantly, it should do so without compromising the accuracy required for confident predictions.

We demonstrate AlphaFastPPi's ability to predict whether two proteins are interacting on a dataset consisting of intra- and inter-species PPIs comprising bacterial and eukaryotic proteins. This work extends the accessibility of AlphaFold-Multimer's predictive capabilities while reducing environmental impact and resource wastage, making it a more inclusive and sustainable method.

Code implementation

First, Multiple Sequence Alignments (MSA) and structural template features are generated using the AlphaPulldown v.1.0.4 (Yu *et al.*, 2022) script create_individual_features.py on CPUs. Subsequently, predictions are made using AlphaFastPPi, which generates a single model for each PPI on GPUs when available, otherwise CPUs are used. Since it has been demonstrated

that MSA pairing does not improve AlphaFold performance, only unpaired MSAs are used to increase speed (Yin *et al.*, 2022).

AlphaFastPPi offers two modalities, similar to AlphaPulldown v.1.0.4 (script run_multimer_jobs.py) (Yu *et al.*, 2022): pull-down and all-versus-all. In pull-down mode, users provide a list of one or more proteins as 'baits' and another protein as 'candidates', which are potential interaction partners. Then, AlphaFold-Multimer evaluates each bait protein against each candidate protein, generating a single model for each pair. In all-versus-all mode, the software computes all possible combinations among the proteins in the provided list, generating a single model for each pair.

After modeling, model quality scores such as pDockQ (Bryant *et al.*, 2022), ipTM, ipTM+pTM, and average plDDT are calculated for each predicted PPI and the results are stored in a table for further analysis. The workflow is shown in Figure 1.

Figure 1. Overview of the AlphaFastPPi workflow.

Benchmark dataset

A test set was built by combining both experimentally validated positive PPIs and a set of negative interactions taken from the Negatome database (Blohm *et al.*, 2014) (Supplementary Table 1). The positive test set was composed of 286 PPIs from *Mycoplasma pneumoniae* (Elfmann et al., 2022) and 142 heterodimeric protein complexes between *Arabidopsis thaliana* and *Serendipita indica* (Osborne *et al.*, 2023). The negative data set consisted of an equal number (428) of true negatives composed by randomly selecting non-interacting protein pairs from the Negatome (Blohm *et al.*, 2014).

Results

We assessed the modeling performance of the AlphaPulldown (Yu *et al.*, 2022) modeling step (run_multimer_jobs.py), which generates a minimum of five models, and compared it with that of AlphaFastPPi, which produces just one model for each protein pair, on a dataset of experimentally-proven interacting and non-interacting protein pairs using the pull down mode. All the predictions were performed on NVIDIA A100 SXM6 64GB GPUs. While GPU acceleration significantly speeds up the code, it is not a strict requirement. If no GPU is detected, the tool will automatically turn down to use CPU resources at the cost of increased computational time. As expected, AlphaFastPPi allowed us to save approximately 4.7 times the GPU hours, translating to over 8 days in total for screening 856 interactions, and approximately 5.0 times the disk space, saving more than 2 TB of disk space. We then assessed the ability of the method to distinguish between interacting and non-interacting pairs. Although various scoring metrics (e.g. ipTM, pDockQ), have been developed to evaluate the quality of a model, none have been explicitly designed to address this specific question of whether two proteins are interacting or not. However, among these metrics, pDockQ displayed some capability in addressing this task (Bryant *et al.*, 2022). When considering AlphaPulldown's results, only the model with the highest pDockQ among the five generated was considered to compare the distribution of values with those from AlphaFastPPi. The same approach was applied for ipTM. We did not observe any significant difference between the two methods considering both scores. This suggests that lowering the number of predictions from five to a single one does not affect the discriminatory power in distinguishing between interacting and non-interacting pairs (Figure 2).

Figure 2. ROC curves comparing AlphaPulldown (yellow) and AlphaFastPPi (blue). The ROC curves using both the pDockQ (solid line) and ipTM (dashed line) scores to distinguish true from false interactions are shown. DeLong's test was performed to compare AlphaFastPPi and AlphaPulldown for both ipTM and pDockQ, indicating no statistically significant difference between the AUCs (pDockQ Z=0.53849, p-value=0.428; ipTM: Z=0.41, p-value=0.328).

However, consistent with previous findings (Bryant *et al*., 2022), pDockQ performed better than ipTM. When applying a pDockQ cut-off of 0.23, deemed sufficient to ensure a reasonable model quality (Burke *et al.*, 2023), both AlphaPulldown and AlphaFastPPi achieved a specificity above 70%, with sensitivity around 24% on our benchmark dataset. Increasing the pDockQ threshold to 0.5 resulted in a specificity above 90%, although the sensitivity dropped below 10%. Moreover, inter-species interactions (i.e between *A. thaliana* and *S. indica* proteins in this benchmark) showed lower confidence scores compared to intra-species interactions (i.e among *M. pneumoniae* proteins).

It should be mentioned that massive sampling, which has been demonstrated to effectively increase the quality of models (Wallner, 2023), will likely also enhance the method's ability to distinguish between interacting and non-interacting protein pairs. However, this approach is not applicable for large-scale studies due to its substantial computational requirements.

Conclusions

AlphaFastPPi represents a streamlined and efficient approach for predicting protein-protein interactions (PPIs) that reduces computational resources consumption while maintaining a competitive performance in predicting interacting pairs. This tool aligns with the needs of the scientific community, ranging from conducting quick preliminary analyses, offering a way for a rapid and effective means of narrowing down potential interactions for further investigation, to those involved in extensive studies with limited resources. It also contributes to more sustainable computational studies of PPIs.

Availability

AlphaFastPPi is is freely available on GitHub https://github.com/MIDIfactory/AlphaFastPPi

Funding

This work was supported by HPC Cineca under Project name IsCb2 to DS. A.M.J.J.B. acknowledges funding from the European Union Horizon 2020 project BioExcel (823830).

References

Blohm,P. *et al.* (2014) Negatome 2.0: a database of non-interacting proteins derived by literature mining, manual annotation and protein structure analysis. *Nucleic Acids Res.*, **42**, D396–400.

Bryant,P. *et al.* (2022) Improved prediction of protein-protein interactions using AlphaFold2. *Nat. Commun.*, **13**, 1265.

Burke,D.F. *et al.* (2023) Towards a structurally resolved human protein interaction network. *Nat. Struct. Mol. Biol.*, **30**, 216–225.

Evans R. et al. (2022) Protein complex prediction with AlphaFold-Multimer. https://github.com/deepmind/alphafold

Jumper, J. et al. (2021) Highly accurate protein structure prediction with AlphaFold. Nature 596, 583–589

Mirdita,M. *et al.* (2022) ColabFold: making protein folding accessible to all. *Nat. Methods*, **19**, 679–682.

Osborne,R. *et al.* (2023) Symbiont-host interactome mapping reveals effector-targeted modulation of hormone networks and activation of growth promotion. *Nat. Commun.*, **14**, 1–16.

Wallner,B. (2023) AFsample: improving multimer prediction with AlphaFold using massive sampling. *Bioinformatics*, **39**, btad573.

Yin,R. *et al.* (2022) Benchmarking AlphaFold for protein complex modeling reveals accuracy determinants. *Protein Sci.*, **31**, e4379.

Yu,D. *et al.* (2022) AlphaPulldown—a python package for protein–protein interaction screens using AlphaFold-Multimer. *Bioinformatics*, **39**, btac749.