The systematic nature of splitter cells

Naomi Chaix-Eichel[1,2,†], Snigdha Dagar[1,2,†], Fréderic Alexandre[1,2, ‡], Thomas Boraud[1,‡], Nicolas P. Rougier[1, 2,‡,*]

1 Univ. Bordeaux, CNRS, IMN, UMR 5293, F-33000 Bordeaux, France
2 Univ. Bordeaux, CNRS, Bordeaux INP, INRIA, LaBRI, UMR 5800, F-33400 Talence, France
* nicolas.rougier@inria.fr

†These authors contributed equally to this work.
‡These authors also contributed equally to this work.

Keywords: Hippocampal formation, reservoir computing, spatial navigation, splitter cells.

Abstract

During the past decades, hippocampal formation has undergone extensive studies, leading researchers to identify a vast collection of cells with functional properties. Several investigations, supported by carefully crafted models, have examined the origin of such cells. The most recent models hypothesize that temporal sequences underlie the observed spatial properties. We aim at investigating whether a random recurrent structure is sufficient to allow such latent sequence to appear. To do so, we simulated an agent with egocentric sensory inputs that must navigate and alternate choices at intersections. We were subsequently able to identify several splitter cells inside the model. Remarkably, when we systematically lesioned the identified splitter cells, the model's behavioral performance remained intact, and new splitter cells consistently emerged through network reorganization. Furthermore, we successfully decoded position, orientation, and decision representations from the reservoir activity, even after repeated lesioning of the splitter cells. These findings suggest that the splitter cells activity is primarily task-driven and does not derive from a specific architecture nor learning. Any sufficiently recurrent network will exhibit such activity. Our results challenge the notion of functional necessity for specific neural populations and highlight the remarkable adaptability of neural networks in reorganizing computation to maintain behavioral performance.

1 Introduction

The hippocampal formation has been heavily studied in the past few decades (Maguire et al., 1996; Buzsáki and Moser, 2013; Hartley et al., 2014; Moser et al., 2017) and researchers have since then established a huge repertoire of cells displaying very specific properties. In his book "The Brain from Inside out" (György Buzsáki, 2019), György Buzsáki named a few of them in a footnote (page 356): *place cells, time cells, grid cells, head direction cells, boundary vector cells, border cells, object cells, object vector cells, distance cells, reward cells, concept cells, view cells, speed cells, memory cells, goal cells, goal direction cells, splitter cells, prospective cells, retrospective cells, island cells, ocean cells, band cells, object cells, pitch cells, trial order cells, etc*. Each and every cells have been characterized in terms of correlation between their activity and some combination of high level property involving space, time and internal state. This is the case for place (cell fires when animal is in a specific place), head direction (cell fires preferentially when head is pointing toward a specific direction), time cells (cell fires at successive moments), etc. Facing such huge repertoire, one may legitimately wonder how the brain orchestrates all these information and makes use of it to ensure survival. Part of the answer is given by György Buzsáki himself in the same footnote where he further explained that *physiological attributes of neurons in the hippocampal-enthorinal system ... might be explained by the apparent distinctiveness of a few sets of continuous distributions*. In other words, even though we can and we do observe these cells *in vivo*, they might be a simple epiphenomenon: their activity might be correlated to some unknown latent variables.

This is actually hardly different from the hypothesis provided by Raju et al. (2024) where authors suggest that spatial representations are not explicitly encoded but emerge as a byproduct of sequence learning. Their model is based on a variant of Hidden Markov Model (HMM) theory and employs a clone-structured causal graph (CSCG) (George et al., 2021) to differentiate between various sequences of input. In this framework, multiple "clones" represent the same observation across different contexts, enabling the model to handle ambiguous sensory input sequentially. Consequently, the representation of space arises implicitly through the process of sequence learning, rather than being an explicit function of the hippocampus. Other research has similarly challenged the traditional space-centric view of the hippocampus. Using the concept of successor representation (Dayan, 1993), Stachenfeld et al. (2017) suggest that hippocampal cells encode a predictive map rather than a purely euclidean spatial map. Sanders et al. (2020) propose that the hippocampus builds more abstract representations of environmental structure based on the animal's subjective beliefs rather than directly representing objective spatial properties of the environment. Whittington et al. (2020) introduced

the Tolman-Eichenbaum machine (TEM), a model that unifies spatial and non-spatial functions of the hippocampus. They argue that hippocampal cells emerge as a result of the system learning to represent abstract relationships, enabling the representation of both spatial and non-spatial information. In this study, we align with current approaches and propose to reconsider the role of hippocampal cells. More precisely, we decided to focus our study on splitter cells about which Duvelle et al. (2023) published recently an extended review of the literature. Splitter cells encode information about the past or the future trajectory (Wood et al., 2000)). In other words, they demonstrate different firing patterns depending on the animal's origin or intended destination, even if the animal is in the same physical location, as explained in Figure 1.

Figure 1: Figure from Duvelle et al. (2023) explaining splitter cells at the single cell and population levels. (A) Schematic activity of six idealized splitter cells during a plus-maze task with four possible trajectories (SW, SE, NW, NE). Splitter cells differentiate either past or future trajectories. Some show rate differences (left), others respond to only one trajectory (middle), or shift their firing location depending on trajectory (right). (B) Left: Schematic neural trajectories in population activity space for SW and SE paths. Despite identical physical paths, activity diverges based on future direction (E vs W). Middle: Neural trajectories projected onto the first three principal components, showing separation during both shared and diverging path segments. Right: Hypothetical population activity without splitter cell modulation, shown for comparison.

We adopt a novel perspective based on György Buzsáki's interpretation of the brain as a large reservoir of neurons with pre-existing patterns of activity (György Buzsáki, 2019). According to this view, when a new experience occurs, the brain assigns it to a pre-existing pattern from a vast reservoir of internally generated patterns, thereby assigning behavioral meaning to the neuronal sequence. This mechanism is considered more biologically plausible than creating entirely new patterns for each experience. Building on this concept, we propose to study a reservoir computing model composed of a pool of recurrently interconnected neurons, representing a vast reservoir capable of generating an extensive repertoire of neuronal patterns. The model's synaptic weights are randomly initialized and kept fixed, implying that the neuronal patterns within the reservoir remain unchanged after learning. The only trained part is the readout layer that connects the reservoir to the output. This fixed-weight approach does not model plasticity in the reservoir, but we argue that it is sufficient and consistent with György Buzsáki (2019)'s perspective. This is supported by experiments showing that learning only modestly and transiently impacts network dynamics (Golub et al., 2018). Furthermore, this view of the navigation system allows for a simple model that is easy to understand and manipulate, which is our main novelty and contribution compared to the other models listed: we don't require complex architectures or concepts to study splitter cells, just a pool of randomly interconnected neurons. Despite its simplicity, this model has already demonstrated great success and robustness in several works by Eric A. Antonelo (Antonelo et al., 2007, 2008; Antonelo and Schrauwen, 2009, 2012), and has even been successfully implemented on real robots navigating spatial environments (Antonelo and Schrauwen, 2015). We demonstrate that this model can robustly solve a T-maze alternation task, specifically within a continuous state-space. Similarly to the model of Raju et al. (2024), our model handles ambiguous sensory inputs reflecting a more realistic scenario. Rather than relying on allocentric information such as spatial coordinates, the model has access only to partially observable inputs, i.e. egocentric information: distance sensors. These sensors can read identical values in different locations within the maze, making the sensory information ambiguous. This feature increases the task's realism and difficulty and distinguishes our approach from Stachenfeld et al. (2017); Whittington et al. (2020); George et al. (2021), where such ambiguity was not explicitly addressed.

By conducting a theoretical analysis similar to that of Duvelle et al. (2023), we show that the internal states of certain model units exhibit properties similar to biological splitter cells. Interestingly, when we 'lesioned' the model by explicitely removing these units, the performances remained unaffected and new splitter cells emerged. In a configuration where navigation behavior is forced, this lesion–regeneration cycle can be

repeated multiple times, leading to a reorganization of the internal dynamics of the network, that is shown to be able to support the task. This repeated emergence suggests that splitter cell-like representations are not fixed structural features but functional strategies that arise from the demands of navigation. Although it remains unclear whether splitter cells drive navigation or emerge as a consequence of it, our findings caution against attributing functional necessity to any specific unit subset. Instead, the network flexibly reallocates computation across remaining or newly initialized units. Furthermore, position, orientation and decision can be successfully decoded from the model, even after lesions, aligning with prior studies (Luo et al., 2024) but using a more parsimonious architecture consistent with György Buzsáki (2019). The flexibility of splitter cell emergence indicates that these representations are likely byproducts of the navigation task, rather than innates structural modules dedicated to trajectory coding.

2   Materials and Methods

2.1   Environment

Task presentation.   The class of tasks called spatial alternation has been widely used to study hippocampal and working memory functions (Frank et al., 2000). For the purpose of our investigation, we simulated a continuous versions of the task, wherein an agent must navigate through an 8-shaped track and alternate between right and left choices at a decision point, then returns to the central corridor, essentially following an 8-shape trace while moving (see the 'LR' task of Figure 2-A). This 8-maze environment offers an ideal setup for observing splitter cells when the agent enters the central corridor, because the agent can have various past trajectories leading to the central corridor and different future trajectories upon exiting it. A more challenging variant requires the agent to alternate every two loops (see 'LL-RR' task in Figure 2-B), generating left-left-right-right sequences. This variation allows trajectories with the same past but different futures (e.g., right-left vs. right-right) or different pasts but the same future (e.g., right-right vs. left-right), allowing to distinguish between retrospective splitter cells (encoding past trajectories) and prospective splitter cells (encoding future trajectories).

2.2   Modeling framework

Reservoir computing.   Solving an alternating task necessitates the presence of a functional working memory, as the agent must retain information about its previous direction, such as turning right in the prior loop, to inform its decision to turn left at the

Figure 2: **A-B. An expanded view of a T-Maze**. **A**. The first task involves alternating every time it is located at the decision point, consequently doing the sequence of decision 'R-L-R-L-R...' . **B**. The second task involves alternating every two times, consequently doing the sequence of decision 'R-R-L-L-R-R-...' . **C. Recording area of the splitter cells.** In the red zone, the agent commits to left (L); in the blue zone, to right (R). The grey region in the central corridor indicates the area where splitter cell activity is recorded. Markers C1, C2, and C3 correspond to specific locations used to track neural activity within this recording zone. The left and right cues act as salient signals presented when the bot enters the central corridor, indicating which direction to take at the upcoming decision point. Unlike externally provided cues, these signals are generated internally by the model itself. **D. Snapshot of simulation.** Each ray represents a distance sensor reading from the bot, and the dotted line indicates its trajectory. These visualizations allow to assess whether the model successfully completes the task. **E. Ambiguous egocentric sensory inputs during the agent simulation**. In several locations within the maze, such as when the bot is at positions A and B, the sensors record identical distance values despite the bot being in different positions. Additionally, there are instances where the bot, despite being at the same location, receives varying inputs, as seen in the comparison between positions B and C, illustrating the model's challenge in handling ambiguous sensory information. **F. Model Architecture.** The model consists of 8 sensor inputs, a reservoir, and a motor output representing the change in relative orientation. Black arrows indicate fixed connections, while red arrows represent plastic, trainable connections. Two versions of the model: the *regular model* takes sensor inputs and outputs the next orientation change; and the *self-generated cues model* includes two readouts: one for predicting the next orientation change and another one for generating the next cue. This cue is then fed back into the model as an additional input. The model receives both sensor values and the self-generated cue as input.

subsequent decision point. Reservoir computing is thus a natural choice because of its fading memory propertyPascanu and Jaeger (2011). This enables the system to retain past experiences, facilitating their recall for subsequent decisions. Moreover, the reservoir computing approach has been shown to exhibit some biologically plausible characteristics (Lukoševičius and Jaeger, 2009). Consequently, our model consists of a reservoir computing network of type Echo State Network (ESN) (Jaeger, 2007) that controls the movement of the agent solving a continuous navigation task in the 8-maze of Figure 2-A/B. An ESN is a recurrent neural network (called reservoir) composed of randomly connected units, associated with an input and an output layer. As shown in Figure 2-F, inputs are projected into the reservoir, a nonlinear, high-dimensional space, enabling the integration of information across time and space. Only the output units, referred to as readout neurons (highlighted in red), are trained. The reservoir neurons follow the dynamics:

$$\frac{1}{\alpha}\frac{d\mathbf{x}}{dt} = -\mathbf{x} + \tanh(W.\mathbf{x} + W_{in}.\mathbf{u}) \quad \text{and} \quad \mathbf{y} = W_{out}.\mathbf{x} \tag{1}$$

where $\mathbf{x}$, $\mathbf{u}$ and $\mathbf{y}$ represent the reservoir states, input, and output. W, W_{in}, and W_{out} are weight matrices, while $tanh$ refers to the hyperbolic tangent function. α refers to the leak rate, a crucial parameter of the ESN that plays a central role in controlling the memory and timescale of the network's dynamics: a low leak rate indicates a longer memory and a slower dynamics, whereas a high leak rate leads to a shorter memory but a higher speed of update dynamics (Lukoševičius, 2012). The model was built thanks to the python library ReservoirPy (Trouvain et al., 2020).

Training. Only the output weights W_{out} are trained, using supervised learning with linear ridge regression method (the Tikhonov regularization) on pre-generated data:

$$W_{out} = Y^{target}X^T(XX^T + \beta I)^{-1} \quad \text{with} \quad X = [1, \mathbf{u}, \mathbf{x}] \tag{2}$$

where Y^{target}, β and I are respectively the target signal to approximate, the regularization coefficient and the identity matrix.

To generate training data, we implemented a simple Braintenberg vehicle (Braitenberg, 1986) where the agent moves automatically with a constant speed and changes its orientation according to the values of its sensors. The model takes as input the sensor values $S_0, ..., S_n$ of the agent and outputs the next variation of orientation $d\theta$ (see Figure 2-F). At each time step the sensors measure the distance to the walls and the bot turns in order to avoid the walls. Since the Braitenberg algorithm is designed solely for obstacle avoidance, the desired trajectory is initially shaped by temporarily adding walls at key intersection points. These walls are then removed, and the agent repeats the trajectory without them, ensuring the correct sensory inputs are recorded in the absence

of the guiding structures. The sensors are limited in their ability to calculate distance, saturating for distances exceeding 100 distance units. Additionally, the sensor readings are affected by Gaussian noise, represented as $N(0, 0.03)$. A reading of 0 indicates proximity to an object, while a reading of 1 signifies that the object is far away or not detected. The sensors can record identical distance values even when the bot is not at the same spatial location in the maze, as illustrated in Figure 2-E. The challenge for the model lies in disambiguating this sensory information to accurately determine the bot's location. The decision to use distance sensors as input provides a simplified egocentric representation of the environment, abstracting the complexities of the multiple sensory modalities involved in visual and auditory processing that animals like rats typically utilize. We argue that this simplification is justified: despite their simplicity, distance sensors still yield ambiguous sensory signals, preserving a key challenge of real-world navigation. Moreover, certain animals, such as bats (Wenstrup and Portfors, 2011) and others (Brinkløv et al., 2013; Evans, 1973), use echolocation to obtain distance-based information analogous to these sensor readings. Notably, egocentric boundary cells that likely contributing to hippocampal input in the medial entorhinal cortex (mEC), also encode similar spatial information (Long et al., 2025).

At each timestep, the position of the bot is updated as follows:

$$
\begin{aligned}
\theta(t) &= \theta(t-1) + 0.01 \sum_i \alpha_i s_i & (3) \\
p(t) &= p(t-1) + 2 * (cos(\theta(t)) + sin(\theta(t))) & (4)
\end{aligned}
$$

where $p(t)$ and $p(t+1)$ are the positions of the agent at time step t and $t+1$, $\theta(t)$ is the orientation of the agent, calculated as the weighted (α_i) sum of the values of the sensors s_i. The norm of the movement is kept constant and fixed at 2.

The regular and the self-generated cue model. We introduce two model variants depicted in Figure 2-F. The regular model relies solely on sensory input from the bot to make decisions. Its variant, the self-generated cue model, includes two readouts: one for predicting the next change in orientation, and another for generating a cue. These cues, interpretable as visual indicators within the central corridor (see Figure 2-C), signal to the agent which direction to take at the upcoming decision point: "L" for left and "R" for right. In more classic setups, such cues are typically provided by the environment; here, they are self-generated by the model. They correspond to binary values, set to 1 when the agent is expected to turn in the corresponding direction, and are only active when the agent enters the central corridor. This self-generated cue is fed back into the system as an additional input, allowing the model to receive both the sensory data and the generated cue.

2.3 Analysis

Task solving. After the training phase, we look at the model's ability to solve the task by directly looking at the online simulation whose snapshot is depicted in Figure 2-D. If the bot can perform the navigation task for at least five loops (one loop is composed of 700 time steps with one alternation, going one time to the right and one time to the left), the model is considered to have successfully solved the task.

Single-cell level analysis. We analyze the mean firing activity of individual neurons within the reservoir to identify splitter cells. These neurons exhibit different firing rates along overlapping segments of distinct trajectories. To detect such cells, we applied the ANCOVA (Analysis of Covariance) method described in Box 3 of Duvelle et al. (2023), originally used in hippocampal studies (Wood et al., 2000; Kinsky et al., 2020). This statistical technique tests for significant differences in firing rates across behavioral conditions. Neuronal firing are recorded as the agent traversed the central stem of the T-maze, a shared segment of both trajectories (see Figure 2-C). Firing rates are grouped by trajectory direction: right-to-left (RL), left-to-right (LR), right-to-right (RR) and left-to-left (LL). For each trajectory, we record at 15 activity sequences. The main ANCOVA factor was trajectory direction (x-axis in Figure 2-C), with the agent's lateral position (y-axis) and orientation included as covariates. These covariates account for variability in position and heading along the central corridor. Speed was not included as a covariate, as it remained constant throughout the experiment. We classified neurons as splitter cells if the ANCOVA revealed a statistically significant difference in firing rates between RL and LR conditions with $p < 0.001$. Detected splitter cells were visualized using raster plots of their firing activity recorded along the central corridor. Their activity was converted to dynamic firing rates using a Poisson process model (Heeger et al., 2000; Dayan and Abbott, 2005), with each neuron's activity scaled accordingly:

$$f_{rate}(t) = baseline\_rate + V(t) \times max\_rate\_change \tag{5}$$

where $f_{rate}(t)$ corresponds to the computed firing rate at time t, $V(t)$ is the normalized activity of the reservoir neuron at time t, $baseline\_rate$ is the baseline firing rate (in spikes per second) and set to 45 and max_rate_change is the maximum deviation from the baseline also set to 45. The firing rate is subsequently converted into spike counts using a Poisson process:

$$count_{spike}(t) \sim \text{Poisson}(f_{rate}(t) \times dt) \tag{6}$$

where $count_{spike}(t)$ represents the number of spikes occurring at time t, given the firing rate $f_{rate}(t)$. The Poisson process models the probabilistic occurrence of spikes over time with its paramater $\lambda = f_{rate}(t)dt$.

Population-level analysis. We analyze the reservoir state of the ESN at the population level using Principal Component Analysis (PCA) as a dimensionality reduction technique to identify patterns and significant features within the processed data.

Lesioning splitter cells within the model. We investigated the effects of lesioning the detected splitter cells within the model. To do so, we inactivate the connections associated with the splitter cells by setting their weight values to 0 in W_{in}, W, and W_{bias}. The resulting model is denoted as the *Lesioned model* (see Figure 5).

Decoding spatial information associated with other hippocampal cell types. In addition to splitter cells, we explore whether the reservoir's dynamical systems could encode other hippocampal cell-related activities, such as head-direction, decision, and position. We employ an additional readout, referred as the "decoder readout", trained using offline supervised learning to decode their activity. The decoder was trained on 7500 time steps and tested on 2500 time steps, with a regularization factor of $1e - 3$ for all readouts. Head-direction cells, which fire in response to a specific orientation, are decoded by generating output vectors representing eight distinct orientations intervals: $[(-\pi, -3\pi/4), (-3\pi/4, -\pi/2), (-\pi/2, -\pi/4), (-\pi/4, 0), (0, \pi/4), (\pi/4, \pi/2), (\pi/2, 3\pi/4), (3\pi/4, \pi)]$. For example, if the bot's orientation is between $3\pi/4$ and π, the output vector will be $[0, 0, 0, 0, 0, 0, 0, 1]$. For decision, we generate training data by recording the bot's next decision (right or left) at one of the intersection point following the central corridor, labeling these decisions as 0 (left) or 1 (right). For position, the training data was the sequence of coordinates of the bot's trajectory. To complement this analysis, we tested whether spatial information could be directly decoded from sensory inputs using a Support Vector Machine (SVM) (Cortes and Vapnik, 1995) to predict the robot's position, orientation, or decision.

3 Results

3.1 Model performances

We conducted four experiments in total: (1) the regular model on the 'LR' task, (2) the regular model on the 'LLRR' task, (3) the self-generated cue model on the 'LR' task, and (4) the self-generated cue model on the 'LLRR' task (see Figure 2). Each experiment was run with 10 different random seeds, corresponding to 10 distinct random initializations of the input (W_{in}) and recurrent (W) connectivity matrices within the reservoir.

For the 'LR' task, both the regular and self-generated cue models successfully completed the task across all 10 seeds. Hyperparameters (detailed in the Tables section) were manually optimized and showed strong robustness, consistent with findings from Antonelo and Schrauwen (2015). Although we used 1000 reservoir units, similar performance was achieved with 500 units when other parameters were adjusted accordingly. Input/output connectivity could vary widely without affecting performance. The most sensitive parameters were the leak rate and the spectral radius, which jointly control the dynamics of the model, the memory, and the stability. Regularization was also important to prevent overfitting. For efficiency, the remainder of the analysis was conducted using the offline learning rule due to the slower convergence of online learning.

In the 'LLRR' task, the self-generated cue model succeeded consistently across all 10 seeds, whereas the regular model failed since it could navigate for only two loops (in average and below the five-loop success threshold). It is to be noted that this task is more demanding, as it requires remembering the last two decisions instead of just one, increasing the working memory demand. The self-generated cue model overcomes this limitation thanks to the presence of the internal cues, which act constantly to tell which decision to take next, and reduce the need for persistent memory within the reservoir. In contrast, the regular model appears to lack sufficient working memory to solve the task.

Table 1: Task performance summary for each model. A task is considered successful if the model completes at least 5 loops on average across 10 seeds.

Task	Regular Model	Self-Generated Cue Model
LR	Success	Success
LLRR	Fail (avg. < 5 loops)	Success

3.2 Splitter cells

3.3 Splitting effect at the single cell level

We replicate the analysis from Duvelle et al. (2023) to assess whether their hypotheses about splitter cells also apply to our reservoir-based models. Splitter cells were identified in the regular model and, notably, also emerged in the self-generated cue model for both tasks. This is an interesting result, as the self-generated cue model does not rely on splitter cells to encode past or future directions: the cues explicitly inform the model at each time step in the central corridor which direction to take next, greatly reducing the need for working memory, and thus for cells encoding past and future trajectories.

Yet, splitter cells still emerge, suggesting that their presence is not strictly tied to task demands. The average number of splitter cells for each model and task is shown in Table 2.

Table 2: Average number of splitter cells across 10 seeds for each model-task combination.

Task	Regular Model	Self-Generated Cue Model
LR	217.3 ± 148.2	326.7 ± 138.5
LLRR	—	402.5 ± 159.1

Examples of splitter cell activity are shown in Figure 3-A, which displays the firing patterns of six splitter cells from the self-generated cue model model as the bot traverses the central corridor (grey zone in Figure 2-B) during the LR task. Each trace shows the firing activity of a single splitter cell over 50 time steps within the corridor, averaged across 15 traversals per trajectory. Clear differences in activity can be observed: red traces correspond to trials where the bot moves from right to left ('RL'), and blue traces to left-to-right ('LR') movements (see color code in Figure 2-B). Raster plots generated using a Poisson process, shown in the lower panels of Figure 3-A, further illustrate the average firing activity of this subset of splitter cells during central corridor traversal. Comparable patterns are observed with the regular model on the same task.

Figure 3-B shows similar results for the 'RR-LL' task, with the two first rows that shows the activity of four splitter cells from the self-generated cue model. Additionally, this task allows one to distinguish between prospective and retrospective splitter cells. Notably, the cells in the first row are prospective: they differentiate between trajectories that share the same past but have different futures (e.g., 'LR' and 'RR' (right-to-right) vs. 'LL' (left-to-left) and 'RL'). In contrast, the cells in the second row are retrospective: they differentiate between trajectories with the same future but different pasts (e.g., 'LR' and 'LL' vs. 'RL' and 'RR'). For comparison, the last row shows cells that are not splitter cells, as they exhibit no detectable splitting effect across different trajectories.

Figure 3: **Comparing firing rates of individual splitter cells in the central stem**. The identification of these cells was achieved using the ANCOVA method, which revealed significantly different firing activities ($p < 0.001$) in overlapping trajectories 'RL' (blue), 'LR' (red), 'RR' (yellow), 'LL' (green). The activity of splitter cells is recorded when the bot enters the central corridor (grey zone in Figure 2-B). Each trace represents the firing activity of a splitter cell in the central corridor over 50 time steps. Each line corresponds to the mean firing activity of at least 5 traversals, and the shaded areas indicates the standard deviation. Bellow each graph, the corresponding raster plots are depicted showing a difference in spiking activity rate between the overlapping trajectories during one traversal. **A**. Splitter cells in the regular model for the LR task. Comparable patterns are observed with the self-generated cue model on the same task. **B**. Prospective cells, retrospective cells and non splitter cell in the self-generated-cue model for the 'LL-RR' task. The two cells in the first row are prospective: they differentiate between trajectories that share the same past but have different futures (e.g., LR and RR vs. LL and RL). The two cells in the second row are retrospective: they differentiate between trajectories with the same future but different pasts (e.g., LR and LL vs. RL and RR). The last row shows two cells are not splitter cells, as they exhibit no detectable splitting effect across different trajectories. These patterns were not observed in the regular model on the same task, as the model failed to successfully complete it.

3.4   Splitting effect at the population level

Temporal Context Model versus Latent State Inference Model.   The splitting effect refers to distinct neural trajectories in neural state space when the animal occupies the same spatial location. This is illustrated in Figure 1-B, where Duvelle et al. (2023) hypothesize neural activity patterns during an alternation task. Two distinct trajectories are shown: one for movement from the central corridor to the left arm, and one from the same central corridor to the right arm. In the middle panel, these trajectories occupy separate regions in PCA space even though the animal is at the same spatial location, indicating a splitting effect. In contrast, the right panel illustrates the absence of a splitter signal: the neural trajectories fully overlap, corresponding to the same physical location and indistinguishable neural activity.

Furthermore, Duvelle et al. (2023) suggest that the splitting effect can be studied through the lens of two different models introduced in Figure 4-C. First, the "Temporal Context Model" (TCM) emphasizes sensitivity to prior experiences, meaning the animal's current neural state depends on its recent history. When recent pasts are similar, population activity at a given location exhibits closer proximity in PCA space. Conversely, when the recent past differs, the distances increase. This phenomenon is demonstrated by the varying distances between the markers C1, C2, and C3, each representing specific positions within the central corridor. When the animal reaches C1 in the maze, it has traversed the entire central corridor, resulting in a shared trajectory that accounts for the smaller distance between the C1 markers. In contrast, the animal's past experiences at C3 differ significantly, which explains the greater distance between the C3 markers. Second, the "Latent State Inference" (LSI) organizes experiences into discrete states, resulting in a neural state less sensitive to historical context. As a result, the distances between the two neural trajectories in the central corridor remain constant: the distance between C1 markers is equal to the one between C2 markers and C3 markers. In the LSI model, experiences can be categorized into distinct states without strong dependencies on past experiences. For example, in scenarios where each stimulus is associated with a specific state, the categorization remains valid regardless of how previous stimuli were encountered. Duvelle et al. (2023) illustrates this with the example of one arm being rewarded while the other is not.

Implicit approximation of the state-space environment and splitting effect at the population level.   We proceed to a similar population analysis by applying 3D PCA to the reservoir states. This analysis was performed on all 10 seeds for both the regular and self-generated cue models. Examples from one seed of each model are shown in Figure 4-B1 and B2. he blue trace indicates the agent has just completed the left loop and is in the central corridor; the red trace corresponds to the agent having just

Figure 4: **A. TCM vs. LSI** from Duvelle et al. (2023). In the PCA space illustrating the TCM, the population activity at a specific location exhibits closer proximity in PCA space when the recent past is similar and greater distance when it is less similar. This is demonstrated in the distances between markers C1, C2, and C3. In the PCA illustrating the LSI, the distances between the markers C1, C2, and C3 don't vary. The **B. PCA during the 'LR' task**. **B.1**. PCA applied to the regular model, resembling the TCM model. The increasing distances between C1, C2, and C3 markers suggest an amplified influence of past trajectories on neural activity. **B.2**. PCA applied to the self-generated cue model, resembling the LSI model. The distances between C1, C2, and C3 markers remain constant, indicating more distinct neural activity between the two trajectories due to the presence of the cues. **C. PCA during the 'LR' task over sevral trajectories**. **C.1** Same as B.1 but for several loops. **C.2** PCA distance d_{intra} between two identical trajectories (PCA distance between RL and RL, and LR and LR) and d_{inter} between two different trajectories (PCA distance between RL and LR). The figure shows the average over 10 different seeds, each seed containing 15 passes per trajectory. We observe that $d_{intra} < d_{inter}$ until d_{inter} becomes sufficiently small, consistent with the behavior expected under a TCM. This demonstrates that the TCM and LSI do not arise from variations in the bot's lateral position, but rather because the two activity patterns originate from different trajectories **D.1** Same as B.2 but for several loops. **D.2** Same as C.2 but with the self-generated cue model. We observe that $d_{intra} < d_{inter}$ consistently across all positions. **E.PCA during the 'LL-RR' task**. **E.1** The regular model fails to distinguish LL from RL and RR from RL, consistent with its inability to complete the task. **E.2** The self-generated cue model clearly separates all four trajectories, aligning with its successful task performance.

completed the right loop. These two trajectories occupy distinct regions in the PCA space, despite they share the same location. The three markers (C1, C2, C3) indicating specific positions within the main corridor are distinctly separated with a measurable PCA distance, demonstrating the presence of splitter cells. Figures 4-C1 and D1 show the same PCA analysis while the bot traverses the central corridor across multiple loops. The PCAs show two linearly separable sub-attractors, corresponding to the two loops of the 8-shape. This result demonstrates the ESN's ability to implicitly approximate the state-space of the 8-maze environment through continuous temporal dynamics. The model achieves this by mapping the input data into a higher-dimensional space (Jaeger, 2001). The recurrent connections within the reservoir enable the network to incorporate and reverberate past information, allowing for the encoding of temporal context and the integration of the past trajectory.

The regular model corresponds the TCM.   In the regular model, we observed decreasing distances between C1,C2 and C3 markers in the central corridor (Figure 4-B1, C.1 and C.2), which aligns with the TCM (Figure 4-A). This is expected, as the model is influenced not only by current sensory inputs but also by recently experienced events, as the past trajectory of the bot is stored through the reverberation of recurrently connected neurons, allowing for a context-dependent response to present events.

The self-generated cue model corresponds the LSI.   In contrast, in the self-generated cue model, the distances between neural trajectories increase or remain stable as the bot enters the central corridor (Figure 4-B2, D.1 and D.3), reflecting a stronger association with one of the two discrete states (right or left). The presence of contextual cues provides direction information at each time step within the central corridor, positioning the model in a more discrete configuration. Consequently, the model does not require extensive memory of the past trajectory to successfully complete the navigation task. Figures 4-C2 and D2 show d_{intra}, the PCA distance between identical trajectories (e.g., RL vs. RL and LR vs. LR), and d_{inter}, the distance between different trajectories (RL vs. LR). Distances are averaged over 10 seeds, each comprising 15 passes per trajectory. At the C3 marker for the regular model (Figure C.2), and consistently across all positions for the self-generated cue model (Figure D.2), d_{inter} is significantly greater than d_{intra}. This indicates that the differences in neural activity are driven by distinct underlying trajectories, rather than minor lateral variations within each trajectory.

Differentiation of retrospective and prospective cells at the population level.   Figure 4-E shows a 3D PCA of internal states during the RR-LL task for the regular model,

which failed after two loops. The left subpanel spans the full maze; the right focuses on the central corridor. No clear separation is observed between trajectories. In particular, the model fails to distinguish LL from RL and RR from RL. This likely reflects insufficient memory capacity to represent the four required sequences, contributing to task failure. In contrast, the self-generated cue model, which successfully completed the task beyond five loops, shows well-separated neural trajectories in the 3D PCA, as illustrated in Figure 4-E2. In the right subpanel, the four trajectories are clearly distinguished within the central corridor, and the full-maze PCA in the left subpanel also reveals a better separation between the two loops. The separation between RR and LR, and between RL and LL, reflects retrospective coding, neuronal activity differs depending on past trajectories. Conversely, the separation between LL and LR, and between RR and RL, indicates prospective coding, activity differs based on upcoming paths.

Together, these findings support and extend the hypotheses proposed by Duvelle et al. (2023) regarding the properties of splitter cells. We observe TCM-like activity in the regular model and LSI-like activity in the self-generated cue model. Furthermore, the ability to successfully complete the task may be linked to the presence of a population-level splitting effect. In cases where the model fails to generate distinct neural trajectories, it also fails to accomplish the task, reinforcing the importance of trajectory differentiation in successful performance. Notably, even when sensory cues reduce memory demands, splitter cells still appear, providing further support that they are likely a byproduct of the behavior itself and emerge as long as the task is performed, regardless of whether they are functionally required.

3.5   Silencing splitter cells inside the models

Table 3: Average number of splitter cells across 10 seeds before and after lesioning the splitter cells during the 'LR' task

Model state	Regular Model	Self-Generated Cue Model
Intact	217.3 ± 148.2	326.7 ± 138.5
Lesioned	256.7 ± 93.6	216.2 ± 64.8

Dynamic emergence of splitter cells supports persistent task performance.   During the LR task, we identified an average of 217 splitter cells (SC1) in the regular model and 326 in the self-generated cue model across 10 seeds, as depicted in Table 3. All SC1 cells were subsequently silenced in both models, as illustrated in Figure 5-A.1 and A.2. The readout layers were re-trained using the same hyperparameters, without modifying the structural connectivity (see Figure 5-A.1). Despite SC1 inactivation, the lesioned

Figure 5: **A. Silencing all splitter cells in the model**. **A.1-2**. Yellow cells represent splitter cells (SC), and those marked with a black cross are the silenced ones. First, all splitter cells are identified in the full model with or without cues (left). They are subsequently silenced, resulting in the lesioned model (right). The lesioned model is still able to perform the task, and a new set of splitter cells (SC2) emerges. **A.3. Activity of selected cells before and after lesioninf**. Each row shows the activity of the same neuron across both models. These cells did not exhibit a splitting effect before the lesion but developed one afterward. This change highlights how lesioning induces a re-organization of the model's dynamics. **A.4. 3D PCA**.The splitting effect is still visible at the population level after lesion. **B. Snapshot of bot navigation and position predictions**. The grey dotted line indicates the bot's actual trajectory, while the red dotted line represents the predicted position at each time step based on the reservoir state. The decoder readout effectively tracks the bot's position within the maze from the reservoir states (left) but not from the sensory input (right). **B. Orientation prediction.** The bot's orientation is monitored over approximately 4000 time steps (black dotted line). The reservoir state enables highly accurate predictions of the bot's next orientation (in red) from the resevoir states (top) but not from the sensory input (bottom). **C. Decision prediction**. Over 4000 time steps, the reservoir state reveals early internal shifts after the decision point. These shifts enable predictions within just a few dozen time steps—that the bot will switch direction at the next decision point (top). Predicting the next decision is not possible from the sensory inputs (bottom).

models in both conditions successfully performed the alternation task across all seeds. On average, 256 new splitter cells (SC2) emerged in the lesioned regular model, and 216 SC2 in the lesioned self-generated cue model (see Table 3). Figure 5-A.3 shows examples of cells that were not initially splitter cells but became so after lesioning, and Figure 5-A.4 shows that the splitting effect at the population level is still observable after lesion. These findings indicate that silencing SC1 triggered a reorganization of the internal dynamics, giving rise to a new population of splitter cells (SC2). Thus, this result supports the idea that as long as the model performs the alternation task, splitter cells are likely to emerge from different neural populations. They reflect a flexible coding mechanism tied to task demands, rather than static circuit features. Similar reorganization was observed when silencing SC1 in the self-generated cue model during the LL-RR task, where 8 out of 10 seeds still succeeded.

Decoding position, decision, and head direction from the internal state of the reservoir. Three readouts were added to the reservoir to extract additional spatial information as the bot navigated, referred as decoder readouts. The first decoder accurately identified the bot's position with 96% accuracy, consistently activating the correct location on the map, mimicking the behavior of place cells (Figure 5-A). The second decoder predicted the bot's next decision with 84% accuracy. As shown in Figure 5-B, after a right turn, the reservoir state evolved to favor a left turn, indicating that internal dynamics anticipate future choices. The third decoder achieved 94% accuracy in estimating head direction, confirming that orientation is also reliably embedded in the reservoir's internal states (Figure 5-C). These results demonstrate that spatial information of the bot can be decoded from the reservoir thanks to its capacity of implicitly approximate the state-space of the environment.

Sensor-Based Decoding. In contrast, applying the same decoding techniques directly to raw sensor inputs failed to predict position, head-direction, or decision as depicted in Figure 4.-B,C and D. This confirms that the reservoir's internal states encode critical space information, while the ambiguous sensory data alone does not.

Forced mode. Since the reservoir remains fixed during both training and testing (i.e., fixed W_{in} and W in Equation 1), training does not alter the architecture and therefore has no impact on splitting activity. To avoid retraining for every condition, we instead forced the model to perform the task by feeding it the exact sensory inputs the bot would receive if it were alternating correctly. This approach enabled us to systematically evaluate a wide range of conditions and hyperparameter settings without requiring optimization or training.

Cumulative lesion of splitter cells. In forced mode, we conducted cumulative lesioning of splitter cells across 10 different seeds. Specifically, we repeatedly silenced all identified splitter cells, ran the model to allow new splitter cells to emerge, silenced them again, and repeated this process iteratively. The results, shown in Figure 6-A, begin with a reservoir of 1000 units, with each iteration reducing the reservoir size as splitter cells are cumulatively silenced. Remarkably, new splitter cells continued to emerge up to iteration 8, and decoding accuracy for position, orientation, and decision remained stable across all lesioned models as shown in Figure 6-B. The consistent emergence of splitter cells and the continued decodability of task-relevant information support the idea that these representations are byproducts of correct task execution, rather than fixed prerequisites for behavior. This view aligns with Luo et al. (2024), who argue that cell types like place and grid cells may not be essential circuit components but instead arise inevitably from task constraints and behavior. In their study, spatial decoding also remained intact even after removing units classified as spatial cell types, indicating that these representations are neither unique nor necessary.

Figure 6: **Cumulative lesion of splitter cells.** The curves shows the mean across 10 seeds the shaded area represents the standard deviation **A**. Number of splitter cells per model after cumulative lesioning. **B**. Decoder accuracy for position, decision and orientation following cumulative lesioning.

The number of splitter cells depends on the reservoir hyperparameters. In forced mode, we tested different values of spectral radius, leak rate, and recurrent connectivity, examining their effects on both the number of splitter cells and decoder accuracy. Results are shown in Figure 7, based on simulations run over 10 seeds per hyperparameter setting, using the regular model on the LR task. Figure 7-A shows that the number of splitter cells increases with the spectral radius. Figure 7-B indicates an optimal leak rate around 0.15, corresponding to the peak number of splitter cells. In contrast, Figure 7-C demonstrates that the connectivity of W has no significant effect on splitter

cell count. These trends align with decoder performance shown in Figure 7-D,E and F: position, decision, and orientation decoding are most accurate at the same leak rate that maximizes splitter cells, and decoding improves with increasing spectral radius. As with splitter cells, connectivity has no clear effect on decoding accuracy. Overall, these results suggest that specific reservoir properties, particularly spectral radius and leak rate critically influence the number of splitter cells and the quality of internal representations, while connectivity has little impact.

Figure 7: **Evolution of splitter cell count and decoder accuracy across hyperparameters**. Curves show the mean across 10 seeds, shaded areas represent standard deviation. Splitter cell count is shown as a function of **A**. spectral radius, **B**. leak rate, and **C**. reservoir connectivity. Decoder accuracy is shown as a function of **D**. spectral radius, **E**. leak rate, and **F**. reservoir connectivity.

4 Discussion

The model under consideration is characterized by its fundamental simplicity, consisting of a random recurrent network that is informed by sensors enabling the computation of directional changes. Despite this apparent simplicity, the model is able to solve a continuous and non-trivial alternating navigation task, using ambiguous, limited and egocentric sensory information. Inside that model, we've been able to demonstrate for the existence of splitter cells as described by Duvelle et al. (2023) in their review. By replicating their analyses on the reservoir, we identified activities indicative of splitter cells in rodents and demonstrated their re-emergence following targeted lesions and subsequent retraining. Furthermore, we've also validated the proposed theoretical framework by developing a model that incorporates concepts from both TCM (Temporal Context Model, Howard and Kahana (2002)) and LSI (Latent State Inference, Gershman and Niv (2010)). Strikingly, we showed that splitter cells emerge even in configurations where working memory is not required for task performance. Moreover, they are dynamic and adaptable: across multiple lesioning experiments, new splitter cells consistently appeared as long as the model performed the alternation task. Collectively, these findings imply that splitter cells may not serve as essential precursors for task execution, but rather emerge as byproducts of it. However, it is still unclear whether this byproduct can serve as an internal representation in other contexts, though it is conceivable that its emergence could support broader application.

Even though we did not claim any architectural plausibility with the hippocampal formation, the structure of the model is reminiscent of the CA3 structure with its highly recurrent nature, with the notable absence of learning inside the reservoir. In our case, the learning process is a simple linear identification of a random pattern of activity inside the reservoir in order to issue the proper motor command. This process is indeed well aligned with György Buzsáki (2019)'s inside-out view of the brain, where he suggests that brain activity is not generated from scratch during exploration and learning. According to this view, the brain can be considered as a vast reservoir capable of generating an extensive repertoire of neuronal patterns, initially independent of experience. In other words, these patterns have initially no meaning and acquire it through exploration and learning. In this sense, experience is primarily a process of matching preexisting neuronal dynamics to outside events, and learning does not create new brain activity from scratch, but rather selects preexisting pattern of activity responding to the external stimuli.

This "inside-out" view of brain function is supported by Langston et al. (2010), showing that spatial memory cells and their properties are already present when young pups first begin to move or even emerge early in postnatal development, before signif-

icant spatial exploration takes place (Muessig et al., 2016; Wills et al., 2014). These studies indicate that the hippocampus is capable of generating a wide range of possible neuronal trajectories even before the organism begins exploring its environment. On this regards, it is interesting to note that the randomness of the network in our model is not strongly constrained such that any matrix with the proper spectral radius will provide a sufficiently rich reservoir of dynamics from which the behavior can be acquired. Furthermore, in case of targeted lesion, it is relatively easy for the model to re-acquire a behavior based on the new dynamics inside the reservoir, leading to the emergence of new splitter cells. The concept of splitter cells bears a striking resemblance to the notion of mixed selectivity (Rigotti et al., 2013), which refers to the property of neurons that respond to multiple, statistically independent variables or task-relevant aspects. This characteristic is a well-established property of reservoir-type networks which emerges due to the random connectivity and dynamic nature of such networks (Enel et al., 2016; Scleidorovich et al., 2022; Dominey, 2024) and is also observed in primate cortical neurons (Rigotti et al., 2010; Tye et al., 2024). The emergence of new splitter cells when existing ones are silenced suggests that mixed selectivity is an inherent property of recurrent networks. When cells displaying mixed selectivity are removed, a new network topology is created, inevitably giving rise to mixed selectivity once again. This feature enables the reservoir to represent complex combinations of inputs and internal states, which is crucial for processing temporal information and solving complex cognitive tasks.

Beyond splitter cells, we also decoded the bot's position, head direction, and upcoming decision from the activity units, information that echoes features of place cell, head direction cell, and decision cell activity. Even though we did not look for each and every other type of cells, we're confident that we would probably be able to decode them. Remarkably, spatial and decision-related information remained decodable even after repeatedly lesioning all identified splitter cells in the model. This strongly suggests that their activities do not derive from structure nor learning (we have no learning, and no feedback inside the reservoir) but are rather indicative of a correlation with some pre-existing dynamics that are linked to the actual behavior. Considering for example decision cells (indicating decision to go left or right), it comes as no surprise that we can identify them inside the reservoir since the agent is really going left or right at the end of the central corridor, at least for an external observer. For the agent however, the sensory world is fully described by a set of eight sensors that do not convey the notions of *left* or *right*. Ultimately, this means that these decision cells may only exist in the eye of the observer. In other words, if a reservoir can solve a task with a minimal set of inputs, any variable that can be decoded from the activity of the reservoir derived from the resolution of the task itself as opposed to the specificity of structures involved in

the resolution. This interpretation resonates with the CRISP model proposed by Cheng (2013), which argues that sequential activity patterns in CA3 are intrinsic to the network rather than imposed by external cortical inputs. According to this view, CA3 contains a reservoir of pre-established intrinsic sequences that serve as a substrate onto which external experiences are mapped via synaptic plasticity in feedforward projections, rather than through plasticity in recurrent CA3 connections.

Finally, during the past decade, the understanding of neural coding has gradually shifted from a population vector sum where a behavioral output is generated when the sum exceeds a threshold, to a more complex theory that involves multidimensional neural activity space (Churchland and Shenoy, 2024). This theoretical framework implies several subspaces: a null space, that refers to the subspace of neural activity that does not directly affect certain output variables, and a task-relevant subspace. In this context, splitter cells (and any other task related cells) reflect only a small partial dimension of the global encoding of the neuronal population. Disturbing the whole multidimensional space by silencing specific neurons induces a general reorganization of the neuronal activity that affects the neural response of the remaining neurons to the task, hence "creating" new splitter cells, place cells, etc. This reorganization may, with some training, allows the network to adapt and to reproduce the same behavioral output as before. If we demonstrated how this can be achieved using supervised offline and online training inside the model, the question of continuous and gradual adaptation remains open.

5 Table

Table 4: Model parameters when using offline linear regression learning

Model/Task	Reg. LR	Self-gen LR	Reg. LLRR	Self-gen LLRR
Input size	8	10	8	10
Number of units	1000	1000	1000	1000
Input connectivity	0.20	0.10	0.06	0.10
Reservoir connectivity	0.10	0.10	0.10	0.10
Spectral radius	0.99	0.99	0.99	0.999
Leak rate	0.10	0.15	0.08	0.08
Warmup steps	500	500	500	500
Regularization	1e-5	5e-4	8e-6	1e-4

6   Code availability

The code associated with this work is publicly available on GitHub at
https://github.com/naomichx/splitter_cells_in_reservoir_2025

References

Antonelo, E.A., E. and Schrauwen, B. (2009). Unsupervised learning in reservoir computing: Modeling hippocampal place cells for small mobile robots. In *Artificial Neural Networks–ICANN 2009: 19th International Conference, Limassol, Cyprus, September 14-17, 2009, Proceedings, Part I 19*, pages 747–756. Springer.

Antonelo, E.A., E. and Schrauwen, B. (2012). Learning slow features with reservoir computing for biologically-inspired robot localization. *Neural Networks*, 25:178–190.

Antonelo, E.A., E. and Schrauwen, B. (2015). On learning navigation behaviors for small mobile robots with reservoir computing architectures. *IEEE Transactions on Neural Networks and Learning Systems*, 26(4):763–780.

Antonelo, E.A., E., Schrauwen, B., and Stroobandt, D. (2008). Event detection and localization for small mobile robots using reservoir computing. *Neural Networks*, 21(6):862–871.

Antonelo, E.A., E., Schrauwen, B., and Van Campenhout, J. (2007). Generative modeling of autonomous robots and their environments using reservoir computing. *Neural Processing Letters*, 26:233–249.

Braitenberg, V. (1986). *Vehicles: Experiments in synthetic psychology*. MIT press.

Brinkløv, S., Fenton, M. B., and Ratcliffe, J. M. (2013). Echolocation in oilbirds and swiftlets. *Frontiers in physiology*, 4:123.

Buzsáki, G. and Moser, E. I. (2013). Memory, navigation and theta rhythm in the hippocampal-entorhinal system. *Nature neuroscience*, 16(2):130–138.

Cheng, S. (2013). The crisp theory of hippocampal function in episodic memory. *Frontiers in neural circuits*, 7:88.

Churchland, M. M. and Shenoy, K. V. (2024). Preparatory activity and the expansive null-space. *Nature Reviews Neuroscience*, 25(4):213–236.

Cortes, C. and Vapnik, V. (1995). Support-vector networks. *Machine learning*, 20:273–297.

Dayan, P. (1993). Improving generalization for temporal difference learning: The successor representation. *Neural computation*, 5(4):613–624.

Dayan, P. and Abbott, L. F. (2005). *Theoretical neuroscience: computational and mathematical modeling of neural systems*. MIT press.

Dominey, P. F. (2024). A connectivity gradient in structured reservoir computing predicts a hierarchy for mixed selectivity in human cortex. In *2024 International Joint Conference on Neural Networks (IJCNN)*, pages 1–8. IEEE.

Duvelle, É., Grieves, R. M., and Van der Meer, M. A. (2023). Temporal context and latent state inference in the hippocampal splitter signal. *ELife*, 12:e82357.

Enel, P., Procyk, E., Quilodran, R., and Dominey, P. F. (2016). Reservoir computing properties of neural dynamics in prefrontal cortex. *PLoS computational biology*, 12(6):e1004967.

Evans, W. (1973). Echolocation by marine delphinids and one species of fresh-water dolphin. *The Journal of the Acoustical Society of America*, 54(1):191–199.

Frank, L. M., Brown, E. N., and Wilson, M. (2000). Trajectory encoding in the hippocampus and entorhinal cortex. *Neuron*, 27(1):169–178.

George, D., Rikhye, R. V., Gothoskar, N., Guntupalli, J. S., Dedieu, A., and Lázaro-Gredilla, M. (2021). Clone-structured graph representations enable flexible learning and vicarious evaluation of cognitive maps. *Nature communications*, 12(1):2392.

Gershman, S. J. and Niv, Y. (2010). Learning latent structure: carving nature at its joints. *Current Opinion in Neurobiology*, 20(2):251–256.

Golub, M. D., Sadtler, P. T., Oby, E. R., Quick, K. M., Ryu, S. I., Tyler-Kabara, E. C., Batista, A. P., Chase, S. M., and Yu, B. M. (2018). Learning by neural reassociation. *Nature neuroscience*, 21(4):607–616.

György Buzsáki, M. (2019). *The brain from inside out*. Oxford University Press.

Hartley, T., Lever, C., Burgess, N., and O'Keefe, J. (2014). Space in the brain: how the hippocampal formation supports spatial cognition. *Philosophical Transactions of the Royal Society B: Biological Sciences*, 369(1635):20120510.

Heeger, D. et al. (2000). Poisson model of spike generation. *Handout, University of Standford*, 5(1-13):76.

Howard, M. W. and Kahana, M. J. (2002). A distributed representation of temporal context. *Journal of Mathematical Psychology*, 46(3):269–299.

Jaeger, H. (2001). The "echo state" approach to analysing and training recurrent neural networks-with an erratum note. *Bonn, Germany: German National Research Center for Information Technology GMD Technical Report*, 148(34):13.

Jaeger, H. (2007). Echo state network. *scholarpedia*, 2(9):2330.

Kinsky, N. R., Mau, W., Sullivan, D. W., Levy, S. J., Ruesch, E. A., and Hasselmo, M. E. (2020). Trajectory-modulated hippocampal neurons persist throughout memory-guided navigation. *Nature communications*, 11(1):2443.

Langston, R. F., Ainge, J. A., Couey, J. J., Canto, C. B., Bjerknes, T. L., Witter, M. P., Moser, E. I., and Moser, M.-B. (2010). Development of the spatial representation system in the rat. *Science*, 328(5985):1576–1580.

Long, X., Bush, D., Deng, B., Burgess, N., and Zhang, S.-J. (2025). Allocentric and egocentric spatial representations coexist in rodent medial entorhinal cortex. *Nature Communications*, 16(1):356.

Lukoševičius, M. (2012). A practical guide to applying echo state networks. In *Neural Networks: Tricks of the Trade: Second Edition*, pages 659–686. Springer.

Lukoševičius, M. and Jaeger, H. (2009). Reservoir computing approaches to recurrent neural network training. *Computer science review*, 3(3):127–149.

Luo, X., Mok, R. M., and Love, B. C. (2024). The inevitability and superfluousness of cell types in spatial cognition. *bioRxiv*, pages 2024–01.

Maguire, E., Frackowiak, R. S., and Frith, C. D. (1996). Learning to find your way: a role for the human hippocampal formation. *Proceedings of the Royal Society of London. Series B: Biological Sciences*, 263(1377):1745–1750.

Moser, E. I., Moser, M.-B., and McNaughton, B. L. (2017). Spatial representation in the hippocampal formation: a history. *Nature neuroscience*, 20(11):1448–1464.

Muessig, L., Hauser, J., Wills, T., and Cacucci, F. (2016). Place cell networks in pre-weanling rats show associative memory properties from the onset of exploratory behavior. *Cerebral Cortex*, 26(8):3627–3636.

Pascanu, R. and Jaeger, H. (2011). A neurodynamical model for working memory. *Neural networks*, 24(2):199–207.

Raju, R. V., Guntupalli, J. S., Zhou, G., Wendelken, C., Lázaro-Gredilla, M., and George, D. (2024). Space is a latent sequence: A theory of the hippocampus. *Science Advances*, 10(31):eadm8470.

Rigotti, M., Barak, O., Warden, M. R., Wang, X.-J., Daw, N. D., Miller, E. K., and Fusi, S. (2013). The importance of mixed selectivity in complex cognitive tasks. *Nature*, 497(7451):585–590.

Rigotti, M., Rubin, D. B. D., Wang, X.-J., and Fusi, S. (2010). Internal representation of task rules by recurrent dynamics: the importance of the diversity of neural responses. *Frontiers in computational neuroscience*, 4:24.

Sanders, H., Wilson, M. A., and Gershman, S. J. (2020). Hippocampal remapping as hidden state inference. *Elife*, 9:e51140.

Scleidorovich, P., Weitzenfeld, A., Fellous, J.-M., and Dominey, P. F. (2022). Integration of velocity-dependent spatio-temporal structure of place cell activation during navigation in a reservoir model of prefrontal cortex. *Biological Cybernetics*, 116(5):585–610.

Stachenfeld, K. L., Botvinick, M. M., and Gershman, S. J. (2017). The hippocampus as a predictive map. *Nature neuroscience*, 20(11):1643–1653.

Trouvain, N., Pedrelli, L., Dinh, T. T., and Hinaut, X. (2020). ReservoirPy: An efficient and user-friendly library to design echo state networks. In *Artificial Neural Networks and Machine Learning – ICANN 2020*, pages 494–505. Springer International Publishing.

Tye, K. M., Miller, E. K., Taschbach, F. H., Benna, M. K., Rigotti, M., and Fusi, S. (2024). Mixed selectivity: Cellular computations for complexity. *Neuron*.

Wenstrup, J. J. and Portfors, C. V. (2011). Neural processing of target distance by echolocating bats: functional roles of the auditory midbrain. *Neuroscience & Biobehavioral Reviews*, 35(10):2073–2083.

Whittington, J. C., Muller, T. H., Mark, S., Chen, G., Barry, C., Burgess, N., and Behrens, T. E. (2020). The tolman-eichenbaum machine: unifying space and relational memory through generalization in the hippocampal formation. *Cell*, 183(5):1249–1263.

Wills, T. J., Muessig, L., and Cacucci, F. (2014). The development of spatial behaviour and the hippocampal neural representation of space. *Philosophical Transactions of the Royal Society B: Biological Sciences*, 369(1635):20130409.

Wood, E. R., Dudchenko, P. A., Robitsek, R. J., and Eichenbaum, H. (2000). Hippocampal neurons encode information about different types of memory episodes occurring in the same location. *Neuron*, 27(3):623–633.