A cognitive process model captures near-optimal confidence-guided waiting in rats

J Tyler Boyd-Meredith[1], Alex T Piet[2], Chuck D Kopec[3], and Carlos D Brody[3,4,*]

[1]Sainsbury Wellcome Centre, University College London, London, UK.
[2]Allen Institute, Seattle, Washington, United States.
[3]Princeton Neuroscience Institute, Princeton University, Princeton, United States.
[4]Howard Hughes Medical Institute, Princeton University, Princeton, United States.
[*]correspondence should be addressed to: Carlos D Brody (brody@princeton.edu)

1 Abstract

Rational decision-makers invest more time pursuing rewards they are more confident
they will eventually receive. A series of studies have therefore used willingness to wait
for delayed rewards as a proxy for decision confidence. However, interpretation of
waiting behavior is limited because it is unclear how environmental statistics influence
optimal waiting, and how sources of internal variability influence subjects' behavior. We
trained rats to perform a confidence-guided waiting task, and derived expressions for
optimal waiting that make relevant environmental statistics explicit, including travel
time incurred traveling from one reward opportunity to another. We found that rats
waited longer than fully optimal agents, but that their behavior was closely matched
by optimal agents with travel times constrained to match their own. We developed
a process model describing the decision to stop waiting as an accumulation to bound
process, which allowed us to compare the effects of multiple sources of internal variability
on waiting. Surprisingly, although mean wait times grew with confidence, variability
did not, inconsistent with scalar invariant timing, and best explained by variability in
the stopping bound. Our results describe a tractable process model that can capture
the influence of environmental statistics and internal sources of variability on subjects'
decision process during confidence-guided waiting.

19 Introduction

A decision maker's estimate of the probability that a decision is correct given the evidence
is referred to as decision confidence (Pouget et al., 2016; Hangya et al., 2016). Confidence
is critical for learning improvements in decision policy in response to feedback (e.g.
Drugowitsch et al., 2019), for deciding whether to act or gather more information (e.g.
Drugowitsch et al., 2012), and for determining how to long to wait for an expected
outcome before seeking reward elsewhere (Lak et al., 2014). However, study of the neural
underpinnings of confidence has been limited by the difficulty of measuring confidence in
animal subjects.

Recent work (Kepecs et al., 2008; Lak et al., 2014) has developed a promising assay
of decision confidence by asking how long subjects are willing to wait for a rewarding

outcome after a decision before moving on to another reward opportunity. This temporal post decision wagering paradigm has been used to study confidence in olfactory (Lak et al., 2014; Masset et al., 2020), auditory (Masset et al., 2020), visual (Stolyarova et al., 2019), and mnemonic (Joo et al., 2021) decisions, and has been used to study hallucinations (Schmack et al., 2021). Temporal post decision wagers have also been used to probe learning about environmental reward statistics (Mah et al., 2023).

The premise of these confidence-guided waiting studies is that reward-rate-maximizing ("optimal") agents are willing to wait longer for delayed rewards when they are more confident in their decisions. Modulations in willingness to wait are therefore understood to reflect variations in decision confidence. However, optimal waiting behavior also depends on the opportunity cost of opting to continue waiting for reward rather than starting a new trial, which is set by the maximum achievable environmental reward rate (Lak et al., 2014; Charnov, 1976; Stephens and Krebs, 1986; Constantino and Daw, 2015; McNamara, 1982). Previous work on this task did not explicitly define the environmental reward rate and therefore cannot specify how to choose the optimal average willingness to wait in a given environment, which is the first-order statistic that needs to be optimized in order to maximize reward rate. A complete account of optimal behavior in this task requires a definition of the reward rate that specifies all relevant environmental statistics affecting the environmental reward rate. Without such an account, it is not possible to determine whether animal subjects performing this task are behaving optimally.

Here, we trained rats to perform an auditory evidence accumulation task (Brunton et al., 2013) requiring binary decisions followed by a temporal wager (Lak et al., 2014). We developed an expression for the reward rate in the task, which allowed us to find the reward-rate-maximizing waiting policy. Doing so made explicit a key environmental statistic: the travel time that is incurred when moving on from one reward opportunity to the next. We found that rats performing the task spent longer waiting for rewards than optimal agents who maximized reward rate on matched datasets. This finding was consistent with the observation of "overharvesting" in foraging studies (Kane et al., 2019; Constantino and Daw, 2015). However, when we measured each individual subject's travel times and treated these as constraints on agents' behavior, the rats' overall average willingness to wait was not different from the optimal agents', suggesting that their waiting behavior was approximately optimal.

In addition to finding near-optimal overall average waiting behavior, the rats' also showed modulation of wait times by decision confidence, as has been seen previously (Lak et al., 2014; Masset et al., 2020; Stolyarova et al., 2019; Schmack et al., 2021), consistent with optimal agents. However, it is not clear how the near-optimal behavior we observed can be executed algorithmically in the brain. Nor is it clear how that decision might evolve in time and be influenced by sources of internal variability other than confidence. To develop a candidate model of the waiting decision process, we used the sequential probability ratio test (SPRT) to derive a decision variable that could achieve optimal waiting via an accumulation to bound process, as is often used in decision-making tasks (Wald, 1945; Ratcliff and McKoon, 2008; Gold and Shadlen, 2007). The decision variable was initialized at a point encoding the decision confidence and evolved with a linear drift toward a single fixed bound that encoded the estimate of the environmental reward rate. The drift in this model came from the observation that as time elapses without reward after a decision, the odds that the trial will be rewarded eventually decrease. Under the model, waiting continues until the moment that the decision variable crosses the bound at which point the current trial is abandoned.

The process model allowed us to compare various mechanistic sources of noise that

might effect the decision process (Brunton et al., 2013). We considered variability in the drift rate that would produce the property of scale invariance often observed in the literature on timing judgments (Gibbon, 1977; Simen et al., 2013, 2016), whereby the standard deviation of timing judgments grows proportionally to the interval being timed. We also considered diffusion noise that would corrupt the decision variable in each time step and cause the standard deviation of timing judgments to scale with the square root of the interval being timed, as in the drift diffusion model (Ratcliff, 1978). Finally, we considered variability in the setting of the bound, which would cause variability in timing judgments to be constant across all intervals being timed. Surprisingly, we found that, whereas scalar invariant timing noise had been assumed to dominate during this task (Lak et al., 2014), the data was most consistent with variability in the bound. We speculate that the dominance of this source of variability may arise from continual learning of the bound setting based on a recency weighted average of the reward history, as has been observed in previous studies (Constantino and Daw, 2015; Mah et al., 2023) and is used in models of foraging as evidence accumulation (Davidson and El Hady, 2019).

Our results lay out a more complete theory of optimal behavior in temporal post decision wagering tasks and present a process model for estimating the moment-to-moment cognitive state of subjects during the waiting decision process. Taken together, these contributions increase the interpretive value of post-decision temporal wagers for studies of confidence and learning.

Results

Evidence accumulation task with confidence-guided waiting

We trained rats (n=16) to perform an auditory evidence accumulation task (Brunton et al., 2013) with randomly delayed reward delivery (Fig. 1a), as in Lak et al. (2014). The task requires two decisions of interest. First, the animal should decide which of two reward ports is more likely to provide a water reward given the auditory stimulus. Then, the animal must decide how long to wait for reward to be delivered before moving on to the next trial. In principle, this decision could be made at the time of the port choice, but may also be characterized as a series of decisions to wait at the chosen port for another timestep or abandon the port and move on.

Port choice Rats performed the task in a chamber containing an array of three nose ports. Rats initiated trials by poking their nose into a central nose port, which triggered stimulus playback. The stimulus consisted of two trains of auditory clicks, generated from two different Poisson rates, played from speakers on either side of the rat's head. The rat's task was to listen to the click trains and then, after a "go" cue, report which click train had the larger number of clicks by poking it's nose into the reward port on the side associated with the higher click rate. Trials where the rat withdrew from the center port before the "go" cue were labeled "center pokes violations," invalidated and the rat was moved on to the next trial after a brief white noise stimulus.

There were two versions of this task, referred to as the location task and the frequency task. Each rat was trained to perform one of the two tasks (location task, n=9; frequency task, n=7). In the location task, the two click trains were played from different speakers and the rats were rewarded for orienting toward the speaker that emitted more clicks. In the frequency task, the clicks were played in stereo, but the clicks in the two click trains were played at different frequencies. The high frequency click train instructed rightward

Figure 1: **Evidence accumulation task with delayed rewards** (a) Schematic of the task structure. Rats first make a port choice based on an auditory stimulus. On non-probe trials, if the port choice is correct, a reward is scheduled for delivery. The rat waits at the chosen port until either the reward is delivered or the rat decides to abandon the current trial and move on to the next. (b) Example trials from an example rat aligned to the time of the port choice. Correct port choices (purple bars) often lead to rewards (cyan bars), but sometimes the animal abandons the trial and center pokes to start a new trial before reward is delivered (an example is annotated). Error trials (orange bar) are never signalled and the rat eventually has to abandon the trial (an example is annotated). If the animal fails to hold it's nose in the center port during the stimulus period, the trial is considered a "center violation" (an example is annotated), increasing the time to the next possibly rewarded trial. (c) Probability of choosing the rightward reward port is plotted as a function of the evidence, operationalized as the click difference ($\#R - \#L$), normalized by the total number of clicks ($\#R + \#L$), denoted Δ/Σ. Each rat is shown as a gray trace and the average (with 95% confidence intervals) of the gray curves is shown in black. (d) Wait time distributions for an example rat conditioned on whether the decision was incorrect (shaded orange), correct with a baited reward (shaded cyan), or a correct probe trial (shaded purple). The reward delay distribution used to draw reward delivery time on non-probe trials is underlaid (cyan trace). (e) Violin plots showing each rat's wait times for error trials (orange) and correct probe trials (purple). Medians are plotted as dashed white lines with 25^{th} and 75^{th} as dotted white lines. (f) Mean wait time for an example rat in correct probe trial (purple) and error trials (orange) as a function of the absolute evidence strength, $|\Delta/\Sigma|$. Data are overlaid on linear fits to the correct and error trials separately. Errorbars are bootstrapped 95% confidence intervals. (g) Wait time chronometric curve showing the mean wait times from F plotted as a function of the strength of evidence favoring the chosen option, $|\Delta/\Sigma| \times$ correct. Data are overlaid on a linear fit to all the data. (h) Wait time chronometric curve for each rat computed as in g (gray traces) along with the mean (with 95% confidence intervals) of all the gray traces (black trace).

choices, whereas the low frequency click train instructed leftward choices. The click trains depicted in Fig 1a correspond to the location task. Trial difficulty was controlled by

¹²⁶ varying the rates of the two click trains.

Wait time decision After reporting a decision at the reward port, rats did not receive
¹²⁸ immediate feedback. Instead, after correct choices, reward delivery was delayed until
¹²⁹ an experimenter-determined reward time, t_r. On a subset of correct trials (mean: 7.1%
¹³⁰ $\pm$ 1.6%), rewards were omitted to provide an uncensored report of the rat's maximum
¹³¹ willingness to wait on that trial. We refer to these trials as "probe" trials (but, note that
¹³² "catch" trials is another common terminology). On error trials, feedback was omitted
¹³³ entirely. Rats were allowed to give up waiting for reward and move on to a new trial at
¹³⁴ any time after making the port choice by withdrawing from the reward port and poking
¹³⁵ into the center port. A series of example trials is shown in Figure 1b.
¹³⁶   In these experiments, reward delays were drawn from an exponential distribution, so
¹³⁷ that the density of reward delays was given by

$$P(t_r = t) = \frac{1}{\tau}e^{-(t_r - t_{r,\min})/\tau} \tag{1}$$

¹³⁸ with time constant $\tau = 1.5$, and a minimum reward delay $t_{r,\min} \in (.05, .5)$. The
¹³⁹ exponential distribution has a flat hazard rate on the interval $t \in (t_{r,\min}, \infty)$. This means
¹⁴⁰ that, given that reward is set to be delivered on a trial, but hasn't been delivered so far
¹⁴¹ by time t_w, the probability of receiving reward in the next time step is constant. We will
¹⁴² write the hazard rate of the reward distribution as

$$P(r_w \mid \neg R_w, R_\infty) = 1/\tau \tag{2}$$

¹⁴³ where we have used $r_w \equiv t_r \in (t_w, t_w + \delta t)$ to indicate the event that reward is delivered
¹⁴⁴ in the next timestep for some infinitesimal timestep δt, and we have used the sum
¹⁴⁵ $R_w \equiv \sum_{i=0}^{w-1} r_i$ to indicate whether reward is baited at some time before t_w, with it's
¹⁴⁶ negation, $\neg R_w$, indicating the opposite. In this notation R_∞ is used to indicate whether
¹⁴⁷ reward is set to be delivered eventually in the trial. The resulting mean reward delay is
¹⁴⁸ $\langle t_r \rangle \approx t_{r,\min} + \tau$ for trials where reward was baited.

Rat behavior All rats included in the study learned to perform the task with at least
¹⁵⁰ 60% accuracy (group mean: 74.4% correct trials). We computed each rat's psychometric
¹⁵¹ function for the port choice (Figure 1c). The psychometric function was defined as the
¹⁵² probability of making a rightward choice given the stimulus evidence favoring rightward
¹⁵³ choice. Stimulus evidence favoring rightward choice is defined as the click difference
¹⁵⁴ normalized by the total number of clicks, $\Delta/\Sigma \equiv \frac{\#R - \#L}{\#R + \#L}$, where $\#R$ represents the
¹⁵⁵ number of clicks favoring rightward choice and $\#L$ represents the number of clicks favoring
¹⁵⁶ a leftward choice on a given trial.
¹⁵⁷   We measured time spent waiting for reward at the side port in three trial types of
¹⁵⁸ interest: error trials, correct probe trials (where no reward is baited) and correct trials
¹⁵⁹ where reward is baited. We excluded trials where the animal took more than 2 seconds
¹⁶⁰ to initiate a new trial by center poking after leaving the chosen port. This is a standard
¹⁶¹ criterion used to focus analysis on trials where the animal is engaged in the task (Lak
¹⁶² et al., 2014). The example rat was willing to wait long enough to receive reward on most
¹⁶³ correct trials, so the distribution of waiting times on correct trials where reward was
¹⁶⁴ baited closely resembles the reward delay distribution (Figure 1d).
¹⁶⁵   On trials where the rat waited long enough to receive reward, the full duration that
¹⁶⁶ the rat would have been willing to wait is unknown, because reward delivery censors our

observation of the full willingness to wait. We used the probe trials to measure how long rats were willing to wait on correct trials. On both error trials and correct probe trials, rats were willing to wait much longer than the typical reward delays (Fig 1d,e). This held across all rats who learned the task (Fig 1e). Additionally, all rats waited longer at the choice port after correct choices on probe trials than after error trials (Fig. 1d,e; $p < .01$, rank-sum test, 16/16 rats), indicating that waiting was guided by an internal estimate of decision accuracy.

To measure the modulation of wait time by the stimulus evidence, we plotted the example rat's average wait time as a function of the absolute stimulus strength, $|\Delta/\Sigma|$, separately for correct probe trials and error trials (Fig 1f). We expected correct trials with strong signal to be the trials in which the animal has the highest confidence on average. Indeed, wait times were longest for correct trials where the evidence most strongly favored the choice made by the animal, as has been seen previously (Lak et al., 2014; Masset et al., 2020; Schmack et al., 2021). Correspondingly, wait times were shortest in the trials where the evidence most strongly favored the alternative not chosen by the animal. We expect these to be the trials where the animal has the lowest confidence on average.

To create an axis along which both confidence and wait time should increase monotonically, we used the strength of the evidence supporting the option chosen by the rat, $|\Delta/\Sigma| \times$ correct. This quantity takes positive values when the animal makes a correct choice and negative values when the choice is incorrect. When we plot the example rat's wait times against this axis, we see a graded increase in wait time as a function of evidence supporting the choice (Fig 1g). The data is overlaid on a linear fit to the data, which has a significantly positive slope (Pearson's $r = .22$, $p < .01$). We computed wait time as a function of evidence supporting choice for all rats (Fig 1h) and computed linear fits to each rat. All rats had a significant, positive relationship between waiting time and the strength of evidence for the chosen option ($p < .01$ for 16/16 rats). This indicates that all of our rats modulated waiting times by their decision confidence.

Overall reward rate maximization depends on travel time

Previous work (Lak et al., 2014) has shown that in order to maximize reward rate in decision tasks with delayed reward, subjects should be willing to wait longer when they are more confident in their decisions. However, the trial-by-trial modulation of waiting time by confidence alone is not enough to maximize the long term average reward rate. To maximize the long term average reward rate, subjects must also find an appropriate overall average willingness to wait. This value depends on a variety of other environmental statistics that influence the environmental reward rate. However, previous work has not developed an explicit expression for the environmental reward rate in the task, so it has not been possible to test whether rats learn this first-order optimization of overall wait time. In another study of rats performing confidence-guided waiting for delayed rewards, Stolyarova et al. (2019) noted that their rats' overall wait times were long relative to the average time of reward delivery, as is true in our rats. The authors interpreted this observation as likely being a deviation from optimality in rat behavior. This would be consistent with previous studies in human (Constantino and Daw, 2015) and animal subjects (Kane et al., 2019; Hayden et al., 2011) often report a bias, referred to as "overharvesting," toward spending more time than would be optimal on a given reward opportunity before moving on to the next. Here, we develop a definition of the reward rate that makes all relevant environmental statistics explicit. We can then determine the optimal average willingness to wait for a given environment, making it possible to test

Figure 2: **Across trial reward maximization depends on travel time** (A) Task timing can be broken into travel time, t_0, time at the port, t_{port}, and time spent drinking reward, t_{drink} (top). Travel time includes all periods between the end of the waiting/drinking period and the start of the next period of waiting, including trial reinitiation time, t_{reinit}, center fixation time t_{stim}, and movement time, t_{move} (bottom). (B) Expected reward in a trial, $g(t_w)$, if willing to wait for time t_w. Colormap shows probability of eventual reward, αC_0. Points indicate 2s increments of t_w. (C) Expected time spent at the port per trial, $\mathbb{E}[t_{port} \mid t_w]$, plotted as in B. (D) Expected reward in a trial, $g(t_w)$, as a function of expected time at the port, $\mathbb{E}[t_{port} \mid t_w]$, plotted as in B and C. The effect of an additional 2s increment in t_w now depends on t_w and αC_0. (E-J) Consider reward maximization for an example agent with $\alpha C_0 = .67$ on every trial. (E) Expected reward in a trial, $g(t_w)$, plotted as a function of full trial time, $T(t_w) = t_0 + \mathbb{E}[t_{port} \mid t_w]$ (solid purple trace). The reward rate is $RR = \frac{g(t_w)}{T(t_w)}$ and is maximized when $RR^* = \frac{\partial g}{\partial T}(t_w^*)$ (red point) at $T(t_w^*)$. The red trace from the origin through this point has the highest slope of any line from the origin through the purple trace. All other values of $T(t_w)$ are suboptimal (e.g., gray and black points). The example gray and black points achieve the reward rate RR^{sub}, which is the slope of the gray and black traces. Here, t_0 is set to 2.5s. (F) The reward rate for the example agent is plotted as a function of $T(t_w)$ (dashed red trace) with the maximum reward rate marked (red point) along with the reward rate achieved if not willing to wait long enough (gray point) or willing to wait too long (black point). (G) The instantaneous reward expectation within a trial (solid purple trace) after time t_w passes without receiving reward, $\frac{\partial g}{\partial T} = P(r_w \mid \neg R_w)$ is plotted as a function of t_w. The session reward rate from F is shown for comparison (solid red trace). Reward rate is maximized if the agent sets a moving on threshold, $\kappa = RR^*$ (dashed red trace). Suboptimal reward is achieved when κ is not set to RR^* (e.g., gray and back traces). (H) Probability of reward, $g(t_w) = P(R_w)$, plotted as a function of expected port time, $T(t_w) - t_0 = \mathbb{E}[t_{port} \mid t_w]$ (rather than as a function of T as in E). Reward maximizing solutions are marked for three values of t_0, including the same from E, one (darkest red trace) smaller, and one larger (lightest red trace). (I) Instantaneous reward expectation plotted as in G with the reward rates and optimal settings of κ for the three levels of t_0 used in H. (J) Optimal wait time, t_w^*, as a function of travel time, t_0, for all levels of αC_0 used in panels b-d, except $\alpha C_0 = 1$, which corresponds to $t_w^* = \infty$ with the example levels of t_0 marked for the example level of αC_0 (red points).

whether subjects achieve optimal behavior in the task.

To develop an expression for reward rate in our task, we make use of optimal foraging theory (Charnov, 1976; Stephens and Krebs, 1986), which describes the optimal time an agent should spend in a series of "patches" containing depleting, continuous rewards before traveling to the next patch. In each trial, we think of the rat's nose poke into the chosen reward port as an entry into a "patch." We refer to the time spent at the port as t_{port}. We refer to the elapsed time between leaving the reward port on a given trial and entering a reward port on the next trial as "travel time", after foraging theory, and note it in equations as t_0 (Fig. 2a). In this task, the travel time includes the period of trial reinitiation from leaving the reward port on the previous trial to entering the center port on the current trial (labeled t_{reinit} in Fig 2a), plus the stimulus period during which the rat hears the stimulus to inform the port choice (labeled t_{stim} in Fig 2a)), and the time it takes to move from the center port to the chosen reward port (labeled t_{move} in Fig 2a). Unlike in the classical foraging theory where reward is continuous and the agent has perfect information about the patch identity, rewards in our task are stochastic, limited to at most one per trial, and the subject has only partial information about whether it is in a rewarded or unrewarded patch. The optimal strategy for such a task has been described for environments where rewarded and unrewarded patches occur with equal probability (McNamara, 1982). We generalize that theory to arbitrary initial probability of being in the rewarded patch.

The partial information about patch type comes from the agent's decision confidence, an estimate of the probability that the port choice was correct at the time of the decision given the available perceptual evidence, which we write as

$$C_0 \equiv P(\text{correct} \mid \text{percept}). \tag{3}$$

If the agent believes that all correct choices are rewarded, then their initial estimate of the probability that the choice will eventually be rewarded is C_0. If the agent believes that correct choices are only rewarded in some fraction, α, of non-probe trials, then the probability that the choice will be rewarded eventually is

$$P(R_\infty) = P(R_\infty \mid \text{correct})P(\text{correct} \mid \text{percept}) = \alpha C_0. \tag{4}$$

Later, we will see that the agent's posterior belief about whether the port choice will be rewarded (rewarded or unrewarded) falls over time.

We will simplify the expression for reward rate as a function of the subject's willingness to wait for reward across trials by beginning with the case of an agent who has no trial to trial variation in decision confidence (i.e., $P(\text{correct} \mid \text{percept}) = P(\text{correct})$). This agent should therefore be willing to wait the same amount of time, t_w, on every trial. We can write the expected overall reward rate for an agent willing to wait until time t_w as the ratio of expected reward per trial, $g(t_w)$, and expected time per trial, $T_{\text{total}}(t_w)$:

$$RR_{\text{total}} = \frac{g(t_w)}{T_{\text{total}}(t_w)} = \frac{g(t_w)}{t_0 + \mathbb{E}\left[t_{\text{port}} \mid t_w\right] + \mathbb{E}\left[t_{\text{drink}} \mid t_w\right]} \tag{5}$$

where t_0 is the "travel" time between leaving the chosen side port on one trial and nose poking at a side port on the next trial, $\mathbb{E}\left[t_{\text{port}} \mid t_w\right]$ is the expected time spent at the side port, and $\mathbb{E}\left[t_{\text{drink}} \mid t_w\right]$ is the expected time spent consuming reward. While $\mathbb{E}\left[t_{\text{drink}} \mid t_w\right]$ affects the overall reward rate, it can be ignored for the reward maximization process (see Supplemental Information for derivation).

Both expected reward on each trial, $g(t_w)$, and expected time at the port, $\mathbb{E}[t_{\text{port}} \mid t_w]$, depend implicitly on the probability that reward will be delivered eventually if the agent waits long enough ($P(R_\infty)$; equation 4). Expected reward per trial rises exponentially as a function of willingness to wait toward an asymptote at αC_0 (Figure 2b; see Supplemental Information for mathematical details). Expected time at the port per trial increases as a function of willingness to wait, but does not asymptote except in the case that all trials are eventually rewarded ($\alpha C_0 = 1$) (Figure 2c; see Supplemental Information for mathematical details). When there is a chance that trials will not be rewarded, greater willingness to wait increases expected time spent at the port on each trial (in the extreme case where no trials are rewarded, the expected time at the trial is equal to willingness to wait). Figure 2d shows how expected reward per trial increases as the expected time at the port increases when t_w is varied, combining the information in Figures 2b and c.

We can maximize the total reward rate in equation 5 by computing its derivative and setting it to zero, which yields

$$\frac{\partial g}{\partial T_{\text{total}}}(t_w^*) = RR_{\text{total}}^* \tag{6}$$

where t_w^* and RR^* are the optimal willingness to wait and the reward rate at that optimal t_w^* (see supplement for derivation). This is a generalization of the marginal value theorem (MVT; Charnov 1976) to the case of stochastic rewards (McNamara, 1982). That is, equation 6 states that the prescribed rule for maximizing reward rate is to be willing to wait for reward until the time, t_w^*, when the derivative of expected reward rate within the trial, $\frac{\partial g}{\partial T_{\text{total}}}(t_w^*)$, falls to the level of the maximum achievable reward rate across trials, RR_{total}^*. The latter quantity is the opportunity cost of continuing to wait for reward rather than beginning a new trial.

As noted above, we can simplify the computation by ignoring the reward consumption time in the denominator of equation 5. Instead, we will maximize the expected reward per time spent pursuing (not consuming) reward, $T(t_w)$:

$$RR = \frac{g(t_w)}{T(t_w)} = \frac{g(t_w)}{t_0 + \mathbb{E}[t_{\text{port}} \mid t_w]}, \tag{7}$$

which is maximized when

$$\frac{\partial g}{\partial T}(t_w^*) = RR^*. \tag{8}$$

(Note that previous work (Lak et al., 2014) assumed the optimality condition $\frac{\partial g}{\partial T}(t_w^*) = RR_{\text{total}}^*$, which produces suboptimal behavior when $t_{\text{drink}} \neq 0$, as is the case in our data.)

This reward maximization rule can be understood graphically by plotting expected reward in a trial, $g(t_w)$, as a function of expected time pursuing reward in the trial, $T(t_w)$, for an example agent (Fig 2d,e). The reward rate for any choice of t_w will be equal to the slope of a line that passes through the origin and the point $(T(t_w), g(t_w))$. The maximum possible slope (and maximum possible reward rate) is achieved when this line is tangent to the reward rate curve, which is when the condition of equation 8 is satisfied (Fig 2e,f). In standard optimal foraging theory, the forager receives continuous reward and gives up and moves on at a time under its full control, $\mathbb{E}[t_{\text{port}} \mid t_w] = t_w$, which would mean that $\frac{\partial T}{\partial t_w} = 1$ and equation 8 reduces to the standard MVT. However, because our task provides at most one reward per trial, the agent sets an upper bound on time spent waiting for reward delivery, but moves on if it is rewarded before t_w.

Optimizing wait time Now that we have found the condition under which reward rate is maximized (equation 8), we are able to find t_w^* for a given set of environmental statistics. To do so, we first compute the derivative in left hand side of equation 8, which we write as

$$\frac{\partial g}{\partial T}(t_w) = \lim_{\delta t \to 0} \frac{g(t_w + \delta t) - g(t_w)}{T(t_w + \delta t) - T(t_w)}. \tag{9}$$

For an agent that has already waited for time t_w, this quantity takes one of two values. If reward has already been delivered, the derivative is zero ($g(t_w) = g(t_w + \delta t) = 1$), and the agent should move on to the next trial as soon as it finishes consuming reward. In the second case, the agent has not yet received the reward ($g(t_w) = 0$). In this case the expected reward after waiting for an additional time step is the probability of receiving reward in the next time step given that it hasn't been delivered so far, $P(r_w \mid \neg R_w)$. We refer to this quantity as the instantaneous reward expectation after waiting for time t_w without reward.

Because the agent does not know whether it will be rewarded until the reward is delivered, the instantaneous reward expectation can be expressed as a product of the reward hazard rate for rewarded trials (equation 2) and the posterior probability that reward will be delivered on this trial given that it has not been delivered so far:

$$P(r_w \mid \neg R_w) = P(r_w \mid \neg R_w, R_\infty)P(R_\infty \mid \neg R_w). \tag{10}$$

We refer to the second term as the posterior belief that reward will be delivered on a given trial after waiting for time t_w without receiving reward. We can write this quantity using Bayes' rule

$$P(R_\infty \mid \neg R_w) = \frac{P(\neg R_w \mid R_\infty)P(R_\infty)}{P(\neg R_w)}. \tag{11}$$

Evaluating this expression for the reward distribution used in our experiment, we find that the posterior belief that that reward will be delivered eventually given that it hasn't been delivered so far is:

$$P(R_\infty \mid \neg R_w) = \frac{\alpha C_0 e^{-(t_w - t_{r,\min})/\tau}}{1 - \alpha C_0 + \alpha C_0 e^{-(t_w - t_{r,\min})/\tau}} \tag{12}$$

(see Supplemental Information materials for detailed derivation). Note that when the agent is unaware of the probe trials (i.e., the agent estimates $\alpha = 1$), equation 12 is equal to the posterior belief that the port choice was correct, the posterior decision confidence, after waiting for time t_w without reward.

Substituting equations 2 and 12 into equation 10, we find that the instantaneous reward expectation after waiting for time t_w without reward is the posterior belief that reward is still coming times the reward hazard rate:

$$P(r_w \mid \neg R_w) = \frac{1}{\tau} \cdot \frac{\alpha C_0 e^{-(t_w - t_{r,\min})/\tau}}{1 - \alpha C_0 + \alpha C_0 e^{-(t_w - t_{r,\min})/\tau}} \tag{13}$$

for $t_w \geq t_{r,\min}$ (for $t_w < t_{r,\min}$, instantaneous reward expectation is 0). Note that equation 13 is equivalent to equation 5 in Lak et al. (2014) if we substitute $C = \alpha C_0$ and $t = t_w - t_{r,\min}$. However, our derivation clarifies that even though the reward hazard rate is fixed in the task, there is a decrease in instantaneous reward expectation while

waiting for reward that can be attributed to a decrease in the posterior belief that the trial will be rewarded as time passes without reward delivery. Later, we will make use of this observation to develop a model for describing the port leaving decision as a process that unfolds in time.

Instantaneous reward expectation (equation 13) for the example agent is plotted as a function of elapsed time without reward in Figure 2g. To find t_w^*, the agent needs to estimate the instantaneous reward expectation as a function of t_w and choose a moving on threshold, κ, whose optimal value is RR^* (Fig 2g). When $\kappa < RR^*$, the agent is impatient and receives a below average reward rate, and when $\kappa > RR^*$, the agent wastes time at the reward port that would be better spent starting a new trial. Choosing the appropriate threshold will lead to optimal waiting with

$$ t_w^* = t_{r,\min} + \tau \left(\log \frac{\alpha C_0}{1 - \alpha C_0} - \log \frac{RR^*\tau}{1 - RR^*\tau} \right) \tag{14} $$

(see Supplementary Information for detailed derivation). This is equivalent to equation 6 in Lak et al. (2014) if we again substitute $C = \alpha C_0$, set $t_{r,\min} = 0$, and substitute $\kappa = RR^*$. But note that in Lak et al. (2014), κ is defined in words as the "environmental reward rate" whereas we have developed an explicit expression for RR^*, which clarifies that the correct RR^* in this expression is not the total environmental reward rate (equation 5), but rather the reward per time spent pursuing reward (equation 7). Moreover, because we have provided an expression for RR that makes all relevant environmental statistics explicit, we can now compute t_w^* for a given experiment, which was not possible previously.

The optimal strategy for maximizing reward is influenced by the confidence on a given trial and all of the factors that influence the maximum achievable reward rate, including the probe trial fraction, the reward delivery time constant τ, and the travel time, t_0. As t_0 increases, the maximum possible reward rate decreases and the value of t_w^* increases. The reward optimization procedure is depicted for three example levels of travel time in Figure 2h,i.

We found the optimal willingness to wait, t_w^*, as a function of travel time, t_0, for all the levels of αC_0 by using root finding to solve equation 8 (Figure 2j; see Methods for details). The amount of time that a reward rate maximizing agent is willing to wait in this task increases monotonically as travel time increases for all levels of αC_0 (except 0 and 1, where the agent should either not be willing to wait at all, or should always be willing to wait until the reward is delivered, respectively).

Rats maximize reward rate after accounting for travel time

Now that we can compute t_w^* for an agent with fixed confidence across trials, we can test whether our rats achieved the maximum possible reward rate across trials. To do this, we compared rats' willingness to wait, averaged across trials, to t_w^*, the willingness to wait that would maximize the reward rate for an agent with fixed confidence across trials. To estimate the rats' average willingness to wait across trials, we computed the average wait time for correct probe trials and for a subset of error trials, subsampled so that the proportion of error trials used in this analysis matched the proportion in the full dataset (which also includes non-probe trials; Fig 3c,d). To compute t_w^* for each subject's dataset, we estimated the necessary terms from that subject's data: α was the fraction of non-probe trials in the rat's dataset, C_0 was the fraction of correct trials, and t_0 was estimated from the mean travel time for the rat (after excluding the longest 1% of travel times, because the rats occasionally fully disengaged from the task for long periods of

Figure 3: **Rats maximize reward rate after accounting for travel times** (A) Cumulative distribution of travel times, t_0, for each rat (black traces). We excluded the longest 1% of travel times for each rat to compute the mean travel time (dashed red line). (B) Minimum t_0 for each rat (gray diamonds) and mean included t_0 for each rat (red points). Means of the presented values are shown as horizontal lines for the minimum and mean t_0 values. (C) Each rat's willingness to wait is plotted as a function of the optimal willingness to wait for an agent with the same reward delivery statistics, trial accuracy, and the same mean travel time as the rat, but without trial-by-trial variations in confidence (red points). Each rat's willingness to wait is also plotted as a function of the optimal willingness to wait for an agent as described, but with travel time equal to the minimum travel time achieved by the rat (gray diamonds). Rat willingness to wait is estimated by computing the mean wait time in correct probe trials and in a subsample of error trials (subsampled so that the proportion of error trials in this analysis is equal to the proportion of error trials for the full dataset when all correct trials are included). Optimal willingness to wait was determined by root finding using equation 8. The mean and 95% confidence intervals are shown as crosses for each group. The shade of the red points indicates the fraction of the reward maximizing agent's reward rate achieved by the rat. For the comparison between the rat and the agent with matched mean t_0, the shade of red of the points indicates the fraction of the maximized agent reward rate achieved by the rat. (D) Difference between the rat data and the agent data for the rats' travel times (red points) and for the shorter travel times (gray diamonds). Colormap is the same as in C. The mean difference for each group is marked with a horizontal line.

time; Fig 3a, b). Using these terms allowed us to evaluate both sides of equation 8 and compute t_w^* by root finding (see Methods for details).

A fully optimal agent performing this task should spend as little time traveling from one reward opportunity to the next. However, our rats spent more time than necessary traveling between reward opportunities. This was due to the self-paced nature of the task and exacerbated by center poke violations, which caused trials to be invalidated. We reasoned that it may be very difficult for the rats to further minimize travel time. Among other things, decreasing travel times would require reducing the center port violation rate, which the animal is presumably already incentivized to do as much as possible. Therefore, we treated travel time as a constraint experienced by the animal and used the agents with matched travel times to ask whether the rats maximized reward rate given their constraints. To compare each rat to an agent who had also minimized travel time, we also computed t_w^* for an agent whose average t_0 was set to the value of the shortest travel time achieved by the rat across sessions (Fig 3b).

We found that the rats' average willingness to wait was not different from the reward maximizing agents' with matched travel times ($p = .25$, paired t-test; Fig 3c,d). However, rats' wait times were much longer than those of the agents optimized with short travel

times ($p = 6.15 \times 10^{-11}$, paired t-test; Fig 3c,d). Subjects "overharvested" relative to fully optimal agents, as has been seen in previous studies of foraging behaviors (Kane et al., 2019; Constantino and Daw, 2015). However, when travel time is treated as constrained, and behavior is optimized over willingness to wait t_w alone, subjects' overall willingness to wait was near-optimal, approximately maximizing their overall reward rate.

Figure 4: **Optimal waiting can be implemented with linear drift from a confidence-dependent initial point to a fixed bound** (A) Optimal wait time procedure as presented in fig 2g,i, but scaled by τ, so that we track the evolution of $P(R_\infty \mid \neg R_w)$ to a bound $\kappa\tau$. Two settings of κ are shown (gray and black dashed traces) along with the bound hitting times for different levels of αC_0 (left) and the resulting wait times are plotted against αC_0 (right). (B) Equivalent model with linear drift from an initial point $x_0 = \log \frac{\alpha C_0}{1 - \alpha C_0}$, which terminates at a bound $Z = \log \frac{\kappa\tau}{1 - \kappa\tau}$. This process leads to the same waiting times as in A. Colormaps are the same as in A, but note that $C_0 = 0$ and $C_0 = 1$ do not appear in panel B, because they start at $-\infty$ and $+\infty$, respectively, and never hit the bound.

Process model for optimal confidence modulated waiting

To understand how the port leaving decision might be implemented in the brain, we developed a process model that described the decision to stop waiting as an accumulation to bound process. This model provides us with a cognitively tractable algorithm that can achieve optimal waiting and model the cognitive state of the animal during this task, which may be useful for studies of neural recordings in the task. It also allows us to capture variability in waiting that may be explained by sources of internal variability other than variations in decision confidence.

To develop such a model, we used the sequential probability ratio test (Wald, 1945) to derive a tractable update rule, a linear drift with time, for a decision variable that can be used to produce optimal wait times. From equations 8 and 10, we know that optimal policy is to stop waiting when the instantaneous reward expectation falls to the level of the maximum reward rate in the environment, or equivalently, when the posterior belief that reward will be delivered eventually, $P(R_\infty \mid \neg R_w)$ falls to the maximum reward rate

in the environment scaled by τ

$$P(R_\infty \mid \neg R_w) = RR^*\tau. \tag{15}$$

We can describe an agent who uses this strategy, but does not necessarily choose the optimal bound by replacing RR^* with a parameter κ whose optimal value is $\kappa^* = RR^*$. This process is shown in Figure 4a.

To produce a decision variable that is tractable to update, we define x_w as the log odds of eventual reward delivery, given that reward has not been delivered by time t_w:

$$x_w = \log \frac{P(R_\infty \mid \neg R_w)}{P(\neg R_\infty \mid \neg R_w)}. \tag{16}$$

Since the passage of time without reward provides evidence that reward is not coming in this trial, we can find an update rule that integrates the information from the passage of time without reward into x_w. To do this, we decompose x_w into two terms representing the previous value x_{w-1} and an update Δx when timestep w elapses without reward (note that if reward is delivered in timestep w, the process ends)

$$\begin{aligned} x_w &= \log\left(\frac{P(R_\infty \mid \neg R_{w-1})}{P(\neg R_\infty \mid \neg R_{w-1})} \frac{P(\neg r_w \mid R_\infty, \neg R_{w-1})}{P(\neg r_w \mid \neg R_\infty, \neg R_{w-1})} \right) \\ &= x_{w-1} + \log\left(P\left(\neg r_w \mid R_\infty, \neg R_{w-1}\right) \Delta t \right) \\ \Delta x &= \log\left(P\left(\neg r_w \mid R_\infty, \neg R_{w-1}\right) \Delta t \right) \end{aligned} \tag{17}$$

This gives an update term, Δx, to guide the evolution of x_w in every time step. In the time before the earliest possible reward delivery ($t_w < t_{r,\min}$), the update term is 0 and x_w is constant, afterward x drifts at the hazard rate of the reward distribution

$$\Delta x = \log\left(1 - \frac{1}{\tau}\Delta t\right) = -\frac{1}{\tau}\Delta t$$

where we have used $\log(1 - n) \approx -n$ for $|n| << 1$. Taking the timestep to zero, we get the linear drift dynamics

$$dx = -\frac{1}{\tau}dt, \tag{18}$$

which we can combine with equation 4 to write the x_w at time t_w and at it's initial value x_0:

$$x_w = x_0 - (t_w - t_{r,\min})/\tau \qquad\qquad x_0 = \log \frac{\alpha C_0}{1 - \alpha C_0}. \tag{19}$$

By equation 15, we know that the agent should stop waiting when x_w hits a bound specified by

$$Z^* = \log \frac{RR^*\tau}{1 - RR^*\tau}. \tag{20}$$

If the waiting process terminates when x hits the bound Z^*, we achieve the reward maximizing wait times equivalent to equation 14:

$$t_w^* = t_{r,\min} + \frac{Z^* - x_0}{A^*} \tag{21}$$

where A is a drift rate whose optimal value is $A^* = -1/\tau$. The evolution of x_w and equivalence of this waiting process with that of Figure 4a is shown in Figure 4b. This expression for optimal willingness to wait is equal to equation 6 in Lak et al. (2014) after setting $t_{r,\min} = 0$ and $C = \alpha C_0$. But, now also has an algorithmic interpretation that may be possible to implement in the brain. In words, the wait time decision is made by initializing a decision variable at a value that is set by the decision confidence and evolving it toward a fixed bound that is set by the overall reward rate and reward delivery timing in the task. The drift rate toward that bound is set by the reward hazard rate.

Contributions of different sources of timing noise to waiting process

In studies of timing judgments, subjects often exhibit the phenomenon of scalar invariance in which the standard deviation of timing estimates increases linearly in proportion to the interval to be timed (Gibbon, 1977; Simen et al., 2013). A previous model (Lak et al., 2014) of this confidence-guided waiting behavior assumed that scalar invariant timing noise was the dominant source of noise affecting wait times. However, this has not been directly tested and it is not clear that timing in this task is dominated by the same sources of variability as in interval timing tasks where the goal is to learn to respond when reward is most likely, rather than to persist until the moment that reward is sufficiently unlikely that it is worth giving up and moving on. It is also not trivial to separate noise in the timing decision from variability in the confidence level that might result from any given percept.

We used the process model defined in the previous section to examine the patterns of timing variability expected when different aspects of the process were corrupted by noise. We considered three possible ways of adding timing noise to our process model. In the first, we add noise to the drift rate, A (Fig 5a). For a given initial point, x_0, this produces a standard deviation in bound hitting times times that is proportional to the mean, which is the scalar invariant property. In the second model, we added diffusion noise to the position of x at each time step, which adds a random walk to the deterministic drift (Fig 5b). In this model, the standard deviation of wait times is proportional to the square root of the mean hitting times for a given x_0, meaning that the standard deviation will grow slower than for the scalar model. Finally, we considered a model with a noisy bound (Fig 5c). In this model, the standard deviation is constant regardless of the initial point x_0.

While the patterns of timing variability produced by each of these models are simple when the initial wait time decision variable, x_0, is known, we don't have access to x_0 for our rats. To understand the pattern of variability expected under each model when x_0 is unknown, we generated simulated x_0 values for 50,000 trials. To do this, we supposed a signal detection theory model of the decision process in which the stimulus is characterized by the ratio between the click difference and the total number of clicks on each trial, $s = \frac{\Delta}{\Sigma}$. For each trial, we generated a percept by adding noise with standard deviation σ_s to the stimulus, $p = s + \xi$ where $\xi \sim \mathcal{N}(0, \sigma_s^2)$. Decisions we made by comparing the stimulus to a decision boundary, $b = 0$. Confidence was then defined (beginning with

Figure 5: **Candidate timing noise models** (A-C) We consider three candidate models for adding noise to the wait time decision. In all three models, the agent makes left/right port choice based on a stimulus, which is corrupted by perceptual noise and creates an accompanying decision confidence, C_0. The waiting decision variable (DV), x is created by setting $x_0 = \log \frac{\alpha C_0}{1-\alpha C_0}$ where α is the fraction of non-probe trials. And x drifts with rate A toward a boundary Z. The agent is willing to wait for reward until x hits the bound Z, but gives up and moves immediately when the bound is hit. (A) Left panel shows example particles from a model in which the noise comes from variability in the drift rate. This noisy drift model produces the scalar invariant property that the ratio of the standard deviation of hitting times to the mean of hitting times is constant across all x_0 values. Traces are colored according to the binned normalized evidence favoring the choice, $|\frac{\Delta}{\Sigma}| \times$ correct. Second panel from left shows kernel density estimates of bound hitting times for each of the bins of normalized evidence favoring the choice with the same colormap. The third panel from the left shows the mean wait time as a function of the normalized evidence favoring the choice (black trace with points colored by bin). The second panel from the right shows the standard deviation of the bound hitting times as a function of the mean in each bin (black trace with points colored by bin). The generative relationship between standard deviation and mean is underlaid (pink trace). Any deviation reflects noise added by the psychometric decision process. The rightmost panel shows the coefficient of variation (CV) as a function of the mean wait time in each bin (black trace with points colored by bin). Again, the generative relationship is underlaid (pink trace). (B) Plots are as in A, but for a model with a diffusion noise process in which noise is added in every time step. The pink traces from A are maintained for comparison. (C) Plots as in A and B, but for a model in which noise comes from variability in the bound. The pink traces from A and B are maintained for comparison.

469 equation 3) as

$$C_0 \equiv P(\text{correct} \mid p)$$
$$= \int_s P(\text{correct} \mid p, s) P(p, s) ds$$
$$= \int_s \mathbb{1}^{\text{sign}(p)=\text{sign}(s)} P(p \mid s) P(s) ds \qquad (22)$$

where we are integrating the probability of experiencing the percept p given the stimulus s over all levels of s that would produce a correct choice (see Supplemental Information for full equations). For the simulations, we assumed an uniform prior $P(s)$ and the probability of a percept given a stimulus is the Gaussian $P(p \mid s) = \mathcal{N}(s, \sigma_s^2)$. We used a value of σ_s^2 that best fit an example rat (see Methods for details). We assumed an accurate estimate of the non-probe trial frequency, α. Combining this with confidence, we produced a sample x_0 for each trial using equation 19. We then generated a sample willingness to wait on each trial by applying the drift dynamics (equation 18) until the particle hit a bound Z (set to -3 in the simulations), chosen to produce a similar range of wait times as observed in data.

To determine what patterns we would be able to see in our rat data, we analyzed the simulated dataset for models with each source of timing noise as though we did not know generative x_0, but could only observe the stimulus, choice accuracy, and willingness to wait on a given trial. We binned trials by the evidence supporting choice, $\frac{\Delta}{\Sigma} \times$ correct. We then plotted conditioned kernel density estimates of willingness to wait for each bin. We also computed the mean, standard deviation, and coefficient of variation (standard deviation divided by mean) in each bin.

All models achieved increasing mean willingness to wait as a function of evidence supporting choice. But, the models had different relationships between standard deviation and mean within each bin. The variable drift model produced a roughly proportional increase in standard deviation as the mean grew, corresponding to flat coefficient of variation, as expected under scalar invariant noise (Fig 5a). But, there was additional noise across all bins that arose from variability in confidence (x_0) within each bin. The diffusion noise model produced a slightly sublinear increase in standard deviation as the mean grew, corresponding to a decreasing coefficient of variation (Fig 5b). Finally, the bound noise model produced a distinctly sublinear increase in standard deviation as the mean grew, with almost no increase between the last two evidence bins (Fig 5c). This corresponded to a dramatic decline in the coefficient of variation for the simulated data.

Scalar variability is not the dominant source of noise in rat waiting data

To test whether scalar invariant timing noise was the dominant noise source affecting rats waiting time decisions, we analyzed the rat data using the analysis methods used to study the simulated data. We analyzed the mean and standard deviation of probe trial wait times in bins of normalized evidence strength favoring the rat's choice ($\Delta/\Sigma \times$ correct). These bins should group similar levels of confidence together and therefore similar levels of desired wait time. The average wait time in each bin is shown for an example rat in Figure 6a. The distribution of wait times in each of these bins is shown for the example rat in Figure 6b. We compared the standard deviation of wait times in each of the bins to the mean (Fig 6c) and computed the coefficient of variation in each bin (Fig 6d) for the example rat. The pattern we observed was not consistent with the simulated data for the model with scalar invariant timing variability caused by noisy drift. Instead, the pattern we observed was sublinear, with minimal increase in standard deviation between the last two bins.

We repeated this procedure for all rats. Average wait time as a function of binned evidence for choice is shown for all rats in Figure 6e. The standard deviations as a function of average wait time are plotted for all rats in Figure 6f (as in Figure 6c). To compare across rats, we subtracted off the average wait time of the bins from each rat's data (Fig 6g). We then computed the distance between each rat's data and the scalar

Figure 6: **Scalar timing is not the dominant source of noise in the data** (A) Average wait times for an example rat for correct probe trials and proportionally sampled error trials as a function of evidence for chosen option bin. (B) Kernel density estimate for the wait times in each bin from A (the same colormap is used to indicate evidence bin). (C) Standard deviation of the wait times in each bin (points connected by black trace) is overlaid on the predicted relationship between wait time standard deviation and mean under scalar timing with a coefficient of variation equal to .3 (pink trace). (D) Coefficient of variation (the standard deviation divided by the mean) in each bin is plotted as a function of mean wait time in each bin for the data (points) and for scalar model shown in C (pink trace). (E) All rats' mean wait times plotted as a function of evidence for chosen option as in A. (F) All rats' wait time standard deviations plotted against mean wait time as in C. Again, overlaid on the prediction from scalar timing. (G) Standard deviation in each bin for all rats plotted against the difference between the mean wait time in the bin and the average of the bins for that rat. (H) Coefficient of variation plotted as in G for all rats with the mean across rats overlaid (black trace). If scalar timing was the dominant source of noise, each rat's trace should be flat.

timing prediction (as in Fig 6d) and plotted them together (as in Fig 6g) for comparison. We find a consistent pattern across the rats that the standard deviation builds up more slowly than expected under scalar invariant timing. This suggests that other sources of noise dominate any scalar invariant noise that exists in our rats' behavior. The standard deviation also appears to increase more slowly than expected if diffusion process was the dominant source of noise. Qualitatively, the variability in our data appears most consistent with the model in which bound noise dominates. One possible explanation for this is noise in the bound used to control the moving on decision. Constant bound noise would have an equal impact across trials with different desired wait times. Variations in the bound setting may also arise from continual learning of the appropriate bound setting which is a function of the recent reward history.

Discussion

We trained rats to perform a task requiring auditory evidence accumulation (Brunton et al., 2013) combined with a post-decision temporal wager designed to assess their decision confidence (Lak et al., 2014). The time that animals are willing to wait for a delayed reward after making a decision has become a popular proxy measurement of decision confidence, because we know that optimal agents wait longer for rewards they are more confident they will receive (Lak et al., 2014; Masset et al., 2020; Schmack et al., 2021). However, willingness to wait in optimal agents is also influenced by the maximum possible reward rate in the environment, which is in turn influenced by many environmental statistics. These statistics determine the optimal overall average willingness to wait, but they are not explicitly accounted for in previous studies of confidence-guided waiting.

Here, we developed an expression for the reward rate in the environment which made all of the relevant environmental statistics explicit. Using this environmental reward rate, we derived an expression for the conditions under which reward was maximized in the environment. This generalized the marginal value theorem (Charnov, 1976) into the case of stochastic rewards (McNamara, 1982) with arbitrary initial expectations about the probability of eventual reward. This work made it possible to test whether rats performing this task achieved overall reward-rate-maximization, which we refer to as "optimal" behavior.

One of the key statistics that determines the optimal overall average willingness to wait is the travel time incurred when deciding to move on from a given reward opportunity and pursue the next. We observed that our animals were willing to wait longer than fully optimal agents who minimized travel time and then maximized reward rate by finding the best overall willingness to wait for that minimized travel time. Compared to these agents, our animals "overharvested" reward on each trial, as has been seen in other studies of foraging behaviors (Kane et al., 2019; Constantino and Daw, 2015). Unlike fully optimal agents, our animals took longer to travel between reward opportunities than was strictly necessary. We asked whether their waiting behavior was optimal if we treated their travel times as constrained, meaning that they had minimized travel time to the best of their ability and then optimized willingness to wait given those travel times. We found that when we treated travel times as constrained, the rats' waiting behavior was near optimal.

One limitation of our study is that we don't know for certain that our rats' have minimized travel time to the best of their ability. It is possible that rats could decrease time between trials and achieve a higher reward rate. One way that future studies could test this would be to impose a longer minimum inter trial interval and test whether rats found a new willingness to wait that was optimal for the increased travel times.

To understand how our rats achieved near-optimal wait times, we developed a model of the wait time decision process, which sought to capture the unfolding cognitive state throughout the decision. Taking inspiration from the success of the drift diffusion model in modeling two alternative decisions (Bogacz et al., 2006; Gold and Shadlen, 2007; Ratcliff, 1978), we used the sequential probability ratio test (Wald, 1945) to develop a tractable and optimal update rule for a decision variable that can control the port leaving decision. This produced a continuously evolving cognitive process model for controlling port-leaving time via the linear drift of a decision variable toward a fixed bound. This process model provided a tractable algorithm for implementing optimal waiting in the brain in which each of the separate parameters could be learned from experience.

The model also allowed us to consider sources of variability that might contribute to

the decision process, drawing on extensive work on pacemaker accumulator models of timing behavior (Simen et al., 2013). To understand the mapping between willingness to wait and confidence, it is useful to know what sources of variability are contributing to wait times. Previous work has assumed that variability in the timing of willingness to wait would be dominated by the scale invariant property (Lak et al., 2014) in which the standard deviation of observed wait times should be proportional to the animals' desired wait time. However, this had not been tested. We compared three models. A noisy drift model, which produced scale invariant timing noise. A diffusion noise model, in which timing noise grew like the square root of the interval to be timed. And a noisy bound model, in which timing noise was constant across desired wait times. We found that our data was most consistent with the model dominated by bound noise.

While our model provides an improved description of the port leaving decision process, there are several avenues of possible improvement to the model that we should consider in the future. First, there are well-documented aspects of the port choice decision process that are not being accounted for here, including it's evolution in time (Brunton et al., 2013), effects of trial history (Gupta et al., 2024), and change in the parameters of the decision process from trial to trial (Roy et al., 2021; Drugowitsch et al., 2019). Second, there are alternative decision-making models that might produce similar side port choices, but provide different cognitive variables used as input to the waiting process. Of particular interest are decision models that impose a bound on the side choice process, and decision models in which choice results from a race between accumulators associated with each click train rather than a single accumulator representing the difference between the click trains (Bogacz et al., 2006). Third, there may be postprocessing of the stimulus following choice that leads to evolution of confidence independently from that instructed by the environment (Navajas et al., 2016). Finally, just as the parameters governing the choice process may evolve from trial to trial, the same may happen for the wait time decision either due to learning or changes in internal state like increasing satiety or patience (Bukwich et al., 2023). Indeed, we speculate that continual learning of the bound controlling port leaving may explain the variability we observed in our data.

Our model provides a tractable algorithm for solving this task, which can produce optimal behavior, and can also produce a variety of forms of variability and deviation from optimality. Studying this model allowed us to develop a mechanistic explanation for the variability observed in our behavior. This model may also be useful for interpreting neural data, because it provides a candidate signal that may be computed in the brain to guide the behavior. The model may also be helpful for interpreting the results of perturbations, which may separately influence the estimates of the confidence, the drift rate, the bound setting, or may affect sources of noise during the task. Future work investigating the neural basis of confidence computations using the confidence-guided waiting paradigm should seek to link neural activity and perturbations of brain regions to the parameters of a dynamic model of the internal cognitive process for deciding when to give up and move on, like the one developed here. Using such a model will increase the interpretive power of experiments using this paradigm to understand how the brain computes confidence estimates and uses them to guide subsequent behavior.

Methods

Subjects

Animal use procedures were approved by the Princeton University Institutional Animal Care and Use Committee and carried out in accordance with NIH standards. All subjects were adult male Long Evans rats bred either at Princeton Neuroscience Institute (VGAT-ReaChR rats) or by one of the following vendors (wild type rats): Taconic, Hilltop and Harlan, USA. Rats were pair-housed unless implanted with infusion cannulae at which point they were single-housed. Rats were placed on a water restriction schedule to motivate them to perform the task for water rewards.

Behavioral tasks

Poisson Clicks We trained rats on the Poisson Clicks task (Brunton et al., 2013), with a post-decision wait time wager (Lak et al., 2014; Kepecs et al., 2008), using an automated training protocol. Throughout training, rats were put on a controlled water schedule where they received at least 3% of their weight every day. Rats trained each day in training sessions of around 120 minutes.

In the final stage of training, each trial began with the illumination of a center nose port by an LED light inside the port. This LED indicated that the rat could initiate a trial by placing its nose into the center port. Rats were required to keep their nose in the center port (nose fixation) for a fixed duration until the LED turned off as a "go" signal. During center fixation, two trains of randomly-timed auditory clicks were played from speakers on either side of the center port after a variable delay. The duration of the click trains was uniformly distributed. The two click trains were each associated with one of two side ports and clicks in each click train were generated using different Poisson rates. For a given rat, the two generative rates always summed to a fixed value (20 or 40 clicks s^{-1}).

After the "go" signal, rats made a port choice by poking their nose into one of the two side ports. If they exited from the center port before the "go" signal, the trial was considered a violation and they experienced a white noise stimulus followed by a short time out. These trials did not yield decisions or wait times, but did contribute to travel times.

Choices were considered correct, and potentially rewarded, if they corresponded to the click train with the greater number of clicks, which corresponds to a noiseless ideal observer's estimate of the larger click rate.

Confidence-guided waiting Rewards were only delivered if the rat stayed at the side port until a reward time t_r drawn from an exponential distribution between a minimum $t_{r,\min} \in (.05s, .5s)$ and maximum $t_{r,max} > 15s$ with time constant $\tau = 1.5s$. The resulting mean reward delay was $\langle t_r \rangle = t_{r,\min} + \tau$. After errors, no feedback was delivered. Instead, the animal had to eventually give up on waiting for reward and start a new trial.

With probability $\zeta \in (.05, .15)$, the trial was turned into a probe trial by setting $t_r = 100s$. We did not allow multiple probe trials to occur consecutively. These probe trials allowed us to observe port-leaving times on a subset of correct trials when they might otherwise have been censored by reward delivery. Rats were given a grace period between 500 and 1500ms for leaving and returning to the choice port. If they withdrew from the reward port for longer than this grace period, reward was no longer available.

If the rat returned to the center port, during or after the grace period, a new trial was immediately initiated. If they returned to the chosen side port after the grace period, or entered the opposite side port at any time, the possibility of reward delivery was removed. For analysis of uncensored wait times, we focused on trials where the rat initiated a new trial by center poking within 2 seconds of leaving the side port.

Shaping

We shaped the animals by first training them to perform the Poisson Clicks task via a standardized set of training stages and then add the reward delay component. First, feedback delays were introduced on error trials and grew in each trial until they reached 100s and the rat never waited long enough to get the feedback. Next, fixed reward delays were introduced and were gradually increased until they reached $t_{r,min}$. Afterwards, we gradually increased were randomized by slowing increasing the delay time constant τ and the maximum delay time $t_{r,max}$. We introduced the probe trials after the rest of the reward delay statistics had reached their final values.

Inclusion criteria

Rats trained on this task were included in this study if they had more than 30 sessions that met the session inclusion criteria and if the fraction of unrewarded trials that ended with a re-initiating center poke (as opposed to re-entry in the chosen side port or entry into the opposite side port) met a minimum threshold of 55%. The session inclusion criteria required that the rat perform at least 150 trials with an overall accuracy rate exceeded 60%. In order to prevent the rats from developing biases towards particular side ports an anti-biasing algorithm detected biases and probabilistically generated trials with the correct answer on the non-favored side.

Psychometric curves

Behavioral sensitivity was assessed using psychometric curves. The probability of choosing the rightward port was computed as a function of the binned stimulus strengths, either the click difference ($\Delta \equiv \#R - \#L$) or the normalized click difference ($\frac{\Delta}{\Sigma} \equiv \frac{\#R-\#L}{\#R+\#L}$). We used the normalized click difference for comparison across rats with different total click rates. We fit psychometric curves with 2 parameters, a bias parameter b and a noise parameter σ for all rats as a function of the normalized click difference. We fit the data by minimized the negative log likelihood across trials where the probability of a rightward choice on a given trial was given by

$$P(\text{go right}) = .5 \left(1 + \text{erf}\left(-\frac{b - \frac{\Delta}{\Sigma}}{\sigma\sqrt{2}}\right)\right). \tag{23}$$

Wait time chronometric curves

Wait time modulation was assessed using error trials and correct probe trials to create wait time chronometric curves, which relate mean wait time to the strength of evidence supporting the chosen option. This can be computed as $y \cdot \frac{\Delta}{\Sigma}$, where $y = \pm 1$ is the choice. This quantity is positive when the choice is correct ($\text{sign}(y) = \text{sign}(\Delta)$) and negative when the choice is incorrect. The trials with the most evidence supporting the chosen option have large, positive values and the trials with the most evidence against the chosen option

have large, negative values. The most difficult trials, with the least evidence weighing on the choice, have small magnitudes. We expect confidence to increase monotonically along this axis. For plotting purposes, we fit a line to each rat's wait times in the space of normalized click difference supporting the choice.

Optimality analysis

We sought to test whether rats' waiting times maximized overall reward rate. To do this, we found t_w^* by evaluated equation 14 for each rat. To do this, we estimated the relevant terms in equation 14 from the rats' datasets: α was the fraction of non-probe trials in the rat's dataset, C_0 was the fraction of correct trials, τ and $t_{r,\min}$ were estimated from the reward delays scheduled for the rat, and t_0 was estimated from either the mean travel time achieved by the rat (after excluding the longest 1% of travel times, because the rats occasionally fully disengaged from the task for long periods of time), or the minimum travel time achieved by the rat. Because we are only interested in average overall waiting time here, we don't need to consider the variations in wait time associated with confidence. Therefore, this agent was constrained to wait the same amount of time on every trial. The reward maximizing willingness to wait for this agent will be the same as the reward maximizing willingness to wait of an agent with variations in confidence, so it is fair to use this agent as a benchmark of reward maximization and avoid making choices about how to capture confidence variations for now. We used a root finding algorithm to evaluate t_w^* for a given set of task statistics. We compared the willingness to wait for each of these agents to the average waiting times for the corresponding rats in correct probe trials and in a subset of error trials (subsampled to ensure that the frequency of error trials in this comparison matched that in the overall dataset). We also measured the optimal agent's reward rate and the fraction of the agent's reward rate achieved by the rat.

Process model simulations with candidate noise sources

We used euler integration to simulate the wait time decision process for three candidate noise models. In all simulations, we sampled 50,000 trial stimulus strengths, s, with replacement from the dataset of an example rat. We then generated a percept, $p = s + \xi$, for each trial, by adding Gaussian noise, $\xi \sim \mathcal{N}(0, \sigma_s^2)$, to the stimulus. The model made a rightward choice if the resulting percept was greater than a decision boundary, which we set to zero (i.e., $p > b$ for $b = 0$). Given this percept, we generated confidence levels according to equation 22. We then produced an corresponding x_0 and updated it in 25 millisecond timesteps ($\Delta t = .025s$) according to equation 19. The drift was set to it's optimal setting $A = -\frac{1}{\tau}$ (per equation 18) and the bound was set to $Z = -3$ to produce mean wait times across trials that roughly matched the example rat's. To produce a model with scale invariant timing noise with a coefficient of variation of 0.3 as in Lak et al. (2014), we set the drift on each trial to be $A^{\text{trial}} = -\frac{1}{\hat{\tau}}$ where $\hat{\tau} \sim \mathcal{N}(\tau, 0.3\tau)$. To produce a model with diffusion noise, we added Gaussian noise in each time step drawn from $\mathcal{N}(0, c\sqrt{\Delta t})$ with $c = 0.3\sqrt{ZA}$ to produce an equivalent level of noise at $x_0 = 0$ as produced under the scale invariant model. To produce a model with constant noise, we sampled a different bound on each trial $Z^{\text{trial}} \sim \mathcal{N}(Z, 0.3 \cdot |Z|)$. The magnitude of noise was again chosen to produce the same noise level as the other models for $x_0 = 0$. We recorded each models willingness to wait on each trial as the timestep in which the particle x first crossed the bound Z.

Analysis of variability in simulations and rat data

We used our simulations to ask what patterns of variability would be expected as a function of the stimulus. This was useful for analyzed rat data in which the confidence level and x_0 level are unknown. To do this, we binned trials by the evidence supporting the chosen option for both the simulated data and the rat data. Within these bins, we kernel density estimates of the distribution, as well as computing the mean, standard deviation, and coefficient of variation (ratio of standard deviation to mean) of the wait times in each bin. These produced different patterns for the each of the candidate models, which we then compared qualitatively to the rat data. In particular, the assumption of scalar variability predicted a flat coefficient of variation, which we did not observe in the rat data. Instead, our data was most consistent with the constant bound noise in which the standard deviation in each bin grows slowly as mean wait time increases.

Acknowledgements

We thank Athena Akrami, Adrian Bondy, Diksha Gupta, Thomas Luo, all other members of the Brody lab, as well as Lukas Braun, Nathaniel Daw, Javier Masís, Stefano Sarao Mannelli, and Pat Simen for helpful conversations and suggestions. TB acknowledges support by NIH grant T32 MH 65214-16. This work was supported by a grant from the Simons Foundation (Grant # 542953) awarded to CB, as well as NIH grant R01MH108358 awarded to CB.

References

Rafal Bogacz, Eric Brown, Jeff Moehlis, Philip Holmes, and Jonathan Cohen. The physics of optimal decision making: A formal analysis of models of performance in two-alternative forced-choice tasks. *Psychological Review*, 2006.

Bingni W. Brunton, Matthew M. Botvinick, and Carlos D. Brody. Rats and humans can optimally accumulate evidence for decision-making. *Science*, 340(6128):95–98, 2013. ISSN 0036-8075. doi:10.1126/science.1233912.

Michael Bukwich, Malcolm G. Campbell, David Zoltowski, Lyle Kingsbury, Momchil S. Tomov, Joshua Stern, HyungGoo R. Kim, Jan Drugowitsch, Scott W. Linderman, and Naoshige Uchida. Competitive integration of time and reward explains value-sensitive foraging decisions and frontal cortex ramping dynamics. September 2023. doi:10.1101/2023.09.05.556267.

E L Charnov. Optimal foraging, the marginal value theorem. *Theor. Popul. Biol.*, 9(2): 129–136, April 1976.

Sara M. Constantino and Nathaniel D. Daw. Learning the opportunity cost of time in a patch-foraging task. *Cognitive, Affective, and Behavioral Neuroscience*, 15(4):837–853, April 2015. ISSN 1531-135X. doi:10.3758/s13415-015-0350-y.

Jacob D. Davidson and Ahmed El Hady. Foraging as an evidence accumulation process. *PLOS Computational Biology*, 15(7):e1007060, July 2019. ISSN 1553-7358. doi:10.1371/journal.pcbi.1007060.

Jan Drugowitsch, Rubén Moreno-Bote, Anne K. Churchland, Michael N. Shadlen, and Alexandre Pouget. The cost of accumulating evidence in perceptual decision making. *Journal of Neuroscience*, 32(11):3612–3628, 2012. ISSN 0270-6474. doi:10.1523/JNEUROSCI.4010-11.2012.

Jan Drugowitsch, André G. Mendonça, Zachary F. Mainen, and Alexandre Pouget. Learning optimal decisions with confidence. *Proceedings of the National Academy of Sciences*, 116(49):24872–24880, 2019. ISSN 0027-8424. doi:10.1073/pnas.1906787116.

John Gibbon. Scalar expectancy theory and weber's law in animal timing. *The psychological review.*, 84(3), 1977. ISSN 0033-295X.

Joshua I. Gold and Michael N. Shadlen. The neural basis of decision making. *Annual Review of Neuroscience*, 30(1):535–574, 2007. doi:10.1146/annurev.neuro.29.051605.113038.

Diksha Gupta, Brian DePasquale, Charles D. Kopec, and Carlos D. Brody. Trial-history biases in evidence accumulation can give rise to apparent lapses in decision-making. *Nature Communications*, 15(1), January 2024. ISSN 2041-1723. doi:10.1038/s41467-024-44880-5.

Balázs Hangya, Joshua I. Sanders, and Adam Kepecs. A Mathematical Framework for Statistical Decision Confidence. *Neural Computation*, 28(9):1840–1858, 09 2016. ISSN 0899-7667.

Benjamin Y Hayden, John M Pearson, and Michael L Platt. Neuronal basis of sequential foraging decisions in a patchy environment. *Nature Neuroscience*, 14(7):933–939, June 2011. ISSN 1546-1726. doi:10.1038/nn.2856.

Hannah R. Joo, Hexin Liang, Jason E. Chung, Charlotte Geaghan-Breiner, Jiang Lan

Fan, Benjamin P. Nachman, Adam Kepecs, and Loren M. Frank. Rats use memory confidence to guide decisions. *Current Biology*, 31(20):4571–4583, 2021/11/11 2021. doi:10.1016/j.cub.2021.08.013.

Gary A Kane, Aaron M Bornstein, Amitai Shenhav, Robert C Wilson, Nathaniel D Daw, and Jonathan D Cohen. Rats exhibit similar biases in foraging and intertemporal choice tasks. *eLife*, 8:e48429, September 2019. ISSN 2050-084X. doi:10.7554/eLife.48429. Publisher: eLife Sciences Publications, Ltd.

Adam Kepecs, Naoshige Uchida, Hatim A. Zariwala, and Zachary F. Mainen. Neural correlates, computation and behavioural impact of decision confidence. *Nature*, 455 (7210):227–231, August 2008. ISSN 1476-4687. doi:10.1038/nature07200.

Armin Lak, Gil M. Costa, Erin Romberg, Alexei A. Koulakov, Zachary F. Mainen, and Adam Kepecs. Orbitofrontal cortex is required for optimal waiting based on decision confidence. *Neuron*, 84(1):190–201, 2014. ISSN 0896-6273. doi:https://doi.org/10.1016/j.neuron.2014.08.039.

Andrew Mah, Shannon S. Schiereck, Veronica Bossio, and Christine M. Constantinople. Distinct value computations support rapid sequential decisions. *Nature Communications*, 14(1):7573, November 2023. ISSN 2041-1723. doi:10.1038/s41467-023-43250-x. Number: 1 Publisher: Nature Publishing Group.

Paul Masset, Torben Ott, Armin Lak, Junya Hirokawa, and Adam Kepecs. Behavior- and Modality-General representation of confidence in orbitofrontal cortex. *Cell*, 182(1): 112–126.e18, July 2020.

John McNamara. Optimal patch use in a stochastic environment. *Theoretical Population Biology*, 21(2):269–288, April 1982. ISSN 0040-5809. doi:10.1016/0040-5809(82)90018-1.

Joaquin Navajas, Bahador Bahrami, and Peter E Latham. Post-decisional accounts of biases in confidence. *Current Opinion in Behavioral Sciences*, 11:55–60, October 2016. ISSN 2352-1546. doi:10.1016/j.cobeha.2016.05.005.

Alexandre Pouget, Jan Drugowitsch, and Adam Kepecs. Confidence and certainty: distinct probabilistic quantities for different goals. *Nat. Neurosci.*, 19(3):366–374, March 2016.

Roger Ratcliff. A theory of memory retrieval. *Psychological Review*, 85(2):59–108, March 1978. ISSN 0033-295X. doi:10.1037/0033-295x.85.2.59.

Roger Ratcliff and Gail McKoon. The Diffusion Decision Model: Theory and Data for Two-Choice Decision Tasks. *Neural Computation*, 20(4):873–922, April 2008. ISSN 0899-7667. doi:10.1162/neco.2008.12-06-420.

Nicholas A. Roy, Ji Hyun Bak, Athena Akrami, Carlos D. Brody, and Jonathan W. Pillow. Extracting the dynamics of behavior in sensory decision-making experiments. *Neuron*, 109(4):597–610.e6, February 2021. ISSN 0896-6273. doi:10.1016/j.neuron.2020.12.004.

K. Schmack, M. Bosc, T. Ott, J. F. Sturgill, and A. Kepecs. Striatal dopamine mediates hallucination-like perception in mice. *Science*, 372(6537), April 2021. ISSN 1095-9203. doi:10.1126/science.abf4740.

Patrick Simen, Francois Rivest, Elliot A. Ludvig, Fuat Balci, and Peter Killeen. Timescale Invariance in the Pacemaker-Accumulator Family of Timing Models. *Timing & Time Perception*, 1(2):159–188, January 2013. ISSN 2213-445X, 2213-4468. doi:10.1163/22134468-00002018. Publisher: Brill.

Patrick Simen, Ksenia Vlasov, and Samantha Papadakis. Scale (in)variance in a unified diffusion model of decision making and timing. *Psychological Review*, 123(2):151–181, 2016. ISSN 0033-295X. doi:10.1037/rev0000014.

David W Stephens and John R Krebs. *Foraging Theory*, volume 1. Princeton University Press, 1986. ISBN 9780691084411.

A Stolyarova, M Rakhshan, E E Hart, T J O'Dell, M A K Peters, H Lau, A Soltani, and A Izquierdo. Contributions of anterior cingulate cortex and basolateral amygdala to decision confidence and learning under uncertainty. *Nat. Commun.*, 10(1):4704, October 2019.

A Wald. Sequential tests of statistical hypotheses. *Ann. Math. Stat.*, 16(2):117–186, 1945.

Supplementary Information
A cognitive process model captures near-optimal confidence-guided waiting in rats

J Tyler Boyd-Meredith, Alex T Piet, Chuck D Kopec, and Carlos D Brody

Contents

1 Derivation of reward rate maximizing behavior

The total reward rate in the task is defined as the expected reward per trial, $g(t_w)$, divided by the expected time spent in each trial, $\mathbb{E}[t_{\text{port}} \mid t_w]$:

$$RR_{\text{total}} = \frac{g(t_w)}{T_{\text{total}}(t_w)}. \tag{S1}$$

To maximize the reward rate, we find the condition such that its derivative is zero, $\frac{\partial RR_{\text{total}}}{\partial t_w} = 0$. We compute the derivative using the quotient rule

$$\frac{\partial RR_{\text{total}}}{\partial t_w} = \frac{\frac{\partial g}{\partial t_w} T_{\text{total}}(t_w) - \frac{\partial T_{\text{total}}}{\partial t_w} g(t_w)}{T_{\text{total}}^2(t_w)}$$

which is equal to zero when

$$\frac{\partial g(t_w^*)}{\partial t_w} T_{\text{total}}(t_w^*) = \frac{\partial T_{\text{total}}(t_w^*)}{\partial t_w} g(t_w^*)$$

$$\frac{\partial g(t_w^*)}{\partial t_w} \frac{\partial t_w}{\partial T_{\text{total}}(t_w^*)} = \frac{g(t_w^*)}{T_{\text{total}}(t_w^*)}$$

$$\frac{\partial g}{\partial T_{\text{total}}}(t_w^*) = RR_{\text{total}}^* \tag{S2}$$

where t_w^* is the reward-maximizing willingness to wait and RR_{total}^* is the reward achieved at t_w^*.

To find a solution for t_w^* for a given set of task statistics from equation S2, we need expressions for $g(t_w)$ and $T_{\text{total}}(t_w)$. To do so, we will use the notation introduced in the main text to simplify these expressions. We will use

$$r_w \equiv (t_w, \ t_w + \delta t) \tag{S3}$$

to indicate whether reward is set to be delivered in some infinitesimal timestep δt beginning at time t_w. Then, we can indicate whether reward is set to be delivered before time t_w using the sum

$$R_w \equiv \sum_{i=0}^{w-1} r_i. \tag{S4}$$

We will use the negation, $\neg R_w$ to indicate when no reward is delivered by time t_w.

1.1 Expected reward per trial

Because at most 1 reward is delivered per trial and it always has the same magnitude, we can set the reward magnitude to 1 and make the expected reward per trial equivalent to the probability of reward in a trial

$$g(t_w) \equiv P(R_w). \tag{S5}$$

Our reward distribution is exponential, meaning that, given that reward is coming, the delivery times, t_r, are distributed according to

$$P(r_w \mid R_\infty) = \frac{1}{\tau} e^{-(t_w - t_{r,\min})/\tau}$$

where τ is an experimenter-specified time constant and $t_{r,\min}$ is an experimenter-specified minimum reward time (equation 1 in the main text). The probability of receiving a reward before time t_w depends on this distribution and on the probability that reward will be delivered on this trial, $P(R_\infty)$. The probability that reward will be delivered on this trial is estimated based on the decision confidence, C_0, and the probability that a trial is not a probe a trial

$$P(R_\infty) = \alpha C_0$$

(equation 4 in the main text). The expected reward per trial as the probability of receiving a reward before time t_w is the cumulative density function for the exponential given that the reward is coming times the prior probability that the reward is coming, $P(R_\infty)$:

$$g(t_w) = P(R_w \mid R_\infty)P(R_\infty) \tag{S6}$$
$$= \alpha C_0(1 - e^{-(t_w - t_{r,\min})/\tau}) \tag{S7}$$

where we have used the cumulative density for an exponential to compute $P(R_w \mid R_\infty)$.

1.2 Expected time per trial

The expected time per trial can be broken into three epochs: the time between leaving the reward port on the previous trial and entering a reward port on the current trial, t_0, the time spent at the port on the current trial, t_{port}, and the time spent consuming reward on the current trial, t_{drink}. Adding together the expected duration of each epoch, we get:

$$T_{\mathrm{total}} = t_0 + \mathbb{E}\left[t_{\mathrm{port}} \mid t_w\right] + \mathbb{E}\left[t_{\mathrm{drink}} \mid t_w\right]. \tag{S8}$$

The first quantity is referred to as the "travel time" and, for the reward-maximizing agent, does not depend on t_w. The other two quantities depend on whether reward is set to be delivered and how long the agent waits. The consumption time, t_{drink}, is either 0, if no reward is received, or a constant, if reward is delivered. Its expectation can be written

$$\mathbb{E}\left[t_{\mathrm{drink}} \mid t_w\right] = t_{\mathrm{drink}}P(R_w) = t_{\mathrm{drink}}g(t_w). \tag{S9}$$

We will show that t_{drink} can be ignored for the reward maximization process.

Expected time at the port To compute the expected time at the port, $\mathbb{E}\left[t_{\mathrm{port}} \mid t_w\right]$, we will separately consider trials in which reward is not set to be delivered and trials in which reward will be delivered if the agent waits long enough. Marginalizing over these possibilities gives us

$$\mathbb{E}\left[t_{\mathrm{port}} \mid t_w\right] = \mathbb{E}\left[t_{\mathrm{port}} \mid t_w, \neg R_\infty\right]P(\neg R_\infty) + \mathbb{E}\left[t_{\mathrm{port}} \mid t_w, R_\infty\right]P(R_\infty) \tag{S10}$$

When no reward is set to be delivered, the agent always gives up and moves on at the time t_w:

$$\mathbb{E}\left[t_{\mathrm{port}} \mid t_w, \neg R_\infty\right] = t_w. \tag{S11}$$

In trials where reward is set to be delivered at some time t_r, the time at the port can take one of two values. If the agent is not willing to wait long enough to get the reward, the agent will give up before the reward is delivered and we will again observe time t_w spent at the port:

$$\mathbb{E}\left[t_{\text{port}} \mid t_w, R_\infty, t_r > t_w\right] = t_w \tag{S12}$$

If the agent is willing to wait long enough to get the reward, the reward delivery will censor the agent's willingness to wait and we will observe t_r time spent at the port. To compute the expected port time for this trial type, we need to marginalize over the possible values that t_r can take, as follows:

$$
\begin{aligned}
\mathbb{E}\left[t_{\text{port}} \mid t_w, R_\infty, t_r \leq t_w\right] &= \int_{t_{r,\min}}^{t_w} t \cdot P(t_r = t \mid R_\infty, t_r \leq t_w) dt \\
&= \int_{t_{r,\min}}^{t_w} t \cdot \frac{P(t_r \leq t_w \mid R_\infty, t_r = t) P(t_r = t \mid R_\infty)}{P(t_r \leq t_w \mid R_\infty)} dt \\
&= \frac{1}{P(t_r \leq t_w \mid R_\infty)} \int_{t_{r,\min}}^{t_w} t P(t_r = t \mid R_\infty) dt \\
&= \frac{1}{P(t_r \leq t_w \mid R_\infty)} \int_0^{t_w} \frac{t}{\tau} e^{-(t-t_{r,\min})/\tau} dt \\
&= \frac{t_{r,\min} + \tau(1 - e^{-t_w - t_{r,\min}/\tau}) - t_w e^{-(t_w - t_{r,\min})/\tau}}{P(t_r \leq t_w \mid R_\infty)}
\end{aligned} \tag{S13}
$$

Combining equations S12 and S13 and multiplying each by their probabilities, we can compute the expected time at the port on trials where reward is set to be delivered eventually:

$$
\begin{aligned}
\mathbb{E}\left[t_{\text{port}} \mid t_w, R_\infty\right] &= \mathbb{E}\left[t_{\text{port}} \mid t_w, R_\infty, t_r > t_w\right] P(t_r > t_w \mid R_\infty, t_w) + \\
&\qquad \mathbb{E}\left[t_{\text{port}} \mid t_w, R_\infty, t_r \leq t_w\right] P(t_r \leq t_w \mid R_\infty, t_w) \\
&= t_w e^{-(t_w - t_{r,\min})/\tau} + t_{r,\min} + \tau(1 - e^{-(t_w - t_{r,\min})/\tau}) - t_w e^{-(t_w - t_{r,\min})/\tau} \\
&= t_{r,\min} + \tau(1 - e^{-(t_w - t_{r,\min})/\tau})
\end{aligned} \tag{S14}
$$

Finally, we can combine the expected port time in trials where no reward is baited (equation S11) and trials where reward is set to be delivered if the agent waits long enough (equation S14) to get the expected time at the port overall:

$$
\begin{aligned}
\mathbb{E}\left[t_{\text{port}} \mid t_w\right] &= \mathbb{E}\left[t_{\text{port}} \mid t_w, \neg R_\infty\right] P(\neg R_\infty) + \mathbb{E}\left[t_{\text{port}} \mid t_w, R_\infty\right] P(R_\infty) \\
&= (1 - \alpha C_0) t_w + \alpha C_0 \left(t_{r,\min} + \tau \left(1 - e^{-(t_w - t_{r,\min})/\tau}\right)\right)
\end{aligned} \tag{S15}
$$

1.2.1 Reward maximization doesn't depend on consumption time

As mentioned above, we can ignore the consumption time in the reward maximization process, which simplifies equation S2. We will use $T(t_w) \equiv t_0 + \mathbb{E}\left[t_{\text{port}} \mid t_w\right]$, to represent the expected time spent searching for, but not consuming reward, which we refer to as RR. The solution t_w^* produced by the equality condition in equation S2 is also achieved by maximizing RR. We can see this by rewriting equation S2 with the search and

consumption times made explicit

$$\frac{\partial g}{\partial T_{\text{total}}}(t_w^*) = RR_{\text{total}}^*$$

$$\frac{\frac{\partial}{\partial t_w}g(t_w^*)}{\frac{\partial}{\partial t_w}T(t_w^*) + t_{\text{drink}}\frac{\partial}{\partial t_w}g(t_w^*)} = \frac{g(t_w^*)}{T(t_w^*) + t_{\text{drink}}g(t_w^*)}$$

$$\frac{\frac{\partial}{\partial t_w}T(t_w^*)}{\frac{\partial}{\partial t_w}g(t_w^*)} + t_{\text{drink}} = \frac{T(t_w^*)}{g(t_w^*)} + t_{\text{drink}}$$

$$\frac{\frac{\partial}{\partial t_w}g(t_w^*)}{\frac{\partial}{\partial t_w}T(t_w^*)} = \frac{g(t_w^*)}{T(t_w^*)}$$

$$\frac{\partial g}{\partial T}(t_w^*) = RR^*.$$

We will use equation 8 to find the optimal waiting behavior.

1.3 Expected reward per time searching

Combing the equations S15 and S7 we get the definition of expected reward rate per time spent pursuing, but not consuming, reward:

$$RR = \frac{\alpha C_0 \left(1 - e^{-(t_w - t_{r,\text{min}})/\tau}\right)}{t_0 + (1 - \alpha C_0)\, t_w + \alpha C_0 \left(t_{r,\text{min}} + \tau \left(1 - e^{-(t_w - t_{r,\text{min}})/\tau}\right)\right)}. \tag{S16}$$

1.4 Derivation of posterior belief that reward will be delivered

From equation 11 in the main text, we know that the posterior belief that reward will be delivered on a given trial after waiting for time t_w without receiving reward is

$$P(R_\infty \mid \neg R_w) = \frac{P(\neg R_w \mid R_\infty)P(R_\infty)}{P(\neg R_w)}.$$

The first term in the numerator is the probability that reward is not delivered by time t_w given that it will be delivered eventually, which is the survivor function of the exponential distribution (or 1 minus the CDF)

$$P(\neg R_w \mid R_\infty) = e^{-(t_w - t_{r,\text{min}})/\tau}. \tag{S17}$$

The denominator can be expressed as

$$\begin{aligned}
P(\neg R_w) &= P(\neg R_w \mid \neg R_\infty)P(\neg R_\infty) + P(\neg R_w \mid R_\infty)P(R_\infty) \\
&= 1 - \alpha C_0 + \alpha C_0 e^{-(t_w - t_{r,\text{min}})/\tau}
\end{aligned} \tag{S18}$$

where we have used equation S17 and the $P(\neg R_\infty) = 1 - P(R_\infty)$. Combining these expressions with the definition of $P(R_\infty)$ (equation 4), we get:

$$P(R_\infty \mid \neg R_w) = \frac{\alpha C_0 e^{-(t_w - t_{r,\text{min}})/\tau}}{1 - \alpha C_0 + \alpha C_0 e^{-(t_w - t_{r,\text{min}})/\tau}}.$$

1.5 Derivation of optimal willingness to wait

We rearrange the terms of the optimality condition from equation 8 and use the expression we derived for the instantaneous reward expectation (equation 13) to find the optimal willingness to wait

$$P(r_w \mid \neg R_w) = RR^*$$

$$\frac{1}{\tau} \cdot \frac{\alpha C_0 e^{-(t_w^* - t_{r,\min})/\tau}}{1 - \alpha C_0 + \alpha C_0 e^{-(t_w^* - t_{r,\min})/\tau}} = RR^*$$

$$\frac{\alpha C_0}{(1 - \alpha C_0)e^{(t_w^* - t_{r,\min})/\tau} + \alpha C_0} = RR^*\tau$$

$$(1 - \alpha C_0)e^{(t_w^* - t_{r,\min})/\tau} = \frac{\alpha C_0}{RR^*\tau} - \alpha C_0$$

$$e^{(t_w^* - t_{r,\min})/\tau} = \frac{\alpha C_0 - \alpha C_0 RR^*\tau}{(1 - \alpha C_0)RR^*\tau}$$

$$e^{(t_w^* - t_{r,\min})/\tau} = \frac{\alpha C_0(1 - RR^*\tau)}{(1 - \alpha C_0)RR^*\tau}$$

$$t_w^* = t_{r,\min} + \tau \log\left(\frac{\alpha C_0}{1 - \alpha C_0}\frac{1 - RR^*\tau}{RR^*\tau}\right)$$

$$t_w^* = t_{r,\min} + \tau \left(\log\frac{\alpha C_0}{1 - \alpha C_0} - \log\frac{RR^*\tau}{1 - RR^*\tau}\right)$$